3.4 LAB

Complete this lab as follows:

1. Log in to the CISCO switch.
    1. Click Start, then select **Google Chrome**.
    2. In the URL field, enter **192.168.0.2** and press **Enter**.
    3. Maximize the window for easier viewing.
    4. In the Username and Password fields, enter **cisco** (case sensitive).
    5. Select **Log In**.
2. Create a new user account.
    1. Under Quick Access on the Getting Started menu, select **Change Device Password**.
    2. Select **Add**.
    3. For the username, enter **ITSwitchAdmin** (case sensitive).
    4. For the password, enter **Admin$only1844** (case sensitive).
    5. For Confirm Password, enter **Admin$only1844**.
    6. For User Level, make sure **Read/Write Management Access (15)** is selected.
    7. Select **Apply**.
    8. Select **Close**.
3. Edit the default user account.
    1. Under the User Account Table heading, select **cisco** (the default user) and then select **Edit**.
    2. For Password, enter **CLI$only1958**.
    3. For Confirm Password, enter **CLI$only1958**.
    4. For User Level, select **Read-Only CLI Access (1)**.
    5. Select **Apply**.
4. Save the changes to the switch's startup configuration file.
    1. From the top of the switch window, select **Save**.
    2. Under *Source File Name*, make sure **Running configuration** is selected.
    3. Under *Destination File Name*, make sure **Startup configuration** is selected.
    4. Select **Apply**.
    5. Select **OK**.
    6. Select **Done**.