

# 12.9 Lab: Enable Wireless Intrusion Prevention

Candidate: COMPTIA COMPTIA ()

Time Spent: 00:11

Score: 0%

## Task Summary

### Required Actions

- 
- |  |                              |
|--|------------------------------|
| ✕ Configure denial-of-service protection | <a href="#">Show Details</a> |
|--|------------------------------|
- 
- |  |                              |
|--|------------------------------|
| ✕ Enable wireless intrusion protection | <a href="#">Show Details</a> |
|--|------------------------------|
- 
- |                                      |  |
|--------------------------------------|--|
| ✕ Enable rogue DHCP server detection |  |
|--------------------------------------|--|
- 

## Explanation

Complete this lab as follows:

1. Configure the wireless controller to protect against denial-of-service (DOS) attacks.
  - a. Click on the Start button, then select **Google Chrome**.
  - b. Enter the address of **192.168.0.6** and press **Enter**.
  - c. Maximize the Google Chrome browser for better viewing.
  - d. From the Ruckus controller, select the **Configure** tab.
  - e. From the left menu, select **WIPS**.
  - f. From the right pane, select:
    - **Protect my wireless network against excessive wireless requests.**
    - **Temporarily block wireless clients with repeated authentication failures.**
  - g. Enter a threshold of **120** seconds.
  - h. On the right, for this area, select **Apply**.
2. Configure intrusion detection and prevention.
  - a. Select **Enable report rogue devices**.
  - b. Select **Report all rogue devices**.
  - c. Select **Protect the network from malicious rogue access points**.
  - d. On the right, for this area, select **Apply**.
3. Select **Enable rogue DHCP server detection** and then select **Apply**.