

10.10 Lab: Disable Switch Ports - GUI

Candidate: COMPTIA COMPTIA ()

Time Spent: 00:13

Score: 0%

Task Summary

Required Actions

-
- ✕ Disable port 9
-
- ✕ Copy GE9 settings to ports 12 and 14-17 [Show Details](#)
-
- ✕ Save configuration settings to the startup configuration file [Show Details](#)
-

Explanation

Complete this lab as follows:

- Log in to the CISCO switch.
 - In the Google Chrome URL field, enter **192.168.0.2** and press **Enter**.
 - Maximize the window for better viewing.
 - In the Username and Password fields, enter **cisco** (case sensitive).
 - Select **Log In**.
- Disable port GE9.
 - From the left navigation bar, expand and select **Port Management > Port Settings**.
 - Select **GE9** (port 9) and then select **Edit**.
 - For *Administrative Status*, select **Down**.
 - Select **Apply**.
 - Select **Close**.
- Copy GE9 port settings to ports 12 and 14-17.
 - Select **GE9** and then select **Copy Settings**.
 - Type **12,14-17** in the *To:* field.
 - Select **Apply**.
- Save the changes to the switch's startup configuration file.
 - From the upper right of the switch window, select **Save**.
 - For *Source File Name*, make sure **Running configuration** is selected.
 - For *Destination File Name*, make sure **Startup configuration** is selected.
 - Select **Apply**.
 - Select **OK**.

f. Select **Done**.