

Mlfuns Sample Script

Parameter Table

June 8, 2011

Tim Bergsma



1 Purpose

This script picks up after model. Rnw to process bootstrap results and make a parameter table.

1.1 Package

```
Listing 1:

> getwd()

[1] "/Users/timb/code/inst/sample/script"

Listing 2:

> require(MIfuns,lib.loc=' ~ /Rlibs')

MIfuns 4.3.4
```

2 Parameter Table

Listing 3:

```
> library(Hmisc)
> tab <- wikitab(1005,'../nonmem')
> tab$estimate <- as.character(signif(as.numeric(tab$estimate),3))
> tab$estimate <- with(tab, paste(estimate,'$',justUnits(model),'$'))
> tab$name <- with(tab, nospace(noUnits(lhs(model))))
> tab$root <- signif(sqrt(exp(text2decimal(tab$estimate))-1),3)*100
> needcv <- contains('OMEGA|SIGMA',tab$parameter)
> tab <- within(tab, estimate[needcv] <- paste(estimate[needcv],parens(glue('\\%CV=',root[needcv]))))
> tab$root <- NULL
> #offdiag <- contains('2.1',tab$parameter)</pre>
```



```
> #tab$estimate[offdiag] <- text2decimal(tab$estimate[offdiag])</pre>
> #omegablock <- text2decimal(tab$estimate[contains('Omega..(1|2)',tab$parameter)])</pre>
> #cor <- signif(half(cov2cor(as.matrix(as.halfmatrix(omegablock)))))[[2]],3)</pre>
> #tab$estimate[offdiag] <- paste(sep='',tab$estimate[offdiag],' (COR=',cor,')')</pre>
> tab$model[is.na(tab$model)] <- ''</pre>
> boot <- read.csv('../nonmem/1005.boot/log.csv',as.is=TRUE)</pre>
> boot <- boot[boot$moment=='estimate',]</pre>
> boot <- data.frame(cast(boot,... ~ moment))</pre>
> boot[] <- lapply(boot,as.character)</pre>
> boot <- boot[contains('THETA|OMEGA|SIGMA',boot$parameter),c('parameter','estimate')]</pre>
> boot$estimate <- as.numeric(boot$estimate)</pre>
> boot <- data.frame(cast(boot,parameter ~ .,value='estimate',fun=function(x)list(lo=as.character(signif(quantile(x,
   probs=0.05),3)),hi=as.character(signif(quantile(x,probs=0.95),3))))
> boot$CI <- with(boot, parens(glue(lo,',',hi)))</pre>
> tab <- stableMerge(tab, boot[, c('parameter', 'CI')])</pre>
> tab <- within(tab, se <- name <- run <- tool <- parameter <- NULL)
> tab$model <- wiki2latex(noUnits(tab$model))</pre>
> tab
                                  description
1
                       apparent oral clearance
2
                 central volume of distribution
3
                      absorption rate constant
4
                   intercompartmental clearance
5
              peripheral volume of distribution
6
                      male effect on clearance
7
                    weight effect on clearance
8
       interindividual variability of clearance
9 interindividual variability of central volume
10
              interindividual variability of Ka
11
                            proportional error
                                                                                                     model
```



```
3
4
5
6
7
8
9
10
11
                                                CI
                   estimate prse
1
               8.58 $ L/h $ 9.51
                                      (7.46, 9.94)
2
                 21.6 $ L $ 9.33
                                      (18.5, 25.7)
3
           0.0684 $ h^-1 $ 8.04 (0.0602, 0.0785)
4
               3.78 $ L/h $ 13.5
                                      (3.01, 4.87)
5
                  107 $ L $ 15.7
                                       (86.2, 149)
6
                 0.999 $ $ 13.7
                                      (0.775, 1.29)
7
                  1.67 $ $ 21.9
                                         (1, 2.35)
8
                                     (0.115, 0.255)
    0.196 $ $ (\\%CV=46.5) 23.1
   0.129 \ \$ \ (\\\CV=37.1) \ 30.4
                                    (0.0641, 0.184)
10 0.107 $ $ (\\%CV=33.6) 25.2
                                   (0.0651, 0.147)
11 0.0671 $ $ (\\%CV=26.3) 11.4 (0.0548,0.0803)
```



Table 1: Parameter Estimates from Population Pharmacokinetic Model Run 1005

description	model	estimate	prse	CI
apparent oral clearance	$\mathrm{CL/F} \sim \theta_1 \cdot \theta_6^{\mathrm{MALE}} \cdot (\mathrm{WT/70})^{\theta_7} \cdot \mathrm{e}^{\eta_1}$	8.58 L/h	9.51	(7.46,9.94)
central volume of distribution	$V_c/F \sim \theta_2 \cdot (WT/70)^1 \cdot e^{\eta_2}$	21.6 L	9.33	(18.5,25.7)
absorption rate constant	$ m K_a \sim heta_3 \cdot e^{\eta_3}$	$0.0684 \ h^-1$	8.04	(0.0602, 0.0785)
intercompartmental clearance	$\mathrm{Q/F}\sim heta_4$	3.78 L/h	13.5	(3.01,4.87)
peripheral volume of distribution	$ m V_p/F \sim heta_5$	107 L	15.7	(86.2,149)
male effect on clearance	$\mathrm{MALE_{CL/F}} \sim heta_6$	0.999	13.7	(0.775, 1.29)
weight effect on clearance	${ m WT_{CL/F}}\sim heta_7$	1.67	21.9	(1,2.35)
interindividual variability of clearance	$\mathrm{IIV}_{\mathrm{CL/F}} \sim \Omega_{1.1}$	0.196 (%CV=46.5)	23.1	(0.115, 0.255)
interindividual variability of central volume	$\mathrm{IIV}_{\mathrm{V_c/F}} \sim \Omega_{2.2}$	0.129 (%CV=37.1)	30.4	(0.0641, 0.184)
interindividual variability of Ka	$\mathrm{IIV}_{\mathrm{K_a}} \sim \Omega_{3.3}$	0.107 (%CV=33.6)	25.2	(0.0651, 0.147)
proportional error	$\mathrm{err}_{\mathrm{prop}} \sim \Sigma_{1.1}$	0.0671 (%CV=26.3)	11.4	(0.0548, 0.0803)