

```
/tmp/CVE-2024-48990/.git/info/exclude
/tmp/CVE-2024-48990/.git/logs
/tmp/CVE-2024-48990/.git/logs/HEAD
/tmp/CVE-2024-48990/.git/logs/refs
/tmp/CVE-2024-48990/.git/logs/refs/heads
/tmp/CVE-2024-48990/.git/logs/refs/heads/main
/tmp/CVE-2024-48990/.git/logs/refs/remotes
/tmp/CVE-2024-48990/.git/logs/refs/remotes/origin
/tmp/CVE-2024-48990/.git/logs/refs/remotes/origin/HEAD
/tmp/CVE-2024-48990/.git/refs
/tmp/CVE-2024-48990/.git/refs/tags
/tmp/CVE-2024-48990/.git/refs/heads
/tmp/CVE-2024-48990/.git/refs/heads/main
/tmp/CVE-2024-48990/.git/refs/remotes
/tmp/CVE-2024-48990/.git/refs/remotes/origin
/tmp/CVE-2024-48990/.git/refs/remotes/origin/HEAD
/tmp/CVE-2024-48990/.git/packed-refs
/tmp/CVE-2024-48990/.git/index
/tmp/CVE-2024-48990/.git/description
/tmp/CVE-2024-48990/exploit.c
/dev/mqueue/linpeas.txt
```

[+] Searching passwords in config PHP files

[+] Finding IPs inside logs

```
4 /var/log/dpkg.log.1:0.22.04.2
6 /var/log/dpkg.log.1:0.22.04.3
6 /var/log/journal/820335f82dd1461f995fd8f34d5a0a52/user-1000@198caa68593e40fe8e33920a2ed6d51e-0000000000002b86-000641a893de49a4.journal:10.10.15.137
2 /var/log/journal/820335f82dd1461f995fd8f34d5a0a52/user-1000@198caa68593e40fe8e33920a2ed6d51e-0000000000002b86-000641a893de49a4.journal:10.10.15.239
1 /var/log/lastlog:10.10.15.239
1 /var/log/wtmp:10.10.14.117
1 /var/log/wtmp:10.10.14.77
1 /var/log/wtmp:10.10.15.137
2 /var/log/wtmp:10.10.15.239
```

[+] Finding passwords inside logs (limited 100)

[+] Finding emails inside logs (limited 100)

[+] Finding 'pwd' or 'passw' string inside /home, /var/www, /etc, /root and list possible web(/var/www) and config(/etc) passwords

```
/etc/apache2/sites-available/default-ssl.conf: # file needs this password: `xxj31ZMTZzkVA'.
/etc/apache2/sites-available/default-ssl.conf: # Note that no password is obtained from the user. Every entry in the user
/etc/apparmor.d/abstractions/authentication: # databases containing passwords, PAM configuration files, PAM libraries
```