

```
show databases;  
show tables;  
delimiter $$
```

```
delimiter ;
```

```
create database vita;  
use vita;
```

```
use testdb;  
desc dept;
```

```
select * from dept;
```

```
use vita;
```

```
create table dept  
(deptid int,  
deptname varchar(100));
```

```
select * from dept;
```

```
insert into dept(deptid,deptname)  
values(1,'HR');
```

```
insert into dept  
values(2,'IT');
```

```
insert into dept  
values(3,'Finance'),  
(4,'OPR');
```

```
select current_date();
```

```
select curdate();
```

```
select current_time();
```

```
select curtime();
```

```
select now();
```

```
select * from dept;
```

```
select deptname,deptid from dept;
```

```
select * from dept where deptid=1;
```

```
select * from dept where deptid!=1;
```

```
select * from dept where deptid<>1;
```

```
select * from dept where deptid>1;
```

```
select * from dept where deptid>=1;
```

```
select * from dept where deptid<2;
```

```
select * from dept where deptid<=2;
```

```
select * from dept where deptname<'HR';
```

```
select * from dept where deptname<='HR';
```

```
select * from dept where deptname>='HR';
```

```
select * from dept where deptid between 1 and 3;
```

```
select * from dept where deptid not between 1 and 3;
```

```
insert into dept values(5,null);
```

```
insert into dept(deptid) values(6);
```

```
-- null means value not yet defined
```

```
select * from dept where deptname is null;
```

```
select * from dept where deptname is not null;
```

```
select * from dept where deptname like 'H%';
```

```
select * from dept where deptname like 'H_';
```

```
select * from dept where deptname like '%R';
```

```
select * from dept where deptname like '_R';
```

```
select * from dept where deptname like '__R';
```

```
select * from dept where deptname not like '__R';
```

```
update dept  
set deptname='Supply Chain'  
where deptid=5;
```

```
update dept  
set deptname='Supply Chain' ,deptid=5  
where deptid=5;
```

```
update dept  
set deptname='Supply Chain' ,deptid=5  
where deptid=5 and deptname='Supply Chain';
```

```
delete from dept where deptname='Supply Chain';
```

```
alter table dept add c1 int;
```

```
alter table dept drop column c1;
```

```
alter table dept add c1 int;
```

```
update dept set c1=deptid+1;  
alter table dept modify column c1 varchar(100);  
alter table dept modify column c1 varchar(100) not null;
```

```
insert into dept values(7,'New',null); -- fails
```

```
insert into dept(deptid,deptname) values(8,'D'); -- fails
alter table dept modify column c1 varchar(100) not null default 'Something';
insert into dept(deptid,deptname) values(8,'D'); -- works
alter table dept rename to department;
alter table department rename to dep;
alter table dep rename to dept;
```

```
alter table dept rename column c1 to col1;
```

```
create table t_dt(id int, dt date);
```

```
insert into t_dt values(1,'2022-12-30');
```

```
-- unique key
```

```
create table t_uk(id int unique , name varchar(100));
insert into t_uk values(1,'a'); -- works
```

```
insert into t_uk values(1,'b'); -- fails
```

```
insert into t_uk values(null,'b'); -- works
insert into t_uk values(null,'b'); -- works
```

```
-- composite unique key
create table t_uk_comp
(c1 int, c2 int, c3 varchar(100), unique(c1,c2));
```

```
insert into t_uk_comp values(1,1,'a'); -- works
```

```
insert into t_uk_comp values(1,2,'b'); -- works
```

```
insert into t_uk_comp values(2,2,'c'); -- works
```

```
insert into t_uk_comp values(2,2,'d'); -- fails
```

```
insert into t_uk_comp values(2,null,'d'); -- works
```

```
insert into t_uk_comp values(2,null,'e'); -- works
```

```
-- multi unique keys
```

```
create table t_uk_multi(c1 int unique, c2 int unique , c3 varchar(100));
```

```
insert into t_uk_multi values(1,1,'a'); -- works
```

```
insert into t_uk_multi values(1,1,'b'); -- fails
```

```
insert into t_uk_multi values(1,2,'b'); -- fails
```

```
select table_name,column_name,COLUMN_KEY from information_schema.columns  
where table_name='t_uk_comp' and table_schema='vita';
```

```
select * from information_schema.KEY_COLUMN_USAGE  
where table_name='t_uk_comp' and table_schema='vita';
```

```
show create table t_uk_comp;
```

```
create table t_no_unq(c1 int, c2 int, c3 varchar(100));
```

```
insert into t_no_unq values(1,1,'a');
```

```
insert into t_no_unq values(1,1,'a');
```

```
alter table t_no_unq add unique(c1); -- fails
```

```
delete from t_no_unq limit 1;
```

```
alter table t_no_unq add unique(c1,c2);
```

-- primary key

```
create table t_pk (id int primary key, name varchar(100));
```

```
insert into t_pk values(1,'a'); -- works
```

```
insert into t_pk values(1,'b'); -- fails
```

```
insert into t_pk values(null,'b'); -- fails
```

```
insert into t_pk values(2,null); -- works
```

--Comp primary key

```
create table t_comp_pk (c1 int, c2 int, name varchar(100), primary key(c1,c2));
```

--Multiple primary key

```
create table t_pk_multi (c1 int primary key, c2 int primary key, name varchar(100));
```

```
-- ERROR 1068 (42000): Multiple primary key defined
```

-- null constraint

```
create table t_nn(id int, name varchar(100) not null);
```

```
insert into t_nn values(1,null); -- fails
```

```
insert into t_nn(id) values(1); -- fails
```

-- check constraint

```
create table t_check (eid int, ename varchar(100), salary int check(salary>0));
```

```
insert into t_check values(1,'a',0); -- fails
```

```
insert into t_check values(1,'a',1000); -- works
```

```
insert into t_check values(1,'a',null); -- works
```

```
create table t_check2 (eid int, ename varchar(100), gender varchar(10) check(gender in ('Male','Female')));
```

```
insert into t_check2 values(1,'a',null); -- works
insert into t_check2 values(1,'a','male'); -- works
insert into t_check2 values(1,'a','male2'); -- fails
```

```
create table t_check_comp
(eid int, ename varchar(100), salary int, gender varchar(100),
check((salary<=100000 and gender='Male') or (salary<=200000 and gender='Female')));
```

```
insert into t_check_comp values(1,'a',200000,'Male'); -- fails
insert into t_check_comp values(1,'a',200000,'Female'); -- works
```

```
-- foreign key
```

```
create table t_parent(deptid int primary key , deptname varchar(100));
```

```
create table t_child(eid int, ename varchar(100),
deptid int,
foreign key fk1(deptid) references t_parent(deptid));
```

```
insert into t_child values(1,'a',1); -- fails
insert into t_child values(1,'a',null); -- works
insert into t_parent values(1,'HR');
insert into t_child values(1,'a',1); -- works
delete from t_parent where deptid=1; -- fails
delete from t_parent ; -- fails
```

-- comp FK

```
create table t_parent_comp  
(c1 int , c2 int, c3 varchar(100), unique (c1,c2));
```

```
create table t_child_comp  
(c1 int,c2 int, c4 varchar(100),  
foreign key fk2(c1,c2) references t_parent_comp(c1,c2));
```

```
insert into t_child_comp values(1,1,'a'); -- fails
```

```
insert into t_child_comp values(1,null,'a'); -- works
```

```
insert into t_child_comp values(null,1,'a'); -- works
```

```
insert into t_child_comp values(null,null,'a'); -- works
```

-- default

```
create table t_def (id int , salary int default 10);
```

```
insert into t_def(id) values(1);
```

```
insert into t_def(id,salary) values(1,null);
```

```
create table t_name_def(id int, name varchar(100) default 'NA');
```

```
insert into t_name_def(id) values(1);
```

```
select * from t_name_def;
```

```
grant select on dept to u1@localhost;
```

```
revoke select on dept from u1@localhost;
```

```
show variables like '%commit%';
```



```
start transaction;  
update dept set col1=300 where deptid=1;  
rollback;
```

-- Joins

```
create table t1 (c1 int, c2 varchar(10));  
create table t2 (c1 int, c3 varchar(10));
```

```
insert into t1 values(1,'a'),(2,'b'),(3,'c');  
insert into t2 values(3,'x'),(4,'y'),(5,'z');
```

-- cross join
-- old syntax

```
select * from t1, t2;
```

-- new/Ansi Syntax

```
select * from t1 cross join t2;
```

```
select c1,c2,c3 from t1 cross join t2; -- fails
```

```
select t1.c1,c2,c3 from t1 cross join t2; -- works
```

-- inner join

-- old syntax

```
select * from t1, t2 where t1.c1=t2.c1;
```

-- new/Ansi Syntax

```
select * from t1 inner join t2 on t1.c1=t2.c1;
```

```
select * from t1 join t2 on t1.c1=t2.c1;
```

```
select c1,c2,c3 from t1 join t2 on t1.c1=t2.c1; -- fails
```

```
select t1.c1,c2,c3 from t1 join t2 on t1.c1=t2.c1; -- works
```

left join

-- new/Ansi Syntax

```
select * from t1 left outer join t2 on t1.c1=t2.c1;
```

```
select * from t1 left join t2 on t1.c1=t2.c1;
```

```
select c1,c2,c3 from t1 left join t2 on t1.c1=t2.c1; -- fails
```

```
select t1.c1,c2,c3 from t1 left join t2 on t1.c1=t2.c1; -- works
```

Right join

-- new/Ansi Syntax

```
select * from t1 Right outer join t2 on t1.c1=t2.c1;
```

```
select * from t1 Right join t2 on t1.c1=t2.c1;
```

```
select c1,c2,c3 from t1 Right join t2 on t1.c1=t2.c1; -- fails
```

```
select t1.c1,c2,c3 from t1 Right join t2 on t1.c1=t2.c1; -- works
```

```
select ename,deptname  
from t_parent, t_child  
where t_parent.deptid=t_child.deptid;
```

```
select ename,deptname  
from t_parent right join t_child  
on t_parent.deptid=t_child.deptid;
```

```
create table a (c1 int);  
create table b (c1 int);
```

```
insert into a values(1),(2),(3);  
insert into b values(3),(4),(5);
```

```
select * from a  
union  
select * from b;
```

```
select * from b  
union  
select * from a;
```

```
select * from a  
union all  
select * from b;
```

```
select * from b  
union all  
select * from a;
```

```
-- full join workaround in mysql  
select * from t1 left outer join t2 on t1.c1=t2.c1  
union  
select * from t1 Right outer join t2 on t1.c1=t2.c1;
```

```
select count(*) from t_parent;  
select count(*) from t_child;  
select count(1) from t_child;
```

```
select count(deptid) from t_child;
```

```
select sum(eid) from t_child;
```

```
select max(eid) from t_child;  
select min(ename) from t_child;
```

```
select avg(eid) from t_child;
```

```
drop table dept;
```

```
create table dept (deptid int , deptname varchar(100));  
insert into dept values ( 1, 'HR'),  
( 2, 'IT'),  
( 3, 'Finance'),  
( 4, 'OPR');
```

```
create table emp(eid int, ename varchar(100), salary int, deptid int);
```

```
select version();
```

```
insert into emp  
with recursive tab  
as  
(select 1 eid , cast(concat('a',1) as char(100)) ename,rand()*100000 salary,mod(0,3)+1 deptid  
union all  
select  eid+1 , concat('a',eid+1) ename,rand()*100000 salary,mod(eid,3)+1 deptid  
from tab where eid<100)  
select * from tab;
```

```
select deptname, sum(salary) dep_total_salary from emp join dept on emp.deptid=dept.deptid  
group by deptname;
```

```
select deptname, sum(salary) as dep_total_salary from emp join dept on  
emp.deptid=dept.deptid  
group by deptname;
```

```
select deptname, sum(salary) as dep_total_salary from emp right join dept on  
emp.deptid=dept.deptid  
group by deptname;
```

```
select deptname, sum(salary) as dep_total_salary from emp e right join dept d on  
e.deptid=d.deptid  
group by deptname;
```

-- intersect workaround

```
select * from a where c1 in (select * from b);
```

-- Minus workaround

```
select * from a where c1 not in (select * from b);
```

```
select * from b where c1 not in (select * from a);
```

```
select deptname, sum(salary) as dep_total_salary from emp e right join dept d on  
e.deptid=d.deptid  
group by deptname  
having sum(salary)>1800000;
```