kuskus - granular processor (Beads)

I/O jacks (fixed)

Audio	
In L/R	codec 48k
Out A / Out B	mono + trims
Stereo out	TRS

CV in (7)	
Size/Pos A/B	size / time
Mix A/B	shape / density
V/Oct A/B	A: pitch; B: -
Crossfade CV	dry/wet

Clock / Gate	
Clock in (TRS 4PPQN)	sync
Gate in A/B	A: seed; B: freeze toggle
Gate out A/B	A: grain gates (gate-out route)

Mod CV / MIDI	
Mod CV out A/B	-
MIDI in/out	24 PPQN + notes

Front panel

Deck A and B (identical)

Knobs (7)	
Pitch	A: pitch (+/-24 st, detents); B: pitch attenuverter
Position	A: time; B: time attenuverter
Size	A: size (top = delay mode); B: size attenuverter
Envelope	A: shape; B: shape attenuverter
Mix (SOS)	A: dry/wet; B: output level
Cycle	A: density; B: input gain
Glow	A: feedback; B: reverb

Pads (5)	
Play	A: seed tap (Alt = latch); B: freeze
Reverse	A: clock-follow; B: -
Grit	-
Flux	A: hold = seed held; B: -
Seq	-

Ring A / B
A: output level (media colour) + time dot; B: input level, cyan when frozen

Shared / Transport

Crossfade	
Crossfade	dry/wet

Switches (74HC165)	
Mode (L/C/R)	A: digital / clean tape / dirty tape; B: Drift = vintage digital
Routing (L/C/R)	stereo / mono / gate out
CV target (U/C/D)	-
Out trims A/B	output trims

Transport	
Tap	tempo (clock-follow)
Alt	modifier (held)
Spot	-

Clock
[src color]