Lab Report: 07

Title: Implementation of FCFS Scheduling Algorithm

Course code: ICT-3110

Course title: Operating Systems Lab

Date of

Performance:

Date of

Submission:

SUBMITTED BY

Name: Shakhera khanom

ID: IT-18033

3rd year 1st semester

Session: 2017-18

Department of ICT,

MBSTU.

SUBMITTED TO

Nazrul Islam

Assistant Professor

Department of ICT,

MBSTU.

Experiment No :07

Experiment Name: Implementation of FCFS Scheduling Algorithm.
Objectives:
- ➢ What is FCFS Scheduling Algorithm?
- ➢ How to implementation in C?

❖ **FCFS Scheduling Algorithm :**

The First Come First Served (FCFS) Scheduling Algorithm is the simplest one. In this algorithm the set of ready processes is managed as FIFO (first-in-first-out) Queue. The processes are serviced by the CPU until completion in order of their entering in the FIFO queue.

A process once allocated the CPU keeps it until releasing the CPU either by terminating or requesting I/O. For example, interrupted process is allowed to run after interrupt handling is done with.

FIRST COME FIRST SERVE SCHEDULING (FCFS)

Description:
To calculate the average waiting time using the FCFS algorithm first the waiting time of the first process is kept zero and the waiting time of the second process is the burst time of the first process and the waiting time of the third process is the sum of the burst times of the first and the second process and so on. After calculating all the waiting times the average waiting time is calculated as the average of all the waiting times. FCFS mainly says first come first serve the algorithm which came first will be served first.

Algorithm:

Step 1: Start the process

Step 2: Accept the number of processes in the ready Queue

Step 3: For each process in the ready Q, assign the process name and the burst time.

Step 4: Set the waiting of the first process as _0'and its burst time as its turnaround time.

Step 5: for each process in the Ready Q calculate

   a) Waiting time (n) = waiting time (n-1) + Burst time (n-1)

   b) Turnaround time (n)= waiting time(n)+Burst time(n)

Step 6: Calculate

   a) Average waiting time = Total waiting Time / Number of process

   b) Average Turnaround time = Total Turnaround Time / Number of process

Step 7: Stop the process

Program: To write the c program to implement scheduling algorithm for first come first serve scheduling (FCFS).

```c
#include<stdio.h>
#include<conio.h>
void main()
{
   int  n,i,j,bt[30],wt[30],tat[30];
   float awt=0,atat=0;
   printf("\nEnter the num of process: ");
   scanf("%d",&n);
```

```c
for(i=0;i<n;i++)
{
   printf("\nEnter the burst time p%d: ",i);
   scanf("%d",&bt[i]);
}

printf("\nprocess \t burst time \t waiting time \t turnaround time\n");
for(i=0;i<n;i++)
{
   wt[i]=0;
   tat[i]=0;
   for(j=0;j<i;j++)
   {
      wt[i]=wt[i]+bt[j];
   }
   tat[i]=wt[i]+bt[i];

   awt=awt+wt[i];
   atat= atat+tat[i];
   printf("\tp%d\t\t%d\t\t%d\t\t%d\n",i,bt[i],wt[i],tat[i]);
}
awt=awt/n;
atat=atat/n;
printf("\nAverage waiting time %.2f\n",awt);
printf("Average turnaround time %.2f\n",atat);

}
```

Output:

```
E:\programming\OS_Lab\FCFS.exe

Enter the num of process: 4

Enter the burst time p0: 7

Enter the burst time p1: 5

Enter the burst time p2: 2

Enter the burst time p3: 9

process          burst time      waiting time     turnaround time
        p0            7              0                  7
        p1            5              7                  12
        p2            2              12                 14
        p3            9              14                 23

Average waiting time 8.25
Average turnaround time 14.00

Process returned 30 (0x1E)   execution time : 6.594 s
Press any key to continue.
```

Result: Thus the FCFS process scheduling program was executed and verified successfully.

Discussion: This lab help to learn about FCFS scheduling algorithm. we have implemented this algorithm using c language. Using this algorithm we can find waiting and turnaround time.