

```
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int e0/1
Router(config-if)#ip add 60.0.0.1 255.0.0.0
Router(config-if)#no shut
Router(config-if)#exit
Router(config)#
*Aug 21 13:05:32.726: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
Router(config)#exit
Router#
*Aug 21 13:05:35.819: %SYS-5-CONFIG_I: Configured from console by console
Router#show ip int brief
```

Interface	IP-Address	OK?	Method	Status	Protocol
Ethernet0/0	50.0.0.1	YES	manual	up	up
Ethernet0/1	60.0.0.1	YES	manual	up	up
Ethernet0/2	unassigned	YES	TFTP	down	down
Ethernet0/3	unassigned	YES	TFTP	down	down

```
Router#
```


C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix	:	
IP Address	:	50.0.0.10
Subnet Mask	:	255.0.0.0
Default Gateway	:	

C:\Documents and Settings\user>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Reply from 50.0.0.1:	bytes=32	time=1ms	TTL=255
Reply from 50.0.0.1:	bytes=32	time<1ms	TTL=255
Reply from 50.0.0.1:	bytes=32	time=1ms	TTL=255
Reply from 50.0.0.1:	bytes=32	time=1ms	TTL=255

Ping statistics for 50.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Documents and Settings\user>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Reply from 50.0.0.1:	bytes=32	time=1ms	TTL=255
Reply from 50.0.0.1:	bytes=32	time=1ms	TTL=255
Reply from 50.0.0.1:	bytes=32	time=1ms	TTL=255
Reply from 50.0.0.1:	bytes=32	time<1ms	TTL=255

Ping statistics for 50.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Documents and Settings\user>route add 60.0.0.0 mask 255.0.0.0 50.0.0.1

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Reply from 60.0.0.10:	bytes=32	time=2ms	TTL=127
Reply from 60.0.0.10:	bytes=32	time<1ms	TTL=127
Reply from 60.0.0.10:	bytes=32	time=1ms	TTL=127
Reply from 60.0.0.10:	bytes=32	time=1ms	TTL=127

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>

C:\WINDOWS\system32\cmd.exe

Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>route print

Interface List

0x1 MS TCP Loopback interface
0x2 ...50 86 5f 09 50 00 Intel(R) PRO/1000 MT Network Connection - Packet
Scheduler Miniport

Active Routes:

Network	Destination	Netmask	Gateway	Interface	Metric
60.0.0.0		255.0.0.0	60.0.0.10	60.0.0.10	10
60.0.0.10		255.255.255.255	127.0.0.1	127.0.0.1	10
60.255.255.255		255.255.255.255	60.0.0.10	60.0.0.10	10
127.0.0.0		255.0.0.0	127.0.0.1	127.0.0.1	1
224.0.0.0		240.0.0.0	60.0.0.10	60.0.0.10	10
255.255.255.255		255.255.255.255	60.0.0.10	60.0.0.10	1

Persistent Routes:

None

C:\Documents and Settings\user>route add 50.0.0.0 mask 255.0.0.0 60.0.0.1

C:\Documents and Settings\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=2ms TTL=127

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>