

04 — API Documentation

Complete documentation suite (Markdown → PDF with Mermaid diagrams)

Generated: 2026-09-22

Source: repository `docs/` directory

Diagrams rendered with Mermaid 11

Table of Contents

- 04-api/01-api-overview.md
- 04-api/02-authentication.md
- 04-api/03-api-conventions.md
- 04-api/04-error-handling.md
- 04-api/05-endpoints.md

API Overview

Style

REST over HTTP/JSON. Multipart for file uploads. SSE for notification streams.

Public entrypoints (defaults)

Service	Base URL (local)	Notes
opms-backend	<code>http://localhost:7001</code>	BFF + order domain; Swagger <code>/api-docs</code>
auth-service	<code>http://localhost:7003</code>	Identity
product-service	<code>http://localhost:7005</code>	Catalog
party-service	<code>http://localhost:7006</code>	Parties/zones/rates
work-planner-backend	<code>http://localhost:7007</code>	<code>/api/work-planner</code>
lead-manager-backend	<code>http://localhost:7009</code>	Leads/quotations
message-service	<code>http://localhost:7011</code>	Messaging
notification-service	<code>http://localhost:7012</code>	Notifications/push

Production hostnames: see nginx `*.spspl.com` / `*.medicaent.in`.

OpenAPI

- **Live:** `opms-backend` `GET /api-docs` generated from `opms-backend/src/docs/swagger.js` + `swaggerExtended.js` (OpenAPI 3.1)
- **Docs copy:** `openapi.yaml` — inventory of verified routes across services (may be less detailed than Swagger UI for `opms-backend` schemas)

Health

All backends: `GET /health`

Related

- [Authentication](#)
- [Endpoints](#)

API Authentication

Method

Bearer JWT in `Authorization: Bearer <token>` header.

Obtain token

```
POST /api/auth/login
Content-Type: application/json

{ "email": "user@example.com", "password": "*****" }
```

Hit auth-service (:7003) or via opms-backend proxy (:7001/api/auth/login).

Session introspection

```
GET /api/auth/me
Authorization: Bearer <token>
```

Authorization

Gate	Applies to
<code>requireAuth</code>	Most domain routes
<code>requireOpmsAccess</code>	OPMS domain on opms-backend
<code>requireLeadManagerAccess</code>	Lead Manager mutating/list routes
<code>requireWorkPlannerAccess</code>	Work Planner routes
Webhook secrets	Google Sheet / WhatsApp verify

Portal requirement (OPMS)

User must include `portals[]` entry `{ portal_code: "opms", access_roles: [...] }`.

Related

- [Architecture Auth](#)

API Conventions

Verified patterns

Pattern	Description
Resource nouns	/api/orders , /api/parties , ...
Soft-delete	DELETE /:id sets deletedAt ; GET /deleted ; POST /:id/restore
Patch updates	Prefer PATCH /:id for partial updates
Nested actions	POST /:id/submit , /approve , /transition
Multipart	Attachments/dispatch bill/due sheet documents via multer field names
Proxies	Same path on BFF as owning service

IDs

MongoDB ObjectId strings in path params.

Pagination / filters

Many list endpoints accept query filters — **exact query schema varies by controller**. Prefer Swagger UI / controller source for each list. Not fully standardized across services.

Idempotency

Not identified as a global idempotency-key convention.

Versioning

No /v1 prefix — **Not identified**.

API Error Handling

Typical HTTP statuses (observed pattern)

Status	Meaning
200/201	Success
400	Validation / bad request
401	Missing/invalid JWT
403	Authenticated but portal/role forbidden
404	Not found
409	Conflict (e.g. unique constraints) — where implemented
500	Server error

Exact error JSON shape varies by service/middleware — **not a single shared error schema across all services**. Inspect controllers for `{ message }` / `{ error }` patterns.

Workflow transition errors

Invalid next status or blocked by flags returns error from workflow layer (message indicates rule failure).

Source

Express middlewares and module controllers under each service `src/` .

API Endpoints Inventory

Rule: Only endpoints verified from `*.routes.js` / `app.js` mounts. Request/response bodies: see Swagger (`/api-docs`) for opms-backend where defined; otherwise **Requires confirmation** from controller source.

Authentication column: Public / Bearer / Bearer+Portal / Secret / Internal.

auth-service (:7003)

Method	Endpoint	Auth	Purpose	Source
POST	<code>/api/auth/login</code>	Public	Login	<code>auth.routes.js</code>
GET	<code>/api/auth/me</code>	Bearer	Current user	
POST	<code>/api/auth/change-password</code>	Bearer	Change password	
GET/POST	<code>/api/users</code>	Bearer	List/create users	<code>user.routes.js</code>
GET/PATCH/DELETE	<code>/api/users/:id</code>	Bearer	User CRUD	
GET/POST	<code>/api/users/roles</code>	Bearer	Roles	
POST	<code>/api/users/roles/seed</code>	Bearer	Seed roles	
PUT/DELETE	<code>/api/users/roles/:id</code>	Bearer	Update/delete role	
GET	<code>/api/company-info</code>	Public	Company info	<code>companyInfo.routes.js</code>
GET	<code>/api/company-info/data</code>	Bearer	Data	
PUT/PATCH	<code>/api/company-info</code>	Bearer	Update	
*	<code>/api/portals</code>	Bearer	Portal CRUD + seed	<code>portal.routes.js</code>
*	<code>/api/departments</code>	Bearer	Department CRUD + seed	<code>department.routes.js</code>
GET	<code>/health</code>	Public	Health	

opms-backend domain (:7001) — local routers

Orders `/api/orders` — Bearer + OPMS portal (except webhook)

Method	Path	Notes
POST	<code>/google-sheet-webhook</code>	Public + webhook secret
GET	<code>/</code>	List
GET	<code>/stats</code>	Workflow stats

Method	Path	Notes
GET	/workflow-context	Context
POST	/	Create
GET	/deleted	Trash
GET	/:id	Get
GET	/:id/history	History
GET	/:id/fulfillment	Fulfillment
GET	/:id/approvals	Approvals
GET	/:id/assignees	Assignees
PATCH	/:id	Update
PATCH	/:id/super-sheet	Super sheet patch
DELETE	/:id	Soft-delete
POST	/:id/restore	Restore
POST	/:id/submit	Submit
POST	/:id/transition	Transition status
POST	/:id/close-after-full-delivery	Close helper

Source: `opms-backend/src/modules/orders/order.routes.js`

Order approvals `/api/order-approvals`

Method	Path
GET	/, /deleted, /:id
POST	/, /:id/approve, /:id/reject, /:id/send-to-finance, /:id/send-to-account, /:id/finance-amend, /:id/amend, /:id/resolve-dispatch, /:id/restore
PATCH	/:id, /:id/super-sheet
DELETE	/:id

Finance `/api/finance`

GET /queue, GET /summary

Approvals `/api/approvals`

GET /

Dispatch `/api/dispatch`

List/get/create(with `bill_document`)/patch/soft-delete/restore/deleted

Transport `/api/transport`

Soft-delete CRUD pattern

Order deliveries `/api/order-deliveries`

List/get/patch/soft-delete/restore + `POST /log-shipment`

Order returns `/api/order-returns`

List/get/create/patch/soft-delete/restore

Due sheets `/api/order-due-sheets`

CRUD + document upload + current-by-order + restore

Unbilled `/api/unbilled-orders`

CRUD soft-delete + `GET /order/:orderId`

Final statements `/api/final-order-statements`

`GET /` , `GET /order/:orderId`

Flags `/api/flags`

`GET /` , `GET /:id` , `POST /` , `PATCH /:id`

Dashboard `/api/dashboard`

`GET /admin|/sales|/finance|/dispatch|/account|/super`

Activity `/api/activity`

`GET /`

Attachments `/api/attachments`

List/get/create(multipart)/delete/restore/deleted

Files `/api`

`GET /files/:fileId/view` , `GET /files/:fileId/download`

Fleet

`/api/vehicles` , `/api/drivers` , `/api/transport-agents` — soft-delete CRUD

Reminders `/api/reminders`

Webhook + CRUD + `POST /:id/follow-ups`

Transport planner `/api/transport-plans`

list/stats/eligible-orders/CRUD/submit/complete/cancel/add-remove orders/LR/packed/dispatched/delivered actions

Terms `/api/terms-and-conditions`

No requireAuth on router — GET/POST/PUT/DELETE including text subresources

Proxied (same paths as owning services)

auth, products, parties, notifications, messages/emails/...

product-service (:7005)

Mounts: `/api/products` , `/api/product-groups` , `/api/product-subgroups` , `/api/product-brands` , `/api/product-manufacturers` , `/api/product-kit-items`

Pattern: auth + list/get/create/patch/soft-delete/bulk; products webhook; kit by-kit routes; meta-options on products.

party-service (:7006)

Mount	Highlights
<code>/api/parties</code>	webhook; CRUD; bulk; restore
<code>/api/zones</code>	CRUD; parties; sales-persons
<code>/api/party-products</code>	CRUD; rates approve
<code>/api/party-order-products-rate</code>	check/map helpers

notification-service (:7012)

Method	Path	Auth
POST	<code>/api/notifications/internal/order-transition</code>	Internal (no requireAuth)
POST	<code>/api/notifications/internal/create</code>	Internal
GET	<code>/api/notifications</code>	Bearer
GET	<code>/api/notifications/stream</code>	Bearer SSE
PATCH	<code>/api/notifications/:id/read</code>	Bearer
GET	<code>/api/push/vapid-public-key</code>	Public
POST/DELETE	<code>/api/subscribe</code>	Bearer
POST	<code>/api/push/notify</code>	Bearer

message-service (:7011)

Mount	Endpoints
/api/messages	GET/POST webhook (public); GET/POST send; GET :id (auth)
/api/emails	POST/, GET/, GET/:id
/api/auto-emails	POST /trigger
/api/communication	GET /types; POST /send; /order-received; /queue/:type

lead-manager-backend (:7009)

Mount	Notes
/api/leads	Full CRM actions; list may allow work_planner
/api/lead-masters	sources & lost reasons
/api/quotations	admin/manager gates
/api/terms-and-conditions	lead_manager access
/api/attachments	No requireAuth on router
Proxies	notifications, emails, messages, ...

work-planner-backend (:7007)

Base: /api/work-planner

Area	Notes
GET /attachments/:attachmentId/view	Before auth (public view redirect)
plans/visits/works/expenses	CRUD + lifecycle actions
user-settings	Per-user settings
uploads/stats	Supporting

Auth: Bearer + requireWorkPlannerAccess

Example: login

Request

```
POST /api/auth/login HTTP/1.1
Host: localhost:7003
Content-Type: application/json

{
  "email": "admin@example.com",
  "password": "*****"
}
```

Response (shape Inferred — confirm against controller)

```
{
  "token": "<jwt>",
  "user": {
    "email": "admin@example.com",
    "portals": [{ "portal_code": "opms", "access_roles": ["admin"] }]
  }
}
```

Example: transition order

```
POST /api/orders/{id}/transition HTTP/1.1
Host: localhost:7001
Authorization: Bearer <token>
Content-Type: application/json

{
  "to_status": "finance_review",
  "remarks": "optional"
}
```

Exact body field names: confirm in `order.controller` / service — do not assume.

Related

- [OpenAPI YAML](#)
- Live Swagger: `/api-docs` on opms-backend