

Project Name: Create Onchange Client Script

Milestone: 3

Solution

To solve the problem, a **Client Script** is created in ServiceNow to automatically set the **Urgency** of an Incident when its **Impact** is changed to **High**.

First, navigate to **System UI → Client Scripts** and click **New**. Create the Client Script with the following details:

- **Name:** Auto set urgency for high impact
- **Table:** Incident
- **Type:** onChange
- **Field name:** Impact
- **Active:** True

Enter the following script in the Script section:

```
function onChange(control, oldValue, newValue,
isLoading) {
    if (isLoading || newValue == '') {
        return;
    }

    if (newValue == '1') {
        g_form.setValue('urgency', '1');
        g_form.addInfoMessage(
            'Urgency set to High for High impact
incident.'
        );
    }
}
```

The script checks the value of the **Impact** field whenever it is changed. If the Impact is set to **High**, the **Urgency** field is

automatically changed to **High**. An information message is also displayed to confirm the update.

After entering the details and script, click **Submit** to save the Client Script.

Result

When the **Impact** of an Incident is changed to **High**, the system automatically sets the **Urgency** to **High**, reducing manual effort and maintaining consistent incident information.

The screenshot shows the ServiceNow interface for configuring a new Catalog Client Script. The browser address bar shows the URL: `dev435320.service-now.com/now/nav/ui/classic/params/target/catalog_script_client.do%3Fsys_id%3D-1%26sys_is_list%3Dtrue%26sys_target%3Dcatalog_script_client%26sysparm_checked_items%...`. The page title is "Catalog Client Scripts - New Record".

A blue informational banner at the top states: "New client-scripts are run in strict mode, with direct DOM access disabled. Access to jQuery, prototype and the window object are likewise disabled. To disable this on a per-script basis, configure this form and add the 'Isolate script' field. To disable this feature for all new globally-scoped client-side scripts set the system property 'glide.script.block.client.globals' to false."

The form contains the following fields and options:

- Name:** Auto set urgency for high impact
- Applies to:** A Catalog Item
- Active:** ☒
- UI Type:** Desktop
- Application:** Global
- Type:** onChange
- Catalog Item:** (empty search field)
- Variable name:** (empty dropdown)
- Applies on a Catalog Item view:** ☒
- Applies on Requested Items:** ☐
- Applies on Catalog Tasks:** ☐
- Applies on Target Record:** ☐

The **Script** editor shows the following code:

```
1 function onChange(control, oldValue, newValue, isLoading) {
2
3 }
4
5
6 //Type appropriate comment here, and begin script below
7 function onChange(control, oldValue, newValue, isLoading) {
8   if (isLoading || newValue == '') {
9     return;
10  }
11
12   if (newValue == '1') {
13     g_form.setValue('urgency', '1');
14     g_form.addInfoMessage('Urgency set to High for High impact incident.');
```