

Ex. No.: 10

Database with VIEW and INDEX

Create a view with name 'v1' using employees1 table which holds the value of employee_id and salary of employee.

```
mysql> CREATE VIEW v1 AS
      -> SELECT employee_id, salary
      -> FROM employees1;
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> SELECT * FROM v1;
+-----+-----+
| employee_id | salary |
+-----+-----+
|          1 | 120000.00 |
|          2 | 150000.00 |
|          3 | 170000.00 |
|          4 | 140000.00 |
|         10 | 180000.00 |
+-----+-----+
5 rows in set (0.01 sec)
```

Do the insert and delete records from v1 table.

```
mysql> INSERT INTO v1
      -> VALUES (11,160000);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> SELECT * FROM v1;
+-----+-----+
| employee_id | salary |
+-----+-----+
|          1 | 120000.00 |
|          2 | 150000.00 |
|          3 | 170000.00 |
|          4 | 140000.00 |
|         10 | 180000.00 |
|         11 | 160000.00 |
+-----+-----+
6 rows in set (0.00 sec)
```

```
mysql> DELETE FROM v1
      -> WHERE employee_id = 11;
Query OK, 1 row affected (0.01 sec)
```

```
mysql> SELECT * FROM v1;
+-----+-----+
| employee_id | salary |
+-----+-----+
|          1 | 120000.00 |
|          2 | 150000.00 |
|          3 | 170000.00 |
|          4 | 140000.00 |
|         10 | 180000.00 |
+-----+-----+
5 rows in set (0.00 sec)
```

Create index1 for 'salary' attribute from employees1 relation and list the first name of the employees whose salary is above 145000 and explain the working principle of indexing and then drop the index1.

```
mysql> CREATE INDEX index1
      -> ON employees1(salary);
Query OK, 0 rows affected (0.12 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> SELECT first_name
      -> FROM employees1
      -> WHERE salary > 145000;
+-----+
| first_name |
+-----+
| Priya      |
| Kiran      |
| Rahul      |
+-----+
3 rows in set (0.01 sec)
```

Create index1 for 'employee_id' attribute and display the first name of an employee whose employee id is 10 and explain the working principle of index1.

```
mysql> DROP INDEX index1
      -> ON employees1;
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> CREATE INDEX index1
      -> ON employees1(employee_id);
Query OK, 0 rows affected (0.06 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> SELECT first_name
      -> FROM employees1
      -> WHERE employee_id = 10;
+-----+
| first_name |
+-----+
| Rahul      |
+-----+
1 row in set (0.00 sec)
```