

- 1) Create a table name STUDENT with following structure.

```
mysql> CREATE DATABASE CollegeDB;
ERROR 1007 (HY000): Can't create database 'collegedb'; database exists
mysql> USE CollegeDB;
Database changed
mysql> CREATE TABLE STUDENT
-> (
->   RegNo INT(3),
->   Name VARCHAR(15),
->   Gender CHAR(1),
->   DOB DATE,
->   MobileNo BIGINT,
->   City VARCHAR(15)
-> );
Query OK, 0 rows affected, 1 warning (0.07 sec)

mysql> DESC STUDENT;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| RegNo | int  | YES  |     | NULL    |       |
| Name  | varchar(15) | YES  |     | NULL    |       |
| Gender | char(1) | YES  |     | NULL    |       |
| DOB   | date  | YES  |     | NULL    |       |
| MobileNo | bigint | YES  |     | NULL    |       |
| City  | varchar(15) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.01 sec)
```

- 2) Create a table name FACULTY with following structure.

```
mysql> CREATE TABLE FACULTY
-> (
->   FacNo VARCHAR(4),
->   FacName VARCHAR(15),
->   Gender CHAR(1),
->   DOB DATE,
->   DOJ DATE,
->   MobileNo BIGINT
-> );
ERROR 1050 (42S01): Table 'faculty' already exists
mysql> DESC FACULTY;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| FacNo | varchar(4) | YES  |     | NULL    |       |
| FacName | varchar(15) | YES  |     | NULL    |       |
| Gender | char(1) | YES  |     | NULL    |       |
| DOB   | date  | YES  |     | NULL    |       |
| DOJ   | date  | YES  |     | NULL    |       |
| MobileNo | bigint | YES  |     | NULL    |       |
| Dept  | varchar(10) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)
```

- 3) Create a table name DEPARTMENT with following structure.

```
mysql> CREATE TABLE DEPARTMENT
-> (
-> DeptNo VARCHAR(4),
-> DeptName VARCHAR(15),
-> DeptHead VARCHAR(4)
-> );
ERROR 1050 (42S01): Table 'department' already exists
mysql> DESC DEPARTMENT;
```

Field	Type	Null	Key	Default	Extra
DeptNo	varchar(4)	YES		NULL	
DeptName	varchar(15)	YES		NULL	
DeptHead	varchar(4)	YES		NULL	

3 rows in set (0.00 sec)

- 4) Create a table name COURSE with following structure.

```
mysql> CREATE TABLE COURSE
-> (
-> CourseNo VARCHAR(3),
-> CourseDesc VARCHAR(14),
-> CourseType CHAR(1),
-> SemNo CHAR(1),
-> HallNo VARCHAR(4),
-> FacNo VARCHAR(4)
-> );
ERROR 1050 (42S01): Table 'course' already exists
mysql> DESC COURSE;
```

Field	Type	Null	Key	Default	Extra
CourseNo	varchar(3)	YES		NULL	
CourseDesc	varchar(14)	YES		NULL	
CourseType	char(1)	YES		NULL	
SemNo	char(1)	YES		NULL	
HallNo	varchar(4)	YES		NULL	
FacNo	varchar(4)	YES		NULL	

6 rows in set (0.00 sec)

- 5) Modify the table FACULTY by adding a column name Dept of datatype VARCHAR

```
mysql> ALTER TABLE FACULTY
-> ADD Dept VARCHAR(10);
ERROR 1060 (42S21): Duplicate column name 'Dept'
mysql> DESC FACULTY;
```

Field	Type	Null	Key	Default	Extra
FacNo	varchar(4)	YES		NULL	
FacName	varchar(15)	YES		NULL	
Gender	char(1)	YES		NULL	
DOB	date	YES		NULL	
DOJ	date	YES		NULL	
MobileNo	bigint	YES		NULL	
Dept	varchar(10)	YES		NULL	

```
7 rows in set (0.00 sec)
```