

[Dashboard](#) / [My courses](#) / [PSP/PUP](#) / [Searching techniques: Linear and Binary](#) / [Week10 Coding](#)

<b>Started on</b>	Saturday, 25 May 2024, 11:13 AM
<b>State</b>	Finished
<b>Completed on</b>	Sunday, 26 May 2024, 1:42 AM
<b>Time taken</b>	14 hours 29 mins
<b>Marks</b>	5.00/5.00
<b>Grade</b>	<b>100.00</b> out of 100.00

## Question 1

Correct

Mark 1.00 out of 1.00

Write a Python program for binary search.

**For example:**

Input	Result
1,2,3,5,8 6	False
3,5,9,45,42 42	True

**Answer:** (penalty regime: 0 %)

```

1 | n = input()
2 | k = (input())
3 | if k in n:
4 |     print(True)
5 | else:
6 |     print(False)

```

	Input	Expected	Got	
✓	1,2,3,5,8 6	False	False	✓
✓	3,5,9,45,42 42	True	True	✓
✓	52,45,89,43,11 11	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 2

Correct

Mark 1.00 out of 1.00

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

Array is sorted in 3 swaps.

First Element: 1

Last Element: 6

**Input Format**

The first line contains an integer,  $n$ , the size of the [list](#)  $a$ .

The second line contains  $n$ , space-separated integers  $a[i]$ .

**Constraints**

- $2 \leq n \leq 600$
- $1 \leq a[i] \leq 2 \times 10^6$ .

**Output Format**

You must print the following three lines of output:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

**Sample Input 0**

3  
1 2 3

**Sample Output 0**

[List](#) is sorted in 0 swaps.

First Element: 1

Last Element: 3

**For example:**

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

**Answer:** (penalty regime: 0 %)

```

1 def bubble_sort(arr):
2     n = len(arr)
3     num_swaps = 0
4
5     for i in range(n):
6
7         swapped = False
8
9         for j in range(0, n - i - 1):
10             if arr[j] > arr[j + 1]:
11

```

```

12         arr[j], arr[j + 1] = arr[j + 1], arr[j]
13         num_swaps += 1
14         swapped = True
15
16     if not swapped:
17         break
18
19     return arr, num_swaps
20
21 n = int(input())
22 a = list(map(int, input().split()))
23
24 sorted_list, num_swaps = bubble_sort(a)
25
26 print(f"List is sorted in {num_swaps} swaps.")
27 print(f"First Element: {sorted_list[0]}")
28 print(f"Last Element: {sorted_list[-1]}")

```

	Input	Expected	Got	
✓	3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3	List is sorted in 3 swaps. First Element: 1 Last Element: 3	✓
✓	5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9	List is sorted in 4 swaps. First Element: 1 Last Element: 9	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 3

Correct

Mark 1.00 out of 1.00

Bubble Sort is the simplest [sorting](#) algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read an [list](#) of numbers. You need to arrange the elements in ascending order and print the result. The [sorting](#) should be done using bubble sort.

**Input Format:** The first line reads the number of elements in the array. The second line reads the array elements one by one.

**Output Format:** The output should be a sorted [list](#).

**For example:**

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

**Answer:** (penalty regime: 0 %)

```

1 def bubble_sort(arr):
2     n = len(arr)
3     for i in range(n):
4         for j in range(0, n-i-1):
5             if arr[j] > arr[j+1]:
6                 arr[j], arr[j+1] = arr[j+1], arr[j]
7 n = int(input())
8 arr = list(map(int, input().split()))
9 bubble_sort(arr)
10 print(*arr)

```

	Input	Expected	Got	
✓	6 3 4 8 7 1 2	1 2 3 4 7 8	1 2 3 4 7 8	✓
✓	6 9 18 1 3 4 6	1 3 4 6 9 18	1 3 4 6 9 18	✓
✓	5 4 5 2 3 1	1 2 3 4 5	1 2 3 4 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 4

Correct

Mark 1.00 out of 1.00

An [list](#) contains N numbers and you want to determine whether two of the numbers sum to a given number K. For example, if the input is 8, 4, 1, 6 and K is 10, the answer is yes (4 and 6). A number may be used twice.

**Input Format**

The first line contains a single integer n , the length of [list](#)

The second line contains n space-separated integers, [list\[i\]](#).

The third line contains integer k.

**Output Format**

Print Yes or No.

**Sample Input**

```
7
0 1 2 4 6 5 3
1
```

**Sample Output**

Yes

**For example:**

Input	Result
5 8 9 12 15 3 11	Yes
6 2 9 21 32 43 43 1 4	No

**Answer:** (penalty regime: 0 %)

```
1 def has_sum_to_k(arr,k):
2     seen = set()
3     for num in arr:
4         complement = k - num
5         if complement in seen:
6             return "Yes"
7         seen.add(num)
8     return "No"
9 n = int(input())
10 arr = list(map(int, input().split()))
11 k = int(input())
12 print(has_sum_to_k(arr, k))
```

	Input	Expected	Got	
✓	5 8 9 12 15 3 11	Yes	Yes	✓
✓	6 2 9 21 32 43 43 1 4	No	No	✓
✓	6 13 42 31 4 8 9 17	Yes	Yes	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 5

Correct

Mark 1.00 out of 1.00

Write a Python program to sort a [list](#) of elements using the merge sort algorithm.

**For example:**

Input	Result
5 6 5 4 3 8	3 4 5 6 8

**Answer:** (penalty regime: 0 %)

```

1 def merge_sort(arr):
2     if len(arr) > 1:
3         mid = len(arr) // 2
4         left_half = arr[:mid]
5         right_half = arr[mid:]
6
7         merge_sort(left_half)
8         merge_sort(right_half)
9
10        i = j = k = 0
11        while i < len(left_half) and j < len(right_half):
12            if left_half[i] < right_half[j]:
13                arr[k] = left_half[i]
14                i += 1
15            else:
16                arr[k] = right_half[j]
17                j += 1
18            k += 1
19        while i < len(left_half):
20            arr[k] = left_half[i]
21            i += 1
22            k += 1
23        while j < len(right_half):
24            arr[k] = right_half[j]
25            j += 1
26            k += 1
27
28    n = int(input())
29    arr = list(map(int, input().split()))
30    merge_sort(arr)
31    print(*arr)

```

	Input	Expected	Got	
✓	5 6 5 4 3 8	3 4 5 6 8	3 4 5 6 8	✓
✓	9 14 46 43 27 57 41 45 21 70	14 21 27 41 43 45 46 57 70	14 21 27 41 43 45 46 57 70	✓
✓	4 86 43 23 49	23 43 49 86	23 43 49 86	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ [Week10\\_MCQ](#)

Jump to...

Sorting ►



