```
TCP
                                                                         74
                                                                               44420 → 80 [SYN] Seq=0
     1 0.000000
                      172.16.7.228
                                           210.212.97.132
Win=29200 Len=0 MSS=1460 SACK_PERM=1 TSval=440947 TSecr=0 WS=128
Frame 1: 74 bytes on wire (592 bits), 74 bytes captured (592 bits)
   Encapsulation type: Ethernet (1)
   Arrival Time: Aug 8, 2017 10:42:28.481260000 BST
    [Time shift for this packet: 0.000000000 seconds]
   Epoch Time: 1502185348.481260000 seconds
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 0.000000000 seconds]
   Frame Number: 1
   Frame Length: 74 bytes (592 bits)
   Capture Length: 74 bytes (592 bits)
    [Frame is marked: True]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:tcp]
    [Coloring Rule Name: HTTP]
    [Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: IntelCor_89:8b:31 (78:0c:b8:89:8b:31), Dst: ExtremeN_1d:e4:00 (00:04:96:1d:e4:00)
   Destination: ExtremeN_1d:e4:00 (00:04:96:1d:e4:00)
       Address: ExtremeN_1d:e4:00 (00:04:96:1d:e4:00)
        .... ..0. .... (factory default)
        .... ...0 .... .... = IG bit: Individual address (unicast)
   Source: IntelCor_89:8b:31 (78:0c:b8:89:8b:31)
       Address: IntelCor_89:8b:31 (78:0c:b8:89:8b:31)
        .... ..0. .... (factory default)
        .... ...0 .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 172.16.7.228, Dst: 210.212.97.132
   0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes
   Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
       0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
   Total Length: 60
   Identification: 0x98b1 (39089)
   Flags: 0x02 (Don't Fragment)
       0... = Reserved bit: Not set
       .1.. .... = Don't fragment: Set
       ..0. .... = More fragments: Not set
   Fragment offset: 0
   Time to live: 64
   Protocol: TCP (6)
   Header checksum: 0xb9bd [validation disabled]
        [Good: False]
       [Bad: False]
   Source: 172.16.7.228
   Destination: 210.212.97.132
    [Source GeoIP: Unknown]
    [Destination GeoIP: Jaipur, 24, AS9829 National Internet Backbone, India, 26.916700, 75.816704]
        [Destination GeoIP City: Jaipur, 24]
        [Destination GeoIP AS Number: AS9829 National Internet Backbone]
        [Destination GeoIP Country: India]
        [Destination GeoIP Latitude: 26.916700]
        [Destination GeoIP Longitude: 75.816704]
Transmission Control Protocol, Src Port: 44420 (44420), Dst Port: 80 (80), Seq: 0, Len: 0
    Source Port: 44420
   Destination Port: 80
    [Stream index: 0]
    [TCP Segment Len: 0]
    Sequence number: 0
                         (relative sequence number)
   Acknowledgment number: 0
   Header Length: 40 bytes
   Flags: 0x002 (SYN)
       000. .... = Reserved: Not set
       ...0 .... = Nonce: Not set
        .... 0... = Congestion Window Reduced (CWR): Not set
       \dots .0.. = ECN-Echo: Not set
       .... ..0. .... = Urgent: Not set
        .... ...0 .... = Acknowledgment: Not set
       .... 0... = Push: Not set
        .... .... .0.. = Reset: Not set
        .... syn: Set
           [Expert Info (Chat/Sequence): Connection establish request (SYN): server port 80]
               [Connection establish request (SYN): server port 80]
```

[Severity level: Chat]

```
[Group: Sequence]
        \dots Not set
        [TCP Flags: ************
    Window size value: 29200
    [Calculated window size: 29200]
    Checksum: 0x53e9 [validation disabled]
        [Good Checksum: False]
        [Bad Checksum: False]
    Urgent pointer: 0
    Options: (20 bytes), Maximum segment size, SACK permitted, Timestamps, No-Operation (NOP),
Window scale
        Maximum segment size: 1460 bytes
            Kind: Maximum Segment Size (2)
            Length: 4
           MSS Value: 1460
        TCP SACK Permitted Option: True
           Kind: SACK Permitted (4)
            Length: 2
        Timestamps: TSval 440947, TSecr 0
           Kind: Time Stamp Option (8)
            Length: 10
           Timestamp value: 440947
           Timestamp echo reply: 0
        No-Operation (NOP)
           Type: 1
               0... = Copy on fragmentation: No
                .00. .... = Class: Control (0)
                ...0 0001 = Number: No-Operation (NOP) (1)
        Window scale: 7 (multiply by 128)
            Kind: Window Scale (3)
            Length: 3
            Shift count: 7
            [Multiplier: 128]
```