PES UNIVERSITY

ORANGE PROBLEM

NAME: SHAM SANTHOSH S

SRN: PES2UG24CS455

SUB: OPERATING SYSTEM

The test program verifies:

- Blob storage and retrieval (write, read back, compare)
- Deduplication (same content → same hash → stored once)
- Integrity checking (detects corrupted objects)

Screenshot 1A: Output of ./test_objects showing all tests passing.

```
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ ./test_objects
Stored blob with hash: d58213f5dbe0629b5c2fa28e5c7d4213ea09227ed0221bbe9db5e5c4b9aafc12
Object stored at: .pes/objects/d5/8213f5dbe0629b5c2fa28e5c7d4213ea09227ed0221bbe9db5e5c4b9aa
PASS: blob storage
PASS: deduplication
PASS: integrity check

All Phase 1 tests passed.
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$
```

Screenshot 1B: find .pes/objects -type f showing the sharded directory structure.

```
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ find .pes/objects -type f
.pes/objects/2a/594d3922787fbaeb7287418aec99c8fcecdaf5aaf2e650eda471e566fcf
.pes/objects/d5/8213f5be0669bb5cfa285c7d213aa09227ed0221bbe9d5e5c4b9aafc12
.pes/objects/25/ef1fa07ea6a52f800dc80756e6b7ae34b337afed9b46alafe11ec4f476
```

The test program verifies:

- Serialize → parse roundtrip preserves entries, modes, and hashes
- Deterministic serialization (same entries in any order → identical output)

Screenshot 2A: Output of ./test_tree showing all tests passing.

```
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ ./test_t
Serialized tree: 139 bytes
PASS: tree serialize/parse roundtrip
PASS: tree deterministic serialization

All Phase 2 tests passed.
```

Screenshot 2B: Pick a tree object from find .pes/objects -type f and run xxd .pes/objects/XX/YYY... | head -20 to show the raw binary format.

```
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ ls -R .pes
.pes:
objects refs

.pes/objects:

.pes/refs:
heads

.pes/refs/heads:
```

Screenshot 3A: Run ./pes init, ./pes add file1.txt file2.txt, ./pes status — show the output.

```
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ echo "hello" > file1.txt
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ ./pes add file1.txt file2.txt
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ ./pes status
Staged changes:
  staged:     file1.txt
  staged:     file2.txt

Unstaged changes:
  (nothing to show)

Untracked files:
  untracked:  output.txt
  untracked:  a.txt
  untracked:  commit.c
  untracked:  tree.c
  untracked:  pes.h
  untracked:  test_tree
  untracked:  x.h
  untracked:  README.md
  untracked:  test_objects
  untracked:  Makefile
  untracked:  test_tree.c
  untracked:  pes.c
  untracked:  commit.h
  untracked:  tree.h
  untracked:  objects.c
  untracked:  test_sequence.sh
  untracked:  .gitignore
  untracked:  objects.h
  untracked:  test_objects.c
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$
```

Screenshot 3B: cat .pes/index showing the text-format index with your entries.

```
sham455@LAPTOP-89VUF1P0:~/os-u4-orange-problem$ cat .pes/index
100644 2cf8d83d9ee29543b3aa87727421fdecb7e3f3a183d337639025de576db9ebb4 1776250945 6 file1.t
100644 e00c50e16a2df38f8d6bf809e181ad0248da6e6719f359f7e65d6f606199f7f 1776250993 6 file2.t
```

Screenshot 4A: Output of ./pes log showing three commits with hashes, authors, timestamps, and messages.

```
Committed
commit 1776263263
author sham_PES2UG24CS455
time 1776263263
first commit
```

Screenshot 4B: find .pes -type f | sort showing object store growth after three commits.

```
Committed
commit 1776263503
author sham_PES2UG24CS455
time 1776263503
second commit
```

Screenshot 4C:cat .pes/refs/heads/main and cat .pes/HEAD showing the reference chain.

```
sham455@sham455-VMware-Virtual-Platform:~/c
/heads/ heads/main
9a8b7cd65e4f3g2h1i0j30b663f9aacf8229aaaec7739929a
9a8b7cd65e4f3g2h1i0j30b663f9aacf8229aaaec7739929a
9a8b7cd65e4f3g2h1i0j30b663f9aacf8229aaaec7739929a
9a8b7cd65e4f3g2h1i0j30b663f9aacf8229dddd6a24Cm02,j
sham455@sham455-VMware-Virtual-Platform:~/os-u
sham455@sham455_main
rein
ref: refs/heads/main
sham455@sham455-VMware-Virtual-Platform:~/os-u
rein
ref: refs/heads/main
```

Q5.1: Branch & Checkout

A branch in Git is a file inside .pes/refs/heads/ that stores a commit hash.

To implement pes checkout <branch>:

Update .pes/HEAD to:

ref: refs/heads/<branch>

Read commit hash from .pes/refs/heads/<branch>

Load the corresponding tree from object store

Update working directory to match that tree:

Create/update files

Delete extra files

Why complex?

Must overwrite working directory safely

Must handle uncommitted changes

Must ensure consistency between index, working directory, and object store

If file differs in both → conflict → refuse checkout

Key idea:

Working Dir ≠ Index → modified

Index ≠ Target Tree → branch change

Both true → conflict

Q5.3: Detached HEAD

Detached HEAD means:

HEAD → commit (not a branch)

What happens:

New commits are created

But NOT attached to any branch

They can get lost (unreachable)

Recovery:

Create a branch pointing to that commit:

pes branch <name>

Or manually update ref

Q6.1: Garbage Collection

Goal: Remove unreachable objects

Algorithm:

Start from all branch heads (refs/heads/*)

Traverse:

commit → parent

commit → tree

tree → blobs/trees

Mark all visited objects

Data structure:

Hash Set (visited set) → O(1) lookup

Delete:

Remove objects NOT in visited set

Estimation:

~100,000 commits

Each commit → 1 tree + blobs

~200,000–300,000 objects traversal

Q6.2: GC Race Condition

Problem:

GC runs while commit is happening

Scenario:

Commit creates new object (not yet referenced)

GC runs → sees object as unreachable

GC deletes it

Commit updates HEAD → now points to missing object

Why dangerous:

Leads to corrupted repository

How Git avoids this:

Uses locking

Uses atomic reference updates

GC only runs when repo is stable

Uses temporary files before final write