☑ Autocommit Display 10 ⌄

```
SELECT emp.empno,emp.ename,emp.deptno,dept.deptno,dept.loc
FROM emp,dept
WHERE emp.deptno=dept.deptno;
```

Results **Explain** **Describe** **Saved SQL** **History**

EMPNO	ENAME	DEPTNO	DEPTNO	LOC
7369	SMITH	20	20	DALLAS
7499	ALLEN	30	30	CHICAGO
7521	WARD	30	30	CHICAGO
7566	JONES	20	20	DALLAS
7654	MARTIN	30	30	CHICAGO
7698	BLAKE	30	30	CHICAGO
7782	CLARK	10	10	NEW YORK
7788	SCOTT	20	20	DALLAS
7839	KING	10	10	NEW YORK
7844	TURNER	30	30	CHICAGO

More than 10 rows available. Increase rows selector to view more rows.

☑ Autocommit **Display** 10 ▽

```sql
SELECT e.empno,e.ename,e.deptno,d.deptno,d.loc
FROM emp e,dept d
WHERE e.deptno=d.deptno;
```

Results **Explain** **Describe** **Saved SQL** **History**

EMPNO	ENAME	DEPTNO	DEPTNO	LOC
7369	SMITH	20	20	DALLAS
7499	ALLEN	30	30	CHICAGO
7521	WARD	30	30	CHICAGO
7566	JONES	20	20	DALLAS
7654	MARTIN	30	30	CHICAGO
7698	BLAKE	30	30	CHICAGO
7782	CLARK	10	10	NEW YORK
7788	SCOTT	20	20	DALLAS
7839	KING	10	10	NEW YORK
7844	TURNER	30	30	CHICAGO

More than 10 rows available. Increase rows selector to view more rows.

```
SELECT e.ename,e.sal,s.grade
FROM emp e,salgrade s
WHERE e.sal
BETWEEN s.losal AND s.hisal;
```

Results   Explain   Describe   Saved SQL   History

ENAME	SAL	GRADE
SMITH	800	1
JAMES	950	1
ADAMS	1100	1
SMITH	800	1
JAMES	950	1
ADAMS	1100	1
SMITH	800	1
JAMES	950	1
ADAMS	1100	1
SMITH	800	1
More than 10 rows available. Increase rows selector to view more rows.		

10 rows returned in 0.00 seconds   CSV Export