

Detailed Data Dictionary

One row per implemented attribute. PK = primary key; FK = foreign key; Null? indicates whether NULL is accepted.

Table	Attribute	Data type	Null?	Key / constraint	Reference / default	Description
Category	CategoryID	INT	No	PK, Identity	Auto-generated	Unique identifier for a product category.
Category	CategoryName	VARCHAR(80)	No	UNIQUE	-	Unique product-category name.
Category	Description	VARCHAR(255)	Yes	-	-	Optional explanation of the category.
Brand	BrandID	INT	No	PK, Identity	Auto-generated	Unique identifier for a brand.
Brand	BrandName	VARCHAR(80)	No	UNIQUE	-	Unique manufacturer or brand name.
UnitOfMeasure	UnitID	INT	No	PK, Identity	Auto-generated	Unique identifier for a unit of measure.
UnitOfMeasure	UnitCode	VARCHAR(10)	No	UNIQUE	-	Short stock unit code, such as PCS or M.
UnitOfMeasure	UnitName	VARCHAR(50)	No	-	-	Full name of the unit of measure.
Product	ProductID	INT	No	PK, Identity	Auto-generated	Unique identifier for a plumbing product.
Product	SKU	VARCHAR(30)	No	UNIQUE	-	Unique stock-keeping code.
Product	ProductName	VARCHAR(150)	No	-	-	Descriptive product name.
Product	CategoryID	INT	No	FK	Category(CategoryID)	Category assigned to the product.
Product	BrandID	INT	No	FK	Brand(BrandID)	Brand assigned to the product.
Product	UnitID	INT	No	FK	UnitOfMeasure(UnitID)	Unit used to count or measure the product.
Product	StandardCost	DECIMAL(12,2)	No	CHECK >= 0	DEFAULT 0	Standard purchasing cost per unit.
Product	StandardSellingPrice	DECIMAL(12,2)	No	CHECK >= 0	DEFAULT 0	Standard selling price per unit.
Product	IsActive	BIT	No	DEFAULT	1	Shows whether the product is available for use.
Product	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
Product	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
Product	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
Product	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
ProductSpecification	SpecificationID	INT	No	PK, Identity	Auto-generated	Unique identifier for a specification row.
ProductSpecification	ProductID	INT	No	FK; UNIQUE (composite)	Product(ProductID)	Product to which the specification belongs.
ProductSpecification	SpecName	VARCHAR(60)	No	UNIQUE (composite)	With ProductID	Specification label, such as diameter.
ProductSpecification	SpecValue	VARCHAR(100)	No	-	-	Value recorded for the specification.
Supplier	SupplierID	INT	No	PK, Identity	Auto-generated	Unique identifier for a supplier.
Supplier	SupplierName	VARCHAR(120)	No	-	-	Supplier's business name.
Supplier	Email	VARCHAR(120)	Yes	-	-	Optional supplier email address.
Supplier	Phone	VARCHAR(30)	Yes	-	-	Optional supplier telephone number.
Supplier	AddressLine	VARCHAR(200)	Yes	-	-	Optional supplier address.
Supplier	IsActive	BIT	No	DEFAULT	1	Shows whether the supplier can be used.
Supplier	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
Supplier	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
Supplier	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
Supplier	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
Warehouse	WarehouseID	INT	No	PK, Identity	Auto-generated	Unique identifier for a warehouse.
Warehouse	WarehouseName	VARCHAR(100)	No	UNIQUE	-	Unique warehouse or store name.
Warehouse	Location	VARCHAR(150)	No	-	-	Physical location of the warehouse.
Warehouse	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
Warehouse	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
Warehouse	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
Warehouse	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
SystemUser	UserID	INT	No	PK, Identity	Auto-generated	Unique identifier for a staff account.

Detailed Data Dictionary

One row per implemented attribute. PK = primary key; FK = foreign key; Null? indicates whether NULL is accepted.

Table	Attribute	Data type	Null?	Key / constraint	Reference / default	Description
SystemUser	Username	VARCHAR(50)	No	UNIQUE	-	Unique sign-in name.
SystemUser	FullName	VARCHAR(100)	No	-	-	Staff member's full name.
SystemUser	Email	VARCHAR(120)	No	UNIQUE	-	Unique staff email address.
SystemUser	PasswordHash	VARCHAR(255)	No	-	-	Hashed credential; plain-text passwords are not stored.
SystemUser	IsActive	BIT	No	DEFAULT	1	Shows whether the account can be used.
Role	RoleID	INT	No	PK, Identity	Auto-generated	Unique identifier for a business role.
Role	RoleName	VARCHAR(50)	No	UNIQUE	-	Unique authorised role name.
UserRole	UserID	INT	No	PK, FK (composite)	SystemUser(UserID)	User included in the role assignment.
UserRole	RoleID	INT	No	PK, FK (composite)	Role(RoleID)	Role assigned to the user.
PurchaseOrder	PurchaseOrderID	INT	No	PK, Identity	Auto-generated	Unique identifier for a purchase order.
PurchaseOrder	SupplierID	INT	No	FK	Supplier(SupplierID)	Supplier receiving the purchase order.
PurchaseOrder	OrderDate	DATE	No	-	-	Date on which the order was placed.
PurchaseOrder	ExpectedDate	DATE	Yes	-	-	Expected delivery date, when known.
PurchaseOrder	Status	VARCHAR(20)	No	CHECK	DEFAULT 'Draft'	Current purchase-order workflow status.
PurchaseOrder	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
PurchaseOrder	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
PurchaseOrder	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
PurchaseOrder	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
PurchaseOrderItem	PurchaseOrderItemID	INT	No	PK, Identity	Auto-generated	Unique identifier for a purchase-order line.
PurchaseOrderItem	PurchaseOrderID	INT	No	FK	PurchaseOrder(PurchaseOrderID)	Purchase-order header containing the line.
PurchaseOrderItem	ProductID	INT	No	FK	Product(ProductID)	Product being ordered.
PurchaseOrderItem	QuantityOrdered	DECIMAL(12,2)	No	CHECK > 0	-	Positive quantity requested from the supplier.
PurchaseOrderItem	UnitCost	DECIMAL(12,2)	No	CHECK >= 0	-	Agreed supplier cost per unit.
GoodsReceipt	GoodsReceiptID	INT	No	PK, Identity	Auto-generated	Unique identifier for a goods receipt.
GoodsReceipt	PurchaseOrderID	INT	No	FK	PurchaseOrder(PurchaseOrderID)	Purchase order being received.
GoodsReceipt	WarehouseID	INT	No	FK	Warehouse(WarehouseID)	Warehouse receiving the goods.
GoodsReceipt	ReceivedByUserID	INT	No	FK	SystemUser(UserID)	Staff account that accepted the receipt.
GoodsReceipt	ReceiptDate	DATE	No	-	-	Date on which the goods were received.
GoodsReceipt	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
GoodsReceipt	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
GoodsReceipt	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
GoodsReceipt	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
GoodsReceiptItem	GoodsReceiptItemID	INT	No	PK, Identity	Auto-generated	Unique identifier for a receipt line.
GoodsReceiptItem	GoodsReceiptID	INT	No	FK	GoodsReceipt(GoodsReceiptID)	Goods-receipt header containing the line.
GoodsReceiptItem	PurchaseOrderItemID	INT	No	FK	PurchaseOrderItem(PurchaseOrderItemID)	Purchase-order line being fulfilled.
GoodsReceiptItem	ProductID	INT	No	FK	Product(ProductID)	Product physically received.
GoodsReceiptItem	QuantityReceived	DECIMAL(12,2)	No	CHECK > 0	-	Positive quantity received on this line.
Inventory	ProductID	INT	No	PK, FK (composite)	Product(ProductID)	Product represented by the stock balance.
Inventory	WarehouseID	INT	No	PK, FK (composite)	Warehouse(WarehouseID)	Warehouse represented by the stock balance.
Inventory	QuantityOnHand	DECIMAL(12,2)	No	CHECK >= 0	DEFAULT 0	Physical quantity currently held.
Inventory	ReservedQuantity	DECIMAL(12,2)	No	CHECK >= 0	DEFAULT 0	Quantity reserved for sales orders.
Inventory	ReorderLevel	DECIMAL(12,2)	No	CHECK >= 0	DEFAULT 0	Stock level that indicates replenishment is needed.
Inventory	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.

Detailed Data Dictionary

One row per implemented attribute. PK = primary key; FK = foreign key; Null? indicates whether NULL is accepted.

Table	Attribute	Data type	Null?	Key / constraint	Reference / default	Description
Inventory	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
Inventory	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
Inventory	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
StockMovement	StockMovementID	BIGINT	No	PK, Identity	Auto-generated	Unique identifier for a stock movement.
StockMovement	ProductID	INT	No	FK	Product(ProductID)	Product affected by the stock movement.
StockMovement	WarehouseID	INT	No	FK	Warehouse(WarehouseID)	Warehouse affected by the stock movement.
StockMovement	MovementType	VARCHAR(20)	No	CHECK	-	Reason category for the stock change.
StockMovement	QuantityChange	DECIMAL(12,2)	No	CHECK <> 0	-	Signed quantity added to or removed from stock.
StockMovement	ReferenceType	VARCHAR(40)	Yes	-	-	Optional source transaction type.
StockMovement	ReferenceID	INT	Yes	-	-	Optional identifier of the source transaction.
StockMovement	AuthorisedByUserID	INT	No	FK	SystemUser(UserID)	User who authorised the stock movement.
StockMovement	MovementDateTime	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the movement was recorded.
Customer	CustomerID	INT	No	PK, Identity	Auto-generated	Unique identifier for a customer.
Customer	CustomerName	VARCHAR(120)	No	-	-	Customer or business name.
Customer	CustomerType	VARCHAR(30)	No	CHECK	-	Customer classification, such as plumber or retailer.
Customer	Email	VARCHAR(120)	Yes	-	-	Optional customer email address.
Customer	Phone	VARCHAR(30)	Yes	-	-	Optional customer telephone number.
Customer	AddressLine	VARCHAR(200)	Yes	-	-	Optional customer address.
Customer	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
Customer	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
Customer	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
Customer	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
SalesOrder	SalesOrderID	INT	No	PK, Identity	Auto-generated	Unique identifier for a sales order.
SalesOrder	CustomerID	INT	No	FK	Customer(CustomerID)	Customer that placed the order.
SalesOrder	OrderDate	DATE	No	-	-	Date on which the sales order was placed.
SalesOrder	Status	VARCHAR(20)	No	CHECK	DEFAULT 'Pending'	Current sales-order workflow status.
SalesOrder	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
SalesOrder	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
SalesOrder	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
SalesOrder	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
SalesOrderItem	SalesOrderItemID	INT	No	PK, Identity	Auto-generated	Unique identifier for a sales-order line.
SalesOrderItem	SalesOrderID	INT	No	FK	SalesOrder(SalesOrderID)	Sales-order header containing the line.
SalesOrderItem	ProductID	INT	No	FK	Product(ProductID)	Product ordered by the customer.
SalesOrderItem	WarehouseID	INT	No	FK	Warehouse(WarehouseID)	Warehouse allocated to fulfil the line.
SalesOrderItem	QuantityOrdered	DECIMAL(12,2)	No	CHECK > 0	-	Positive quantity ordered by the customer.
SalesOrderItem	SellingPrice	DECIMAL(12,2)	No	CHECK >= 0	-	Agreed selling price per unit.
Payment	PaymentID	INT	No	PK, Identity	Auto-generated	Unique identifier for a payment.
Payment	SalesOrderID	INT	No	FK	SalesOrder(SalesOrderID)	Sales order to which the payment applies.
Payment	PaymentDate	DATE	No	-	-	Date on which payment was received.
Payment	Amount	DECIMAL(12,2)	No	CHECK > 0	-	Positive amount received.
Payment	PaymentMethod	VARCHAR(30)	No	CHECK	-	Method used to make the payment.
Payment	ReferenceNo	VARCHAR(80)	Yes	-	-	Optional bank, card or receipt reference.
Payment	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.

Detailed Data Dictionary

One row per implemented attribute. PK = primary key; FK = foreign key; Null? indicates whether NULL is accepted.

Table	Attribute	Data type	Null?	Key / constraint	Reference / default	Description
Payment	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
Payment	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
Payment	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
Delivery	DeliveryID	INT	No	PK, Identity	Auto-generated	Unique identifier for a delivery.
Delivery	SalesOrderID	INT	No	FK	SalesOrder(SalesOrderID)	Sales order being delivered.
Delivery	WarehouseID	INT	No	FK	Warehouse(WarehouseID)	Warehouse dispatching the delivery.
Delivery	DeliveryDate	DATE	Yes	-	-	Actual delivery date when completed.
Delivery	DeliveryStatus	VARCHAR(20)	No	CHECK	DEFAULT 'Pending'	Current delivery workflow status.
Delivery	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
Delivery	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
Delivery	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
Delivery	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
DeliveryItem	DeliveryItemID	INT	No	PK, Identity	Auto-generated	Unique identifier for a delivery line.
DeliveryItem	DeliveryID	INT	No	FK	Delivery(DeliveryID)	Delivery header containing the line.
DeliveryItem	SalesOrderItemID	INT	No	FK	SalesOrderItem(SalesOrderItemID)	Sales-order line being delivered.
DeliveryItem	QuantityDelivered	DECIMAL(12,2)	No	CHECK > 0	-	Positive quantity delivered on this line.
SalesReturn	ReturnID	INT	No	PK, Identity	Auto-generated	Unique identifier for a sales return.
SalesReturn	SalesOrderID	INT	No	FK	SalesOrder(SalesOrderID)	Original sales order for the return.
SalesReturn	ReturnDate	DATE	No	-	-	Date on which the return was recorded.
SalesReturn	Reason	VARCHAR(255)	Yes	-	-	Optional reason supplied for the return.
SalesReturn	CreatedAt	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the record was created.
SalesReturn	UpdatedAt	DATETIME2	Yes	-	-	Date and time of the most recent update.
SalesReturn	CreatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that created the record.
SalesReturn	UpdatedByUserID	INT	Yes	FK	SystemUser(UserID)	User account that most recently updated the record.
ReturnItem	ReturnItemID	INT	No	PK, Identity	Auto-generated	Unique identifier for a returned-item line.
ReturnItem	ReturnID	INT	No	FK	SalesReturn(ReturnID)	Return header containing the item.
ReturnItem	SalesOrderItemID	INT	No	FK	SalesOrderItem(SalesOrderItemID)	Original sales-order line being returned.
ReturnItem	QuantityReturned	DECIMAL(12,2)	No	CHECK > 0	-	Positive quantity returned.
ReturnItem	ItemCondition	VARCHAR(20)	No	CHECK	-	Condition of the item when returned.
AuditLog	AuditLogID	BIGINT	No	PK, Identity	Auto-generated	Unique identifier for an audit event.
AuditLog	UserID	INT	No	FK	SystemUser(UserID)	User responsible for the recorded action.
AuditLog	ActionName	VARCHAR(80)	No	-	-	Name of the action performed.
AuditLog	TableName	VARCHAR(80)	No	-	-	Name of the affected table.
AuditLog	RecordID	VARCHAR(50)	Yes	-	-	Identifier of the affected record, when applicable.
AuditLog	ActionDateTime	DATETIME2	No	DEFAULT	SYSDATETIME()	Date and time the audit event occurred.
AuditLog	Outcome	VARCHAR(20)	No	CHECK	-	Result of the attempted action.