

Guide for Deploying Cognos BI With Informix Dynamic Server

Environment:

Windows 7 64 bit
Cognos BI Server 10.2.1
Informix Dynamic Server 11.70

This article will give a guide to show using IDS as the content store and data source for Cognos BI server. There are three parts as bellow:


Part One – Install Informix Dynamic Server 11.70



Part Two – Set IDS as the content store for Cognos BI



Part Three – Set IDS as the data source for Cognos BI



Part One – Install Informix Dynamic Server 11.70



1. Download and install IBM Informix Dynamic Server
You can search IBM Informix Dynamic Server 11.7 from:
<http://w3-103.ibm.com/software/xl/download/ticket.do>
2. The install process is as below screen shot:















IBM Informix 11.70

System Resources Usage

- ✓ Overview
- ✓ Installation location
- ✓ Installation features
- ✓ Security
- ▶ Instance configuration
- ▶ Installation summary
- ▶ Installing...
- ▶ Post-installation steps
- ▶ Installation Complete

Processors:

Total available processors: 8

Allocate processors to the database server:

☒ Number ☐ Percentage of total (%)

1

Memory:

Total available memory: 15950 (MB)

Allocate memory to the database server:

☒ Size (MB) ☐ Percentage of total (%)

128

InstallAnywhere

Cancel Help Previous Next

IBM Informix 11.70

Database Server Usage

- ✓ Overview
- ✓ Installation location
- ✓ Installation features
- ✓ Security
- ▶ Instance configuration
- ▶ Installation summary
- ▶ Installing...
- ▶ Post-installation steps
- ▶ Installation Complete

Workload type

☒ Online transaction processing (OLTP)

☐ Data warehousing (DSS)

Maximum number of concurrent users

20

Maximum number of decision support users

5

Transaction logging supported by application(s)?

☒ Yes

☐ No


Recovery time objective

InstallAnywhere

Cancel Help Previous Next

Next step is very important, Cognos content store must use DRDA protocol to connect with Informix database.

The Service name and Port you can change to what you like.



IBM Informix 11.70

Connectivity

- ✓ Overview
- ✓ Installation location
- ✓ Installation features
- ✓ Security
- ▶ Instance configuration
- ▷ Installation summary
- ▷ Installing...
- ▷ Post-installation steps
- ▷ Installation Complete

9088

Instance server number

0

DRDA Support

DRDA supports applications and database systems using IBM data server clients:

☒ Enable DRDA protocol

Server alias:

dr_cbiwin


Port

9089

InstallAnywhere

Cancel Help Previous Next

Instance Configuration

 **Instance configuration**

The parameters specified for expected instance usage yielded a configuration that will require 1562 MB of the 335179 MB available on disk; is this acceptable?

No - Review Yes - Acceptable

IBM Informix 11.70

Disk Space Allocation Summary

- ✓ Overview
- ✓ Installation location
- ✓ Installation features
- ✓ Security
- ▶ Instance configuration
- ▷ Installation summary
- ▷ Installing...
- ▷ Post-installation steps
- ▷ Installation Complete

Recommended space allocation

Total instance space: 1562 (MB)

On the following panels, you can adjust the calculated values for the configured database spaces, physical log, and transaction logs.



Would you like to review the configuration details?



☒ Yes



☐ No

InstallAnywhere

Cancel Help Previous Next







Now the install process has finished.

The information of new IDS instance as below:

Server Name: cbiwin

Service Name for SQLI connections: cbiwin

Port number for SQLI: 9088

Server number: 0


Server Alias for DRDA support: dr_cbiwin

Port number for DRDA support: 9089


Part Two – Set IDS as the content store for Cognos BI

1. Set Informix database environment

Follow the procedure below to set some environment variables for UTF8 databases.



1) Start Setnet32 by clicking Start -> All Programs -> IBM Informix Client SDK 11.70 -> Setnet32.2) From the Server Information tab, select the IBM Informix server dr_cbiwin.



3). Click the Environment tab and set the following environment variables:


Set the value for below parameters:

CLIENT_LOCALE=en_us.utf8

```
DB_LOCALE=en_us.utf8
GL_USEGLU=1
INFORMIXSERVER=cbiwin
```

3). Click OK.

2. As Cognos recommendations, in the ONCONFIG.cbiwin file (%INFORMIXDIR%\etc\%ONCONFIG%), set the property SHMBASE to at least 0x13000000L.




```
C:\ibm\Informix\11.70\etc\onconfig.cbiwin - Notepad++
File Edit Search View Encoding Language Settings Macro Run Plugins Window ? X
onconfig.cbiwin
330 #####
331
332 RESIDENT 0
333 SHMBASE 0x13000000L
334 SHMVIRTSIZE 105472
335 SHMADD 3290
336 EXTSHMADD 8192
337 SHMTOTAL 0
338 SHMVIRT_ALLOCSEG 0,3
339 #SHMNOACCESS 0x70000000-0x7FFFFFFF
length: 72366 lines Ln: 333 Col: 21 Sel: 0 | 0 Dos\Windows ANSI as UTF-8 INS
```

3. Restart the Informix instance service (Informix IDS –cbiwin) in the windows services.

4. As Cognos recommendations, create two sbspaces namely CMDATASPACE and CMOBJPROPS7SPACE, with the logging turned on.

Follow the below procedure:

- 1) Set up cbiwin environment, using notepad open %INFORMIXDIR%\cbiwin.cmd, enter below parameters:



```
cbiwin.cmd - Notepad
File Edit Format View Help
set INFORMIXDIR=C:\IBM\Informix\11.70
set REGMACHINE=\\ADMINIB-M13P0FS
set INFORMIXSERVER=cbiwin
set ONCONFIG=onconfig.cbiwin
set PATH=%INFORMIXDIR%\bin;%PATH%
set CLIENT_LOCALE=en_us.utf8
set DB_LOCALE=en_us.utf8
set DBDATE=Y4MD
set GL_USEGLU=1
```

- 2) Start cbiwin by clicking Start -> All Programs -> IBM Informix 11.70 -> cbiwin.

Input below commands:

```
type NUL > C:\IFMXDATA\cbiwin\CMDATASPACE.000
type NUL > C:\IFMXDATA\cbiwin\CMOBJPROPS7SPACE.000

onspaces -c -S CMDATASPACE -p C:\IFMXDATA\cbiwin\CMDATASPACE.000 -o 0 -s
300000 -Df "LOGGING=ON"
onspaces -c -S CMOBJPROPS7SPACE -p C:\IFMXDATA\cbiwin\CMOBJPROPS7SPACE.000 -o
0 -s 300000 -Df "LOGGING=ON"
```

3) Now we are ready to create a database for the content store. The content store database has to be created with “log mode ANSI”. Save the following “CREATE DATABASE” SQL statement into a file called create_csdb.sql at %INFORMIXDIR%\CREATE DATABASE csdb WITH LOG MODE ANSI;

4) Run the create_csdb.sql script with the following command at the cbiwin command prompt

dbaccess - create_csdb.sql

5. Set the following system environment variables:



DB_LOCALE to en_us.utf8 (User)

CLIENT_LOCALE to en_us.utf8 (System)
GL_USEGLU to 1 (System)



6. We have already installed IBM Data Server Driver for JDBC. Copy db2jcc.jar file from <DataServerDriver_location>\java to <c10_location>\webapps\p2pd\WEB-INF\lib folder.

If you do not have drivers you can find them bellow



[\\wottsmithdalab.ottawa.ibm.com\DataBase Drivers\Caspian\Informix](http://wottsmithdalab.ottawa.ibm.com/DataBase%20Drivers/Caspian/Informix)



7. Set Advanced properties in Cognos Configuration:






8. Set Informix as content store as below and test it.




Part Three – Set IDS as the data source for Cognos BI

1. Create a new server instance.
Start -> All Programs -> Informix Dynamic Server 11.70 -> Server Instance Manager
Click create new, the process as below screen shot:






Click next, you need to input your password, and then click yes for initialize it now



2. Extend table Dbospace and restore database.



The default size of ce_remote_dat.000 is 100M, we should extend the space, the method as below:

- 1) Create new files named ce_remote_dat.001 and ce_remote_dat.002 under %IFMXDATA%\ce_remote directory.
- 2) Start -> All Programs -> Informix Dynamic Server 11.70 -> ce_remote
Input below command:


```
onspaces -a ce_remote -p c:\IFMXDATA\ce_remote\ce_remote_dat.001 -s 300000 -o 0
onspaces -a ce_remote -p c:\IFMXDATA\ce_remote\ce_remote_dat.002 -s 300000 -o 0
```

3) Copy gosales.exp and gosalesdw.exp to %INFORMIXDIR%. You can search Cognos Informix Sample from: <http://w3-103.ibm.com/software/xl/download/ticket.do>

4) Restore GOSALES and GOSALESDW database. Input the command as below:

```
dbimport -ci gosales -d ce_remote
dbimport -ci gosalesdw -d ce_remote
```

When finished , you can input command : dbaccess and select database. You can see the two database.



3. Add new data source connection for Cognos.

1) In IBM Cognos Administration, select Configuration table, click add new data source icon, type the name as great_outdoors_sales.

IBM Cognos Administration

Status Security **Configuration** Library Multitenancy Index Search

Data Source Connections

- Content Administration
- Distribution Lists and Contacts
- Printers
- Styles
- Portlets
- Dispatchers and Services
- Query Service Caching

Specify a name and description - New Data Source wizard

Specify a name and location for this entry. You can also specify a description and screen tip.

Name:
great_outdoors_sales

Description:

Screen tip:

Location:
Directory > Cognos

Cancel < Back Next > Finish

2) Select type as IBM Informix Dynamic Server

Specify the connection - New Data Source wizard
Specify the parameters for the connection of this new data source.

Type:

Isolation level:
☒ Use the default object gateway
☐ Specify a value:

☐ Configure JDBC connection

3) Input Informix database parameters as below:

Host name:

Server name:

Collation sequence:

Service:
☐ SQLEXEC
☐ SQLTURBO
☒ 9090

Signon
 Select whether a user ID and password is required in the connection string and, if so, whether to create a signon.

☒ User ID
☒ Password
☒ Create a signon that the Everyone group can use:

User ID:

Password:

Confirm password:

Testing
[Test the connection...](#)

4) Click test the connection

...> Name	Type / Query Mode	Status	Message
http://adminib-m13p0fs:9300/p2pd	IBM Informix Dynamic Server / Compatible	Succeeded	

5) Do the same process add new great_outdoors_warehouse connection with informix

database gosalesdw.

4. Import sample package

1) Copy the IBM_Cognos_Samples.zip file from the c10_location/webcontent/samples/content directory to the c10_location/deployment directory.

2) On the Welcome page, click Administer IBM Cognos Content. On the Configuration tab, click Content Administration. On the toolbar, click New Import.

The screenshot shows the IBM Cognos Administration web interface. The left sidebar contains a navigation menu with links: Data Source Connections, Content Administration (selected), Distribution Lists and Contacts, Printers, Styles, Portlets, Dispatchers and Services, and Query Service Caching. The main content area is titled 'Select a deployment archive - New Import wizard'. It includes instructions: 'Select the deployment archive from which to get the entries to import. If the archive is encrypted, you will be prompted for the password.' Below this is a section for 'Deployment archive' with a text box stating: 'The location of the deployment archive is set using the deployment files location in IBM Cognos Configuration.' A table lists available archives:

	Name
<input checked="" type="radio"/>	IBM_Cognos_Samples

At the bottom, there are four buttons: Cancel, < Back, Next >, and Finish.

3) Click next ,type a unique name and an optional description and screen tip for the deployment archive, select the folder where you want to save it, and then click Next.

4) In the Public Folders Content pane, select the folders that you want to import.

The screenshot shows the second step of the 'New Import wizard', titled 'Select the public folders and directory content - New Import wizard'. It includes instructions: 'Select one or more packages, folders or directory content and select the options to include in the import.' Below this is a section for 'Public folders, directory and library content' with a text box stating: 'Change the target name of packages and folders if you do not want to overwrite them in the target with packages. Disable the packages or folders if you do not want users to access them in the target after the import.' A table lists available content:

<input type="checkbox"/>	...> Name	...> Target name
<input checked="" type="checkbox"/>	Samples	Samples

5) Click next, Review the summary information and click Next. To run once now or later, click Save and run once. Click Finish.

6) Select run options, and click run.