

#### **AQUATICA**

Inspired by underwater flora, the Aquatica decorative film will add character to a sophisticated and professional environment. The use of original shapes on your glazing or glass partitions is an excellent way to brighten up any space.



Warranty **5 YEARS** 



Fire-resistance rating



Storage from -5°C to +40°C **3 YEARS** 



RoHS

REACH RoHS compliant



# WIDTHS AVAILABLE:



152 cm

## TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

| Ultraviolet transmission             | NC %   |
|--------------------------------------|--------|
| Visible light transmission           | 0 %    |
| Reflection of external visible light | 0 %    |
| Reflection of internal visible light | 0 %    |
| Total solar energy rejected          | %      |
| Total solar energy rejected 2*       | %      |
| Solar ratio:                         |        |
| Solar energy reflection              | 0 %    |
| Solar energy absorption              | 0 %    |
| Solar energy transmission            | 0 %    |
| Reduction in Solar Glare             | 0 %    |
| g-value                              | NC     |
| u-value                              | NC     |
| Shading coefficient                  | NC     |
| Installation type : Interior         |        |
| Roll length                          | 30,5 m |
| Film composition                     | PET    |
| Thickness                            | 40 μ   |
|                                      |        |

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

| Clear single pane              | ~ |
|--------------------------------|---|
| Tinted single pane             | ~ |
| Reflective tinted single pane  | ~ |
| Clear double pane              | ~ |
| Tinted double pane             | ~ |
| Reflective tinted double pane  | ~ |
| Gas-filled double pane - Low E | ~ |
| STADIP EXT. clear double pane  | ~ |
| STADIP INT. clear double pane  | ~ |
|                                |   |




\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.

### **CONSTRUCTION**

Colour from the outside: FROSTED

- 1. High optical quality polyester with printed design
- 2. PS adhesive, glass polymerization within 15 days 3. Protection release liner, disposable after installation



#### **MAINTENANCE INSTRUCTIONS**

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.