



### **BRAIN**

Composed of interlaced lines, the Brain film decorates your windows and glass partitions in an original way. The use of a discretion film is ideal to embellish your space while preserving your privacy.



Warranty

**5 YEARS** 



Fire-resistance rating





Storage from -5°C to +40°C

**3 YEARS** 



REACH RoHS compliant

RESPECTED

## WIDTHS AVAILABLE:



152 cm

### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	0 %
Reflection of external visible light	0 %
Reflection of internal visible light	0 %
Total solar energy rejected	%
Total solar energy rejected 2*	%
Solar ratio:	
Solar energy reflection	0 %
Solar energy absorption	0 %
Solar energy transmission	0 %
Reduction in Solar Glare	0 %
g-value	NC
u-value	NC
Shading coefficient	NC
Installation type : Interior	
Roll length	30,5 m
Film composition	PET
Thickness	40 μ

# Colour from the outside: FROSTED

# **CONSTRUCTION**

- 1. High optical quality polyester with printed design
- 2. PS adhesive, glass polymerization within 15 days 3. Protection release liner, disposable after installation


### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

Clear single pane	<b>~</b>
Tinted single pane	<b>~</b>
Reflective tinted single pane	<b>~</b>
Clear double pane	~
Tinted double pane	<b>~</b>
Reflective tinted double pane	<b>~</b>
Gas-filled double pane - Low E	<b>~</b>
STADIP EXT. clear double pane	<b>~</b>
STADIP INT. clear double pane	<b>~</b>



\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.



#### **MAINTENANCE INSTRUCTIONS**

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.