



STRADA

The Strada decorative film, featuring a pattern of opaque horizontal bands, allows you to effectively customize your windows and glass partitions.



Warranty
5 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED



Approved transparent
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

| | |
|--------------------------------------|--------|
| Ultraviolet transmission | NC % |
| Visible light transmission | NC % |
| Reflection of external visible light | NC % |
| Reflection of internal visible light | NC % |
| Total solar energy rejected | % |
| Total solar energy rejected 2* | % |
| Solar ratio : | |
| Solar energy reflection | NC % |
| Solar energy absorption | NC % |
| Solar energy transmission | NC % |
| Reduction in Solar Glare | NC % |
| g-value | NC |
| u-value | NC |
| Shading coefficient | NC |
| Installation type : Interior | |
| Roll length | 30,5 m |
| Film composition | PET |
| Thickness | 40 µ |

Colour from the outside : FROSTED

CONSTRUCTION

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.

INSTALLATION ADVICE

Vertical installation and on standard glass surface*

| | |
|--------------------------------|---|
| Clear single pane | ✓ |
| Tinted single pane | ✓ |
| Reflective tinted single pane | ✓ |
| Clear double pane | ✓ |
| Tinted double pane | ✓ |
| Reflective tinted double pane | ✓ |
| Gas-filled double pane - Low E | ✓ |
| STADIP EXT. clear double pane | ✓ |
| STADIP INT. clear double pane | ✓ |

✓ Yes ! Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

