



### **BOREAL**

The Boreal decorative film allows you to effectively personalise your windows and glass partitions. Decorated with a graduated white mottled effect pattern, arranged in 40 mm linear bands.



Warranty





Fire-resistance rating





Storage from -5°C to +40°C

**3 YEARS** 



REACH RoHS compliant

RESPECTED

### WIDTHS AVAILABLE:



152 cm

### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	NC %
Reflection of external visible light	NC %
Reflection of internal visible light	NC %
Total solar energy rejected	%
Total solar energy rejected 2*	%
Solar ratio:	
Solar energy reflection	NC %
Solar energy absorption	NC %
Solar energy transmission	NC %
Reduction in Solar Glare	NC %
g-value	NC
u-value	NC
Shading coefficient	NC
Installation type: Interior	
Roll length	50 m
Film composition	PET
Thickness	$40~\mu$

# Colour from the outside: WHITE

## **CONSTRUCTION**

- 1. High optical quality polyester with printed design
- 2. PS adhesive, glass polymerization within 15 days 3. Protection release liner, disposable after installation

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

Clear single pane	<b>~</b>
Tinted single pane	~
Reflective tinted single pane	<b>~</b>
Clear double pane	<b>~</b>
Tinted double pane	<b>~</b>
Reflective tinted double pane	<b>~</b>
Gas-filled double pane - Low E	<b>~</b>
STADIP EXT. clear double pane	<b>~</b>
STADIP INT. clear double pane	<b>~</b>



\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.



#### **MAINTENANCE INSTRUCTIONS**

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.