

## Lecture 5: Evaluation

How do I choose among the various models?

e.g. choose  $k$  for  $kNN$

e.g. choose design for OLS

We need some way to evaluate which model building process is going to perform better.

- use OLS w/ 5 vars
- use  $kNN$  w/  $k=5$
- use  $kNN$  and optimize over possible values of  $k$

A (maybe not always great) way of doing this!

calculate some performance metric on  $\hat{f}$  from the training data

e.g.

① training residual sums of squares

$$RSS_{\text{train}} = \sum_{n=1}^N (y_n - \hat{y}_n)^2$$

② training mean sq. error

$$MSE_{\text{train}} = \frac{RSS_{\text{train}}}{N}$$

③ training root mean sq. err:  $RMSE_{\text{train}} = \sqrt{MSE_{\text{train}}}$

$$(4) \text{ training } R^2_{\text{train}} = 1 - \frac{RSS_{\text{train}}}{TSS_{\text{train}}}$$

$$TSS_{\text{train}} = \sum_n (y_n - \bar{y})^2$$

↑ % of var. explained by  $\hat{f}$   
% of variance

Why isn't a training metric always a good measure of performance?

→ I don't actually care about performance on my training data  
(I already know the answer)

→ I actually care about performance of  $\hat{f}$  on new/unseen data.  
(generalization performance)

ERM:

$$\underbrace{\frac{1}{N} \sum_{n=1}^N L(y_n, \hat{f}(x_n))}_{\text{avg. loss over training data}} \approx \underbrace{E[L(Y, \hat{f}(X))]}_{\text{actual loss}}$$

Similarly:

$$\underbrace{\text{Metric}(\{y_n, \hat{f}(x_n)\})}_{\substack{\text{training metric/perf.} \\ \text{performance}}} \approx E[\underbrace{\text{Metric}(\{Y, \hat{f}(X)\})}_{\substack{\text{generalization} \\ \text{performance}}}]$$

Focusing too much on training metric can be misleading.

This happens b/c when I evaluate  $\hat{f}$  on my training data I am evaluating it on the same data used to build  $\hat{f}$ .

So my model building process has already seen the training data - it's not a fair evaluation.

Analogy: Test 1: I give you 10 practice problems and a week from now I give exam w/ exactly those 10 problems.

eval. on training data →

Test 2: I give you 10 practice problem and a week from now I give exam w/ 10 related but not exactly the same questions.

generalization perf. →

---


Ex. This can happen in SML too.

Consider optimizing the value of  $R$  for  $k$ NN by choosing the value of  $k$  that minimizes  $RSS_{train}$ .

What value of  $k$  do I choose?

$$k = 1$$

When  $k=1$  I interpolate my training data




So  $\hat{y}_n = y_n$  for training data  $n=1, \dots, N$

hence  $RSS_{\text{train}} = \sum_n \underbrace{(y_n - \hat{y}_n)^2}_{=0} = 0$

A similar story is true for OLS when choosing what terms to include in the design.

As  $p \rightarrow N$  I will interpolate my training data

We call this "over-fitting"



How do we solve this?

Let's estimate generalization perf.

Need independent set of (unseen) data to evaluate our model on.

Testing Data:  $\{(x_{\text{test},h}, y_{\text{test},h})\}_{h=1}^{N_{\text{test}}}$

Procedure:


- (1) use training data to build  $\hat{f}$
- (2) eval. perf. of  $\hat{f}$  on testing data

$RSS_{\text{test}}, MSE_{\text{test}},$   
 $RMSE_{\text{test}}, R^2_{\text{test}}$

↙ an estimate of generalization perf. of my model building process.

How do I get testing data?


Do a test/train split.



$p = 90, 80, 50$

One can do this split multiple times which is called Cross-validation

## K-Fold Cross Validation



Cycle through folds  
For  $k=1, \dots, K$

- ① train model on all but fold  $k$
- ② test model on fold  $k$   
call this test metric  $m_k$

So at the end of loop I have

$$m_1, m_2, \dots, m_K$$

can combine to get overall perf. metric

$$m = \text{median}(m_1, \dots, m_K)$$

But wait! If I train  $K$  different models which do I use?

None. I train a model using all of my data.

We want to evaluate performance generally for two reasons:

① I want to know how good this MBP might be

Model Building Process

② I want to choose among various models.

We can use a test/train split or x-validation to choose among models - but we need to be very careful.

---