Ansible Automation - Use Cases

A reference of the use cases by which Ansible Automation Platform is commonly implemented, by domain. Each use case is described in the same format (Description, Collection, Key content, Notes) and mapped to Red Hat Certified and Validated content.

17 solution use cases · 293 product use cases · generated 2026-10-21 · community reference, not an official Red Hat publication

Contents

1. Security
    - Solution use cases (17)
        - Harden RHEL to CIS and DISA STIG baselines
        - Scan and remediate compliance
        - Remediate vulnerabilities from scanner findings
        - Manage firewall policy across vendors
        - Enrich SIEM investigations and automate response
        - Contain threats from EDR detections
        - Manage IDS/IPS and threat-prevention rules
        - Retrieve secrets from external vaults
        - Rotate privileged credentials
        - Install Red Hat IdM servers, replicas and clients
        - Manage users and access policy in IdM
        - Integrate Active Directory and single sign-on
        - Manage the certificate lifecycle
        - Secure the software supply chain
        - Configure RHACS as code
        - Respond to security events with Event-Driven Ansible
        - Secure web and private access with Zscaler
    - Product use cases
        - Check Point Gaia (10)
        - Check Point Management (Security Management API) (22)
        - Cisco ASA (2)
        - Cisco Identity Services Engine (ISE) (15)
        - CrowdStrike Falcon (4)
        - CyberArk Conjur (1)
        - CyberArk Identity Security Platform (2)
        - CyberArk Privileged Access Security (2)
        - Delinea Privileged Access Service (1)
        - Entrust Certificate Authority Gateway (1)
        - Fortinet FortiGate (via FortiManager) (35)
        - Fortinet FortiAnalyzer (21)
        - Fortinet FortiFlex (3)
        - Fortinet FortiManager (34)
        - Fortinet FortiGate (FortiOS) (29)
        - Fortinet FortiSASE (9)
        - Fortinet FortiSwitch (13)
        - HashiCorp Vault (4)
        - IBM Security Verify Access (ISAM) (17)
        - IBM QRadar (2)
        - Red Hat Advanced Cluster Security for Kubernetes (RHACS) (5)
        - 1Password Connect (1)
        - Palo Alto Networks PAN-OS and Panorama (10)
        - Palo Alto Networks PAN-OS (2)
        - Red Hat Trusted Artifact Signer (1)
        - Red Hat Identity Management (FreeIPA) (17)
        - Red Hat Trusted Profile Analyzer (1)
        - Splunk Enterprise Security (2)
        - Open Policy Agent (1)
        - Thales CipherTrust Manager (5)
        - Trend Micro Deep Security (2)
        - CyberArk Certificate Manager (Venafi) (2)
        - Virsec Security Platform (1)
        - Zscaler Internet Access (ZIA) (9)
        - Zscaler Private Access (7)

Security

Harden, scan, remediate, orchestrate security tools, and manage secrets and identity.

Solution use cases

Use Case: Harden RHEL to CIS and DISA STIG baselines

Description	Bring new and existing RHEL servers to a documented security baseline such as CIS or DISA STIG, and re-apply it on a schedule so that hosts do not drift. The same automation is used at build time and for hosts already in production.
Collection	`redhat.rhel_hardening_roles` (Certified, v1.1.82, updated 2026-10-12), `infra.automation_development_office` (Validated, v2.0.0, updated 2026-10-06), `redhat.rhel_system_roles` (Certified, v2.4.2, updated 2026-10-06)
Key content	• `infra.automation_development_office.rhel_stig_cac` — Apply DISA STIG Compliance-as-Code on RHEL 8, 9, and 10 hosts. • `redhat.rhel_system_roles.selinux` — Essentially provide mechanisms to manage local customizations: • `redhat.rhel_system_roles.crypto_policies` — This Ansible role manages system-wide crypto policies. • `redhat.rhel_system_roles.auditd` — Manage auditd and audit rules • `redhat.rhel_system_roles.aide` — This is an ansible role that installs and configures the Advanced Intrusion Detection Environment (AIDE). For Day 2 tasks it can run integrity checks and update the AIDE database. • `redhat.rhel_system_roles.fapolicyd` — Fapolicyd System Role • `redhat.rhel_system_roles.ssh` — An Ansible role for managing ssh clients configuration.
Notes	• Applying a STIG or CIS profile can change SSH, authentication and audit settings. Test on non-production hosts first and keep out-of-band console access. • Hardening is the fix side of compliance. Use Scan and remediate compliance to measure it. • Controls for the identity layer are covered in Install Red Hat IdM. • Pair with Event-Driven Ansible to re-apply the baseline when a configuration change on a host is detected, for example from `ansible.eda.file_watch`.

Use Case: Scan and remediate compliance

Description	Detect configuration that does not meet the chosen security policy, report it in a form auditors accept, and fix it with the same automation that applies the baseline. The loop covers RHEL hosts and OpenShift clusters and runs continuously, not only before audits.
Collection	`redhat.satellite` (Certified, v5.11.0, updated 2026-04-17), `redhat.insights` (Certified, v1.3.1, updated 2026-03-12), `infra.automation_development_office` (Validated, v2.0.0, updated 2026-10-06), `redhat.rhel_system_roles` (Certified, v2.4.2, updated 2026-10-06), `servicenow.itsm` (Certified, v2.16.0, updated 2026-08-24)
Key content	• `redhat.satellite.scap_content` — Manage SCAP content • `redhat.satellite.scap_tailoring_file` — Manage SCAP Tailoring Files • `redhat.insights.compliance` — Install and configure Red Hat Insights Client • `infra.automation_development_office.rhel_stig_cac` — Apply DISA STIG Compliance-as-Code on RHEL 8, 9, and 10 hosts. • `infra.automation_development_office.ocp_compliance_scan` — An collection. • `infra.automation_development_office.ocp_compliance_remediation` — An collection. • `servicenow.itsm.incident` — Manage ServiceNow incidents
Notes	• Scan first and remediate in a separate job template, so a change window and an approval can sit between them. • Pair with Harden RHEL to CIS and DISA STIG baselines for the baseline itself and Remediate vulnerabilities from scanner findings for patch-level findings. • Pair with Event-Driven Ansible when a scanner can send a webhook on a new failed rule; see Respond to security events with Event-Driven Ansible.

Use Case: Remediate vulnerabilities from scanner findings

Description	Close the gap between "the scanner found it" and "it is fixed and verified". Findings from a vulnerability scanner start a workflow in Automation Platform that maps each finding to a fix, applies it with the right approvals, and asks the scanner to confirm that the finding has gone.
Collection	`redhat.satellite` (Certified, v5.11.0, updated 2026-04-17), `ansible.controller` (Certified, v4.8.11, updated 2026-09-30), `ansible.eda` (Certified, v2.13.0, updated 2026-07-07), `servicenow.itsm` (Certified, v2.16.0, updated 2026-08-24)
Key content	• `redhat.satellite.host_errata_info` — Fetch information about Host Errata • `redhat.satellite.content_view_version` — Manage Content View Versions • `redhat.satellite.job_invocation` — Invoke Remote Execution Jobs • `ansible.controller.workflow_job_template` — create, update, or destroy Automation Platform Controller workflow job templates. • `ansible.eda.webhook` — Receive events via a webhook. • `servicenow.itsm.change_request` — Manage ServiceNow change requests
Notes	• There is no Red Hat Certified collection for Tenable, Qualys or Rapid7 today; integrations call the scanner's REST API (for example with `ansible.builtin.uri`) or use community content from Ansible Galaxy. See the security vendor pages for what exists and how it is supported. • Not every finding can be patched. Route configuration findings to Harden RHEL to CIS and DISA STIG baselines and send the rest to a ticket with an exception owner. • Kernel or library updates may need a reboot. Add a reboot and wait step to the workflow and respect maintenance windows. • Pair with Scan and remediate compliance for policy-level findings. • Pair with Event-Driven Ansible for the trigger, as described in Respond to security events with Event-Driven Ansible.

Use Case: Manage firewall policy across vendors

Description	Handle firewall rule requests the same way on every platform. A request supplies source, destination and service, the automation checks whether the traffic is already allowed, adds the objects and rule on the right firewall, commits the change and records it. Teams with several vendors get one process instead of one per console.
Collection	`paloaltonetworks.panos` (Certified, v3.4.1, updated 2026-07-24), `paloaltonetworks.panos_policy_automation` (Validated, v1.4.6, updated 2026-02-03), `fortinet.fortios` (Certified, v2.6.0, updated 2026-08-15), `fortinet.fortimanager` (Certified, v2.15.0, updated 2026-08-11), `check_point.mgmt` (Certified, v7.0.1, updated 2026-09-02), `cisco.asa` (Certified, v6.1.0, updated 2025-01-17), `servicenow.itsm` (Certified, v2.16.0, updated 2026-08-24)
Key content	• `paloaltonetworks.panos_policy_automation.policy_creation` — Configure new network access in Palo Alto Networks Panorama • `paloaltonetworks.panos.panos_security_rule` — Manage security rule policy on PAN-OS devices or Panorama management console. • `fortinet.fortios.fortios_firewall_policy` — Configure IPv4/IPv6 policies in Fortinet's FortiOS and FortiGate. • `fortinet.fortimanager.fmgr_securityconsole_install_package` — Copy and install a policy package to devices. • `check_point.mgmt.cp_mgmt_access_rule` — Manages access-rule objects on Check Point over Web Services API • `check_point.mgmt.cp_mgmt_install_policy` — install policy on Check Point over Web Services API • `cisco.asa.asa_acls` — Access-Lists resource module
Notes	• Run the change against a pre-production firewall or a candidate configuration first where the platform supports it. • Back up the configuration before each change; see Back up device configuration. • For cloud-delivered policy use Secure web and private access with Zscaler. • For intrusion prevention and threat profiles on the same firewalls see Manage IDS/IPS and threat-prevention rules.

Use Case: Enrich SIEM investigations and automate response

Description	Give analysts the context they would otherwise collect by hand, and run the routine response steps automatically. When the SIEM raises a finding or offense, Automation Platform gathers host, user and ticket details, writes them back to the case, and starts the matching response plan. Analysts decide on the exceptions.
Collection	`splunk.es` (Certified, v6.0.1, updated 2026-07-13), `ibm.qradar` (Certified, v4.0.0, updated 2024-06-12), `crowdstrike.falcon` (Certified, v4.14.1, updated 2026-10-08), `servicenow.itsm` (Certified, v2.16.0, updated 2026-08-24)
Key content	• `splunk.es.splunk_correlation_searches` — Splunk Enterprise Security Correlation searches resource module • `splunk.es.splunk_investigation` — Manage Splunk Enterprise Security investigations • `splunk.es.splunk_notes` — Manage notes for findings, investigations, and response plan tasks • `splunk.es.splunk_response_plan_execution` — Apply response plans to investigations and manage tasks • `ibm.qradar.offense_info` — Obtain information about one or many QRadar Offenses, with filter options • `ibm.qradar.offense_note` — Create or update a QRadar Offense Note • `ibm.qradar.offense_action` — Take action on a QRadar Offense • `crowdstrike.falcon.ngsiem_search` — Execute searches against CrowdStrike Next-Gen SIEM repositories
Notes	• Start with read-only enrichment, then add response actions after the quality of the alerts is proven. • Send containment actions to Contain threats from EDR detections. • Pair with Respond to security events with Event-Driven Ansible for the trigger side. • ibm.qradar log source and rule modules marked deprecated in the collection should be replaced by their resource-module successors, such as `ibm.qradar.qradar_log_sources_management`.

Use Case: Contain threats from EDR detections

Description	Limit the spread of an attack in minutes. When the EDR reports a high-severity detection, the automation confirms the host, isolates it at the endpoint and at the network access layer, opens an incident, and releases the host only after an analyst approves.
Collection	`crowdstrike.falcon` (Certified, v4.14.1, updated 2026-10-08), `cisco.ise` (Certified, v3.3.0, updated 2026-10-16), `ansible.eda` (Certified, v2.13.0, updated 2026-07-07), `servicenow.itsm` (Certified, v2.16.0, updated 2026-08-24)
Key content	• `crowdstrike.falcon.host_info` — Get information about Falcon hosts • `crowdstrike.falcon.host_contain` — Network contain hosts in Falcon • `crowdstrike.falcon.host_group` — Manage Falcon host groups • `cisco.ise.anc_policy` — Resource module for ANCpolicy • `cisco.ise.anc_endpoint_apply` — Resource module for ANCendpoint Apply • `cisco.ise.anc_endpoint_clear` — Resource module for ANCendpoint Clear • `servicenow.itsm.incident` — Manage ServiceNow incidents
Notes	• Use an approval step for critical servers where automatic isolation could cause an outage. • Falcon sensors themselves can be rolled out and configured with `crowdstrike.falcon.falcon_install` and `crowdstrike.falcon.falcon_configure`. • Combine with Enrich SIEM investigations and automate response and Respond to security events with Event-Driven Ansible.

Use Case: Manage IDS/IPS and threat-prevention rules

Description	Treat intrusion detection and prevention settings as managed configuration. Profiles, custom signatures, exceptions and update schedules live in version control, are applied the same way across devices and products, and can be changed quickly when a new threat appears.
Collection	`fortinet.fortios` (Certified, v2.6.0, updated 2026-08-15), `fortinet.fortimanager` (Certified, v2.15.0, updated 2026-08-11), `check_point.mgmt` (Certified, v7.0.1, updated 2026-09-02), `trendmicro.deepsec` (Certified, v4.0.0, updated 2024-06-12), `zscaler.ziacloud` (Certified, v2.2.4, updated 2026-06-02)

Key content	• `fortinet.fortios.fortios_ips_sensor` — Configure IPS sensor in Fortinet's FortiOS and FortiGate. • `fortinet.fortimanager.fmgr_ips_sensor` — Configure IPS sensor. • `check_point.mgmt.cp_mgmt_threat_profile` — Manages threat-profile objects on Check Point over Web Services API • `check_point.mgmt.cp_mgmt_run_ips_update` — Runs IPS database update. If "package-path" is not provided server will try to get the latest package from the User Center. • `trendmicro.deepsec.deepsec_intrusion_prevention_rules` — Intrusion Prevention Rule resource module. • `zscaler.ziacloud.zia_cloud_firewall_ips_rules` — Firewall Filtering policy IPS rule.
Notes	• Zscaler also supports custom IPS signatures through `zscaler.ziacloud.zia_ips_signature_rules`. • In `trendmicro.deepsec`, older modules such as `deepsec_intrusion_preventionrules` are marked deprecated; use the resource modules such as `deepsec_intrusion_prevention_rules`. • Combine with Manage firewall policy across vendors for the policy that the profile is attached to. • Pair with Event-Driven Ansible to push a block rule when a SIEM alert names an attacker address; see Respond to security events with Event-Driven Ansible.

Use Case: Retrieve secrets from external vaults

Description	Keep secrets in the corporate vault and let automation read them only when a job runs. Automation Platform authenticates to the vault, passes the value to the job, and never writes it to the project, the inventory or the job output.
Collection	`hashicorp.vault` (Certified, v1.3.0, updated 2026-07-09), `cyberark.conjur` (Certified, v1.3.14, updated 2026-08-05), `cyberark.isp` (Certified, v1.0.8, updated 2026-04-28), `onepassword.connect` (Certified, v2.4.0, updated 2026-05-04), `delinea.ss` (Certified, v1.1.0, updated 2023-09-14), `akeyless.secrets_management` (Certified, v1.2.2, updated 2026-07-31), `ansible.controller` (Certified, v4.8.11, updated 2026-09-30)
Key content	• `hashicorp.vault.kv2_secret_get` — Look up KV2 secrets stored in HashiCorp Vault. • `hashicorp.vault.kv2_secret_info` — Read HashiCorp Vault KV version 2 secrets • `cyberark.conjur.conjur_variable` — Fetch credentials from CyberArk Conjur. • `cyberark.isp.cyberark_credential` — Credential retrieval using Secrets Manager Central Credential Provider. • `onepassword.connect.field_info` — Returns the value of a field in a 1Password item. • `ansible.controller.credential_input_source` — create, update, or destroy Automation Platform Controller credential input sources.
Notes	• Prefer credential input sources for platform credentials, and direct lookups only when a playbook needs a value for its own use. • `delinea.ss` and `akeyless.secrets_management` are certified collections; check their documentation for the plugins available in your version. • Rotate the values themselves with Rotate privileged credentials. • Pair with Event-Driven Ansible by storing rulebook credentials in the same way; `ansible.eda.credential_input_source` exists for that purpose.

Use Case: Rotate privileged credentials

Description	Replace long-lived shared passwords with credentials that the vault owns and changes regularly. Automation onboards accounts into the privileged access system, sets up rotation, and updates the systems that depend on the credentials.
Collection	`cyberark.isp` (Certified, v1.0.8, updated 2026-04-28), `cyberark.pas` (Certified, v1.0.40, updated 2026-04-28), `hashicorp.vault` (Certified, v1.3.0, updated 2026-07-09), `delinea.pas` (Certified, v1.0.4, updated 2024-09-23), `ansible.controller` (Certified, v4.8.11, updated 2026-09-30)
Key content	• `cyberark.isp.cyberark_safe` — CyberArk Safe Management using Privilege Cloud Shared Services REST APIs. • `cyberark.isp.cyberark_account` — Module for CyberArk Account object creation, deletion, modification, and password retrieval using PAS Web Services SDK. • `cyberark.isp.cyberark_safe_member` — CyberArk Safe Member Management using Privilege Cloud Services Shared Services REST APIs. • `hashicorp.vault.database_connection` — Manage database secrets engine connections in HashiCorp Vault. • `hashicorp.vault.database_static_role` — Manage database static roles in HashiCorp Vault • `hashicorp.vault.database_credential_rotation` — Rotate Database Credentials in HashiCorp Vault. • `delinea.pas.delinea_vault` — This role installs, enrolls, unenrolls, and removes Delinea Privileged Access Services (PAS) on your systems. It supports RHEL/CentOS, Debian, and SUSE distributions.
Notes	• Rotate a test account first and confirm every consumer picks up the new value before widening the scope. • Use the vault's own audit log as the record of who retrieved which credential. • Pair with Event-Driven Ansible to rotate immediately after a suspected compromise; the `cyberark.pas.syslog` event source can feed such a rulebook, see Respond to security events with Event-Driven Ansible.

Use Case: Install Red Hat IdM servers, replicas and clients

Description	Stand up Red Hat Identity Management as the central directory, Kerberos and certificate service for Linux. The first server, its replicas and every client are installed from the same inventory, so a new site or a rebuild takes a job run instead of a runbook.
Collection	`redhat.rhel_idm` (Certified, v1.16.0, updated 2026-02-10), `infra.automation_development_office` (Validated, v2.0.0, updated 2026-10-06)
Key content	• `redhat.rhel_idm.ipaserver` — A role to setup an iPA domain server • `redhat.rhel_idm.ipareplica` — A role to setup an IPA domain replica • `redhat.rhel_idm.ipaclient` — A role to join a machine to an IPA domain • `redhat.rhel_idm.ipadnszone` — Manage FreeIPA dnszone • `infra.automation_development_office.idm_server` — An IDM client role for managing identity management clients. • `infra.automation_development_office.idm_client` — An IDM client role for managing identity management clients.
Notes	• Back up the IdM servers before upgrades or topology changes. • Day-two administration is covered in Manage users and access policy in IdM; trusts to Active Directory in Integrate Active Directory and single sign-on. • Certificates issued by the IdM CA can be managed as described in Manage the certificate lifecycle.

Use Case: Manage users and access policy in IdM

Description	Define who can log in where, and who can run what with elevated rights, in files under version control. Joiner, mover and leaver changes and access policy changes are made through reviewed pull requests and applied by Automation Platform.
Collection	`redhat.rhel_idm` (Certified, v1.16.0, updated 2026-02-10), `redhat.rhel_system_roles` (Certified, v2.4.2, updated 2026-10-06)
Key content	• `redhat.rhel_idm.ipauser` — Manage FreeIPA users • `redhat.rhel_idm.ipagroup` — Manage FreeIPA groups • `redhat.rhel_idm.ipahostgroup` — Manage FreeIPA hostgroups • `redhat.rhel_idm.ipahbacrule` — Manage FreeIPA HBAC rules • `redhat.rhel_idm.ipasudorule` — Manage FreeIPA sudo rules • `redhat.rhel_idm.ipapwpolicy` — Manage FreeIPA pwpolicies
Notes	• Test HBAC changes on a limited host group first, because a wrong rule can lock out administrators. • Use `redhat.rhel_system_roles.sudo` for hosts that are not in IdM. • For organizations that source users from Active Directory, see Integrate Active Directory and single sign-on.

Use Case: Integrate Active Directory and single sign-on

Description	Let people use their existing corporate identity everywhere. Linux hosts either trust Active Directory through IdM or join it directly, and applications, including Automation Platform, authenticate through Red Hat build of Keycloak or another external identity provider.
Collection	`redhat.rhel_idm` (Certified, v1.16.0, updated 2026-02-10), `redhat.rhel_system_roles` (Certified, v2.4.2, updated 2026-10-06), `microsoft.ad` (Certified, v1.12.1, updated 2026-08-26), `redhat.rhbk` (Certified, v3.0.2, updated 2026-06-25), `ansible.platform` (Certified, v2.7.20260930, updated 2026-09-30), `infra.automation_development_office` (Validated, v2.0.0, updated 2026-10-06)
Key content	• `redhat.rhel_idm.ipatrust` — Manage FreeIPA Domain Trusts. • `infra.automation_development_office.idm_ad_trust` — Establish two-way IdM/AD trust and map AD users for SSH/sudo • `redhat.rhel_system_roles.ad_integration` — An ansible role which configures direct Active Directory integration. • `microsoft.ad.user` — Manage Active Directory users • `microsoft.ad.group` — Manage Active Directory group objects • `redhat.rhbk.keycloak_identity_provider` — Allows administration of Keycloak identity providers using Keycloak API • `ansible.platform.authenticator` — Configure a gateway authenticator. • `ansible.platform.authenticator_map` — Configure a gateway authenticator maps.
Notes	• Okta and other SAML or OIDC providers can be configured as the upstream source of an authenticator; no Okta-specific collection is among the certified security content. • Test the trust on a lab realm first, since DNS and time errors are the common causes of failure. • Combine with Install Red Hat IdM servers, replicas and clients and Manage users and access policy in IdM.

Use Case: Manage the certificate lifecycle

Description	Stop certificate expiry from causing outages. Automation requests certificates from the approved authority, installs them where services use them, reloads the services, and renews or revokes certificates on a schedule or on demand.
Collection	`venafi.machine_identity` (Certified, v1.1.1, updated 2025-09-12), `entrust.crypto` (Certified, v1.0.1, updated 2023-12-20), `hashicorp.vault` (Certified, v1.3.0, updated 2026-07-09), `redhat.rhel_idm` (Certified, v1.16.0, updated 2026-02-10), `redhat.rhel_system_roles` (Certified, v2.4.2, updated 2026-10-06), `microsoft.ad` (Certified, v1.12.1, updated 2026-08-26)
Key content	• `venafi.machine_identity.venafi_certificate` — CyberArk certificate module for working with CyberArk Certificate Manager, SaaS or CyberArk Certificate Manager, Self-Hosted • `venafi.machine_identity.venafi_certificate_revoke` — Revoke a certificate on CyberArk platforms • `entrust.crypto.cagw_certificate` — Entrust Certificate Gateway (CAGW) API Integration - Request/Get/Hold/Unhold/Revoke an SSL certificate from the CAGW API. • `hashicorp.vault.pki_certificate` — Issue, sign, or revoke HashiCorp Vault PKI certificates • `redhat.rhel_idm.ipacert` — Manage FreeIPA certificates • `redhat.rhel_system_roles.certificate` — Role for managing TLS/SSL certificate issuance and renewal
Notes	• Keep private keys on the host that uses them, and do not copy them through job output or artifacts. • `venafi.machine_identity` also covers SSH certificates, through `venafi.machine_identity.venafi_ssh_certificate`. • Pair with Event-Driven Ansible to renew on an expiry alert from monitoring; see Respond to security events with Event-Driven Ansible. • Related: Install Red Hat IdM servers, replicas and clients for the IdM CA.

Use Case: Secure the software supply chain

Description	Make it possible to prove where a container image or build artifact came from, what is inside it, and that only trusted artifacts run. Automation installs the signing and analysis services and sets the cluster policy that rejects unsigned or vulnerable content.
Collection	`redhat.artifact_signer` (Certified, v1.4.4, updated 2026-10-16), `redhat.trusted_profile_analyzer` (Certified, v3.1.1, updated 2026-10-13), `infra.rhacs_configuration` (Validated, v2.0.1, updated 2026-07-16)
Key content	• `redhat.artifact_signer.tas_single_node` — Configure Red Hat Trusted Artifact Signer (RHTAS) on a single managed node. • `redhat.trusted_profile_analyzer.tpa_single_node` — Configure Red Hat Trusted Profile Analyzer (RHTPA) on a single managed node. • `infra.rhacs_configuration.rhacs_signature` — Manage RHACS integration with Cosign signatures • `infra.rhacs_configuration.rhacs_policy` — Manage security policies • `infra.rhacs_configuration.rhacs_image_integration` — Manage image vulnerability scanner and registry integration

Notes	• The single-node roles suit evaluation and small environments; plan separately for production availability. • Continue with Configure RHACS as code for the full policy and integration set. • Use Retrieve secrets from external vaults for registry and signing credentials.

Use Case: Configure RHACS as code

Description	Keep the Kubernetes security policy for all clusters in one reviewed place. Policies, notifiers, authentication, report schedules and compliance schedules of Red Hat Advanced Cluster Security for Kubernetes are defined as variables and applied by Automation Platform, so every central and secured cluster behaves the same.
Collection	`infra.rhacs_configuration` (Validated, v2.0.1, updated 2026-07-16), `infra.automation_development_office` (Validated, v2.0.0, updated 2026-10-06)
Key content	• `infra.rhacs_configuration.rhacs_policy` — Manage security policies • `infra.rhacs_configuration.rhacs_policy_notifier` — Associate notifiers to policies • `infra.rhacs_configuration.rhacs_notifier_integration` — Manage notification methods • `infra.rhacs_configuration.rhacs_auth_provider` — Manage authentication providers • `infra.rhacs_configuration.rhacs_report_schedule` — Manage vulnerability reporting schedules • `infra.rhacs_configuration.rhacs_compliance_schedule` — Manage compliance schedule configurations
Notes	• The validated roles `infra.automation_development_office.acs_upload_policies` and `infra.automation_development_office.acs_report` apply policies and generate vulnerability workload reports on top of the collection. • Policies set to enforce can block deployments. Introduce them in inform mode first. • Related: Secure the software supply chain.

Use Case: Respond to security events with Event-Driven Ansible

Description	Act on a security event while it is still relevant. Event-Driven Ansible listens to sources such as SIEM webhooks, message queues, syslog and ticketing systems, matches events against rules, and starts the right job template in Automation Platform with the event data as input.
Collection	`ansible.eda` (Certified, v2.13.0, updated 2026-07-07), `cyberark.pas` (Certified, v1.0.40, updated 2026-04-28), `servicenow.itsm` (Certified, v2.16.0, updated 2026-08-24), `redhat.insights_eda` (Certified, v1.2.6, updated 2026-08-14), `ansible.controller` (Certified, v4.8.11, updated 2026-09-30)
Key content	• `ansible.eda.webhook` — Receive events via a webhook. • `ansible.eda.kafka` — Receive events via a kafka topic. • `ansible.eda.rulebook_activation` — Manage rulebook activations in the EDA Controller • `cyberark.pas.syslog` — • `servicenow.itsm.records` — Event Driven Ansible source for ServiceNow records. • `redhat.insights_eda.insights` — Receive Red Hat Insights events.
Notes	• Start with notification and enrichment actions, then add containment once false positives are measured. • Typical actions: Contain threats from EDR detections, Enrich SIEM investigations and automate response and Rotate privileged credentials. • Use Retrieve secrets from external vaults for the credentials that rulebooks use to call back into the platform.

Use Case: Secure web and private access with Zscaler

Description	Manage cloud-delivered web security and zero trust access from the same pipeline as other infrastructure. URL filtering and cloud firewall rules in Zscaler Internet Access (ZIA) and application segments and access policies in Zscaler Private Access (ZPA) are defined in Git, reviewed, and applied with Automation Platform.
Collection	`zscaler.ziacloud` (Certified, v2.2.4, updated 2026-06-02), `zscaler.zpacloud` (Certified, v2.2.12, updated 2026-08-27)
Key content	• `zscaler.ziacloud.zia_url_categories` — Manages custom URL categories. • `zscaler.ziacloud.zia_url_filtering_rules` — Adds a new URL Filtering rule. • `zscaler.ziacloud.zia_cloud_firewall_rule` — Firewall Filtering policy rule. • `zscaler.ziacloud.zia_activation_status` — Activates the saved configuration changes. • `zscaler.zpacloud.zpa_application_segment` — Create an application segment in the ZPA Cloud. • `zscaler.zpacloud.zpa_segment_group` — Create a Segment Group • `zscaler.zpacloud.zpa_policy_access_rule` — Create a Policy Access Rule
Notes	• Zscaler policy order matters. Keep rule order explicit in the variables. • For on-premises and data-center firewalls see Manage firewall policy across vendors. • ZIA also has IPS and DLP modules; see Manage IDS/IPS and threat-prevention rules.

Product use cases

Grouped from the modules of each certified or validated collection. Key content lists the components each use case supports, with the modules that manage them (create, update, delete) and query them (_info).

Check Point Gaia `check_point.gaia`

Certified Check Point · version 7.0.0 · updated 2025-02-06 · 114 modules → 10 use cases

Use Case: Configure network interfaces

Description	Configure physical, VLAN, bond, bridge, alias and loopback interfaces, and query interface state.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**Physical interface** `cp_gaia_physical_interface` **Physical interface info** `cp_gaia_physical_interfaces_facts` **VLAN interfaces** `cp_gaia_vlan_interface`, `cp_gaia_vlan_interface_facts` **Bond interfaces** `cp_gaia_bond_interface`, `cp_gaia_bond_interface_facts` **Bridge interfaces** `cp_gaia_bridge_interface`, `cp_gaia_bridge_interface_facts` **Alias interfaces** `cp_gaia_alias_interface`, `cp_gaia_alias_interface_facts` **Loopback interfaces** `cp_gaia_loopback_interface`, `cp_gaia_loopback_interface_facts` **IPv6 support** `cp_gaia_ipv6`, `cp_gaia_ipv6_facts` **DHCP server** `cp_gaia_dhcp_server`, `cp_gaia_dhcp_server_facts`

Use Case: Configure routing

Description	Configure static routes and view active routes learned by direct, kernel, static, BGP, OSPF, RIP and aggregate routing.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**Static routes** `cp_gaia_static_route`, `cp_gaia_static_route_facts` **Active routes** `cp_gaia_routes_facts` **Aggregate routes** `cp_gaia_routes_aggregate_facts` **BGP routes** `cp_gaia_routes_bgp_facts` **Interface routes** `cp_gaia_routes_direct_facts` **Kernel routes** `cp_gaia_routes_kernel_facts` **OSPF routes** `cp_gaia_routes_ospf_facts` **RIP routes** `cp_gaia_routes_rip_facts` **Static routes (active)** `cp_gaia_routes_static_facts`

Use Case: Manage administrators, roles and authentication

Description	Manage Gaia users, roles, system groups, password policy and expert and GRUB passwords, and external RADIUS and TACACS authentication.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**Users** `cp_gaia_user`, `cp_gaia_user_facts` **Roles** `cp_gaia_role`, `cp_gaia_role_facts` **System groups** `cp_gaia_system_group`, `cp_gaia_system_group_facts` **Password policy** `cp_gaia_password_policy`, `cp_gaia_password_policy_facts` **Expert password** `cp_gaia_expert_password`, `cp_gaia_expert_password_facts` **GRUB password** `cp_gaia_grub_password`, `cp_gaia_grub_password_facts` **RADIUS servers** `cp_gaia_radius_server`, `cp_gaia_radius_server_facts` **TACACS servers** `cp_gaia_tacacs_server`, `cp_gaia_tacacs_server_facts`

Use Case: Harden access to the gateway

Description	Control allowed management clients, SSH server settings and login messages.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**Allowed clients** `cp_gaia_allowed_clients`, `cp_gaia_allowed_clients_facts` **SSH server settings** `cp_gaia_ssh_server_settings`, `cp_gaia_ssh_server_settings_facts` **Banner message** `cp_gaia_banner`, `cp_gaia_banner_facts` **Message of the day** `cp_gaia_message_of_the_day`, `cp_gaia_message_of_the_day_facts` **Hostname on login page** `cp_gaia_hostname_on_login_page`, `cp_gaia_hostname_on_login_page_facts`

Use Case: Configure basic system settings

Description	Set hostname, DNS, NTP, time zone and date, proxy and run the first-time wizard.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)

Key content	**Hostname** `cp_gaia_hostname`, `cp_gaia_hostname_facts` **DNS** `cp_gaia_dns`, `cp_gaia_dns_facts` **NTP** `cp_gaia_ntp`, `cp_gaia_ntp_facts` **Time and date** `cp_gaia_time_and_date`, `cp_gaia_time_and_date_facts` **Time zones** `cp_gaia_timezones_facts` **Proxy** `cp_gaia_proxy`, `cp_gaia_proxy_facts` **First-time wizard** `cp_gaia_initial_setup`

Use Case: Monitor with SNMP and syslog

Description	Configure the SNMP agent, traps, receivers and SNMPv3 users, and local and remote system logging.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**SNMP agent** `cp_gaia_snmp`, `cp_gaia_snmp_facts` **Custom SNMP traps** `cp_gaia_snmp_custom_trap`, `cp_gaia_snmp_custom_trap_facts` **Predefined SNMP traps** `cp_gaia_snmp_pre_defined_traps`, `cp_gaia_snmp_pre_defined_traps_facts` **SNMP trap receivers** `cp_gaia_snmp_trap_receiver`, `cp_gaia_snmp_trap_receiver_facts` **SNMPv3 users** `cp_gaia_snmp_user`, `cp_gaia_snmp_user_facts` **System logging** `cp_gaia_syslog`, `cp_gaia_syslog_facts` **Remote syslog servers** `cp_gaia_remote_syslog`, `cp_gaia_remote_syslog_facts`

Use Case: Schedule jobs and snapshots

Description	Create scheduled jobs with mail notification and scheduled snapshots, and check task status.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**Scheduled jobs** `cp_gaia_scheduled_job`, `cp_gaia_scheduled_job_facts` **Job mail notifications** `cp_gaia_scheduled_job_mail`, `cp_gaia_scheduled_job_mail_facts` **Scheduled snapshots** `cp_gaia_scheduled_snapshot`, `cp_gaia_scheduled_snapshot_facts` **Tasks** `cp_gaia_task_facts`

Use Case: Manage Maestro security groups and virtual systems

Description	Manage Maestro security groups, gateways, ports and sites with pending changes, and virtual gateways, switches and virtual systems.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**Pending changes** `cp_gaia_maestro_changes` **Security group members** `cp_gaia_maestro_gateways`, `cp_gaia_maestro_gateways_facts` **Ports** `cp_gaia_maestro_ports`, `cp_gaia_maestro_ports_facts` **Security groups** `cp_gaia_maestro_security_groups`, `cp_gaia_maestro_security_groups_facts` **Sites** `cp_gaia_maestro_sites`, `cp_gaia_maestro_sites_facts` **Virtual gateways** `cp_gaia_virtual_gateway`, `cp_gaia_virtual_gateway_facts` **Virtual switches** `cp_gaia_virtual_switch`, `cp_gaia_virtual_switch_facts` **Virtual systems** `cp_gaia_virtual_systems_facts` **VSNext state** `cp_gaia_vsnext_state_facts`

Use Case: Install policy and run commands

Description	Install dynamic content layers, simulate packets, run scripts, upload files and reboot the machine.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)
Key content	**Dynamic content** `cp_gaia_dynamic_content` **Dynamic content layer** `cp_gaia_dynamic_content_layer_facts` **Dynamic content layers** `cp_gaia_dynamic_content_layers_facts` **Packet simulation** `cp_gaia_simulate_packet` **Run scripts** `cp_gaia_run_script` **File upload** `cp_gaia_put_file` **Reboot** `cp_gaia_run_reboot`

Use Case: Inspect version, features and diagnostics

Description	Query Gaia version, API versions, features, extended commands, asset details and diagnostics.
Collection	`check_point.gaia` (Certified, Check Point, v7.0.0, updated 2025-02-06)

Key content	**Gaia version** `cp_gaia_version_facts` **API versions** `cp_gaia_api_versions_facts` **Features** `cp_gaia_features_facts` **Extended commands** `cp_gaia_extended_commands_facts` **Asset** `cp_gaia_asset_facts` **Diagnostics** `cp_gaia_diagnostics_facts` **Diagnostics topics** `cp_gaia_diagnostics_topics_facts`

Check Point Management (Security Management API) `check_point.mgmt`

Certified Check Point · version 7.0.1 · updated 2026-09-02 · 440 modules → 22 use cases

Use Case: Control sessions, publishing and change tracking

Description	Open, publish, discard, submit, approve and reject management sessions, lock objects, and review changes, tasks, validations and where objects are used.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Approve session** `cp_mgmt_approve_session` **Discard** `cp_mgmt_discard` **Get attachment** `cp_mgmt_get_attachment` **Lock object** `cp_mgmt_lock_object` **Objects** `cp_mgmt_objects_facts` **Publish** `cp_mgmt_publish` **Put file** `cp_mgmt_put_file` **Reject session** `cp_mgmt_reject_session` **Session** `cp_mgmt_session_facts` **Set session** `cp_mgmt_set_session` **Show API versions** `cp_mgmt_show_api_versions` **Show changes** `cp_mgmt_show_changes` **Show commands** `cp_mgmt_show_commands` **Show last published session** `cp_mgmt_show_last_published_session` **Show place holder** `cp_mgmt_show_place_holder` **Show unused objects** `cp_mgmt_show_unused_objects` **Show validations** `cp_mgmt_show_validations` **Submit session** `cp_mgmt_submit_session` **Task** `cp_mgmt_task_facts` **Unlock object** `cp_mgmt_unlock_object` **Where used** `cp_mgmt_where_used`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage access control layers, rules and policy packages

Description	Create access layers, sections and rules (including batch operations and rulebase export), manage policy packages and settings, and verify and install policy.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Access layer** `cp_mgmt_access_layer`, `cp_mgmt_access_layer_facts` **Access layers (bulk)** `cp_mgmt_access_layers` **Access rules** `cp_mgmt_access_rule`, `cp_mgmt_access_rule_facts` **Access rules (batch)** `cp_mgmt_access_rules` **Access section** `cp_mgmt_access_section` **Add rules batch** `cp_mgmt_add_rules_batch` **Delete rules batch** `cp_mgmt_delete_rules_batch` **Export access rulebase** `cp_mgmt_export_access_rulebase` **Install database** `cp_mgmt_install_database` **Install policy** `cp_mgmt_install_policy` **Package** `cp_mgmt_package`, `cp_mgmt_package_facts` **Set policy settings** `cp_mgmt_set_policy_settings` **Show access section** `cp_mgmt_show_access_section` **Show layer structure** `cp_mgmt_show_layer_structure` **Show policy settings** `cp_mgmt_show_policy_settings` **Verify policy** `cp_mgmt_verify_policy`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage NAT policy

Description	Create NAT rules and sections for address translation.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**NAT rule** `cp_mgmt_nat_rule`, `cp_mgmt_nat_rule_facts` **NAT section** `cp_mgmt_nat_section` **Show NAT section** `cp_mgmt_show_nat_section`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Configure HTTPS inspection

Description	Define HTTPS inspection layers, sections and rules, advanced settings and outbound inspection certificates.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Add outbound inspection certificate** `cp_mgmt_add_outbound_inspection_certificate` **Delete outbound inspection certificate** `cp_mgmt_delete_outbound_inspection_certificate` **HTTPS layer** `cp_mgmt_https_layer`, `cp_mgmt_https_layer_facts` **HTTPS rule** `cp_mgmt_https_rule`, `cp_mgmt_https_rule_facts` **HTTPS section** `cp_mgmt_https_section` **Import outbound inspection certificate** `cp_mgmt_import_outbound_inspection_certificate` **Outbound inspection certificate** `cp_mgmt_outbound_inspection_certificate_facts` **Set HTTPS advanced settings** `cp_mgmt_set_https_advanced_settings` **Set outbound inspection certificate** `cp_mgmt_set_outbound_inspection_certificate` **Show HTTPS advanced settings** `cp_mgmt_show_https_advanced_settings` **Show HTTPS section** `cp_mgmt_show_https_section`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage network objects and groups

Description	Create hosts, networks, address ranges, wildcards, groups, DNS domains, security zones, time objects and tags used in policy.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Address range** `cp_mgmt_address_range`, `cp_mgmt_address_range_facts` **Checkpoint host** `cp_mgmt_checkpoint_host`, `cp_mgmt_checkpoint_host_facts` **DNS domain** `cp_mgmt_dns_domain`, `cp_mgmt_dns_domain_facts` **Dynamic global network object** `cp_mgmt_dynamic_global_network_object`, `cp_mgmt_dynamic_global_network_object_facts` **Dynamic object** `cp_mgmt_dynamic_object`, `cp_mgmt_dynamic_object_facts` **Group** `cp_mgmt_group`, `cp_mgmt_group_facts` **Group with exclusion** `cp_mgmt_group_with_exclusion`, `cp_mgmt_group_with_exclusion_facts` **Host** `cp_mgmt_host`, `cp_mgmt_host_facts` **Hosts (bulk)** `cp_mgmt_hosts` **Interoperable device** `cp_mgmt_interoperable_device`, `cp_mgmt_interoperable_device_facts` **Logical server** `cp_mgmt_logical_server`, `cp_mgmt_logical_server_facts` **Multicast address range** `cp_mgmt_multicast_address_range`, `cp_mgmt_multicast_address_range_facts` **Network** `cp_mgmt_network`, `cp_mgmt_network_facts` **Security zone** `cp_mgmt_security_zone`, `cp_mgmt_security_zone_facts` **Tag** `cp_mgmt_tag`, `cp_mgmt_tag_facts` **Time** `cp_mgmt_time`, `cp_mgmt_time_facts` **Time group** `cp_mgmt_time_group`, `cp_mgmt_time_group_facts` **Wildcard** `cp_mgmt_wildcard`, `cp_mgmt_wildcard_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Integrate data centers and updatable objects

Description	Import data center objects and queries from cloud and virtualization servers, and manage updatable objects and their repository content.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Add data center object** `cp_mgmt_add_data_center_object` **Add data center query** `cp_mgmt_add_data_center_query` **Add updatable object** `cp_mgmt_add_updatable_object` **Data center object** `cp_mgmt_data_center_object_facts` **Data center query** `cp_mgmt_data_center_query_facts` **Delete data center object** `cp_mgmt_delete_data_center_object` **Delete data center query** `cp_mgmt_delete_data_center_query` **Delete updatable object** `cp_mgmt_delete_updatable_object` **Set data center query** `cp_mgmt_set_data_center_query` **Show updatable objects repository content** `cp_mgmt_show_updatable_objects_repository_content` **Updatable object** `cp_mgmt_updatable_object_facts` **Update updatable objects repository content** `cp_mgmt_update_updatable_objects_repository_content`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Define services and resources

Description	Define TCP, UDP, ICMP, RPC, SCTP and other services, service groups, protocol resources and bandwidth limits.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)

Key content	**Limit** `cp_mgmt_limit`, `cp_mgmt_limit_facts` **Resource CIFS** `cp_mgmt_resource_cifs`, `cp_mgmt_resource_cifs_facts` **Resource FTP** `cp_mgmt_resource_ftp`, `cp_mgmt_resource_ftp_facts` **Resource MMS** `cp_mgmt_resource_mms`, `cp_mgmt_resource_mms_facts` **Resource SMTP** `cp_mgmt_resource_smtp`, `cp_mgmt_resource_smtp_facts` **Resource TCP** `cp_mgmt_resource_tcp`, `cp_mgmt_resource_tcp_facts` **Resource URI** `cp_mgmt_resource_uri`, `cp_mgmt_resource_uri_facts` **Resource URI for QoS** `cp_mgmt_resource_uri_for_qos`, `cp_mgmt_resource_uri_for_qos_facts` **Service citrix TCP** `cp_mgmt_service_citrix_tcp`, `cp_mgmt_service_citrix_tcp_facts` **Service compound TCP** `cp_mgmt_service_compound_tcp`, `cp_mgmt_service_compound_tcp_facts` **Service DCE RPC** `cp_mgmt_service_dce_rpc`, `cp_mgmt_service_dce_rpc_facts` **Service group** `cp_mgmt_service_group`, `cp_mgmt_service_group_facts` **Service ICMP** `cp_mgmt_service_icmp`, `cp_mgmt_service_icmp_facts` **Service ICMPv6** `cp_mgmt_service_icmp6`, `cp_mgmt_service_icmp6_facts` **Service other** `cp_mgmt_service_other`, `cp_mgmt_service_other_facts` **Service RPC** `cp_mgmt_service_rpc`, `cp_mgmt_service_rpc_facts` **Service SCTP** `cp_mgmt_service_sctp`, `cp_mgmt_service_sctp_facts` **Service TCP** `cp_mgmt_service_tcp`, `cp_mgmt_service_tcp_facts` **Service UDP** `cp_mgmt_service_udp`, `cp_mgmt_service_udp_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Control applications and URL filtering

Description	Manage application sites, categories and groups, categorization overrides, and Application Control settings and updates.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Application site** `cp_mgmt_application_site`, `cp_mgmt_application_site_facts` **Application site category** `cp_mgmt_application_site_category`, `cp_mgmt_application_site_category_facts` **Application site group** `cp_mgmt_application_site_group`, `cp_mgmt_application_site_group_facts` **Override categorization** `cp_mgmt_override_categorization`, `cp_mgmt_override_categorization_facts` **Run app control update** `cp_mgmt_run_app_control_update` **Set app control advanced settings** `cp_mgmt_set_app_control_advanced_settings` **Set app control update schedule** `cp_mgmt_set_app_control_update_schedule` **Show app control** `cp_mgmt_show_app_control_status` **Show app control advanced settings** `cp_mgmt_show_app_control_advanced_settings` **Show app control update schedule** `cp_mgmt_show_app_control_update_schedule`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Configure threat prevention

Description	Manage threat prevention layers, rules, profiles, exceptions, protections, IPS, anti-malware, threat emulation and extraction, indicators and IOC feeds.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Check network feed** `cp_mgmt_check_network_feed` **Check threat IOC feed** `cp_mgmt_check_threat_ioc_feed` **Exception group** `cp_mgmt_exception_group`, `cp_mgmt_exception_group_facts` **IPS protection extended attribute** `cp_mgmt_ips_protection_extended_attribute_facts` **Network feed** `cp_mgmt_network_feed`, `cp_mgmt_network_feed_facts` **Run IPS update** `cp_mgmt_run_ips_update` **Set anti malware update schedule** `cp_mgmt_set_anti_malware_update_schedule` **Set IPS update schedule** `cp_mgmt_set_ips_update_schedule` **Set threat advanced settings** `cp_mgmt_set_threat_advanced_settings` **Set threat emulation file type** `cp_mgmt_set_threat_emulation_file_type` **Set threat emulation file types** `cp_mgmt_set_threat_emulation_file_types` **Set threat extraction file type** `cp_mgmt_set_threat_extraction_file_type` **Set threat extraction file types** `cp_mgmt_set_threat_extraction_file_types` **Set threat protection category** `cp_mgmt_set_threat_protection_category` **Set threat protection sub category** `cp_mgmt_set_threat_protection_sub_category` **Show anti malware update schedule** `cp_mgmt_show_anti_malware_update_schedule` **Show IPS** `cp_mgmt_show_ips_status` **Show IPS update schedule** `cp_mgmt_show_ips_update_schedule` **Show threat advanced settings** `cp_mgmt_show_threat_advanced_settings` **Threat emulation file type** `cp_mgmt_threat_emulation_file_type_facts` **Threat emulation image** `cp_mgmt_threat_emulation_image_facts` **Threat exception** `cp_mgmt_threat_exception`, `cp_mgmt_threat_exception_facts` **Threat extraction file type** `cp_mgmt_threat_extraction_file_type_facts` **Threat indicator** `cp_mgmt_threat_indicator`, `cp_mgmt_threat_indicator_facts` **Threat layer** `cp_mgmt_threat_layer`, `cp_mgmt_threat_layer_facts` **Threat layers** `cp_mgmt_threat_layers` **Threat profile** `cp_mgmt_threat_profile`, `cp_mgmt_threat_profile_facts` **Threat protection category** `cp_mgmt_threat_protection_category_facts` **Threat protection override** `cp_mgmt_threat_protection_override` **Threat protection sub category** `cp_mgmt_threat_protection_sub_category_facts` **Threat rule** `cp_mgmt_threat_rule`, `cp_mgmt_threat_rule_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Prevent data loss and manage content awareness

Description	Define DLP data types and groups, and configure Content Awareness settings.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)

Key content	**Data type compound group** `cp_mgmt_data_type_compound_group`, `cp_mgmt_data_type_compound_group_facts` **Data type file attributes** `cp_mgmt_data_type_file_attributes`, `cp_mgmt_data_type_file_attributes_facts` **Data type file group** `cp_mgmt_data_type_file_group_facts` **Data type group** `cp_mgmt_data_type_group`, `cp_mgmt_data_type_group_facts` **Data type keywords** `cp_mgmt_data_type_keywords`, `cp_mgmt_data_type_keywords_facts` **Data type patterns** `cp_mgmt_data_type_patterns`, `cp_mgmt_data_type_patterns_facts` **Data type traditional group** `cp_mgmt_data_type_traditional_group`, `cp_mgmt_data_type_traditional_group_facts` **Data type weighted keywords** `cp_mgmt_data_type_weighted_keywords`, `cp_mgmt_data_type_weighted_keywords_facts` **DLP next data type** `cp_mgmt_dlp_next_data_type`, `cp_mgmt_dlp_next_data_type_facts` **Set content awareness advanced settings** `cp_mgmt_set_content_awareness_advanced_settings` **Show content awareness advanced settings** `cp_mgmt_show_content_awareness_advanced_settings` **Show DLP next data types repository content** `cp_mgmt_show_dlp_next_data_types_repository_content`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Configure VPN communities and remote access

Description	Create meshed, star and remote access VPN communities, key exchange settings, Mobile Access rules and profiles, and SecuRemote DNS.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Mobile access profile rule** `cp_mgmt_mobile_access_profile_rule`, `cp_mgmt_mobile_access_profile_rule_facts` **Mobile access profile section** `cp_mgmt_mobile_access_profile_section` **Mobile access rule** `cp_mgmt_mobile_access_rule`, `cp_mgmt_mobile_access_rule_facts` **Mobile access section** `cp_mgmt_mobile_access_section` **Mobile profile** `cp_mgmt_mobile_profile`, `cp_mgmt_mobile_profile_facts` **Multiple key exchanges** `cp_mgmt_multiple_key_exchanges`, `cp_mgmt_multiple_key_exchanges_facts` **Passcode profile** `cp_mgmt_passcode_profile`, `cp_mgmt_passcode_profile_facts` **Securemote DNS server** `cp_mgmt_securemote_dns_server`, `cp_mgmt_securemote_dns_server_facts` **Set VPN community remote access** `cp_mgmt_set_vpn_community_remote_access` **Show mobile access profile section** `cp_mgmt_show_mobile_access_profile_section` **Show mobile access section** `cp_mgmt_show_mobile_access_section` **VPN community meshed** `cp_mgmt_vpn_community_meshed`, `cp_mgmt_vpn_community_meshed_facts` **VPN community remote access** `cp_mgmt_vpn_community_remote_access_facts` **VPN community star** `cp_mgmt_vpn_community_star`, `cp_mgmt_vpn_community_star_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage gateways, clusters and high availability

Description	Define simple gateways and clusters, read interfaces and platform data, establish and test trust (SIC), and manage HA state and synchronization.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Abort get interfaces** `cp_mgmt_abort_get_interfaces` **Cluster members** `cp_mgmt_cluster_members_facts` **Get interfaces** `cp_mgmt_get_interfaces` **Get platform** `cp_mgmt_get_platform` **HA full sync** `cp_mgmt_ha_full_sync` **Interface** `cp_mgmt_interface`, `cp_mgmt_interface_facts` **Network probe** `cp_mgmt_network_probe`, `cp_mgmt_network_probe_facts` **Reset SIC** `cp_mgmt_reset_sic` **Set gateway global use** `cp_mgmt_set_gateway_global_use` **Set HA state** `cp_mgmt_set_ha_state` **Set trust** `cp_mgmt_set_trust` **Show gateway capabilities** `cp_mgmt_show_gateway_capabilities` **Show gateway global use** `cp_mgmt_show_gateway_global_use` **Show gateways and servers** `cp_mgmt_show_gateways_and_servers` **Show HA** `cp_mgmt_show_ha_status` **Show HA state** `cp_mgmt_show_ha_state` **Show servers and processes** `cp_mgmt_show_servers_and_processes` **Simple cluster** `cp_mgmt_simple_cluster`, `cp_mgmt_simple_cluster_facts` **Simple gateway** `cp_mgmt_simple_gateway`, `cp_mgmt_simple_gateway_facts` **Test SIC** `cp_mgmt_test_sic_status` **Test trust** `cp_mgmt_test_trust`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage VSX and large-scale (LSM) gateways

Description	Provision VSX objects and run VSX operations, and manage LSM gateways, clusters and profiles, provisioning profiles and satellites.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)

Key content	**Def setting** `cp_mgmt_def_setting`, `cp_mgmt_def_setting_facts` **Install LSM policy** `cp_mgmt_install_lsm_policy` **Install LSM settings** `cp_mgmt_install_lsm_settings` **LSM cluster** `cp_mgmt_lsm_cluster`, `cp_mgmt_lsm_cluster_facts` **LSM cluster profile** `cp_mgmt_lsm_cluster_profile_facts` **LSM gateway** `cp_mgmt_lsm_gateway`, `cp_mgmt_lsm_gateway_facts` **LSM gateway profile** `cp_mgmt_lsm_gateway_profile_facts` **LSM run script** `cp_mgmt_lsm_run_script` **LSV profile** `cp_mgmt_lsv_profile`, `cp_mgmt_lsv_profile_facts` **Provisioning profile** `cp_mgmt_provisioning_profile_facts` **Update provisioned satellites** `cp_mgmt_update_provisioned_satellites` **VSX provisioning tool** `cp_mgmt_vsx_provisioning_tool` **VSX run operation** `cp_mgmt_vsx_run_operation`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Install and manage software packages and scripts

Description	Upload packages to the central repository, prepare, verify, install and uninstall software on targets, and run or store scripts.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Add repository package** `cp_mgmt_add_repository_package` **Delete repository package** `cp_mgmt_delete_repository_package` **Install software package** `cp_mgmt_install_software_package` **Prepare software package** `cp_mgmt_prepare_software_package` **Repository package** `cp_mgmt_repository_package_facts` **Repository script** `cp_mgmt_repository_script`, `cp_mgmt_repository_script_facts` **Run script** `cp_mgmt_run_script` **Show software package details** `cp_mgmt_show_software_package_details` **Show software packages per targets** `cp_mgmt_show_software_packages_per_targets` **Uninstall software package** `cp_mgmt_uninstall_software_package` **Verify software package** `cp_mgmt_verify_software_package`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage licenses

Description	Add and delete central licenses, manage cloud license pools and gateways, distribute and update cloud licenses, and verify management licensing.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Add central license** `cp_mgmt_add_central_license` **Central license** `cp_mgmt_central_license_facts` **Cloud license gateway** `cp_mgmt_cloud_license_gateway_facts` **Cloud license pool** `cp_mgmt_cloud_license_pool_facts` **Delete central license** `cp_mgmt_delete_central_license` **Distribute cloud licenses** `cp_mgmt_distribute_cloud_licenses` **Set cloud license gateway** `cp_mgmt_set_cloud_license_gateway` **Set cloud license pool** `cp_mgmt_set_cloud_license_pool` **Set cloud license scope** `cp_mgmt_set_cloud_license_scope` **Show cloud license scope** `cp_mgmt_show_cloud_license_scope` **Show cloud licenses usage** `cp_mgmt_show_cloud_licenses_usage` **Update cloud license** `cp_mgmt_update_cloud_license` **Verify management license** `cp_mgmt_verify_management_license`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Administer administrators, permissions and login policy

Description	Manage administrators and API keys, permission profiles, password requirements, login restrictions and messages, idle timeouts and API settings.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)

Key content	**Add API key** `cp_mgmt_add_api_key` **Administrator** `cp_mgmt_administrator`, `cp_mgmt_administrator_facts` **Change password on next login** `cp_mgmt_change_password_on_next_login` **Delete API key** `cp_mgmt_delete_api_key` **Domain permissions profile** `cp_mgmt_domain_permissions_profile`, `cp_mgmt_domain_permissions_profile_facts` **MD permissions profile** `cp_mgmt_md_permissions_profile`, `cp_mgmt_md_permissions_profile_facts` **Set API settings** `cp_mgmt_set_api_settings` **Set Check Point password requirements** `cp_mgmt_set_cp_password_requirements` **Set default administrator settings** `cp_mgmt_set_default_administrator_settings` **Set login message** `cp_mgmt_set_login_message` **Set login restrictions** `cp_mgmt_set_login_restrictions` **Set smart console idle timeout** `cp_mgmt_set_smart_console_idle_timeout` **Show API settings** `cp_mgmt_show_api_settings` **Show Check Point password requirements** `cp_mgmt_show_cp_password_requirements` **Show default administrator settings** `cp_mgmt_show_default_administrator_settings` **Show login message** `cp_mgmt_show_login_message` **Show login restrictions** `cp_mgmt_show_login_restrictions` **Show smart console idle timeout** `cp_mgmt_show_smart_console_idle_timeout` **Unlock administrator** `cp_mgmt_unlock_administrator`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage multi-domain environments and global policy

Description	Create and configure domains, Multi-Domain Servers and global domains, assign global policy, and import or export management data.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Add domain** `cp_mgmt_add_domain` **Assign global assignment** `cp_mgmt_assign_global_assignment` **Delete domain** `cp_mgmt_delete_domain` **Domain** `cp_mgmt_domain_facts` **Export management** `cp_mgmt_export_management` **Global assignment** `cp_mgmt_global_assignment`, `cp_mgmt_global_assignment_facts` **Import management** `cp_mgmt_import_management` **Multi-Domain Servers** `cp_mgmt_mds`, `cp_mgmt_mds_facts` **Set domain** `cp_mgmt_set_domain` **Set global domain** `cp_mgmt_set_global_domain` **Set global properties** `cp_mgmt_set_global_properties` **Show global domain** `cp_mgmt_show_global_domain` **Show global properties** `cp_mgmt_show_global_properties`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Integrate identity providers, users and authentication servers

Description	Manage users, groups and templates, access roles, identity providers and tags, and LDAP, RADIUS, TACACS+, SecurID and IF-MAP servers.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Access role** `cp_mgmt_access_role`, `cp_mgmt_access_role_facts` **Delete infinity IdP** `cp_mgmt_delete_infinity_idp` **Delete infinity IdP object** `cp_mgmt_delete_infinity_idp_object` **Identity provider** `cp_mgmt_identity_provider`, `cp_mgmt_identity_provider_facts` **Identity tag** `cp_mgmt_identity_tag`, `cp_mgmt_identity_tag_facts` **IdP administrator group** `cp_mgmt_idp_administrator_group`, `cp_mgmt_idp_administrator_group_facts` **IdP to domain assignment** `cp_mgmt_idp_to_domain_assignment_facts` **If map server** `cp_mgmt_if_map_server`, `cp_mgmt_if_map_server_facts` **Infinity IdP** `cp_mgmt_infinity_idp_facts` **Infinity IdP object** `cp_mgmt_infinity_idp_object_facts` **LDAP group** `cp_mgmt_ldap_group`, `cp_mgmt_ldap_group_facts` **RADIUS group** `cp_mgmt_radius_group`, `cp_mgmt_radius_group_facts` **RADIUS server** `cp_mgmt_radius_server`, `cp_mgmt_radius_server_facts` **Securid server** `cp_mgmt_securid_server`, `cp_mgmt_securid_server_facts` **Set IdP default assignment** `cp_mgmt_set_idp_default_assignment` **Set IdP to domain assignment** `cp_mgmt_set_idp_to_domain_assignment` **Show AD content** `cp_mgmt_show_ad_content` **Show Azure AD content** `cp_mgmt_show_azure_ad_content` **Show IdP default assignment** `cp_mgmt_show_idp_default_assignment` **TACACS+ group** `cp_mgmt_tacacs_group`, `cp_mgmt_tacacs_group_facts` **TACACS+ server** `cp_mgmt_tacacs_server`, `cp_mgmt_tacacs_server_facts` **Trusted client** `cp_mgmt_trusted_client`, `cp_mgmt_trusted_client_facts` **User** `cp_mgmt_user`, `cp_mgmt_user_facts` **User group** `cp_mgmt_user_group`, `cp_mgmt_user_group_facts` **User template** `cp_mgmt_user_template`, `cp_mgmt_user_template_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Configure logging, notifications and automation

Description	Configure log exporters, syslog and SMTP servers, query logs, and manage SmartTask automations and triggers.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)

Key content	**Export smart task** `cp_mgmt_export_smart_task` **Import smart task** `cp_mgmt_import_smart_task` **Log exporter** `cp_mgmt_log_exporter`, `cp_mgmt_log_exporter_facts` **Show logs** `cp_mgmt_show_logs` **Smart task** `cp_mgmt_smart_task`, `cp_mgmt_smart_task_facts` **Smart task trigger** `cp_mgmt_smart_task_trigger_facts` **SMTP server** `cp_mgmt_smtp_server`, `cp_mgmt_smtp_server_facts` **Syslog server** `cp_mgmt_syslog_server`, `cp_mgmt_syslog_server_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Assess compliance and best practices

Description	Run compliance scans, manage best practices, regulations, requirements and guidelines, and configure compliance settings.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Best practice** `cp_mgmt_best_practice_facts` **Compliance scan** `cp_mgmt_compliance_scan` **Firewall best practice** `cp_mgmt_firewall_best_practice`, `cp_mgmt_firewall_best_practice_facts` **Guideline** `cp_mgmt_guideline`, `cp_mgmt_guideline_facts` **Guideline cell approvals** `cp_mgmt_guideline_cell_approvals` **Regulation** `cp_mgmt_regulation`, `cp_mgmt_regulation_facts` **Requirement** `cp_mgmt_requirement`, `cp_mgmt_requirement_facts` **Set best practice** `cp_mgmt_set_best_practice` **Set compliance settings** `cp_mgmt_set_compliance_settings` **Show compliance settings** `cp_mgmt_show_compliance_settings` **Show guideline cells** `cp_mgmt_show_guideline_cells`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Manage certificates and trusted CAs

Description	Manage trusted CA certificates, internal and subordinate CAs, OPSEC trusted CAs and server certificate renewal.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Add custom trusted CA certificate** `cp_mgmt_add_custom_trusted_ca_certificate` **Check Point trusted CA certificate** `cp_mgmt_cp_trusted_ca_certificate_facts` **Custom trusted CA certificate** `cp_mgmt_custom_trusted_ca_certificate_facts` **Delete custom trusted CA certificate** `cp_mgmt_delete_custom_trusted_ca_certificate` **External trusted CA** `cp_mgmt_external_trusted_ca`, `cp_mgmt_external_trusted_ca_facts` **Opsec trusted CA** `cp_mgmt_opsec_trusted_ca`, `cp_mgmt_opsec_trusted_ca_facts` **Renew scaled sharing server certificate** `cp_mgmt_renew_scaled_sharing_server_certificate` **Set Check Point trusted CA certificate** `cp_mgmt_set_cp_trusted_ca_certificate` **Set internal trusted CA** `cp_mgmt_set_internal_trusted_ca` **Show internal trusted CA** `cp_mgmt_show_internal_trusted_ca` **Subordinate CA** `cp_mgmt_subordinate_ca`, `cp_mgmt_subordinate_ca_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Use Case: Connect cloud services and telecom objects

Description	Connect to and configure Check Point cloud services, test AI agent security API keys, and define VoIP domain objects, GSN handover groups and access point names.
Collection	`check_point.mgmt` (Certified, Check Point, v7.0.1, updated 2026-09-02)
Key content	**Access point name** `cp_mgmt_access_point_name`, `cp_mgmt_access_point_name_facts` **Connect cloud services** `cp_mgmt_connect_cloud_services` **Disconnect cloud services** `cp_mgmt_disconnect_cloud_services` **GSN handover group** `cp_mgmt_gsn_handover_group`, `cp_mgmt_gsn_handover_group_facts` **Set cloud services** `cp_mgmt_set_cloud_services` **Show cloud services** `cp_mgmt_show_cloud_services` **Test AI agent security API key** `cp_mgmt_test_ai_agent_security_api_key` **Voip domain H.323 gatekeeper** `cp_mgmt_voip_domain_h323_gatekeeper`, `cp_mgmt_voip_domain_h323_gatekeeper_facts` **Voip domain H.323 gateway** `cp_mgmt_voip_domain_h323_gateway`, `cp_mgmt_voip_domain_h323_gateway_facts` **Voip domain MGCP call agent** `cp_mgmt_voip_domain_mgcp_call_agent`, `cp_mgmt_voip_domain_mgcp_call_agent_facts` **Voip domain SCCP call manager** `cp_mgmt_voip_domain_sccp_call_manager`, `cp_mgmt_voip_domain_sccp_call_manager_facts` **Voip domain SIP proxy** `cp_mgmt_voip_domain_sip_proxy`, `cp_mgmt_voip_domain_sip_proxy_facts`
Notes	• Modules named after a resource (for example host, access_rule) support create, update, delete and info; verb-named modules (set_, show_, add_, delete_) wrap single management API commands.

Cisco ASA `cisco.asa`

Certified Cisco · version 6.1.0 · updated 2025-01-17 · 7 modules → 2 use cases

Use Case: Manage Cisco ASA firewall policy and objects

Description	Configure access lists, objects and object groups on Cisco ASA devices.
Collection	`cisco.asa` (Certified, Cisco, v6.1.0, updated 2025-01-17)
Key content	**Access lists** `asa_acls` **Objects** `asa_objects` **Object groups** `asa_ogs`

Use Case: Configure and administer Cisco ASA devices

Description	Run commands, manage configuration sections and banners, and collect facts from ASA devices.
Collection	`cisco.asa` (Certified, Cisco, v6.1.0, updated 2025-01-17)
Key content	**Configuration sections** `asa_config` **Banners** `asa_banner` **Commands** `asa_command` **Facts** `asa_facts`

Cisco Identity Services Engine (ISE) `cisco.ise`

Certified Cisco · version 3.3.0 · updated 2026-10-16 · 252 modules → 15 use cases

Use Case: Onboard network devices and device groups

Description	Create and update network devices and network device groups in ISE and read their configuration.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**Network device** `network_device`, `network_device_info` **Network device group** `network_device_group`, `network_device_group_info` **Network Device playbook** playbook `networkdevice` **Network Device (information playbook)** playbook `networkdevice_info` **Network Device Group playbook** playbook `networkdevicegroup` **Network Device Group (information playbook)** playbook `networkdevicegroup_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Connect identity sources and manage internal users

Description	Join ISE to Active Directory, LDAP, REST ID and external RADIUS or Duo identity sources, and manage internal users, identity groups, certificate authentication profiles and identity store sequences.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)

Key content	**Active directories** `active_directories_info` **Active directory** `active_directory`, `active_directory_info` **Active directory add groups** `active_directory_add_groups` **Active directory groups by domain** `active_directory_groups_by_domain_info` **Active directory join domain** `active_directory_join_domain` **Active directory leave domain** `active_directory_leave_domain` **AD groups** `ad_groups_info` **Admin user** `admin_user_info` **AD resource reservations** `adresourcereservation_info` **AD resource reservations** `adresourcereservation_` **Adresourcereservation name** `adresourcereservation_name_info` **Certificate profile** `certificate_profile`, `certificate_profile_info` **Duo identity sync** `duo_identity_sync`, `duo_identity_sync_info`, `duo_identity_sync_status` **Duo identity sync cancel** `duo_identity_sync_cancel_info` **Duo identitysync sync** `duo_identitysync_sync_info` **Duo MFA** `duo_mfa`, `duo_mfa_info` **Duo MFA testconnection** `duo_mfa_testconnection` **Duo mfainfo** `duo_mfainfo_info` **External RADIUS server** `external_radius_server`, `external_radius_server_info` **Identitygroup** `identitygroup`, `identitygroup_info` **Identity store sequences** `idstoresequence`, `idstoresequence_info` **Internal user** `internal_user`, `internal_user_info` **LDAP** `ldap`, `ldap_info` **REST ID stores** `restid_store`, `restid_store_info` **Restidstorepredefinedregex fetch SAN predefinedregexs** `restidstorepredefinedregex_fetch_san_predefinedregexs_info` **Restidstorepredefinedregex fetch SNF predefinedregexs** `restidstorepredefinedregex_fetch_snf_predefinedregexs_info` **Restidstoresettings** `restidstoresettings_info` **Active Directory Configuration playbook** playbook `activedirectory` **Active Directory (information playbook)** playbook `activedirectory_info` **Active Directory Groups (information playbook)** playbook `ad_groups_info` **Admin User (information playbook)** playbook `adminuser_info` **AD Resource Reservation playbook** playbook `adresourcereservation_` **AD Resource Reservation (information playbook)** playbook `adresourcereservation_info` **AD Resource Reservation by Name (information playbook)** playbook `adresourcereservation_name_info` **Certificate Profile playbook** playbook `certificateprofile` **Certificate Profile (information playbook)** playbook `certificateprofile_info` **Duo Identity Sync playbook** playbook `duo_identity_sync` **Cancel Duo Identity Sync playbook** playbook `duo_identity_sync_cancel_info` **Duo Identity Sync (information playbook)** playbook `duo_identity_sync_info` **Duo Identity Sync Status (information playbook)** playbook `duo_identity_sync_status` **Duo IdentitySync Sync (information playbook)** playbook `duo_identitysync_sync_info` **Duo MFA Configuration playbook** playbook `duo_mfa` **Duo MFA (information playbook)** playbook `duo_mfa_info` **Test Duo MFA Connection playbook** playbook `duo_mfa_testconnection` **Duo MFA Info (information playbook)** playbook `duo_mfainfo_info` **External RADIUS Server (information playbook)** playbook `externalradiusserver_info` **Identity Group playbook** playbook `identitygroup` **Identity Group (information playbook)** playbook `identitygroup_info` **Identity Store Sequence playbook** playbook `idstoresequence` **Identity Store Sequence (information playbook)** playbook `idstoresequence_info` **Internal User playbook** playbook `internaluser` **Internal User (information playbook)** playbook `internaluser_info` **LDAP (information playbook)** playbook `ldap_info` **REST ID Store playbook** playbook `restidstore` **REST ID Store (information playbook)** playbook `restidstore_info` **REST ID Store Predefined Regex SAN (information playbook)** playbook `restidstorepredefinedregex_fetch_san_predefinedregexs_info` **REST ID Store Predefined Regex SNF (information playbook)** playbook `restidstorepredefinedregex_fetch_snf_predefinedregexs_info` **REST ID Store Settings (information playbook)** playbook `restidstoresettings_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Configure TACACS+ device administration

Description	Manage TACACS+ command sets, profiles, external servers and server sequences used for network device administration.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**TACACS command sets** `tacacs_command_sets`, `tacacs_command_sets_info` **TACACS external servers** `tacacs_external_servers`, `tacacs_external_servers_info` **TACACS profile** `tacacs_profile`, `tacacs_profile_info` **TACACS server sequence** `tacacs_server_sequence`, `tacacs_server_sequence_info` **TACACS Command Sets playbook** playbook `tacacscommandsets` **TACACS Command Sets (information playbook)** playbook `tacacscommandsets_info` **TACACS External Servers (information playbook)** playbook `tacacsexternalservers_info` **TACACS Profile playbook** playbook `tacacsprofile` **TACACS Profile (information playbook)** playbook `tacacsprofile_info` **TACACS Server Sequence playbook** playbook `tacacsserversequence` **TACACS Server Sequence (information playbook)** playbook `tacacsserversequence_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Define authentication protocols and authorization results

Description	Manage allowed protocols, authorization profiles, downloadable ACLs, RADIUS server sequences and filter policies that policy rules return to network devices.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**Allowed protocols** `allowed_protocols`, `allowed_protocols_info` **Authorization profile** `authorization_profile`, `authorization_profile_info` **Downloadable ACL** `downloadable_acl`, `downloadable_acl_info` **Filter policy** `filter_policy`, `filter_policy_info` **NSP profiles** `nspprofile_info` **RADIUS server sequence** `radius_server_sequence`, `radius_server_sequence_info` **Allowed Protocols playbook** playbook `allowedprotocols` **Allowed Protocols (information playbook)** playbook `allowedprotocols_info` **Authorization Profile playbook** playbook `authorizationprofile` **Authorization Profile (information playbook)** playbook `authorizationprofile_info` **Downloadable ACL playbook** playbook `downloadableacl` **Downloadable ACL (information playbook)** playbook `downloadableacl_info` **Filter Policy playbook** playbook `filterpolicy` **Filter Policy (information playbook)** playbook `filterpolicy_info` **NSP Profile (information playbook)** playbook `nspprofile_info` **RADIUS Server Sequence playbook** playbook `radiusserversequence` **RADIUS Server Sequence (information playbook)** playbook `radiusserversequence_info`

Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Manage endpoints, profiling and adaptive network control

Description	Create and update endpoints and endpoint groups, run bulk endpoint tasks, apply or clear ANC policies and manage profiler profiles and custom attributes.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**ANC endpoint** `anc_endpoint_info` **ANC endpoint apply** `anc_endpoint_apply` **ANC endpoint clear** `anc_endpoint_clear` **ANC policy** `anc_policy`, `anc_policy_info` **Custom attributes** `custom_attributes`, `custom_attributes_info` **Custom attributes rename** `custom_attributes_rename` **Endpoints** `endpoint`, `endpoint_info` **Endpointgroup** `endpointgroup`, `endpointgroup_info` **Endpoints (bulk operations)** `endpoints`, `endpoints_info` **Endpoints bulk** `endpoints_bulk`, `endpoints_bulk_info` **Endpoints device type** `endpoints_device_type_info` **Endpoints task** `endpoints_task` **Profiler profile** `profiler_profile_info` **Clear ANC Endpoint playbook** playbook `ancendpoint_clear` **ANC Endpoint (information playbook)** playbook `ancendpoint_info` **ANC Policy playbook** playbook `ancpolicy` **ANC Policy (information playbook)** playbook `ancpolicy_info` **Custom Attributes playbook** playbook `custom_attributes` **Custom Attributes (information playbook)** playbook `custom_attributes_info` **Rename Custom Attribute playbook** playbook `custom_attributes_rename` **Endpoint (information playbook)** playbook `endpoint_info` **Endpoint Group playbook** playbook `endpointgroup` **Endpoint Group (information playbook)** playbook `endpointgroup_info` **Endpoints playbook** playbook `endpoints` **Bulk Endpoints Status (information playbook)** playbook `endpoints_bulk_info` **Endpoints Device Type (information playbook)** playbook `endpoints_device_type_info` **Endpoints (information playbook)** playbook `endpoints_info` **Endpoints Task playbook** playbook `endpoints_task` **Profiler Profile (information playbook)** playbook `profilerprofile_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Manage TrustSec security groups and policy matrix

Description	Manage security group tags, security group ACLs, SGT mappings, the egress policy matrix, virtual networks and NBAR applications.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**TrustSec environment data** `ctsenvdata` **TrustSec matrix** `ctsmatrix` **Egress matrix cell** `egress_matrix_cell`, `egress_matrix_cell_info` **Security group ACLs** `sgacl`, `sgacl_info` **Security group ACLs (bulk)** `sgacls` **SGT mappings** `sgmapping`, `sgmapping_info` **SGT mapping groups** `sgmappinggroup`, `sgmappinggroup_info` **Security group tags (SGT)** `sgt`, `sgt_info` **SGT to VN and VLAN mapping** `sgtvnvlan`, `sgtvnvlan_info` **Trustsec NBAR app** `trustsec_nbar_app`, `trustsec_nbar_app_info` **Trustsec VN** `trustsec_vn`, `trustsec_vn_info` **Trustsec VN bulk create** `trustsec_vn_bulk_create` **Trustsec VN bulk delete** `trustsec_vn_bulk_delete` **Trustsec VN bulk update** `trustsec_vn_bulk_update` **TrustSec Environment Data playbook** playbook `ctsenvdata` **TrustSec Matrix playbook** playbook `ctsmatrix` **Egress Matrix Cell (information playbook)** playbook `egressmatrixcell_info` **Security Group ACL playbook** playbook `sgacl` **Security Group ACL (information playbook)** playbook `sgacl_info` **Security Group ACLs (Bulk) playbook** playbook `sgacls` **Security Group Mapping playbook** playbook `sgmapping` **Security Group Mapping (information playbook)** playbook `sgmapping_info` **Security Group Mapping Group playbook** playbook `sgmappinggroup` **Security Group Mapping Group (information playbook)** playbook `sgmappinggroup_info` **Security Group Tag (SGT) playbook** playbook `sgt` **Security Group Tag (SGT) (information playbook)** playbook `sgt_info` **SGT VN VLAN Mapping playbook** playbook `sgtvnvlan` **SGT VN VLAN Mapping (information playbook)** playbook `sgtvnvlan_info` **TrustSec NBAR Application playbook** playbook `trustsec_nbar_app` **TrustSec NBAR Application (information playbook)** playbook `trustsec_nbar_app_info` **TrustSec NBAR Apps on ISE playbook** playbook `trustsec_nbarapp` **ISE TrustSec Virtual Network Playbook playbook** playbook `trustsec_vn` **Bulk Create TrustSec Virtual Networks playbook** playbook `trustsec_vn_bulk_create` **TrustSec Virtual Network (information playbook)** playbook `trustsec_vn_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Propagate TrustSec bindings with SXP

Description	Configure SXP connections, local bindings and SXP VPNs that distribute IP-to-SGT mappings.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**SXP connections** `sxp_connections`, `sxp_connections_info` **SXP local bindings** `sxp_local_bindings`, `sxp_local_bindings_info` **SXP vpns** `sxp_vpns`, `sxp_vpns_info` **SXP Connections playbook** playbook `sxpconnections` **SXP Connections (information playbook)** playbook `sxpconnections_info` **SXP Local Bindings playbook** playbook `sxplocalbindings` **SXP Local Bindings (information playbook)** playbook `sxplocalbindings_info` **SXP VPNs playbook** playbook `sxpvpns` **SXP VPNs (information playbook)** playbook `sxpvpns_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Run guest, BYOD and self-service portals

Description	Configure guest, sponsor, hotspot, self-registration, BYOD and My Devices portals along with guest types, sponsor groups, guest users, SSIDs, SMTP and SMS settings.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**BYOD portal** `byod_portal`, `byod_portal_info` **Guest location** `guest_location_info` **Guest SSID** `guest_ssid`, `guest_ssid_info` **Guest type** `guest_type`, `guest_type_info` **Guest user** `guest_user`, `guest_user_info` **Guest SMTP notification settings** `guestsmtpnotificationsettings`, `guestsmtpnotificationsettings_info` **Hotspot portal** `hotspot_portal`, `hotspot_portal_info` **My device portal** `my_device_portal`, `my_device_portal_info` **Portals** `portal_info` **Portal global setting** `portal_global_setting_info` **Portal theme** `portal_theme`, `portal_theme_info` **Selfregportal** `selfregportal`, `selfregportal_info` **SMS providers** `sms_provider_info` **Sponsor group** `sponsor_group`, `sponsor_group_info` **Sponsor group member** `sponsor_group_member_info` **Sponsor portal** `sponsor_portal`, `sponsor_portal_info` **Sponsored guest portal** `sponsored_guest_portal`, `sponsored_guest_portal_info` **BYOD Portal playbook** playbook `byodportal` **BYOD Portal (information playbook)** playbook `byodportal_info` **Guest Location (information playbook)** playbook `guestlocation_info` **Guest SMTP Notification Settings (information playbook)** playbook `guestsmtpnotificationsettings_info` **Guest SSID playbook** playbook `guestssid` **Guest SSID (information playbook)** playbook `guestssid_info` **Guest Type playbook** playbook `guesttype` **Guest Type (information playbook)** playbook `guesttype_info` **Guest User playbook** playbook `guestuser` **Guest User (information playbook)** playbook `guestuser_info` **Hotspot Portal playbook** playbook `hotspotportal` **Hotspot Portal (information playbook)** playbook `hotspotportal_info` **My Device Portal playbook** playbook `mydeviceportal` **My Device Portal (information playbook)** playbook `mydeviceportal_info` **Portal (information playbook)** playbook `portal_info` **Portal Global Setting (information playbook)** playbook `portalglobalsetting_info` **Portal Theme (information playbook)** playbook `portaltheme_info` **Self Registration Portal playbook** playbook `selfregportal` **Self Registration Portal (information playbook)** playbook `selfregportal_info` **SMS Provider (information playbook)** playbook `smsprovider_info` **Sponsored Guest Portal playbook** playbook `sponsoredguestportal` **Sponsored Guest Portal (information playbook)** playbook `sponsoredguestportal_info` **Sponsor Group playbook** playbook `sponsorgroup` **Sponsor Group (information playbook)** playbook `sponsorgroup_info` **Sponsor Group Member (information playbook)** playbook `sponsorgroupmember_info` **Sponsor Portal playbook** playbook `sponsorportal` **Sponsor Portal (information playbook)** playbook `sponsorportal_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Manage certificates and certificate signing requests

Description	Generate and export CSRs, bind signed certificates, import, export and renew system and trusted certificates, issue self-signed certificates and regenerate the ISE root CA.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**Bind signed certificate** `bind_signed_certificate` **Certificate template** `certificate_template_info` **Certificate signing requests (CSR)** `csr_info` **CSR delete** `csr_delete` **CSR export** `csr_export_info` **CSR generate** `csr_generate` **CSR generate intermediate CA** `csr_generate_intermediate_ca` **ISE root CA regeneration** `ise_root_ca_regenerate` **Renew certificate** `renew_certificate` **Selfsigned certificate generate** `selfsigned_certificate_generate` **System certificate** `system_certificate`, `system_certificate_info` **System certificate export** `system_certificate_export_info` **System certificate import** `system_certificate_import` **Trusted certificate** `trusted_certificate`, `trusted_certificate_info` **Trusted certificate export** `trusted_certificate_export_info` **Trusted certificate import** `trusted_certificate_import` **Bind Signed Certificate playbook** playbook `bind_signed_certificate` **Certificate management playbook** playbook `certificate_management` **Certificates on ISE playbook** playbook `certificates` **Certificate Template (information playbook)** playbook `certificatetemplate_info` **Export CSR from ISE playbook** playbook `csr_export` **Generate Certificate Signing Request playbook** playbook `csr_generate` **Generate Intermediate CA Certificate Signing Request playbook** playbook `csr_generate_intermediate_ca` **Certificate Signing Request (information playbook)** playbook `csr_info` **Regenerate ISE Root CA playbook** playbook `ise_root_ca_regenerate` **Renew Certificate playbook** playbook `renew_certificate` **Generate Self-Signed Certificate playbook** playbook `selfsigned_certificate_generate` **System Certificate Playbook playbook** playbook `system_certificate` **System Certificate (information playbook)** playbook `system_certificate_info` **System Certificate playbook** playbook `systemcertificate` **Trusted Certificate playbook** playbook `trusted_certificate` **Trusted Certificate (information playbook)** playbook `trusted_certificate_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Deploy and orchestrate ISE nodes and personas

Description	Register nodes, change node roles and personas, promote primary and secondary admin nodes, configure node groups and PAN high availability, and deploy ISE in AWS.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)

Key content	**Nodes** `node_info` **Node deployment** `node_deployment`, `node_deployment_info` **Node deployment sync** `node_deployment_sync` **Node group** `node_group`, `node_group_info` **Node group node** `node_group_node_info` **Node group node create** `node_group_node_create` **Node group node delete** `node_group_node_delete` **Node promotion** `node_promotion` **Node replication status** `node_replication_status_info` **Node secondary to primary** `node_secondary_to_primary` **Node services profiler probe config** `node_services_profiler_probe_config`, `node_services_profiler_probe_config_info` **Node standalone to primary** `node_standalone_to_primary` **Node sync** `node_sync` **PAN high availability** `pan_ha` **Personas check standalone** `personas_check_standalone` **Personas export certs** `personas_export_certs` **Personas promote primary** `personas_promote_primary` **Personas update roles** `personas_update_roles` **ISE services** `service_info` **Sessionservicenode** `sessionservicenode_info` **Replication stop** `stop_replication`, `stop_replication_info` **AWS ISE Deployment Playbook playbook** playbook `aws_deployment` **Node (information playbook)** playbook `node_info` **Node Replication Status (information playbook)** playbook `node_replication_status_info` **Check if Node is Standalone playbook** playbook `personas_check_standalone` **ISE Personas Deployment Playbook playbook** playbook `personas_deployment` **Export Personas Certificates playbook** playbook `personas_export_certs` **Promote Node to Primary playbook** playbook `personas_promote_primary` **Service (information playbook)** playbook `service_info` **Session Service Node (information playbook)** playbook `sessionservicenode_info` **Stop Replication Status (information playbook)** playbook `stop_replication_info` **Cisco ISE deployment in AWS** role `aws_deployment` **Cisco ISE deployment in AWS** role `personas_deployment`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Secure node-to-node traffic with IPsec

Description	Enable, disable and manage IPsec tunnels between ISE nodes and review the IPsec certificates in use.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**IPsec** `ipsec`, `ipsec_info` **IPsec bulk** `ipsec_bulk` **IPsec certificates** `ipsec_certificates_info` **IPsec delete** `ipsec_delete`, `ipsec_delete_info` **IPsec disable** `ipsec_disable`, `ipsec_disable_info` **IPsec enable** `ipsec_enable`, `ipsec_enable_info` **IPsec Configuration playbook** playbook `ipsec` **IPsec Certificates (information playbook)** playbook `ipsec_certificates_info` **IPsec Delete Status (information playbook)** playbook `ipsec_delete_info` **Disable IPsec playbook** playbook `ipsec_disable` **IPsec Disable Status (information playbook)** playbook `ipsec_disable_info` **Enable IPsec playbook** playbook `ipsec_enable` **IPsec Enable Status (information playbook)** playbook `ipsec_enable_info` **IPsec (information playbook)** playbook `ipsec_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Back up, patch and troubleshoot ISE

Description	Schedule and restore configuration backups, manage repositories, install and roll back patches and hotpatches, and collect support bundles and reports.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**Backup cancel** `backup_cancel` **Backup config** `backup_config` **Backup last status** `backup_last_status_info` **Backup restore** `backup_restore` **Backup schedule config** `backup_schedule_config` **Backup schedule config update** `backup_schedule_config_update` **Hotpatches** `hotpatch_info` **Hotpatch install** `hotpatch_install` **Hotpatch rollback** `hotpatch_rollback` **Patches** `patch_info` **Patch install** `patch_install` **Patch rollback** `patch_rollback` **Report configuration** `reportconfig` **Repository** `repository`, `repository_info` **Repository files** `repository_files_info` **Support bundle download** `support_bundle_download` **Support bundle status** `support_bundle_status_info` **Support bundles** `supportbundle` **Cancel Backup Operation playbook** playbook `backup_cancel` **Backup configuration playbook** playbook `backup_create` **Last Backup Status (information playbook)** playbook `backup_last_status_info` **Restore configuration backup playbook** playbook `backup_restore` **Schedule configuration backup playbook** playbook `backup_schedule` **Hotpatch (information playbook)** playbook `hotpatch_info` **Patch (information playbook)** playbook `patch_info` **Report Configuration playbook** playbook `reportconfig` **Repository playbook** playbook `repository` **Repository Files (information playbook)** playbook `repository_files_info` **Repository (information playbook)** playbook `repository_info` **Support Bundle Status (information playbook)** playbook `supportbundlestatus_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Manage ISE licensing

Description	Review licensing registration, Smart licensing and tier state, evaluation licenses and feature-to-tier mappings, and create licensing registrations and tier states.

Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**Licensing connection type** `licensing_connection_type_info` **Licensing eval license** `licensing_eval_license_info` **Licensing feature to tier mapping** `licensing_feature_to_tier_mapping_info` **Licensing registration** `licensing_registration_info` **Licensing registration create** `licensing_registration_create` **Licensing smart state** `licensing_smart_state_info` **Licensing smart state create** `licensing_smart_state_create` **Licensing tier state** `licensing_tier_state_info` **Licensing tier state create** `licensing_tier_state_create` **Licensing Connection Type (information playbook)** playbook `licensing_connection_type_info` **Evaluation License (information playbook)** playbook `licensing_eval_license_info` **Licensing Feature to Tier Mapping (information playbook)** playbook `licensing_feature_to_tier_mapping_info` **Licensing Registration (information playbook)** playbook `licensing_registration_info` **Create Licensing Smart State playbook** playbook `licensing_smart_state_create` **Licensing Smart State (information playbook)** playbook `licensing_smart_state_info` **Create Licensing Tier State playbook** playbook `licensing_tier_state_create` **Licensing Tier State (information playbook)** playbook `licensing_tier_state_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Monitor sessions and authentication status

Description	Query the Monitoring node for active sessions, sessions by MAC address or user name, authentication status, failure reasons, posture and profiler counts, and delete sessions.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**MNT account status** `mnt_account_status_info` **MNT authentication status** `mnt_athentication_status_info` **MNT failure reasons** `mnt_failure_reasons_info` **MNT session active count** `mnt_session_active_count_info` **MNT session active list** `mnt_session_active_list_info` **MNT session by MAC** `mnt_session_by_mac_info` **MNT session by username** `mnt_session_by_username_info` **MNT session delete all** `mnt_session_delete_all` **MNT session posture count** `mnt_session_posture_count_info` **MNT session profiler count** `mnt_session_profiler_count_info` **MNT version** `mnt_version_info` **MNT Account Status (information playbook)** playbook `mnt_account_status_info` **MNT Authentication Status (information playbook)** playbook `mnt_athentication_status_info` **MNT Failure Reasons (information playbook)** playbook `mnt_failure_reasons_info` **MNT Active Session Count (information playbook)** playbook `mnt_session_active_count_info` **MNT Active Session List (information playbook)** playbook `mnt_session_active_list_info` **MNT Session By MAC Address (information playbook)** playbook `mnt_session_by_mac_info` **MNT Session By Username (information playbook)** playbook `mnt_session_by_username_info` **Delete All MNT Sessions playbook** playbook `mnt_session_delete_all` **MNT Session Posture Count (information playbook)** playbook `mnt_session_posture_count_info` **MNT Session Profiler Count (information playbook)** playbook `mnt_session_profiler_count_info` **MNT Version (information playbook)** playbook `mnt_version_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

Use Case: Integrate external services and administer system settings

Description	Configure pxGrid Direct connectors and pxGrid nodes, ACI settings, Data Connect, telemetry, proxy and transport gateway settings, and review ISE configuration, reservations and tasks.
Collection	`cisco.ise` (Certified, Cisco, v3.3.0, updated 2026-10-16)
Key content	**ACI settings** `aci_settings_info` **ISE configuration** `configuration`, `configuration_info` **Data Connect** `dataconnect_info` **Dataconnect settings** `dataconnect_settings_info`, `dataconnect_settings_status` **Dataconnect settings password** `dataconnect_settings_password` **Dataconnect settings password expiry** `dataconnect_settings_password_expiry` **Proxy connection settings** `proxy_connection_settings`, `proxy_connection_settings_info` **pxGrid Direct connectors** `px_grid_direct`, `px_grid_direct_info` **PxGrid grid direct dictionary** `px_grid_direct_dictionary_info` **PxGrid grid direct sync** `px_grid_direct_sync`, `px_grid_direct_sync_info` **PxGrid grid direct test connector** `px_grid_direct_test_connector` **PxGrid grid node** `px_grid_node_info` **Reservations** `reservation`, `reservation_info` **Tasks** `tasks_info` **Telemetry** `telemetryinfo_info` **Transport gateway settings** `transport_gateway_settings`, `transport_gateway_settings_info` **ACI Settings (information playbook)** playbook `acisettings_info` **ISE Configuration playbook** playbook `configuration` **ISE Configuration (information playbook)** playbook `configuration_info` **Data Connect (information playbook)** playbook `dataconnect_info` **Data Connect Settings (information playbook)** playbook `dataconnect_settings_info` **Update Data Connect Settings Password Expiry playbook** playbook `dataconnect_settings_password_expiry` **Update Data Connect Settings Status playbook** playbook `dataconnect_settings_status` **Proxy Connection Settings playbook** playbook `proxy_connection_settings` **Proxy Connection Settings (information playbook)** playbook `proxy_connection_settings_info` **pxGrid Direct Configuration playbook** playbook `px_grid_direct` **pxGrid Direct Dictionary (information playbook)** playbook `px_grid_direct_dictionary_info` **pxGrid Direct (information playbook)** playbook `px_grid_direct_info` **pxGrid Direct Sync playbook** playbook `px_grid_direct_sync` **pxGrid Direct Sync (information playbook)** playbook `px_grid_direct_sync_info` **Test pxGrid Direct Connector playbook** playbook `px_grid_direct_test_connector` **pxGrid Node (information playbook)** playbook `pxgridnode_info` **Reservation playbook** playbook `reservation` **Reservation (information playbook)** playbook `reservation_info` **Tasks (information playbook)** playbook `tasks_info` **Telemetry (information playbook)** playbook `telemetryinfo_info` **Transport Gateway Settings playbook** playbook `transport_gateway_settings` **Transport Gateway Settings (information playbook)** playbook `transport_gateway_settings_info`
Notes	• Most resources are available both as modules and as playbook entries; the playbooks wrap the modules for ready-to-run use.

CrowdStrike Falcon `crowdstrike.falcon`

Certified CrowdStrike · version 4.14.1 · updated 2026-10-08 · 27 modules → 4 use cases

Use Case: Install and configure the Falcon sensor

Description	Download, install, configure and uninstall the Falcon sensor and manage sensor update policies and builds.
Collection	`crowdstrike.falcon` (Certified, CrowdStrike, v4.14.1, updated 2026-10-08)
Key content	**Sensor installation** role `falcon_install` **Sensor configuration** role `falcon_configure` **Sensor removal** role `falcon_uninstall` **Sensor settings** `falconctl`, `falconctl_info` **Sensor installer download** `sensor_download`, `sensor_download_info` **Sensor update policies** `sensor_update_policy`, `sensor_update_policy_info` **Sensor builds** `sensor_update_builds_info` **Supported kernels** `kernel_support_info` **Customer ID** `cid_info` **Maintenance token** lookup `maintenance_token`

Use Case: Manage hosts and host groups

Description	Look up hosts, group them, contain or hide them, and query Flight Control child CIDs.
Collection	`crowdstrike.falcon` (Certified, CrowdStrike, v4.14.1, updated 2026-10-08)
Key content	**Hosts** `host_info` **Host groups** `host_group`, `host_group_info` **Network containment** `host_contain` **Host visibility** `host_hide` **Flight Control child CIDs** `fctl_child_cid_info` **Child CID lookup** lookup `fctl_child_cids` **Host ID lookup** lookup `host_ids` **Authentication** `auth`

Use Case: Run Next-Gen SIEM and threat hunting

Description	Manage NG-SIEM correlation rules, data connections and parsers, search repositories, and download hunting and intel rules.
Collection	`crowdstrike.falcon` (Certified, CrowdStrike, v4.14.1, updated 2026-10-08)
Key content	**Correlation rules** `correlation_rule`, `correlation_rule_info` **Data connections** `ngsiem_data_connection`, `ngsiem_data_connection_info` **Data connectors** `ngsiem_data_connector_info` **Parsers** `ngsiem_parser`, `ngsiem_parser_info` **Searches** `ngsiem_search` **Hunting rules** `hunting_rule_download` **Intel rules** `intel_rule_info` **Intel rule downloads** `intel_rule_download` **YARA rules for Red Hat Insights** playbook `redhat_insights_yara`

Use Case: Build inventory and react to Falcon events

Description	Build inventory from Falcon Hosts and Discover and stream Falcon events to Event-Driven Ansible.
Collection	`crowdstrike.falcon` (Certified, CrowdStrike, v4.14.1, updated 2026-10-08)
Key content	**Falcon Hosts inventory** inventory `falcon_hosts` **Falcon Discover inventory** inventory `falcon_discover` **Event Stream source** eda event source `eventstream`

CyberArk Conjur `cyberark.conjur`

Certified CyberArk · version 1.3.14 · updated 2026-08-05 · 0 modules → 1 use cases

Use Case: Retrieve secrets and grant host identity

Description	Fetch credentials from Conjur and grant machine identity to hosts.
Collection	`cyberark.conjur` (Certified, CyberArk, v1.3.14, updated 2026-08-05)
Key content	**Conjur variable lookup** lookup `conjur_variable` **Host identity** role `conjur_host_identity`

CyberArk Identity Security Platform `cyberark.isp`

Certified CyberArk · version 1.0.8 · updated 2026-04-28 · 8 modules → 2 use cases

Use Case: Manage privileged accounts, safes and platforms

Description	Create and update CyberArk accounts, safes, safe members, users, applications and platforms, and authenticate to the Identity Security Platform.
Collection	`cyberark.isp` (Certified, CyberArk, v1.0.8, updated 2026-04-28)
Key content	**Authentication** `cyberark_authentication` **Accounts** `cyberark_account` **Safes** `cyberark_safe` **Safe members** `cyberark_safe_member` **Users** `cyberark_user` **Applications** `cyberark_application` **Platforms** `cyberark_platform`

Use Case: Retrieve credentials at run time

Description	Retrieve credentials from the Secrets Manager Central Credential Provider for use in playbooks.
Collection	`cyberark.isp` (Certified, CyberArk, v1.0.8, updated 2026-04-28)
Key content	**Credentials** `cyberark_credential`

CyberArk Privileged Access Security `cyberark.pas`

Certified CyberArk · version 1.0.40 · updated 2026-04-28 · 4 modules → 2 use cases

Use Case: Manage privileged accounts and credentials

Description	Authenticate, manage accounts and users and retrieve credentials through PAS Web Services and the Central Credential Provider, or install the AIM provider.
Collection	`cyberark.pas` (Certified, CyberArk, v1.0.40, updated 2026-04-28)
Key content	**Authentication** `cyberark_authentication` **Accounts** `cyberark_account` **Users** `cyberark_user` **Credentials** `cyberark_credential` **Credential Provider (AIM)** role `aimprovider`

Use Case: Receive CyberArk events

Description	Receive CyberArk syslog events in Event-Driven Ansible.
Collection	`cyberark.pas` (Certified, CyberArk, v1.0.40, updated 2026-04-28)
Key content	**Syslog event source** eda event source `syslog`

Delinea Privileged Access Service `delinea.pas`

Certified Delinea · version 1.0.4 · updated 2024-09-23 · 0 modules → 1 use cases

Use Case: Install and enrol Delinea agents

Description	Install, enrol, unenrol and remove Delinea audit and monitoring, authentication and privilege elevation, and privileged access services on Linux hosts.
Collection	`delinea.pas` (Certified, Delinea, v1.0.4, updated 2024-09-23)
Key content	**Privileged access services** role `delinea_vault` **Authentication and privilege elevation** role `delinea_auth` **Audit and monitoring** role `delinea_audit`

Entrust Certificate Authority Gateway `entrust.crypto`

Certified Entrust · version 1.0.1 · updated 2023-12-20 · 1 modules → 1 use cases

Use Case: Request and manage certificates from Entrust

Description	Request, get, hold, unhold and revoke SSL/TLS certificates through the CAGW API.
Collection	`entrust.crypto` (Certified, Entrust, v1.0.1, updated 2023-12-20)
Key content	**CAGW certificates** `cagw_certificate` **CAGW certificate role** role `cagw_certificate`

Fortinet FortiGate (via FortiManager) `fortinet.fmgdevice`

Certified Fortinet · version 1.2.0 · updated 2026-08-18 · 1410 modules → 35 use cases

Use Case: Manage firewall policies and traffic shaping

Description	Create IPv4, IPv6, proxy, local-in, multicast, DoS and interface policies, and traffic shapers, shaping policies and profiles on managed FortiGates.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Firewall authentication portals** `fmgd_firewall_authportal` **IPv4 DoS policies** `fmgd_firewall_dospolicy` **IPv6 DoS policies** `fmgd_firewall_dospolicy6` **IPv6 DoS policies - anomaly** `fmgd_firewall_dospolicy6_anomaly` **Global firewall settings** `fmgd_firewall_global` **Identity based routing** `fmgd_firewall_identitybasedroute` **Identity based routing - rule** `fmgd_firewall_identitybasedroute_rule` **IPv4 interface policies** `fmgd_firewall_interfacepolicy` **IPv6 interface policies** `fmgd_firewall_interfacepolicy6` **IPv6 extension header filter** `fmgd_firewall_ipv6ehfilter` **User defined IPv4 local-in policies** `fmgd_firewall_localinpolicy` **User defined IPv6 local-in policies** `fmgd_firewall_localinpolicy6` **Multicast NAT policies** `fmgd_firewall_multicastpolicy` **IPv6 multicast NAT policies** `fmgd_firewall_multicastpolicy6` **On-demand packet sniffer** `fmgd_firewall_ondemandsniffer` **IPv4 policies** `fmgd_firewall_policy` **IPv4 policies - fabric policy** `fmgd_firewall_policy_fabricpolicy` **Proxy policies** `fmgd_firewall_proxypolicy` **Firewall response shaping policy** `fmgd_firewall_responseshapingpolicy` **Security policies (policy package)** `fmgd_firewall_securitypolicy` **Per-IP traffic shaper** `fmgd_firewall_shaper_peripshaper` **Shared traffic shaper** `fmgd_firewall_shaper_trafficshaper` **Shaping policies** `fmgd_firewall_shapingpolicy` **Shaping profiles** `fmgd_firewall_shapingprofile` **Shaping profiles - shaping entries** `fmgd_firewall_shapingprofile_shapingentries` **Sniffer policies** `fmgd_firewall_sniffer` **Sniffer policies - anomaly** `fmgd_firewall_sniffer_anomaly` **Traffic classes** `fmgd_firewall_trafficclass` **TTL policies** `fmgd_firewall_ttlpolicy` **DSCP based priority table** `fmgd_system_dscpbasedpriority` **ToS based priority table** `fmgd_system_tosbasedpriority`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Manage addresses, services, schedules and Internet Services

Description	Define address and address-group objects, services, schedules, Internet Service entries, GeoIP and external resources used by policies.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**IPv4 addresses** `fmgd_firewall_address`, `fmgd_firewall_address_list` **IPv6 firewall addresses** `fmgd_firewall_address6`, `fmgd_firewall_address6_list` **IPv6 firewall addresses - subnet segment** `fmgd_firewall_address6_subnetsegment` **IPv6 firewall addresses - tagging** `fmgd_firewall_address6_tagging` **IPv6 address templates** `fmgd_firewall_address6template` **IPv6 address templates - subnet segment** `fmgd_firewall_address6template_subnetsegment` **IPv6 address templates - subnet segment - values** `fmgd_firewall_address6template_subnetsegment_values` **IPv4 addresses - tagging** `fmgd_firewall_address_tagging` **IPv4 address groups** `fmgd_firewall_addrgrp` **IPv6 address groups** `fmgd_firewall_addrgrp6` **IPv6 address groups - tagging** `fmgd_firewall_addrgrp6_tagging` **IPv4 address groups - tagging** `fmgd_firewall_addrgrp_tagging` **Custom tag table** `fmgd_firewall_customtag` **DNS translation** `fmgd_firewall_dnstranslation` **Internet Service application** `fmgd_firewall_internetservice` **Internet Services Addition** `fmgd_firewall_internetserviceaddition` **Internet Services Addition - entry** `fmgd_firewall_internetserviceaddition_entry` **Internet Services Addition - entry - port range** `fmgd_firewall_internetserviceaddition_entry_portrange` **Additional port mappings for Internet Services** `fmgd_firewall_internetserviceappend` **Custom Internet Services** `fmgd_firewall_internetservicecustom` **Custom Internet Services - entry** `fmgd_firewall_internetservicecustom_entry` **Custom Internet Service group** `fmgd_firewall_internetservicecustomgroup` **Internet Service definition** `fmgd_firewall_internetservicedefinition` **Internet Service definition - entry** `fmgd_firewall_internetservicedefinition_entry` **Internet Service definition - entry - port range** `fmgd_firewall_internetservicedefinition_entry_portrange` **Internet Services Extension** `fmgd_firewall_internetserviceextension` **Internet Services Extension - disable entry** `fmgd_firewall_internetserviceextension_disableentry` **Internet Services Extension - disable entry - IPv6 range** `fmgd_firewall_internetserviceextension_disableentry_ip6range` **Internet Services Extension - disable entry - IP range** `fmgd_firewall_internetserviceextension_disableentry_iprange` **Internet Services Extension - disable entry - port range** `fmgd_firewall_internetserviceextension_disableentry_portrange` **Internet Services Extension - entry** `fmgd_firewall_internetserviceextension_entry` **Internet Services Extension - entry - port range** `fmgd_firewall_internetserviceextension_entry_portrange` **Group of Internet Service** `fmgd_firewall_internetservicegroup` **Internet service names** `fmgd_firewall_internetservicename` **IP to MAC binding settings** `fmgd_firewall_ipmacbinding_setting` **IP MAC binding table** `fmgd_firewall_ipmacbinding_table` **Multicast addresses** `fmgd_firewall_multicastaddress` **IPv6 multicast address** `fmgd_firewall_multicastaddress6` **IPv6 multicast address - tagging** `fmgd_firewall_multicastaddress6_tagging` **Multicast addresses - tagging** `fmgd_firewall_multicastaddress_tagging` **Dynamic Network Services** `fmgd_firewall_networkservicedynamic` **Web proxy address** `fmgd_firewall_proxyaddress` **Web proxy address (IPv6)** `fmgd_firewall_proxyaddress6` **Web proxy address (IPv6) - header group** `fmgd_firewall_proxyaddress6_headergroup` **Web proxy address (IPv6) - tagging** `fmgd_firewall_proxyaddress6_tagging` **Web proxy address - header group** `fmgd_firewall_proxyaddress_headergroup` **Web proxy address - tagging** `fmgd_firewall_proxyaddress_tagging` **Web proxy address group** `fmgd_firewall_proxyaddrgrp` **Web proxy address group (IPv6)** `fmgd_firewall_proxyaddrgrp6` **Web proxy address group (IPv6) - tagging** `fmgd_firewall_proxyaddrgrp6_tagging` **Web proxy address group - tagging** `fmgd_firewall_proxyaddrgrp_tagging` **Schedule group configuration** `fmgd_firewall_schedule_group` **Onetime schedule configuration** `fmgd_firewall_schedule_onetime` **Recurring schedule configuration** `fmgd_firewall_schedule_recurring` **Service categories** `fmgd_firewall_service_category` **Custom services** `fmgd_firewall_service_custom` **Service groups** `fmgd_firewall_service_group` **Vendor and the MAC address they have** `fmgd_firewall_vendormac` **Config global/VDOM Wildcard FQDN address** `fmgd_firewall_wildcardfqdn_custom` **Config global Wildcard FQDN address groups** `fmgd_firewall_wildcardfqdn_group` **External resource** `fmgd_system_externalresource` **Device system geoip country** `fmgd_system_geoipcountry` **Geographical location mapping for IP address** `fmgd_system_geoipoverride` **Geographical location mapping for IP address - IPv6 range** `fmgd_system_geoipoverride_ip6range` **Geographical location mapping for IP address - IP range** `fmgd_system_geoipoverride_iprange` **Object tags** `fmgd_system_objecttag` **Object tagging** `fmgd_system_objecttagging`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure NAT, virtual IPs and IP pools

Description	Configure virtual IPs and groups, IP pools, central SNAT maps, IP translation, NAT64 and load-balancing health monitors.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**IPv4 and IPv6 central SNAT policies** `fmgd_firewall_centralsnatmap` **IPv4 IP pools** `fmgd_firewall_ippool` **IPv6 IP pools** `fmgd_firewall_ippool6` **IP translation** `fmgd_firewall_iptranslation` **Server load balancing health monitors** `fmgd_firewall_ldbmonitor` **Virtual IP for IPv4** `fmgd_firewall_vip` **Virtual IP for IPv6** `fmgd_firewall_vip6` **Virtual IP for IPv6 - quic** `fmgd_firewall_vip6_quic` **Virtual IP for IPv6 - real servers** `fmgd_firewall_vip6_realservers` **Virtual IP for IPv6 - SSL cipher suites** `fmgd_firewall_vip6_sslciphersuites` **Virtual IP for IPv6 - SSL server cipher suites** `fmgd_firewall_vip6_sslserverciphersuites` **Virtual IP for IPv4 - GSLB public IPS** `fmgd_firewall_vip_gslbpublicips` **Virtual IP for IPv4 - quic** `fmgd_firewall_vip_quic` **Virtual IP for IPv4 - real servers** `fmgd_firewall_vip_realservers` **Virtual IP for IPv4 - SSL cipher suites** `fmgd_firewall_vip_sslciphersuites` **Virtual IP for IPv4 - SSL server cipher suites** `fmgd_firewall_vip_sslserverciphersuites` **IPv4 virtual IP groups** `fmgd_firewall_vipgrp` **IPv6 virtual IP groups** `fmgd_firewall_vipgrp6` **NAT64 settings** `fmgd_system_nat64` **NAT64 settings - secondary prefix** `fmgd_system_nat64_secondaryprefix` **PCP server information** `fmgd_system_pcpserver` **PCP server information - pools** `fmgd_system_pcpserver_pools`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure SSL/SSH inspection and protocol options

Description	Set up SSL/SSH inspection profiles, protocol options, SSL servers and profile groups that security policies reference.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Profile groups** `fmgd_firewall_profilegroup` **Protocol options** `fmgd_firewall_profileprotocoloptions` **Protocol options - CIFS** `fmgd_firewall_profileprotocoloptions_cifs` **Protocol options - CIFS - server keytab** `fmgd_firewall_profileprotocoloptions_cifs_serverkeytab` **Protocol options - DNS** `fmgd_firewall_profileprotocoloptions_dns` **Protocol options - FTP** `fmgd_firewall_profileprotocoloptions_ftp` **Protocol options - HTTP** `fmgd_firewall_profileprotocoloptions_http` **Protocol options - IMAP** `fmgd_firewall_profileprotocoloptions_imap` **Protocol options - mail signature** `fmgd_firewall_profileprotocoloptions_mailsignature` **Protocol options - MAPI** `fmgd_firewall_profileprotocoloptions_mapi` **Protocol options - NNTP** `fmgd_firewall_profileprotocoloptions_nntp` **Protocol options - POP3** `fmgd_firewall_profileprotocoloptions_pop3` **Protocol options - SMTP** `fmgd_firewall_profileprotocoloptions_smtp` **Protocol options - SSH** `fmgd_firewall_profileprotocoloptions_ssh` **Protocol options - websocket** `fmgd_firewall_profileprotocoloptions_websocket` **SSH proxy host public keys** `fmgd_firewall_ssh_hostkey` **SSH proxy local CA** `fmgd_firewall_ssh_localca` **SSH proxy local keys** `fmgd_firewall_ssh_localkey` **SSH proxy settings** `fmgd_firewall_ssh_setting` **SSL default certificate** `fmgd_firewall_ssl_defaultcertificate` **SSL keyring list** `fmgd_firewall_ssl_keyringlist` **SSL proxy settings** `fmgd_firewall_ssl_setting` **SSL servers** `fmgd_firewall_sslserver` **SSL/SSH protocol options** `fmgd_firewall_sslsshprofile` **SSL/SSH protocol options - DoT** `fmgd_firewall_sslsshprofile_dot` **SSL/SSH protocol options - echoutersni** `fmgd_firewall_sslsshprofile_echoutersni` **SSL/SSH protocol options - FTPS** `fmgd_firewall_sslsshprofile_ftps` **SSL/SSH protocol options - HTTPS** `fmgd_firewall_sslsshprofile_https` **SSL/SSH protocol options - IMAPS** `fmgd_firewall_sslsshprofile_imaps` **SSL/SSH protocol options - POP3S** `fmgd_firewall_sslsshprofile_pop3s` **SSL/SSH protocol options - SMTPS** `fmgd_firewall_sslsshprofile_smtps` **SSL/SSH protocol options - SSH** `fmgd_firewall_sslsshprofile_ssh` **SSL/SSH protocol options - SSL** `fmgd_firewall_sslsshprofile_ssl` **SSL/SSH protocol options - SSL client certificate** `fmgd_firewall_sslsshprofile_sslclientcertificate` **SSL/SSH protocol options - SSL exempt** `fmgd_firewall_sslsshprofile_sslexempt` **SSL/SSH protocol options - SSL server** `fmgd_firewall_sslsshprofile_sslserver`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Publish applications with ZTNA and access proxy

Description	Configure access proxies and virtual hosts, ZTNA servers, tags, traffic forwarding and web portals for zero-trust application access.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**IPv4 access proxy** `fmgd_firewall_accessproxy` **IPv6 access proxy** `fmgd_firewall_accessproxy6` **IPv6 access proxy - API gateway** `fmgd_firewall_accessproxy6_apigateway` **IPv6 access proxy - API gateway (IPv6)** `fmgd_firewall_accessproxy6_apigateway6` **IPv6 access proxy - API gateway (IPv6) - real servers** `fmgd_firewall_accessproxy6_apigateway6_realservers` **IPv6 access proxy - API gateway (IPv6) - SSL cipher suites** `fmgd_firewall_accessproxy6_apigateway6_sslciphersuites` **IPv6 access proxy - API gateway - quic** `fmgd_firewall_accessproxy6_apigateway_quic` **IPv6 access proxy - API gateway - real servers** `fmgd_firewall_accessproxy6_apigateway_realservers` **IPv6 access proxy - API gateway - SSL cipher suites** `fmgd_firewall_accessproxy6_apigateway_sslciphersuites` **IPv4 access proxy - API gateway** `fmgd_firewall_accessproxy_apigateway` **IPv4 access proxy - API gateway (IPv6)** `fmgd_firewall_accessproxy_apigateway6` **IPv4 access proxy - API gateway (IPv6) - quic** `fmgd_firewall_accessproxy_apigateway6_quic` **IPv4 access proxy - API gateway (IPv6) - real servers** `fmgd_firewall_accessproxy_apigateway6_realservers` **IPv4 access proxy - API gateway (IPv6) - SSL cipher suites** `fmgd_firewall_accessproxy_apigateway6_sslciphersuites` **IPv4 access proxy - API gateway - quic** `fmgd_firewall_accessproxy_apigateway_quic` **IPv4 access proxy - API gateway - real servers** `fmgd_firewall_accessproxy_apigateway_realservers` **IPv4 access proxy - API gateway - SSL cipher suites** `fmgd_firewall_accessproxy_apigateway_sslciphersuites` **Access Proxy SSH client certificate** `fmgd_firewall_accessproxysshclientcert` **Access Proxy SSH client certificate - certextension** `fmgd_firewall_accessproxysshclientcert_certextension` **Access Proxy virtual hosts** `fmgd_firewall_accessproxyvirtualhost` **ZTNA connector edge** `fmgd_ztna_connectoredge` **ZTNA connector service edge** `fmgd_ztna_connectorserviceedge` **ZTNA destination** `fmgd_ztna_destination` **ZTNA Reverse-Connector** `fmgd_ztna_reverseconnector` **ZTNA service connector** `fmgd_ztna_serviceconnector` **ZTNA traffic forward proxy** `fmgd_ztna_trafficforwardproxy` **ZTNA traffic forward proxy - quic** `fmgd_ztna_trafficforwardproxy_quic` **ZTNA traffic forward proxy - SSL cipher suites** `fmgd_ztna_trafficforwardproxy_sslciphersuites` **ZTNA traffic forward proxy - SSL server cipher suites** `fmgd_ztna_trafficforwardproxy_sslserverciphersuites` **ZTNA traffic forward proxy reverse service** `fmgd_ztna_trafficforwardproxyreverseservice` **ZTNA traffic forward proxy reverse service - remote servers** `fmgd_ztna_trafficforwardproxyreverseservice_remoteservers` **ZTNA web-portal** `fmgd_ztna_webportal` **ZTNA web-portal bookmark** `fmgd_ztna_webportalbookmark` **ZTNA web-portal bookmark - bookmarks** `fmgd_ztna_webportalbookmark_bookmarks` **ZTNA web-portal bookmark - LLM secure proxy** `fmgd_ztna_webportalbookmark_llmsecureproxy` **ZTNA web-proxy** `fmgd_ztna_webproxy` **ZTNA web-proxy - API gateway** `fmgd_ztna_webproxy_apigateway` **ZTNA web-proxy - API gateway (IPv6)** `fmgd_ztna_webproxy_apigateway6` **ZTNA web-proxy - API gateway (IPv6) - quic** `fmgd_ztna_webproxy_apigateway6_quic` **ZTNA web-proxy - API gateway (IPv6) - real servers** `fmgd_ztna_webproxy_apigateway6_realservers` **ZTNA web-proxy - API gateway (IPv6) - SSL cipher suites** `fmgd_ztna_webproxy_apigateway6_sslciphersuites` **ZTNA web-proxy - API gateway - quic** `fmgd_ztna_webproxy_apigateway_quic` **ZTNA web-proxy - API gateway - real servers** `fmgd_ztna_webproxy_apigateway_realservers` **ZTNA web-proxy - API gateway - SSL cipher suites** `fmgd_ztna_webproxy_apigateway_sslciphersuites`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Block malware and intrusions

Description	Configure antivirus profiles and quarantine, IPS sensors, signatures and virtual patching.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Antivirus exempt lists** `fmgd_antivirus_exemptlist` **Antivirus heuristics** `fmgd_antivirus_heuristic` **Antivirus profiles** `fmgd_antivirus_profile` **Antivirus profiles - CIFS** `fmgd_antivirus_profile_cifs` **Antivirus profiles - FTP** `fmgd_antivirus_profile_ftp` **Antivirus profiles - HTTP** `fmgd_antivirus_profile_http` **Antivirus profiles - IMAP** `fmgd_antivirus_profile_imap` **Antivirus profiles - nacquar** `fmgd_antivirus_profile_nacquar` **Antivirus profiles - NNTP** `fmgd_antivirus_profile_nntp` **Antivirus profiles - POP3** `fmgd_antivirus_profile_pop3` **Antivirus profiles - SMTP** `fmgd_antivirus_profile_smtp` **Antivirus profiles - websocket** `fmgd_antivirus_profile_websocket` **Antivirus quarantine options** `fmgd_antivirus_quarantine` **Antivirus settings** `fmgd_antivirus_settings` **IPS custom signatures** `fmgd_ips_custom` **IPS decoders** `fmgd_ips_decoder` **IPS decoders - parameter** `fmgd_ips_decoder_parameter` **IPS global settings** `fmgd_ips_global` **IPS rules** `fmgd_ips_rule` **IPS rule settings** `fmgd_ips_rulesettings` **IPS sensors** `fmgd_ips_sensor` **IPS sensors - entries** `fmgd_ips_sensor_entries` **IPS sensors - entries - exempt IP** `fmgd_ips_sensor_entries_exemptip` **IPS VDOM settings** `fmgd_ips_settings` **IPS TLS active probe** `fmgd_ips_tlsactiveprobe` **FMWP signatures** `fmgd_rule_fmwp` **OT detection signatures** `fmgd_rule_otdt` **OT patch signatures** `fmgd_rule_otvp` **IPS system settings** `fmgd_system_ips` **Virtual-patch profile** `fmgd_virtualpatch_profile` **Virtual-patch profile - exemption** `fmgd_virtualpatch_profile_exemption`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Control applications and SaaS usage

Description	Configure application control lists, custom signatures and categories, and CASB SaaS applications, profiles and user activities.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Application control lists** `fmgd_application_list` **Application categories** `fmgd_application_categories` **App classification setting** `fmgd_application_classificationsettings` **Custom application signatures** `fmgd_application_custom` **Application groups** `fmgd_application_group` **Default network service entries** `fmgd_application_list_defaultnetworkservices` **Application list entries** `fmgd_application_list_entries` **Application signatures** `fmgd_application_name` **Application rule settings** `fmgd_application_rulesettings` **Unsanctioned applications** `fmgd_application_unsanctionedapps` **CASB attribute matching** `fmgd_casb_attributematch` **CASB attribute matching - attribute** `fmgd_casb_attributematch_attribute` **CASB attribute matching - match** `fmgd_casb_attributematch_match` **CASB attribute matching - match - rule** `fmgd_casb_attributematch_match_rule` **CASB profile** `fmgd_casb_profile` **CASB profile - saas application** `fmgd_casb_profile_saasapplication` **CASB profile - saas application - access rule** `fmgd_casb_profile_saasapplication_accessrule` **CASB profile - saas application - access rule - attribute filter** `fmgd_casb_profile_saasapplication_accessrule_attributefilter` **CASB profile - saas application - advanced tenant control** `fmgd_casb_profile_saasapplication_advancedtenantcontrol` **CASB profile - saas application - advanced tenant control - attribute** `fmgd_casb_profile_saasapplication_advancedtenantcontrol_attribute` **CASB profile - saas application - custom control** `fmgd_casb_profile_saasapplication_customcontrol` **CASB profile - saas application - custom control - attribute filter** `fmgd_casb_profile_saasapplication_customcontrol_attributefilter` **CASB profile - saas application - custom control - option** `fmgd_casb_profile_saasapplication_customcontrol_option` **CASB SaaS applications** `fmgd_casb_saasapplication` **CASB SaaS applications - input attributes** `fmgd_casb_saasapplication_inputattributes` **CASB SaaS applications - output attributes** `fmgd_casb_saasapplication_outputattributes` **CASB user activity** `fmgd_casb_useractivity` **CASB user activity - match** `fmgd_casb_useractivity_match` **CASB user activity - match - rules** `fmgd_casb_useractivity_match_rules` **CASB user activity - match - tenant extraction** `fmgd_casb_useractivity_match_tenantextraction` **CASB user activity - match - tenant extraction - filters** `fmgd_casb_useractivity_match_tenantextraction_filters` **CASB user activity - match - tenant session extraction** `fmgd_casb_useractivity_match_tenantsessionextraction` **CASB user activity - match - tenant session extraction - filters** `fmgd_casb_useractivity_match_tenantsessionextraction_filters`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Filter web, DNS, email and files and prevent data loss

Description	Configure web, DNS, video, email and file filters, DLP sensors, ICAP offload, image analysis and browser isolation.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**DLP data types** `fmgd_dlp_datatype` **DLP dictionaries** `fmgd_dlp_dictionary` **DLP dictionaries - entries** `fmgd_dlp_dictionary_entries` **DLP exact data match templates** `fmgd_dlp_exactdatamatch` **DLP exact data match templates - columns** `fmgd_dlp_exactdatamatch_columns` **DLP file patterns** `fmgd_dlp_filepattern` **DLP file patterns - entries** `fmgd_dlp_filepattern_entries` **DLP fingerprint document sources** `fmgd_dlp_fpdocsource` **DLP labels** `fmgd_dlp_label` **DLP labels - entries** `fmgd_dlp_label_entries` **DLP profiles** `fmgd_dlp_profile` **DLP profiles - rule** `fmgd_dlp_profile_rule` **DLP sensors** `fmgd_dlp_sensor` **DLP sensors - entries** `fmgd_dlp_sensor_entries` **DLP settings** `fmgd_dlp_settings` **DLP settings - OCR** `fmgd_dlp_settings_ocr` **DNS domain filters** `fmgd_dnsfilter_domainfilter` **DNS domain filters - entries** `fmgd_dnsfilter_domainfilter_entries` **DNS domain filter profile** `fmgd_dnsfilter_profile` **DNS domain filter profile - DNS translation** `fmgd_dnsfilter_profile_dnstranslation` **DNS domain filter profile - domain filter** `fmgd_dnsfilter_profile_domainfilter` **DNS domain filter profile - ftgddns** `fmgd_dnsfilter_profile_ftgddns` **DNS domain filter profile - ftgddns - filters** `fmgd_dnsfilter_profile_ftgddns_filters` **Anti-spam block/allow list** `fmgd_emailfilter_blockallowlist` **Anti-spam block/allow list - entries** `fmgd_emailfilter_blockallowlist_entries` **AntiSpam banned word list** `fmgd_emailfilter_bword` **AntiSpam banned word list - entries** `fmgd_emailfilter_bword_entries` **AntiSpam DNSBL/ORBL** `fmgd_emailfilter_dnsbl` **AntiSpam DNSBL/ORBL - entries** `fmgd_emailfilter_dnsbl_entries` **Email filter FortiGuard settings** `fmgd_emailfilter_fortiguard` **Email filter FortiShield settings** `fmgd_emailfilter_fortishield` **AntiSpam IP trust** `fmgd_emailfilter_iptrust` **AntiSpam IP trust - entries** `fmgd_emailfilter_iptrust_entries` **AntiSpam MIME header** `fmgd_emailfilter_mheader` **AntiSpam MIME header - entries** `fmgd_emailfilter_mheader_entries` **AntiSpam options** `fmgd_emailfilter_options` **Email Filter profiles** `fmgd_emailfilter_profile` **Email Filter profiles - gmail** `fmgd_emailfilter_profile_gmail` **Email Filter profiles - IMAP** `fmgd_emailfilter_profile_imap` **Email Filter profiles - msn hotmail** `fmgd_emailfilter_profile_msnhotmail` **Email Filter profiles - POP3** `fmgd_emailfilter_profile_pop3` **Email Filter profiles - SMTP** `fmgd_emailfilter_profile_smtp` **File-filter profiles** `fmgd_filefilter_profile` **File-filter profiles - rules** `fmgd_filefilter_profile_rules` **ICAP local servers** `fmgd_icap_localserver` **ICAP local servers - ICAP service** `fmgd_icap_localserver_icapservice` **ICAP profiles** `fmgd_icap_profile` **ICAP profiles - ICAP headers** `fmgd_icap_profile_icapheaders` **ICAP remote servers** `fmgd_icap_remoteserver` **ICAP remote server groups** `fmgd_icap_remoteservergroup` **ICAP remote server groups - server list** `fmgd_icap_remoteservergroup_serverlist` **ICAP servers** `fmgd_icap_server` **ICAP server groups** `fmgd_icap_servergroup` **ICAP server groups - server list** `fmgd_icap_servergroup_serverlist` **Image analyzer profile** `fmgd_imageanalyzer_profile` **Isolator profile** `fmgd_isolator_profile` **Isolator profile - entries** `fmgd_isolator_profile_entries` **Isolator setting** `fmgd_isolator_setting` **Video filter keywords** `fmgd_videofilter_keyword` **Video filter keywords - word** `fmgd_videofilter_keyword_word` **VideoFilter profile** `fmgd_videofilter_profile` **VideoFilter profile - filters** `fmgd_videofilter_profile_filters` **VideoFilter profile - FortiGuard category filters** `fmgd_videofilter_profile_fortiguardcategory_filters` **YouTube API keys** `fmgd_videofilter_youtubekey` **Web filter banned word tables** `fmgd_webfilter_content` **Web filter banned word tables - entries** `fmgd_webfilter_content_entries` **Web filter content types** `fmgd_webfilter_contentheader` **Web filter content types - entries** `fmgd_webfilter_contentheader_entries` **Web filter domain lists** `fmgd_webfilter_domainlist` **Web filter domain lists - entries** `fmgd_webfilter_domainlist_entries` **FortiGuard Web Filter service** `fmgd_webfilter_fortiguard` **FortiGuard Web Filter local categories** `fmgd_webfilter_ftgdlocalcat` **FortiGuard local ratings** `fmgd_webfilter_ftgdlocalrating` **FortiGuard Web Filter local risk score** `fmgd_webfilter_ftgdlocalrisk` **FortiGuard Web Filter risk level** `fmgd_webfilter_ftgdrisklevel` **IPS URL filter cache settings** `fmgd_webfilter_ipsurlfiltercachesetting` **IPS URL filter settings** `fmgd_webfilter_ipsurlfiltersetting` **IPS URL filter settings for IPv6** `fmgd_webfilter_ipsurlfiltersetting6` **Web filter overrides** `fmgd_webfilter_override` **Web filter profiles** `fmgd_webfilter_profile` **Web filter profiles - antiphish custom patterns** `fmgd_webfilter_profile_antiphish_custompatterns` **Web filter profiles - antiphish inspection entries** `fmgd_webfilter_profile_antiphish_inspectionentries` **Web filter profiles - ftgdwf** `fmgd_webfilter_profile_ftgdwf` **Web filter profiles - ftgdwf - filters** `fmgd_webfilter_profile_ftgdwf_filters` **Web filter profiles - ftgdwf - quota** `fmgd_webfilter_profile_ftgdwf_quota` **Web filter profiles - ftgdwf - risk** `fmgd_webfilter_profile_ftgdwf_risk` **Web filter profiles - override** `fmgd_webfilter_profile_override` **Web filter profiles - web** `fmgd_webfilter_profile_web` **Web filter search engines** `fmgd_webfilter_searchengine` **Web filter URL filters** `fmgd_webfilter_urlfilter` **Web filter URL filters - entries** `fmgd_webfilter_urlfilter_entries` **Web filter URL lists** `fmgd_webfilter_urllist` **Web filter URL lists - entries** `fmgd_webfilter_urllist_entries`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Protect web applications and LLM traffic

Description	Configure web application firewall profiles and signatures, and LLM proxy servers and profiles.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**LLM Proxy profiles** `fmgd_llm_profile` **LLM Proxy profiles - chat** `fmgd_llm_profile_chat` **LLM Proxy profiles - imagegen** `fmgd_llm_profile_imagegen` **LLM Proxy profiles - list models** `fmgd_llm_profile_listmodels` **LLM Proxy profiles - response** `fmgd_llm_profile_response` **LLM Proxy** `fmgd_llm_proxy` **LLM Proxy servers** `fmgd_llm_server` **WAF signature main classes** `fmgd_waf_mainclass` **Web application firewall (WAF) profiles** `fmgd_waf_profile` **Web application firewall (WAF) profiles - address list** `fmgd_waf_profile_addresslist` **Web application firewall (WAF) profiles - constraint** `fmgd_waf_profile_constraint` **Web application firewall (WAF) profiles - constraint - content length** `fmgd_waf_profile_constraint_contentlength` **Web application firewall (WAF) profiles - constraint - exception** `fmgd_waf_profile_constraint_exception` **Web application firewall (WAF) profiles - constraint - header length** `fmgd_waf_profile_constraint_headerlength` **Web application firewall (WAF) profiles - constraint - hostname** `fmgd_waf_profile_constraint_hostname` **Web application firewall (WAF) profiles - constraint - line length** `fmgd_waf_profile_constraint_linelength` **Web application firewall (WAF) profiles - constraint - malformed** `fmgd_waf_profile_constraint_malformed` **Web application firewall (WAF) profiles - constraint - maxcookie** `fmgd_waf_profile_constraint_maxcookie` **Web application firewall (WAF) profiles - constraint - max header line** `fmgd_waf_profile_constraint_maxheaderline` **Web application firewall (WAF) profiles - constraint - max range segment** `fmgd_waf_profile_constraint_maxrangesegment` **Web application firewall (WAF) profiles - constraint - max URL param** `fmgd_waf_profile_constraint_maxurlparam` **Web application firewall (WAF) profiles - constraint - method** `fmgd_waf_profile_constraint_method` **Web application firewall (WAF) profiles - constraint - param length** `fmgd_waf_profile_constraint_paramlength` **Web application firewall (WAF) profiles - constraint - URL param length** `fmgd_waf_profile_constraint_urlparamlength` **Web application firewall (WAF) profiles - constraint - version** `fmgd_waf_profile_constraint_version` **Web application firewall (WAF) profiles - method** `fmgd_waf_profile_method` **Web application firewall (WAF) profiles - method - method policy** `fmgd_waf_profile_method_methodpolicy` **Web application firewall (WAF) profiles - signature** `fmgd_waf_profile_signature` **Web application firewall (WAF) profiles - signature - custom signature** `fmgd_waf_profile_signature_customsignature` **Web application firewall (WAF) profiles - signature - main class** `fmgd_waf_profile_signature_mainclass` **Web application firewall (WAF) profiles - URL access** `fmgd_waf_profile_urlaccess` **Web application firewall (WAF) profiles - URL access - access pattern** `fmgd_waf_profile_urlaccess_accesspattern` **WAF signatures** `fmgd_waf_signature` **WAF signature subclasses** `fmgd_waf_subclass`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure proxies, WAN optimization and protocol security

Description	Configure explicit web and FTP proxies, WAN optimization, web caching, and VoIP, GTP, PFCP, SCTP, SSH and Diameter protocol filters.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Diameter filter profiles** `fmgd_diameterfilter_profile` **PFCP firewall settings** `fmgd_firewall_pfcp` **Explicit FTP proxy settings** `fmgd_ftpproxy_explicit` **Global per-APN shaper** `fmgd_gtp_apnshaper` **IE allow list** `fmgd_gtp_ieallowlist` **IE allow list - entries** `fmgd_gtp_ieallowlist_entries` **RAT timeout profile** `fmgd_gtp_rattimeoutprofile` **Message filter for PFCP messages** `fmgd_pfcp_messagefilter` **SCTP filter profiles** `fmgd_sctpfilter_profile` **SCTP filter profiles - ppid filters** `fmgd_sctpfilter_profile_ppidfilters` **SSH filter profile** `fmgd_sshfilter_profile` **SSH filter profile - shellcommands** `fmgd_sshfilter_profile_shellcommands` **VoIP profiles** `fmgd_voip_profile` **VoIP profiles - MSRP** `fmgd_voip_profile_msrp` **VoIP profiles - SCCP** `fmgd_voip_profile_sccp` **VoIP profiles - SIP** `fmgd_voip_profile_sip` **WAN optimization authentication groups** `fmgd_wanopt_authgroup` **WAN optimization cache services** `fmgd_wanopt_cacheservice` **WAN optimization cache services - dstpeer** `fmgd_wanopt_cacheservice_dstpeer` **WAN optimization cache services - srcpeer** `fmgd_wanopt_cacheservice_srcpeer` **WAN optimization content delivery network rules** `fmgd_wanopt_contentdeliverynetworkrule` **WAN optimization content delivery network rules - rules** `fmgd_wanopt_contentdeliverynetworkrule_rules` **WAN optimization content delivery network rules - rules - content ID** `fmgd_wanopt_contentdeliverynetworkrule_rules_contentid` **WAN optimization content delivery network rules - rules - match entries** `fmgd_wanopt_contentdeliverynetworkrule_rules_matchentries` **WAN optimization content delivery network rules - rules - skip entries** `fmgd_wanopt_contentdeliverynetworkrule_rules_skipentries` **WAN optimization peers** `fmgd_wanopt_peer` **WAN optimization profiles** `fmgd_wanopt_profile` **WAN optimization profiles - CIFS** `fmgd_wanopt_profile_cifs` **WAN optimization profiles - FTP** `fmgd_wanopt_profile_ftp` **WAN optimization profiles - HTTP** `fmgd_wanopt_profile_http` **WAN optimization profiles - MAPI** `fmgd_wanopt_profile_mapi` **WAN optimization profiles - TCP** `fmgd_wanopt_profile_tcp` **Remote cache storage devices** `fmgd_wanopt_remotestorage` **WAN optimization settings** `fmgd_wanopt_settings` **Global web cache settings** `fmgd_wanopt_webcache` **Webcache prefetch** `fmgd_webcache_prefetch` **Webcache reverse cache server** `fmgd_webcache_reversecacheserver` **Webcache settings** `fmgd_webcache_settings` **Webcache user agent** `fmgd_webcache_useragent` **Debug URL addresses** `fmgd_webproxy_debugurl` **Web proxy dynamic bypass** `fmgd_webproxy_dynamicbypass` **Explicit web proxy settings** `fmgd_webproxy_explicit` **Explicit web proxy settings - pac policy** `fmgd_webproxy_explicit_pacpolicy` **Explicit web proxy (legacy table)** `fmgd_webproxy_explicitproxy` **Proxy destination connection fast-fallback** `fmgd_webproxy_fastfallback` **Web proxy forward servers** `fmgd_webproxy_forwardserver` **Forward server group** `fmgd_webproxy_forwardservergroup` **Forward server group - server list** `fmgd_webproxy_forwardservergroup_serverlist` **Web proxy global settings** `fmgd_webproxy_global` **Web proxy implicit proxy rule** `fmgd_webproxy_implicitproxyrule` **Web proxy implicit proxy rule - proxy servers** `fmgd_webproxy_implicitproxyrule_proxyservers` **Web proxy implicit proxy setting** `fmgd_webproxy_implicitproxysetting` **Web proxy isolator servers** `fmgd_webproxy_isolatorserver` **Web proxy pac policy** `fmgd_webproxy_pacpolicy` **Web proxy profiles** `fmgd_webproxy_profile` **Web proxy profiles - headers** `fmgd_webproxy_profile_headers` **Web proxy redirect profile** `fmgd_webproxy_redirectprofile` **Web proxy redirect profile - entries** `fmgd_webproxy_redirectprofile_entries` **Web proxy URL list** `fmgd_webproxy_urllist` **Web proxy URL list - entries** `fmgd_webproxy_urllist_entries` **URL match** `fmgd_webproxy_urlmatch` **Websense WISP servers** `fmgd_webproxy_wisp`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure static routes, policy routes and route filters

Description	Configure static and policy routes, access, prefix, AS-path and community lists, route maps, key chains and global routing settings.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Access lists** `fmgd_router_accesslist` **IPv6 access lists** `fmgd_router_accesslist6` **IPv6 access lists - rule** `fmgd_router_accesslist6_rule` **Access lists - rule** `fmgd_router_accesslist_rule` **AS path lists** `fmgd_router_aspathlist` **AS path lists - rule** `fmgd_router_aspathlist_rule` **Authentication based routing** `fmgd_router_authpath` **Community lists** `fmgd_router_communitylist` **Community lists - rule** `fmgd_router_communitylist_rule` **Extended community lists** `fmgd_router_extcommunitylist` **Extended community lists - rule** `fmgd_router_extcommunitylist_rule` **Key chains** `fmgd_router_keychain` **Key chains - key** `fmgd_router_keychain_key` **IPv4 routing policies** `fmgd_router_policy` **IPv6 routing policies** `fmgd_router_policy6` **IPv4 prefix lists** `fmgd_router_prefixlist` **IPv6 prefix lists** `fmgd_router_prefixlist6` **IPv6 prefix lists - rule** `fmgd_router_prefixlist6_rule` **IPv4 prefix lists - rule** `fmgd_router_prefixlist_rule` **Route maps** `fmgd_router_routemap` **Route maps - rule** `fmgd_router_routemap_rule` **Router settings** `fmgd_router_setting` **IPv4 static routing tables** `fmgd_router_static` **IPv6 static routing tables** `fmgd_router_static6`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure BGP and BFD

Description	Configure BGP neighbors, groups, networks and redistribution, and BFD for IPv4 and IPv6.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**BFD** `fmgd_router_bfd` **IPv6 BFD** `fmgd_router_bfd6` **IPv6 BFD - multi hop template** `fmgd_router_bfd6_multihoptemplate` **IPv6 BFD - neighbor** `fmgd_router_bfd6_neighbor` **BFD - multi hop template** `fmgd_router_bfd_multihoptemplate` **BFD - neighbor** `fmgd_router_bfd_neighbor` **BGP** `fmgd_router_bgp` **BGP - admin distance** `fmgd_router_bgp_admindistance` **BGP - aggregate address** `fmgd_router_bgp_aggregateaddress` **BGP - aggregate address (IPv6)** `fmgd_router_bgp_aggregateaddress6` **BGP - neighbor** `fmgd_router_bgp_neighbor` **BGP - neighbor - conditional advertise** `fmgd_router_bgp_neighbor_conditionaladvertise` **BGP - neighbor - conditional advertise (IPv6)** `fmgd_router_bgp_neighbor_conditionaladvertise6` **BGP - neighbor group** `fmgd_router_bgp_neighborgroup` **BGP - neighbor range** `fmgd_router_bgp_neighborrange` **BGP - neighbor range (IPv6)** `fmgd_router_bgp_neighborrange6` **BGP - network** `fmgd_router_bgp_network` **BGP - network (IPv6)** `fmgd_router_bgp_network6` **BGP - redistribute** `fmgd_router_bgp_redistribute` **BGP - redistribute (IPv6)** `fmgd_router_bgp_redistribute6` **BGP - vrf** `fmgd_router_bgp_vrf` **BGP - vrf (IPv6)** `fmgd_router_bgp_vrf6` **BGP - vrf (IPv6) - leak target** `fmgd_router_bgp_vrf6_leaktarget` **BGP - vrf - leak target** `fmgd_router_bgp_vrf_leaktarget` **BGP - vrf leak** `fmgd_router_bgp_vrfleak` **BGP - vrf leak (IPv6)** `fmgd_router_bgp_vrfleak6` **BGP - vrf leak (IPv6) - target** `fmgd_router_bgp_vrfleak6_target` **BGP - vrf leak - target** `fmgd_router_bgp_vrfleak_target`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure OSPF, RIP, IS-IS and multicast routing

Description	Configure OSPF and OSPFv3, RIP and RIPng, IS-IS, and PIM and multicast flow routing.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**IS-IS** `fmgd_router_isis` **IS-IS - IS-IS interface** `fmgd_router_isis_isisinterface` **IS-IS - IS-IS net** `fmgd_router_isis_isisnet` **IS-IS - redistribute** `fmgd_router_isis_redistribute` **IS-IS - redistribute (IPv6)** `fmgd_router_isis_redistribute6` **IS-IS - summary address** `fmgd_router_isis_summaryaddress` **IS-IS - summary address (IPv6)** `fmgd_router_isis_summaryaddress6` **Router multicast** `fmgd_router_multicast` **IPv6 multicast** `fmgd_router_multicast6` **IPv6 multicast - interface** `fmgd_router_multicast6_interface` **IPv6 multicast - pimsm global** `fmgd_router_multicast6_pimsmglobal` **IPv6 multicast - pimsm global - rp address** `fmgd_router_multicast6_pimsmglobal_rpaddress` **IPv6 multicast - pimsm global vrf** `fmgd_router_multicast6_pimsmglobalvrf` **IPv6 multicast - pimsm global vrf - rp address** `fmgd_router_multicast6_pimsmglobalvrf_rpaddress` **IPv6 multicast-flow** `fmgd_router_multicast6flow` **IPv6 multicast-flow - flows** `fmgd_router_multicast6flow_flows` **Router multicast - interface** `fmgd_router_multicast_interface` **Router multicast - interface - IGMP** `fmgd_router_multicast_interface_igmp` **Router multicast - interface - join group** `fmgd_router_multicast_interface_joingroup` **Router multicast - pimsm global** `fmgd_router_multicast_pimsmglobal` **Router multicast - pimsm global - rp address** `fmgd_router_multicast_pimsmglobal_rpaddress` **Router multicast - pimsm global vrf** `fmgd_router_multicast_pimsmglobalvrf` **Router multicast - pimsm global vrf - rp address** `fmgd_router_multicast_pimsmglobalvrf_rpaddress` **Multicast flow** `fmgd_router_multicastflow` **Multicast flow - flows** `fmgd_router_multicastflow_flows` **OSPF** `fmgd_router_ospf` **IPv6 OSPF** `fmgd_router_ospf6` **IPv6 OSPF - area** `fmgd_router_ospf6_area` **IPv6 OSPF - area - IPsec keys** `fmgd_router_ospf6_area_ipseckeys` **IPv6 OSPF - area - range** `fmgd_router_ospf6_area_range` **IPv6 OSPF - area - virtual link** `fmgd_router_ospf6_area_virtuallink` **IPv6 OSPF - area - virtual link - IPsec keys** `fmgd_router_ospf6_area_virtuallink_ipseckeys` **IPv6 OSPF - OSPFv3 interface** `fmgd_router_ospf6_ospf6interface` **IPv6 OSPF - OSPFv3 interface - IPsec keys** `fmgd_router_ospf6_ospf6interface_ipseckeys` **IPv6 OSPF - OSPFv3 interface - neighbor** `fmgd_router_ospf6_ospf6interface_neighbor` **IPv6 OSPF - redistribute** `fmgd_router_ospf6_redistribute` **IPv6 OSPF - summary address** `fmgd_router_ospf6_summaryaddress` **OSPF - area** `fmgd_router_ospf_area` **OSPF - area - filter list** `fmgd_router_ospf_area_filterlist` **OSPF - area - range** `fmgd_router_ospf_area_range` **OSPF - area - virtual link** `fmgd_router_ospf_area_virtuallink` **OSPF - area - virtual link - MD5 keys** `fmgd_router_ospf_area_virtuallink_md5keys` **OSPF - distribute list** `fmgd_router_ospf_distributelist` **OSPF - neighbor** `fmgd_router_ospf_neighbor` **OSPF - network** `fmgd_router_ospf_network` **OSPF - OSPF interface** `fmgd_router_ospf_ospfinterface` **OSPF - OSPF interface - MD5 keys** `fmgd_router_ospf_ospfinterface_md5keys` **OSPF - redistribute** `fmgd_router_ospf_redistribute` **OSPF - summary address** `fmgd_router_ospf_summaryaddress` **RIP** `fmgd_router_rip` **RIP - distance** `fmgd_router_rip_distance` **RIP - distribute list** `fmgd_router_rip_distributelist` **RIP - interface** `fmgd_router_rip_interface` **RIP - neighbor** `fmgd_router_rip_neighbor` **RIP - network** `fmgd_router_rip_network` **RIP - offset list** `fmgd_router_rip_offsetlist` **RIP - redistribute** `fmgd_router_rip_redistribute` **RIPng** `fmgd_router_ripng` **RIPng - aggregate address** `fmgd_router_ripng_aggregateaddress` **RIPng - distance** `fmgd_router_ripng_distance` **RIPng - distribute list** `fmgd_router_ripng_distributelist` **RIPng - interface** `fmgd_router_ripng_interface` **RIPng - neighbor** `fmgd_router_ripng_neighbor` **RIPng - network** `fmgd_router_ripng_network` **RIPng - offset list** `fmgd_router_ripng_offsetlist` **RIPng - redistribute** `fmgd_router_ripng_redistribute`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Build IPsec VPNs and tunnels

Description	Configure IPsec phase 1 and 2, IKE settings, Fabric VPN, GRE, IP-in-IP, SIT, VXLAN and other tunnels, plus L2TP, PPTP and OCVPN.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**EVPN instance** `fmgd_system_evpn` **Fabric VPN** `fmgd_system_fabricvpn` **Fabric VPN - advertised subnets** `fmgd_system_fabricvpn_advertisedsubnets` **Fabric VPN - overlays** `fmgd_system_fabricvpn_overlays` **GENEVE devices** `fmgd_system_geneve` **GRE tunnel** `fmgd_system_gretunnel` **IKE global attributes** `fmgd_system_ike` **IKE global attributes - DH group 1** `fmgd_system_ike_dhgroup1` **IKE global attributes - DH group 14** `fmgd_system_ike_dhgroup14` **IKE global attributes - DH group 15** `fmgd_system_ike_dhgroup15` **IKE global attributes - DH group 16** `fmgd_system_ike_dhgroup16` **IKE global attributes - DH group 17** `fmgd_system_ike_dhgroup17` **IKE global attributes - DH group 18** `fmgd_system_ike_dhgroup18` **IKE global attributes - DH group 19** `fmgd_system_ike_dhgroup19` **IKE global attributes - DH group 2** `fmgd_system_ike_dhgroup2` **IKE global attributes - DH group 20** `fmgd_system_ike_dhgroup20` **IKE global attributes - DH group 21** `fmgd_system_ike_dhgroup21` **IKE global attributes - DH group 27** `fmgd_system_ike_dhgroup27` **IKE global attributes - DH group 28** `fmgd_system_ike_dhgroup28` **IKE global attributes - DH group 29** `fmgd_system_ike_dhgroup29` **IKE global attributes - DH group 30** `fmgd_system_ike_dhgroup30` **IKE global attributes - DH group 31** `fmgd_system_ike_dhgroup31` **IKE global attributes - DH group 32** `fmgd_system_ike_dhgroup32` **IKE global attributes - DH group 5** `fmgd_system_ike_dhgroup5` **IP in IP Tunneling** `fmgd_system_ipiptunnel` **Aggregate of IPsec tunnels** `fmgd_system_ipsecaggregate` **IPv6/IPv4 in IPv6 tunnel** `fmgd_system_ipv6tunnel` **Mobile tunnels, an implementation of Network Mobility** `fmgd_system_mobiletunnel` **Mobile tunnels, an implementation of Network Mobility - network** `fmgd_system_mobiletunnel_network` **IPv6 tunnel over IPv4** `fmgd_system_sittunnel` **Sovereign SASE** `fmgd_system_sovsase` **Virtual network enabler tunnels** `fmgd_system_vneinterface` **Virtual network enabler tunnel** `fmgd_system_vnetunnel` **VXLAN devices** `fmgd_system_vxlan` **Concentrator configuration** `fmgd_vpn_ipsec_concentrator` **Forward Error Correction** `fmgd_vpn_ipsec_fec` **Forward Error Correction - mappings** `fmgd_vpn_ipsec_fec_mappings` **Forward Error Correction - mappings - ToS** `fmgd_vpn_ipsec_fec_mappings_tos` **FortiClient policy realm** `fmgd_vpn_ipsec_forticlient` **IPsec manual keys (policy-based)** `fmgd_vpn_ipsec_manualkey` **IPsec manual key interfaces** `fmgd_vpn_ipsec_manualkeyinterface` **IPsec phase 1 (policy-based)** `fmgd_vpn_ipsec_phase1` **IPsec phase 1 (policy-based) - IPv4 exclude range** `fmgd_vpn_ipsec_phase1_ipv4excluderange` **IPsec phase 1 (policy-based) - IPv6 exclude range** `fmgd_vpn_ipsec_phase1_ipv6excluderange` **IPsec phase 1 interfaces (route-based)** `fmgd_vpn_ipsec_phase1interface` **IPsec phase 1 interfaces (route-based) - IPv4 exclude range** `fmgd_vpn_ipsec_phase1interface_ipv4excluderange` **IPsec phase 1 interfaces (route-based) - IPv6 exclude range** `fmgd_vpn_ipsec_phase1interface_ipv6excluderange` **IPsec phase 2 (policy-based)** `fmgd_vpn_ipsec_phase2` **IPsec phase 2 interfaces (route-based)** `fmgd_vpn_ipsec_phase2interface` **L2TP** `fmgd_vpn_l2tp` **Overlay Controller VPN settings** `fmgd_vpn_ocvpn` **Overlay Controller VPN settings - forticlient access** `fmgd_vpn_ocvpn_forticlientaccess` **Overlay Controller VPN settings - forticlient access - auth groups** `fmgd_vpn_ocvpn_forticlientaccess_authgroups` **Overlay Controller VPN settings - overlays** `fmgd_vpn_ocvpn_overlays` **Overlay Controller VPN settings - overlays - subnets** `fmgd_vpn_ocvpn_overlays_subnets` **PPTP** `fmgd_vpn_pptp` **Quantum Key Distribution servers** `fmgd_vpn_qkd`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure SSL VPN and web portals

Description	Configure SSL VPN settings, portals, realms, bookmarks and host-check software.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**SSL VPN clients** `fmgd_vpn_ssl_client` **SSL VPN settings** `fmgd_vpn_ssl_settings` **SSL VPN settings - authentication rule** `fmgd_vpn_ssl_settings_authenticationrule` **SSL-VPN host check software** `fmgd_vpnsslweb_hostchecksoftware` **SSL-VPN host check software - check item list** `fmgd_vpnsslweb_hostchecksoftware_checkitemlist` **SSL VPN portals** `fmgd_vpnsslweb_portal` **SSL VPN portals - bookmark group** `fmgd_vpnsslweb_portal_bookmarkgroup` **SSL VPN portals - bookmark group - bookmarks** `fmgd_vpnsslweb_portal_bookmarkgroup_bookmarks` **SSL VPN portals - bookmark group - bookmarks - form data** `fmgd_vpnsslweb_portal_bookmarkgroup_bookmarks_formdata` **SSL VPN portals - landing page** `fmgd_vpnsslweb_portal_landingpage` **SSL VPN portals - landing page - form data** `fmgd_vpnsslweb_portal_landingpage_formdata` **SSL VPN portals - MAC addr check rule** `fmgd_vpnsslweb_portal_macaddrcheckrule` **SSL VPN portals - oschecklist** `fmgd_vpnsslweb_portal_oschecklist` **SSL VPN portals - splitdns** `fmgd_vpnsslweb_portal_splitdns` **SSL VPN realms** `fmgd_vpnsslweb_realm` **SSL-VPN user bookmark** `fmgd_vpnsslweb_userbookmark` **SSL-VPN user bookmark - bookmarks** `fmgd_vpnsslweb_userbookmark_bookmarks` **SSL-VPN user bookmark - bookmarks - form data** `fmgd_vpnsslweb_userbookmark_bookmarks_formdata` **SSL-VPN user group bookmark** `fmgd_vpnsslweb_usergroupbookmark` **SSL-VPN user group bookmark - bookmarks** `fmgd_vpnsslweb_usergroupbookmark_bookmarks` **SSL-VPN user group bookmark - bookmarks - form data** `fmgd_vpnsslweb_usergroupbookmark_bookmarks_formdata`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Manage certificates, keys and HSMs

Description	Manage local, CA, remote and HSM-backed certificates, KMIP servers, ACME and network HSM settings.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Local certificates on HSM** `fmgd_certificate_hsmlocal` **Remote certificates (PEM)** `fmgd_certificate_remote` **ACME client** `fmgd_system_acme` **ACME client - accounts** `fmgd_system_acme_accounts` **Network HSM settings** `fmgd_system_nethsm` **Network HSM settings - hagroups** `fmgd_system_nethsm_hagroups` **Network HSM settings - partitions** `fmgd_system_nethsm_partitions` **Network HSM settings - servers** `fmgd_system_nethsm_servers` **Network HSM settings - slots** `fmgd_system_nethsm_slots` **CA certificate** `fmgd_vpn_certificate_ca` **Certificate Revocation List as a PEM file** `fmgd_vpn_certificate_crl` **Local certificates on HSM (VPN)** `fmgd_vpn_certificate_hsmlocal` **Local keys and certificates** `fmgd_vpn_certificate_local` **OCSP server configuration** `fmgd_vpn_certificate_ocspserver` **Remote certificates (VPN PEM)** `fmgd_vpn_certificate_remote` **VPN certificate setting** `fmgd_vpn_certificate_setting` **VPN certificate setting - crl verification** `fmgd_vpn_certificate_setting_crlverification` **KMIP server entry configuration** `fmgd_vpn_kmipserver` **KMIP server entry configuration - server list** `fmgd_vpn_kmipserver_serverlist`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure authentication rules and single sign-on

Description	Configure authentication rules, schemes and settings, FSSO agents and polling, and domain controller integration.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Authentication Rules** `fmgd_authentication_rule` **Authentication Schemes** `fmgd_authentication_scheme` **Authentication setting** `fmgd_authentication_setting` **FSSO polling (system)** `fmgd_system_fssopolling` **FSSO groups** `fmgd_user_adgrp` **Domain controller entries** `fmgd_user_domaincontroller` **MS Exchange server entries** `fmgd_user_exchange` **FSSO agents** `fmgd_user_fsso` **FSSO active directory servers for polling mode** `fmgd_user_fssopolling` **FSSO active directory servers for polling mode - adgrp** `fmgd_user_fssopolling_adgrp` **Kerberos keytab entries** `fmgd_user_krbkeytab` **NAC policy** `fmgd_user_nacpolicy` **User authentication setting** `fmgd_user_setting`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Manage users, groups and identity providers

Description	Configure local users, groups, LDAP, RADIUS, TACACS+, SAML, OIDC and SCIM identity sources, FortiTokens, peers and password policies.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**FortiClient EMS servers** `fmgd_endpointcontrol_fctems` **FortiClient EMS server overrides** `fmgd_endpointcontrol_fctemsoverride` **Endpoint control settings** `fmgd_endpointcontrol_settings` **Global settings for SAML authentication** `fmgd_system_saml` **Global settings for SAML authentication - service providers** `fmgd_system_saml_serviceproviders` **Global settings for SAML authentication - service providers - assertion attributes** `fmgd_system_saml_serviceproviders_assertionattributes` **VDOM RADIUS server** `fmgd_system_vdomradiusserver` **Certificate users** `fmgd_user_certificate` **Domain controller entries - extra server** `fmgd_user_domaincontroller_extraserver` **External identity provider** `fmgd_user_externalidentityprovider` **FortiTokens** `fmgd_user_fortitoken` **User groups** `fmgd_user_group` **User groups - match** `fmgd_user_group_match` **LDAP server entries** `fmgd_user_ldap` **Local users** `fmgd_user_local` **OpenID Connect server entry configuration** `fmgd_user_oidc` **User password policy** `fmgd_user_passwordpolicy` **Peer users** `fmgd_user_peer` **Peer groups** `fmgd_user_peergrp` **POP3 server entry configuration** `fmgd_user_pop3` **Quarantine support** `fmgd_user_quarantine` **Quarantine support - targets** `fmgd_user_quarantine_targets` **Quarantine support - targets - macs** `fmgd_user_quarantine_targets_macs` **RADIUS server entries** `fmgd_user_radius` **RADIUS server entries - accounting server** `fmgd_user_radius_accountingserver` **SAML server entry configuration** `fmgd_user_saml` **SCIM client entries** `fmgd_user_scim` **Security exemption list** `fmgd_user_securityexemptlist` **Security exemption list - rule** `fmgd_user_securityexemptlist_rule` **User authentication setting - auth ports** `fmgd_user_setting_authports` **TACACS+ server entries** `fmgd_user_tacacs`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Manage administrators and access profiles

Description	Create administrator accounts, access profiles, API users, SSO administrators and password and SSH settings for device management.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Access profiles for system administrators** `fmgd_system_accprofile` **Access profiles for system administrators - firewall group permission** `fmgd_system_accprofile_fwgrppermission` **Access profiles for system administrators - log group permission** `fmgd_system_accprofile_loggrppermission` **Access profiles for system administrators - net group permission** `fmgd_system_accprofile_netgrppermission` **Access profiles for system administrators - Security Fabric group permission** `fmgd_system_accprofile_secfabgrppermission` **Access profiles for system administrators - system group permission** `fmgd_system_accprofile_sysgrppermission` **Access profiles for system administrators - UTM group permission** `fmgd_system_accprofile_utmgrppermission` **Admin users** `fmgd_system_admin` **Admin users - trusthosts** `fmgd_system_admin_trusthosts` **API users** `fmgd_system_apiuser` **API users - trusthost** `fmgd_system_apiuser_trusthost` **Password policy** `fmgd_system_passwordpolicy` **Password policy for guest administrators** `fmgd_system_passwordpolicyguestadmin` **SSH config** `fmgd_system_sshconfig` **SSO admin users** `fmgd_system_ssoadmin` **FortiCloud SSO administrators** `fmgd_system_ssoforticloudadmin` **FortiGate Cloud SSO administrators** `fmgd_system_ssofortigatecloudadmin`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Integrate the Security Fabric, FortiGuard and firmware updates

Description	Configure the Security Fabric, FortiGuard, FortiSandbox and other Fortinet service connections, update schedules and device firmware upgrades.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**USB auto installation** `fmgd_system_autoinstall` **Auto script** `fmgd_system_autoscript` **Push updates** `fmgd_system_autoupdate_pushupdate` **Update schedule** `fmgd_system_autoupdate_schedule` **Web proxy tunneling for the FDN** `fmgd_system_autoupdate_tunneling` **Central management** `fmgd_system_centralmanagement` **Central management - server list** `fmgd_system_centralmanagement_serverlist` **System cloud service** `fmgd_system_cloudservice` **Security Fabric (CSF)** `fmgd_system_csf` **Security Fabric (CSF) - fabric connector** `fmgd_system_csf_fabricconnector` **Security Fabric (CSF) - fabric datasource exemption** `fmgd_system_csf_fabricdatasourceexemption` **Security Fabric (CSF) - fabric device** `fmgd_system_csf_fabricdevice` **Security Fabric (CSF) - shared objects** `fmgd_system_csf_sharedobjects` **Security Fabric (CSF) - shared objects - objects** `fmgd_system_csf_sharedobjects_objects` **Security Fabric (CSF) - shared objects - objects - keys** `fmgd_system_csf_sharedobjects_objects_keys` **Security Fabric (CSF) - trusted list** `fmgd_system_csf_trustedlist` **Independent upgrades for managed devices** `fmgd_system_deviceupgrade` **Independent upgrades for managed devices - known HA members** `fmgd_system_deviceupgrade_knownhamembers` **Device upgrade exemptions** `fmgd_system_deviceupgradeexemptions` **Coordinate federated upgrades within the Security Fabric** `fmgd_system_federatedupgrade` **Coordinate federated upgrades within the Security Fabric - known HA members** `fmgd_system_federatedupgrade_knownhamembers` **Coordinate federated upgrades within the Security Fabric - nodelist** `fmgd_system_federatedupgrade_nodelist` **FortiAI** `fmgd_system_fortiai` **FortiData** `fmgd_system_fortidata` **FortiGuard services** `fmgd_system_fortiguard` **FortiMQ settings** `fmgd_system_fortimq` **FortiNDR** `fmgd_system_fortindr` **FortiSandbox** `fmgd_system_fortisandbox` **FortiToken Mobile push services** `fmgd_system_ftmpush` **SD-WAN status checking or health checking** `fmgd_system_healthcheckfortiguard` **Settings for individual Security Rating controls** `fmgd_system_securityrating_controls` **Settings for Security Rating** `fmgd_system_securityrating_settings`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Automate with stitches and integrate cloud and SDN platforms

Description	Configure automation triggers, conditions, actions and stitches, notifications, and SDN connectors for AWS, Azure and NSX.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Automation setting configuration** `fmgd_automation_setting` **AWS VPC configuration** `fmgd_aws_vpc` **Azure vWAN SLB ingress public IPs** `fmgd_azure_vwaningresspublicips` **Azure vWAN slb setting** `fmgd_azure_vwanslb` **Azure vWAN slb setting - permanent security rules** `fmgd_azure_vwanslb_permanentsecurityrules` **Azure vWAN slb setting - permanent security rules - rules** `fmgd_azure_vwanslb_permanentsecurityrules_rules` **Azure vWAN slb setting - temporary security rules** `fmgd_azure_vwanslb_temporarysecurityrules` **Azure vWAN slb setting - temporary security rules - rules** `fmgd_azure_vwanslb_temporarysecurityrules_rules` **Event notification configuration** `fmgd_notification` **NSX Profile** `fmgd_nsx_profile` **NSX-T service chain** `fmgd_nsxt_servicechain` **NSX-T service chain - service index** `fmgd_nsxt_servicechain_serviceindex` **NSX-T setting** `fmgd_nsxt_setting` **Action for automation stitches** `fmgd_system_automationaction` **Action for automation stitches - form data** `fmgd_system_automationaction_formdata` **Action for automation stitches - HTTP headers** `fmgd_system_automationaction_httpheaders` **Condition for automation stitches** `fmgd_system_automationcondition` **Automation destinations** `fmgd_system_automationdestination` **Automation stitches** `fmgd_system_automationstitch` **Automation stitches - actions** `fmgd_system_automationstitch_actions` **Trigger for automation stitches** `fmgd_system_automationtrigger` **Trigger for automation stitches - fields** `fmgd_system_automationtrigger_fields` **System auto-scaling** `fmgd_system_autoscale` **Connection to SDN Connector** `fmgd_system_sdnconnector` **Connection to SDN Connector - compartment list** `fmgd_system_sdnconnector_compartmentlist` **Connection to SDN Connector - external account list** `fmgd_system_sdnconnector_externalaccountlist` **Connection to SDN Connector - forwarding rule** `fmgd_system_sdnconnector_forwardingrule` **Connection to SDN Connector - oci region list** `fmgd_system_sdnconnector_ociregionlist` **Connection to SDN Connector - route table** `fmgd_system_sdnconnector_routetable` **SDN proxy** `fmgd_system_sdnproxy` **Public cloud VPN service** `fmgd_system_sdnvpn` **System VPC configuration** `fmgd_system_vpce`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure interfaces, zones, DHCP and addressing

Description	Configure physical, VLAN and virtual interfaces, zones, modems, LLDP, DHCP servers and relays, IPAM and neighbor and ARP settings.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**3G MODEM custom** `fmgd_system_3gmodem_custom` **USB 5G modems** `fmgd_system_5gmodem` **USB 5G modems - dataplan** `fmgd_system_5gmodem_dataplan` **USB 5G modems - modem 1** `fmgd_system_5gmodem_modem1` **USB 5G modems - modem 1 SIM switch** `fmgd_system_5gmodem_modem1_simswitch` **USB 5G modems - modem 2** `fmgd_system_5gmodem_modem2` **ARP table** `fmgd_system_arptable` **System bypass** `fmgd_system_bypass` **Dedicated management** `fmgd_system_dedicatedmgmt` **DHCPv6 servers** `fmgd_system_dhcp6_server` **DHCPv6 servers - IP range** `fmgd_system_dhcp6_server_iprange` **DHCPv6 servers - options** `fmgd_system_dhcp6_server_options` **DHCPv6 servers - prefix range** `fmgd_system_dhcp6_server_prefixrange` **DHCP servers** `fmgd_system_dhcp_server` **DHCP servers - exclude range** `fmgd_system_dhcp_server_excluderange` **DHCP servers - IP range** `fmgd_system_dhcp_server_iprange` **DHCP servers - options** `fmgd_system_dhcp_server_options` **DHCP servers - reserved address** `fmgd_system_dhcp_server_reservedaddress` **DHCP server templates** `fmgd_system_dhcp_template` **DHCP server templates - exclude range** `fmgd_system_dhcp_template_excluderange` **DHCP server templates - IP range** `fmgd_system_dhcp_template_iprange` **DHCP server templates - options** `fmgd_system_dhcp_template_options` **DHCP server templates - reserved address** `fmgd_system_dhcp_template_reservedaddress` **Digital I/O** `fmgd_system_digitalio` **DNP3 proxy settings** `fmgd_system_dnp3proxy` **Interfaces** `fmgd_system_interface` **Interfaces - client options** `fmgd_system_interface_clientoptions` **Interfaces - DHCP snooping server list** `fmgd_system_interface_dhcpsnoopingserverlist` **Interfaces - egress queues** `fmgd_system_interface_egressqueues` **Interfaces - IPv6** `fmgd_system_interface_ipv6` **Interfaces - IPv6 - client options** `fmgd_system_interface_ipv6_clientoptions` **Interfaces - IPv6 - DHCPv6 iapd list** `fmgd_system_interface_ipv6_dhcp6iapdlist` **Interfaces - IPv6 - IPv6 delegated prefix list** `fmgd_system_interface_ipv6_ip6delegatedprefixlist` **Interfaces - IPv6 - IPv6 dnssl list** `fmgd_system_interface_ipv6_ip6dnssllist` **Interfaces - IPv6 - IPv6 extra addr** `fmgd_system_interface_ipv6_ip6extraaddr` **Interfaces - IPv6 - IPv6 prefix list** `fmgd_system_interface_ipv6_ip6prefixlist` **Interfaces - IPv6 - IPv6 rdnss list** `fmgd_system_interface_ipv6_ip6rdnsslist` **Interfaces - IPv6 - IPv6 route list** `fmgd_system_interface_ipv6_ip6routelist` **Interfaces - IPv6 - vrrp (IPv6)** `fmgd_system_interface_ipv6_vrrp6` **Interfaces - L2TP client settings** `fmgd_system_interface_l2tpclientsettings` **Interfaces - mirroring filter** `fmgd_system_interface_mirroringfilter` **Interfaces - secondary IP** `fmgd_system_interface_secondaryip` **Interfaces - tagging** `fmgd_system_interface_tagging` **Interfaces - vrrp** `fmgd_system_interface_vrrp` **Interfaces - vrrp - proxy ARP** `fmgd_system_interface_vrrp_proxyarp` **Interfaces - wifinetworks** `fmgd_system_interface_wifinetworks` **IP address management services** `fmgd_system_ipam` **IP address management services - pools** `fmgd_system_ipam_pools` **IP address management services - pools - exclude** `fmgd_system_ipam_pools_exclude` **IP address management services - rules** `fmgd_system_ipam_rules` **IPv6 neighbor cache table** `fmgd_system_ipv6neighborcache` **LLDP network policy** `fmgd_system_lldp_networkpolicy` **LLDP network policy - guest** `fmgd_system_lldp_networkpolicy_guest` **LLDP network policy - guest voice signaling** `fmgd_system_lldp_networkpolicy_guestvoicesignaling` **LLDP network policy - softphone** `fmgd_system_lldp_networkpolicy_softphone` **LLDP network policy - streaming video** `fmgd_system_lldp_networkpolicy_streamingvideo` **LLDP network policy - video conferencing** `fmgd_system_lldp_networkpolicy_videoconferencing` **LLDP network policy - video signaling** `fmgd_system_lldp_networkpolicy_videosignaling` **LLDP network policy - voice** `fmgd_system_lldp_networkpolicy_voice` **LLDP network policy - voice signaling** `fmgd_system_lldp_networkpolicy_voicesignaling` **USB LTE/WIMAX devices** `fmgd_system_ltemodem` **USB LTE/WIMAX devices - dataplan** `fmgd_system_ltemodem_dataplan` **USB LTE/WIMAX devices - simswitch** `fmgd_system_ltemodem_simswitch` **MAC address tables** `fmgd_system_macaddresstable` **Modem** `fmgd_system_modem` **IPv6 neighbor discovery proxy** `fmgd_system_ndproxy` **Physical switches** `fmgd_system_physicalswitch` **PPPoE interfaces** `fmgd_system_pppoeinterface` **Proxy ARP** `fmgd_system_proxyarp` **Device system span port** `fmgd_system_spanport` **Split port mode of ports** `fmgd_system_splitportmode` **Spanning Tree Protocol** `fmgd_system_stp` **Switch interface** `fmgd_system_switchinterface` **Virtual hardware switch interfaces** `fmgd_system_virtualswitch` **Virtual hardware switch interfaces - port** `fmgd_system_virtualswitch_port` **Virtual wire pairs** `fmgd_system_virtualwirepair` **WCCP** `fmgd_system_wccp` **Zones to group two or more interfaces** `fmgd_system_zone` **Zones to group two or more interfaces - tagging** `fmgd_system_zone_tagging`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure SD-WAN and link health

Description	Configure SD-WAN zones, members, health checks and rules, virtual WAN link, link monitors and speed tests.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Link Health Monitor** `fmgd_system_linkmonitor` **Link Health Monitor - server list** `fmgd_system_linkmonitor_serverlist` **SD-WAN** `fmgd_system_sdwan` **SD-WAN - duplication** `fmgd_system_sdwan_duplication` **SD-WAN - health check** `fmgd_system_sdwan_healthcheck` **SD-WAN - health check - sla** `fmgd_system_sdwan_healthcheck_sla` **SD-WAN - health check FortiGuard** `fmgd_system_sdwan_healthcheckfortiguard` **SD-WAN - health check FortiGuard - sla** `fmgd_system_sdwan_healthcheckfortiguard_sla` **SD-WAN - members** `fmgd_system_sdwan_members` **SD-WAN - neighbor** `fmgd_system_sdwan_neighbor` **SD-WAN - service** `fmgd_system_sdwan_service` **SD-WAN - service - sla** `fmgd_system_sdwan_service_sla` **SD-WAN - zone** `fmgd_system_sdwan_zone` **Speed test schedule for each interface** `fmgd_system_speedtestschedule` **Speed test server list** `fmgd_system_speedtestserver` **Speed test server list - host** `fmgd_system_speedtestserver_host` **Speed test setting** `fmgd_system_speedtestsetting` **Redundant internet connections using SD-WAN** `fmgd_system_virtualwanlink` **Redundant internet connections using SD-WAN - health check** `fmgd_system_virtualwanlink_healthcheck` **Redundant internet connections using SD-WAN - health check - sla** `fmgd_system_virtualwanlink_healthcheck_sla` **Redundant internet connections using SD-WAN - members** `fmgd_system_virtualwanlink_members` **Redundant internet connections using SD-WAN - neighbor** `fmgd_system_virtualwanlink_neighbor` **Redundant internet connections using SD-WAN - service** `fmgd_system_virtualwanlink_service` **Redundant internet connections using SD-WAN - service - sla** `fmgd_system_virtualwanlink_service_sla`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure high availability, clustering and hardware acceleration

Description	Configure HA and cluster synchronisation, standalone clusters, load balancing, NPU and DPDK acceleration and hardware monitoring.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**CPUs** `fmgd_dpdk_cpus` **Global DPDK options** `fmgd_dpdk_global` **Flow rule configuration** `fmgd_loadbalance_flowrule` **Load balance setting** `fmgd_loadbalance_setting` **Load balance setting - workers** `fmgd_loadbalance_setting_workers` **Worker group configuration** `fmgd_loadbalance_workergroup` **NP6 IPsec engine status monitoring** `fmgd_monitoring_np6ipsecengine` **NPU-hpe status monitoring** `fmgd_monitoring_npuhpe` **Interrupt affinity** `fmgd_system_affinityinterrupt` **Packet redistribution** `fmgd_system_affinitypacketredistribution` **Cluster session synchronisation** `fmgd_system_clustersync` **Cluster session synchronisation - session sync filter** `fmgd_system_clustersync_sessionsyncfilter` **Cluster session synchronisation - session sync filter - custom service** `fmgd_system_clustersync_sessionsyncfilter_customservice` **Enhanced load balance cluster** `fmgd_system_elbc` **FIPS-CC mode** `fmgd_system_fipscc` **Gi firewall gatekeeper** `fmgd_system_gigk` **High availability (HA)** `fmgd_system_ha` **High availability (HA) - frup settings** `fmgd_system_ha_frupsettings` **High availability (HA) - HA mgmt interfaces** `fmgd_system_ha_hamgmtinterfaces` **High availability (HA) - link group** `fmgd_system_ha_linkgroup` **High availability (HA) - secondary virtual cluster** `fmgd_system_ha_secondaryvcluster` **High availability (HA) - unicast peers** `fmgd_system_ha_unicastpeers` **High availability (HA) - virtual cluster** `fmgd_system_ha_vcluster` **HA licenses** `fmgd_system_halic` **HA monitoring** `fmgd_system_hamonitor` **System iSCSI** `fmgd_system_iscsi` **Create a queue profile of switch** `fmgd_system_isfqueueprofile` **Memory manager** `fmgd_system_memmgr` **NP6 attributes** `fmgd_system_np6` **NP6 attributes - fpanomaly** `fmgd_system_np6_fpanomaly` **NP6 attributes - hpe** `fmgd_system_np6_hpe` **NP6XLITE attributes** `fmgd_system_np6xlite` **NP6XLITE attributes - fpanomaly** `fmgd_system_np6xlite_fpanomaly` **NP6XLITE attributes - hpe** `fmgd_system_np6xlite_hpe` **NPU DSW DTS profile** `fmgd_system_npu_dswdtsprofile` **Queue assignment on NP7LITE** `fmgd_system_npu_npqueues` **NPU interface to CPU core mapping** `fmgd_system_npu_portcpumap` **Port to NPU group mapping** `fmgd_system_npu_portnpumap` **NPU attributes after interface initialization** `fmgd_system_npupost` **NPU attributes after interface initialization - port NPU map** `fmgd_system_npupost_portnpumap` **NPU PRP attributes** `fmgd_system_npusetting_prp` **NPU VDOM link** `fmgd_system_npuvlink` **Session helper** `fmgd_system_sessionhelper` **Global session TTL timers for this FortiGate** `fmgd_system_sessionttl` **Global session TTL timers for this FortiGate - port** `fmgd_system_sessionttl_port` **FortiGate Session Life Support Protocol** `fmgd_system_standalonecluster` **FortiGate Session Life Support Protocol - cluster peer** `fmgd_system_standalonecluster_clusterpeer` **FortiGate Session Life Support Protocol - cluster peer - session sync filter** `fmgd_system_standalonecluster_clusterpeer_sessionsyncfilter` **FortiGate Session Life Support Protocol - cluster peer - session sync filter custom service** `fmgd_system_standalonecluster_clusterpeer_sessionsyncfilter_customse` **FortiGate Session Life Support Protocol - monitor prefix** `fmgd_system_standalonecluster_monitorprefix` **Logical storage** `fmgd_system_storage`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Forward logs to FortiAnalyzer, syslog and cloud services

Description	Configure log forwarding to FortiAnalyzer, FortiGuard, syslog servers, TACACS+ accounting, WebTrends and Azure Security Center.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Azure Security Center (second) - filter** `fmgd_log_azuresecuritycenter2_filter` **Azure Security Center (second) - filter free style** `fmgd_log_azuresecuritycenter2_filter_freestyle` **Azure Security Center (second) - setting** `fmgd_log_azuresecuritycenter2_setting` **Azure Security Center (second) - setting custom field name** `fmgd_log_azuresecuritycenter2_setting_customfieldname` **Azure Security Center - filter** `fmgd_log_azuresecuritycenter_filter` **Azure Security Center - filter free style** `fmgd_log_azuresecuritycenter_filter_freestyle` **Azure Security Center - setting** `fmgd_log_azuresecuritycenter_setting` **Azure Security Center - setting custom field name** `fmgd_log_azuresecuritycenter_setting_customfieldname` **FortiAnalyzer 2 - filter** `fmgd_log_fortianalyzer2_filter` **FortiAnalyzer 2 - filter free style** `fmgd_log_fortianalyzer2_filter_freestyle` **FortiAnalyzer 2 - override filter** `fmgd_log_fortianalyzer2_overridefilter` **FortiAnalyzer 2 - override filter free style** `fmgd_log_fortianalyzer2_overridefilter_freestyle` **FortiAnalyzer 2 - override setting** `fmgd_log_fortianalyzer2_overridesetting` **FortiAnalyzer 2 - setting** `fmgd_log_fortianalyzer2_setting` **FortiAnalyzer 3 - filter** `fmgd_log_fortianalyzer3_filter` **FortiAnalyzer 3 - filter free style** `fmgd_log_fortianalyzer3_filter_freestyle` **FortiAnalyzer 3 - override filter** `fmgd_log_fortianalyzer3_overridefilter` **FortiAnalyzer 3 - override filter free style** `fmgd_log_fortianalyzer3_overridefilter_freestyle` **FortiAnalyzer 3 - override setting** `fmgd_log_fortianalyzer3_overridesetting` **FortiAnalyzer 3 - setting** `fmgd_log_fortianalyzer3_setting` **FortiAnalyzer - filter** `fmgd_log_fortianalyzer_filter` **FortiAnalyzer - filter free style** `fmgd_log_fortianalyzer_filter_freestyle` **FortiAnalyzer - override filter** `fmgd_log_fortianalyzer_overridefilter` **FortiAnalyzer - override filter free style** `fmgd_log_fortianalyzer_overridefilter_freestyle` **FortiAnalyzer - override setting** `fmgd_log_fortianalyzer_overridesetting` **FortiAnalyzer - setting** `fmgd_log_fortianalyzer_setting` **FortiAnalyzer Cloud - filter** `fmgd_log_fortianalyzercloud_filter` **FortiAnalyzer Cloud - filter free style** `fmgd_log_fortianalyzercloud_filter_freestyle` **FortiAnalyzer Cloud - override filter** `fmgd_log_fortianalyzercloud_overridefilter` **FortiAnalyzer Cloud - override filter free style** `fmgd_log_fortianalyzercloud_overridefilter_freestyle` **FortiAnalyzer Cloud - override setting** `fmgd_log_fortianalyzercloud_overridesetting` **FortiAnalyzer Cloud - setting** `fmgd_log_fortianalyzercloud_setting` **syslog server 2 - filter** `fmgd_log_syslogd2_filter` **syslog server 2 - filter free style** `fmgd_log_syslogd2_filter_freestyle` **syslog server 2 - override filter** `fmgd_log_syslogd2_overridefilter` **syslog server 2 - override filter free style** `fmgd_log_syslogd2_overridefilter_freestyle` **syslog server 2 - override setting** `fmgd_log_syslogd2_overridesetting` **syslog server 2 - override setting custom field name** `fmgd_log_syslogd2_overridesetting_customfieldname` **syslog server 2 - override setting log templates** `fmgd_log_syslogd2_overridesetting_logtemplates` **syslog server 2 - setting** `fmgd_log_syslogd2_setting` **syslog server 2 - setting custom field name** `fmgd_log_syslogd2_setting_customfieldname` **syslog server 2 - setting log templates** `fmgd_log_syslogd2_setting_logtemplates` **syslog server 3 - filter** `fmgd_log_syslogd3_filter` **syslog server 3 - filter free style** `fmgd_log_syslogd3_filter_freestyle` **syslog server 3 - override filter** `fmgd_log_syslogd3_overridefilter` **syslog server 3 - override filter free style** `fmgd_log_syslogd3_overridefilter_freestyle` **syslog server 3 - override setting** `fmgd_log_syslogd3_overridesetting` **syslog server 3 - override setting custom field name** `fmgd_log_syslogd3_overridesetting_customfieldname` **syslog server 3 - override setting log templates** `fmgd_log_syslogd3_overridesetting_logtemplates` **syslog server 3 - setting** `fmgd_log_syslogd3_setting` **syslog server 3 - setting custom field name** `fmgd_log_syslogd3_setting_customfieldname` **syslog server 3 - setting log templates** `fmgd_log_syslogd3_setting_logtemplates` **syslog server 4 - filter** `fmgd_log_syslogd4_filter` **syslog server 4 - filter free style** `fmgd_log_syslogd4_filter_freestyle` **syslog server 4 - override filter** `fmgd_log_syslogd4_overridefilter` **syslog server 4 - override filter free style** `fmgd_log_syslogd4_overridefilter_freestyle` **syslog server 4 - override setting** `fmgd_log_syslogd4_overridesetting` **syslog server 4 - override setting custom field name** `fmgd_log_syslogd4_overridesetting_customfieldname` **syslog server 4 - override setting log templates** `fmgd_log_syslogd4_overridesetting_logtemplates` **syslog server 4 - setting** `fmgd_log_syslogd4_setting` **syslog server 4 - setting custom field name** `fmgd_log_syslogd4_setting_customfieldname` **syslog server 4 - setting log templates** `fmgd_log_syslogd4_setting_logtemplates` **syslog server 1 - filter** `fmgd_log_syslogd_filter` **syslog server 1 - filter free style** `fmgd_log_syslogd_filter_freestyle` **syslog server 1 - override filter** `fmgd_log_syslogd_overridefilter` **syslog server 1 - override filter free style** `fmgd_log_syslogd_overridefilter_freestyle` **syslog server 1 - override setting** `fmgd_log_syslogd_overridesetting` **syslog server 1 - override setting custom field name** `fmgd_log_syslogd_overridesetting_customfieldname` **syslog server 1 - override setting log templates** `fmgd_log_syslogd_overridesetting_logtemplates` **syslog server 1 - setting** `fmgd_log_syslogd_setting` **syslog server 1 - setting custom field name** `fmgd_log_syslogd_setting_customfieldname` **syslog server 1 - setting log templates** `fmgd_log_syslogd_setting_logtemplates` **TACACS+ accounting 2 - filter** `fmgd_log_tacacsaccounting2_filter` **TACACS+ accounting 2 - setting** `fmgd_log_tacacsaccounting2_setting` **TACACS+ accounting 3 - filter** `fmgd_log_tacacsaccounting3_filter` **TACACS+ accounting 3 - setting** `fmgd_log_tacacsaccounting3_setting` **TACACS+ accounting 1 - filter** `fmgd_log_tacacsaccounting_filter` **TACACS+ accounting 1 - setting** `fmgd_log_tacacsaccounting_setting`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure local logging, alerts and reports

Description	Configure disk and memory logging, log settings and filters, threat weights, alert email, and report charts, datasets, layouts and themes.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Alert email settings** `fmgd_alertemail_setting` **Custom log fields** `fmgd_log_customfield` **Custom log formats** `fmgd_log_customformat` **Custom log formats - log templates** `fmgd_log_customformat_logtemplates` **Filters for local disk logging** `fmgd_log_disk_filter` **Filters for local disk logging - free style** `fmgd_log_disk_filter_freestyle` **Settings for local disk logging** `fmgd_log_disk_setting` **Log event filters** `fmgd_log_eventfilter` **FortiGuard (FortiCloud) logging - filter** `fmgd_log_fortiguard_filter` **FortiGuard (FortiCloud) logging - filter free style** `fmgd_log_fortiguard_filter_freestyle` **FortiGuard (FortiCloud) logging - override filter** `fmgd_log_fortiguard_overridefilter` **FortiGuard (FortiCloud) logging - override filter free style** `fmgd_log_fortiguard_overridefilter_freestyle` **FortiGuard (FortiCloud) logging - override setting** `fmgd_log_fortiguard_overridesetting` **FortiGuard (FortiCloud) logging - setting** `fmgd_log_fortiguard_setting` **GUI log display** `fmgd_log_guidisplay` **Filters for memory buffer** `fmgd_log_memory_filter` **Filters for memory buffer - free style** `fmgd_log_memory_filter_freestyle` **Global settings for memory logging** `fmgd_log_memory_globalsetting` **Settings for memory buffer** `fmgd_log_memory_setting` **Filters for null device logging** `fmgd_log_nulldevice_filter` **Filters for null device logging - free style** `fmgd_log_nulldevice_filter_freestyle` **Settings for null device logging** `fmgd_log_nulldevice_setting` **General log settings** `fmgd_log_setting` **LOG Global settings for SLBC platform** `fmgd_log_slbc_globalsetting` **Threat weight settings** `fmgd_log_threatweight` **Threat weight settings - application** `fmgd_log_threatweight_application` **Threat weight settings - geolocation** `fmgd_log_threatweight_geolocation` **Threat weight settings - IPS** `fmgd_log_threatweight_ips` **Threat weight settings - level** `fmgd_log_threatweight_level` **Threat weight settings - malware** `fmgd_log_threatweight_malware` **Threat weight settings - web** `fmgd_log_threatweight_web` **Filters for WebTrends** `fmgd_log_webtrends_filter` **Filters for WebTrends - free style** `fmgd_log_webtrends_filter_freestyle` **Settings for WebTrends** `fmgd_log_webtrends_setting` **Report chart widget configuration** `fmgd_report_chart` **Report chart widget configuration - category series** `fmgd_report_chart_categoryseries` **Report chart widget configuration - column** `fmgd_report_chart_column` **Report chart widget configuration - column - mapping** `fmgd_report_chart_column_mapping` **Report chart widget configuration - drill down charts** `fmgd_report_chart_drilldowncharts` **Report chart widget configuration - value series** `fmgd_report_chart_valueseries` **Report chart widget configuration - xseries** `fmgd_report_chart_xseries` **Report chart widget configuration - yseries** `fmgd_report_chart_yseries` **Report dataset configuration** `fmgd_report_dataset` **Report dataset configuration - field** `fmgd_report_dataset_field` **Report dataset configuration - parameters** `fmgd_report_dataset_parameters` **Report layout configuration** `fmgd_report_layout` **Report layout configuration - body item** `fmgd_report_layout_bodyitem`, `fmgd_report_layout_bodyitem_list` **Report layout configuration - body item - parameters** `fmgd_report_layout_bodyitem_parameters` **Report layout configuration - page** `fmgd_report_layout_page` **Report layout configuration - page - footer** `fmgd_report_layout_page_footer` **Report layout configuration - page - footer - footer item** `fmgd_report_layout_page_footer_footeritem` **Report layout configuration - page - header** `fmgd_report_layout_page_header` **Report layout configuration - page - header - header item** `fmgd_report_layout_page_header_headeritem` **Report setting configuration** `fmgd_report_setting` **Report style configuration** `fmgd_report_style` **Report themes configuration** `fmgd_report_theme`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Monitor with SNMP, NetFlow, sFlow and Ethernet OAM

Description	Configure SNMP agents, communities and users, NetFlow and sFlow export, network visibility and Ethernet OAM connectivity checks.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**CFM domain configuration** `fmgd_ethernetoam_cfm` **CFM domain configuration - service** `fmgd_ethernetoam_cfm_service` **NetFlow** `fmgd_system_netflow` **NetFlow - collectors** `fmgd_system_netflow_collectors` **NetFlow - exclusion filters** `fmgd_system_netflow_exclusionfilters` **Network visibility settings** `fmgd_system_networkvisibility` **sFlow** `fmgd_system_sflow` **sFlow - collectors** `fmgd_system_sflow_collectors` **SNMP community configuration** `fmgd_system_snmp_community` **SNMP community configuration - hosts** `fmgd_system_snmp_community_hosts` **SNMP community configuration - hosts (IPv6)** `fmgd_system_snmp_community_hosts6` **SNMP Access Control MIB View configuration** `fmgd_system_snmp_mibview` **SNMP Remote Network Monitoring** `fmgd_system_snmp_rmonstat` **SNMP system info configuration** `fmgd_system_snmp_sysinfo` **SNMP user configuration** `fmgd_system_snmp_user` **NetFlow per VDOM** `fmgd_system_vdomnetflow` **NetFlow per VDOM - collectors** `fmgd_system_vdomnetflow_collectors` **VDOM sFlow** `fmgd_system_vdomsflow` **VDOM sFlow - collectors** `fmgd_system_vdomsflow_collectors`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Manage FortiSwitch units and fleet settings

Description	Authorise and configure managed FortiSwitches, ports, groups and profiles, FortiLink, initial and auto configuration, locations and PTP.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Auto config custom** `fmgd_switchcontroller_autoconfig_custom` **Auto config custom - switch binding** `fmgd_switchcontroller_autoconfig_custom_switchbinding` **Auto config default** `fmgd_switchcontroller_autoconfig_default` **Auto config policy** `fmgd_switchcontroller_autoconfig_policy` **Custom command** `fmgd_switchcontroller_customcommand` **DSL policy** `fmgd_switchcontroller_dsl_policy` **Integrated FortiLink settings for FortiSwitch** `fmgd_switchcontroller_fortilinksettings` **Integrated FortiLink settings for FortiSwitch - NAC ports** `fmgd_switchcontroller_fortilinksettings_nacports` **FortiSwitch global settings** `fmgd_switchcontroller_global` **Template for auto-generated VLANs** `fmgd_switchcontroller_initialconfig_template` **Initial template for auto-generated VLAN interfaces** `fmgd_switchcontroller_initialconfig_vlans` **FortiSwitch location services** `fmgd_switchcontroller_location` **FortiSwitch location services - address civic** `fmgd_switchcontroller_location_addresscivic` **FortiSwitch location services - coordinates** `fmgd_switchcontroller_location_coordinates` **FortiSwitch location services - elin number** `fmgd_switchcontroller_location_elinnumber` **Managed FortiSwitches** `fmgd_switchcontroller_managedswitch` **Managed FortiSwitches - 802.1X settings** `fmgd_switchcontroller_managedswitch_8021xsettings` **Managed FortiSwitches - components** `fmgd_switchcontroller_managedswitch_components` **Managed FortiSwitches - custom command** `fmgd_switchcontroller_managedswitch_customcommand` **Managed FortiSwitches - DHCP snooping static client** `fmgd_switchcontroller_managedswitch_dhcpsnoopingstaticclient` **Managed FortiSwitches - IGMP snooping** `fmgd_switchcontroller_managedswitch_igmpsnooping` **Managed FortiSwitches - IGMP snooping - vlans** `fmgd_switchcontroller_managedswitch_igmpsnooping_vlans` **Managed FortiSwitches - IP source guard** `fmgd_switchcontroller_managedswitch_ipsourceguard` **Managed FortiSwitches - IP source guard - binding entry** `fmgd_switchcontroller_managedswitch_ipsourceguard_bindingentry` **Managed FortiSwitches - mirror** `fmgd_switchcontroller_managedswitch_mirror` **Managed FortiSwitches - ports** `fmgd_switchcontroller_managedswitch_ports` **Managed FortiSwitches - ports - DHCP snoop option82 override** `fmgd_switchcontroller_managedswitch_ports_dhcpsnoopoption82override` **Managed FortiSwitches - remote log** `fmgd_switchcontroller_managedswitch_remotelog` **Managed FortiSwitches - route offload router** `fmgd_switchcontroller_managedswitch_routeoffloadrouter` **Managed FortiSwitches - router static** `fmgd_switchcontroller_managedswitch_routerstatic` **Managed FortiSwitches - router vrf** `fmgd_switchcontroller_managedswitch_routervrf` **Managed FortiSwitches - SNMP community** `fmgd_switchcontroller_managedswitch_snmpcommunity` **Managed FortiSwitches - SNMP community - hosts** `fmgd_switchcontroller_managedswitch_snmpcommunity_hosts` **Managed FortiSwitches - SNMP system info** `fmgd_switchcontroller_managedswitch_snmpsysinfo` **Managed FortiSwitches - SNMP trap threshold** `fmgd_switchcontroller_managedswitch_snmptrapthreshold` **Managed FortiSwitches - SNMP user** `fmgd_switchcontroller_managedswitch_snmpuser` **Managed FortiSwitches - static MAC** `fmgd_switchcontroller_managedswitch_staticmac` **Managed FortiSwitches - storm control** `fmgd_switchcontroller_managedswitch_stormcontrol` **Managed FortiSwitches - STP instance** `fmgd_switchcontroller_managedswitch_stpinstance` **Managed FortiSwitches - STP settings** `fmgd_switchcontroller_managedswitch_stpsettings` **Managed FortiSwitches - switch log** `fmgd_switchcontroller_managedswitch_switchlog` **Managed FortiSwitches - system DHCP server** `fmgd_switchcontroller_managedswitch_systemdhcpserver` **Managed FortiSwitches - system DHCP server - IP range** `fmgd_switchcontroller_managedswitch_systemdhcpserver_iprange` **Managed FortiSwitches - system DHCP server - options** `fmgd_switchcontroller_managedswitch_systemdhcpserver_options` **Managed FortiSwitches - system interface** `fmgd_switchcontroller_managedswitch_systeminterface` **Managed FortiSwitches - VLAN** `fmgd_switchcontroller_managedswitch_vlan` **PTP interface-policy configuration** `fmgd_switchcontroller_ptp_interfacepolicy` **PTP policy configuration** `fmgd_switchcontroller_ptp_policy` **Global PTP profile** `fmgd_switchcontroller_ptp_profile` **Global PTP settings** `fmgd_switchcontroller_ptp_settings` **FortiSwitch switch groups** `fmgd_switchcontroller_switchgroup` **Switch object tags** `fmgd_switchcontroller_switchinterfacetag` **FortiSwitch switch profile** `fmgd_switchcontroller_switchprofile` **System-wide switch controller settings** `fmgd_switchcontroller_system` **Virtual pool** `fmgd_switchcontroller_virtualportpool`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Define FortiSwitch port, VLAN, security and monitoring policies

Description	Define FortiSwitch ACLs, QoS, 802.1X and NAC, port, VLAN and MAC policies, storm control, STP, IGMP snooping, LLDP, SNMP and logging.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)

Key content	**Global 802.1X settings** `fmgd_switchcontroller_8021xsettings` **ACL group** `fmgd_switchcontroller_acl_group` **ACL ingress** `fmgd_switchcontroller_acl_ingress` **ACL ingress - action** `fmgd_switchcontroller_acl_ingress_action` **ACL ingress - classifier** `fmgd_switchcontroller_acl_ingress_classifier` **Dynamic port policy** `fmgd_switchcontroller_dynamicportpolicy` **Dynamic port policy - policy** `fmgd_switchcontroller_dynamicportpolicy_policy` **FortiSwitch flow tracking and export via ipfix/NetFlow** `fmgd_switchcontroller_flowtracking` **FortiSwitch flow tracking and export via ipfix/NetFlow - aggregates** `fmgd_switchcontroller_flowtracking_aggregates` **FortiSwitch flow tracking and export via ipfix/NetFlow - collectors** `fmgd_switchcontroller_flowtracking_collectors` **FortiSwitch IGMP snooping global settings** `fmgd_switchcontroller_igmpsnooping` **FortiSwitch IGMP snooping static group settings** `fmgd_switchcontroller_igmpsnoopingstaticgroup` **FortiSwitch IGMP snooping static group settings - ports** `fmgd_switchcontroller_igmpsnoopingstaticgroup_ports` **FortiSwitch IP source guard log** `fmgd_switchcontroller_ipsourceguardlog` **FortiSwitch LLDP profiles** `fmgd_switchcontroller_lldpprofile` **FortiSwitch LLDP profiles - custom TLVs** `fmgd_switchcontroller_lldpprofile_customtlvs` **FortiSwitch LLDP profiles - MED location service** `fmgd_switchcontroller_lldpprofile_medlocationservice` **FortiSwitch LLDP profiles - MED network policy** `fmgd_switchcontroller_lldpprofile_mednetworkpolicy` **FortiSwitch LLDP settings** `fmgd_switchcontroller_lldpsettings` **MAC policy** `fmgd_switchcontroller_macpolicy` **NAC device** `fmgd_switchcontroller_nacdevice` **Integrated NAC settings for FortiSwitch** `fmgd_switchcontroller_nacsettings` **Network monitor settings** `fmgd_switchcontroller_networkmonitorsettings` **Port policy** `fmgd_switchcontroller_portpolicy` **QoS 802.1p maps** `fmgd_switchcontroller_qos_dot1pmap` **FortiSwitch QoS IP precedence/DSCP** `fmgd_switchcontroller_qos_ipdscpmap` **FortiSwitch QoS IP precedence/DSCP - map** `fmgd_switchcontroller_qos_ipdscpmap_map` **FortiSwitch QoS policy** `fmgd_switchcontroller_qos_qospolicy` **FortiSwitch QoS egress queue policy** `fmgd_switchcontroller_qos_queuepolicy` **FortiSwitch QoS egress queue policy - CoS queue** `fmgd_switchcontroller_qos_queuepolicy_cosqueue` **Remote log** `fmgd_switchcontroller_remotelog` **802.1X security policies** `fmgd_switchcontroller_securitypolicy_8021x` **Admin security policies** `fmgd_switchcontroller_securitypolicy_admin` **Security policy local access** `fmgd_switchcontroller_securitypolicy_localaccess` **FortiSwitch sFlow** `fmgd_switchcontroller_sflow` **FortiSwitch SNMP v1/v2c communities globally** `fmgd_switchcontroller_snmpcommunity` **FortiSwitch SNMP v1/v2c communities globally - hosts** `fmgd_switchcontroller_snmpcommunity_hosts` **FortiSwitch SNMP system information globally** `fmgd_switchcontroller_snmpsysinfo` **FortiSwitch SNMP trap threshold values globally** `fmgd_switchcontroller_snmptrapthreshold` **FortiSwitch SNMP v3 users globally** `fmgd_switchcontroller_snmpuser` **FortiSwitch storm control** `fmgd_switchcontroller_stormcontrol` **Storm control policy** `fmgd_switchcontroller_stormcontrolpolicy` **FortiSwitch multiple spanning tree protocol** `fmgd_switchcontroller_stpinstance` **FortiSwitch spanning tree protocol** `fmgd_switchcontroller_stpsettings` **FortiSwitch logging** `fmgd_switchcontroller_switchlog` **FortiSwitch traffic policy** `fmgd_switchcontroller_trafficpolicy` **FortiSwitch RSPAN/ERSPAN traffic sniffing parameters** `fmgd_switchcontroller_trafficsniffer` **FortiSwitch RSPAN/ERSPAN traffic sniffing parameters - target IP** `fmgd_switchcontroller_trafficsniffer_targetip` **FortiSwitch RSPAN/ERSPAN traffic sniffing parameters - target MAC** `fmgd_switchcontroller_trafficsniffer_targetmac` **FortiSwitch RSPAN/ERSPAN traffic sniffing parameters - target port** `fmgd_switchcontroller_trafficsniffer_targetport` **VLAN policy** `fmgd_switchcontroller_vlanpolicy`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Manage FortiAP access points and wireless controller

Description	Configure managed FortiAPs, WTP profiles and groups, controller timers, regions, inter-controller links, logging and SNMP.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Accepted wireless APs** `fmgd_system_wireless_apstatus` **Wireless radio settings** `fmgd_system_wireless_settings` **AP local configuration profiles** `fmgd_wireless_apcfgprofile` **AP local configuration profiles - command list** `fmgd_wireless_apcfgprofile_commandlist` **Access point status** `fmgd_wireless_apstatus` **WiFi Automatic Radio Resource Provisioning** `fmgd_wireless_arrppprofile` **Bluetooth Low Energy profile** `fmgd_wireless_bleprofile` **Bonjour profiles** `fmgd_wireless_bonjourprofile` **Bonjour profiles - policy list** `fmgd_wireless_bonjourprofile_policylist` **Wireless controller global settings** `fmgd_wireless_global` **Inter wireless controller operation** `fmgd_wireless_intercontroller` **Inter wireless controller operation - inter controller peer** `fmgd_wireless_intercontroller_intercontrollerpeer` **Wireless controller event log filters** `fmgd_wireless_log` **LoRaWAN profile** `fmgd_wireless_lwprofile` **FortiAP regions** `fmgd_wireless_region` **VDOM wireless controller configuration** `fmgd_wireless_setting` **VDOM wireless controller configuration - offending SSID** `fmgd_wireless_setting_offendingssid` **Wireless controller SNMP** `fmgd_wireless_snmp` **Wireless controller SNMP - community** `fmgd_wireless_snmp_community` **Wireless controller SNMP - community - hosts** `fmgd_wireless_snmp_community_hosts` **Wireless controller SNMP - community - hosts (IPv6)** `fmgd_wireless_snmp_community_hosts6` **Wireless controller SNMP - user** `fmgd_wireless_snmp_user` **Wireless syslog profiles** `fmgd_wireless_syslogprofile` **CAPWAP timers** `fmgd_wireless_timers` **Managed access points (WTPs)** `fmgd_wireless_wtp` **Managed access points (WTPs) - lan** `fmgd_wireless_wtp_lan` **Managed access points (WTPs) - radio 1** `fmgd_wireless_wtp_radio1` **Managed access points (WTPs) - radio 2** `fmgd_wireless_wtp_radio2` **Managed access points (WTPs) - radio 3** `fmgd_wireless_wtp_radio3` **Managed access points (WTPs) - radio 4** `fmgd_wireless_wtp_radio4` **Managed access points (WTPs) - split tunneling ACL** `fmgd_wireless_wtp_splittunnelingacl` **WTP groups** `fmgd_wireless_wtpgroup` **WTP profile** `fmgd_wireless_wtpprofile` **WTP profile - denymaclist** `fmgd_wireless_wtpprofile_denymaclist` **WTP profile - ESL SES dongle** `fmgd_wireless_wtpprofile_eslsesdongle` **WTP profile - lan** `fmgd_wireless_wtpprofile_lan` **WTP profile - LBS** `fmgd_wireless_wtpprofile_lbs` **WTP profile - platform** `fmgd_wireless_wtpprofile_platform` **WTP profile - radio 1** `fmgd_wireless_wtpprofile_radio1` **WTP profile - radio 2** `fmgd_wireless_wtpprofile_radio2` **WTP profile - radio 3** `fmgd_wireless_wtpprofile_radio3` **WTP profile - radio 4** `fmgd_wireless_wtpprofile_radio4` **WTP profile - split tunneling ACL** `fmgd_wireless_wtpprofile_splittunnelingacl`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Configure SSIDs, wireless security and Hotspot 2.0

Description	Configure virtual access points and groups, MPSK, WIDS, QoS, access control lists, UTM and NAC profiles and Hotspot 2.0 settings.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**WiFi bridge access control list** `fmgd_wireless_accesscontrollist` **WiFi bridge access control list - layer 3 IPv4 rules** `fmgd_wireless_accesscontrollist_layer3ipv4rules` **WiFi bridge access control list - layer 3 IPv6 rules** `fmgd_wireless_accesscontrollist_layer3ipv6rules` **3GPP public land mobile network** `fmgd_wireless_hotspot20_anqp3gppcellular` **3GPP public land mobile network - mccmnclist** `fmgd_wireless_hotspot20_anqp3gppcellular_mccmnclist` **IP address type availability** `fmgd_wireless_hotspot20_anqpipaddresstype` **Network access identifier** `fmgd_wireless_hotspot20_anqpnairealm` **Network access identifier - NAI list** `fmgd_wireless_hotspot20_anqpnairealm_nailist` **Network access identifier - NAI list - EAP method** `fmgd_wireless_hotspot20_anqpnairealm_nailist_eapmethod` **Network access identifier - NAI list - EAP method - auth param** `fmgd_wireless_hotspot20_anqpnairealm_nailist_eapmethod_authparam` **Network authentication type** `fmgd_wireless_hotspot20_anqpnetworkauthtype` **Roaming consortium** `fmgd_wireless_hotspot20_anqproamingconsortium` **Roaming consortium - OI list** `fmgd_wireless_hotspot20_anqproamingconsortium_oilist` **Venue name duple** `fmgd_wireless_hotspot20_anqpvenuename` **Venue name duple - value list** `fmgd_wireless_hotspot20_anqpvenuename_valuelist` **Venue URL** `fmgd_wireless_hotspot20_anqpvenueurl` **Venue URL - value list** `fmgd_wireless_hotspot20_anqpvenueurl_valuelist` **Advice of charge** `fmgd_wireless_hotspot20_h2qpadviceofcharge` **Advice of charge - aoc list** `fmgd_wireless_hotspot20_h2qpadviceofcharge_aoclist` **Advice of charge - aoc list - plan info** `fmgd_wireless_hotspot20_h2qpadviceofcharge_aoclist_planinfo` **Connection capability** `fmgd_wireless_hotspot20_h2qpconncapability` **Operator friendly name** `fmgd_wireless_hotspot20_h2qpoperatorname` **Operator friendly name - value list** `fmgd_wireless_hotspot20_h2qpoperatorname_valuelist` **OSU providers** `fmgd_wireless_hotspot20_h2qposuprovider` **OSU providers - friendly name** `fmgd_wireless_hotspot20_h2qposuprovider_friendlyname` **OSU providers - service description** `fmgd_wireless_hotspot20_h2qposuprovider_servicedescription` **OSU provider NAIs** `fmgd_wireless_hotspot20_h2qposuprovidernai` **OSU provider NAIs - NAI list** `fmgd_wireless_hotspot20_h2qposuprovidernai_nailist` **Terms and conditions** `fmgd_wireless_hotspot20_h2qptermsandconditions` **WAN metrics** `fmgd_wireless_hotspot20_h2qpwanmetric` **Hotspot profile** `fmgd_wireless_hotspot20_hsprofile` **OSU provider icon** `fmgd_wireless_hotspot20_icon` **OSU provider icon - icon list** `fmgd_wireless_hotspot20_icon_iconlist` **QoS map set** `fmgd_wireless_hotspot20_qosmap` **QoS map set - dscpexcept** `fmgd_wireless_hotspot20_qosmap_dscpexcept` **QoS map set - DSCP range** `fmgd_wireless_hotspot20_qosmap_dscprange` **MPSK profile** `fmgd_wireless_mpskprofile` **MPSK profile - MPSK group** `fmgd_wireless_mpskprofile_mpskgroup` **MPSK profile - MPSK group - MPSK key** `fmgd_wireless_mpskprofile_mpskgroup_mpskkey` **WiFi network access control** `fmgd_wireless_nacprofile` **WiFi quality of service** `fmgd_wireless_qosprofile` **WiFi SSID policies** `fmgd_wireless_ssidpolicy` **UTM profile** `fmgd_wireless_utmprofile` **Virtual Access Points** `fmgd_wireless_vap` **Virtual Access Points - dynamic mapping** `fmgd_wireless_vap_dynamicmapping` **Virtual Access Points - MAC filter list** `fmgd_wireless_vap_macfilterlist` **Virtual Access Points - MPSK key** `fmgd_wireless_vap_mpskkey` **Virtual Access Points - portal message overrides** `fmgd_wireless_vap_portalmessageoverrides` **Virtual Access Points - VLAN name** `fmgd_wireless_vap_vlanname` **Virtual Access Points - VLAN pool** `fmgd_wireless_vap_vlanpool` **Virtual Access Point** `fmgd_wireless_vapgroup` **Wireless access gateway** `fmgd_wireless_wagprofile` **Wireless intrusion detection system** `fmgd_wireless_widsprofile`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Manage FortiExtender and LAN extension

Description	Configure FortiExtender controllers, profiles and data plans, and extension controller connections.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Extender controller extender** `fmgd_extendercontroller_extender` **Extender controller extender - controller report** `fmgd_extendercontroller_extender_controllerreport` **Extender controller extender - modem 1** `fmgd_extendercontroller_extender_modem1` **Extender controller extender - modem 1 - autoswitch** `fmgd_extendercontroller_extender_modem1_autoswitch` **Extender controller extender - modem 2** `fmgd_extendercontroller_extender_modem2` **Extender controller extender - modem 2 - autoswitch** `fmgd_extendercontroller_extender_modem2_autoswitch` **Extender controller extender - WAN extension** `fmgd_extendercontroller_extender_wanextension` **FortiExtender dataplan configuration** `fmgd_extensioncontroller_dataplan` **Extender controller configuration** `fmgd_extensioncontroller_extender` **Extender controller configuration - WAN extension** `fmgd_extensioncontroller_extender_wanextension` **FortiExtender extender profile configuration** `fmgd_extensioncontroller_extenderprofile` **FortiExtender extender profile configuration - cellular** `fmgd_extensioncontroller_extenderprofile_cellular` **FortiExtender extender profile configuration - cellular - controller report** `fmgd_extensioncontroller_extenderprofile_cellular_controllerreport` **FortiExtender extender profile configuration - cellular - modem 1** `fmgd_extensioncontroller_extenderprofile_cellular_modem1` **FortiExtender extender profile configuration - cellular - modem 1 - autosv** `fmgd_extensioncontroller_extenderprofile_cellular_modem1_autoswitch` **FortiExtender extender profile configuration - cellular - modem 2 autoswi** `fmgd_extensioncontroller_extenderprofile_cellular_modem2_autoswitch` **FortiExtender extender profile configuration - cellular - SMS notification** `fmgd_extensioncontroller_extenderprofile_cellular_smsnotification` **FortiExtender extender profile configuration - cellular - SMS notification -** `fmgd_extensioncontroller_extenderprofile_cellular_smsnotification_a` **FortiExtender extender profile configuration - cellular - SMS notification - receiver** `fmgd_extensioncontroller_extenderprofile_cellular_smsnotification_r` **FortiExtender extender profile configuration - wifi radio 1** `fmgd_extensioncontroller_extenderprofile_wifi_radio1` **FortiExtender extender profile configuration - wifi radio 2** `fmgd_extensioncontroller_extenderprofile_wifi_radio2` **FortiExtender wifi VAP configuration** `fmgd_extensioncontroller_extender` **FortiGate controller configuration** `fmgd_extensioncontroller_fortigate` **FortiGate connector profile configuration** `fmgd_extensioncontroller_fortigateprofile` **FortiGate connector profile configuration - lan extension** `fmgd_extensioncontroller_fortigateprofile_lanextension`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Run FortiManager operations and gather facts

Description	Gather device facts, send generic FortiManager API requests, and clone, move or rename managed objects.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Clone objects** `fmgd_clone` **Device facts** `fmgd_fact` **Generic API requests** `fmgd_generic` **Move objects** `fmgd_move` **Rename objects** `fmgd_rename`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Customize replacement messages and GUI

Description	Customize replacement messages and message groups, images, custom languages and GUI themes shown to users.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**Custom languages** `fmgd_system_customlanguage` **Replacement messages - admin** `fmgd_system_replacemsg_admin` **Replacement messages - alert mail** `fmgd_system_replacemsg_alertmail` **Replacement messages - auth** `fmgd_system_replacemsg_auth` **Replacement messages - automation** `fmgd_system_replacemsg_automation` **Replacement messages - custom message** `fmgd_system_replacemsg_custommessage` **Replacement messages - device detection portal** `fmgd_system_replacemsg_devicedetectionportal` **Replacement messages - fortiguardwf** `fmgd_system_replacemsg_fortiguardwf` **Replacement messages - FTP** `fmgd_system_replacemsg_ftp` **Replacement messages - HTTP** `fmgd_system_replacemsg_http` **Replacement messages - ICAP** `fmgd_system_replacemsg_icap` **Replacement messages - mail** `fmgd_system_replacemsg_mail` **Replacement messages - MM1** `fmgd_system_replacemsg_mm1` **Replacement messages - MM3** `fmgd_system_replacemsg_mm3` **Replacement messages - MM4** `fmgd_system_replacemsg_mm4` **Replacement messages - MM7** `fmgd_system_replacemsg_mm7` **Replacement messages - MMS** `fmgd_system_replacemsg_mms` **Replacement messages - nacquar** `fmgd_system_replacemsg_nacquar` **Replacement messages - NNTP** `fmgd_system_replacemsg_nntp` **Replacement messages - spam** `fmgd_system_replacemsg_spam` **Replacement messages - SSL VPN** `fmgd_system_replacemsg_sslvpn` **Replacement messages - traffic quota** `fmgd_system_replacemsg_trafficquota` **Replacement messages - UTM** `fmgd_system_replacemsg_utm` **Replacement messages - web proxy** `fmgd_system_replacemsg_webproxy` **Replacement message groups** `fmgd_system_replacemsggroup` **Replacement message groups - admin** `fmgd_system_replacemsggroup_admin` **Replacement message groups - alert mail** `fmgd_system_replacemsggroup_alertmail` **Replacement message groups - auth** `fmgd_system_replacemsggroup_auth` **Replacement message groups - automation** `fmgd_system_replacemsggroup_automation` **Replacement message groups - custom message** `fmgd_system_replacemsggroup_custommessage` **Replacement message groups - fortiguardwf** `fmgd_system_replacemsggroup_fortiguardwf` **Replacement message groups - FTP** `fmgd_system_replacemsggroup_ftp` **Replacement message groups - HTTP** `fmgd_system_replacemsggroup_http` **Replacement message groups - ICAP** `fmgd_system_replacemsggroup_icap` **Replacement message groups - mail** `fmgd_system_replacemsggroup_mail` **Replacement message groups - nacquar** `fmgd_system_replacemsggroup_nacquar` **Replacement message groups - spam** `fmgd_system_replacemsggroup_spam` **Replacement message groups - SSL VPN** `fmgd_system_replacemsggroup_sslvpn` **Replacement message groups - traffic quota** `fmgd_system_replacemsggroup_trafficquota` **Replacement message groups - UTM** `fmgd_system_replacemsggroup_utm` **Replacement message groups - web proxy** `fmgd_system_replacemsggroup_webproxy` **Replacement message images** `fmgd_system_replacemsgimage` **Custom GUI themes** `fmgd_system_theme`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Use Case: Set global system settings, DNS, time, VDOMs and messages

Description	Configure global and VDOM settings, DNS, NTP and time zone, console, replacement messages, themes, and other system-wide options.
Collection	`fortinet.fmgdevice` (Certified, Fortinet, v1.2.0, updated 2026-08-18)
Key content	**CLI command aliases** `fmgd_system_alias` **Console settings** `fmgd_system_console` **Console Server** `fmgd_system_consoleserver` **Console Server - entries** `fmgd_system_consoleserver_entries` **Dynamic DNS (DDNS)** `fmgd_system_ddns` **DNS settings** `fmgd_system_dns` **DNS64** `fmgd_system_dns64` **DNS databases** `fmgd_system_dnsdatabase` **DNS databases - DNS entry** `fmgd_system_dnsdatabase_dnsentry` **DNS servers** `fmgd_system_dnsserver` **Email server** `fmgd_system_emailserver` **Global system attributes** `fmgd_system_global` **Industrial connectivity (iCOND)** `fmgd_system_icond` **IPS URL filter DNS servers** `fmgd_system_ipsurlfilterdns` **IPS URL filter IPv6 DNS servers** `fmgd_system_ipsurlfilterdns6` **IPS NGFW policy-mode VDOM settings** `fmgd_system_ngfwsettings` **NTP** `fmgd_system_ntp` **NTP - NTP server** `fmgd_system_ntp_ntpserver` **Probe response** `fmgd_system_proberesponse` **PTP** `fmgd_system_ptp` **PTP - server interface** `fmgd_system_ptp_serverinterface` **VDOM settings** `fmgd_system_settings` **SMC NTP** `fmgd_system_smcntp` **SMC NTP - NTP server** `fmgd_system_smcntp_ntpserver` **SMS server** `fmgd_system_smsserver` **Time zone** `fmgd_system_timezone` **Virtual domains (VDOMs)** `fmgd_system_vdom` **DNS servers for a non-management VDOM** `fmgd_system_vdomdns` **VDOM exceptions** `fmgd_system_vdomexception` **VDOM links** `fmgd_system_vdomlink` **VDOM resource properties** `fmgd_system_vdomproperty` **VIN alarm settings** `fmgd_system_vinalarm`
Notes	• Modules configure FortiGate settings through the FortiManager device database, per managed device and VDOM.

Fortinet FortiAnalyzer `fortinet.fortianalyzer`

Certified Fortinet · version 1.10.0 · updated 2025-10-22 · 239 modules → 21 use cases

Use Case: Add and organise managed devices

Description	Add, import and delete devices, and maintain ADOMs, device groups, folders and VDOMs in the device manager database.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Reclaim device management tunnel** `faz_cli_exec_fgfm_reclaimdevtunnel` **Add device** `faz_dvm_cmd_add_device` **Add multiple devices** `faz_dvm_cmd_add_devlist` **Delete device** `faz_dvm_cmd_del_device` **Delete multiple devices** `faz_dvm_cmd_del_devlist` **Import ADOMs and devices** `faz_dvm_cmd_import_devlist` **ADOMs** `faz_dvmdb_adom` **ADOM object members** `faz_dvmdb_adom_objectmember` **Devices** `faz_dvmdb_device` **Device VDOMs** `faz_dvmdb_device_vdom` **Device folders** `faz_dvmdb_folder` **Device groups** `faz_dvmdb_group` **Device group members** `faz_dvmdb_group_objectmember` **Rename object** `faz_rename`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Manage administrators, profiles and approval workflow

Description	Create admin users, groups and access profiles, set password policy and administrator metadata, and define approval workflows.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Meta fields system admin user** `faz_cli_metafields_system_admin_user` **Admin groups** `faz_cli_system_admin_group` **Admin group member** `faz_cli_system_admin_group_member` **Admin profiles** `faz_cli_system_admin_profile` **Admin profile data mask custom fields** `faz_cli_system_admin_profile_datamaskcustomfields` **Admin profile write password profiles** `faz_cli_system_admin_profile_writepasswdprofiles` **Admin profile write password user list** `faz_cli_system_admin_profile_writepasswduserlist` **Admin settings** `faz_cli_system_admin_setting` **Admin users** `faz_cli_system_admin_user` **Admin user ADOM** `faz_cli_system_admin_user_adom` **Admin user ADOM exclude** `faz_cli_system_admin_user_adomexclude` **Admin user dashboard** `faz_cli_system_admin_user_dashboard` **Admin user dashboard tabs** `faz_cli_system_admin_user_dashboardtabs` **Admin user metadata** `faz_cli_system_admin_user_metadata` **Admin user policy block** `faz_cli_system_admin_user_policyblock` **Admin user policy package** `faz_cli_system_admin_user_policypackage` **Admin user restricted devices/VDOMs** `faz_cli_system_admin_user_restrictdevvdom` **Metadata admins** `faz_cli_system_metadata_admins` **Password policy** `faz_cli_system_passwordpolicy` **Workflow approval matrix** `faz_cli_system_workflow_approvalmatrix` **Workflow approval matrix approver** `faz_cli_system_workflow_approvalmatrix_approver`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Integrate external authentication

Description	Authenticate administrators against LDAP, RADIUS, TACACS+ and SAML identity providers.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**LDAP servers** `faz_cli_system_admin_ldap` **Admin LDAP ADOM** `faz_cli_system_admin_ldap_adom` **RADIUS servers** `faz_cli_system_admin_radius` **TACACS+ servers** `faz_cli_system_admin_tacacs` **SAML settings** `faz_cli_system_saml` **SAML fabric IdP** `faz_cli_system_saml_fabricidp` **SAML service providers** `faz_cli_system_saml_serviceproviders`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Configure network interfaces, routing, DNS and time

Description	Configure interfaces, aggregate and IPv6 settings, static routes, DNS, NTP servers, web proxy and interface sniffers.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)

Key content	**DNS** `faz_cli_system_dns` **Interfaces** `faz_cli_system_interface` **Interface IPv6** `faz_cli_system_interface_ipv6` **Interface member** `faz_cli_system_interface_member` **NTP** `faz_cli_system_ntp` **NTP ntpserver** `faz_cli_system_ntp_ntpserver` **Static routes (IPv4)** `faz_cli_system_route` **Static routes (IPv6)** `faz_cli_system_route6` **Sniffer** `faz_cli_system_sniffer` **Web proxy** `faz_cli_system_webproxy`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Restrict access with local-in policies

Description	Define IPv4 and IPv6 local-in policies with their source, destination, port and interface members.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Local in policy** `faz_cli_system_localinpolicy` **Local in policy IPv6** `faz_cli_system_localinpolicy6` **Local in policy IPv6 destination port** `faz_cli_system_localinpolicy6_dport` **Local in policy IPv6 destination** `faz_cli_system_localinpolicy6_dst` **Local in policy IPv6 interface** `faz_cli_system_localinpolicy6_intf` **Local in policy IPv6 source** `faz_cli_system_localinpolicy6_src` **Local in policy destination port** `faz_cli_system_localinpolicy_dport` **Local in policy destination** `faz_cli_system_localinpolicy_dst` **Local in policy interface** `faz_cli_system_localinpolicy_intf` **Local in policy source** `faz_cli_system_localinpolicy_src`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Configure high availability and backups

Description	Configure HA clusters with peers and virtual IPs, and schedule backups of system settings.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Backup all settings** `faz_cli_system_backup_allsettings` **High availability** `faz_cli_system_ha` **HA peer** `faz_cli_system_ha_peer` **HA private peer** `faz_cli_system_ha_privatepeer` **HA vip** `faz_cli_system_ha_vip`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Manage certificates and TLS settings

Description	Manage CA, local, remote, SSH, OFTP and CRL certificates and preferred SSL/TLS cipher suites.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Certificate ca** `faz_cli_system_certificate_ca` **Certificate crl** `faz_cli_system_certificate_crl` **Certificate local** `faz_cli_system_certificate_local` **Certificate oftp** `faz_cli_system_certificate_oftp` **Certificate remote** `faz_cli_system_certificate_remote` **Certificate SSH** `faz_cli_system_certificate_ssh` **SSL cipher suites** `faz_cli_system_sslciphersuites`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Tune global system settings

Description	Set global attributes, FIPS-CC mode, GUI behaviour, central management and Docker host options.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Central management** `faz_cli_system_centralmanagement` **Docker** `faz_cli_system_docker` **FIPS-CC mode** `faz_cli_system_fips` **Global settings** `faz_cli_system_global` **GUI settings** `faz_cli_system_guiact`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Configure local logging and remote log destinations

Description	Set logging to disk, memory, FortiAnalyzer and remote syslog servers, with per-destination filters.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Local log disk filter** `faz_cli_system_locallog_disk_filter` **Local log disk setting** `faz_cli_system_locallog_disk_setting` **Local log FortiAnalyzer 2 filter** `faz_cli_system_locallog_fortianalyzer2_filter` **Local log FortiAnalyzer 2 setting** `faz_cli_system_locallog_fortianalyzer2_setting` **Local log FortiAnalyzer 3 filter** `faz_cli_system_locallog_fortianalyzer3_filter` **Local log FortiAnalyzer 3 setting** `faz_cli_system_locallog_fortianalyzer3_setting` **Local log FortiAnalyzer filter** `faz_cli_system_locallog_fortianalyzer_filter` **Local log FortiAnalyzer setting** `faz_cli_system_locallog_fortianalyzer_setting` **Local log memory filter** `faz_cli_system_locallog_memory_filter` **Local log memory setting** `faz_cli_system_locallog_memory_setting` **Local log setting** `faz_cli_system_locallog_setting` **Local log syslog 2 filter** `faz_cli_system_locallog_syslogd2_filter` **Local log syslog 2 setting** `faz_cli_system_locallog_syslogd2_setting` **Local log syslog 3 filter** `faz_cli_system_locallog_syslogd3_filter` **Local log syslog 3 setting** `faz_cli_system_locallog_syslogd3_setting` **Local log syslog filter** `faz_cli_system_locallog_syslogd_filter` **Local log syslog setting** `faz_cli_system_locallog_syslogd_setting` **Syslog servers** `faz_cli_system_syslog`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Control log collection, retention and rate limits

Description	Set log rolling policies, rate limits, device selection, topology and auto-deletion of logs, reports, DLP archives and quarantined files.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Auto delete** `faz_cli_system_autodelete` **Auto delete dlpfilesautodeletion** `faz_cli_system_autodelete_dlpfilesautodeletion` **Auto delete logautodeletion** `faz_cli_system_autodelete_logautodeletion` **Auto delete quarantinefilesautodeletion** `faz_cli_system_autodelete_quarantinefilesautodeletion` **Auto delete reportautodeletion** `faz_cli_system_autodelete_reportautodeletion` **Log alert** `faz_cli_system_log_alert` **Log device disable** `faz_cli_system_log_devicedisable` **Log device selector** `faz_cli_system_log_deviceselector` **Log FortiOS policy stats** `faz_cli_system_log_fospolicystats` **Log interface stats** `faz_cli_system_log_interfacestats` **Log IoC** `faz_cli_system_log_ioc` **Log mail domain** `faz_cli_system_log_maildomain` **Log pcap file** `faz_cli_system_log_pcapfile` **Log rate limit** `faz_cli_system_log_ratelimit` **Log rate limit device** `faz_cli_system_log_ratelimit_device` **Log rate limit rate limits** `faz_cli_system_log_ratelimit_ratelimits` **Log settings** `faz_cli_system_log_settings` **Log settings rolling (analyzer)** `faz_cli_system_log_settings_rollinganalyzer` **Log settings rolling (local)** `faz_cli_system_log_settings_rollinglocal` **Log settings rolling (regular)** `faz_cli_system_log_settings_rollingregular` **Log topology** `faz_cli_system_log_topology` **Log UEBA** `faz_cli_system_log_ueba`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Forward and fetch logs

Description	Forward logs to other collectors with filters and masking, and configure log-fetch servers and client profiles.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Log fetch client profile** `faz_cli_system_logfetch_clientprofile` **Log fetch client profile device filter** `faz_cli_system_logfetch_clientprofile_devicefilter` **Log fetch client profile log filter** `faz_cli_system_logfetch_clientprofile_logfilter` **Log fetch server settings** `faz_cli_system_logfetch_serversettings` **Log forward** `faz_cli_system_logforward` **Log forward device filter** `faz_cli_system_logforward_devicefilter` **Log forward log field exclusion** `faz_cli_system_logforward_logfieldexclusion` **Log forward log filter** `faz_cli_system_logforward_logfilter` **Log forward log masking (custom)** `faz_cli_system_logforward_logmaskingcustom` **Log forward service** `faz_cli_system_logforwardservice`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Configure system alerts and SNMP monitoring

Description	Send alert events by console and email, define alert destinations and expose system status through SNMP.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Alert console** `faz_cli_system_alertconsole` **Alert email** `faz_cli_system_alertemail` **Alert event** `faz_cli_system_alertevent` **Alert event alert destination** `faz_cli_system_alertevent_alertdestination` **Alert email server** `faz_cli_system_mail` **SNMP community** `faz_cli_system_snmp_community` **SNMP community hosts** `faz_cli_system_snmp_community_hosts` **SNMP community hosts IPv6** `faz_cli_system_snmp_community_hosts6` **SNMP sysinfo** `faz_cli_system_snmp_sysinfo` **SNMP user** `faz_cli_system_snmp_user`

Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Handle events and alerts

Description	Acknowledge, assign, comment on and mark alert events as read, and import event handlers.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Event management alerts ack** `faz_eventmgmt_alerts_ack` **Event management alerts assign** `faz_eventmgmt_alerts_assign` **Event management alerts comment** `faz_eventmgmt_alerts_comment` **Event management alerts import** `faz_eventmgmt_alerts_import` **Event management alerts read** `faz_eventmgmt_alerts_read` **Event management alerts unack** `faz_eventmgmt_alerts_unack` **Event management basic handlers import** `faz_eventmgmt_basichandlers_import` **Event management correlation handlers import** `faz_eventmgmt_correlationhandlers_import`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Define event handlers and notifications

Description	Configure basic and correlation handlers, data selectors, triggers and notification profiles.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Event management config basic handler** `faz_eventmgmt_config_basichandler` **Event management config correlation handler** `faz_eventmgmt_config_correlationhandler` **Event management config data selector** `faz_eventmgmt_config_dataselector` **Event management config notification profile** `faz_eventmgmt_config_notificationprofile` **Event management config trigger** `faz_eventmgmt_config_trigger` **Event management config trigger device** `faz_eventmgmt_config_trigger_device` **Event management config trigger filter** `faz_eventmgmt_config_trigger_filter` **Event management config trigger filter rule** `faz_eventmgmt_config_trigger_filter_rule`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Design report charts, datasets and layouts

Description	Build report datasets, charts, macros and layouts, and import and install report templates.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Report config chart** `faz_report_config_chart` **Report config chart drill down table** `faz_report_config_chart_drilldowntable` **Report config chart table columns** `faz_report_config_chart_tablecolumns` **Report config chart variable template** `faz_report_config_chart_variabletemplate` **Report config dataset** `faz_report_config_dataset` **Report config dataset variable** `faz_report_config_dataset_variable` **Report config layout** `faz_report_config_layout` **Report config layout component** `faz_report_config_layout_component` **Report config layout component variable** `faz_report_config_layout_component_variable` **Report config layout footer** `faz_report_config_layout_footer` **Report config layout header** `faz_report_config_layout_header` **Report config layout folder** `faz_report_config_layoutfolder` **Report config macro** `faz_report_config_macro` **Report config file import** `faz_report_configfile_import` **Report template delete** `faz_report_template_delete` **Report template import** `faz_report_template_import` **Report template install** `faz_report_template_install`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Schedule, run and deliver reports

Description	Schedule reports with filters and devices, configure output and email recipients, run reports and manage generated reports and graph files.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Report auto cache** `faz_cli_system_report_autocache` **Report estimated browse time** `faz_cli_system_report_estbrowsetime` **Report group** `faz_cli_system_report_group` **Report group chart alternatives** `faz_cli_system_report_group_chartalternative` **Report group group by** `faz_cli_system_report_group_groupby` **Report setting** `faz_cli_system_report_setting` **Report config output** `faz_report_config_output` **Report config output email recipients** `faz_report_config_output_emailrecipients` **Report config schedule** `faz_report_config_schedule` **Report config schedule address filter** `faz_report_config_schedule_addressfilter` **Report config schedule devices** `faz_report_config_schedule_devices` **Report config schedule filter** `faz_report_config_schedule_filter` **Report config schedule report layout** `faz_report_config_schedule_reportlayout` **Report graph file** `faz_report_graphfile` **Report graph file delete** `faz_report_graphfile_delete` **Report reports data delete** `faz_report_reports_data_delete` **Run reports** `faz_report_run` **Report run delete** `faz_report_run_delete`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Join the Security Fabric and connect external services

Description	Add FortiAnalyzer to a Security Fabric or SOC fabric, manage trusted nodes and fabric connectors and query SDN connectors.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Connector** `faz_cli_system_connector` **Security Fabric membership** `faz_cli_system_csf` **Security Fabric fabric connector** `faz_cli_system_csf_fabricconnector` **Security Fabric trusted list** `faz_cli_system_csf_trustedlist` **SOC fabric** `faz_cli_system_socfabric` **SOC fabric trusted list** `faz_cli_system_socfabric_trustedlist` **SDN connector query** `faz_sys_api_sdnconnector`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Configure FortiGuard updates and firmware management

Description	Configure the built-in FortiGuard update service, schedules, server overrides, web proxy, push updates and firmware management settings.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**FortiGuard update analyzer virus report** `faz_cli_fmupdate_analyzer_virusreport` **FortiGuard update AV/IPS advanced log** `faz_cli_fmupdate_avips_advancedlog` **FortiGuard update AV/IPS web proxy** `faz_cli_fmupdate_avips_webproxy` **FortiGuard update custom URL list** `faz_cli_fmupdate_customurllist` **FortiGuard update disk quota** `faz_cli_fmupdate_diskquota` **FortiGuard update FortiClient services** `faz_cli_fmupdate_fctservices` **FortiGuard update FDS setting** `faz_cli_fmupdate_fdssetting` **FortiGuard update FDS setting push override** `faz_cli_fmupdate_fdssetting_pushoverride` **FortiGuard update FDS setting push override to client** `faz_cli_fmupdate_fdssetting_pushoverridetoclient` **FortiGuard update FDS setting push override to client announce IP** `faz_cli_fmupdate_fdssetting_pushoverridetoclient_announceip` **FortiGuard update FDS setting server override** `faz_cli_fmupdate_fdssetting_serveroverride` **FortiGuard update FDS setting server override server list** `faz_cli_fmupdate_fdssetting_serveroverride_servlist` **FortiGuard update FDS setting update schedule** `faz_cli_fmupdate_fdssetting_updateschedule` **FortiGuard update FGD setting** `faz_cli_fmupdate_fgdsetting` **FortiGuard update firmware management setting** `faz_cli_fmupdate_fwmsetting` **FortiGuard update firmware management setting upgrade timeout** `faz_cli_fmupdate_fwmsetting_upgradetimeout` **FortiGuard update multilayer** `faz_cli_fmupdate_multilayer` **FortiGuard update public network** `faz_cli_fmupdate_publicnetwork` **FortiGuard update server access priorities** `faz_cli_fmupdate_serveraccesspriorities` **FortiGuard update server access priorities private server** `faz_cli_fmupdate_serveraccesspriorities_privateserver` **FortiGuard update server override status** `faz_cli_fmupdate_serveroverridestatus` **FortiGuard update service** `faz_cli_fmupdate_service` **FortiGuard update web spam FGD setting** `faz_cli_fmupdate_webspam_fgdsetting` **FortiGuard update web spam FGD setting server override** `faz_cli_fmupdate_webspam_fgdsetting_serveroverride` **FortiGuard update web spam FGD setting server override server list** `faz_cli_fmupdate_webspam_fgdsetting_serveroverride_servlist` **FortiGuard update web spam web proxy** `faz_cli_fmupdate_webspam_webproxy`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Tune the SQL database and FortiView analytics

Description	Configure SQL log database settings and custom index fields, and FortiView cache and display options.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**FortiView auto cache** `faz_cli_system_fortiview_autocache` **FortiView setting** `faz_cli_system_fortiview_setting` **SQL settings** `faz_cli_system_sql` **SQL custom index** `faz_cli_system_sql_customindex` **SQL custom skip index** `faz_cli_system_sql_customskipidx` **SQL text search index field** `faz_cli_system_sql_tsindexfield`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Call the FortiAnalyzer API and gather facts

Description	Gather system facts, log in and out of API sessions, send generic or proxied JSON requests and generate WSDL.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Gather facts** `faz_fact` **Generic API request** `faz_generic` **Generate WSDL** `faz_sys_generate_wsdl` **Login challenge** `faz_sys_login_challenge` **Log in** `faz_sys_login_user` **Log out** `faz_sys_logout` **JSON proxy to managed devices** `faz_sys_proxy_json`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Use Case: Upgrade device firmware and restart

Description	Update firmware on managed devices and restart FortiAnalyzer.
Collection	`fortinet.fortianalyzer` (Certified, Fortinet, v1.10.0, updated 2025-10-22)
Key content	**Restart FortiAnalyzer** `faz_sys_reboot` **Device firmware upgrade (legacy API)** `faz_um_image_upgrade` **Device firmware upgrade** `faz_um_image_upgrade_ext`
Notes	• Modules map one-to-one to FortiAnalyzer API objects (CLI configuration, device manager, event management and report objects).

Fortinet FortiFlex `fortinet.fortiflexvm`

Certified Fortinet · version 2.3.3 · updated 2026-08-27 · 14 modules → 3 use cases

Use Case: Define FortiFlex configurations and estimate cost

Description	Create, update and list configurations, and estimate the points a configuration consumes.
Collection	`fortinet.fortiflexvm` (Certified, Fortinet, v2.3.3, updated 2026-08-27)
Key content	**Create configurations** `fortiflexvm_configs_create` **Update configurations** `fortiflexvm_configs_update` **List configurations** `fortiflexvm_configs_list_info` **Point estimates** `fortiflexvm_tools_calc_info` **Programs** `fortiflexvm_programs_list_info`

Use Case: Create and manage entitlements

Description	Create VM, cloud and hardware entitlements, update them, regenerate VM tokens and report entitlement information and point usage.
Collection	`fortinet.fortiflexvm` (Certified, Fortinet, v2.3.3, updated 2026-08-27)
Key content	**VM entitlements** `fortiflexvm_entitlements_vm_create` **Cloud entitlements** `fortiflexvm_entitlements_cloud_create` **Hardware entitlements** `fortiflexvm_entitlements_hardware_create` **Entitlement updates** `fortiflexvm_entitlements_update` **VM token regeneration** `fortiflexvm_entitlements_vm_regenerate_token` **Entitlement list** `fortiflexvm_entitlements_list_info` **Point usage** `fortiflexvm_entitlements_points_info`

Use Case: Organize assets

Description	List groups (asset folders) and find the next available token.
Collection	`fortinet.fortiflexvm` (Certified, Fortinet, v2.3.3, updated 2026-08-27)
Key content	**Groups** `fortiflexvm_groups_list_info` **Next available token** `fortiflexvm_groups_nexttoken_info`

Fortinet FortiManager `fortinet.fortimanager`

Certified Fortinet · version 2.15.0 · updated 2026-08-11 · 1335 modules → 34 use cases

Use Case: Manage FortiExtender and extension controllers

Description	Configure FortiExtender and extension controller profiles, data plans, SIM profiles, templates and extender VAPs.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Data plan** `fmgr_extendercontroller_dataplan` **Extender profile** `fmgr_extendercontroller_extenderprofile` **Extender profile cellular** `fmgr_extendercontroller_extenderprofile_cellular` **Extender profile cellular controller report** `fmgr_extendercontroller_extenderprofile_cellular_controllerreport` **Extender profile cellular modem 1** `fmgr_extendercontroller_extenderprofile_cellular_modem1` **Extender profile cellular modem 1 auto-switch** `fmgr_extendercontroller_extenderprofile_cellular_modem1_autoswitch` **Extender profile cellular modem 2** `fmgr_extendercontroller_extenderprofile_cellular_modem2` **Extender profile cellular modem 2 auto-switch** `fmgr_extendercontroller_extenderprofile_cellular_modem2_autoswitch` **Extender profile cellular SMS notification** `fmgr_extendercontroller_extenderprofile_cellular_smsnotification` **Extender profile cellular SMS notification alert** `fmgr_extendercontroller_extenderprofile_cellular_smsnotification_alert` **Extender profile cellular SMS notification receiver** `fmgr_extendercontroller_extenderprofile_cellular_smsnotification_receiver` **Extender profile LAN extension** `fmgr_extendercontroller_extenderprofile_lanextension` **Extender profile LAN extension backhaul** `fmgr_extendercontroller_extenderprofile_lanextension_backhaul` **SIM profile** `fmgr_extendercontroller_simprofile` **SIM profile auto-switch profile** `fmgr_extendercontroller_simprofile_autoswitchprofile` **Template** `fmgr_extendercontroller_template` **Extension controller data plan** `fmgr_extensioncontroller_dataplan` **Extension controller extender profile** `fmgr_extensioncontroller_extenderprofile` **Extension controller extender profile cellular** `fmgr_extensioncontroller_extenderprofile_cellular` **Extension controller extender profile cellular controller report** `fmgr_extensioncontroller_extenderprofile_cellular_controllerreport` **Extension controller extender profile cellular modem 1** `fmgr_extensioncontroller_extenderprofile_cellular_modem1` **Extension controller extender profile cellular modem 1 auto-switch** `fmgr_extensioncontroller_extenderprofile_cellular_modem1_autoswitch` **Extension controller extender profile cellular modem 2** `fmgr_extensioncontroller_extenderprofile_cellular_modem2` **Extension controller extender profile cellular modem 2 auto-switch** `fmgr_extensioncontroller_extenderprofile_cellular_modem2_autoswitch` **Extension controller extender profile cellular SMS notification** `fmgr_extensioncontroller_extenderprofile_cellular_smsnotification` **Extension controller extender profile cellular SMS notification alert** `fmgr_extensioncontroller_extenderprofile_cellular_smsnotification_a` **Extension controller extender profile cellular SMS notification receiver** `fmgr_extensioncontroller_extenderprofile_cellular_smsnotification_r` **Extension controller extender profile LAN extension** `fmgr_extensioncontroller_extenderprofile_lanextension` **Extension controller extender profile LAN extension backhaul** `fmgr_extensioncontroller_extenderprofile_lanextension_backhaul` **Extender profile LAN extension downlinks** `fmgr_extensioncontroller_extenderprofile_lanextension_downlinks` **Extender profile LAN extension traffic split services** `fmgr_extensioncontroller_extenderprofile_lanextension_trafficsplits` **Extender profile wifi** `fmgr_extensioncontroller_extenderprofile_wifi` **Extender profile wifi radio 1** `fmgr_extensioncontroller_extenderprofile_wifi_radio1` **Extender profile wifi radio 2** `fmgr_extensioncontroller_extenderprofile_wifi_radio2` **Extender VAP** `fmgr_extensioncontroller_extendervap`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by pc package install.

Use Case: Manage FortiSwitch and switch controller

Description	Provision FortiSwitch VLANs, managed switches, ports, QoS, ACLs, LLDP, security policies and FortiLink settings.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**VLAN** `fmgr_fsp_vlan` **VLAN DHCP server** `fmgr_fsp_vlan_dhcpserver` **VLAN DHCP server exclude range** `fmgr_fsp_vlan_dhcpserver_excluderange` **VLAN DHCP server IP range** `fmgr_fsp_vlan_dhcpserver_iprange` **VLAN DHCP server options** `fmgr_fsp_vlan_dhcpserver_options` **VLAN DHCP server reserved address** `fmgr_fsp_vlan_dhcpserver_reservedaddress` **VLAN dynamic mapping** `fmgr_fsp_vlan_dynamicmapping` **VLAN dynamic mapping DHCP server** `fmgr_fsp_vlan_dynamicmapping_dhcpserver` **VLAN dynamic mapping DHCP server exclude range** `fmgr_fsp_vlan_dynamicmapping_dhcpserver_excluderange` **VLAN dynamic mapping DHCP server IP range** `fmgr_fsp_vlan_dynamicmapping_dhcpserver_iprange` **VLAN dynamic mapping DHCP server options** `fmgr_fsp_vlan_dynamicmapping_dhcpserver_options` **VLAN dynamic mapping DHCP server reserved address** `fmgr_fsp_vlan_dynamicmapping_dhcpserver_reservedaddress` **VLAN dynamic mapping interface** `fmgr_fsp_vlan_dynamicmapping_interface` **VLAN dynamic mapping interface IPv6** `fmgr_fsp_vlan_dynamicmapping_interface_ipv6` **VLAN dynamic mapping interface IPv6 delegated prefix list** `fmgr_fsp_vlan_dynamicmapping_interface_ipv6_ip6delegatedprefixlist` **VLAN dynamic mapping interface IPv6 extra address** `fmgr_fsp_vlan_dynamicmapping_interface_ipv6_ip6extraaddr` **VLAN dynamic mapping interface IPv6 prefix list** `fmgr_fsp_vlan_dynamicmapping_interface_ipv6_ip6prefixlist` **VLAN dynamic mapping interface IPv6 vrrp6** `fmgr_fsp_vlan_dynamicmapping_interface_ipv6_vrrp6` **VLAN dynamic mapping interface secondary IP** `fmgr_fsp_vlan_dynamicmapping_interface_secondaryip` **VLAN dynamic mapping interface vrrp** `fmgr_fsp_vlan_dynamicmapping_interface_vrrp` **VLAN dynamic mapping interface vrrp proxy ARP** `fmgr_fsp_vlan_dynamicmapping_interface_vrrp_proxyarp` **VLAN interface** `fmgr_fsp_vlan_interface` **VLAN interface IPv6** `fmgr_fsp_vlan_interface_ipv6` **VLAN interface IPv6 delegated prefix list** `fmgr_fsp_vlan_interface_ipv6_ip6delegatedprefixlist` **VLAN interface IPv6 extra address** `fmgr_fsp_vlan_interface_ipv6_ip6extraaddr` **VLAN interface IPv6 prefix list** `fmgr_fsp_vlan_interface_ipv6_ip6prefixlist` **VLAN interface IPv6 vrrp6** `fmgr_fsp_vlan_interface_ipv6_vrrp6` **VLAN interface secondary IP** `fmgr_fsp_vlan_interface_secondaryip` **VLAN interface vrrp** `fmgr_fsp_vlan_interface_vrrp` **VLAN interface vrrp proxy ARP** `fmgr_fsp_vlan_interface_vrrp_proxyarp` **ACL group** `fmgr_switchcontroller_acl_group` **ACL ingress** `fmgr_switchcontroller_acl_ingress` **ACL ingress action** `fmgr_switchcontroller_acl_ingress_action` **ACL ingress classifier** `fmgr_switchcontroller_acl_ingress_classifier` **Custom command** `fmgr_switchcontroller_customcommand` **DSL policy** `fmgr_switchcontroller_dsl_policy` **Dynamic port policy** `fmgr_switchcontroller_dynamicportpolicy` **Dynamic port policy policy** `fmgr_switchcontroller_dynamicportpolicy_policy` **FortiLink settings** `fmgr_switchcontroller_fortilinksettings` **FortiLink settings NAC ports** `fmgr_switchcontroller_fortilinksettings_nacports` **LLDP profile** `fmgr_switchcontroller_lldpprofile` **LLDP profile custom TLVs** `fmgr_switchcontroller_lldpprofile_customtlvs` **LLDP profile MED location service** `fmgr_switchcontroller_lldpprofile_medlocationservice` **LLDP profile MED network policy** `fmgr_switchcontroller_lldpprofile_mednetworkpolicy` **MAC policy** `fmgr_switchcontroller_macpolicy` **Managed switch** `fmgr_switchcontroller_managedswitch` **Managed switch custom command** `fmgr_switchcontroller_managedswitch_customcommand` **Managed switch DHCP snooping static client** `fmgr_switchcontroller_managedswitch_dhcpsnoopingstaticclient` **Managed switch IP source guard** `fmgr_switchcontroller_managedswitch_ipsourceguard` **Managed switch IP source guard binding entry** `fmgr_switchcontroller_managedswitch_ipsourceguard_bindingentry` **Managed switch ports** `fmgr_switchcontroller_managedswitch_ports` **Managed switch ports DHCP snooping option 82 override** `fmgr_switchcontroller_managedswitch_ports_dhcpsnoopoption82override` **Managed switch remote log** `fmgr_switchcontroller_managedswitch_remotelog` **Managed switch route offload router** `fmgr_switchcontroller_managedswitch_routeoffloadrouter` **Managed switch router static** `fmgr_switchcontroller_managedswitch_routerstatic` **Managed switch router VRF** `fmgr_switchcontroller_managedswitch_routervrf` **Managed switch SNMP community** `fmgr_switchcontroller_managedswitch_snmpcommunity` **Managed switch SNMP community hosts** `fmgr_switchcontroller_managedswitch_snmpcommunity_hosts` **Managed switch SNMP system info** `fmgr_switchcontroller_managedswitch_snmpsysinfo` **Managed switch SNMP trap threshold** `fmgr_switchcontroller_managedswitch_snmptrapthreshold` **Managed switch SNMP user** `fmgr_switchcontroller_managedswitch_snmpuser` **Managed switch system DHCP server** `fmgr_switchcontroller_managedswitch_systemdhcpserver` **Managed switch system DHCP server IP range** `fmgr_switchcontroller_managedswitch_systemdhcpserver_iprange` **Managed switch system DHCP server options** `fmgr_switchcontroller_managedswitch_systemdhcpserver_options` **Managed switch system interface** `fmgr_switchcontroller_managedswitch_systeminterface` **Managed switch VLAN** `fmgr_switchcontroller_managedswitch_vlan` **PTP profile** `fmgr_switchcontroller_ptp_profile` **QoS 802.1p map** `fmgr_switchcontroller_qos_dot1pmap` **QoS IP DSCP map** `fmgr_switchcontroller_qos_ipdscpmap` **QoS IP DSCP map map** `fmgr_switchcontroller_qos_ipdscpmap_map` **QoS policy** `fmgr_switchcontroller_qos_qospolicy` **QoS queue policy** `fmgr_switchcontroller_qos_queuepolicy` **QoS queue policy CoS queue** `fmgr_switchcontroller_qos_queuepolicy_cosqueue` **Security policy 8021x** `fmgr_switchcontroller_securitypolicy_8021x` **Security policy admin** `fmgr_switchcontroller_securitypolicy_admin` **Security policy captive portal** `fmgr_switchcontroller_securitypolicy_captiveportal` **Security policy local access** `fmgr_switchcontroller_securitypolicy_localaccess` **Switch interface tag** `fmgr_switchcontroller_switchinterfacetag` **Switch profile** `fmgr_switchcontroller_switchprofile` **Traffic policy** `fmgr_switchcontroller_trafficpolicy` **VLAN policy** `fmgr_switchcontroller_vlanpolicy`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Manage wireless LAN, FortiAP and Hotspot 2.0

Description	Configure wireless controller profiles, SSIDs and virtual access points, FortiAP and WTP profiles, WIDS, Bonjour and MPSK profiles, regions, and Hotspot 2.0 settings.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**AP configuration profile** `fmgr_apcfgprofile` **AP configuration profile command list** `fmgr_apcfgprofile_commandlist` **ARRP profile** `fmgr_arrpprofile` **Bluetooth Low Energy profile** `fmgr_bleprofile` **Bonjour profile** `fmgr_bonjourprofile` **Bonjour profile policy list** `fmgr_bonjourprofile_policylist` **ANQP 3GPP cellular** `fmgr_hotspot20_anqp3gppcellular` **ANQP 3GPP cellular MCC/MNC list** `fmgr_hotspot20_anqp3gppcellular_mccmnclist` **ANQP IP address type** `fmgr_hotspot20_anqpipaddresstype` **ANQP NAI realm** `fmgr_hotspot20_anqpnairealm` **ANQP NAI realm nailist** `fmgr_hotspot20_anqpnairealm_nailist` **ANQP NAI realm nailist EAP method** `fmgr_hotspot20_anqpnairealm_nailist_eapmethod` **ANQP NAI realm nailist EAP method authentication parameters** `fmgr_hotspot20_anqpnairealm_nailist_eapmethod_authparam` **ANQP network authentication type** `fmgr_hotspot20_anqpnetworkauthtype` **ANQP roaming consortium** `fmgr_hotspot20_anqproamingconsortium` **ANQP roaming consortium oilist** `fmgr_hotspot20_anqproamingconsortium_oilist` **ANQP venue name** `fmgr_hotspot20_anqpvenuename` **ANQP venue name value list** `fmgr_hotspot20_anqpvenuename_valuelist` **ANQP venue URL** `fmgr_hotspot20_anqpvenueurl` **ANQP venue URL value list** `fmgr_hotspot20_anqpvenueurl_valuelist` **H2QP advice of charge** `fmgr_hotspot20_h2qpadviceofcharge` **H2QP advice of charge AOC list** `fmgr_hotspot20_h2qpadviceofcharge_aoclist` **H2QP advice of charge AOC list planinfo** `fmgr_hotspot20_h2qpadviceofcharge_aoclist_planinfo` **H2QP connection capability** `fmgr_hotspot20_h2qpconncapability` **H2QP operator name** `fmgr_hotspot20_h2qpoperatorname` **H2QP operator name value list** `fmgr_hotspot20_h2qpoperatorname_valuelist` **H2QP OSU provider** `fmgr_hotspot20_h2qposuprovider` **H2QP OSU provider friendly name** `fmgr_hotspot20_h2qposuprovider_friendlyname` **H2QP OSU provider service description** `fmgr_hotspot20_h2qposuprovider_servicedescription` **H2QP OSU provider NAI** `fmgr_hotspot20_h2qposuprovidernai` **H2QP OSU provider NAI nailist** `fmgr_hotspot20_h2qposuprovidernai_nailist` **H2QP terms and conditions** `fmgr_hotspot20_h2qptermsandconditions` **H2QP WAN metric** `fmgr_hotspot20_h2qpwanmetric` **Hotspot 2.0 profile** `fmgr_hotspot20_hsprofile` **Icon** `fmgr_hotspot20_icon` **Icon list** `fmgr_hotspot20_icon_iconlist` **Qosmap** `fmgr_hotspot20_qosmap` **Qosmap DSCP exceptions** `fmgr_hotspot20_qosmap_dscpexcept` **Qosmap DSCP range** `fmgr_hotspot20_qosmap_dscprange` **MPSK profile** `fmgr_mpskprofile` **MPSK profile MPSK group** `fmgr_mpskprofile_mpskgroup` **MPSK profile MPSK group MPSK key** `fmgr_mpskprofile_mpskgroup_mpskkey` **QoS profile** `fmgr_qosprofile` **FortiAP regions** `fmgr_region` **Telemetry controller agent** `fmgr_telemetrycontroller_agent` **Telemetry controller agent profile** `fmgr_telemetrycontroller_agentprofile` **Telemetry controller application predefine** `fmgr_telemetrycontroller_application_predefine` **Telemetry controller profile** `fmgr_telemetrycontroller_profile` **Telemetry controller profile application** `fmgr_telemetrycontroller_profile_application` **Telemetry controller profile application SLA** `fmgr_telemetrycontroller_profile_application_sla` **UTM profile** `fmgr_utmprofile` **Virtual access points (VAP)** `fmgr_vap` **Dynamic mapping** `fmgr_vap_dynamicmapping` **MAC filter list** `fmgr_vap_macfilterlist` **MPSK key** `fmgr_vap_mpskkey` **Portal message overrides** `fmgr_vap_portalmessageoverrides` **VLAN name** `fmgr_vap_vlanname` **VLAN pool** `fmgr_vap_vlanpool` **VAP group** `fmgr_vapgroup` **WAG profile** `fmgr_wagprofile` **WIDS profile** `fmgr_widsprofile` **Access control list** `fmgr_wireless_accesscontrollist` **Access control list layer 3 IPv4 rules** `fmgr_wireless_accesscontrollist_layer3ipv4rules` **Access control list layer 3 IPv6 rules** `fmgr_wireless_accesscontrollist_layer3ipv6rules` **Address** `fmgr_wireless_address` **Address group** `fmgr_wireless_addrgrp` **LW profile** `fmgr_wireless_lwprofile` **SSID policy** `fmgr_wireless_ssidpolicy` **Syslog profile** `fmgr_wireless_syslogprofile` **VAP IPv6 prefix list** `fmgr_wireless_vap_ip6prefixlist` **WTP profile** `fmgr_wtpprofile` **Deny MAC list** `fmgr_wtpprofile_denymaclist` **ESL SES dongle** `fmgr_wtpprofile_eslsesdongle` **LAN** `fmgr_wtpprofile_lan` **Location-based services** `fmgr_wtpprofile_lbs` **Platform** `fmgr_wtpprofile_platform` **Radio 1** `fmgr_wtpprofile_radio1` **Radio 2** `fmgr_wtpprofile_radio2` **Radio 3** `fmgr_wtpprofile_radio3` **Radio 4** `fmgr_wtpprofile_radio4` **Split tunneling ACL** `fmgr_wtpprofile_splittunnelingacl`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Install, preview and import configuration

Description	Install policy packages and objects to devices, preview and reinstall, import device objects, check CLI profiles and templates, and abort or inspect install tasks.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Abort** `fmgr_securityconsole_abort` **Assign package** `fmgr_securityconsole_assign_package` **CLI profile check** `fmgr_securityconsole_cliprof_check` **Import device objects** `fmgr_securityconsole_import_dev_objs` **Install device** `fmgr_securityconsole_install_device` **Install objects v2** `fmgr_securityconsole_install_objects_v2` **Install package** `fmgr_securityconsole_install_package` **Install preview** `fmgr_securityconsole_install_preview` **Package cancel install** `fmgr_securityconsole_package_cancel_install` **Preview result** `fmgr_securityconsole_preview_result` **Reinstall package** `fmgr_securityconsole_reinstall_package` **Template cli preview** `fmgr_securityconsole_template_cli_preview` **Template validate** `fmgr_securityconsole_template_validate`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Manage certificates and cipher suites

Description	Manage CA, local, remote and OCSP certificates, certificate templates and SSL cipher suites, and sign certificate templates.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Certificate template** `fmgr_certificate_template` **Certificate local** `fmgr_dynamic_certificate_local` **Certificate local dynamic mapping** `fmgr_dynamic_certificate_local_dynamicmapping` **Sign certificate template** `fmgr_securityconsole_sign_certificate_template` **Certificate CA** `fmgr_system_certificate_ca` **Certificate CRL** `fmgr_system_certificate_crl` **System certificate local** `fmgr_system_certificate_local` **Certificate OFTP** `fmgr_system_certificate_oftp` **Certificate remote** `fmgr_system_certificate_remote` **Certificate SSH** `fmgr_system_certificate_ssh` **SSL cipher suites** `fmgr_system_sslciphersuites` **VPN certificate CA** `fmgr_vpn_certificate_ca` **Certificate HSM local** `fmgr_vpn_certificate_hsmlocal` **Certificate OCSP server** `fmgr_vpn_certificate_ocspserver` **VPN certificate remote** `fmgr_vpn_certificate_remote`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Provide fabric, SDN and cloud connectors

Description	Configure SDN connectors for cloud and virtualization platforms, Security Fabric and SOC fabric members, FortiSASE and cloud orchestration, and identity or NAC integrations such as ACI, NSX, vCenter, Azure, ClearPass and pxGrid.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**AWS orchestration** `fmgr_cloud_orchestaws` **AWS orchestration connector** `fmgr_cloud_orchestawsconnector` **AWS orchestration template autoscale in existing VPC** `fmgr_cloud_orchestawstemplate_autoscaleexistingvpc` **AWS orchestration template autoscale in new VPC** `fmgr_cloud_orchestawstemplate_autoscalenewvpc` **AWS orchestration template autoscale with transit gateway in new VPC** `fmgr_cloud_orchestawstemplate_autoscaletgwnewvpc` **Orchestration** `fmgr_cloud_orchestration` **SASE manager** `fmgr_fmg_sasemanager_status` **SASE manager settings** `fmgr_fmg_sasemanager_settings` **API SDN connector** `fmgr_sys_api_sdnconnector` **Cloud orchestration tasks** `fmgr_sys_cloud_orchest` **Connector** `fmgr_system_connector` **Security Fabric** `fmgr_system_csf` **Security Fabric fabric connector** `fmgr_system_csf_fabricconnector` **Security Fabric trusted list** `fmgr_system_csf_trustedlist` **Security Fabric trusted list ADOM** `fmgr_system_csf_trustedlist_adom` **SDN connector** `fmgr_system_sdnconnector` **SDN connector compartment list** `fmgr_system_sdnconnector_compartmentlist` **SDN connector external account list** `fmgr_system_sdnconnector_externalaccountlist` **SDN connector external IP** `fmgr_system_sdnconnector_externalip` **SDN connector forwarding rule** `fmgr_system_sdnconnector_forwardingrule` **SDN connector GCP project list** `fmgr_system_sdnconnector_gcpprojectlist` **SDN connector nic** `fmgr_system_sdnconnector_nic` **SDN connector nic IP** `fmgr_system_sdnconnector_nic_ip` **SDN connector OCI region list** `fmgr_system_sdnconnector_ociregionlist` **SDN connector route** `fmgr_system_sdnconnector_route` **SDN connector route table** `fmgr_system_sdnconnector_routetable` **SDN connector route table route** `fmgr_system_sdnconnector_routetable_route` **SDN proxy** `fmgr_system_sdnproxy` **SOC fabric** `fmgr_system_socfabric` **SOC fabric trusted list** `fmgr_system_socfabric_trustedlist` **ACI** `fmgr_user_aci` **Azure** `fmgr_user_azure` **Azure rule** `fmgr_user_azure_rule` **ClearPass** `fmgr_user_clearpass` **User connector** `fmgr_user_connector` **Guardicore** `fmgr_user_guardicore` **NSX** `fmgr_user_nsx` **NSX service** `fmgr_user_nsx_service` **PxGrid** `fmgr_user_pxgrid` **vCenter** `fmgr_user_vcenter` **vCenter rule** `fmgr_user_vcenter_rule`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Manage security policy packages and policy blocks

Description	Create policy packages and folders, assign them to devices, reuse policy blocks, and clone, move or commit packages.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Policy block firewall consolidated policy** `fmgr_pm_config_pblock_firewall_consolidated_policy` **Policy block firewall consolidated policy section value** `fmgr_pm_config_pblock_firewall_consolidated_policy_sectionvalue` **Policy block firewall local-in policy** `fmgr_pm_config_pblock_firewall_localinpolicy` **Policy block firewall IPv6 local-in policy** `fmgr_pm_config_pblock_firewall_localinpolicy6` **Policy block firewall policy** `fmgr_pm_config_pblock_firewall_policy` **Policy block firewall IPv6 policy** `fmgr_pm_config_pblock_firewall_policy6` **Policy block firewall IPv6 policy section value** `fmgr_pm_config_pblock_firewall_policy6_sectionvalue` **Policy block firewall policy section value** `fmgr_pm_config_pblock_firewall_policy_sectionvalue` **Policy block firewall proxy policy** `fmgr_pm_config_pblock_firewall_proxypolicy` **Policy block firewall proxy policy section value** `fmgr_pm_config_pblock_firewall_proxypolicy_sectionvalue` **Policy block firewall security policy** `fmgr_pm_config_pblock_firewall_securitypolicy` **Policy block firewall security policy section value** `fmgr_pm_config_pblock_firewall_securitypolicy_sectionvalue` **Reset database** `fmgr_pm_config_reset_database` **Policy block ADOM** `fmgr_pm_pblock_adom` **Policy block object** `fmgr_pm_pblock_obj` **Package** `fmgr_pm_pkg` **ADOM** `fmgr_pm_pkg_adom` **Global** `fmgr_pm_pkg_global` **Scope member** `fmgr_pm_pkg_scopemember` **Package clone** `fmgr_securityconsole_package_clone` **Package commit** `fmgr_securityconsole_package_commit` **Package move** `fmgr_securityconsole_package_move` **Policy block clone** `fmgr_securityconsole_pblock_clone`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Define traffic shaping and QoS

Description	Configure traffic shapers, shaping profiles, shaping classes and shaping policies, including header and footer shaping policies.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Per-IP shaper** `fmgr_firewall_shaper_peripshaper` **Traffic shaper** `fmgr_firewall_shaper_trafficshaper` **Shaping profile** `fmgr_firewall_shapingprofile` **Shaping profile classes** `fmgr_firewall_shapingprofile_classes` **Shaping profile shaping entries** `fmgr_firewall_shapingprofile_shapingentries` **Traffic class** `fmgr_firewall_trafficclass` **Response shaping policy** `fmgr_pkg_firewall_responseshapingpolicy` **Shaping policy** `fmgr_pkg_firewall_shapingpolicy` **Footer shaping policy** `fmgr_pkg_footer_shapingpolicy` **Header shaping policy** `fmgr_pkg_header_shapingpolicy`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Configure NAT, virtual IPs and IP pools

Description	Create IPv4, IPv6, NAT46 and NAT64 virtual IPs and groups, IP pools, central SNAT and DNAT, and server load-balancing monitors.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**IP pool** `fmgr_dynamic_ippool` **Virtual IP** `fmgr_dynamic_vip` **Firewall IP pool** `fmgr_firewall_ippool` **IPv6 IP pool** `fmgr_firewall_ippool6` **IPv6 IP pool dynamic mapping** `fmgr_firewall_ippool6_dynamicmapping` **IP pool dynamic mapping** `fmgr_firewall_ippool_dynamicmapping` **IP pool group** `fmgr_firewall_ippoolgrp` **Load balance monitor** `fmgr_firewall_ldbmonitor` **Firewall virtual IP** `fmgr_firewall_vip` **NAT46 virtual IP** `fmgr_firewall_vip46` **NAT46 virtual IP dynamic mapping** `fmgr_firewall_vip46_dynamicmapping` **NAT46 virtual IP real servers** `fmgr_firewall_vip46_realservers` **IPv6 virtual IP** `fmgr_firewall_vip6` **NAT64 virtual IP** `fmgr_firewall_vip64` **NAT64 virtual IP dynamic mapping** `fmgr_firewall_vip64_dynamicmapping` **NAT64 virtual IP real servers** `fmgr_firewall_vip64_realservers` **IPv6 virtual IP dynamic mapping** `fmgr_firewall_vip6_dynamicmapping` **IPv6 virtual IP dynamic mapping real servers** `fmgr_firewall_vip6_dynamicmapping_realservers` **IPv6 virtual IP dynamic mapping SSL cipher suites** `fmgr_firewall_vip6_dynamicmapping_sslciphersuites` **IPv6 virtual IP quic** `fmgr_firewall_vip6_quic` **IPv6 virtual IP real servers** `fmgr_firewall_vip6_realservers` **IPv6 virtual IP SSL cipher suites** `fmgr_firewall_vip6_sslciphersuites` **IPv6 virtual IP SSL server cipher suites** `fmgr_firewall_vip6_sslserverciphersuites` **Virtual IP dynamic mapping** `fmgr_firewall_vip_dynamicmapping` **Virtual IP dynamic mapping real servers** `fmgr_firewall_vip_dynamicmapping_realservers` **Virtual IP dynamic mapping SSL cipher suites** `fmgr_firewall_vip_dynamicmapping_sslciphersuites` **Virtual IP GSLB public IPs** `fmgr_firewall_vip_gslbpublicips` **Virtual IP quic** `fmgr_firewall_vip_quic` **Virtual IP real servers** `fmgr_firewall_vip_realservers` **Virtual IP SSL cipher suites** `fmgr_firewall_vip_sslciphersuites` **Virtual IP SSL server cipher suites** `fmgr_firewall_vip_sslserverciphersuites` **Virtual IP group** `fmgr_firewall_vipgrp` **NAT46 virtual IP group** `fmgr_firewall_vipgrp46` **IPv6 virtual IP group** `fmgr_firewall_vipgrp6` **NAT64 virtual IP group** `fmgr_firewall_vipgrp64` **Virtual IP group dynamic mapping** `fmgr_firewall_vipgrp_dynamicmapping` **Central DNAT** `fmgr_pkg_central_dnat` **Central IPv6 DNAT** `fmgr_pkg_central_dnat6` **Central SNAT map** `fmgr_pkg_firewall_centralsnatmap`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Manage firewall policies and policy sections

Description	Create IPv4, IPv6, NAT46/64, consolidated, hyperscale, DoS, local-in, interface, multicast, proxy, explicit proxy, access control and security policies within packages, including headers and footers.

Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Authentication rule** `fmgr_pkg_authentication_rule` **Authentication setting** `fmgr_pkg_authentication_setting` **ACL** `fmgr_pkg_firewall_acl` **Acl6** `fmgr_pkg_firewall_acl6` **Consolidated policy** `fmgr_pkg_firewall_consolidated_policy` **Consolidated policy section value** `fmgr_pkg_firewall_consolidated_policy_sectionvalue` **DoS policy** `fmgr_pkg_firewall_dospolicy` **IPv6 DoS policy** `fmgr_pkg_firewall_dospolicy6` **IPv6 DoS policy anomaly** `fmgr_pkg_firewall_dospolicy6_anomaly` **DoS policy anomaly** `fmgr_pkg_firewall_dospolicy_anomaly` **Explicit proxy policy** `fmgr_pkg_firewall_explicitproxypolicy` **Explicit proxy policy identity-based policy** `fmgr_pkg_firewall_explicitproxypolicy_identitybasedpolicy` **Explicit proxy policy section value** `fmgr_pkg_firewall_explicitproxypolicy_sectionvalue` **Hyperscale policy** `fmgr_pkg_firewall_hyperscalepolicy` **Hyperscale NAT46 policy** `fmgr_pkg_firewall_hyperscalepolicy46` **Hyperscale IPv6 policy** `fmgr_pkg_firewall_hyperscalepolicy6` **Hyperscale NAT64 policy** `fmgr_pkg_firewall_hyperscalepolicy64` **Interface policy** `fmgr_pkg_firewall_interfacepolicy` **IPv6 interface policy** `fmgr_pkg_firewall_interfacepolicy6` **IPv6 interface policy section value** `fmgr_pkg_firewall_interfacepolicy6_sectionvalue` **Interface policy section value** `fmgr_pkg_firewall_interfacepolicy_sectionvalue` **Local-in policy** `fmgr_pkg_firewall_localinpolicy` **IPv6 local-in policy** `fmgr_pkg_firewall_localinpolicy6` **Multicast policy** `fmgr_pkg_firewall_multicastpolicy` **IPv6 multicast policy** `fmgr_pkg_firewall_multicastpolicy6` **Policy** `fmgr_pkg_firewall_policy` **NAT46 policy** `fmgr_pkg_firewall_policy46` **IPv6 policy** `fmgr_pkg_firewall_policy6` **NAT64 policy** `fmgr_pkg_firewall_policy64` **IPv6 policy section value** `fmgr_pkg_firewall_policy6_sectionvalue` **Policy section value** `fmgr_pkg_firewall_policy_sectionvalue` **Policy VPN destination node** `fmgr_pkg_firewall_policy_vpndstnode` **Policy VPN source node** `fmgr_pkg_firewall_policy_vpnsrcnode` **Proxy policy** `fmgr_pkg_firewall_proxypolicy` **Proxy policy section value** `fmgr_pkg_firewall_proxypolicy_sectionvalue` **Security policy** `fmgr_pkg_firewall_securitypolicy` **Security policy section value** `fmgr_pkg_firewall_securitypolicy_sectionvalue` **Footer policy** `fmgr_pkg_footer_policy` **Footer IPv6 policy** `fmgr_pkg_footer_policy6` **Header policy** `fmgr_pkg_header_policy` **Header IPv6 policy** `fmgr_pkg_header_policy6` **NAC policy** `fmgr_pkg_user_nacpolicy` **YouTube key** `fmgr_pkg_videofilter_youtubekey`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Define address, service, schedule and Internet Service objects

Description	Maintain IPv4 and IPv6 addresses and groups, multicast and wildcard FQDN addresses, services, schedules, vendor MACs, custom tags, dynamic address mappings and Internet Service entries.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Internet Service** `fmgr_application_internetservice` **Internet Service entry** `fmgr_application_internetservice_entry` **Custom Internet Service** `fmgr_application_internetservicecustom` **Custom Internet Service disabled entry** `fmgr_application_internetservicecustom_disableentry` **Custom Internet Service disabled entry IP range** `fmgr_application_internetservicecustom_disableentry_iprange` **Custom Internet Service entry** `fmgr_application_internetservicecustom_entry` **Custom Internet Service entry port range** `fmgr_application_internetservicecustom_entry_portrange` **Address** `fmgr_dynamic_address` **Dynamic address mapping** `fmgr_dynamic_address_dynamicaddrmapping` **Firewall address** `fmgr_firewall_address`, `fmgr_firewall_address_list` **IPv6 address** `fmgr_firewall_address6`, `fmgr_firewall_address6_list` **IPv6 address dynamic mapping** `fmgr_firewall_address6_dynamicmapping` **IPv6 address dynamic mapping subnet segment** `fmgr_firewall_address6_dynamicmapping_subnetsegment` **IPv6 address profile list** `fmgr_firewall_address6_profilelist` **IPv6 address subnet segment** `fmgr_firewall_address6_subnetsegment` **IPv6 address tagging** `fmgr_firewall_address6_tagging` **IPv6 address template** `fmgr_firewall_address6template` **IPv6 address template subnet segment** `fmgr_firewall_address6template_subnetsegment` **IPv6 address template subnet segment values** `fmgr_firewall_address6template_subnetsegment_values` **Address dynamic mapping** `fmgr_firewall_address_dynamicmapping` **Address profile list** `fmgr_firewall_address_profilelist` **Address tagging** `fmgr_firewall_address_tagging` **Address group** `fmgr_firewall_addrgrp` **IPv6 address group** `fmgr_firewall_addrgrp6` **IPv6 address group dynamic mapping** `fmgr_firewall_addrgrp6_dynamicmapping` **IPv6 address group tagging** `fmgr_firewall_addrgrp6_tagging` **Address group dynamic mapping** `fmgr_firewall_addrgrp_dynamicmapping` **Address group tagging** `fmgr_firewall_addrgrp_tagging` **Custom tag** `fmgr_firewall_customtag` **Firewall Internet Service** `fmgr_firewall_internetservice` **Firewall Internet Service entry** `fmgr_firewall_internetservice_entry` **Internet Service addition** `fmgr_firewall_internetserviceaddition` **Internet Service addition entry** `fmgr_firewall_internetserviceaddition_entry` **Internet Service addition entry port range** `fmgr_firewall_internetserviceaddition_entry_portrange` **Firewall custom Internet Service** `fmgr_firewall_internetservicecustom` **Firewall custom Internet Service disabled entry** `fmgr_firewall_internetservicecustom_disableentry` **Firewall custom Internet Service disabled entry IP range** `fmgr_firewall_internetservicecustom_disableentry_iprange` **Firewall custom Internet Service entry** `fmgr_firewall_internetservicecustom_entry` **Firewall custom Internet Service entry port range** `fmgr_firewall_internetservicecustom_entry_portrange` **Custom Internet Service group** `fmgr_firewall_internetservicecustomgroup` **Internet Service extension** `fmgr_firewall_internetserviceextension` **Internet Service extension disabled entry** `fmgr_firewall_internetserviceextension_disableentry` **Internet Service extension disabled entry IPv6 range** `fmgr_firewall_internetserviceextension_disableentry_ip6range` **Internet Service extension disabled entry IP range** `fmgr_firewall_internetserviceextension_disableentry_iprange` **Internet Service extension disabled entry port range** `fmgr_firewall_internetserviceextension_disableentry_portrange` **Internet Service extension entry** `fmgr_firewall_internetserviceextension_entry` **Internet Service extension entry port range** `fmgr_firewall_internetserviceextension_entry_portrange` **Internet Service group** `fmgr_firewall_internetservicegroup` **Internet Service name** `fmgr_firewall_internetservicename` **Multicast address** `fmgr_firewall_multicastaddress` **IPv6 multicast address** `fmgr_firewall_multicastaddress6` **IPv6 multicast address tagging** `fmgr_firewall_multicastaddress6_tagging` **Multicast address tagging** `fmgr_firewall_multicastaddress_tagging` **Dynamic network service** `fmgr_firewall_networkservicedynamic` **Schedule group** `fmgr_firewall_schedule_group` **Schedule one-time** `fmgr_firewall_schedule_onetime` **Schedule recurring** `fmgr_firewall_schedule_recurring` **Service category** `fmgr_firewall_service_category` **Service custom** `fmgr_firewall_service_custom` **Service group** `fmgr_firewall_service_group` **Vendor MAC** `fmgr_firewall_vendormac` **Wildcard FQDN custom** `fmgr_firewall_wildcardfqdn_custom` **Wildcard FQDN group** `fmgr_firewall_wildcardfqdn_group`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Control explicit web proxy, isolation and WAN optimization

Description	Configure explicit and forward web proxy settings, proxy addresses, isolation servers, WAN optimization profiles, peers and authentication groups.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Explicit proxy address** `fmgr_firewall_explicitproxyaddress` **Explicit proxy address header group** `fmgr_firewall_explicitproxyaddress_headergroup` **Explicit proxy address group** `fmgr_firewall_explicitproxyaddrgrp` **Proxy address** `fmgr_firewall_proxyaddress` **IPv6 proxy address** `fmgr_firewall_proxyaddress6` **IPv6 proxy address header group** `fmgr_firewall_proxyaddress6_headergroup` **IPv6 proxy address tagging** `fmgr_firewall_proxyaddress6_tagging` **Proxy address header group** `fmgr_firewall_proxyaddress_headergroup` **Proxy address tagging** `fmgr_firewall_proxyaddress_tagging` **Proxy address group** `fmgr_firewall_proxyaddrgrp` **IPv6 proxy address group** `fmgr_firewall_proxyaddrgrp6` **IPv6 proxy address group tagging** `fmgr_firewall_proxyaddrgrp6_tagging` **Proxy address group tagging** `fmgr_firewall_proxyaddrgrp_tagging` **Isolator profile** `fmgr_isolator_profile` **Isolator profile entries** `fmgr_isolator_profile_entries` **Web proxy** `fmgr_system_webproxy` **Authentication group** `fmgr_wanopt_authgroup` **Peer** `fmgr_wanopt_peer` **Profile** `fmgr_wanopt_profile` **Profile CIFS** `fmgr_wanopt_profile_cifs` **Profile FTP** `fmgr_wanopt_profile_ftp` **Profile HTTP** `fmgr_wanopt_profile_http` **Profile MAPI** `fmgr_wanopt_profile_mapi` **Profile TCP** `fmgr_wanopt_profile_tcp` **Explicit proxy** `fmgr_webproxy_explicitproxy` **Forward server** `fmgr_webproxy_forwardserver` **Forward server group** `fmgr_webproxy_forwardservergroup` **Forward server group server list** `fmgr_webproxy_forwardservergroup_serverlist` **Isolator server** `fmgr_webproxy_isolatorserver` **Web proxy profile** `fmgr_webproxy_profile` **Profile headers** `fmgr_webproxy_profile_headers` **Redirect profile** `fmgr_webproxy_redirectprofile` **Redirect profile entries** `fmgr_webproxy_redirectprofile_entries` **Wisp** `fmgr_webproxy_wisp`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Provide ZTNA and CASB access control

Description	Configure ZTNA web portals, web proxy, traffic forwarding and access proxy objects, SSH client certificates, and CASB profiles, user activities and SaaS applications.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Profile** `fmgr_casb_profile` **Profile SaaS application** `fmgr_casb_profile_saasapplication` **Profile SaaS application access rule** `fmgr_casb_profile_saasapplication_accessrule` **Profile SaaS application advanced tenant control** `fmgr_casb_profile_saasapplication_advancedtenantcontrol` **Profile SaaS application advanced tenant control attribute** `fmgr_casb_profile_saasapplication_advancedtenantcontrol_attribute` **Profile SaaS application custom control** `fmgr_casb_profile_saasapplication_customcontrol` **Profile SaaS application custom control option** `fmgr_casb_profile_saasapplication_customcontrol_option` **SaaS application** `fmgr_casb_saasapplication` **SaaS application input attributes** `fmgr_casb_saasapplication_inputattributes` **SaaS application output attributes** `fmgr_casb_saasapplication_outputattributes` **User activity** `fmgr_casb_useractivity` **User activity control options** `fmgr_casb_useractivity_controloptions` **User activity control options operations** `fmgr_casb_useractivity_controloptions_operations` **User activity match** `fmgr_casb_useractivity_match` **User activity match rules** `fmgr_casb_useractivity_match_rules` **User activity match tenant extraction** `fmgr_casb_useractivity_match_tenantextraction` **User activity match tenant extraction filters** `fmgr_casb_useractivity_match_tenantextraction_filters` **User activity match tenant session extraction** `fmgr_casb_useractivity_match_tenantsessionextraction` **User activity match tenant session extraction filters** `fmgr_casb_useractivity_match_tenantsessionextraction_filters` **Access proxy** `fmgr_firewall_accessproxy` **IPv6 access proxy** `fmgr_firewall_accessproxy6` **IPv6 access proxy API gateway** `fmgr_firewall_accessproxy6_apigateway` **IPv6 access proxy IPv6 API gateway** `fmgr_firewall_accessproxy6_apigateway6` **IPv6 access proxy IPv6 API gateway quic** `fmgr_firewall_accessproxy6_apigateway6_quic` **IPv6 access proxy IPv6 API gateway real servers** `fmgr_firewall_accessproxy6_apigateway6_realservers` **IPv6 access proxy IPv6 API gateway SSL cipher suites** `fmgr_firewall_accessproxy6_apigateway6_sslciphersuites` **IPv6 access proxy API gateway quic** `fmgr_firewall_accessproxy6_apigateway_quic` **IPv6 access proxy API gateway real servers** `fmgr_firewall_accessproxy6_apigateway_realservers` **IPv6 access proxy API gateway SSL cipher suites** `fmgr_firewall_accessproxy6_apigateway_sslciphersuites` **Access proxy API gateway** `fmgr_firewall_accessproxy_apigateway` **Access proxy IPv6 API gateway** `fmgr_firewall_accessproxy_apigateway6` **Access proxy IPv6 API gateway quic** `fmgr_firewall_accessproxy_apigateway6_quic` **Access proxy IPv6 API gateway real servers** `fmgr_firewall_accessproxy_apigateway6_realservers` **Access proxy IPv6 API gateway SSL cipher suites** `fmgr_firewall_accessproxy_apigateway6_sslciphersuites` **Access proxy API gateway quic** `fmgr_firewall_accessproxy_apigateway_quic` **Access proxy API gateway real servers** `fmgr_firewall_accessproxy_apigateway_realservers` **Access proxy API gateway SSL cipher suites** `fmgr_firewall_accessproxy_apigateway_sslciphersuites` **Access proxy real servers** `fmgr_firewall_accessproxy_realservers` **Access proxy server public key authentication settings** `fmgr_firewall_accessproxy_serverpubkeyauthsettings` **Access proxy server public key authentication settings certificate extension** `fmgr_firewall_accessproxy_serverpubkeyauthsettings_certextension` **Access proxy SSH client certificate** `fmgr_firewall_accessproxysshclientcert` **Access proxy SSH client certificate certificate extension** `fmgr_firewall_accessproxysshclientcert_certextension` **Access proxy virtual host** `fmgr_firewall_accessproxyvirtualhost` **CASB profile** `fmgr_firewall_casbprofile` **CASB profile SaaS application** `fmgr_firewall_casbprofile_saasapplication` **CASB profile SaaS application access rule** `fmgr_firewall_casbprofile_saasapplication_accessrule` **CASB profile SaaS application custom control** `fmgr_firewall_casbprofile_saasapplication_customcontrol` **CASB profile SaaS application custom control option** `fmgr_firewall_casbprofile_saasapplication_customcontrol_option` **Destination** `fmgr_ztna_destination` **Service connector** `fmgr_ztna_serviceconnector` **Traffic forward proxy** `fmgr_ztna_trafficforwardproxy` **Traffic forward proxy quic** `fmgr_ztna_trafficforwardproxy_quic` **Traffic forward proxy SSL cipher suites** `fmgr_ztna_trafficforwardproxy_sslciphersuites` **Traffic forward proxy SSL server cipher suites** `fmgr_ztna_trafficforwardproxy_sslserverciphersuites` **Traffic forward proxy URL route** `fmgr_ztna_trafficforwardproxy_urlroute` **Web portal** `fmgr_ztna_webportal` **Web portal bookmark** `fmgr_ztna_webportalbookmark` **Web portal bookmark bookmarks** `fmgr_ztna_webportalbookmark_bookmarks` **Web proxy** `fmgr_ztna_webproxy` **Web proxy API gateway** `fmgr_ztna_webproxy_apigateway` **Web proxy IPv6 API gateway** `fmgr_ztna_webproxy_apigateway6` **Web proxy IPv6 API gateway quic** `fmgr_ztna_webproxy_apigateway6_quic` **Web proxy IPv6 API gateway real servers** `fmgr_ztna_webproxy_apigateway6_realservers` **Web proxy IPv6 API gateway SSL cipher suites** `fmgr_ztna_webproxy_apigateway6_sslciphersuites` **Web proxy API gateway quic** `fmgr_ztna_webproxy_apigateway_quic` **Web proxy API gateway real servers** `fmgr_ztna_webproxy_apigateway_realservers` **Web proxy API gateway SSL cipher suites** `fmgr_ztna_webproxy_apigateway_sslciphersuites`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Protect web applications (WAF)

Description	Manage web application firewall profiles, signatures and main and sub classes.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Main class** `fmgr_waf_mainclass` **Profile** `fmgr_waf_profile` **Profile address list** `fmgr_waf_profile_addresslist` **Profile constraint** `fmgr_waf_profile_constraint` **Profile constraint content length** `fmgr_waf_profile_constraint_contentlength` **Profile constraint exception** `fmgr_waf_profile_constraint_exception` **Profile constraint header length** `fmgr_waf_profile_constraint_headerlength` **Profile constraint hostname** `fmgr_waf_profile_constraint_hostname` **Profile constraint line length** `fmgr_waf_profile_constraint_linelength` **Profile constraint malformed** `fmgr_waf_profile_constraint_malformed` **Profile constraint max cookie** `fmgr_waf_profile_constraint_maxcookie` **Profile constraint max header line** `fmgr_waf_profile_constraint_maxheaderline` **Profile constraint max range segment** `fmgr_waf_profile_constraint_maxrangesegment` **Profile constraint max URL parameters** `fmgr_waf_profile_constraint_maxurlparam` **Profile constraint method** `fmgr_waf_profile_constraint_method` **Profile constraint parameter length** `fmgr_waf_profile_constraint_paramlength` **Profile constraint URL parameter length** `fmgr_waf_profile_constraint_urlparamlength` **Profile constraint version** `fmgr_waf_profile_constraint_version` **Profile method** `fmgr_waf_profile_method` **Profile method policy** `fmgr_waf_profile_method_methodpolicy` **Profile signature** `fmgr_waf_profile_signature` **Profile custom signature** `fmgr_waf_profile_signature_customsignature` **Profile signature main class** `fmgr_waf_profile_signature_mainclass` **Profile URL access** `fmgr_waf_profile_urlaccess` **Profile URL access access pattern** `fmgr_waf_profile_urlaccess_accesspattern` **Signature** `fmgr_waf_signature` **Subclass** `fmgr_waf_subclass`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Filter web, DNS and video content

Description	Configure web filter profiles, URL, domain and content lists, FortiGuard categories and ratings, DNS filter profiles and filters, and video filter profiles.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Domain filter** `fmgr_dnsfilter_domainfilter` **Domain filter entries** `fmgr_dnsfilter_domainfilter_entries` **Profile** `fmgr_dnsfilter_profile` **Profile DNS translation** `fmgr_dnsfilter_profile_dnstranslation` **Profile domain filter** `fmgr_dnsfilter_profile_domainfilter` **Profile FortiGuard DDNS** `fmgr_dnsfilter_profile_ftgddns` **Profile FortiGuard DDNS filters** `fmgr_dnsfilter_profile_ftgddns_filters` **Profile URL filter** `fmgr_dnsfilter_profile_urlfilter` **URL filter** `fmgr_dnsfilter_urlfilter` **URL filter entries** `fmgr_dnsfilter_urlfilter_entries` **Keyword** `fmgr_videofilter_keyword` **Keyword word** `fmgr_videofilter_keyword_word` **Video filter profile** `fmgr_videofilter_profile` **Profile filters** `fmgr_videofilter_profile_filters` **Profile FortiGuard category** `fmgr_videofilter_profile_fortiguardcategory` **Profile FortiGuard category filters** `fmgr_videofilter_profile_fortiguardcategory_filters` **YouTube channel filter** `fmgr_videofilter_youtubechannelfilter` **YouTube channel filter entries** `fmgr_videofilter_youtubechannelfilter_entries` **YouTube key** `fmgr_videofilter_youtubekey` **Categories** `fmgr_webfilter_categories` **Content** `fmgr_webfilter_content` **Content entries** `fmgr_webfilter_content_entries` **Content header** `fmgr_webfilter_contentheader` **Content header entries** `fmgr_webfilter_contentheader_entries` **Domain list** `fmgr_webfilter_domainlist` **Domain list entries** `fmgr_webfilter_domainlist_entries` **FortiGuard local category** `fmgr_webfilter_ftgdlocalcat` **FortiGuard local rating** `fmgr_webfilter_ftgdlocalrating` **FortiGuard risk level** `fmgr_webfilter_ftgdrisklevel` **Web filter profile** `fmgr_webfilter_profile` **Profile anti-phishing** `fmgr_webfilter_profile_antiphish` **Profile anti-phishing custom patterns** `fmgr_webfilter_profile_antiphish_custompatterns` **Profile anti-phishing inspection entries** `fmgr_webfilter_profile_antiphish_inspectionentries` **Profile file filter** `fmgr_webfilter_profile_filefilter` **Profile file filter entries** `fmgr_webfilter_profile_filefilter_entries` **Profile FortiGuard web filter** `fmgr_webfilter_profile_ftgdwf` **Profile FortiGuard web filter filters** `fmgr_webfilter_profile_ftgdwf_filters` **Profile FortiGuard web filter quota** `fmgr_webfilter_profile_ftgdwf_quota` **Profile FortiGuard web filter risk** `fmgr_webfilter_profile_ftgdwf_risk` **Profile override** `fmgr_webfilter_profile_override` **Profile URL extraction** `fmgr_webfilter_profile_urlextraction` **Profile web** `fmgr_webfilter_profile_web` **Profile YouTube channel filter** `fmgr_webfilter_profile_youtubechannelfilter` **Web filter URL filter** `fmgr_webfilter_urlfilter` **Web filter URL filter entries** `fmgr_webfilter_urlfilter_entries` **URL list** `fmgr_webfilter_urllist` **URL list entries** `fmgr_webfilter_urllist_entries`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Filter email and spam

Description	Configure email filter and spam filter profiles, block and allow lists, DNS blocklists, banned words and header filters.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Block/allow list** `fmgr_emailfilter_blockallowlist` **Block/allow list entries** `fmgr_emailfilter_blockallowlist_entries` **Black/white list** `fmgr_emailfilter_bwl` **Black/white list entries** `fmgr_emailfilter_bwl_entries` **Banned words** `fmgr_emailfilter_bword` **Banned words entries** `fmgr_emailfilter_bword_entries` **Dnsbl** `fmgr_emailfilter_dnsbl` **Dnsbl entries** `fmgr_emailfilter_dnsbl_entries` **FortiShield** `fmgr_emailfilter_fortishield` **IP trust** `fmgr_emailfilter_iptrust` **IP trust entries** `fmgr_emailfilter_iptrust_entries` **Mail header** `fmgr_emailfilter_mheader` **Mail header entries** `fmgr_emailfilter_mheader_entries` **Options** `fmgr_emailfilter_options` **Profile** `fmgr_emailfilter_profile` **Profile file filter** `fmgr_emailfilter_profile_filefilter` **Profile file filter entries** `fmgr_emailfilter_profile_filefilter_entries` **Profile Gmail** `fmgr_emailfilter_profile_gmail` **Profile IMAP** `fmgr_emailfilter_profile_imap` **Profile MAPI** `fmgr_emailfilter_profile_mapi` **Profile MSN Hotmail** `fmgr_emailfilter_profile_msnhotmail` **Profile other web mail** `fmgr_emailfilter_profile_otherwebmails` **Profile POP3** `fmgr_emailfilter_profile_pop3` **Profile SMTP** `fmgr_emailfilter_profile_smtp` **Profile Yahoo Mail** `fmgr_emailfilter_profile_yahoomail` **Spam filter black/white list** `fmgr_spamfilter_bwl` **Spam filter black/white list entries** `fmgr_spamfilter_bwl_entries` **Spam filter banned words** `fmgr_spamfilter_bword` **Spam filter banned words entries** `fmgr_spamfilter_bword_entries` **Spam filter dnsbl** `fmgr_spamfilter_dnsbl` **Spam filter dnsbl entries** `fmgr_spamfilter_dnsbl_entries` **Spam filter IP trust** `fmgr_spamfilter_iptrust` **Spam filter IP trust entries** `fmgr_spamfilter_iptrust_entries` **Spam filter mail header** `fmgr_spamfilter_mheader` **Spam filter mail header entries** `fmgr_spamfilter_mheader_entries` **Spam filter profile** `fmgr_spamfilter_profile` **Spam filter profile Gmail** `fmgr_spamfilter_profile_gmail` **Spam filter profile IMAP** `fmgr_spamfilter_profile_imap` **Spam filter profile MAPI** `fmgr_spamfilter_profile_mapi` **Spam filter profile MSN Hotmail** `fmgr_spamfilter_profile_msnhotmail` **Spam filter profile POP3** `fmgr_spamfilter_profile_pop3` **Spam filter profile SMTP** `fmgr_spamfilter_profile_smtp` **Spam filter profile Yahoo Mail** `fmgr_spamfilter_profile_yahoomail`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Detect intrusions and control applications

Description	Manage IPS sensors, baselines and custom signatures, virtual patch profiles, and application control lists, categories and custom signatures.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Application control settings** `fmgr_application_list` **CASI profile** `fmgr_application_casi_profile` **CASI profile entries** `fmgr_application_casi_profile_entries` **Categories** `fmgr_application_categories` **Custom** `fmgr_application_custom` **Group** `fmgr_application_group` **List default network services** `fmgr_application_list_defaultnetworkservices` **List entries** `fmgr_application_list_entries` **List entries parameters** `fmgr_application_list_entries_parameters` **List entries parameters members** `fmgr_application_list_entries_parameters_members` **Baseline sensor** `fmgr_ips_baseline_sensor` **Baseline sensor entries** `fmgr_ips_baseline_sensor_entries` **Baseline sensor entries exempt IP** `fmgr_ips_baseline_sensor_entries_exemptip` **Baseline sensor filter** `fmgr_ips_baseline_sensor_filter` **Baseline sensor override** `fmgr_ips_baseline_sensor_override` **Baseline sensor override exempt IP** `fmgr_ips_baseline_sensor_override_exemptip` **IPS custom** `fmgr_ips_custom` **Sensor** `fmgr_ips_sensor` **Sensor entries** `fmgr_ips_sensor_entries` **Sensor entries exempt IP** `fmgr_ips_sensor_entries_exemptip` **Virtual patch profile** `fmgr_virtualpatch_profile` **Virtual patch profile exemption** `fmgr_virtualpatch_profile_exemption`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Prevent malware and data loss

Description	Configure antivirus profiles, file filtering, CIFS profiles, DLP sensors, dictionaries and fingerprints, and ICAP servers and profiles.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**MMS checksum** `fmgr_antivirus_mmschecksum` **MMS checksum entries** `fmgr_antivirus_mmschecksum_entries` **Notification** `fmgr_antivirus_notification` **Notification entries** `fmgr_antivirus_notification_entries` **Profile** `fmgr_antivirus_profile` **Profile CIFS** `fmgr_antivirus_profile_cifs` **Profile content disarm** `fmgr_antivirus_profile_contentdisarm` **Profile FTP** `fmgr_antivirus_profile_ftp` **Profile HTTP** `fmgr_antivirus_profile_http` **Profile IMAP** `fmgr_antivirus_profile_imap` **Profile MAPI** `fmgr_antivirus_profile_mapi` **Profile NAC quarantine** `fmgr_antivirus_profile_nacquar` **Profile NNTP** `fmgr_antivirus_profile_nntp` **Profile outbreak prevention** `fmgr_antivirus_profile_outbreakprevention` **Profile POP3** `fmgr_antivirus_profile_pop3` **Profile smb** `fmgr_antivirus_profile_smb` **Profile SMTP** `fmgr_antivirus_profile_smtp` **Profile SSH** `fmgr_antivirus_profile_ssh` **Profile websocket** `fmgr_antivirus_profile_websocket` **Domain controller** `fmgr_cifs_domaincontroller` **CIFS profile** `fmgr_cifs_profile` **Profile file filter** `fmgr_cifs_profile_filefilter` **Profile file filter entries** `fmgr_cifs_profile_filefilter_entries` **Profile server keytab** `fmgr_cifs_profile_serverkeytab` **Data type** `fmgr_dlp_datatype` **Dictionary** `fmgr_dlp_dictionary` **Dictionary entries** `fmgr_dlp_dictionary_entries` **Exact data match** `fmgr_dlp_exactdatamatch` **Exact data match columns** `fmgr_dlp_exactdatamatch_columns` **File pattern** `fmgr_dlp_filepattern` **File pattern entries** `fmgr_dlp_filepattern_entries` **Fingerprint sensitivity** `fmgr_dlp_fpsensitivity` **Label** `fmgr_dlp_label` **Label entries** `fmgr_dlp_label_entries` **DLP profile** `fmgr_dlp_profile` **Profile rule** `fmgr_dlp_profile_rule` **Sensitivity** `fmgr_dlp_sensitivity` **Sensor** `fmgr_dlp_sensor` **Sensor entries** `fmgr_dlp_sensor_entries` **Sensor filter** `fmgr_dlp_sensor_filter` **File filter profile** `fmgr_filefilter_profile` **File filter profile rules** `fmgr_filefilter_profile_rules` **ICAP profile** `fmgr_icap_profile` **Profile ICAP headers** `fmgr_icap_profile_icapheaders` **Profile response modification forward rules** `fmgr_icap_profile_respmodforwardrules` **Profile response modification forward rules header group** `fmgr_icap_profile_respmodforwardrules_headergroup` **Remote server group** `fmgr_icap_remoteservergroup` **Remote server group server list** `fmgr_icap_remoteservergroup_serverlist` **Server** `fmgr_icap_server` **Server group** `fmgr_icap_servergroup` **Server group server list** `fmgr_icap_servergroup_serverlist`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Secure carrier and telecom traffic

Description	Configure GTP, PFCP, MMS, Diameter and SCTP filtering profiles and carrier endpoint lists.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Diameter filter profile** `fmgr_diameterfilter_profile` **Carrier endpoint black/white list** `fmgr_firewall_carrierendpointbwl` **Carrier endpoint black/white list entries** `fmgr_firewall_carrierendpointbwl_entries` **GTP** `fmgr_firewall_gtp` **GTP APN** `fmgr_firewall_gtp_apn` **GTP IE remove policy** `fmgr_firewall_gtp_ieremovepolicy` **GTP IE validation** `fmgr_firewall_gtp_ievalidation` **GTP imsi** `fmgr_firewall_gtp_imsi` **GTP IP policy** `fmgr_firewall_gtp_ippolicy` **GTP message filter** `fmgr_firewall_gtp_messagefilter` **GTP message rate limit** `fmgr_firewall_gtp_messageratelimit` **GTP GTPv0 message rate limit** `fmgr_firewall_gtp_messageratelimitv0` **GTP GTPv1 message rate limit** `fmgr_firewall_gtp_messageratelimitv1` **GTP GTPv2 message rate limit** `fmgr_firewall_gtp_messageratelimitv2` **GTP no-IP policy** `fmgr_firewall_gtp_noippolicy` **GTP per-APN shaper** `fmgr_firewall_gtp_perapnshaper` **GTP policy** `fmgr_firewall_gtp_policy` **GTP policy v2** `fmgr_firewall_gtp_policyv2` **MMS profile** `fmgr_firewall_mmsprofile` **MMS profile dupe** `fmgr_firewall_mmsprofile_dupe` **MMS profile flood** `fmgr_firewall_mmsprofile_flood` **MMS profile notification** `fmgr_firewall_mmsprofile_notification` **MMS profile notification MSISDN** `fmgr_firewall_mmsprofile_notifmsisdn` **MMS profile outbreak prevention** `fmgr_firewall_mmsprofile_outbreakprevention` **PFCP** `fmgr_firewall_pfcp` **APN** `fmgr_gtp_apn` **APN group** `fmgr_gtp_apngrp` **IE allow list** `fmgr_gtp_ieallowlist` **IE allow list entries** `fmgr_gtp_ieallowlist_entries` **IE white list** `fmgr_gtp_iewhitelist` **IE white list entries** `fmgr_gtp_iewhitelist_entries` **GTPv0/v1 message filter** `fmgr_gtp_messagefilterv0v1` **GTPv2 message filter** `fmgr_gtp_messagefilterv2` **RAT timeout profile** `fmgr_gtp_rattimeoutprofile` **Tunnel limit** `fmgr_gtp_tunnellimit` **SCTP filter profile** `fmgr_sctpfilter_profile` **SCTP filter profile PPID filters** `fmgr_sctpfilter_profile_ppidfilters`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Configure inspection profiles, protocol options and SSL/SSH inspection

Description	Manage security profile groups, protocol options, SSL/SSH inspection profiles, SSH filters, VoIP profiles and decrypted traffic mirroring.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Decrypted traffic mirror** `fmgr_firewall_decryptedtrafficmirror` **Profile group** `fmgr_firewall_profilegroup` **Protocol options profile** `fmgr_firewall_profileprotocoloptions` **Protocol options profile CIFS** `fmgr_firewall_profileprotocoloptions_cifs` **Protocol options profile CIFS file filter** `fmgr_firewall_profileprotocoloptions_cifs_filefilter` **Protocol options profile CIFS file filter entries** `fmgr_firewall_profileprotocoloptions_cifs_filefilter_entries` **Protocol options profile CIFS server keytab** `fmgr_firewall_profileprotocoloptions_cifs_serverkeytab` **Protocol options profile DNS** `fmgr_firewall_profileprotocoloptions_dns` **Protocol options profile FTP** `fmgr_firewall_profileprotocoloptions_ftp` **Protocol options profile HTTP** `fmgr_firewall_profileprotocoloptions_http` **Protocol options profile IMAP** `fmgr_firewall_profileprotocoloptions_imap` **Protocol options profile mail signature** `fmgr_firewall_profileprotocoloptions_mailsignature` **Protocol options profile MAPI** `fmgr_firewall_profileprotocoloptions_mapi` **Protocol options profile NNTP** `fmgr_firewall_profileprotocoloptions_nntp` **Protocol options profile POP3** `fmgr_firewall_profileprotocoloptions_pop3` **Protocol options profile proxy redirect** `fmgr_firewall_profileprotocoloptions_proxyredirect` **Protocol options profile rtmp** `fmgr_firewall_profileprotocoloptions_rtmp` **Protocol options profile SMTP** `fmgr_firewall_profileprotocoloptions_smtp` **Protocol options profile SSH** `fmgr_firewall_profileprotocoloptions_ssh` **Protocol options profile websocket** `fmgr_firewall_profileprotocoloptions_websocket` **SSH local CA** `fmgr_firewall_ssh_localca` **SSL/SSH inspection profile** `fmgr_firewall_sslsshprofile` **SSL/SSH inspection profile dot** `fmgr_firewall_sslsshprofile_dot` **SSL/SSH inspection profile echo outer SNI** `fmgr_firewall_sslsshprofile_echoutersni` **SSL/SSH inspection profile ftps** `fmgr_firewall_sslsshprofile_ftps` **SSL/SSH inspection profile HTTPS** `fmgr_firewall_sslsshprofile_https` **SSL/SSH inspection profile imaps** `fmgr_firewall_sslsshprofile_imaps` **SSL/SSH inspection profile pop3s** `fmgr_firewall_sslsshprofile_pop3s` **SSL/SSH inspection profile smtps** `fmgr_firewall_sslsshprofile_smtps` **SSL/SSH inspection profile SSH** `fmgr_firewall_sslsshprofile_ssh` **SSL/SSH inspection profile SSL** `fmgr_firewall_sslsshprofile_ssl` **SSL/SSH inspection profile SSL client certificate** `fmgr_firewall_sslsshprofile_sslclientcertificate` **SSL/SSH inspection profile SSL exempt** `fmgr_firewall_sslsshprofile_sslexempt` **SSL/SSH inspection profile SSL server** `fmgr_firewall_sslsshprofile_sslserver` **SSH filter profile** `fmgr_sshfilter_profile` **SSH filter profile file filter** `fmgr_sshfilter_profile_filefilter` **SSH filter profile file filter entries** `fmgr_sshfilter_profile_filefilter_entries` **SSH filter profile shell commands** `fmgr_sshfilter_profile_shellcommands` **Profile** `fmgr_voip_profile` **Profile msrp** `fmgr_voip_profile_msrp` **Profile SCCP** `fmgr_voip_profile_sccp` **Profile SIP** `fmgr_voip_profile_sip`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Manage users, groups and authentication servers

Description	Create local users and groups, LDAP, RADIUS, TACACS+, SAML, OIDC, FSSO and Kerberos sources, authentication schemes and rules, device identification and NAC policies, and FortiClient EMS connectors.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Authentication scheme** `fmgr_authentication_scheme` **Credential store domain controller** `fmgr_credentialstore_domaincontroller` **Endpoint control FortiClient EMS** `fmgr_endpointcontrol_fctems` **NAC profile** `fmgr_nacprofile` **AD group** `fmgr_user_adgrp` **Certificate** `fmgr_user_certificate` **Device** `fmgr_user_device` **Device dynamic mapping** `fmgr_user_device_dynamicmapping` **Device tagging** `fmgr_user_device_tagging` **Device access list** `fmgr_user_deviceaccesslist` **Device access list device list** `fmgr_user_deviceaccesslist_devicelist` **Device category** `fmgr_user_devicecategory` **Device group** `fmgr_user_devicegroup` **Device group dynamic mapping** `fmgr_user_devicegroup_dynamicmapping` **Device group tagging** `fmgr_user_devicegroup_tagging` **Domain controller** `fmgr_user_domaincontroller` **Domain controller extra server** `fmgr_user_domaincontroller_extraserver` **Exchange** `fmgr_user_exchange` **External identity provider** `fmgr_user_externalidentityprovider` **FortiFlex VM** `fmgr_user_flexvm` **FortiToken** `fmgr_user_fortitoken` **FSSO** `fmgr_user_fsso` **FSSO dynamic mapping** `fmgr_user_fsso_dynamicmapping` **FSSO polling** `fmgr_user_fssopolling` **FSSO polling AD group** `fmgr_user_fssopolling_adgrp` **Group** `fmgr_user_group` **Group dynamic mapping** `fmgr_user_group_dynamicmapping` **Group dynamic mapping guest** `fmgr_user_group_dynamicmapping_guest` **Group dynamic mapping match** `fmgr_user_group_dynamicmapping_match` **Group dynamic mapping SSL VPN OS check list** `fmgr_user_group_dynamicmapping_sslvpnoschecklist` **Group guest** `fmgr_user_group_guest` **Group match** `fmgr_user_group_match` **JSON** `fmgr_user_json` **Kerberos keytab** `fmgr_user_krbkeytab` **LDAP** `fmgr_user_ldap` **LDAP dynamic mapping** `fmgr_user_ldap_dynamicmapping` **Local** `fmgr_user_local` **Local dynamic mapping** `fmgr_user_local_dynamicmapping` **OIDC** `fmgr_user_oidc` **Password policy** `fmgr_user_passwordpolicy` **Peer** `fmgr_user_peer` **Peer group** `fmgr_user_peergrp` **POP3** `fmgr_user_pop3` **RADIUS** `fmgr_user_radius` **RADIUS accounting server** `fmgr_user_radius_accountingserver` **RADIUS dynamic mapping** `fmgr_user_radius_dynamicmapping` **RADIUS dynamic mapping accounting server** `fmgr_user_radius_dynamicmapping_accountingserver` **SAML** `fmgr_user_saml` **SAML dynamic mapping** `fmgr_user_saml_dynamicmapping` **SCIM** `fmgr_user_scim` **Security exempt list** `fmgr_user_securityexemptlist` **Security exempt list rule** `fmgr_user_securityexemptlist_rule` **TACACS+** `fmgr_user_tacacs` **TACACS+ dynamic mapping** `fmgr_user_tacacs_dynamicmapping`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Configure SSL VPN web portals

Description	Manage SSL VPN portals, realms, bookmarks, landing pages, host checks and virtual desktop applications, and SSL VPN settings.

Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**SSL settings** `fmgr_vpn_ssl_settings` **SSL settings authentication rule** `fmgr_vpn_ssl_settings_authenticationrule` **Host check software** `fmgr_vpnsslweb_hostchecksoftware` **Host check software check item list** `fmgr_vpnsslweb_hostchecksoftware_checkitemlist` **Portal** `fmgr_vpnsslweb_portal` **Portal bookmark group** `fmgr_vpnsslweb_portal_bookmarkgroup` **Portal bookmark group bookmarks** `fmgr_vpnsslweb_portal_bookmarkgroup_bookmarks` **Portal bookmark group bookmarks formdata** `fmgr_vpnsslweb_portal_bookmarkgroup_bookmarks_formdata` **Portal landing page** `fmgr_vpnsslweb_portal_landingpage` **Portal landing page formdata** `fmgr_vpnsslweb_portal_landingpage_formdata` **Portal MAC address check rule** `fmgr_vpnsslweb_portal_macaddrcheckrule` **Portal OS check list** `fmgr_vpnsslweb_portal_oschecklist` **Portal split DNS** `fmgr_vpnsslweb_portal_splitdns` **Realm** `fmgr_vpnsslweb_realm` **Virtual desktop application list** `fmgr_vpnsslweb_virtualdesktopapplist` **Virtual desktop application list apps** `fmgr_vpnsslweb_virtualdesktopapplist_apps`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Build IPsec VPNs and VPN topologies

Description	Configure IPsec phase 1 and manual key settings, FEC, KMIP servers, QKD, dynamic VPN tunnels, and VPN Manager nodes and tables.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**VPN tunnel** `fmgr_dynamic_vpntunnel` **VPN tunnel dynamic mapping** `fmgr_dynamic_vpntunnel_dynamicmapping` **IPsec FEC** `fmgr_vpn_ipsec_fec` **IPsec FEC mappings** `fmgr_vpn_ipsec_fec_mappings` **IPsec FEC mappings ToS** `fmgr_vpn_ipsec_fec_mappings_tos` **IPsec manual key** `fmgr_vpn_ipsec_manualkey` **IPsec phase1** `fmgr_vpn_ipsec_phase1` **IPsec phase1 IPv4 exclude range** `fmgr_vpn_ipsec_phase1_ipv4excluderange` **IPsec phase1 IPv6 exclude range** `fmgr_vpn_ipsec_phase1_ipv6excluderange` **KMIP server** `fmgr_vpn_kmipserver` **KMIP server server list** `fmgr_vpn_kmipserver_serverlist` **QKD** `fmgr_vpn_qkd` **Node** `fmgr_vpnmgr_node` **Node IP range** `fmgr_vpnmgr_node_iprange` **Node IPv4 exclude range** `fmgr_vpnmgr_node_ipv4excluderange` **Node protected subnet** `fmgr_vpnmgr_node_protectedsubnet` **Node summary address** `fmgr_vpnmgr_node_summaryaddr` **VPN table** `fmgr_vpnmgr_vpntable`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Configure SD-WAN and routing

Description	Create SD-WAN and virtual WAN link templates with members, zones, health checks, SLAs and services, and configure route maps, prefix lists, community and AS path lists and access lists.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Virtual WAN link members** `fmgr_dynamic_virtualwanlink_members` **Virtual WAN link members dynamic mapping** `fmgr_dynamic_virtualwanlink_members_dynamicmapping` **Virtual WAN link neighbor** `fmgr_dynamic_virtualwanlink_neighbor` **Virtual WAN link neighbor dynamic mapping** `fmgr_dynamic_virtualwanlink_neighbor_dynamicmapping` **Virtual WAN link server** `fmgr_dynamic_virtualwanlink_server` **Virtual WAN link server dynamic mapping** `fmgr_dynamic_virtualwanlink_server_dynamicmapping` **Identity-based route** `fmgr_firewall_identitybasedroute` **Identity-based route rule** `fmgr_firewall_identitybasedroute_rule` **ADOM** `fmgr_pm_wanprof_adom` **Package** `fmgr_pm_wanprof_pkg` **Scope member** `fmgr_pm_wanprof_scopemember` **Access list** `fmgr_router_accesslist` **IPv6 access list** `fmgr_router_accesslist6` **IPv6 access list rule** `fmgr_router_accesslist6_rule` **Access list rule** `fmgr_router_accesslist_rule` **AS path list** `fmgr_router_aspathlist` **AS path list rule** `fmgr_router_aspathlist_rule` **Community list** `fmgr_router_communitylist` **Community list rule** `fmgr_router_communitylist_rule` **Prefix list** `fmgr_router_prefixlist` **IPv6 prefix list** `fmgr_router_prefixlist6` **IPv6 prefix list rule** `fmgr_router_prefixlist6_rule` **Prefix list rule** `fmgr_router_prefixlist_rule` **Route map** `fmgr_router_routemap` **Route map rule** `fmgr_router_routemap_rule` **SD-WAN** `fmgr_wanprof_system_sdwan` **SD-WAN duplication** `fmgr_wanprof_system_sdwan_duplication` **SD-WAN health check** `fmgr_wanprof_system_sdwan_healthcheck` **SD-WAN health check SLA** `fmgr_wanprof_system_sdwan_healthcheck_sla` **SD-WAN FortiGuard health check** `fmgr_wanprof_system_sdwan_healthcheckfortiguard` **SD-WAN FortiGuard health check SLA** `fmgr_wanprof_system_sdwan_healthcheckfortiguard_sla` **SD-WAN members** `fmgr_wanprof_system_sdwan_members` **SD-WAN neighbor** `fmgr_wanprof_system_sdwan_neighbor` **SD-WAN service** `fmgr_wanprof_system_sdwan_service` **SD-WAN service SLA** `fmgr_wanprof_system_sdwan_service_sla` **SD-WAN zone** `fmgr_wanprof_system_sdwan_zone` **Virtual WAN link** `fmgr_wanprof_system_virtualwanlink` **Virtual WAN link health check** `fmgr_wanprof_system_virtualwanlink_healthcheck` **Virtual WAN link health check SLA** `fmgr_wanprof_system_virtualwanlink_healthcheck_sla` **WAN profile system virtual WAN link members** `fmgr_wanprof_system_virtualwanlink_members` **WAN profile system virtual WAN link neighbor** `fmgr_wanprof_system_virtualwanlink_neighbor` **Virtual WAN link service** `fmgr_wanprof_system_virtualwanlink_service` **Virtual WAN link service SLA** `fmgr_wanprof_system_virtualwanlink_service_sla`

Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Standardise FortiGate settings with device profiles

Description	Maintain device profiles for logging, SNMP, NTP, DNS, email and central management, plus dynamic per-device interface and object mappings.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Profile FortiAnalyzer** `fmgr_devprof_device_profile_fortianalyzer` **Profile FortiGuard** `fmgr_devprof_device_profile_fortiguard` **Import** `fmgr_devprof_import` **FortiAnalyzer setting** `fmgr_devprof_log_fortianalyzer_setting` **FortiAnalyzer Cloud setting** `fmgr_devprof_log_fortianalyzercloud_setting` **Syslog filter** `fmgr_devprof_log_syslogd_filter` **Syslog filter exclude list** `fmgr_devprof_log_syslogd_filter_excludelist` **Syslog filter exclude list fields** `fmgr_devprof_log_syslogd_filter_excludelist_fields` **Syslog filter freestyle** `fmgr_devprof_log_syslogd_filter_freestyle` **Syslog setting** `fmgr_devprof_log_syslogd_setting` **Syslog setting custom field name** `fmgr_devprof_log_syslogd_setting_customfieldname` **Syslog setting log templates** `fmgr_devprof_log_syslogd_setting_logtemplates` **Central management** `fmgr_devprof_system_centralmanagement` **Central management server list** `fmgr_devprof_system_centralmanagement_serverlist` **DNS** `fmgr_devprof_system_dns` **Email server** `fmgr_devprof_system_emailserver` **Global** `fmgr_devprof_system_global` **NTP** `fmgr_devprof_system_ntp` **NTP server** `fmgr_devprof_system_ntp_ntpserver` **SNMP community** `fmgr_devprof_system_snmp_community` **SNMP community hosts** `fmgr_devprof_system_snmp_community_hosts` **SNMP community hosts6** `fmgr_devprof_system_snmp_community_hosts6` **SNMP system info** `fmgr_devprof_system_snmp_sysinfo` **SNMP user** `fmgr_devprof_system_snmp_user` **Template interface** `fmgr_devprof_system_template_interface` **Template interface IP range** `fmgr_devprof_system_template_interface_iprange` **Input interface** `fmgr_dynamic_input_interface` **Input interface dynamic mapping** `fmgr_dynamic_input_interface_dynamicmapping` **Interface** `fmgr_dynamic_interface` **Interface dynamic mapping** `fmgr_dynamic_interface_dynamicmapping` **Interface platform mapping** `fmgr_dynamic_interface_platformmapping` **Log NPU server server group** `fmgr_dynamic_log_npuserver_servergroup` **Log NPU server server group dynamic mapping** `fmgr_dynamic_log_npuserver_servergroup_dynamicmapping` **Multicast interface** `fmgr_dynamic_multicast_interface` **Multicast interface dynamic mapping** `fmgr_dynamic_multicast_interface_dynamicmapping` **ADOM** `fmgr_pm_devprof_adom` **Package** `fmgr_pm_devprof_pkg` **Scope member** `fmgr_pm_devprof_scopemember`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Customise FortiGate system objects

Description	Edit replacement messages and images, NPU hardware acceleration settings, GeoIP overrides, external resources, object tags, sniffers and virtual wire pairs.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Replacement message admin** `fmgr_devprof_system_replacemsg_admin` **Replacement message alert mail** `fmgr_devprof_system_replacemsg_alertmail` **Replacement message auth** `fmgr_devprof_system_replacemsg_auth` **Replacement message device detection portal** `fmgr_devprof_system_replacemsg_devicedetectionportal` **Replacement message ec** `fmgr_devprof_system_replacemsg_ec` **Replacement message FortiGuard web filter** `fmgr_devprof_system_replacemsg_fortiguardwf` **Replacement message FTP** `fmgr_devprof_system_replacemsg_ftp` **Replacement message HTTP** `fmgr_devprof_system_replacemsg_http` **Replacement message mail** `fmgr_devprof_system_replacemsg_mail` **Replacement message MMS** `fmgr_devprof_system_replacemsg_mms` **Replacement message NAC quarantine** `fmgr_devprof_system_replacemsg_nacquar` **Replacement message NNTP** `fmgr_devprof_system_replacemsg_nntp` **Replacement message spam** `fmgr_devprof_system_replacemsg_spam` **Replacement message sslvpn** `fmgr_devprof_system_replacemsg_sslvpn` **Replacement message traffic quota** `fmgr_devprof_system_replacemsg_trafficquota` **Replacement message utm** `fmgr_devprof_system_replacemsg_utm` **Replacement message web proxy** `fmgr_devprof_system_replacemsg_webproxy` **NPU server** `fmgr_log_npuserver` **NPU server server group** `fmgr_log_npuserver_servergroup` **NPU server server info** `fmgr_log_npuserver_serverinfo` **External resource** `fmgr_system_externalresource` **External resource dynamic mapping** `fmgr_system_externalresource_dynamicmapping` **GeoIP country** `fmgr_system_geoipcountry` **GeoIP override** `fmgr_system_geoipoverride` **GeoIP override IPv6 range** `fmgr_system_geoipoverride_ip6range` **GeoIP override IP range** `fmgr_system_geoipoverride_iprange` **NPU** `fmgr_system_npu` **NPU background SSE scan** `fmgr_system_npu_backgroundssescan` **NPU DoS options** `fmgr_system_npu_dosoptions` **NPU DSW DTS profile** `fmgr_system_npu_dswdtsprofile` **NPU DSW queue DTS profile** `fmgr_system_npu_dswqueuedtsprofile` **NPU FP anomaly** `fmgr_system_npu_fpanomaly` **NPU HPE** `fmgr_system_npu_hpe` **NPU ICMP error rate control** `fmgr_system_npu_icmperrorratectrl` **NPU ICMP rate control** `fmgr_system_npu_icmpratectrl` **NPU IP reassembly** `fmgr_system_npu_ipreassembly` **NPU ISF NP queues** `fmgr_system_npu_isfnpqueues` **NPU NP queues** `fmgr_system_npu_npqueues` **NPU NP queues Ethernet type** `fmgr_system_npu_npqueues_ethernettype` **NPU NP queues IP protocol** `fmgr_system_npu_npqueues_ipprotocol` **NPU NP queues IP service** `fmgr_system_npu_npqueues_ipservice` **NPU NP queues profile** `fmgr_system_npu_npqueues_profile` **NPU NP queues scheduler** `fmgr_system_npu_npqueues_scheduler` **NPU TCAM** `fmgr_system_npu_nputcam` **NPU TCAM data** `fmgr_system_npu_nputcam_data` **NPU TCAM mask** `fmgr_system_npu_nputcam_mask` **NPU TCAM MIRACT** `fmgr_system_npu_nputcam_miract` **NPU TCAM PRIACT** `fmgr_system_npu_nputcam_priact` **NPU TCAM SACT** `fmgr_system_npu_nputcam_sact` **NPU TCAM TACT** `fmgr_system_npu_nputcam_tact` **NPU port CPU map** `fmgr_system_npu_portcpumap` **Port NPU map** `fmgr_system_npu_portnpumap` **NPU port path option** `fmgr_system_npu_portpathoption` **NPU priority protocol** `fmgr_system_npu_priorityprotocol` **NPU SSE HA scan** `fmgr_system_npu_ssehascan` **NPU SWEH hash** `fmgr_system_npu_swehhash` **NPU SWTR hash** `fmgr_system_npu_swtrhash` **NPU TCP timeout profile** `fmgr_system_npu_tcptimeoutprofile` **NPU UDP timeout profile** `fmgr_system_npu_udptimeoutprofile` **Object tag** `fmgr_system_objecttag` **Object tagging** `fmgr_system_objecttagging` **Replacement message group** `fmgr_system_replacemsggroup` **Replacement message group admin** `fmgr_system_replacemsggroup_admin` **Replacement message group alert mail** `fmgr_system_replacemsggroup_alertmail` **Replacement message group auth** `fmgr_system_replacemsggroup_auth` **Replacement message group automation** `fmgr_system_replacemsggroup_automation` **Replacement message group custom message** `fmgr_system_replacemsggroup_custommessage` **Replacement message group device detection portal** `fmgr_system_replacemsggroup_devicedetectionportal` **Replacement message group ec** `fmgr_system_replacemsggroup_ec` **Replacement message group FortiGuard web filter** `fmgr_system_replacemsggroup_fortiguardwf` **Replacement message group FTP** `fmgr_system_replacemsggroup_ftp` **Replacement message group HTTP** `fmgr_system_replacemsggroup_http` **Replacement message group ICAP** `fmgr_system_replacemsggroup_icap` **Replacement message group mail** `fmgr_system_replacemsggroup_mail` **Replacement message group MM1** `fmgr_system_replacemsggroup_mm1` **Replacement message group MM3** `fmgr_system_replacemsggroup_mm3` **Replacement message group MM4** `fmgr_system_replacemsggroup_mm4` **Replacement message group MM7** `fmgr_system_replacemsggroup_mm7` **Replacement message group MMS** `fmgr_system_replacemsggroup_mms` **Replacement message group NAC quarantine** `fmgr_system_replacemsggroup_nacquar` **Replacement message group NNTP** `fmgr_system_replacemsggroup_nntp` **Replacement message group spam** `fmgr_system_replacemsggroup_spam` **Replacement message group sslvpn** `fmgr_system_replacemsggroup_sslvpn` **Replacement message group traffic quota** `fmgr_system_replacemsggroup_trafficquota` **Replacement message group utm** `fmgr_system_replacemsggroup_utm` **Replacement message group web proxy** `fmgr_system_replacemsggroup_webproxy` **Replacement message image** `fmgr_system_replacemsgimage` **Sniffer** `fmgr_system_sniffer` **Virtual wire pair** `fmgr_system_virtualwirepair`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Manage devices, ADOMs and device groups

Description	Add, discover, import, update and delete managed devices, manage ADOMs, device groups, folders and revisions, onboard through authorization templates, and reclaim device tunnels.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**ADOM options** `fmgr_adom_options` **Deployment get controller** `fmgr_deployment_get_controller_status` **Command add device** `fmgr_dvm_cmd_add_device` **Command add device list** `fmgr_dvm_cmd_add_devlist` **Command change HA sequence** `fmgr_dvm_cmd_changehaseq` **Command del device** `fmgr_dvm_cmd_del_device` **Command del device list** `fmgr_dvm_cmd_del_devlist` **Command discover device** `fmgr_dvm_cmd_discover_device` **Command import device list** `fmgr_dvm_cmd_import_devlist` **Command reload device list** `fmgr_dvm_cmd_reload_devlist` **Command update device** `fmgr_dvm_cmd_update_device` **Command update device list** `fmgr_dvm_cmd_update_devlist` **ADOM** `fmgr_dvmdb_adom` **ADOM object member** `fmgr_dvmdb_adom_objectmember` **Device** `fmgr_dvmdb_device` **Device replace sn** `fmgr_dvmdb_device_replace_sn` **Device VDOM** `fmgr_dvmdb_device_vdom` **Folder** `fmgr_dvmdb_folder` **Group** `fmgr_dvmdb_group` **Group object member** `fmgr_dvmdb_group_objectmember` **Revision** `fmgr_dvmdb_revision` **Upgrade** `fmgr_dvmdb_upgrade` **Exec FGFM reclaim device tunnel** `fmgr_exec_fgfm_reclaimdevtunnel` **Device blueprint** `fmgr_fmg_device_blueprint` **Fabric authorization template** `fmgr_fmg_fabric_authorization_template` **Fabric authorization template platforms** `fmgr_fmg_fabric_authorization_template_platforms` **Policy manager config upgrade** `fmgr_pm_config_upgrade` **DM** `fmgr_system_dm` **Multicast policy disabled ADOMs** `fmgr_system_mcpolicydisabledadoms`

Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Control workspace locking, commits and approval workflows

Description	Lock and unlock devices and objects, commit workspace changes, and run approve and revert workflows with approval matrices.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Workflow approve** `fmgr_dvmdb_workflow_approve` **Workflow discard** `fmgr_dvmdb_workflow_discard` **Workflow drop** `fmgr_dvmdb_workflow_drop` **Workflow reject** `fmgr_dvmdb_workflow_reject` **Workflow repair** `fmgr_dvmdb_workflow_repair` **Workflow revert** `fmgr_dvmdb_workflow_revert` **Workflow review** `fmgr_dvmdb_workflow_review` **Workflow save** `fmgr_dvmdb_workflow_save` **Workflow start** `fmgr_dvmdb_workflow_start` **Workflow submit** `fmgr_dvmdb_workflow_submit` **Workspace commit** `fmgr_dvmdb_workspace_commit` **Workspace commit device** `fmgr_dvmdb_workspace_commit_dev` **Workspace commit object** `fmgr_dvmdb_workspace_commit_obj` **Workspace commit package** `fmgr_dvmdb_workspace_commit_pkg` **Workspace lock** `fmgr_dvmdb_workspace_lock` **Workspace lock device** `fmgr_dvmdb_workspace_lock_dev` **Workspace lock object** `fmgr_dvmdb_workspace_lock_obj` **Workspace lock package** `fmgr_dvmdb_workspace_lock_pkg` **Workspace unlock** `fmgr_dvmdb_workspace_unlock` **Workspace unlock device** `fmgr_dvmdb_workspace_unlock_dev` **Workspace unlock object** `fmgr_dvmdb_workspace_unlock_obj` **Workspace unlock package** `fmgr_dvmdb_workspace_unlock_pkg` **Policy manager config workspace commit** `fmgr_pm_config_workspace_commit` **Policy manager config workspace lock** `fmgr_pm_config_workspace_lock` **Policy manager config workspace unlock** `fmgr_pm_config_workspace_unlock` **Workflow approval matrix** `fmgr_system_workflow_approvalmatrix` **Workflow approval matrix approver** `fmgr_system_workflow_approvalmatrix_approver`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Run scripts and manage CLI templates, variables and metadata

Description	Run and schedule scripts, manage CLI templates, template groups, variables and meta fields, and export Ansible playbooks.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Metafields ADOM** `fmgr_dvmdb_metafields_adom` **Metafields device** `fmgr_dvmdb_metafields_device` **Metafields group** `fmgr_dvmdb_metafields_group` **Script** `fmgr_dvmdb_script` **Script execute** `fmgr_dvmdb_script_execute` **Script object member** `fmgr_dvmdb_script_objectmember` **Script schedule** `fmgr_dvmdb_script_scriptschedule` **Export playbooks** `fmgr_export_playbooks` **FortiManager script** `fmgr_fmg_script` **FortiManager script schedule** `fmgr_fmg_script_schedule` **Variable** `fmgr_fmg_variable` **Variable dynamic mapping** `fmgr_fmg_variable_dynamicmapping` **Metafields system admin user** `fmgr_metafields_system_admin_user` **Meta reference** `fmgr_pm_config_meta_reference` **Metafields firewall address** `fmgr_pm_config_metafields_firewall_address` **Metafields firewall address group** `fmgr_pm_config_metafields_firewall_addrgrp` **Metafields firewall central SNAT map** `fmgr_pm_config_metafields_firewall_centralsnatmap` **Metafields firewall policy** `fmgr_pm_config_metafields_firewall_policy` **Metafields firewall service custom** `fmgr_pm_config_metafields_firewall_service_custom` **Metafields firewall service group** `fmgr_pm_config_metafields_firewall_service_group` **Meta** `fmgr_system_meta` **System meta fields** `fmgr_system_meta_sysmetafields` **Metadata admins** `fmgr_system_metadata_admins` **Templates** `fmgr_template` **Template groups** `fmgr_templategroup`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Administer FortiManager administrators and login

Description	Manage administrators, profiles, groups, RADIUS, LDAP and TACACS+ logins, password policy, SAML single sign-on and login sessions.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Login challenge** `fmgr_sys_login_challenge` **Login user** `fmgr_sys_login_user` **Logout** `fmgr_sys_logout` **Admin group** `fmgr_system_admin_group` **Admin group member** `fmgr_system_admin_group_member` **Admin LDAP** `fmgr_system_admin_ldap` **Admin LDAP ADOM** `fmgr_system_admin_ldap_adom` **Admin profile** `fmgr_system_admin_profile` **Admin profile data mask custom fields** `fmgr_system_admin_profile_datamaskcustomfields` **Admin profile write password profiles** `fmgr_system_admin_profile_writepasswdprofiles` **Admin profile write password user list** `fmgr_system_admin_profile_writepasswduserlist` **Admin RADIUS** `fmgr_system_admin_radius` **Admin setting** `fmgr_system_admin_setting` **Admin TACACS+** `fmgr_system_admin_tacacs` **Admin user** `fmgr_system_admin_user` **Admin user ADOM** `fmgr_system_admin_user_adom` **Admin user ADOM exclusions** `fmgr_system_admin_user_adomexclude` **Admin user application filter** `fmgr_system_admin_user_appfilter` **Admin user dashboard** `fmgr_system_admin_user_dashboard` **Admin user dashboard tabs** `fmgr_system_admin_user_dashboardtabs` **Admin user IPS filter** `fmgr_system_admin_user_ipsfilter` **Admin user metadata** `fmgr_system_admin_user_metadata` **Admin user policy block** `fmgr_system_admin_user_policyblock` **Admin user policy package** `fmgr_system_admin_user_policypackage` **Admin user restrict device VDOM** `fmgr_system_admin_user_restrictdevvdom` **Admin user web filter** `fmgr_system_admin_user_webfilter` **Password policy** `fmgr_system_passwordpolicy` **SAML** `fmgr_system_saml` **SAML fabric IdP** `fmgr_system_saml_fabricidp`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Configure FortiManager networking and notifications

Description	Configure FortiManager interfaces, routes, DNS, DHCP, NTP, SNMP, local-in policies, mail and SMS servers and global attributes.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**DHCP server** `fmgr_system_dhcp_server` **DHCP server exclude range** `fmgr_system_dhcp_server_excluderange` **DHCP server IP range** `fmgr_system_dhcp_server_iprange` **DHCP server options** `fmgr_system_dhcp_server_options` **DHCP server reserved address** `fmgr_system_dhcp_server_reservedaddress` **DNS** `fmgr_system_dns` **DNS database** `fmgr_system_dnsdatabase` **DNS database DNS entry** `fmgr_system_dnsdatabase_dnsentry` **Fips** `fmgr_system_fips` **Global** `fmgr_system_global` **Interface** `fmgr_system_interface` **Interface IPv6** `fmgr_system_interface_ipv6` **Interface member** `fmgr_system_interface_member` **Local-in policy** `fmgr_system_localinpolicy` **IPv6 local-in policy** `fmgr_system_localinpolicy6` **IPv6 local-in policy dport** `fmgr_system_localinpolicy6_dport` **IPv6 local-in policy dst** `fmgr_system_localinpolicy6_dst` **IPv6 local-in policy intf** `fmgr_system_localinpolicy6_intf` **IPv6 local-in policy src** `fmgr_system_localinpolicy6_src` **Local-in policy dport** `fmgr_system_localinpolicy_dport` **Local-in policy dst** `fmgr_system_localinpolicy_dst` **Local-in policy intf** `fmgr_system_localinpolicy_intf` **Local-in policy src** `fmgr_system_localinpolicy_src` **Mail** `fmgr_system_mail` **NTP** `fmgr_system_ntp` **NTP server** `fmgr_system_ntp_ntpserver` **Route** `fmgr_system_route` **Route6** `fmgr_system_route6` **SMS server** `fmgr_system_smsserver` **SNMP community** `fmgr_system_snmp_community` **SNMP community hosts** `fmgr_system_snmp_community_hosts` **SNMP community hosts6** `fmgr_system_snmp_community_hosts6` **SNMP system info** `fmgr_system_snmp_sysinfo` **SNMP user** `fmgr_system_snmp_user`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Operate FortiManager: HA, backup and API utilities

Description	Configure HA and clustering, back up and restore, set auto-deletion, reboot, check task results and hit counts, and send generic, clone, move or rename API requests.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Clone objects** `fmgr_clone` **Gather facts** `fmgr_fact` **Generic API requests** `fmgr_generic` **Move objects** `fmgr_move` **Rename objects** `fmgr_rename` **Backup** `fmgr_sys_backup` **Generate WSDL** `fmgr_sys_generate_wsdl` **Hit count** `fmgr_sys_hitcount` **Proxy JSON** `fmgr_sys_proxy_json` **Reboot** `fmgr_sys_reboot` **Task result** `fmgr_sys_task_result` **Auto-delete** `fmgr_system_autodelete` **Auto-delete DLP files auto-deletion** `fmgr_system_autodelete_dlpfilesautodeletion` **Auto-delete log auto-deletion** `fmgr_system_autodelete_logautodeletion` **Auto-delete quarantine files auto-deletion** `fmgr_system_autodelete_quarantinefilesautodeletion` **Auto-delete report auto-deletion** `fmgr_system_autodelete_reportautodeletion` **Backup all settings** `fmgr_system_backup_allsettings` **Custom language** `fmgr_system_customlanguage` **Docker** `fmgr_system_docker` **FortiManager cluster** `fmgr_system_fmgcluster` **FortiManager cluster peer** `fmgr_system_fmgcluster_peer` **Guiact** `fmgr_system_guiact` **HA** `fmgr_system_ha` **HA monitored interfaces** `fmgr_system_ha_monitoredinterfaces` **HA monitored IPs** `fmgr_system_ha_monitoredips` **HA peer** `fmgr_system_ha_peer` **HA scheduled check** `fmgr_system_hascheduledcheck`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Collect logs and generate reports

Description	Configure local logging and remote log destinations, log fetching, rate limits, SQL log database, FortiView, reports and alert events.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)

Key content	**Custom field** `fmgr_log_customfield` **Alert console** `fmgr_system_alertconsole` **Alert email** `fmgr_system_alertemail` **Alert event** `fmgr_system_alertevent` **Alert event alert destination** `fmgr_system_alertevent_alertdestination` **FortiView auto-cache** `fmgr_system_fortiview_autocache` **FortiView setting** `fmgr_system_fortiview_setting` **Local log disk filter** `fmgr_system_locallog_disk_filter` **Local log disk setting** `fmgr_system_locallog_disk_setting` **Local log FortiAnalyzer 2 filter** `fmgr_system_locallog_fortianalyzer2_filter` **Local log FortiAnalyzer 2 setting** `fmgr_system_locallog_fortianalyzer2_setting` **Local log FortiAnalyzer 3 filter** `fmgr_system_locallog_fortianalyzer3_filter` **Local log FortiAnalyzer 3 setting** `fmgr_system_locallog_fortianalyzer3_setting` **Local log FortiAnalyzer filter** `fmgr_system_locallog_fortianalyzer_filter` **Local log FortiAnalyzer setting** `fmgr_system_locallog_fortianalyzer_setting` **Local log memory filter** `fmgr_system_locallog_memory_filter` **Local log memory setting** `fmgr_system_locallog_memory_setting` **Local log setting** `fmgr_system_locallog_setting` **Local log syslog 2 filter** `fmgr_system_locallog_syslogd2_filter` **Local log syslog 2 setting** `fmgr_system_locallog_syslogd2_setting` **Local log syslog 3 filter** `fmgr_system_locallog_syslogd3_filter` **Local log syslog 3 setting** `fmgr_system_locallog_syslogd3_setting` **Local log syslog filter** `fmgr_system_locallog_syslogd_filter` **Local log syslog setting** `fmgr_system_locallog_syslogd_setting` **Local log TACACS+ accounting filter** `fmgr_system_locallog_tacacsaccounting_filter` **Local log TACACS+ accounting setting** `fmgr_system_locallog_tacacsaccounting_setting` **Log alert** `fmgr_system_log_alert` **Log API rate limit** `fmgr_system_log_apiratelimit` **Log device disable** `fmgr_system_log_devicedisable` **Log device selector** `fmgr_system_log_deviceselector` **Log FortiOS policy statistics** `fmgr_system_log_fospolicystats` **Log interface statistics** `fmgr_system_log_interfacestats` **Log IOC** `fmgr_system_log_ioc` **Log mail domain** `fmgr_system_log_maildomain` **Log rate limit** `fmgr_system_log_ratelimit` **Log rate limit device** `fmgr_system_log_ratelimit_device` **Log rate limit rate limits** `fmgr_system_log_ratelimit_ratelimits` **Log settings** `fmgr_system_log_settings` **Log settings client certificate authentication** `fmgr_system_log_settings_clientcertauth` **Log settings rolling analyzer** `fmgr_system_log_settings_rollinganalyzer` **Log settings rolling local** `fmgr_system_log_settings_rollinglocal` **Log settings rolling regular** `fmgr_system_log_settings_rollingregular` **Log topology** `fmgr_system_log_topology` **Log UEBA** `fmgr_system_log_ueba` **Log fetch client profile** `fmgr_system_logfetch_clientprofile` **Log fetch client profile device filter** `fmgr_system_logfetch_clientprofile_devicefilter` **Log fetch client profile log filter** `fmgr_system_logfetch_clientprofile_logfilter` **Log fetch server settings** `fmgr_system_logfetch_serversettings` **Report auto-cache** `fmgr_system_report_autocache` **Report estimated browse time** `fmgr_system_report_estbrowsetime` **Report group** `fmgr_system_report_group` **Report group chart alternatives** `fmgr_system_report_group_chartalternative` **Report group by** `fmgr_system_report_group_groupby` **Report setting** `fmgr_system_report_setting` **SQL** `fmgr_system_sql` **SQL custom index** `fmgr_system_sql_customindex` **SQL custom skip index** `fmgr_system_sql_customskipidx` **SQL time-series index field** `fmgr_system_sql_tsindexfield` **Syslog** `fmgr_system_syslog`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Use Case: Manage FortiGuard updates and firmware images

Description	Configure the FortiGuard update service, push and server overrides, update schedules, disk quota and device firmware upgrades.
Collection	`fortinet.fortimanager` (Certified, Fortinet, v2.15.0, updated 2026-08-11)
Key content	**Analyzer virus report** `fmgr_fmupdate_analyzer_virusreport` **Avips advanced log** `fmgr_fmupdate_avips_advancedlog` **Avips web proxy** `fmgr_fmupdate_avips_webproxy` **Custom URL list** `fmgr_fmupdate_customurllist` **Disk quota** `fmgr_fmupdate_diskquota` **FortiClient services** `fmgr_fmupdate_fctservices` **FDS settings** `fmgr_fmupdate_fdssetting` **FDS settings push override** `fmgr_fmupdate_fdssetting_pushoverride` **FDS settings push override to client** `fmgr_fmupdate_fdssetting_pushoverridetoclient` **FDS settings push override to client announce IP** `fmgr_fmupdate_fdssetting_pushoverridetoclient_announceip` **FDS settings server override** `fmgr_fmupdate_fdssetting_serveroverride` **FDS settings server override server list** `fmgr_fmupdate_fdssetting_serveroverride_servlist` **FDS settings update schedule** `fmgr_fmupdate_fdssetting_updateschedule` **FortiGuard settings** `fmgr_fmupdate_fgdsetting` **FortiGuard settings server override** `fmgr_fmupdate_fgdsetting_serveroverride` **Firmware management settings** `fmgr_fmupdate_fwmsetting` **Firmware management settings upgrade timeout** `fmgr_fmupdate_fwmsetting_upgradetimeout` **Multilayer** `fmgr_fmupdate_multilayer` **Public network** `fmgr_fmupdate_publicnetwork` **Server access priorities** `fmgr_fmupdate_serveraccesspriorities` **Server access priorities private server** `fmgr_fmupdate_serveraccesspriorities_privateserver` **Server override status** `fmgr_fmupdate_serveroverridestatus` **Service** `fmgr_fmupdate_service` **Web spam FortiGuard settings** `fmgr_fmupdate_webspam_fgdsetting` **Web spam FortiGuard settings server override** `fmgr_fmupdate_webspam_fgdsetting_serveroverride` **Web spam FortiGuard settings server override server list** `fmgr_fmupdate_webspam_fgdsetting_serveroverride_servlist` **Web spam web proxy** `fmgr_fmupdate_webspam_webproxy` **FortiGuard** `fmgr_system_fortiguard` **Um image upgrade** `fmgr_um_image_upgrade` **Um image upgrade ext** `fmgr_um_image_upgrade_ext` **Ums setting** `fmgr_ums_setting`
Notes	• Most modules are generated from the FortiManager JSON-RPC API and configure objects inside an ADOM database; changes are installed to devices by policy package install.

Fortinet FortiGate (FortiOS) `fortinet.fortios`

Certified Fortinet · version 2.6.0 · updated 2026-08-15 · 729 modules → 29 use cases

Use Case: Manage firewall policies and inspection profiles

Description	Create and order IPv4, IPv6, proxy, multicast, local-in and DoS policies, bind security profile groups and protocol options, and configure SSL/SSH inspection.

Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**IPv4 ACLs** `fortios_firewall_acl` **IPv6 ACLs** `fortios_firewall_acl6` **Consolidated policies** `fortios_firewall_consolidated_policy` **Decrypted traffic mirrors** `fortios_firewall_decrypted_traffic_mirror` **DoS policies** `fortios_firewall_dos_policy` **IPv6 DoS policies** `fortios_firewall_dos_policy6` **Firewall global settings** `fortios_firewall_global` **Identity-based routes** `fortios_firewall_identity_based_route` **Interface policies** `fortios_firewall_interface_policy` **IPv6 interface policies** `fortios_firewall_interface_policy6` **Iprope (policy engine) settings** `fortios_firewall_iprope_list` **IPv6 EH filters** `fortios_firewall_ipv6_eh_filter` **Local-in policies** `fortios_firewall_local_in_policy` **IPv6 local-in policies** `fortios_firewall_local_in_policy6` **Multicast policies** `fortios_firewall_multicast_policy` **IPv6 multicast policies** `fortios_firewall_multicast_policy6` **On demand sniffers** `fortios_firewall_on_demand_sniffer` **IPv4 firewall policies** `fortios_firewall_policy` **NAT46 policies** `fortios_firewall_policy46` **IPv6 firewall policies** `fortios_firewall_policy6` **NAT64 policies** `fortios_firewall_policy64` **Profile groups** `fortios_firewall_profile_group` **Protocol options profiles** `fortios_firewall_profile_protocol_options` **Proxy policies** `fortios_firewall_proxy_policy` **NGFW security policies** `fortios_firewall_security_policy` **Sniffer policies** `fortios_firewall_sniffer` **SSH host keys** `fortios_firewall_ssh_host_key` **SSH local CAs** `fortios_firewall_ssh_local_ca` **SSH local keys** `fortios_firewall_ssh_local_key` **SSH inspection settings** `fortios_firewall_ssh_setting` **SSL servers** `fortios_firewall_ssl_server` **SSL inspection settings** `fortios_firewall_ssl_setting` **SSL/SSH inspection profiles** `fortios_firewall_ssl_ssh_profile` **TTL policies** `fortios_firewall_ttl_policy` **NGFW settings** `fortios_system_ngfw_settings` **Session helpers** `fortios_system_session_helper`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Define firewall addresses, services and schedules

Description	Maintain address and address group objects, custom services, schedules, wildcard FQDNs, Internet Service Database entries and geography objects that policies refer to.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**IPv4 addresses** `fortios_firewall_address` **IPv6 addresses** `fortios_firewall_address6` **IPv6 address templates** `fortios_firewall_address6_template` **IPv4 address groups** `fortios_firewall_addrgrp` **IPv6 address groups** `fortios_firewall_addrgrp6` **Cities** `fortios_firewall_city` **Countries** `fortios_firewall_country` **Custom tags** `fortios_firewall_custom_tag` **DNS translations** `fortios_firewall_dnstranslation` **Internet services** `fortios_firewall_internet_service`, `fortios_firewall_internet_service_list` **Internet service additions** `fortios_firewall_internet_service_addition` **Internet service appends** `fortios_firewall_internet_service_append` **Internet service botnets** `fortios_firewall_internet_service_botnet` **Custom Internet services** `fortios_firewall_internet_service_custom` **Internet service custom groups** `fortios_firewall_internet_service_custom_group` **Internet service definitions** `fortios_firewall_internet_service_definition` **Internet service extensions** `fortios_firewall_internet_service_extension` **FortiGuard Internet services** `fortios_firewall_internet_service_fortiguard` **Internet service groups** `fortios_firewall_internet_service_group` **Internet service IP block-list reasons** `fortios_firewall_internet_service_ipbl_reason` **Internet service IP block-list vendors** `fortios_firewall_internet_service_ipbl_vendor` **Internet service names** `fortios_firewall_internet_service_name` **Internet service owners** `fortios_firewall_internet_service_owner` **Internet service reputations** `fortios_firewall_internet_service_reputation` **Internet service SLDs** `fortios_firewall_internet_service_sld` **IP/MAC binding settings** `fortios_firewall_ipmacbinding_setting` **IP/MAC binding tables** `fortios_firewall_ipmacbinding_table` **Multicast addresses** `fortios_firewall_multicast_address` **IPv6 multicast addresses** `fortios_firewall_multicast_address6` **Dynamic network services** `fortios_firewall_network_service_dynamic` **Proxy addresses** `fortios_firewall_proxy_address` **IPv6 proxy addresses** `fortios_firewall_proxy_address6` **Proxy address groups** `fortios_firewall_proxy_addrgrp` **IPv6 proxy address groups** `fortios_firewall_proxy_addrgrp6` **Regions** `fortios_firewall_region` **Schedule groups** `fortios_firewall_schedule_group` **One-time schedules** `fortios_firewall_schedule_onetime` **Recurring schedules** `fortios_firewall_schedule_recurring` **Service categories** `fortios_firewall_service_category` **Custom services** `fortios_firewall_service_custom` **Service groups** `fortios_firewall_service_group` **Vendor MAC database** `fortios_firewall_vendor_mac` **Wildcard FQDN addresses** `fortios_firewall_wildcard_fqdn_custom` **Wildcard FQDN groups** `fortios_firewall_wildcard_fqdn_group` **GeoIP countries** `fortios_system_geoip_country` **GeoIP overrides** `fortios_system_geoip_override` **Object tags** `fortios_system_object_tagging`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure NAT, virtual IPs and IP pools

Description	Define virtual IPs and groups, IP pools, central SNAT maps, NAT64/NAT46 and load-balance monitors for publishing and translating traffic.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)

Key content	**Central SNAT maps** `fortios_firewall_central_snat_map` **IP translations** `fortios_firewall_ip_translation` **IP pools** `fortios_firewall_ippool` **IPv6 IP pools** `fortios_firewall_ippool6` **Load-balance health monitors** `fortios_firewall_ldb_monitor` **Virtual IPs** `fortios_firewall_vip` **NAT46 virtual IPs** `fortios_firewall_vip46` **IPv6 virtual IPs** `fortios_firewall_vip6` **NAT64 virtual IPs** `fortios_firewall_vip64` **Virtual IP groups** `fortios_firewall_vipgrp` **NAT46 virtual IP groups** `fortios_firewall_vipgrp46` **IPv6 virtual IP groups** `fortios_firewall_vipgrp6` **NAT64 virtual IP groups** `fortios_firewall_vipgrp64` **DNS64** `fortios_system_dns64` **NAT64** `fortios_system_nat64` **PCP servers** `fortios_system_pcp_server`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Shape traffic and apply QoS

Description	Configure traffic shapers, shaping policies and profiles, traffic classes and DSCP/ToS priority mappings.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Per-IP shapers** `fortios_firewall_shaper_per_ip_shaper` **Traffic shapers** `fortios_firewall_shaper_traffic_shaper` **Shaping policies** `fortios_firewall_shaping_policy` **Shaping profiles** `fortios_firewall_shaping_profile` **Traffic classes** `fortios_firewall_traffic_class` **DSCP-based priorities** `fortios_system_dscp_based_priority` **ISF queue profiles** `fortios_system_isf_queue_profile` **ToS-based priorities** `fortios_system_tos_based_priority`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Control web, DNS, video and file access

Description	Configure web filter, DNS filter, video filter, file filter, ICAP and explicit web or FTP proxy settings.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**CIFS domain controllers** `fortios_cifs_domain_controller` **CIFS profiles** `fortios_cifs_profile` **Credential store domain controllers** `fortios_credential_store_domain_controller` **DNS domain filters** `fortios_dnsfilter_domain_filter` **DNS filter profiles** `fortios_dnsfilter_profile` **File filter profiles** `fortios_file_filter_profile` **Explicit FTP proxy** `fortios_ftp_proxy_explicit` **ICAP profiles** `fortios_icap_profile` **ICAP servers** `fortios_icap_server` **ICAP server groups** `fortios_icap_server_group` **SSH filter profiles** `fortios_ssh_filter_profile` **Video filter keywords** `fortios_videofilter_keyword` **Video filter profiles** `fortios_videofilter_profile` **YouTube channel filters** `fortios_videofilter_youtube_channel_filter` **YouTube API keys** `fortios_videofilter_youtube_key` **Web proxy debug URLs** `fortios_web_proxy_debug_url` **Explicit web proxy** `fortios_web_proxy_explicit` **Proxy fast fallbacks** `fortios_web_proxy_fast_fallback` **Forward servers** `fortios_web_proxy_forward_server` **Forward server groups** `fortios_web_proxy_forward_server_group` **Web proxy global settings** `fortios_web_proxy_global` **Isolator servers** `fortios_web_proxy_isolator_server` **Web proxy profiles** `fortios_web_proxy_profile` **URL match lists** `fortios_web_proxy_url_match` **WISP servers** `fortios_web_proxy_wisp` **Web filter profiles (legacy)** `fortios_webfilter_status` **Content filters** `fortios_webfilter_content` **Content headers** `fortios_webfilter_content_header` **FortiGuard web filter settings** `fortios_webfilter_fortiguard` **Local web categories** `fortios_webfilter_ftgd_local_cat` **Local URL ratings** `fortios_webfilter_ftgd_local_rating` **Local risk ratings** `fortios_webfilter_ftgd_local_risk` **Risk levels** `fortios_webfilter_ftgd_risk_level` **IPS URL filter cache settings** `fortios_webfilter_ips_urlfilter_cache_setting` **IPS URL filter settings** `fortios_webfilter_ips_urlfilter_setting` **IPv6 IPS URL filter settings** `fortios_webfilter_ips_urlfilter_setting6` **Web filter overrides** `fortios_webfilter_override` **Web filter profiles** `fortios_webfilter_profile` **Search engines** `fortios_webfilter_search_engine` **URL filters** `fortios_webfilter_urlfilter`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Filter email and prevent data loss

Description	Configure email filter (anti-spam) profiles and lists, and data loss prevention sensors, dictionaries and fingerprints.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)

Key content	**DLP data types** `fortios_dlp_data_type` **DLP dictionaries** `fortios_dlp_dictionary` **Exact data match** `fortios_dlp_exact_data_match` **File patterns** `fortios_dlp_filepattern` **Fingerprint document sources** `fortios_dlp_fp_doc_source` **Fingerprint sensitivities** `fortios_dlp_fp_sensitivity` **DLP labels** `fortios_dlp_label` **DLP profiles** `fortios_dlp_profile` **Sensitivity labels** `fortios_dlp_sensitivity` **DLP sensors** `fortios_dlp_sensor` **DLP settings** `fortios_dlp_settings` **Block/allow entries** `fortios_emailfilter_block_allow_list` **Block/allow lists** `fortios_emailfilter_bwl` **Banned word lists** `fortios_emailfilter_bword` **DNSBL servers** `fortios_emailfilter_dnsbl` **FortiShield settings** `fortios_emailfilter_fortishield` **Trusted IPs** `fortios_emailfilter_iptrust` **MIME header lists** `fortios_emailfilter_mheader` **Email filter options** `fortios_emailfilter_options` **Email filter profiles** `fortios_emailfilter_profile` **Block/allow lists (legacy)** `fortios_spamfilter_bwl` **Banned word lists (legacy)** `fortios_spamfilter_bword` **DNSBL servers (legacy)** `fortios_spamfilter_dnsbl` **FortiShield settings (legacy)** `fortios_spamfilter_fortishield` **Trusted IPs (legacy)** `fortios_spamfilter_iptrust` **MIME header lists (legacy)** `fortios_spamfilter_mheader` **Spam filter options (legacy)** `fortios_spamfilter_options` **Spam filter profiles (legacy)** `fortios_spamfilter_profile`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Protect against malware, intrusions and web attacks

Description	Configure antivirus, IPS, virtual patching, web application firewall, sandbox and threat-intelligence integrations.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Antivirus hash exemptions** `fortios_antivirus_exempt_list` **Antivirus heuristics** `fortios_antivirus_heuristic` **Antivirus notifications** `fortios_antivirus_notification` **Antivirus profiles** `fortios_antivirus_profile` **Antivirus quarantine** `fortios_antivirus_quarantine` **Antivirus settings** `fortios_antivirus_settings` **Custom IPS signatures** `fortios_ips_custom` **IPS decoders** `fortios_ips_decoder` **IPS global settings** `fortios_ips_global` **IPS rules** `fortios_ips_rule` **IPS rule settings** `fortios_ips_rule_settings` **IPS sensors** `fortios_ips_sensor` **IPS settings** `fortios_ips_settings` **IPS view maps** `fortios_ips_view_map` **FortiAI** `fortios_system_fortiai` **FortiData** `fortios_system_fortidata` **FortiNDR** `fortios_system_fortindr` **FortiSandbox** `fortios_system_fortisandbox` **IPS engine settings** `fortios_system_ips` **IPS URL filter DNS** `fortios_system_ips_urlfilter_dns` **IPv6 IPS URL filter DNS** `fortios_system_ips_urlfilter_dns6` **Virtual patch profiles** `fortios_virtual_patch_profile` **WAF main classes** `fortios_waf_main_class` **WAF profiles** `fortios_waf_profile` **WAF signatures** `fortios_waf_signature` **WAF sub classes** `fortios_waf_sub_class`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Control applications, SaaS and AI services

Description	Configure application control, CASB profiles and SaaS applications, and LLM proxy profiles and servers.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Application control lists** `fortios_application_list` **Application classification settings** `fortios_application_classification_settings` **Custom application signatures** `fortios_application_custom` **Application groups** `fortios_application_group` **Application signatures** `fortios_application_name` **Application rule settings** `fortios_application_rule_settings` **Unsanctioned applications** `fortios_application_unsanctioned_apps` **CASB attribute matches** `fortios_casb_attribute_match` **CASB profiles** `fortios_casb_profile` **CASB SaaS applications** `fortios_casb_saas_application` **CASB user activities** `fortios_casb_user_activity` **LLM profiles** `fortios_llm_profile` **LLM proxy** `fortios_llm_proxy` **LLM servers** `fortios_llm_server`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Secure mobile-network and telecom protocols

Description	Configure GTP, PFCP, Diameter, SCTP and VoIP inspection, MMS settings and carrier-specific lists.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)

Key content	**MMS checksum lists** `fortios_antivirus_mms_checksum` **Diameter filter profiles** `fortios_diameter_filter_profile` **Carrier endpoint block/allow lists** `fortios_firewall_carrier_endpoint_bwl` **GTP profiles** `fortios_firewall_gtp` **MMS profiles** `fortios_firewall_mms_profile` **PFCP profiles** `fortios_firewall_pfcp` **APN** `fortios_gtp_apn` **APN shapers** `fortios_gtp_apn_shaper` **APN groups** `fortios_gtp_apngrp` **GTP IE allow lists** `fortios_gtp_ie_allow_list` **GTP IE white lists** `fortios_gtp_ie_white_list` **GTP v0/v1 message filters** `fortios_gtp_message_filter_v0v1` **GTP v2 message filters** `fortios_gtp_message_filter_v2` **RAT timeout profiles** `fortios_gtp_rat_timeout_profile` **GTP tunnel limits** `fortios_gtp_tunnel_limit` **PFCP message filters** `fortios_pfcp_message_filter` **SCTP filter profiles** `fortios_sctp_filter_profile` **Gi/Gk firewall settings** `fortios_system_gi_gk` **MM1 replacement messages** `fortios_system_replacemsg_mm1` **MM3 replacement messages** `fortios_system_replacemsg_mm3` **MM4 replacement messages** `fortios_system_replacemsg_mm4` **MM7 replacement messages** `fortios_system_replacemsg_mm7` **VoIP profiles** `fortios_voip_profile`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Authenticate users and manage identity sources

Description	Configure local users and groups, LDAP, RADIUS, TACACS+, SAML, FSSO, Kerberos and other directory sources, authentication rules, schemes and password policies, FortiToken and NAC policies.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Authentication rules** `fortios_authentication_rule` **Authentication schemes** `fortios_authentication_scheme` **Authentication settings** `fortios_authentication_setting` **FSSO polling** `fortios_system_fsso_polling` **FortiToken Mobile push** `fortios_system_ftm_push` **SAML SP** `fortios_system_saml` **VDOM RADIUS servers** `fortios_system_vdom_radius_server` **Active Directory groups** `fortios_user_adgrp` **User certificates** `fortios_user_certificate` **Devices** `fortios_user_device` **Device access** `fortios_user_device_access_list` **Device categories** `fortios_user_device_category` **Device groups** `fortios_user_device_group` **Domain controllers** `fortios_user_domain_controller` **Exchange servers** `fortios_user_exchange` **External identity providers** `fortios_user_external_identity_provider` **FortiTokens** `fortios_user_fortitoken` **FSSO agents** `fortios_user_fsso` **FSSO polling servers** `fortios_user_fsso_polling` **User groups** `fortios_user_group` **Kerberos keytabs** `fortios_user_krb_keytab` **LDAP servers** `fortios_user_ldap` **Local users** `fortios_user_local` **NAC policies** `fortios_user_nac_policy` **OIDC servers** `fortios_user_oidc` **User password policies** `fortios_user_password_policy` **PKI peers** `fortios_user_peer` **PKI peer groups** `fortios_user_peergrp` **POP3 servers** `fortios_user_pop3` **User quarantine** `fortios_user_quarantine` **RADIUS servers** `fortios_user_radius` **SAML servers** `fortios_user_saml` **SCIM clients** `fortios_user_scim` **Security exempt lists** `fortios_user_security_exempt_list` **User settings** `fortios_user_setting` **TACACS+ servers** `fortios_user_tacacsplus`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Enable zero-trust network access (ZTNA)

Description	Configure ZTNA access proxies, virtual hosts, connectors, web portals and traffic forwarding.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Access proxies** `fortios_firewall_access_proxy` **IPv6 access proxies** `fortios_firewall_access_proxy6` **Access proxy SSH client certificates** `fortios_firewall_access_proxy_ssh_client_cert` **Access proxy virtual hosts** `fortios_firewall_access_proxy_virtual_host` **Authentication portals** `fortios_firewall_auth_portal` **Connector edges** `fortios_ztna_connector_edge` **Destinations** `fortios_ztna_destination` **Reverse connectors** `fortios_ztna_reverse_connector` **Service connectors** `fortios_ztna_service_connector` **Traffic forward proxies** `fortios_ztna_traffic_forward_proxy` **Reverse services** `fortios_ztna_traffic_forward_proxy_reverse_service` **Web portals** `fortios_ztna_web_portal` **Web portal bookmarks** `fortios_ztna_web_portal_bookmark` **Web proxies** `fortios_ztna_web_proxy`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Manage VPN (IPsec, SSL-VPN, L2TP, PPTP)

Description	Configure IPsec phase 1 and 2, gateways, concentrators and aggregates, SSL-VPN portals, realms and settings, L2TP, PPTP and OCVPN.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)

Key content	**Fabric (overlay) VPN** `fortios_system_fabric_vpn` **IKE settings** `fortios_system_ike` **IPsec aggregates** `fortios_system_ipsec_aggregate` **Mobile tunnels** `fortios_system_mobile_tunnel` **SDN VPN** `fortios_system_sdn_vpn` **VNE tunnels** `fortios_system_vne_tunnel` **IKE gateways** `fortios_vpn_ike_gateway` **IPsec concentrators** `fortios_vpn_ipsec_concentrator` **IPsec FEC profiles** `fortios_vpn_ipsec_fec` **FortiClient IPsec** `fortios_vpn_ipsec_forticlient` **IPsec manual keys** `fortios_vpn_ipsec_manualkey` **IPsec manual key interfaces** `fortios_vpn_ipsec_manualkey_interface` **IPsec phase 1 (policy-based)** `fortios_vpn_ipsec_phase1` **IPsec phase 1 interfaces** `fortios_vpn_ipsec_phase1_interface` **IPsec phase 2 (policy-based)** `fortios_vpn_ipsec_phase2` **IPsec phase 2 interfaces** `fortios_vpn_ipsec_phase2_interface` **L2TP** `fortios_vpn_l2tp` **Overlay controller VPN** `fortios_vpn_ocvpn` **PPTP** `fortios_vpn_pptp` **SSL-VPN clients** `fortios_vpn_ssl_client` **SSL-VPN settings** `fortios_vpn_ssl_settings` **SSL-VPN host check software** `fortios_vpn_ssl_web_host_check_software` **SSL-VPN web portals** `fortios_vpn_ssl_web_portal` **SSL-VPN realms** `fortios_vpn_ssl_web_realm` **SSL-VPN user bookmarks** `fortios_vpn_ssl_web_user_bookmark` **SSL-VPN group bookmarks** `fortios_vpn_ssl_web_user_group_bookmark`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure dynamic routing (BGP, OSPF, RIP, IS-IS)

Description	Configure BGP, OSPF and OSPFv3, RIP and RIPng, IS-IS and BFD, plus key chains.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**BFD** `fortios_router_bfd` **BFD (IPv6)** `fortios_router_bfd6` **BGP** `fortios_router_bgp` **IS-IS** `fortios_router_isis` **Key chains** `fortios_router_key_chain` **OSPF** `fortios_router_ospf` **OSPFv3** `fortios_router_ospf6` **RIP** `fortios_router_rip` **RIPng** `fortios_router_ripng`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure static, policy and multicast routing

Description	Configure static and policy routes, route maps, prefix lists, access lists, AS paths and communities, and multicast routing.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Policy routes (legacy)** `fortios_firewall_proute` **Access lists** `fortios_router_access_list` **IPv6 access lists** `fortios_router_access_list6` **AS path lists** `fortios_router_aspath_list` **Authentication paths** `fortios_router_auth_path` **Community lists** `fortios_router_community_list` **Extended community lists** `fortios_router_extcommunity_list` **Multicast routing** `fortios_router_multicast` **IPv6 multicast routing** `fortios_router_multicast6` **IPv6 multicast flows** `fortios_router_multicast6_flow` **Multicast flows** `fortios_router_multicast_flow` **Policy routes** `fortios_router_policy` **IPv6 policy routes** `fortios_router_policy6` **Prefix lists** `fortios_router_prefix_list` **IPv6 prefix lists** `fortios_router_prefix_list6` **Route maps** `fortios_router_route_map` **Routing settings** `fortios_router_setting` **Static routes** `fortios_router_static` **IPv6 static routes** `fortios_router_static6`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure SD-WAN and link monitoring

Description	Configure SD-WAN zones, members, health checks and rules, link monitors and speed tests.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**FortiGuard health checks** `fortios_system_health_check_fortiguard` **Link monitors** `fortios_system_link_monitor` **Probe responses** `fortios_system_probe_response` **SD-WAN** `fortios_system_sdwan` **SASE (SOV) settings** `fortios_system_sov_sase` **Speed test schedules** `fortios_system_speed_test_schedule` **Speed test servers** `fortios_system_speed_test_server` **Speed test settings** `fortios_system_speed_test_setting` **SD-WAN (legacy virtual WAN link)** `fortios_system_virtual_wan_link`

Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure interfaces, zones and tunnels

Description	Configure physical and logical interfaces, zones, virtual switches and wires, VLANs, tunnels (GRE, IPIP, SIT, VXLAN, Geneve), cellular modems, STP, LLDP, ARP and neighbor settings.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Custom 3G modems** `fortios_system_3g_modem_custom` **ARP tables** `fortios_system_arp_table` **Dedicated management interface** `fortios_system_dedicated_mgmt` **EVPN** `fortios_system_evpn` **Geneve tunnels** `fortios_system_geneve` **GRE tunnels** `fortios_system_gre_tunnel` **Interfaces** `fortios_system_interface` **IPIP tunnels** `fortios_system_ipip_tunnel` **IPv6 neighbor caches** `fortios_system_ipv6_neighbor_cache` **IPv6 tunnels** `fortios_system_ipv6_tunnel` **LLDP network policies** `fortios_system_lldp_network_policy` **LTE modems** `fortios_system_lte_modem` **MAC address tables** `fortios_system_mac_address_table` **Modems** `fortios_system_modem` **ND proxy** `fortios_system_nd_proxy` **Physical switches** `fortios_system_physical_switch` **PPPoE interfaces** `fortios_system_pppoe_interface` **Proxy ARP entries** `fortios_system_proxy_arp` **SIT tunnels** `fortios_system_sit_tunnel` **Spanning tree** `fortios_system_stp` **Switch interfaces** `fortios_system_switch_interface` **Virtual switches** `fortios_system_virtual_switch` **Virtual wire pairs** `fortios_system_virtual_wire_pair` **VNE interfaces** `fortios_system_vne_interface` **VXLAN** `fortios_system_vxlan` **Zones** `fortios_system_zone`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Tune hardware acceleration and performance

Description	Configure NIC, NPU/NP6 and DPDK settings, CPU affinity, memory management and monitor hardware offload engines.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**DPDK CPUs** `fortios_dpdk_cpus` **DPDK global settings** `fortios_dpdk_global` **NIC settings** `fortios_hardware_nic` **NP6 DCE settings** `fortios_hardware_npu_np6_dce` **NP6 session settings** `fortios_hardware_npu_np6_session_stats` **NP6 SSE settings** `fortios_hardware_npu_np6_sse_stats` **NP6 IPsec engine monitoring** `fortios_monitoring_np6_ipsec_engine` **NPU HPE monitoring** `fortios_monitoring_npu_hpe` **Interrupt affinity** `fortios_system_affinity_interrupt` **Packet redistribution affinity** `fortios_system_affinity_packet_redistribution` **Memory manager** `fortios_system_mem_mgr` **NP6 settings** `fortios_system_np6` **NPU settings** `fortios_system_npu` **NPU post-processing** `fortios_system_npu_post` **NPU VLINK** `fortios_system_npu_vlink` **Top performance settings** `fortios_system_performance_top` **Resource limits** `fortios_system_resource_limits`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure high availability and virtual domains

Description	Configure HA clusters, standalone clusters and config sync, and create VDOMs with their links, properties and per-VDOM settings.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Cluster sync** `fortios_system_cluster_sync` **HA settings** `fortios_system_ha` **HA monitor** `fortios_system_ha_monitor` **Standalone cluster** `fortios_system_standalone_cluster` **VDOMs** `fortios_system_vdom` **VDOM DNS settings** `fortios_system_vdom_dns` **VDOM exceptions** `fortios_system_vdom_exception` **VDOM links** `fortios_system_vdom_link` **VDOM NetFlow settings** `fortios_system_vdom_netflow` **VDOM properties** `fortios_system_vdom_property` **VDOM sFlow settings** `fortios_system_vdom_sflow`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Administer the device: system settings, admins, firmware

Description	Configure global and system settings, administrators and access profiles, API users, SSO admins, password policies, FortiGuard and FortiManager connections, firmware upgrades, replacement messages and GUI customization.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)

Key content	**Admin access profiles** `fortios_system_accprofile` **Administrators** `fortios_system_admin` **Command aliases** `fortios_system_alias` **REST API users** `fortios_system_api_user` **Auto install** `fortios_system_auto_install` **Auto-update push updates** `fortios_system_autoupdate_push_update` **Auto-update schedules** `fortios_system_autoupdate_schedule` **Auto-update tunneling** `fortios_system_autoupdate_tunneling` **Central management** `fortios_system_central_management` **Console settings** `fortios_system_console` **Custom languages** `fortios_system_custom_language` **Device upgrades** `fortios_system_device_upgrade` **Device upgrade exemptions** `fortios_system_device_upgrade_exemptions` **Federated upgrades** `fortios_system_federated_upgrade` **FIPS-CC mode** `fortios_system_fips_cc` **FortiManager (legacy)** `fortios_system_fm` **FortiGuard services** `fortios_system_fortiguard` **FortiManager connection** `fortios_system_fortimanager` **Global settings** `fortios_system_global` **Management tunnel** `fortios_system_management_tunnel` **Admin password policy** `fortios_system_password_policy` **Guest admin password policy** `fortios_system_password_policy_guest_admin` **Admin replacement messages** `fortios_system_replacemsg_admin` **Alert email replacement messages** `fortios_system_replacemsg_alertmail` **Authentication replacement messages** `fortios_system_replacemsg_auth` **Automation replacement messages** `fortios_system_replacemsg_automation` **Device detection portal replacement messages** `fortios_system_replacemsg_device_detection_portal` **Endpoint control replacement messages** `fortios_system_replacemsg_ec` **FortiGuard web filter replacement messages** `fortios_system_replacemsg_fortiguard_wf` **FTP replacement messages** `fortios_system_replacemsg_ftp` **Replacement message groups** `fortios_system_replacemsg_group` **HTTP replacement messages** `fortios_system_replacemsg_http` **ICAP replacement messages** `fortios_system_replacemsg_icap` **Replacement message images** `fortios_system_replacemsg_image` **Mail replacement messages** `fortios_system_replacemsg_mail` **MMS replacement messages** `fortios_system_replacemsg_mms` **NAC quarantine replacement messages** `fortios_system_replacemsg_nac_quar` **NNTP replacement messages** `fortios_system_replacemsg_nntp` **Spam replacement messages** `fortios_system_replacemsg_spam` **SSL-VPN replacement messages** `fortios_system_replacemsg_sslvpn` **Traffic quota replacement messages** `fortios_system_replacemsg_traffic_quota` **UTM replacement messages** `fortios_system_replacemsg_utm` **Web proxy replacement messages** `fortios_system_replacemsg_webproxy` **Session TTL** `fortios_system_session_ttl` **VDOM settings** `fortios_system_settings` **SSO administrators** `fortios_system_sso_admin` **FortiCloud SSO administrators** `fortios_system_sso_forticloud_admin` **FortiGate Cloud SSO administrators** `fortios_system_sso_fortigate_cloud_admin` **Storage** `fortios_system_storage` **GUI themes** `fortios_system_theme`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Manage certificates and keys

Description	Manage local, CA, remote and HSM-based certificates, CRLs, OCSP servers, ACME, KMIP and SSH keys.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**CA certificate import** `fortios_certificate_ca` **CRL import** `fortios_certificate_crl` **HSM local certificate import** `fortios_certificate_hsm_local` **Local certificate and key import** `fortios_certificate_local` **Remote certificate import** `fortios_certificate_remote` **ACME** `fortios_system_acme` **SSH server settings** `fortios_system_ssh_config` **CA certificates** `fortios_vpn_certificate_ca` **CRLs** `fortios_vpn_certificate_crl` **HSM local certificates** `fortios_vpn_certificate_hsm_local` **Local certificates** `fortios_vpn_certificate_local` **OCSP servers** `fortios_vpn_certificate_ocsp_server` **Remote certificates** `fortios_vpn_certificate_remote` **Certificate settings** `fortios_vpn_certificate_setting` **KMIP servers** `fortios_vpn_kmip_server` **QKD (quantum key distribution)** `fortios_vpn_qkd`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure management services (DNS, DHCP, NTP, SNMP, alerts)

Description	Configure DNS, DHCP servers, NTP and PTP, SNMP, email and SMS servers, alarms, and alert email.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Alert email settings** `fortios_alertemail_setting` **Alarms** `fortios_system_alarm` **Dynamic DNS** `fortios_system_ddns` **DHCPv6 servers** `fortios_system_dhcp6_server` **DHCP servers** `fortios_system_dhcp_server` **DHCP templates** `fortios_system_dhcp_template` **DNS settings** `fortios_system_dns` **DNS databases** `fortios_system_dns_database` **DNS servers** `fortios_system_dns_server` **Email servers** `fortios_system_email_server` **IP address management** `fortios_system_ipam` **NTP** `fortios_system_ntp` **PTP** `fortios_system_ptp` **SMC NTP** `fortios_system_smc_ntp` **SMS servers** `fortios_system_sms_server` **SNMP communities** `fortios_system_snmp_community` **SNMP MIB views** `fortios_system_snmp_mib_view` **SNMP RMON statistics** `fortios_system_snmp_rmon_stat` **SNMP system info** `fortios_system_snmp_sysinfo` **SNMP users** `fortios_system_snmp_user`

Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Automate responses to events

Description	Configure automation triggers, conditions, actions and stitches, plus automation settings.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Automation settings** `fortios_automation_setting` **Auto scripts** `fortios_system_auto_script` **Automation actions** `fortios_system_automation_action` **Automation conditions** `fortios_system_automation_condition` **Automation destinations** `fortios_system_automation_destination` **Automation stitches** `fortios_system_automation_stitch` **Automation triggers** `fortios_system_automation_trigger`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Configure logging, reporting and flow export

Description	Send logs to disk, memory, syslog, FortiAnalyzer, FortiGuard, TACACS+ accounting and other targets, define log filters and settings, and configure reports, NetFlow and sFlow.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Custom log fields** `fortios_log_custom_field` **Custom log formats** `fortios_log_custom_format` **Disk log filter** `fortios_log_disk_filter` **Disk log settings** `fortios_log_disk_setting` **Event filters** `fortios_log_eventfilter` **FortiAnalyzer 2 filter** `fortios_log_fortianalyzer2_filter` **FortiAnalyzer 2 override filter** `fortios_log_fortianalyzer2_override_filter` **FortiAnalyzer 2 override settings** `fortios_log_fortianalyzer2_override_setting` **FortiAnalyzer 2 settings** `fortios_log_fortianalyzer2_setting` **FortiAnalyzer 3 filter** `fortios_log_fortianalyzer3_filter` **FortiAnalyzer 3 override filter** `fortios_log_fortianalyzer3_override_filter` **FortiAnalyzer 3 override settings** `fortios_log_fortianalyzer3_override_setting` **FortiAnalyzer 3 settings** `fortios_log_fortianalyzer3_setting` **FortiAnalyzer Cloud filter** `fortios_log_fortianalyzer_cloud_filter` **FortiAnalyzer Cloud override filter** `fortios_log_fortianalyzer_cloud_override_filter` **FortiAnalyzer Cloud override settings** `fortios_log_fortianalyzer_cloud_override_setting` **FortiAnalyzer Cloud settings** `fortios_log_fortianalyzer_cloud_setting` **FortiAnalyzer filter** `fortios_log_fortianalyzer_filter` **FortiAnalyzer override filter** `fortios_log_fortianalyzer_override_filter` **FortiAnalyzer override settings** `fortios_log_fortianalyzer_override_setting` **FortiAnalyzer settings** `fortios_log_fortianalyzer_setting` **FortiGuard filter** `fortios_log_fortiguard_filter` **FortiGuard override filter** `fortios_log_fortiguard_override_filter` **FortiGuard override settings** `fortios_log_fortiguard_override_setting` **FortiGuard settings** `fortios_log_fortiguard_setting` **Log GUI display** `fortios_log_gui_display` **Memory log filter** `fortios_log_memory_filter` **Memory log global settings** `fortios_log_memory_global_setting` **Memory log settings** `fortios_log_memory_setting` **Null device log filter** `fortios_log_null_device_filter` **Null device log settings** `fortios_log_null_device_setting` **Log settings** `fortios_log_setting` **Syslog 2 filter** `fortios_log_syslogd2_filter` **Syslog 2 override filter** `fortios_log_syslogd2_override_filter` **Syslog 2 override settings** `fortios_log_syslogd2_override_setting` **Syslog 2 settings** `fortios_log_syslogd2_setting` **Syslog 3 filter** `fortios_log_syslogd3_filter` **Syslog 3 override filter** `fortios_log_syslogd3_override_filter` **Syslog 3 override settings** `fortios_log_syslogd3_override_setting` **Syslog 3 settings** `fortios_log_syslogd3_setting` **Syslog 4 filter** `fortios_log_syslogd4_filter` **Syslog 4 override filter** `fortios_log_syslogd4_override_filter` **Syslog 4 override settings** `fortios_log_syslogd4_override_setting` **Syslog 4 settings** `fortios_log_syslogd4_setting` **Syslog filter** `fortios_log_syslogd_filter` **Syslog override filter** `fortios_log_syslogd_override_filter` **Syslog override settings** `fortios_log_syslogd_override_setting` **Syslog settings** `fortios_log_syslogd_setting` **TACACS+ accounting 2 filter** `fortios_log_tacacsplusaccounting2_filter` **TACACS+ accounting 2 settings** `fortios_log_tacacsplusaccounting2_setting` **TACACS+ accounting 3 filter** `fortios_log_tacacsplusaccounting3_filter` **TACACS+ accounting 3 settings** `fortios_log_tacacsplusaccounting3_setting` **TACACS+ accounting filter** `fortios_log_tacacsplusaccounting_filter` **TACACS+ accounting settings** `fortios_log_tacacsplusaccounting_setting` **Threat weights** `fortios_log_threat_weight` **WebTrends filter** `fortios_log_webtrends_filter` **WebTrends settings** `fortios_log_webtrends_setting` **Report charts** `fortios_report_chart` **Report datasets** `fortios_report_dataset` **Report layouts** `fortios_report_layout` **Report settings** `fortios_report_setting` **Report styles** `fortios_report_style` **Report themes** `fortios_report_theme` **NetFlow** `fortios_system_netflow` **Network visibility** `fortios_system_network_visibility` **sFlow** `fortios_system_sflow`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Integrate with Security Fabric, endpoints and cloud connectors

Description	Configure the Security Fabric, FortiClient EMS, SDN and cloud connectors, external threat feeds, telemetry controllers and Fortinet service integrations.

Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Endpoint clients** `fortios_endpoint_control_client` **FortiClient EMS servers** `fortios_endpoint_control_fctems` **FortiClient EMS overrides** `fortios_endpoint_control_fctems_override` **FortiClient EMS servers (legacy)** `fortios_endpoint_control_forticlient_ems` **FortiClient registration sync** `fortios_endpoint_control_forticlient_registration_sync` **Endpoint control profiles** `fortios_endpoint_control_profile` **Registered FortiClients** `fortios_endpoint_control_registered_forticlient` **Endpoint control settings** `fortios_endpoint_control_settings` **NSX-T service chains** `fortios_nsxt_service_chain` **NSX-T settings** `fortios_nsxt_setting` **Cloud services** `fortios_system_cloud_service` **Security Fabric** `fortios_system_csf` **External resources** `fortios_system_external_resource` **FortiMQ** `fortios_system_fortimq` **SDN connectors** `fortios_system_sdn_connector` **SDN proxies** `fortios_system_sdn_proxy` **Security rating controls** `fortios_system_security_rating_controls` **Security rating settings** `fortios_system_security_rating_settings` **Telemetry agents** `fortios_telemetry_controller_agent` **Telemetry agent profiles** `fortios_telemetry_controller_agent_profile` **Predefined telemetry applications** `fortios_telemetry_controller_application_predefine` **Telemetry global settings** `fortios_telemetry_controller_global` **Telemetry profiles** `fortios_telemetry_controller_profile`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Manage Wi-Fi networks and access points

Description	Manage the wireless controller: access points, SSIDs, profiles, WIDS, QoS and Hotspot 2.0 settings.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Wireless controller (legacy)** `fortios_wireless_controller_status` **Access control lists** `fortios_wireless_controller_access_control_list` **Wireless addresses** `fortios_wireless_controller_address` **Wireless address groups** `fortios_wireless_controller_addrgrp` **Access points** `fortios_wireless_controller_ap_status` **AP configuration profiles** `fortios_wireless_controller_apcfg_profile` **ARRP profiles** `fortios_wireless_controller_arrp_profile` **BLE profiles** `fortios_wireless_controller_ble_profile` **Bonjour profiles** `fortios_wireless_controller_bonjour_profile` **Wireless clients** `fortios_wireless_controller_client_info` **Global wireless settings** `fortios_wireless_controller_global` **Hotspot 2.0 ANQP 3GPP cellular** `fortios_wireless_controller_hotspot20_anqp_3gpp_cellular` **Hotspot 2.0 ANQP IP address types** `fortios_wireless_controller_hotspot20_anqp_ip_address_type` **Hotspot 2.0 ANQP NAI realms** `fortios_wireless_controller_hotspot20_anqp_nai_realm` **Hotspot 2.0 ANQP network auth types** `fortios_wireless_controller_hotspot20_anqp_network_auth_type` **Hotspot 2.0 ANQP roaming consortiums** `fortios_wireless_controller_hotspot20_anqp_roaming_consortium` **Hotspot 2.0 ANQP venue names** `fortios_wireless_controller_hotspot20_anqp_venue_name` **Hotspot 2.0 ANQP venue URLs** `fortios_wireless_controller_hotspot20_anqp_venue_url` **Hotspot 2.0 H2QP advice of charge** `fortios_wireless_controller_hotspot20_h2qp_advice_of_charge` **Hotspot 2.0 H2QP connection capabilities** `fortios_wireless_controller_hotspot20_h2qp_conn_capability` **Hotspot 2.0 H2QP operator names** `fortios_wireless_controller_hotspot20_h2qp_operator_name` **Hotspot 2.0 H2QP OSU providers** `fortios_wireless_controller_hotspot20_h2qp_osu_provider` **Hotspot 2.0 H2QP OSU provider NAIs** `fortios_wireless_controller_hotspot20_h2qp_osu_provider_nai` **Hotspot 2.0 H2QP terms and conditions** `fortios_wireless_controller_hotspot20_h2qp_terms_and_conditions` **Hotspot 2.0 H2QP WAN metrics** `fortios_wireless_controller_hotspot20_h2qp_wan_metric` **Hotspot 2.0 profiles** `fortios_wireless_controller_hotspot20_hs_profile` **Hotspot 2.0 icons** `fortios_wireless_controller_hotspot20_icon` **Hotspot 2.0 QoS maps** `fortios_wireless_controller_hotspot20_qos_map` **Inter-controller settings** `fortios_wireless_controller_inter_controller` **Wireless logging** `fortios_wireless_controller_log` **Lightweight profiles** `fortios_wireless_controller_lw_profile` **MPSK profiles** `fortios_wireless_controller_mpsk_profile` **NAC profiles** `fortios_wireless_controller_nac_profile` **QoS profiles** `fortios_wireless_controller_qos_profile` **Wireless regions** `fortios_wireless_controller_region` **RF analysis** `fortios_wireless_controller_rf_analysis` **Wireless settings** `fortios_wireless_controller_setting` **Wireless SNMP** `fortios_wireless_controller_snmp` **Spectral analysis** `fortios_wireless_controller_spectral_info` **SSID policies** `fortios_wireless_controller_ssid_policy` **Syslog profiles** `fortios_wireless_controller_syslog_profile` **Wireless timers** `fortios_wireless_controller_timers` **UTM profiles** `fortios_wireless_controller_utm_profile` **Virtual APs (SSIDs)** `fortios_wireless_controller_vap`, `fortios_wireless_controller_vap_status` **Virtual AP groups** `fortios_wireless_controller_vap_group` **WAG profiles** `fortios_wireless_controller_wag_profile` **WIDS profiles** `fortios_wireless_controller_wids_profile` **FortiAP units** `fortios_wireless_controller_wtp`, `fortios_wireless_controller_wtp_status` **FortiAP groups** `fortios_wireless_controller_wtp_group` **FortiAP profiles** `fortios_wireless_controller_wtp_profile`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Manage FortiSwitch units, ports and security

Description	Manage FortiSwitch units through FortiLink: switch profiles, VLANs, port policies, 802.1X, NAC, QoS, STP, PoE and monitoring.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)

Key content	**802.1X settings** `fortios_switch_controller_802_1x_settings` **FortiSwitch ACL groups** `fortios_switch_controller_acl_group` **FortiSwitch ingress ACLs** `fortios_switch_controller_acl_ingress` **Auto-config custom settings** `fortios_switch_controller_auto_config_custom` **Auto-config defaults** `fortios_switch_controller_auto_config_default` **Auto config policies** `fortios_switch_controller_auto_config_policy` **Custom commands** `fortios_switch_controller_custom_command` **Dynamic port policies** `fortios_switch_controller_dynamic_port_policy` **Flow tracking** `fortios_switch_controller_flow_tracking` **Fortilink settings** `fortios_switch_controller_fortilink_settings` **FortiSwitch global settings** `fortios_switch_controller_global` **IGMP snooping** `fortios_switch_controller_igmp_snooping` **IGMP snooping static groups** `fortios_switch_controller_igmp_snooping_static_group` **Initial config templates** `fortios_switch_controller_initial_config_template` **Initial config VLANs** `fortios_switch_controller_initial_config_vlans` **IP source guard logs** `fortios_switch_controller_ip_source_guard_log` **FortiSwitch LLDP profiles** `fortios_switch_controller_lldp_profile` **FortiSwitch LLDP settings** `fortios_switch_controller_lldp_settings` **FortiSwitch locations** `fortios_switch_controller_location` **MAC policies** `fortios_switch_controller_mac_policy` **MAC sync settings** `fortios_switch_controller_mac_sync_settings` **Managed FortiSwitch units** `fortios_switch_controller_managed_switch` **NAC devices** `fortios_switch_controller_nac_device` **NAC settings** `fortios_switch_controller_nac_settings` **Network monitor settings** `fortios_switch_controller_network_monitor_settings` **FortiSwitch PoE** `fortios_switch_controller_poe` **Port policies** `fortios_switch_controller_port_policy` **PTP interface policies** `fortios_switch_controller_ptp_interface_policy` **PTP policies** `fortios_switch_controller_ptp_policy` **PTP profiles** `fortios_switch_controller_ptp_profile` **PTP settings** `fortios_switch_controller_ptp_settings` **QoS 802.1p maps** `fortios_switch_controller_qos_dot1p_map` **QoS IP DSCP maps** `fortios_switch_controller_qos_ip_dscp_map` **QoS policies** `fortios_switch_controller_qos_qos_policy` **QoS queue policies** `fortios_switch_controller_qos_queue_policy` **FortiSwitch quarantine** `fortios_switch_controller_quarantine` **FortiSwitch remote logging** `fortios_switch_controller_remote_log` **802.1X security policies** `fortios_switch_controller_security_policy_802_1x` **Security policy admin settings** `fortios_switch_controller_security_policy_admin` **Captive portal security policies** `fortios_switch_controller_security_policy_captive_portal` **Local access security policies** `fortios_switch_controller_security_policy_local_access` **FortiSwitch sFlow** `fortios_switch_controller_sflow` **FortiSwitch SNMP communities** `fortios_switch_controller_snmp_community` **FortiSwitch SNMP system info** `fortios_switch_controller_snmp_sysinfo` **FortiSwitch SNMP trap thresholds** `fortios_switch_controller_snmp_trap_threshold` **FortiSwitch SNMP users** `fortios_switch_controller_snmp_user` **Storm control** `fortios_switch_controller_storm_control` **Storm control policies** `fortios_switch_controller_storm_control_policy` **FortiSwitch STP instances** `fortios_switch_controller_stp_instance` **FortiSwitch STP settings** `fortios_switch_controller_stp_settings` **Switch groups** `fortios_switch_controller_switch_group` **Switch interface tags** `fortios_switch_controller_switch_interface_tag` **FortiSwitch logging** `fortios_switch_controller_switch_log` **Switch profiles** `fortios_switch_controller_switch_profile` **FortiSwitch system settings** `fortios_switch_controller_system` **Traffic policies** `fortios_switch_controller_traffic_policy` **Traffic sniffers** `fortios_switch_controller_traffic_sniffer` **Virtual port pools** `fortios_switch_controller_virtual_port_pool` **FortiSwitch VLANs** `fortios_switch_controller_vlan` **VLAN policies** `fortios_switch_controller_vlan_policy`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Manage FortiExtender and extension devices

Description	Configure FortiExtender and extension controller devices, data plans, profiles and LTE carriers.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Extender data plans** `fortios_extender_controller_dataplan` **FortiExtender units** `fortios_extender_controller_extender` **FortiExtender profiles** `fortios_extender_controller_extender_profile` **FortiExtender units (legacy)** `fortios_extender_extender_info` **LTE carriers** `fortios_extender_lte_carrier_list` **LTE carriers by MCC/MNC** `fortios_extender_lte_carrier_by_mcc_mnc` **Extender modems** `fortios_extender_modem_status` **Extender system settings** `fortios_extender_sys_info` **Extension data plans** `fortios_extension_controller_dataplan` **Extension FortiExtender units** `fortios_extension_controller_extender` **Extension FortiExtender profiles** `fortios_extension_controller_extender_profile` **Extender virtual APs** `fortios_extension_controller_extender_vap` **Extension FortiGate units** `fortios_extension_controller_fortigate` **Extension FortiGate profiles** `fortios_extension_controller_fortigate_profile`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Optimize WAN traffic and caching

Description	Configure WAN optimization profiles, peers, authentication groups, web cache and WCCP.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)

Key content	**WCCP** `fortios_system_wccp` **Authentication groups** `fortios_wanopt_auth_group` **Cache services** `fortios_wanopt_cache_service` **CDN rules** `fortios_wanopt_content_delivery_network_rule` **WAN optimization peers** `fortios_wanopt_peer` **WAN optimization profiles** `fortios_wanopt_profile` **Remote storage** `fortios_wanopt_remote_storage` **WAN optimization settings** `fortios_wanopt_settings` **Web cache** `fortios_wanopt_webcache`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Use Case: Gather facts, export configuration and call any API

Description	Retrieve configuration facts and monitor data, export current configuration as playbooks, and call any FortiOS API generically.
Collection	`fortinet.fortios` (Certified, Fortinet, v2.6.0, updated 2026-08-15)
Key content	**Configuration facts** `fortios_configuration_fact` **Export configuration to playbook** `fortios_export_config_playbook` **Generic JSON API** `fortios_json_generic` **Log facts** `fortios_log_fact` **Monitor data** `fortios_monitor` **Monitor facts** `fortios_monitor_fact`
Notes	• Most modules configure one FortiOS table or object; running a job against a FortiGate with a different FortiOS version may reject options that version does not support. • Per-VDOM objects accept a vdom parameter, so one use case can cover several VDOMs on the same device.

Fortinet FortiSASE `fortinet.fortisase`

Certified Fortinet · version 1.1.0 · updated 2025-10-10 · 72 modules → 9 use cases

Use Case: Manage security policies

Description	Define outbound, internal, reverse and endpoint-to-endpoint policies and group security profiles for traffic enforcement.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)
Key content	**Outbound policies** `security_outbound_policies` **Internal policies** `security_internal_policies` **Internal reverse policies** `security_internal_reverse_policies` **Endpoint-to-endpoint policies** `security_endpoint_to_endpoint_policies` **Profile groups** `security_profile_group` **Profile group clones** `security_profile_group_clone`

Use Case: Configure threat protection profiles

Description	Configure antivirus, IPS, application control, web, DNS, file and video filtering, and SSL inspection profiles.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)
Key content	**Antivirus profiles** `security_antivirus_profile` **IPS profiles** `security_ips_profile` **IPS custom signatures** `security_ips_custom_signatures` **Application control profiles** `security_application_control_profile` **Custom application signatures** `security_app_custom_signatures` **Web filter profiles** `security_web_filter_profile` **DNS filter profiles** `security_dns_filter_profile` **File filter profiles** `security_file_filter_profile` **Video filter profiles** `security_video_filter_profile` **YouTube API keys** `security_video_filter_youtube_key` **SSL inspection profiles** `security_ssl_ssh_profile` **FortiGuard local categories** `security_fortiguard_local_categories`

Use Case: Prevent data loss and block threats with feeds

Description	Configure DLP dictionaries, patterns, fingerprints, sensors and profiles, and domain, IP and URL threat feeds.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)

Key content	**DLP dictionaries** `security_dlp_dictionaries` **DLP exact data matches** `security_dlp_exact_data_matches` **DLP file patterns** `security_dlp_file_patterns` **DLP fingerprint databases** `security_dlp_fingerprint_databases` **DLP sensors** `security_dlp_sensors` **DLP profiles** `security_dlp_profile` **Domain threat feeds** `security_domain_threat_feeds` **IP threat feeds** `security_ip_threat_feeds` **URL threat feeds** `security_url_threat_feeds`

Use Case: Define services, schedules and certificates

Description	Maintain reusable policy objects for services, schedules, certificates and PKI users.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)
Key content	**Services** `security_services` **Service groups** `security_service_groups` **One-time schedules** `security_onetime_schedules` **Recurring schedules** `security_recurring_schedules` **Schedule groups** `security_schedule_groups` **Local certificates** `security_cert_local_certs` **Remote CA certificates** `security_cert_remote_ca_certs` **PKI users** `security_pki_users`

Use Case: Define network objects, DNS and wireless

Description	Define hosts, host groups, internet services, DNS rules and FortiAP SSIDs used by policy.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)
Key content	**Hosts** `network_hosts` **Host groups** `network_host_groups` **Internet services** `network_internet_services` **DNS rules** `network_dns_rules` **Implicit DNS rules** `network_implicit_dns_rules` **FortiAP SSIDs** `infra_ssids`

Use Case: Manage users and authentication

Description	Manage users and user groups, and integrate LDAP, RADIUS, FSSO and SAML single sign-on, and end user session sign-out.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)
Key content	**Users** `auth_users` **User groups** `auth_user_groups` **LDAP servers** `auth_ldap_servers` **RADIUS servers** `auth_radius_servers` **FSSO agents** `auth_fsso_agents` **SWG SAML SSO** `auth_swg_saml_server` **VPN SAML SSO** `auth_vpn_saml_server` **SWG session sign-out** `user_swg_sessions_deauth` **VPN session sign-out** `user_vpn_sessions_deauth`

Use Case: Manage endpoints and zero trust access

Description	Configure FortiClient endpoint profiles, policies and invitation codes, ZTNA tags, rules and profiles, and enable, disable or disconnect endpoints.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)

Key content	**Connection profiles** `endpoint_connection_profiles` **FSSO profiles** `endpoint_fsso_profiles` **Group and AD user profiles** `endpoint_group_ad_user_profiles` **Group invitation codes** `endpoint_group_invitation_codes` **Endpoint policies** `endpoint_policies` **Endpoint policy clones** `endpoint_policies_clone` **Protection profiles** `endpoint_protection_profiles` **Sandbox profiles** `endpoint_sandbox_profiles` **Settings profiles** `endpoint_setting_profiles` **ZTNA profiles** `endpoint_ztna_profiles` **ZTNA rules** `endpoint_ztna_rules` **ZTNA tags** `endpoint_ztna_tags` **Access proxy authorize** `endpoints_access_proxy_authorize` **Access proxy disconnect** `endpoints_access_proxy_disconnect` **Enable endpoint management** `endpoints_enable_management` **Disable endpoint management** `endpoints_disable_management`

Use Case: Provide secure private access and monitor digital experience

Description	Configure secure private access networks and service connections, and digital experience monitoring for SaaS and SPA applications.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)
Key content	**Private access network configuration** `private_access_network_configuration` **Private access service connections** `private_access_service_connections` **Custom SaaS applications** `dem_custom_saas_apps` **SPA applications** `dem_spa_applications`

Use Case: Gather facts and call the API directly

Description	Gather FortiSASE facts and send generic API requests.
Collection	`fortinet.fortisase` (Certified, Fortinet, v1.1.0, updated 2025-10-10)
Key content	**Facts** `fortisase_facts` **Generic API requests** `fortisase_generic`

Fortinet FortiSwitch `fortinet.fortiswitch`

Certified Fortinet · version 1.4.0 · updated 2026-10-09 · 200 modules → 13 use cases

Use Case: Back up, restore and upgrade switch configuration and firmware

Description	Back up default, full and standalone configurations, restore configurations and images, stage firmware, upload files and run delayed CLI commands.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Configuration backup** `fortiswitch_execute_backup_config` **Default configuration backup** `fortiswitch_execute_backup_default_config` **Full configuration backup** `fortiswitch_execute_backup_full_config` **Standalone configuration backup** `fortiswitch_execute_backup_standalone_config` **Configuration restore** `fortiswitch_execute_restore_config` **Image restore** `fortiswitch_execute_restore_image` **Firmware image staging** `fortiswitch_execute_stage_image` **File upload** `fortiswitch_execute_upload_file` **Delayed CLI commands (create)** `fortiswitch_execute_create_delayed_cli_cmds` **Delayed CLI commands (query)** `fortiswitch_execute_query_delayed_cli_cmds` **Delayed CLI commands (cancel)** `fortiswitch_execute_cancel_delayed_cli_cmds`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Gather facts and configure through the generic API

Description	Retrieve configuration and monitor facts, configure any switch object through the generic JSON module, and convert the current configuration into playbooks.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Configuration facts** `fortiswitch_configuration_fact` **Monitor facts** `fortiswitch_monitor_fact` **Generic JSON configuration** `fortiswitch_json_generic` **Export configuration as playbooks** `fortiswitch_export_config_playbook`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Configure ports, VLANs and link aggregation

Description	Configure physical ports, trunks, VLANs, VLAN pruning, forwarding domains, static MAC entries and virtual wires.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Physical ports** `fortiswitch_switch_physical_port` **PHY modes** `fortiswitch_switch_phy_mode` **Ports and trunks** `fortiswitch_switch_interface` **Link aggregation** `fortiswitch_switch_trunk` **VLANs** `fortiswitch_switch_vlan` **VLAN pruning** `fortiswitch_switch_vlan_pruning` **VLAN ether-types** `fortiswitch_switch_vlan_tpid` **Forwarding domains** `fortiswitch_switch_domain` **Virtual wires** `fortiswitch_switch_virtual_wire` **Auto ISL port groups** `fortiswitch_switch_auto_isl_port_group` **Auto networks** `fortiswitch_switch_auto_network` **Static MAC entries** `fortiswitch_switch_static_mac` **MAC address table** `fortiswitch_system_mac_address_table` **Port pairs** `fortiswitch_system_port_pair`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Configure Layer 2 protocols and multicast

Description	Configure spanning tree, LLDP, Media Redundancy Protocol, IGMP and MLD snooping, and storm control.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**STP instances** `fortiswitch_switch_stp_instance` **STP settings** `fortiswitch_switch_stp_settings` **LLDP profiles** `fortiswitch_switch_lldp_profile` **LLDP settings** `fortiswitch_switch_lldp_settings` **MRP profiles** `fortiswitch_switch_mrp_profile` **MRP settings** `fortiswitch_switch_mrp_settings` **IGMP snooping** `fortiswitch_switch_igmp_snooping_globals` **MLD snooping** `fortiswitch_switch_mld_snooping_globals` **Storm control** `fortiswitch_switch_storm_control`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Control access and secure switch ports

Description	Configure access control lists, 802.1X dynamic policies, MACsec, IP-MAC binding, IP source guard, RA guard and device quarantine.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Ingress ACL policies** `fortiswitch_switch_acl_ingress` **Egress ACL policies** `fortiswitch_switch_acl_egress` **Prelookup ACL policies** `fortiswitch_switch_acl_prelookup` **802.1X dynamic ACL policies** `fortiswitch_switch_acl_802_1x` **ACL policers** `fortiswitch_switch_acl_policer` **Custom ACL services** `fortiswitch_switch_acl_service_custom` **ACL global settings** `fortiswitch_switch_acl_settings` **MACsec profiles** `fortiswitch_switch_macsec_profile` **IP-MAC binding** `fortiswitch_switch_ip_mac_binding` **IP source guard** `fortiswitch_switch_ip_source_guard` **IPv6 RA guard policies** `fortiswitch_switch_raguard_policy` **Quarantined devices** `fortiswitch_switch_quarantine` **Security feature controls** `fortiswitch_switch_security_feature`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Configure QoS and time synchronisation

Description	Configure QoS mappings and policies, ToS-based priority, PTP policies and profiles, and NTP.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)

Key content	**802.1p QoS maps** `fortiswitch_switch_qos_dot1p_map` **DSCP QoS maps** `fortiswitch_switch_qos_ip_dscp_map` **QoS egress policies** `fortiswitch_switch_qos_qos_policy` **ToS-based priority** `fortiswitch_system_tos_based_priority` **PTP policies** `fortiswitch_switch_ptp_policy` **PTP settings** `fortiswitch_switch_ptp_settings` **PTP interface policies** `fortiswitch_system_ptp_interface_policy` **PTP profiles** `fortiswitch_system_ptp_profile` **NTP** `fortiswitch_system_ntp`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Configure routing

Description	Configure static routes, BGP, OSPF, IS-IS, RIP, multicast, VRFs, policy routing and the route filters they use.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**IPv4 static routes** `fortiswitch_router_static` **IPv6 static routes** `fortiswitch_router_static6` **BGP** `fortiswitch_router_bgp` **OSPF** `fortiswitch_router_ospf` **OSPFv3** `fortiswitch_router_ospf6` **IS-IS** `fortiswitch_router_isis` **RIP** `fortiswitch_router_rip` **RIPng** `fortiswitch_router_ripng` **Multicast routing** `fortiswitch_router_multicast` **Multicast flows** `fortiswitch_router_multicast_flow` **VRFs** `fortiswitch_router_vrf` **Policy routing** `fortiswitch_router_policy` **Auth-based routing** `fortiswitch_router_auth_path` **Gateway detection** `fortiswitch_router_gwdetect` **RIB settings** `fortiswitch_router_setting` **Key chains** `fortiswitch_router_key_chain` **Route maps** `fortiswitch_router_route_map` **Access lists** `fortiswitch_router_access_list` **IPv6 access lists** `fortiswitch_router_access_list6` **AS path lists** `fortiswitch_router_aspath_list` **Community lists** `fortiswitch_router_community_list` **Prefix lists** `fortiswitch_router_prefix_list` **IPv6 prefix lists** `fortiswitch_router_prefix_list6`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Configure management interfaces, IP services and virtual domains

Description	Configure layer 3 interfaces, DHCP and DNS servers, ARP and neighbor tables, zones, VDOMs and VXLAN.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Interfaces** `fortiswitch_system_interface` **DHCP servers** `fortiswitch_system_dhcp_server` **DHCP lease clearing** `fortiswitch_execute_clear_dhcp_lease` **DNS settings** `fortiswitch_system_dns` **DNS databases** `fortiswitch_system_dns_database` **DNS servers** `fortiswitch_system_dns_server` **ARP table** `fortiswitch_system_arp_table` **Proxy ARP** `fortiswitch_system_proxy_arp` **IPv6 neighbor cache** `fortiswitch_system_ipv6_neighbor_cache` **Zones** `fortiswitch_system_zone` **Virtual domains** `fortiswitch_system_vdom` **VDOM DNS** `fortiswitch_system_vdom_dns` **VDOM properties** `fortiswitch_system_vdom_property` **VXLAN devices** `fortiswitch_system_vxlan`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Manage administrators, authentication and certificates

Description	Configure administrator accounts and access profiles, password policy, local, LDAP, RADIUS and TACACS+ users, and CA, local and remote certificates.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Administrators** `fortiswitch_system_admin` **Administrator access profiles** `fortiswitch_system_accprofile` **Password policy** `fortiswitch_system_password_policy` **Local users** `fortiswitch_user_local` **User groups** `fortiswitch_user_group` **LDAP servers** `fortiswitch_user_ldap` **RADIUS servers** `fortiswitch_user_radius` **TACACS+ servers** `fortiswitch_user_tacacsplus` **Peer users** `fortiswitch_user_peer` **Peer user groups** `fortiswitch_user_peergrp` **User authentication settings** `fortiswitch_user_setting` **CA certificates** `fortiswitch_system_certificate_ca` **Local certificates** `fortiswitch_system_certificate_local` **Remote certificates** `fortiswitch_system_certificate_remote` **Certificate revocation lists** `fortiswitch_system_certificate_crl` **OCSP servers** `fortiswitch_system_certificate_ocsp` **CA certificate import** `fortiswitch_execute_import_ca_certificate` **Local certificate import** `fortiswitch_execute_import_local_certificate` **Data signing** `fortiswitch_execute_sign_data` **Secure mode** `fortiswitch_system_security`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Configure logging and alerting

Description	Send logs to disk, memory, syslog servers and FortiAnalyzer, filter log events, and configure alarms and alert e-mail.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Disk logging** `fortiswitch_log_disk_setting` **Disk log filters** `fortiswitch_log_disk_filter` **Memory logging** `fortiswitch_log_memory_setting` **Memory log global settings** `fortiswitch_log_memory_global_setting` **Memory log filters** `fortiswitch_log_memory_filter` **Syslog server 1** `fortiswitch_log_syslogd_setting` **Syslog server 1 filters** `fortiswitch_log_syslogd_filter` **Syslog override settings** `fortiswitch_log_syslogd_override_setting` **Syslog override filters** `fortiswitch_log_syslogd_override_filter` **Syslog server 2** `fortiswitch_log_syslogd2_setting` **Syslog server 2 filters** `fortiswitch_log_syslogd2_filter` **Syslog server 3** `fortiswitch_log_syslogd3_setting` **Syslog server 3 filters** `fortiswitch_log_syslogd3_filter` **FortiAnalyzer logging 1** `fortiswitch_log_fortianalyzer_setting` **FortiAnalyzer log filters 1** `fortiswitch_log_fortianalyzer_filter` **FortiAnalyzer override settings** `fortiswitch_log_fortianalyzer_override_setting` **FortiAnalyzer override filters** `fortiswitch_log_fortianalyzer_override_filter` **FortiAnalyzer logging 2** `fortiswitch_log_fortianalyzer2_setting` **FortiAnalyzer log filters 2** `fortiswitch_log_fortianalyzer2_filter` **FortiAnalyzer logging 3** `fortiswitch_log_fortianalyzer3_setting` **FortiAnalyzer log filters 3** `fortiswitch_log_fortianalyzer3_filter` **FortiGuard Analysis Service logging** `fortiswitch_log_fortiguard_setting` **Remote logging** `fortiswitch_log_remote_setting` **Log event filter** `fortiswitch_log_eventfilter` **Custom log fields** `fortiswitch_log_custom_field` **GUI log display** `fortiswitch_log_gui` **Alert e-mail settings** `fortiswitch_alertemail_setting` **Alert e-mail server** `fortiswitch_system_alertemail` **E-mail server** `fortiswitch_system_email_server` **Alarms** `fortiswitch_system_alarm`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Monitor and troubleshoot the switch

Description	Capture packets, mirror ports, export sFlow and flow data, monitor links and networks, configure SNMP and set debug and bug-report options.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Packet sniffer profiles** `fortiswitch_system_sniffer_profile` **Sniffer capture start** `fortiswitch_execute_start_sniffer_profile_capture` **Sniffer capture pause** `fortiswitch_execute_pause_sniffer_profile_capture` **Sniffer capture stop** `fortiswitch_execute_stop_sniffer_profile_capture` **Sniffer capture download** `fortiswitch_execute_download_sniffer_profile` **Sniffer capture deletion** `fortiswitch_execute_delete_sniffer_profile_capture` **Port mirroring** `fortiswitch_switch_mirror` **sFlow** `fortiswitch_system_sflow` **Flow export** `fortiswitch_system_flow_export` **Link health monitors** `fortiswitch_system_link_monitor` **Network monitor settings** `fortiswitch_switch_network_monitor_settings` **Directed network monitor entries** `fortiswitch_switch_network_monitor_directed` **SNMP communities** `fortiswitch_system_snmp_community` **SNMP system information** `fortiswitch_system_snmp_sysinfo` **SNMP users** `fortiswitch_system_snmp_user` **Startup debug values** `fortiswitch_system_debug` **Bug reports** `fortiswitch_system_bug_report`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Manage central management, cloud and FortiGuard updates

Description	Connect the switch to FortiManager, FortiSwitch cloud and FortiLAN cloud, set up management tunnels and FortiAnalyzer, and configure FortiGuard and automatic updates.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)
Key content	**Central management** `fortiswitch_system_central_management` **FortiManager** `fortiswitch_system_fortimanager` **FortiManager (fm)** `fortiswitch_system_fm` **FortiSwitch cloud** `fortiswitch_system_fsw_cloud` **FortiLAN cloud** `fortiswitch_system_flan_cloud` **Management tunnel** `fortiswitch_system_management_tunnel` **Switch controller global settings** `fortiswitch_switch_controller_global` **FortiAnalyzer 1** `fortiswitch_system_fortianalyzer` **FortiAnalyzer 2** `fortiswitch_system_fortianalyzer2` **FortiAnalyzer 3** `fortiswitch_system_fortianalyzer3` **FortiGuard services** `fortiswitch_system_fortiguard` **Update schedule** `fortiswitch_system_autoupdate_schedule` **Push updates** `fortiswitch_system_autoupdate_push_update` **FDS server override** `fortiswitch_system_autoupdate_override` **FDN client override** `fortiswitch_system_autoupdate_clientoverride` **Web proxy tunneling** `fortiswitch_system_autoupdate_tunneling`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

Use Case: Configure global system settings, scheduling and automation

Description	Set global and system options, console and web access, resource limits, command aliases, schedules, auto scripts, automation stitches and object tags.
Collection	`fortinet.fortiswitch` (Certified, Fortinet, v1.4.0, updated 2026-10-09)

Key content	**Global attributes** `fortiswitch_system_global` **Switch global settings** `fortiswitch_switch_global` **System settings** `fortiswitch_system_settings` **Console** `fortiswitch_system_console` **Dashboard CLI console** `fortiswitch_gui_console` **Web attributes** `fortiswitch_system_web` **Session TTL** `fortiswitch_system_session_ttl` **Resource limits** `fortiswitch_system_resource_limits` **Locations** `fortiswitch_system_location` **Object tags** `fortiswitch_system_object_tag` **Alias commands** `fortiswitch_system_alias_command` **Alias groups** `fortiswitch_system_alias_group` **Auto scripts** `fortiswitch_system_auto_script` **Automation actions** `fortiswitch_system_automation_action` **Automation destinations** `fortiswitch_system_automation_destination` **Automation stitches** `fortiswitch_system_automation_stitch` **Automation triggers** `fortiswitch_system_automation_trigger` **One-time schedules** `fortiswitch_system_schedule_onetime` **Recurring schedules** `fortiswitch_system_schedule_recurring` **Schedule groups** `fortiswitch_system_schedule_group`
Notes	• Most modules configure one FortiSwitch object each; execute_* modules run one-off actions.

HashiCorp Vault `hashicorp.vault`

Certified HashiCorp | An IBM Company · version 1.3.0 · updated 2026-07-09 · 22 modules → 4 use cases

Use Case: Store and read secrets

Description	Manage KV version 1 and 2 secrets and look them up in playbooks.
Collection	`hashicorp.vault` (Certified, HashiCorp | An IBM Company, v1.3.0, updated 2026-07-09)
Key content	**KV v1 secrets** `kv1_secret`, `kv1_secret_info` **KV v2 secrets** `kv2_secret`, `kv2_secret_info` **KV v1 secret lookup** lookup `kv1_secret_get` **KV v2 secret lookup** lookup `kv2_secret_get`

Use Case: Manage database credentials

Description	Manage database connections, dynamic and static roles, generate credentials and rotate them.
Collection	`hashicorp.vault` (Certified, HashiCorp | An IBM Company, v1.3.0, updated 2026-07-09)
Key content	**Database connections** `database_connection`, `database_connection_info` **Dynamic roles** `database_role`, `database_role_info` **Dynamic role credentials** `database_dynamic_role_credentials` **Static roles** `database_static_role`, `database_static_role_info` **Static role credentials** `database_static_role_credentials` **Credential rotation** `database_credential_rotation`

Use Case: Issue certificates

Description	Issue, sign and revoke PKI certificates.
Collection	`hashicorp.vault` (Certified, HashiCorp | An IBM Company, v1.3.0, updated 2026-07-09)
Key content	**PKI certificates** `pki_certificate`, `pki_certificate_info`

Use Case: Control access to Vault

Description	Authenticate, manage tokens, ACL policies and Enterprise namespaces.
Collection	`hashicorp.vault` (Certified, HashiCorp | An IBM Company, v1.3.0, updated 2026-07-09)
Key content	**Login** `auth_login` **Tokens** `auth_token`, `auth_token_info` **ACL policies** `acl_policy`, `acl_policy_info` **Namespaces** `vault_namespace`, `vault_namespace_info`

IBM Security Verify Access (ISAM) `ibm.isam`

Certified IBM · version 3.6.0 · updated 2026-04-28 · 3 modules → 17 use cases

Use Case: Connect to appliances and run ISAM functions

Description	Connect to Verify Access appliances through the ISAM connection plugin and run ibmsecurity functions, CLI commands and connectivity checks.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)

Key content	**ISAM module (run any ibmsecurity function)** `isam` **ISAM admin module** `isamadmin` **ISAM appliance connection plugin** connection `isam` **CLI (playbook)** playbook `cli` **Connectivity check (playbook)** playbook `connectivity_check`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Transform configuration data for appliances

Description	Reshape YAML configuration, build XML policy documents and read configuration file trees for use in ISAM tasks.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Exclude keys filter** filter `exclude` **Flatten management root filter** filter `flatten_management_root` **Include-only filter** filter `include_only` **Rename key filter** filter `rename_key` **Nice XML filter** filter `to_nice_xml` **XML filter** filter `to_xml` **File tree lookup** lookup `filetree`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Apply a baseline configuration to a fleet

Description	Bootstrap appliances and apply a common site configuration, run sanity checks, or revert appliances to their pre-configuration state.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**First steps (playbook)** playbook `base.first_steps` **Template (playbook)** playbook `base.template` **Base site (playbook)** playbook `base_site` **Bootstrap local (playbook)** playbook `bootstrap_local` **Revert (playbook)** playbook `revert` **Site (playbook)** playbook `site` **Base (role)** role `base` **Bootstrap local (role)** role `bootstrap_local` **Common handlers (role)** role `common_handlers` **Meta (role)** role `meta` **Sanity checks (role)** role `sanity_checks`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Configure network, DNS and time settings

Description	Set appliance interfaces, VLANs, IPv4 and DHCP addresses, static routes, host records, hostname, DNS, NTP and TCP/IP tuning.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Add interfaces (playbook)** playbook `base.add_interfaces` **Configure DHCP (playbook)** playbook `base.configure_dhcp` **Configure DNS (playbook)** playbook `base.configure_dns` **Configure interfaces (playbook)** playbook `base.configure_interfaces` **Configure static routes (playbook)** playbook `base.configure_static_routes` **Configure time (playbook)** playbook `base.configure_time` **Delete interfaces (playbook)** playbook `base.delete_interfaces` **Set DNS (playbook)** playbook `base.set_dns` **Set host records (playbook)** playbook `base.set_host_records` **Set hostname (playbook)** playbook `base.set_hostname` **Set listening interfaces (playbook)** playbook `base.set_listening_interfaces` **Add network IPv4 (role)** role `add_network_ipv4` **Add runtime listening interface (role)** role `add_runtime_listening_interface` **Add static route (role)** role `add_static_route` **Config DNS (role)** role `config_dns` **Config NTP (role)** role `config_ntp` **Set host records (role)** role `set_host_records` **Set network hostname (role)** role `set_network_hostname` **Set network IPv4 DHCP (role)** role `set_network_ipv4_dhcp` **Set tcpip tuning (role)** role `set_tcpip_tuning` **Update network interface VLAN (role)** role `update_network_interface_vlan` **Update network IPv4 (role)** role `update_network_ipv4` **Update static route (role)** role `update_static_route`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Update firmware, fixpacks and licensing

Description	Upload and install firmware updates and fixpacks, swap or back up firmware partitions, import licenses, activate modules and report fix levels.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)

Key content	**Activate modules (playbook)** playbook `base.activate_modules` **Backup firmware (playbook)** playbook `base.backup_firmware` **Install fixpacks (playbook)** playbook `base.install_fixpacks` **Install update (playbook)** playbook `base.install_update` **Install updates (playbook)** playbook `base.install_updates` **Swap firmware (playbook)** playbook `base.swap_firmware` **Upload updates (playbook)** playbook `base.upload_updates` **Install firmware (playbook)** playbook `install_firmware` **Install fixpack (playbook)** playbook `install_fixpack` **Report fix levels (playbook)** playbook `report_fix_levels` **Activate module (role)** role `activate_module` **Delete activation (role)** role `delete_activation` **Get firmware (role)** role `get_firmware` **Get fixpack (role)** role `get_fixpack` **Install firmware (role)** role `install_firmware` **Install fixpack (role)** role `install_fixpack` **Install license (role)** role `install_license`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Manage snapshots and application logs

Description	Create, upload, download, apply and delete configuration snapshots, and export, archive or delete application logs.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Apply snapshot (playbook)** playbook `base.apply_snapshot` **Create snapshot (playbook)** playbook `base.create_snapshot` **Delete application logs (playbook)** playbook `base.delete_application_logs` **Delete snapshots (playbook)** playbook `base.delete_snapshots` **Download snapshots (playbook)** playbook `base.download_snapshots` **Export application logs (playbook)** playbook `base.export_application_logs` **Upload snapshot (playbook)** playbook `base.upload_snapshot` **Export logs (playbook)** playbook `export_logs` **RP archive logs (playbook)** playbook `rp_archive_logs` **Archive logs (role)** role `archive_logs` **Create snapshot (role)** role `create_snapshot` **Export application logs (role)** role `export_application_logs`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Monitor appliances and forward alerts

Description	Set up SNMP monitoring, system alerts by email, SNMP or syslog, remote syslog forwarding and audit settings, and collect CPU and memory statistics.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Report CPU statistics (playbook)** playbook `report_cpu_statistics` **Report memory statistics (playbook)** playbook `report_memory_statistics` **System alerts (playbook)** playbook `system_alerts` **Add system alerts rsyslog (role)** role `add_system_alerts_rsyslog` **Add system alerts SMTP (role)** role `add_system_alerts_smtp` **Add system alerts SNMP (role)** role `add_system_alerts_snmp` **Config SNMP monitoring (role)** role `config_snmp_monitoring` **Config SNMP monitoring v3 (role)** role `config_snmp_monitoring_v3` **Get CPU statistics (role)** role `get_cpu_statistics` **Get memory statistics (role)** role `get_memory_statistics` **Set audit configuration (role)** role `set_audit_configuration` **Set rsyslog forwarder (role)** role `set_rsyslog_forwarder` **Set rsyslog forwarder sources (role)** role `set_rsyslog_forwarder_sources`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Compare appliances and generate reports

Description	Compare an appliance against a master configuration and generate reports on junctions and other appliance details.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Appliance comparison module** `isamcompare` **Compare (playbook)** playbook `compare` **Report junctions (playbook)** playbook `report_junctions` **Execute compare (role)** role `execute_compare` **Gen report (role)** role `gen_report`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Manage certificates and keystores

Description	Create certificate databases, generate self-signed certificates and CSRs, import and export personal and signer certificates, and update the management SSL certificate.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)

Key content	**Configure certificate databases (playbook)** playbook `base.configure_certificate_databases` **Configure certificate requests (playbook)** playbook `base.configure_certificate_requests` **Configure management SSL (playbook)** playbook `base.configure_management_ssl` **Configure personal certificates (playbook)** playbook `base.configure_personal_certificates` **Configure signer certificates (playbook)** playbook `base.configure_signer_certificates` **Create SSL certificate databases (playbook)** playbook `base.create_ssl_certificate_databases` **Export personal certificates (playbook)** playbook `base.export_personal_certificates` **Extract certificates (playbook)** playbook `base.extract_certificates` **Generate self signed certificates (playbook)** playbook `base.generate_self_signed_certificates` **Import personal certificates (playbook)** playbook `base.import_personal_certificates` **Import signer certificates (playbook)** playbook `base.import_signer_certificates` **Load signer certificates (playbook)** playbook `base.load_signer_certificates` **Upload personal certificate (playbook)** playbook `web.upload_personal_certificate` **Create keystore (role)** role `create_keystore` **Import ca certs (role)** role `import_ca_certs` **Import certificate DB (role)** role `import_certificate_db` **Import personal cert (role)** role `import_personal_cert` **Load signer cert (role)** role `load_signer_cert` **Set cert replication (role)** role `set_cert_replication` **Set keystore desc (role)** role `set_keystore_desc` **Update management SSL cert (role)** role `update_management_ssl_cert`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Manage administrators, system accounts and management authorization

Description	Change administrator passwords, create system accounts and groups, assign management authorization roles and switch appliance authentication to an external directory.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Change admin password (playbook)** playbook `base.change_admin_password` **Configure sysaccounts (playbook)** playbook `base.configure_sysaccounts` **Create sysaccount (playbook)** playbook `base.create_sysaccount` **Create sysaccounts (playbook)** playbook `base.create_sysaccounts` **Set management authorization (playbook)** playbook `base.set_management_authorization` **Set password sysaccounts (playbook)** playbook `base.set_password_sysaccounts` **Change passwords (playbook)** playbook `change_passwords` **ISAM va sysaccount (playbook)** playbook `isam-va-sysaccount` **Switch auth (playbook)** playbook `switch_auth` **Add mgmtazn role (role)** role `add_mgmtazn_role` **Add sysaccount group (role)** role `add_sysaccount_group` **Add sysaccount user (role)** role `add_sysaccount_user` **Set admin cfg (role)** role `set_admin_cfg` **Set admin pw (role)** role `set_admin_pw` **Set mgmtazn role feature (role)** role `set_mgmtazn_role_feature` **Set mgmtazn role group (role)** role `set_mgmtazn_role_group` **Set role group (role)** role `set_role_group` **Set role user (role)** role `set_role_user` **Switch auth (role)** role `switch_auth`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Configure clusters, containers and runtime tuning

Description	Join nodes to a cluster, replicate certificates and runtime state, tune advanced and runtime parameters, load extensions and run Verify Access in containers.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Configure advanced tuning parameters (playbook)** playbook `base.configure_advanced_tuning_parameters` **Configure cluster (playbook)** playbook `base.configure_cluster` **Configure containers (playbook)** playbook `base.configure_containers` **Configure extensions (playbook)** playbook `base.configure_extensions` **Configure runtime tunings (playbook)** playbook `base.configure_runtime_tunings` **Get container metadata (playbook)** playbook `base.get_container_metadata` **Publish (playbook)** playbook `base.publish` **Docker (playbook)** playbook `docker` **Add cluster node (role)** role `add_cluster_node` **Docker (role)** role `docker` **Export cluster sign (role)** role `export_cluster_sign` **Externalize hvdb db2 (role)** role `externalize_hvdb_db2` **Set advanced tuning parameter (role)** role `set_advanced_tuning_parameter` **Set cluster config (role)** role `set_cluster_config` **Set dsc config (role)** role `set_dsc_config` **Set runtime replication (role)** role `set_runtime_replication` **Set runtime tuning parameter (role)** role `set_runtime_tuning_parameter` **Upload extension (role)** role `upload_extension`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Configure reverse proxy instances and junctions

Description	Create, configure, restart and delete WebSEAL reverse proxy instances, edit their configuration stanzas, and manage junctions and failover cookies.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)

Key content	**Isamcfg (playbook)** playbook `isamcfg` **RP conf update (playbook)** playbook `rp_conf_update` **RP operation (playbook)** playbook `rp_operation` **RP restart (playbook)** playbook `rp_restart` **Config reverseproxy AAC (playbook)** playbook `web.config_reverseproxy_aac` **Config reverseproxy federations (playbook)** playbook `web.config_reverseproxy_federations` **Config reverseproxy MMFA (playbook)** playbook `web.config_reverseproxy_mmfa` **Config reverseproxy OAuth (playbook)** playbook `web.config_reverseproxy_oauth` **Configure reverseproxy instances (playbook)** playbook `web.configure_reverseproxy_instances` **Configure reverseproxy junctions (playbook)** playbook `web.configure_reverseproxy_junctions` **Configure reverseproxy junctions setall (playbook)** playbook `web.configure_reverseproxy_junctions_setall` **Configure reverseproxy wafcrssetup (playbook)** playbook `web.configure_reverseproxy_wafcrssetup` **Create reverseproxy instances (playbook)** playbook `web.create_reverseproxy_instances` **Delete reverseproxy instance (playbook)** playbook `web.delete_reverseproxy_instance` **Get reverseproxy stanza (playbook)** playbook `web.get_reverseproxy_stanza` **Restart reverseproxy instances (playbook)** playbook `web.restart_reverseproxy_instances` **Add junction (role)** role `add_junction` **Add junction servers (role)** role `add_junction_servers` **Add reverseproxy conf (role)** role `add_reverseproxy_conf` **Config failover cookie (role)** role `config_failover_cookie` **Config reverseproxy AAC (role)** role `config_reverseproxy_aac` **Config reverseproxy federation (role)** role `config_reverseproxy_federation` **Config reverseproxy OAuth (role)** role `config_reverseproxy_oauth` **Create reverseproxy (role)** role `create_reverseproxy` **Delete junction (role)** role `delete_junction` **Delete reverseproxy conf (role)** role `delete_reverseproxy_conf` **Execute RP op (role)** role `execute_rp_op` **Get junction details (role)** role `get_junction_details` **Get junctions (role)** role `get_junctions` **Get reverseproxies (role)** role `get_reverseproxies` **Set junction (role)** role `set_junction` **Set reverseproxy conf (role)** role `set_reverseproxy_conf` **Update reverseproxy conf (role)** role `update_reverseproxy_conf`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Manage management root, SSO keys and web content

Description	Upload management root files, SSO, LTPA and Kerberos key files, certificate mapping files, URL mappings and HTTP transformation rules to the reverse proxy.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Configure HTTP transformation rules (playbook)** playbook `web.configure_http_transformation_rules` **Configure kerberos (playbook)** playbook `web.configure_kerberos` **Configure management root (playbook)** playbook `web.configure_management_root` **Create SSO keys (playbook)** playbook `web.create_sso_keys` **Export SSO keys (playbook)** playbook `web.export_sso_keys` **Import certificate mapping files (playbook)** playbook `web.import_certificate_mapping_files` **Import keytab files (playbook)** playbook `web.import_keytab_files` **Import SSO keys (playbook)** playbook `web.import_sso_keys` **Update JMT files (playbook)** playbook `web.update_jmt_files` **Upload dynurl files (playbook)** playbook `web.upload_dynurl_files` **Upload HTTP transformation files (playbook)** playbook `web.upload_http_transformation_files` **Upload JMT files (playbook)** playbook `web.upload_jmt_files` **Upload LTPA files (playbook)** playbook `web.upload_ltpa_files` **Upload management root files (playbook)** playbook `web.upload_management_root_files` **Upload runtime components (playbook)** playbook `web.upload_runtime_components` **Create mgmt root dir (role)** role `create_mgmt_root_dir` **Create mgmt root file (role)** role `create_mgmt_root_file` **Delete mgmt root file (role)** role `delete_mgmt_root_file` **Import client cert mapping (role)** role `import_client_cert_mapping` **Import HTTP transformation (role)** role `import_http_transformation` **Import management root (role)** role `import_management_root` **Import URL mapping (role)** role `import_url_mapping` **Update auth mech (role)** role `update_auth_mech` **Update management root (role)** role `update_management_root` **Upload LTPA key (role)** role `upload_ltpa_key`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Configure the policy server and user registry

Description	Configure the policy server, federated directories, embedded LDAP, Redis and runtime components, and run pdadmin commands.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Pdadmin (playbook)** playbook `pdadmin` **Configure federated directories (playbook)** playbook `web.configure_federated_directories` **Configure policyserver (playbook)** playbook `web.configure_policyserver` **Configure redis (playbook)** playbook `web.configure_redis` **Configure runtime components (playbook)** playbook `web.configure_runtime_components` **Execute pdadmin (playbook)** playbook `web.execute_pdadmin` **Set embedded LDAP admin pw (playbook)** playbook `web.set_embedded_ldap_admin_pw` **Set runtime components (playbook)** playbook `web.set_runtime_components` **Add suffix (role)** role `add_suffix` **Config FED dir (role)** role `config_fed_dir` **Config policyserver (role)** role `config_policyserver` **Execute pdadmin (role)** role `execute_pdadmin` **Web (role)** role `web`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Configure advanced access control and authentication policies

Description	Define authentication mechanisms and policies, access control policies and attributes, mapping rules, information points, FIDO2, mobile MFA and SCIM settings.

Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Configure access control attributes (playbook)** playbook `aac.configure_access_control_attributes` **Configure access control policies (playbook)** playbook `aac.configure_access_control_policies` **Configure access control policy attachments (playbook)** playbook `aac.configure_access_control_policy_attachments` **Configure access control policy resources (playbook)** playbook `aac.configure_access_control_policy_resources` **Configure advanced configurations (playbook)** playbook `aac.configure_advanced_configurations` **Configure authentication mechanisms (playbook)** playbook `aac.configure_authentication_mechanisms` **Configure authentication policies (playbook)** playbook `aac.configure_authentication_policies` **Configure FIDO2 (playbook)** playbook `aac.configure_fido2` **Configure mapping rules (playbook, aac)** playbook `aac.configure_mapping_rules` **Configure MMFA (playbook)** playbook `aac.configure_mmfa` **Configure policy information points (playbook)** playbook `aac.configure_policy_information_points` **Configure runtime template root (playbook)** playbook `aac.configure_runtime_template_root` **Configure SCIM (playbook)** playbook `aac.configure_scim` **Configure server connections (playbook)** playbook `aac.configure_server_connections` **Configure user registry (playbook)** playbook `aac.configure_user_registry` **Create authentication mechanisms (playbook)** playbook `aac.create_authentication_mechanisms` **Create authentication policies (playbook)** playbook `aac.create_authentication_policies` **Create runtime template directories (playbook)** playbook `aac.create_runtime_template_directories` **Disable all authentication policies (playbook)** playbook `aac.disable_all_authentication_policies` **Export runtime template root (playbook)** playbook `aac.export_runtime_template_root` **Import runtime template files (playbook)** playbook `aac.import_runtime_template_files` **AAC (role)** role `aac` **Add attribute source (role)** role `add_attribute_source` **Add server connection LDAP (role)** role `add_server_connection_ldap` **Add server connection ws (role)** role `add_server_connection_ws` **Config policy attachments (role)** role `config_policy_attachments` **Create runtime template directories (role)** role `create_runtime_template_directories` **Import runtime template file (role)** role `import_runtime_template_file` **Search attribute source (role)** role `search_attribute_source` **Search mapping rule (role)** role `search_mapping_rule` **Set access control policy (role)** role `set_access_control_policy` **Set access policy (role)** role `set_access_policy` **Set attribute source (role)** role `set_attribute_source` **Set auth mech (role)** role `set_auth_mech` **Set auth policy (role)** role `set_auth_policy` **Set mapping rule (role)** role `set_mapping_rule` **Update advanced configuration (role)** role `update_advanced_configuration` **Upload mapping rule (role)** role `upload_mapping_rule`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Protect APIs with OAuth

Description	Create API protection definitions and OAuth 2.0 clients for API access control.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Configure API protection clients (playbook)** playbook `aac.configure_api_protection_clients` **Configure API protection definitions (playbook)** playbook `aac.configure_api_protection_definitions` **Create API protection clients (playbook)** playbook `aac.create_api_protection_clients` **Create API protection definitions (playbook)** playbook `aac.create_api_protection_definitions` **Add OAuth client (role)** role `add_oauth_client` **Add OAuth definition (role)** role `add_oauth_definition` **Set OAuth client (role)** role `set_oauth_client` **Set OAuth definition (role)** role `set_oauth_definition`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

Use Case: Configure identity federation

Description	Create federations and partners, STS chain templates and points of contact for SAML and OIDC single sign-on, including the federation cookbook scenarios.
Collection	`ibm.isam` (Certified, IBM, v3.6.0, updated 2026-04-28)
Key content	**Configure mapping rules (playbook, fed)** playbook `fed.configure_mapping_rules` **Configure sts chain templates (playbook)** playbook `fed.configure_sts_chain_templates` **Configure sts chains (playbook)** playbook `fed.configure_sts_chains` **Create federation partners (playbook)** playbook `fed.create_federation_partners` **Create federations (playbook)** playbook `fed.create_federations` **Set current poc profile (playbook)** playbook `fed.set_current_poc_profile` **Set user registry user pw (playbook)** playbook `fed.set_user_registry_user_pw` **FED idp part1 (playbook)** playbook `federation_cookbook.fed_idp_part1` **FED idp part2 (playbook)** playbook `federation_cookbook.fed_idp_part2` **FED sp part1 (playbook)** playbook `federation_cookbook.fed_sp_part1` **FED sp part2 (playbook)** playbook `federation_cookbook.fed_sp_part2` **Add chain template (role)** role `add_chain_template` **Add federation (role)** role `add_federation` **Add module chain (role)** role `add_module_chain` **Add partner (role)** role `add_partner` **FED (role)** role `fed` **Get federation (role)** role `get_federation` **Set current point of contact (role)** role `set_current_point_of_contact` **Set federation (role)** role `set_federation` **Set partner (role)** role `set_partner` **Update point of contact (role)** role `update_point_of_contact`
Notes	• Modules are generic wrappers around the ibmsecurity library; most functionality is delivered through the bundled roles and example playbooks.

IBM QRadar `ibm.qradar`

Certified IBM · version 4.0.0 · updated 2024-06-12 · 10 modules → 2 use cases

Use Case: Manage offenses

Description	Query offenses with filters, take action on them and add or update notes.
Collection	`ibm.qradar` (Certified, IBM, v4.0.0, updated 2024-06-12)
Key content	**Offenses** `offense_info` **Offense actions** `offense_action` **Offense notes** `offense_note` **Offense information** `qradar_offense_info` **Offense actions (qradar_ prefix)** `qradar_offense_action` **Offense notes (qradar_ prefix)** `qradar_offense_note`

Use Case: Manage detection content and deployment

Description	Manage analytics rules and log sources and deploy configuration changes.
Collection	`ibm.qradar` (Certified, IBM, v4.0.0, updated 2024-06-12)
Key content	**Analytics rules** `qradar_analytics_rules` **Log sources** `qradar_log_sources_management` **Configuration deployment** `deploy` **Configuration deployment (qradar_ prefix)** `qradar_deploy`

Red Hat Advanced Cluster Security for Kubernetes (RHACS) `infra.rhacs_configuration`

Validated Red Hat · version 2.0.1 · updated 2026-07-16 · 27 modules → 5 use cases

Use Case: Manage security policies

Description	Create, clone, import and export security policies and categories, and attach notifiers to them.
Collection	`infra.rhacs_configuration` (Validated, Red Hat, v2.0.1, updated 2026-07-16)
Key content	**Security policies** `rhacs_policy`, `rhacs_policy_status` **Policy categories** `rhacs_policy_category` **Policy cloning** `rhacs_policy_clone` **Policy export** `rhacs_policy_export` **Policy import** `rhacs_policy_import` **Policy notifiers** `rhacs_policy_notifier` **Vulnerability exception expiration** `rhacs_exception`

Use Case: Control access

Description	Configure authentication providers, group-to-role mapping, roles, permission sets, access scopes, machine access and API tokens.
Collection	`infra.rhacs_configuration` (Validated, Red Hat, v2.0.1, updated 2026-07-16)
Key content	**Authentication providers** `rhacs_auth_provider` **Role mappings** `rhacs_group` **Roles** `rhacs_role` **Permission sets** `rhacs_permission_set` **Access scopes** `rhacs_access_scope` **Machine access** `rhacs_machine_access` **API tokens** `rhacs_api_token`

Use Case: Scan images and verify signatures

Description	Integrate image scanners, registries, delegated scanning, image watches and Cosign signatures.
Collection	`infra.rhacs_configuration` (Validated, Red Hat, v2.0.1, updated 2026-07-16)
Key content	**Scanner and registry integrations** `rhacs_image_integration` **Delegated image scanning** `rhacs_delegated_image_scan` **Image watches** `rhacs_image_watch` **Cosign signatures** `rhacs_signature`

Use Case: Report on compliance and vulnerabilities

Description	Schedule compliance scans and vulnerability reports and group deployments into collections.
Collection	`infra.rhacs_configuration` (Validated, Red Hat, v2.0.1, updated 2026-07-16)
Key content	**Compliance schedules** `rhacs_compliance_schedule` **Vulnerability report schedules** `rhacs_report_schedule` **Deployment collections** `rhacs_collection`

Use Case: Configure the RHACS platform and integrations

Description	Manage RHACS configuration, secured cluster init bundles, notifier integrations, cloud platform integrations and external backups.
Collection	`infra.rhacs_configuration` (Validated, Red Hat, v2.0.1, updated 2026-07-16)
Key content	**RHACS configuration** `rhacs_config` **Cluster init bundles** `rhacs_init_bundle` **Notification methods** `rhacs_notifier_integration` **Cloud platform integrations** `rhacs_cloud_management_platform` **External backups** `rhacs_external_backup`

1Password Connect `onepassword.connect`

Certified 1Password · version 2.4.0 · updated 2026-05-04 · 3 modules → 1 use cases

Use Case: Read and create 1Password items

Description	Look up items and field values in 1Password and create generic items.
Collection	`onepassword.connect` (Certified, 1Password, v2.4.0, updated 2026-05-04)
Key content	**Item information** `item_info` **Field values** `field_info` **Generic items** `generic_item`

Palo Alto Networks PAN-OS and Panorama `paloaltonetworks.panos`

Certified Palo Alto Networks · version 3.4.1 · updated 2026-07-24 · 105 modules → 10 use cases

Use Case: Manage security policy rules

Description	Create and order security, NAT, policy-based forwarding and decryption rules, and test traffic against the rule base.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Security rules** `panos_security_rule` **NAT rules** `panos_nat_rule2` **Policy-based forwarding rules** `panos_pbf_rule` **Decryption rules** `panos_decryption_rule` **Security rule match tests** `panos_match_rule` **Security profile groups** `panos_pg`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Manage policy objects

Description	Maintain addresses, services, applications, URL categories, tags, schedules, regions and dynamic lists used by rules.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)

Key content	**Address objects** `panos_address_object` **Address groups** `panos_address_group` **Service objects** `panos_service_object` **Service groups** `panos_service_group` **Application objects** `panos_application_object` **Application filters** `panos_application_filter` **Application groups** `panos_application_group` **Custom URL categories** `panos_custom_url_category` **External dynamic lists** `panos_edl` **Tags** `panos_tag_object` **Schedules** `panos_schedule_object` **Regions** `panos_region` **Dynamic user groups** `panos_dynamic_user_group` **Registered IP addresses** `panos_registered_ip`, `panos_registered_ip_facts` **User-ID mappings** `panos_userid`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Configure zones, interfaces and Layer 2 switching

Description	Set up security zones, data-port, aggregate, loopback, tunnel and VLAN interfaces, subinterfaces, virtual wires and DHCP.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Security zones** `panos_zone` **Ethernet interfaces** `panos_interface` **Aggregate interfaces** `panos_aggregate_interface` **Loopback interfaces** `panos_loopback_interface` **Tunnel interfaces** `panos_tunnel` **VLANs** `panos_vlan` **VLAN interfaces** `panos_vlan_interface` **Layer 2 subinterfaces** `panos_l2_subinterface` **Layer 3 subinterfaces** `panos_l3_subinterface` **Virtual wires** `panos_virtual_wire` **IPv6 interface addresses** `panos_ipv6_address` **DHCP** `panos_dhcp` **DHCP relay** `panos_dhcp_relay` **DHCP IPv6 relay addresses** `panos_dhcp_relay_ipv6_address` **Interface management profiles** `panos_management_profile`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Configure routing: virtual routers, BGP and OSPF

Description	Manage virtual routers and logical routers with static routes, BGP peers and policies, OSPF areas and redistribution.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Virtual routers** `panos_virtual_router` **Static routes** `panos_static_route` **Redistribution profiles** `panos_redistribution` **BGP** `panos_bgp` **BGP peer groups** `panos_bgp_peer_group` **BGP peers** `panos_bgp_peer` **BGP authentication profiles** `panos_bgp_auth` **BGP dampening profiles** `panos_bgp_dampening` **BGP aggregation** `panos_bgp_aggregate` **BGP conditional advertisement** `panos_bgp_conditional_advertisement` **BGP policy filters** `panos_bgp_policy_filter` **BGP policy rules** `panos_bgp_policy_rule` **BGP redistribution rules** `panos_bgp_redistribute` **Logical routers** `panos_logical_router` **Logical router VRFs** `panos_logical_router_vrf` **Logical router static routes** `panos_logical_router_vrf_static_route` **OSPF areas** `panos_logical_router_vrf_ospf_area` **OSPF area interfaces** `panos_logical_router_vrf_ospf_area_interface`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Build VPN and tunnels

Description	Configure IKE gateways, IKE and IPsec crypto profiles, IPsec tunnels, proxy IDs and GRE tunnels.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**IKE crypto profiles** `panos_ike_crypto_profile` **IKE gateways** `panos_ike_gateway` **IPsec crypto profiles** `panos_ipsec_profile` **IPsec tunnels** `panos_ipsec_tunnel` **IPsec proxy IDs** `panos_ipsec_ipv4_proxyid` **GRE tunnels** `panos_gre_tunnel`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Forward logs and send alerts

Description	Define syslog, HTTP, email and SNMP server profiles and log forwarding profiles with their match lists.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Syslog profiles** `panos_syslog_profile` **Syslog servers** `panos_syslog_server` **HTTP server profiles** `panos_http_profile` **HTTP servers** `panos_http_server` **HTTP profile headers** `panos_http_profile_header` **HTTP profile parameters** `panos_http_profile_param` **Email profiles** `panos_email_profile` **Email servers** `panos_email_server` **SNMP profiles** `panos_snmp_profile` **SNMP v2c servers** `panos_snmp_v2c_server` **SNMP v3 servers** `panos_snmp_v3_server` **Log forwarding profiles** `panos_log_forwarding_profile` **Log forwarding match lists** `panos_log_forwarding_profile_match_list` **Log forwarding match actions** `panos_log_forwarding_profile_match_list_action` **PAN-OS log events (Event-Driven Ansible)** eda event source `logs`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Manage Panorama device groups and templates

Description	Organise managed firewalls with device groups, templates, template stacks and template variables.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Device groups** `panos_device_group` **Templates** `panos_template` **Template stacks** `panos_template_stack` **Template variables** `panos_template_variable`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Commit and push configuration

Description	Commit candidate configuration on firewalls and Panorama, push to managed devices, and load, import, export or edit configuration.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Firewall commit** `panos_commit_firewall` **Panorama commit** `panos_commit_panorama` **Push to managed devices** `panos_commit_push` **Configuration elements** `panos_config_element` **Configuration load** `panos_loadcfg` **File import** `panos_import` **File export** `panos_export`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Administer devices: access, certificates, licences and upgrades

Description	Manage administrators, API keys, SSH-based admin and certificate tasks, licences, content updates, software versions, HA, restarts and VM-Series bootstrapping.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Administrators** `panos_administrator` **Admin password change** `panos_admpwd` **API keys** `panos_api_key` **Self-signed certificates** `panos_cert_gen_ssh` **Device management settings** `panos_mgtconfig` **Licence authcodes** `panos_lic` **Dynamic updates** `panos_dynamic_updates` **Software versions** `panos_software` **High availability** `panos_ha` **Device restart** `panos_restart` **VM-Series auth keys** `panos_vm_auth_key`
Notes	• Module names have the panos_ prefix omitted.

Use Case: Check device state and run operational commands

Description	Verify readiness and HA role, collect facts, take and compare state snapshots, and run operational or type commands.
Collection	`paloaltonetworks.panos` (Certified, Palo Alto Networks, v3.4.1, updated 2026-07-24)
Key content	**Device readiness check** `panos_check` **Active HA node check** `panos_active_in_ha` **Readiness checks** `panos_readiness_checks` **Facts** `panos_facts` **State snapshots** `panos_state_snapshot` **Snapshot comparison reports** `panos_snapshot_report` **Operational commands** `panos_op` **Type commands** `panos_type_cmd`
Notes	• Module names have the panos_ prefix omitted.

Palo Alto Networks PAN-OS `paloaltonetworks.panos_policy_automation`

Validated Palo Alto Networks · version 1.4.6 · updated 2026-02-03 · 0 modules → 2 use cases

Use Case: Check whether traffic is permitted

Description	Look up whether traffic is permitted or denied by PAN-OS firewalls and interpret routing and policy match results.
Collection	`paloaltonetworks.panos_policy_automation` (Validated, Palo Alto Networks, v1.4.6, updated 2026-02-03)
Key content	**Policy lookup** role `lookup_policy` **Policy lookup example** playbook `examples.lookup_policy` **Policy match result** filter `panos_op_policy_match_result_to_bool` **Logical routers** filter `panos_op_get_routers_from_dict_or_list` **Zone from interface** filter `panos_op_get_zone_from_interface` **Interfaces from routing test** filter `panos_op_routing_result_to_interfaces` **Operational results as list** filter `panos_op_stdout_results_to_list` **Operational output as dictionary** filter `panos_op_stdout_to_dict`

Use Case: Create new network access

Description	Configure new network access in Panorama.
Collection	`paloaltonetworks.panos_policy_automation` (Validated, Palo Alto Networks, v1.4.6, updated 2026-02-03)
Key content	**Policy creation** role `policy_creation` **Policy creation example** playbook `examples.create_policy`

Red Hat Trusted Artifact Signer `redhat.artifact_signer`

Certified Red Hat · version 1.4.4 · updated 2026-10-16 · 0 modules → 1 use cases

Use Case: Deploy Trusted Artifact Signer

Description	Configure Trusted Artifact Signer on a single managed node.
Collection	`redhat.artifact_signer` (Certified, Red Hat, v1.4.4, updated 2026-10-16)
Key content	**Single-node deployment** role `tas_single_node`

Red Hat Identity Management (FreeIPA) `redhat.rhel_idm`

Certified Red Hat · version 1.16.0 · updated 2026-02-10 · 43 modules → 17 use cases

Use Case: Manage users, groups and password policy

Description	Create, modify, disable and delete IdM users and groups, set password policies and manage system accounts and user certificates.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)

Key content	**Groups** `ipagroup` **Password policies** `ipapwpolicy` **System accounts** `ipasysaccount` **Users** `ipauser` **Add group (playbook)** playbook `group.add-group` **Add groups (playbook)** playbook `group.add-groups` **Add groups to group (playbook)** playbook `group.add-groups-to-group` **Add user to group (playbook)** playbook `group.add-user-to-group` **Delete group (playbook)** playbook `group.delete-group` **Pwpolicy absent (playbook)** playbook `pwpolicy.pwpolicy_absent` **Pwpolicy grace limit (playbook)** playbook `pwpolicy.pwpolicy_grace_limit` **Pwpolicy password check (playbook)** playbook `pwpolicy.pwpolicy_password_check` **Pwpolicy present (playbook)** playbook `pwpolicy.pwpolicy_present` **Sysaccount absent (playbook)** playbook `sysaccount.sysaccount-absent` **Sysaccount disabled (playbook)** playbook `sysaccount.sysaccount-disabled` **Sysaccount enabled (playbook)** playbook `sysaccount.sysaccount-enabled` **Sysaccount present (playbook)** playbook `sysaccount.sysaccount-present` **Sysaccount privileged (playbook)** playbook `sysaccount.sysaccount-privileged` **Sysaccount unprivileged (playbook)** playbook `sysaccount.sysaccount-unprivileged` **Add user (playbook)** playbook `user.add-user` **Add user external idp (playbook)** playbook `user.add-user-external-idp` **Delete preserve user (playbook)** playbook `user.delete-preserve-user` **Delete user (playbook)** playbook `user.delete-user` **Disable user (playbook)** playbook `user.disable-user` **Enable user (playbook)** playbook `user.enable-user` **Ensure user with randompassword (playbook)** playbook `user.ensure_user_with_randompassword` **Ensure users with randompasswords (playbook)** playbook `user.ensure_users_with_randompasswords` **SMB attributes (playbook)** playbook `user.smb-attributes` **Undelete user (playbook)** playbook `user.undelete-user` **Unlock users (playbook)** playbook `user.unlock-users` **User certificate absent (playbook)** playbook `user.user_certificate_absent` **User certificate present (playbook)** playbook `user.user_certificate_present` **User present (playbook)** playbook `user.user_present` **Users absent (playbook)** playbook `user.users_absent` **Users certificate absent (playbook)** playbook `user.users_certificate_absent` **Users certificate present (playbook)** playbook `user.users_certificate_present` **Users present (playbook)** playbook `user.users_present`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Manage hosts, host groups and netgroups

Description	Add and remove IdM hosts with their IP addresses, principals, keytab permissions and certificates, and organise them into host groups and netgroups.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Hosts** `ipahost` **Host groups** `ipahostgroup` **Netgroups** `ipanetgroup` **Add host (playbook)** playbook `host.add-host` **Delete host (playbook)** playbook `host.delete-host` **Disable host (playbook)** playbook `host.disable-host` **Ensure host with randompassword (playbook)** playbook `host.ensure_host_with_randompassword` **Host member allow create keytab absent (playbook)** playbook `host.host-member-allow_create_keytab-absent` **Host member allow create keytab present (playbook)** playbook `host.host-member-allow_create_keytab-present` **Host member allow retrieve keytab absent (playbook)** playbook `host.host-member-allow_retrieve_keytab-absent` **Host member allow retrieve keytab present (playbook)** playbook `host.host-member-allow_retrieve_keytab-present` **Host member certificate absent (playbook)** playbook `host.host-member-certificate-absent` **Host member certificate present (playbook)** playbook `host.host-member-certificate-present` **Host member ipaddresses absent (playbook)** playbook `host.host-member-ipaddresses-absent` **Host member ipaddresses present (playbook)** playbook `host.host-member-ipaddresses-present` **Host member managedby host absent (playbook)** playbook `host.host-member-managedby_host-absent` **Host member managedby host present (playbook)** playbook `host.host-member-managedby_host-present` **Host member principal absent (playbook)** playbook `host.host-member-principal-absent` **Host member principal present (playbook)** playbook `host.host-member-principal-present` **Host present (playbook)** playbook `host.host-present` **Host present with allow create keytab (playbook)** playbook `host.host-present-with-allow_create_keytab` **Host present with allow retrieve keytab (playbook)** playbook `host.host-present-with-allow_retrieve_keytab` **Host present with certificate (playbook)** playbook `host.host-present-with-certificate` **Host present with managedby host (playbook)** playbook `host.host-present-with-managedby_host` **Host present with principal (playbook)** playbook `host.host-present-with-principal` **Host present with randompassword (playbook)** playbook `host.host-present-with-randompassword` **Host present with several IP addresses (playbook)** playbook `host.host-present-with-several-ip-addresses` **Hosts member certificate absent (playbook)** playbook `host.hosts-member-certificate-absent` **Hosts member certificate present (playbook)** playbook `host.hosts-member-certificate-present` **Hosts member managedby host absent (playbook)** playbook `host.hosts-member-managedby_host-absent` **Hosts member managedby host present (playbook)** playbook `host.hosts-member-managedby_host-present` **Hosts member principal absent (playbook)** playbook `host.hosts-member-principal-absent` **Hosts member principal present (playbook)** playbook `host.hosts-member-principal-present` **Hosts present with certificate (playbook)** playbook `host.hosts-present-with-certificate` **Hosts present with managedby host (playbook)** playbook `host.hosts-present-with-managedby_host` **Hosts present with randompasswords (playbook)** playbook `host.hosts-present-with-randompasswords` **Ensure hostgroup is absent (playbook)** playbook `hostgroup.ensure-hostgroup-is-absent` **Ensure hostgroup is present (playbook)** playbook `hostgroup.ensure-hostgroup-is-present` **Ensure hosts and hostgroups are absent in hostgroup (playbook)** playbook `hostgroup.ensure-hosts-and-hostgroups-are-absent-in-hostgroup` **Ensure hosts and hostgroups are present in hostgroup (playbook)** playbook `hostgroup.ensure-hosts-and-hostgroups-are-present-in-hostgroup` **Rename hostgroup (playbook)** playbook `hostgroup.rename-hostgroup` **Netgroup absent (playbook)** playbook `netgroup.netgroup-absent` **Netgroup member absent (playbook)** playbook `netgroup.netgroup-member-absent` **Netgroup member present (playbook)** playbook `netgroup.netgroup-member-present` **Netgroup present (playbook)** playbook `netgroup.netgroup-present`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Automate group membership with automember rules

Description	Define automember rules and default groups that place new users and hosts into groups automatically, and rebuild memberships.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Automember rules** `ipaautomember` **Automember default group not set (playbook)** playbook `automember.automember-default-group-not-set` **Automember default group set (playbook)** playbook `automember.automember-default-group-set` **Automember default hostgroup not set (playbook)** playbook `automember.automember-default-hostgroup-not-set` **Automember default hostgroup set (playbook)** playbook `automember.automember-default-hostgroup-set` **Automember group absent (playbook)** playbook `automember.automember-group-absent` **Automember group membership all users rebuilt (playbook)** playbook `automember.automember-group-membership-all-users-rebuilt` **Automember group membership users rebuilt (playbook)** playbook `automember.automember-group-membership-users-rebuilt` **Automember group orphans removed (playbook)** playbook `automember.automember-group-orphans-removed` **Automember group present (playbook)** playbook `automember.automember-group-present` **Automember hostgroup absent (playbook)** playbook `automember.automember-hostgroup-absent` **Automember hostgroup membership all hosts rebuilt (playbook)** playbook `automember.automember-hostgroup-membership-all-hosts-rebuilt` **Automember hostgroup membership hosts rebuilt (playbook)** playbook `automember.automember-hostgroup-membership-hosts-rebuilt` **Automember hostgroup orphans removed (playbook)** playbook `automember.automember-hostgroup-orphans-removed` **Automember hostgroup present (playbook)** playbook `automember.automember-hostgroup-present` **Automember hostgroup rule absent (playbook)** playbook `automember.automember-hostgroup-rule-absent` **Automember hostgroup rule present (playbook)** playbook `automember.automember-hostgroup-rule-present`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Control host-based access (HBAC)

Description	Create HBAC rules, services and service groups that decide which users may reach which hosts and services.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**HBAC rules** `ipahbacrule` **HBAC services** `ipahbacsvc` **HBAC service groups** `ipahbacsvcgroup` **Ensure hbarule allhosts absent (playbook)** playbook `hbacrule.ensure-hbarule-allhosts-absent` **Ensure hbarule allhosts disabled (playbook)** playbook `hbacrule.ensure-hbarule-allhosts-disabled` **Ensure hbarule allhosts enabled (playbook)** playbook `hbacrule.ensure-hbarule-allhosts-enabled` **Ensure hbarule allhosts present (playbook)** playbook `hbacrule.ensure-hbarule-allhosts-present` **Ensure hbarule allhosts server member absent (playbook)** playbook `hbacrule.ensure-hbarule-allhosts-server-member-absent` **Ensure hbarule allhosts server member present (playbook)** playbook `hbacrule.ensure-hbarule-allhosts-server-member-present` **Ensure hbacsvc absent (playbook)** playbook `hbacsvc.ensure-hbacsvc-absent` **Ensure hbacsvc present (playbook)** playbook `hbacsvc.ensure-hbacsvc-present` **Ensure hbacsvcgroup absent (playbook)** playbook `hbacsvcgroup.ensure-hbacsvcgroup-absent` **Ensure hbacsvcgroup member absent (playbook)** playbook `hbacsvcgroup.ensure-hbacsvcgroup-member-absent` **Ensure hbacsvcgroup member present (playbook)** playbook `hbacsvcgroup.ensure-hbacsvcgroup-member-present` **Ensure hbacsvcgroup present (playbook)** playbook `hbacsvcgroup.ensure-hbacsvcgroup-present`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Manage sudo rules and commands

Description	Define sudo commands, command groups and rules with their users, hosts and run-as settings centrally.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)

Key content	**Sudo commands** `ipasudocmd` **Sudo command groups** `ipasudocmdgroup` **Sudo rules** `ipasudorule` **Ensure sudocmd is absent (playbook)** playbook `sudocmd.ensure-sudocmd-is-absent` **Ensure sudocmd is present (playbook)** playbook `sudocmd.ensure-sudocmd-is-present` **Ensure sudocmd are absent in sudocmdgroup (playbook)** playbook `sudocmdgroup.ensure-sudocmd-are-absent-in-sudocmdgroup` **Ensure sudocmd are present in sudocmdgroup (playbook)** playbook `sudocmdgroup.ensure-sudocmd-are-present-in-sudocmdgroup` **Ensure sudocmdgroup is absent (playbook)** playbook `sudocmdgroup.ensure-sudocmdgroup-is-absent` **Ensure sudocmdgroup is present (playbook)** playbook `sudocmdgroup.ensure-sudocmdgroup-is-present` **Ensure sudorule does not have sudooption (playbook)** playbook `sudorule.ensure-sudorule-does-not-have-sudooption` **Ensure sudorule has sudooption (playbook)** playbook `sudorule.ensure-sudorule-has-sudooption` **Ensure sudorule host member is absent (playbook)** playbook `sudorule.ensure-sudorule-host-member-is-absent` **Ensure sudorule host member is present (playbook)** playbook `sudorule.ensure-sudorule-host-member-is-present` **Ensure sudorule hostgroup member is absent (playbook)** playbook `sudorule.ensure-sudorule-hostgroup-member-is-absent` **Ensure sudorule hostgroup member is present (playbook)** playbook `sudorule.ensure-sudorule-hostgroup-member-is-present` **Ensure sudorule hostmask member is absent (playbook)** playbook `sudorule.ensure-sudorule-hostmask-member-is-absent` **Ensure sudorule hostmask member is present (playbook)** playbook `sudorule.ensure-sudorule-hostmask-member-is-present` **Ensure sudorule is absent (playbook)** playbook `sudorule.ensure-sudorule-is-absent` **Ensure sudorule is disabled (playbook)** playbook `sudorule.ensure-sudorule-is-disabled` **Ensure sudorule is enabled (playbook)** playbook `sudorule.ensure-sudorule-is-enabled` **Ensure sudorule is present (playbook)** playbook `sudorule.ensure-sudorule-is-present` **Ensure sudorule is present with order (playbook)** playbook `sudorule.ensure-sudorule-is-present-with-order` **Ensure sudorule runasuser group is absent (playbook)** playbook `sudorule.ensure-sudorule-runasuser-group-is-absent` **Ensure sudorule runasuser group is present (playbook)** playbook `sudorule.ensure-sudorule-runasuser-group-is-present` **Ensure sudorule runasuser is absent (playbook)** playbook `sudorule.ensure-sudorule-runasuser-is-absent` **Ensure sudorule runasuser is present (playbook)** playbook `sudorule.ensure-sudorule-runasuser-is-present` **Ensure sudorule sudocmd is absent (playbook)** playbook `sudorule.ensure-sudorule-sudocmd-is-absent` **Ensure sudorule sudocmd is present (playbook)** playbook `sudorule.ensure-sudorule-sudocmd-is-present`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Delegate administration with roles and permissions

Description	Build role-based access control from permissions, privileges, roles, delegations and self-service rules.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Delegations** `ipadelegation` **Permissions** `ipapermission` **Privileges** `ipaprivilege` **Roles** `iparole` **Self-service permissions** `ipaselfservice` **Delegation absent (playbook)** playbook `delegation.delegation-absent` **Delegation member absent (playbook)** playbook `delegation.delegation-member-absent` **Delegation member present (playbook)** playbook `delegation.delegation-member-present` **Delegation present (playbook)** playbook `delegation.delegation-present` **Permission absent (playbook)** playbook `permission.permission-absent` **Permission allow read employeenum (playbook)** playbook `permission.permission-allow-read-employeenum` **Permission member absent (playbook)** playbook `permission.permission-member-absent` **Permission member present (playbook)** playbook `permission.permission-member-present` **Permission present (playbook)** playbook `permission.permission-present` **Permission renamed (playbook)** playbook `permission.permission-renamed` **Privilege absent (playbook)** playbook `privilege.privilege-absent` **Privilege member absent (playbook)** playbook `privilege.privilege-member-absent` **Privilege member present (playbook)** playbook `privilege.privilege-member-present` **Privilege present (playbook)** playbook `privilege.privilege-present` **Role is absent (playbook)** playbook `role.role-is-absent` **Role is present (playbook)** playbook `role.role-is-present` **Role member group absent (playbook)** playbook `role.role-member-group-absent` **Role member group present (playbook)** playbook `role.role-member-group-present` **Role member host absent (playbook)** playbook `role.role-member-host-absent` **Role member host present (playbook)** playbook `role.role-member-host-present` **Role member hostgroup absent (playbook)** playbook `role.role-member-hostgroup-absent` **Role member hostgroup present (playbook)** playbook `role.role-member-hostgroup-present` **Role member privilege absent (playbook)** playbook `role.role-member-privilege-absent` **Role member privilege present (playbook)** playbook `role.role-member-privilege-present` **Role member service absent (playbook)** playbook `role.role-member-service-absent` **Role member service present (playbook)** playbook `role.role-member-service-present` **Role member user absent (playbook)** playbook `role.role-member-user-absent` **Role member user present (playbook)** playbook `role.role-member-user-present` **Role members absent (playbook)** playbook `role.role-members-absent` **Role members present (playbook)** playbook `role.role-members-present` **Role rename (playbook)** playbook `role.role-rename` **Selfservice absent (playbook)** playbook `selfservice.selfservice-absent` **Selfservice member absent (playbook)** playbook `selfservice.selfservice-member-absent` **Selfservice member present (playbook)** playbook `selfservice.selfservice-member-present` **Selfservice present (playbook)** playbook `selfservice.selfservice-present`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Manage Kerberos services and delegation

Description	Register services and configure constrained delegation rules and targets.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)

Key content	**Services** `ipaservice` **Service delegation rules** `ipaservicedelegationrule` **Service delegation targets** `ipaservicedelegationtarget` **Service host is absent (playbook)** playbook `service.service-host-is-absent` **Service host is present (playbook)** playbook `service.service-host-is-present` **Service is absent (playbook)** playbook `service.service-is-absent` **Service is disabled (playbook)** playbook `service.service-is-disabled` **Service is present (playbook)** playbook `service.service-is-present` **Service is present with all attributes (playbook)** playbook `service.service-is-present-with-all-attributes` **Service is present with host force (playbook)** playbook `service.service-is-present-with-host-force` **Service is present without host object (playbook)** playbook `service.service-is-present-without-host-object` **Service member allow create keytab absent (playbook)** playbook `service.service-member-allow_create_keytab-absent` **Service member allow create keytab present (playbook)** playbook `service.service-member-allow_create_keytab-present` **Service member allow retrieve keytab absent (playbook)** playbook `service.service-member-allow_retrieve_keytab-absent` **Service member allow retrieve keytab present (playbook)** playbook `service.service-member-allow_retrieve_keytab-present` **Service member certificate absent (playbook)** playbook `service.service-member-certificate-absent` **Service member certificate present (playbook)** playbook `service.service-member-certificate-present` **Service member principal absent (playbook)** playbook `service.service-member-principal-absent` **Service member principal present (playbook)** playbook `service.service-member-principal-present` **Servicedelegationrule absent (playbook)** playbook `servicedelegationrule.servicedelegationrule-absent` **Servicedelegationrule present (playbook)** playbook `servicedelegationrule.servicedelegationrule-present` **Servicedelegationrule principal member absent (playbook)** playbook `servicedelegationrule.servicedelegationrule-principal-member-absent` **Servicedelegationrule principal member present (playbook)** playbook `servicedelegationrule.servicedelegationrule-principal-member-present` **Servicedelegationrule target member absent (playbook)** playbook `servicedelegationrule.servicedelegationrule-target-member-absent` **Servicedelegationrule target member present (playbook)** playbook `servicedelegationrule.servicedelegationrule-target-member-present` **Servicedelegationtarget absent (playbook)** playbook `servicedelegationtarget.servicedelegationtarget-absent` **Servicedelegationtarget member absent (playbook)** playbook `servicedelegationtarget.servicedelegationtarget-member-absent` **Servicedelegationtarget member present (playbook)** playbook `servicedelegationtarget.servicedelegationtarget-member-present` **Servicedelegationtarget present (playbook)** playbook `servicedelegationtarget.servicedelegationtarget-present`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Request and manage certificates

Description	Request, retrieve, hold, release and revoke certificates for users, hosts and services.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Certificates** `ipacert` **Cert hold (playbook)** playbook `cert.cert-hold` **Cert release (playbook)** playbook `cert.cert-release` **Cert request host (playbook)** playbook `cert.cert-request-host` **Cert request service (playbook)** playbook `cert.cert-request-service` **Cert request user (playbook)** playbook `cert.cert-request-user` **Cert retrieve (playbook)** playbook `cert.cert-retrieve` **Cert revoke (playbook)** playbook `cert.cert-revoke`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Manage DNS zones and records

Description	Configure global DNS options and forwarders, DNS zones, forward zones and DNS records.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)

Key content	**Global DNS configuration** `ipadnsconfig` **DNS forward zones** `ipadnsforwardzone` **DNS records** `ipadnsrecord` **DNS zones** `ipadnszone` **Disable global forwarders (playbook)** playbook `dnsconfig.disable-global-forwarders` **Disallow reverse sync (playbook)** playbook `dnsconfig.disallow-reverse-sync` **Forwarders absent (playbook)** playbook `dnsconfig.forwarders-absent` **Forwarders present (playbook)** playbook `dnsconfig.forwarders-present` **Set configuration (playbook)** playbook `dnsconfig.set-configuration` **Ensure dnsforwardzone is absent (playbook)** playbook `dnsforwardzone.ensure-dnsforwardzone-is-absent` **Ensure dnsforwardzone is present (playbook)** playbook `dnsforwardzone.ensure-dnsforwardzone-is-present` **Ensure dnsforwardzone with forwarder port (playbook)** playbook `dnsforwardzone.ensure-dnsforwardzone-with-forwarder-port` **Ensure A and AAAA records are absent (playbook)** playbook `dnsrecord.ensure-A-and-AAAA-records-are-absent` **Ensure A and AAAA records are present (playbook)** playbook `dnsrecord.ensure-A-and-AAAA-records-are-present` **Ensure CNAME record is absent (playbook)** playbook `dnsrecord.ensure-CNAME-record-is-absent` **Ensure CNAME record is present (playbook)** playbook `dnsrecord.ensure-CNAME-record-is-present` **Ensure MX record is present (playbook)** playbook `dnsrecord.ensure-MX-record-is-present` **Ensure PTR record is present (playbook)** playbook `dnsrecord.ensure-PTR-record-is-present` **Ensure SRV record is present (playbook)** playbook `dnsrecord.ensure-SRV-record-is-present` **Ensure SSHFP record is present (playbook)** playbook `dnsrecord.ensure-SSHFP-record-is-present` **Ensure TLSA record is present (playbook)** playbook `dnsrecord.ensure-TLSA-record-is-present` **Ensure TXT record is present (playbook)** playbook `dnsrecord.ensure-TXT-record-is-present` **Ensure URI record is present (playbook)** playbook `dnsrecord.ensure-URI-record-is-present` **Ensure dnsrecord is absent (playbook)** playbook `dnsrecord.ensure-dnsrecord-is-absent` **Ensure dnsrecord is present (playbook)** playbook `dnsrecord.ensure-dnsrecord-is-present` **Ensure dnsrecord with reverse is present (playbook)** playbook `dnsrecord.ensure-dnsrecord-with-reverse-is-present` **Ensure multiple A records are present (playbook)** playbook `dnsrecord.ensure-multiple-A-records-are-present` **Ensure presence multiple records (playbook)** playbook `dnsrecord.ensure-presence-multiple-records` **Disable zone forwarders (playbook)** playbook `dnszone.disable-zone-forwarders` **Dnszone absent (playbook)** playbook `dnszone.dnszone-absent` **Dnszone all params (playbook)** playbook `dnszone.dnszone-all-params` **Dnszone disable (playbook)** playbook `dnszone.dnszone-disable` **Dnszone enable (playbook)** playbook `dnszone.dnszone-enable` **Dnszone present (playbook)** playbook `dnszone.dnszone-present` **Dnszone reverse from IP (playbook)** playbook `dnszone.dnszone-reverse-from-ip`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Manage automount maps and locations

Description	Define automount locations, maps and keys for NFS and similar shares.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Automount keys** `ipaautomountkey` **Automount locations** `ipaautomountlocation` **Automount maps** `ipaautomountmap` **Automount location absent (playbook)** playbook `automount.automount-location-absent` **Automount location present (playbook)** playbook `automount.automount-location-present` **Automount map absent (playbook)** playbook `automount.automount-map-absent` **Automount map indirect map (playbook)** playbook `automount.automount-map-indirect-map` **Automount map present (playbook)** playbook `automount.automount-map-present` **Automountkey present (playbook)** playbook `automount.automountkey-present` **Automountkey renamed (playbook)** playbook `automount.automountkey-renamed` **Automoutkey absent (playbook)** playbook `automount.automoutkey-absent`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Manage ID views, ranges, trusts and external IdPs

Description	Configure ID views and overrides, ID ranges, AD domain trusts, external identity providers and passkey authentication.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**ID overrides for groups** `ipaidoverridegroup` **ID overrides for users** `ipaidoverrideuser` **External identity providers** `ipaidp` **ID ranges** `ipaidrange` **ID views** `ipaidview` **Passkey configuration** `ipapasskeyconfig` **Domain trusts** `ipatrust` **Idoverridegroup absent (playbook)** playbook `idoverridegroup.idoverridegroup-absent` **Idoverridegroup present (playbook)** playbook `idoverridegroup.idoverridegroup-present` **Idoverrideuser absent (playbook)** playbook `idoverrideuser.idoverrideuser-absent` **Idoverrideuser certificate absent (playbook)** playbook `idoverrideuser.idoverrideuser-certificate-absent` **Idoverrideuser certificate present (playbook)** playbook `idoverrideuser.idoverrideuser-certificate-present` **Idoverrideuser present (playbook)** playbook `idoverrideuser.idoverrideuser-present` **Idp absent (playbook)** playbook `idp.idp-absent` **Idp present (playbook)** playbook `idp.idp-present` **Idrange absent (playbook)** playbook `idrange.idrange-absent` **Idrange AD posix present (playbook)** playbook `idrange.idrange-ad-posix-present` **Idrange AD present (playbook)** playbook `idrange.idrange-ad-present` **Idrange present (playbook)** playbook `idrange.idrange-present` **Idview absent (playbook)** playbook `idview.idview-absent` **Idview host applied (playbook)** playbook `idview.idview-host-applied` **Idview host unapplied (playbook)** playbook `idview.idview-host-unapplied` **Idview present (playbook)** playbook `idview.idview-present` **Passkeyconfig present (playbook)** playbook `passkeyconfig.passkeyconfig-present` **Passkeyconfig retrieve (playbook)** playbook `passkeyconfig.passkeyconfig-retrieve` **Add trust (playbook)** playbook `trust.add-trust` **Del trust (playbook)** playbook `trust.del-trust`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Store secrets in vaults

Description	Create standard, symmetric and asymmetric vaults and archive, retrieve and share secret data with their owners and members.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Vaults** `ipavault` **Change password symmetric vault (playbook)** playbook `vault.change-password-symmetric-vault` **Data archive in asymmetric vault (playbook)** playbook `vault.data-archive-in-asymmetric-vault` **Data archive in symmetric vault (playbook)** playbook `vault.data-archive-in-symmetric-vault` **Ensure asymetric vault is absent (playbook)** playbook `vault.ensure-asymetric-vault-is-absent` **Ensure asymetric vault is present (playbook)** playbook `vault.ensure-asymetric-vault-is-present` **Ensure service vault is absent (playbook)** playbook `vault.ensure-service-vault-is-absent` **Ensure service vault is present (playbook)** playbook `vault.ensure-service-vault-is-present` **Ensure shared vault is absent (playbook)** playbook `vault.ensure-shared-vault-is-absent` **Ensure shared vault is present (playbook)** playbook `vault.ensure-shared-vault-is-present` **Ensure standard vault is absent (playbook)** playbook `vault.ensure-standard-vault-is-absent` **Ensure standard vault is present (playbook)** playbook `vault.ensure-standard-vault-is-present` **Ensure symetric vault is absent (playbook)** playbook `vault.ensure-symetric-vault-is-absent` **Ensure symetric vault is present (playbook)** playbook `vault.ensure-symetric-vault-is-present` **Ensure vault is present with members (playbook)** playbook `vault.ensure-vault-is-present-with-members` **Ensure vault member group is absent (playbook)** playbook `vault.ensure-vault-member-group-is-absent` **Ensure vault member group is present (playbook)** playbook `vault.ensure-vault-member-group-is-present` **Ensure vault member user is absent (playbook)** playbook `vault.ensure-vault-member-user-is-absent` **Ensure vault member user is present (playbook)** playbook `vault.ensure-vault-member-user-is-present` **Ensure vault owner is absent (playbook)** playbook `vault.ensure-vault-owner-is-absent` **Ensure vault owner is present (playbook)** playbook `vault.ensure-vault-owner-is-present` **Retrive data asymmetric vault (playbook)** playbook `vault.retrive-data-asymmetric-vault` **Retrive data symmetric vault (playbook)** playbook `vault.retrive-data-symmetric-vault` **Vault is present with password file (playbook)** playbook `vault.vault-is-present-with-password-file` **Vault is present with public key file (playbook)** playbook `vault.vault-is-present-with-public-key-file`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Manage IdM topology, servers and global configuration

Description	Adjust global IPA settings, servers and locations, hide servers or set service weights, and manage replication topology segments and suffixes.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Global IPA configuration** `ipaconfig` **Locations** `ipalocation` **IdM servers** `ipaserver` **Topology segments** `ipatopologysegment` **Topology suffixes** `ipatopologysuffix` **Change IPA domain netbios name (playbook)** playbook `config.change-ipa-domain-netbios-name` **Generate users groups SIDs (playbook)** playbook `config.generate-users-groups-sids` **Retrieve config (playbook)** playbook `config.retrieve-config` **Set ca renewal master server (playbook)** playbook `config.set-ca-renewal-master-server` **Location absent (playbook)** playbook `location.location-absent` **Location present (playbook)** playbook `location.location-present` **Server absent (playbook)** playbook `server.server-absent` **Server absent continue (playbook)** playbook `server.server-absent-continue` **Server absent force (playbook)** playbook `server.server-absent-force` **Server absent ignore last of role (playbook)** playbook `server.server-absent-ignore_last_of_role` **Server absent ignore topology disconnect (playbook)** playbook `server.server-absent-ignore_topology_disconnect` **Server hidden (playbook)** playbook `server.server-hidden` **Server location (playbook)** playbook `server.server-location` **Server no location (playbook)** playbook `server.server-no-location` **Server no service weight (playbook)** playbook `server.server-no-service-weight` **Server not hidden (playbook)** playbook `server.server-not-hidden` **Server present (playbook)** playbook `server.server-present` **Server service weight (playbook)** playbook `server.server-service-weight` **Add topologysegment (playbook)** playbook `topology.add-topologysegment` **Add topologysegments (playbook)** playbook `topology.add-topologysegments` **Check topologysegments (playbook)** playbook `topology.check-topologysegments` **Delete topologysegment (playbook)** playbook `topology.delete-topologysegment` **Delete topologysegments (playbook)** playbook `topology.delete-topologysegments` **Reinitialize topologysegment (playbook)** playbook `topology.reinitialize-topologysegment` **Verify topologysuffix (playbook)** playbook `topology.verify-topologysuffix`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Install and uninstall IdM servers, replicas and clients

Description	Deploy IdM servers, replicas and enrolled clients, or whole clusters, and remove them again.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)

Key content	**Install client (playbook)** playbook `install-client` **Install cluster (playbook)** playbook `install-cluster` **Install replica (playbook)** playbook `install-replica` **Install server (playbook)** playbook `install-server` **Uninstall client (playbook)** playbook `uninstall-client` **Uninstall cluster (playbook)** playbook `uninstall-cluster` **Uninstall replica (playbook)** playbook `uninstall-replica` **Uninstall server (playbook)** playbook `uninstall-server` **Client enrollment role** role `ipaclient` **Replica deployment role** role `ipareplica` **Server deployment role** role `ipaserver`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Enable smart card authentication

Description	Configure IdM servers, replicas and clients for smart card login.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Install smartcard clients (playbook)** playbook `install-smartcard-clients` **Install smartcard replicas (playbook)** playbook `install-smartcard-replicas` **Install smartcard server (playbook)** playbook `install-smartcard-server` **Install smartcard servers (playbook)** playbook `install-smartcard-servers` **Smart card client role** role `ipasmartcard_client` **Smart card server role** role `ipasmartcard_server`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Back up and restore IdM servers

Description	Back up an IdM server locally or to the controller, copy or remove backups, and restore a server from a backup.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**Backup server (playbook)** playbook `backup-server` **Backup server to controller (playbook)** playbook `backup-server-to-controller` **Copy all backups from server (playbook)** playbook `copy-all-backups-from-server` **Copy backup from controller (playbook)** playbook `copy-backup-from-controller` **Copy backup from server (playbook)** playbook `copy-backup-from-server` **Remove all backups from server (playbook)** playbook `remove-all-backups-from-server` **Remove backup from server (playbook)** playbook `remove-backup-from-server` **Restore server (playbook)** playbook `restore-server` **Restore server from controller (playbook)** playbook `restore-server-from-controller` **Backup and restore role** role `ipabackup`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Use Case: Build dynamic inventory from IdM

Description	Compile an Ansible inventory from the hosts and host groups of an IPA domain.
Collection	`redhat.rhel_idm` (Certified, Red Hat, v1.16.0, updated 2026-02-10)
Key content	**FreeIPA dynamic inventory** inventory `freeipa`
Notes	• Modules and playbooks target a FreeIPA / Red Hat IdM server; the playbooks are ready-to-run examples for each module.

Red Hat Trusted Profile Analyzer `redhat.trusted_profile_analyzer`

Certified Red Hat · version 3.1.1 · updated 2026-10-13 · 0 modules → 1 use cases

Use Case: Deploy Trusted Profile Analyzer

Description	Configure Trusted Profile Analyzer on a single managed node.
Collection	`redhat.trusted_profile_analyzer` (Certified, Red Hat, v3.1.1, updated 2026-10-13)
Key content	**Single-node deployment** role `tpa_single_node`

Splunk Enterprise Security `splunk.es`

Certified Red Hat · version 6.0.1 · updated 2026-07-13 · 17 modules → 2 use cases

Use Case: Manage detection content and data inputs

Description	Manage correlation searches, adaptive response notable events and monitor, TCP and UDP data inputs.
Collection	`splunk.es` (Certified, Red Hat, v6.0.1, updated 2026-07-13)
Key content	**Correlation searches** `splunk_correlation_searches` **Correlation search information** `splunk_correlation_search_info` **Adaptive response notable events** `splunk_adaptive_response_notable_events` **Monitor data inputs** `splunk_data_inputs_monitor` **TCP and UDP data inputs** `splunk_data_inputs_network`

Use Case: Investigate and respond to findings

Description	Manage findings, investigations and investigation types, notes, response plans and their execution.
Collection	`splunk.es` (Certified, Red Hat, v6.0.1, updated 2026-07-13)
Key content	**Findings** `splunk_finding`, `splunk_finding_info` **Investigations** `splunk_investigation`, `splunk_investigation_info` **Investigation types** `splunk_investigation_type`, `splunk_investigation_type_info` **Notes** `splunk_notes`, `splunk_notes_info` **Response plans** `splunk_response_plan`, `splunk_response_plan_info` **Response plan execution** `splunk_response_plan_execution`, `splunk_response_plan_execution_info`

Open Policy Agent `styra.opa`

Certified Styra · version 1.1.1 · updated 2024-04-18 · 0 modules → 1 use cases

Use Case: Deploy an OPA policy decision point on Kubernetes

Description	Deploy an OPA-based policy decision point.
Collection	`styra.opa` (Certified, Styra, v1.1.1, updated 2024-04-18)
Key content	**Kubernetes policy decision point** role `k8s_pdp`

Thales CipherTrust Manager `thalesgroup.ciphertrust`

Certified · version 1.0.1 · updated 2024-10-22 · 33 modules → 5 use cases

Use Case: Manage encryption keys and cloud key management

Description	Create and update keys in the CipherTrust vault, run key operations, and try cloud key management for Azure and GCP.
Collection	`thalesgroup.ciphertrust` (Certified, , v1.0.1, updated 2024-10-22)
Key content	**Keys** `vault_keys2_save` **Key operations** `vault_keys2_op` **Key management sample** playbook `keyMgmtSample` **Key operations sample** playbook `keyOpsSample` **Azure key management sample** playbook `cckm_az` **GCP key management sample** playbook `cckm_gcp`

Use Case: Protect files and volumes with Transparent Encryption

Description	Configure CTE clients and client groups, CSI storage groups, policies and the process, resource, signature and user sets that govern encryption and access, and deploy CTE agents.
Collection	`thalesgroup.ciphertrust` (Certified, , v1.0.1, updated 2024-10-22)

Key content	**CTE clients** `cte_client` **CTE client groups** `cte_client_group` **CSI storage groups** `cte_csi_storage_group` **CTE policies** `cte_policy_save` **Process sets** `cte_process_set` **Resource sets** `cte_resource_set` **Signature sets** `cte_signature_set` **User sets** `cte_user_set` **CTE for Linux and Unix role** role `cte4u` **CTE for Kubernetes role** role `cte4k8s` **CTE setup sample** playbook `setupCTESample`

Use Case: Protect application data with Data Protection Gateway and CRDP

Description	Configure DPG access, protection and execution policies, character sets, masking formats, client profiles and user sets, and deploy DPG and CipherTrust RDP.
Collection	`thalesgroup.ciphertrust` (Certified, , v1.0.1, updated 2024-10-22)
Key content	**DPG access policies** `dpg_access_policy_save` **Character sets** `dpg_character_set_save` **Client profiles** `dpg_client_profile_save` **Masking formats** `dpg_masking_format_save` **DPG policies** `dpg_policy_save` **Protection policies** `dpg_protection_policy_save` **DPG user sets** `dpg_user_set_save` **DPG role** role `dpg` **CRDP role** role `crdp` **DPG setup sample** playbook `setupDPGSample` **DPG removal sample** playbook `deleteDPGSample`

Use Case: Administer domains, users and groups

Description	Create domains, users and groups, change group membership, and look up or delete resources by name or ID.
Collection	`thalesgroup.ciphertrust` (Certified, , v1.0.1, updated 2024-10-22)
Key content	**Domains** `domain_save` **Users** `usermgmt_users_save` **Groups** `group_save` **Group membership** `group_add_remove_object` **Resource ID lookup** `cm_resource_get_id_from_name` **Resource deletion** `cm_resource_delete` **User management sample** playbook `userMgmtSample` **Group management sample** playbook `groupMgmtSample`

Use Case: Deploy and operate CipherTrust Manager

Description	Create and join node clusters, local certificate authorities and registration tokens, manage services, interfaces and licences, including trial licences.
Collection	`thalesgroup.ciphertrust` (Certified, , v1.0.1, updated 2024-10-22)
Key content	**Node clusters** `cm_cluster` **Local certificate authorities** `cm_certificate_authority` **Registration tokens** `cm_regtoken` **Services** `cm_services` **Interfaces** `interface_save` **Interface actions** `interface_actions` **Licences** `license_create` **Trial licence info** `license_trial_get` **Trial licence activation** `license_trial_action` **Licence lock data** `licensing_lockdata_get` **Cluster role playbook** playbook `cluster` **Interface management sample** playbook `interfaceMgmtSample` **Licence management sample** playbook `licenseMgmtSample`

Trend Micro Deep Security `trendmicro.deepsec`

Certified Red Hat · version 4.0.0 · updated 2024-06-12 · 9 modules → 2 use cases

Use Case: Manage protection rules

Description	Manage anti-malware, firewall, integrity monitoring, intrusion prevention and log inspection rules.

Collection	`trendmicro.deepsec` (Certified, Red Hat, v4.0.0, updated 2024-06-12)
Key content	**Anti-malware rules** `deepsec_anti_malwares` **Firewall rules** `deepsec_firewall_rules` **Integrity monitoring rules** `deepsec_integrity_monitoring_rules` **Intrusion prevention rules** `deepsec_intrusion_prevention_rules` **Log inspection rules** `deepsec_log_inspection_rules`

Use Case: Administer Deep Security and view hosts

Description	Create API keys, configure syslog and system settings and get information about hosts.
Collection	`trendmicro.deepsec` (Certified, Red Hat, v4.0.0, updated 2024-06-12)
Key content	**API keys** `deepsec_apikey` **Syslog configuration** `deepsec_syslog` **System settings** `deepsec_system_settings` **Hosts** `deepsec_hosts_info`

CyberArk Certificate Manager (Venafi) `venafi.machine_identity`

Certified Venafi · version 1.1.1 · updated 2025-09-12 · 5 modules → 2 use cases

Use Case: Manage TLS certificates and policies

Description	Request, retrieve and revoke certificates and create or delete policies and certificate issuing templates.
Collection	`venafi.machine_identity` (Certified, Venafi, v1.1.1, updated 2025-09-12)
Key content	**Certificates** `venafi_certificate` **Certificate revocation** `venafi_certificate_revoke` **Policies** `venafi_policy` **Certificate management** role `certificate` **Policy management** role `policy`

Use Case: Manage SSH certificates

Description	Request SSH certificates and retrieve SSH certificate authority public keys and principals.
Collection	`venafi.machine_identity` (Certified, Venafi, v1.1.1, updated 2025-09-12)
Key content	**SSH certificates** `venafi_ssh_certificate` **SSH certificate authorities** `venafi_ssh_ca` **SSH certificate management** role `ssh_certificate` **SSH CA configuration** role `ssh_ca`

Virsec Security Platform `virsec.vsp`

Certified Virsec Systems · version 1.0.2 · updated 2022-11-11 · 0 modules → 1 use cases

Use Case: Install the Virsec Probe

Description	Install the Virsec Probe on managed hosts so they can be monitored by the Virsec Security Platform.
Collection	`virsec.vsp` (Certified, Virsec Systems, v1.0.2, updated 2022-11-11)
Key content	**Virsec Probe installation** role `vsp`

Zscaler Internet Access (ZIA) `zscaler.ziacloud`

Certified Zscaler · version 2.2.4 · updated 2026-06-02 · 156 modules → 9 use cases

Use Case: Control web access with URL filtering and file type rules

Description	Manage URL filtering rules and custom categories, file type control, browser control, FTP control and custom file types.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)

Key content	**URL filtering rules** `zia_url_filtering_rules` **URL filtering rule queries** `zia_url_filtering_rule_info` **URL categories** `zia_url_categories`, `zia_url_categories_info` **URL filtering and cloud app settings** `zia_url_filtering_and_cloud_app_settings`, `zia_url_filtering_and_cloud_app_settings_info` **File type control rules** `zia_file_type_control_rules`, `zia_file_type_control_rules_info` **File type categories** `zia_file_type_categories_info` **Custom file types** `zia_custom_file_types`, `zia_custom_file_types_info` **Browser control policy** `zia_browser_control_policy`, `zia_browser_control_policy_info` **Supported browser versions** `zia_browser_control_supported_versions_info` **FTP control policy** `zia_ftp_control_policy`, `zia_ftp_control_policy_info` **End user notifications** `zia_end_user_notification`, `zia_end_user_notification_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Control SaaS and cloud application usage

Description	Manage cloud app control rules and application instances, risk profiles, tenant restrictions and bandwidth control.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**Cloud app control rules** `zia_cloud_app_control_rules`, `zia_cloud_app_control_rules_info` **Cloud app control rule actions** `zia_cloud_app_control_rule_actions_info` **Cloud applications** `zia_cloud_applications_info` **Cloud application instances** `zia_cloud_application_instances`, `zia_cloud_application_instances_info` **Risk profiles** `zia_risk_profiles`, `zia_risk_profiles_info` **Tenant restriction profiles** `zia_tenant_restriction_profile`, `zia_tenant_restriction_profile_info` **Bandwidth control rules** `zia_bandwidth_control_rules`, `zia_bandwidth_control_rules_info` **Bandwidth classes** `zia_bandwidth_classes`, `zia_bandwidth_classes_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Enforce cloud firewall policy

Description	Manage firewall filtering, DNS, IPS and NAT control rules with their IP groups, network services and time windows.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**Firewall filtering rules** `zia_cloud_firewall_rule`, `zia_cloud_firewall_rule_info` **Firewall DNS rules** `zia_cloud_firewall_dns_rules`, `zia_cloud_firewall_dns_rules_info` **Firewall IPS rules** `zia_cloud_firewall_ips_rules`, `zia_cloud_firewall_ips_rules_info` **NAT control rules** `zia_nat_control_policy`, `zia_nat_control_policy_info` **IP destination groups** `zia_cloud_firewall_ip_destination_groups`, `zia_cloud_firewall_ip_destination_groups_info` **IP source groups** `zia_cloud_firewall_ip_source_groups`, `zia_cloud_firewall_ip_source_groups_info` **Network services** `zia_cloud_firewall_network_services`, `zia_cloud_firewall_network_services_info` **Network service groups** `zia_cloud_firewall_network_services_groups`, `zia_cloud_firewall_network_services_groups_info` **Network applications** `zia_cloud_firewall_network_application_info` **Network application groups** `zia_cloud_firewall_network_application_group`, `zia_cloud_firewall_network_application_group_info` **Time windows** `zia_cloud_firewall_time_windows_info` **Custom IPS signature rules** `zia_ips_signature_rules`, `zia_ips_signature_rules_info` **DNS gateways** `zia_dns_gateway`, `zia_dns_gateway_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Protect against advanced threats and malware

Description	Configure advanced threat protection, malware inspection and exceptions, sandbox rules and submission, and security denylists.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**Advanced threat settings** `zia_atp_settings`, `zia_atp_settings_info` **Malicious URL denylist** `zia_atp_malicious_urls`, `zia_atp_malicious_urls_info` **Malware inspection** `zia_atp_malware_inspection`, `zia_atp_malware_inspection_info` **Malware policy exceptions** `zia_atp_malware_policy`, `zia_atp_malware_policy_info` **Malware protocol inspection** `zia_atp_malware_protocols`, `zia_atp_malware_protocols_info` **Malware settings** `zia_atp_malware_settings`, `zia_atp_malware_settings_info` **Security exceptions** `zia_atp_security_exceptions`, `zia_atp_security_exceptions_info` **Mobile malware protection** `zia_mobile_advanced_threat_settings`, `zia_mobile_advanced_threat_settings_info` **Security denylist** `zia_security_policy_settings` **Sandbox rules** `zia_sandbox_rules`, `zia_sandbox_rules_info` **Sandbox MD5 blocklist** `zia_sandbox_advanced_settings`, `zia_sandbox_advanced_settings_info` **Sandbox file submission** `zia_sandbox_submission` **SSL inspection rules** `zia_ssl_inspection_rules`, `zia_ssl_inspection_rules_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Prevent data loss and protect SaaS data

Description	Manage DLP rules, dictionaries, engines and notifications, and CASB DLP and malware rules.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**DLP web rules** `zia_dlp_web_rules`, `zia_dlp_web_rules_info` **DLP dictionaries** `zia_dlp_dictionaries`, `zia_dlp_dictionaries_info` **DLP engines** `zia_dlp_engine`, `zia_dlp_engine_info` **DLP notification templates** `zia_dlp_notification_template`, `zia_dlp_notification_template_info` **DLP ICAP servers** `zia_dlp_icap_server_info` **DLP IDM profiles** `zia_dlp_idm_profile_info` **DLP incident receivers** `zia_dlp_incident_receiver_info` **CASB DLP rules** `zia_casb_dlp_rules`, `zia_casb_dlp_rules_info` **CASB malware rules** `zia_casb_malware_rules`, `zia_casb_malware_rules_info` **CASB tenants** `zia_casb_tenant_info` **CASB email labels** `zia_casb_email_label_info` **CASB tombstone templates** `zia_casb_tombstone_template_info` **Email profiles** `zia_email_profiles`, `zia_email_profiles_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Forward traffic to Zscaler

Description	Manage forwarding control rules, GRE tunnels, static IPs, VPN credentials, ZPA gateways, proxies and extranets.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**Forwarding control rules** `zia_forwarding_control_rule`, `zia_forwarding_control_rule_info` **GRE tunnels** `zia_traffic_forwarding_gre_tunnels` **GRE tunnel queries** `zia_traffic_forwarding_gre_tunnel_info` **GRE internal IP ranges** `zia_traffic_forwarding_gre_internal_ranges_info` **Static IPs** `zia_traffic_forwarding_static_ip`, `zia_traffic_forwarding_static_ip_info` **VPN credentials** `zia_traffic_forwarding_vpn_credentials`, `zia_traffic_forwarding_vpn_credentials_info` **ZPA gateways** `zia_ip_source_anchoring_zpa_gateway`, `zia_ip_source_anchoring_zpa_gateway_info` **Third-party proxy services** `zia_third_party_proxy_service`, `zia_third_party_proxy_service_info` **Extranets** `zia_extranet`, `zia_extranet_info` **Traffic capture rules** `zia_traffic_capture_rules`, `zia_traffic_capture_rules_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Manage locations, service edges and data centres

Description	Define locations and groups, data centres and exclusions, sub-clouds, virtual service edges and NSS servers.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**Locations** `zia_location_management`, `zia_location_management_info` **Location groups** `zia_location_groups_info` **Data centres** `zia_datacenters_info` **Data centre exclusions** `zia_dc_exclusions`, `zia_dc_exclusions_info` **Sub-clouds** `zia_sub_cloud`, `zia_sub_cloud_info` **Virtual service edge nodes** `zia_virtual_service_edge_node`, `zia_virtual_service_edge_node_info` **Virtual service edge clusters** `zia_vzen_cluster`, `zia_vzen_cluster_info` **NSS servers** `zia_nss_servers`, `zia_nss_servers_info` **Workload groups** `zia_workload_groups`, `zia_workload_groups_info` **Browser isolation profiles** `zia_cloud_browser_isolation_profile_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Manage users, devices and authentication

Description	Query users, departments, groups and devices, and configure authentication settings and exempt URLs.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**Users** `zia_user_management_info` **Departments** `zia_user_management_department_info` **User groups** `zia_user_management_groups_info` **Device groups** `zia_device_group_info` **Devices** `zia_devices_info` **Domain profiles** `zia_domain_profiles_info` **Authentication settings** `zia_authentication_settings`, `zia_authentication_settings_info` **Authentication-exempt URLs** `zia_auth_settings_urls`, `zia_auth_settings_urls_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Use Case: Administer the ZIA tenant

Description	Review admin users and roles, configure advanced settings, alerts and remote assistance, label rules and activate saved changes.
Collection	`zscaler.ziacloud` (Certified, Zscaler, v2.2.4, updated 2026-06-02)
Key content	**Admin users** `zia_admin_users_info` **Admin roles** `zia_admin_roles_info` **Advanced settings** `zia_advanced_settings`, `zia_advanced_settings_info` **Alert subscriptions** `zia_alerts`, `zia_alerts_info` **Remote assistance** `zia_remote_assistance`, `zia_remote_assistance_info` **Rule labels** `zia_rule_labels`, `zia_rule_labels_info` **Configuration activation** `zia_activation_status` **Activation status** `zia_activation_status_info`
Notes	• Module names have the zia_ prefix omitted. Many modules are info-only lookups used to reference objects in rules.

Zscaler Private Access `zscaler.zpacloud`

Certified Zscaler · version 2.2.12 · updated 2026-08-27 · 105 modules → 7 use cases

Use Case: Define applications and segments

Description	Create application segments (standard, browser access, inspection and privileged remote access), segment groups, servers and server groups, and query segments by type.
Collection	`zscaler.zpacloud` (Certified, Zscaler, v2.2.12, updated 2026-08-27)
Key content	**Application segments** `zpa_application_segment`, `zpa_application_segment_info` **Browser access segments** `zpa_application_segment_ba_v2` **Inspection segments** `zpa_application_segment_inspection` **Privileged remote access segments** `zpa_application_segment_pra` **Segments by access type** `zpa_application_segment_by_type_info` **Multimatch bulk settings** `zpa_application_segment_multimatch_bulk`, `zpa_application_segment_multimatch_bulk_info` **Weighted load balancing** `zpa_application_segment_weightedlb_config`, `zpa_application_segment_weightedlb_config_info` **Segment groups** `zpa_segment_group`, `zpa_segment_group_info` **Application servers** `zpa_application_server`, `zpa_application_server_info` **Server groups** `zpa_server_group`, `zpa_server_group_info` **Browser access certificates** `zpa_ba_certificate`, `zpa_ba_certificate_info`

Use Case: Manage App Connectors and Private Service Edges

Description	Manage App Connector and Service Edge groups and controllers, provisioning keys, version profiles and auto-delete schedules for disconnected connectors.
Collection	`zscaler.zpacloud` (Certified, Zscaler, v2.2.12, updated 2026-08-27)
Key content	**App Connector groups** `zpa_app_connector_groups` **App Connector group info** `zpa_app_connector_group_info` **App Connector controllers** `zpa_app_connector_controller`, `zpa_app_connector_controller_info` **Connector auto-delete schedule** `zpa_connector_assistant_schedule`, `zpa_connector_assistant_schedule_info` **Service Edge groups** `zpa_service_edge_groups`, `zpa_service_edge_groups_info` **Service Edge controllers** `zpa_service_edge_controller`, `zpa_service_edge_controller_info` **Service Edge auto-delete schedule** `zpa_service_edge_assistant_schedule_info` **Provisioning keys** `zpa_provisioning_key`, `zpa_provisioning_key_info` **Version profiles** `zpa_customer_version_profile_info` **Enrollment certificates** `zpa_enrollement_certificate_info` **Private cloud groups** `zpa_private_cloud_group`, `zpa_private_cloud_group_info` **Cloud Connector groups** `zpa_cloud_connector_group_info` **Branch Connector groups** `zpa_branch_connector_group_info` **Machine groups** `zpa_machine_group_info`

Use Case: Control access with policy rules

Description	Create and reorder access, timeout, forwarding, isolation, redirection, capabilities and credential policy rules, including the v2 rule types.
Collection	`zscaler.zpacloud` (Certified, Zscaler, v2.2.12, updated 2026-08-27)

Key content	**Access policy rules** `zpa_policy_access_rule`, `zpa_policy_access_rule_info` **Access policy rules (v2)** `zpa_policy_access_rule_v2` **Rule reordering** `zpa_policy_access_rule_reorder` **Timeout rules** `zpa_policy_access_timeout_rule` **Timeout rules (v2)** `zpa_policy_access_timeout_rule_v2` **Forwarding rules** `zpa_policy_access_forwarding_rule` **Forwarding rules (v2)** `zpa_policy_access_forwarding_rule_v2` **Isolation rules** `zpa_policy_access_isolation_rule` **Isolation rules (v2)** `zpa_policy_access_isolation_rule_v2` **Redirection rules (v2)** `zpa_policy_access_redirection_rule_v2` **Capabilities rules (v2)** `zpa_policy_capabilities_access_rule_v2` **Privileged credential rules** `zpa_policy_credential_access_rule` **App protection rules** `zpa_policy_access_app_protection_rule` **App protection rules (v2)** `zpa_policy_access_app_protection_rule_v2`

Use Case: Look up identity and device context for policy

Description	Read identity provider, SAML and SCIM attributes, posture profiles, trusted networks, risk scores and location data used when building policy conditions.
Collection	`zscaler.zpacloud` (Certified, Zscaler, v2.2.12, updated 2026-08-27)
Key content	**Identity providers** `zpa_idp_controller_info` **SAML attributes** `zpa_saml_attribute_info` **SCIM attribute headers** `zpa_scim_attribute_header_info` **SCIM groups** `zpa_scim_group_info` **Posture profiles** `zpa_posture_profile_info` **Trusted networks** `zpa_trusted_networks_info` **Risk score values** `zpa_risk_score_values_info` **Locations** `zpa_location_controller_info` **Location summary** `zpa_location_controller_summary_info` **Location groups** `zpa_location_group_controller_info` **ZIA cloud configuration** `zpa_cloud_config`, `zpa_cloud_config_info` **C2C IP ranges** `zpa_c2c_ip_ranges`, `zpa_c2c_ip_ranges_info` **Extranet resource partners** `zpa_extranet_resource_partner_info`

Use Case: Provide privileged remote access

Description	Configure privileged remote access consoles, portals, credentials, credential pools and approvals.
Collection	`zscaler.zpacloud` (Certified, Zscaler, v2.2.12, updated 2026-08-27)
Key content	**PRA approvals** `zpa_pra_approval`, `zpa_pra_approval_info` **PRA consoles** `zpa_pra_console_controller`, `zpa_pra_console_controller_info` **PRA credentials** `zpa_pra_credential_controller`, `zpa_pra_credential_controller_info` **PRA credential pools** `zpa_pra_credential_pool` **PRA portals** `zpa_pra_portal_controller`, `zpa_pra_portal_controller_info`

Use Case: Isolate and protect browsing

Description	Configure cloud browser isolation banners, certificates and profiles, managed browser and browser protection profiles, and AppProtection controls and security profiles.
Collection	`zscaler.zpacloud` (Certified, Zscaler, v2.2.12, updated 2026-08-27)
Key content	**Isolation banners** `zpa_cloud_browser_isolation_banner`, `zpa_cloud_browser_isolation_banner_info` **Isolation certificates** `zpa_cloud_browser_isolation_certificate`, `zpa_cloud_browser_isolation_certificate_info` **Isolation profiles** `zpa_cloud_browser_isolation_profile_info` **ZPA isolation profiles** `zpa_isolation_profile_info` **Managed browser profiles** `zpa_managed_browser_profile_info` **Browser protection profiles** `zpa_browser_protection_info` **AppProtection custom controls** `zpa_app_protection_custom_control_info` **AppProtection predefined controls** `zpa_app_protection_predefined_control_info` **AppProtection security profiles** `zpa_app_protection_security_profile_info`

Use Case: Configure user portals, tags and log streaming

Description	Publish user portals with links and acceptable use policies, organise resources with tags, and configure Log Streaming Service receivers.
Collection	`zscaler.zpacloud` (Certified, Zscaler, v2.2.12, updated 2026-08-27)

Key content	**User portals** `zpa_user_portal_controller`, `zpa_user_portal_controller_info` **Portal links** `zpa_user_portal_link`, `zpa_user_portal_link_info` **Acceptable use policies** `zpa_user_portal_aup`, `zpa_user_portal_aup_info` **Tag groups** `zpa_tag_group`, `zpa_tag_group_info` **Tag keys** `zpa_tag_key`, `zpa_tag_key_info` **Tag namespaces** `zpa_tag_namespace`, `zpa_tag_namespace_info` **Workload tag groups** `zpa_workload_tag_group_info` **LSS configurations** `zpa_lss_config_controller`, `zpa_lss_config_controller_info` **LSS client types** `zpa_lss_client_types_info` **LSS log formats** `zpa_lss_config_log_types_formats_info`

Other certified and validated collections

Module-level content for these collections could not be read from a public source repository. Browse them on Automation Hub.

`akeyless.secrets_management`	Akeyless plugins collection (Certified, akeyless)
`ansible.security`	Ansible Security meta Collection to install all security supported content. (Certified, Red Hat)
`delinea.ss`	Delinea Secret Server Collection for Ansible. (Certified, Delinea; The repository now hosts delinea.platform_secretserver.)
`redhat.rhel_hardening_roles`	Ansible collection providing hardening roles for Red Hat Enterprise Linux. (Certified, Red Hat)