Ansible Automation - Use Cases

A reference of the use cases by which Ansible Automation Platform is commonly implemented, by domain. Each use case is described in the same format (Description, Collection, Key content, Notes) and mapped to Red Hat Certified and Validated content.

6 solution use cases · 126 product use cases · generated 2026-10-21 · community reference, not an official Red Hat publication

Contents

1. Servers, Mainframe & Power
    - Solution use cases (6)
        - Update server firmware and BIOS
        - Provision bare-metal servers
        - Automate IBM Z (z/OS) operations
        - Manage IBM Power systems with the HMC
        - Patch and maintain AIX, VIOS and IBM i
        - Manage out-of-band devices and PDUs
    - Product use cases
        - Cisco UCS (Intersight) (3)
        - Cisco Intersight (11)
        - Dell OpenManage (iDRAC, OpenManage Enterprise, Redfish) (17)
        - IBM PowerHA SystemMirror for AIX (3)
        - HPE iLO (Integrated Lights-Out) (14)
        - HPE OneView (9)
        - IBM z/OS Event-Driven Ansible (3)
        - IBM Z Hardware Management Console (5)
        - IBM CICS Transaction Server for z/OS (3)
        - IBM z/OS (5)
        - IBM IMS (2)
        - IBM Z System Automation (1)
        - IBM z/OSMF (4)
        - IBM AIX on Power (11)
        - IBM Power HMC (5)
        - IBM i (IBM Power) (12)
        - IBM Power Virtual I/O Server (VIOS) (3)
        - Inspur server BMC (ISPIM) (9)
        - WTI OOB console servers and PDUs (6)

Servers, Mainframe & Power

Bare-metal servers and their controllers, IBM Z mainframe and IBM Power systems.

Solution use cases

Use Case: Update server firmware and BIOS

Description	Bring server firmware and BIOS settings to an approved baseline without visiting each system. Automation Platform queries the out-of-band controllers (iDRAC, iLO, OneView, Intersight), reports what is out of date, stages the update and applies it in controlled batches, so fleets stay patched and consistent.
Collection	`dellemc.openmanage` (Certified), `hpe.ilo` (Certified), `hpe.oneview` (Certified), `cisco.intersight` (Certified), `cisco.cvd_compute` (Validated)
Key content	• `dellemc.openmanage.idrac_firmware` — Firmware update from a repository on a network share (CIFS, NFS, HTTP, HTTPS, FTP) • `dellemc.openmanage.ome_firmware` — Update firmware on PowerEdge devices and its components through OpenManage Enterprise • `dellemc.openmanage.idrac_bios` — Modify and clear BIOS attributes, and reset BIOS settings • `hpe.ilo.ilo_firmware` — Performs Firmware related operations on iLO using Redfish APIs • `hpe.oneview.oneview_server_profile` — Ansible role to manage OneView Server Profile resource. • `cisco.intersight.intersight_firmware_policy` — Firmware Policy configuration for Cisco Intersight • `cisco.cvd_compute.upgrade_ucs_fi_firmware` — A role that runs **Cisco UCS Fabric Interconnects (FIs)** firmware upgrade.
Notes	• Always check the vendor compatibility guidance for the combination of firmware, operating system drivers and hypervisor before approving a baseline. • Storage controllers and NICs often need a reboot; plan the order with the host maintenance step. • Use the same pattern for storage systems in Standardise storage system configuration, and for IBM Power systems in Manage IBM Power systems with the HMC. • Event-Driven Ansible can start an inventory-and-compare job when a controller reports a new alert or a vendor advisory is published.

Use Case: Provision bare-metal servers

Description	Take a rack-mounted or blade server from racked and cabled to ready for an operating system. A template defines the BIOS, boot order, storage layout, firmware and network identity. The automation applies it to each new server, installs the operating system and hands the host over to configuration management.
Collection	`dellemc.openmanage` (Certified), `hpe.ilo` (Certified), `hpe.oneview` (Certified), `cisco.intersight` (Certified), `cisco.cvd_compute` (Validated)
Key content	• `dellemc.openmanage.idrac_server_config_profile` — Export or Import iDRAC Server Configuration Profile (SCP) • `dellemc.openmanage.idrac_storage_volume` — Configures the RAID configuration attributes • `dellemc.openmanage.idrac_boot` — Configure the boot order settings • `dellemc.openmanage.idrac_os_deployment` — Role to deploy operating system on the iDRAC servers • `hpe.ilo.ilo_storage` — Performs Storage related operations on iLO using Redfish APIs • `hpe.oneview.oneview_server_profile_template` — Ansible role to manage OneView Server Profile Template resources. • `cisco.intersight.intersight_server_profile_template` — Configure Server Profile Template • `cisco.cvd_compute.deploy_ucs_server_profile` — A role that deploys **Cisco UCS Server profile** in Intersight.
Notes	• Keep hardware profiles in Git and compare them to live settings regularly to detect drift. • Apply the firmware baseline before the operating system install; see Update server firmware and BIOS. • Servers from other vendors are supported by their own certified collections, such as `inspur.ispim` for Inspur BMCs. • For remote power control of servers without a BMC, see Manage out-of-band devices and PDUs. • Event-Driven Ansible can launch this job when a new server is added to the CMDB or discovered by the management platform.

Use Case: Automate IBM Z (z/OS) operations

Description	Extend the same automation platform used for distributed systems to the mainframe. z/OS system programmers use Ansible to submit JCL, manage data sets and files, issue operator commands, apply software updates, control partitions and manage CICS and IMS resources, and combine those steps with tasks on other platforms in a single workflow.
Collection	`ibm.ibm_zos_core` (Certified), `ibm.ibm_zosmf` (Certified), `ibm.ibm_zhmc` (Certified), `ibm.ibm_zos_cics` (Certified), `ibm.ibm_zos_ims` (Certified), `ibm.ibm_zos_sysauto` (Certified), `ibm.ibm_eda_zos` (Validated)
Key content	• `ibm.ibm_zos_core.zos_job_submit` — Submit JCL • `ibm.ibm_zos_core.zos_data_set` — Manage data sets • `ibm.ibm_zos_core.zos_operator` — Execute operator command • `ibm.ibm_zos_core.zos_gather_facts` — Gather z/OS system facts. • `ibm.ibm_zosmf.zmf_workflow` — Operate z/OS workflows • `ibm.ibm_zhmc.zhmc_partition` — Manage a partition (DPM mode) • `ibm.ibm_zos_cics.cmci_get` — Query CICS and CICSPlex SM resources and definitions • `ibm.ibm_zos_ims.ims_command` — Submit IMS Commands
Notes	• `ibm.ibm_zos_core.playbook_upgrade_validator` helps move older playbooks to a current major release of the collection. • `ibm.ibm_eda_zos` is validated Event-Driven Ansible content for IBM Z, including an event filter for zSecure alerts, so security alerts on the mainframe can start automation. • For a combined view with other IBM platforms, see Manage IBM Power systems with the HMC and Patch and maintain AIX, VIOS and IBM i. • Mainframe teams usually keep their JCL and members in Git; the job template can fetch them at run time.

Use Case: Manage IBM Power systems with the HMC

Description	Operate IBM Power servers through the Hardware Management Console with the same job templates used for other infrastructure. Administrators create and activate partitions, change CPU and memory dynamically, move running partitions between systems, set up virtual networking and Virtual I/O Servers, and maintain HMC and system firmware.
Collection	`ibm.power_hmc` (Certified), `ibm.power_vios` (Certified)
Key content	• `ibm.power_hmc.powervm_lpar_instance` — Create, Delete, Shutdown, Activate, Restart, Facts and Install of PowerVM Partitions • `ibm.power_hmc.powervm_dlpar` — Dynamically managing resources of partition • `ibm.power_hmc.powervm_lpar_migration` — Validate, migrate, and recover LPARs • `ibm.power_hmc.power_system` — PowerOn, PowerOff, modify_syscfg, modify_hwres, facts of the Managed system • `ibm.power_hmc.firmware_update` — Change firmware level on Managed Systems • `ibm.power_hmc.vios` — Creation and management of Virtual I/O Server partition • `ibm.power_hmc.powervm_inventory` — HMC-based inventory source for Power Servers • `ibm.power_hmc.redhat_linux_install` — Redhat Linux installation using pxe server
Notes	• Power-specific VIOS tasks outside the HMC, such as backup and update from the VIOS itself, are covered in Patch and maintain AIX, VIOS and IBM i. • `ibm.power_vios` modules such as `viosbr` and `viosecure` can be run directly against a VIOS partition. • For firmware practices on x86 servers, see Update server firmware and BIOS. • Event-Driven Ansible can start a service event report or an extra health check job when a serviceable event is raised.

Use Case: Patch and maintain AIX, VIOS and IBM i

Description	Bring order to patching and routine maintenance on IBM Power operating systems. The process checks installed levels, identifies missing security and HIPER fixes, takes a rollback point, applies the fix, and verifies the result, with the same approvals and reporting as for Linux and Windows servers.
Collection	`ibm.power_aix` (Certified), `ibm.power_vios` (Certified), `ibm.power_ibmi` (Certified), `enfence.powerha_aix` (Certified)
Key content	• `ibm.power_aix.flrtvc` — Generate FLRTVC report, download and install security and HIPER fixes. • `ibm.power_aix.suma` — Download/Install fixes, SP or TL from IBM Fix Central website. • `ibm.power_aix.nim` — Performs NIM operations - server setup, install packages, update SP or TL. • `ibm.power_aix.alt_disk` — Alternate rootvg disk management. • `ibm.power_vios.updateios` — Updates the Virtual I/O Server to the latest maintenance level • `ibm.power_vios.viosbr` — Backup/Restore the configuration of the VIOS • `ibm.power_ibmi.ibmi_fix` — Install, remove or query an individual fix or a set of fixes on to IBM i system. • `ibm.power_ibmi.ibmi_lib_save` — Save one libary
Notes	• AIX security settings, users and groups, filesystems and NIM operations have dedicated modules in `ibm.power_aix`, so the same collection supports hardening and routine administration. • For clusters running PowerHA, `enfence.powerha_aix` manages cluster and resource group configuration and can be used in the maintenance workflow. • Combine with Manage IBM Power systems with the HMC for partition-level operations, and with Automate IBM Z (z/OS) operations for a mainframe equivalent. • Event-Driven Ansible can start a fix-check job when a new security bulletin or a monitoring alert arrives.

Use Case: Manage out-of-band devices and PDUs

Description	Keep the access path that works when everything else is down: console servers and remote power switches. Automation applies a common configuration to every unit, monitors alarms, power and temperature, backs up settings, updates firmware, and lets other workflows power-cycle an outlet to recover a hung device.
Collection	`wti.remote` (Certified)
Key content	• `wti.remote.cpm_config_backup` — Get parameters from WTI OOB and PDU devices • `wti.remote.cpm_config_restore` — Send operational parameters to WTI OOB and PDU devices • `wti.remote.cpm_firmware_update` — Set Serial port parameters in WTI OOB and PDU devices • `wti.remote.cpm_plugcontrol` — Get and Set Plug actions on WTI OOB and PDU power devices • `wti.remote.cpm_status_info` — Get general status information from WTI OOB and PDU devices • `wti.remote.cpm_alarm_info` — Get alarm information from WTI OOB and PDU devices
Notes	• Use the out-of-band network for these jobs, so automation still reaches the devices during an outage. • Server BMCs (iDRAC, iLO) are covered in Provision bare-metal servers and Update server firmware and BIOS. • Event-Driven Ansible can trigger the power-cycle job after a monitoring alert shows a host unresponsive, with a guard that requires approval for production systems.

Product use cases

Grouped from the modules of each certified or validated collection. Key content lists the components each use case supports, with the modules that manage them (create, update, delete) and query them (_info).

Cisco UCS (Intersight) `cisco.cvd_compute`

Validated Cisco · version 1.1.0 · updated 2025-07-03 · 0 modules → 3 use cases

Use Case: Deploy UCS server and chassis profiles

Description	Deploy server profiles, derive chassis profiles from templates and rediscover chassis.
Collection	`cisco.cvd_compute` (Validated, Cisco)
Key content	**Server profile deployment** role `deploy_ucs_server_profile` **Chassis profile derivation** role `derive_ucs_chassis_profile_template` **Chassis rediscovery** role `rediscover_ucs_chassis`

Use Case: Configure UCS networking

Description	Add vNICs and VLANs to LAN connectivity policies and query and update fabric interconnect port policies.
Collection	`cisco.cvd_compute` (Validated, Cisco)
Key content	**vNICs** role `add_ucs_vnic` **VLANs on vNICs** role `add_ucs_vlan_to_vnic` **Available fabric interconnect ports** role `query_ucs_fi_available_ports` **Fabric interconnect port configuration** role `query_ucs_fi_port_configuration` **Fabric interconnect port policy** role `update_ucs_fi_port_policy`

Use Case: Upgrade fabric interconnect firmware

Description	Run firmware upgrades on Cisco UCS fabric interconnects.
Collection	`cisco.cvd_compute` (Validated, Cisco)
Key content	**Firmware upgrade** role `upgrade_ucs_fi_firmware`

Cisco Intersight `cisco.intersight`

Certified Cisco · version 2.23.0 · updated 2026-10-12 · 137 modules → 11 use cases

Use Case: Define server hardware and boot policies

Description	Configure BIOS and AI-optimized BIOS presets, boot order, memory, GPU, power, thermal, firmware, storage and drive security, virtual media and adapter policies for servers.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**BIOS policies** `intersight_bios_policy`, `intersight_bios_policy_info` **AI-optimized BIOS presets** `intersight_bios_ai_tuning`, `intersight_bios_ai_tuning_info` **Confidential computing BIOS policies** `intersight_confidential_compute`, `intersight_confidential_compute_info` **Boot order policies** `intersight_boot_order_policy`, `intersight_boot_order_policy_info` **Memory policies** `intersight_memory_policy`, `intersight_memory_policy_info` **Persistent memory policies** `intersight_memory_persistent_policy`, `intersight_memory_persistent_policy_info` **GPU policies** `intersight_gpu_policy`, `intersight_gpu_policy_info` **Power policies** `intersight_power_policy`, `intersight_power_policy_info` **Thermal policies** `intersight_thermal_policy`, `intersight_thermal_policy_info` **Firmware policies** `intersight_firmware_policy`, `intersight_firmware_policy_info` **Storage policies** `intersight_storage_policy`, `intersight_storage_policy_info` **AI-optimized storage policies** `intersight_ai_storage_policy`, `intersight_ai_storage_policy_info` **Drive security policies** `intersight_drive_security_policy`, `intersight_drive_security_policy_info` **Virtual media policies** `intersight_virtual_media_policy`, `intersight_virtual_media_policy_info` **Adapter configuration policies** `intersight_adapter_config_policy`, `intersight_adapter_config_policy_info` **BIOS policy playbook** playbook `intersight_bios_policy` **Boot order policy playbook** playbook `intersight_boot_order_policy` **Virtual media policy playbook** playbook `intersight_virtual_media_policy` **PXE boot policy playbook** playbook `pxe_boot`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Define management, access and monitoring policies

Description	Configure IMC access, IPMI over LAN, KVM, SSH, LDAP and local users, certificates, device connector, network connectivity, NTP, SMTP, SNMP and syslog policies.
Collection	`cisco.intersight` (Certified, Cisco)

Key content	**IMC access policies** `intersight_imc_access_policy`, `intersight_imc_access_policy_info` **IPMI over LAN policies** `intersight_ipmi_over_lan_policy`, `intersight_ipmi_over_lan_policy_info` **Virtual KVM policies** `intersight_kvm_policy`, `intersight_kvm_policy_info` **SSH policies** `intersight_ssh_policy`, `intersight_ssh_policy_info` **LDAP policies** `intersight_ldap_policy`, `intersight_ldap_policy_info` **Local user policies** `intersight_local_user_policy`, `intersight_local_user_policy_info` **Certificate management policies** `intersight_certificate_management_policy`, `intersight_certificate_management_policy_info` **Device connector policies** `intersight_device_connector_policy`, `intersight_device_connector_policy_info` **Network connectivity policies** `intersight_network_connectivity_policy`, `intersight_network_connectivity_policy_info` **NTP policies** `intersight_ntp_policy`, `intersight_ntp_policy_info` **SMTP policies** `intersight_smtp_policy`, `intersight_smtp_policy_info` **SNMP policies** `intersight_snmp_policy`, `intersight_snmp_policy_info` **Syslog policies** `intersight_syslog_policy`, `intersight_syslog_policy_info` **IMC access policy playbook** playbook `intersight_imc_access_policy` **Out-of-band IMC access policy playbook** playbook `intersight_oob_imc_access_policy` **NTP policy playbook** playbook `intersight_ntp_policy`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Configure server Ethernet connectivity

Description	Define LAN connectivity policies with vNICs, vNIC templates, Ethernet adapter, network control, network group and QoS policies.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**LAN connectivity policies and vNICs** `intersight_lan_connectivity_policy`, `intersight_lan_connectivity_policy_info` **vNIC templates** `intersight_vnic_template`, `intersight_vnic_template_info` **Ethernet adapter policies** `intersight_ethernet_adapter_policy`, `intersight_ethernet_adapter_policy_info` **Ethernet network control policies** `intersight_ethernet_network_control_policy`, `intersight_ethernet_network_control_policy_info` **Ethernet network group policies** `intersight_ethernet_network_group_policy`, `intersight_ethernet_network_group_policy_info` **Ethernet QoS policies** `intersight_ethernet_qos_policy`, `intersight_ethernet_qos_policy_info` **LAN connectivity policy playbook** playbook `intersight_lan_connectivity_policy` **vNIC template playbook** playbook `intersight_vnic_template` **vNIC template attachment playbook** playbook `intersight_attach_vnic_template` **Ethernet network VLAN report playbook** playbook `intersight_eth_network`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Configure server SAN, Fibre Channel and iSCSI connectivity

Description	Define SAN connectivity policies with vHBAs, vHBA templates, Fibre Channel adapter, network, QoS and zone policies, and iSCSI adapter, boot and static target policies.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**SAN connectivity policies and vHBAs** `intersight_san_connectivity_policy`, `intersight_san_connectivity_policy_info` **vHBA templates** `intersight_vhba_template`, `intersight_vhba_template_info` **Fibre Channel adapter policies** `intersight_fibre_channel_adapter_policy`, `intersight_fibre_channel_adapter_policy_info` **Fibre Channel network policies** `intersight_fibre_channel_network_policy`, `intersight_fibre_channel_network_policy_info` **Fibre Channel QoS policies** `intersight_fibre_channel_qos_policy`, `intersight_fibre_channel_qos_policy_info` **Fibre Channel zone policies** `intersight_fibre_channel_zone_policy`, `intersight_fibre_channel_zone_policy_info` **iSCSI adapter policies** `intersight_iscsi_adapter_policy`, `intersight_iscsi_adapter_policy_info` **iSCSI boot policies** `intersight_iscsi_boot_policy`, `intersight_iscsi_boot_policy_info` **iSCSI static target policies** `intersight_iscsi_static_target_policy`, `intersight_iscsi_static_target_policy_info` **vHBA template attachment playbook** playbook `attach_vhba_template`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Configure UCS domains and fabric policies

Description	Manage UCS domain profiles and chassis profiles, and the fabric port, VLAN, VSAN, multicast, flow control, link, MACsec, switch control and system QoS policies they use.
Collection	`cisco.intersight` (Certified, Cisco)

Key content	**UCS domain profiles** `intersight_domain`, `intersight_domain_info` **Chassis profiles** `intersight_chassis_profile`, `intersight_chassis_profile_info` **Port policies** `intersight_port_policy`, `intersight_port_policy_info` **VLAN policies and VLANs** `intersight_vlan_policy`, `intersight_vlan_policy_info` **VSAN policies and VSANs** `intersight_vsan_policy`, `intersight_vsan_policy_info` **Multicast policies** `intersight_multicast_policy`, `intersight_multicast_policy_info` **Flow control policies** `intersight_flow_control_policy`, `intersight_flow_control_policy_info` **Link aggregation policies** `intersight_link_aggregation_policy`, `intersight_link_aggregation_policy_info` **Link control policies** `intersight_link_control_policy`, `intersight_link_control_policy_info` **MACsec policies** `intersight_macsec_policy`, `intersight_macsec_policy_info` **Switch control policies** `intersight_switch_control_policy`, `intersight_switch_control_policy_info` **System QoS policies** `intersight_system_qos_policy`, `intersight_system_qos_policy_info` **Domain profile playbook** playbook `intersight_domain_profile` **Domain profile deployment preview playbook** playbook `deploy_domain_profile` **Fabric port policy playbook** playbook `intersight_port_policy` **Fabric port policy JSON patch playbook** playbook `port_policy_json_patch`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Allocate identity pools

Description	Manage IP, IQN, MAC, UUID and WWN pools and reserve identifiers in them.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**IP pools** `intersight_ip_pool`, `intersight_ip_pool_info` **IQN pools** `intersight_iqn_pool`, `intersight_iqn_pool_info` **MAC pools** `intersight_mac_pool`, `intersight_mac_pool_info` **UUID pools** `intersight_uuid_pool`, `intersight_uuid_pool_info` **WWNN and WWPN pools** `intersight_wwn_pool`, `intersight_wwn_pool_info` **Pool reservations** `intersight_pool_reservation`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Create and deploy server profiles

Description	Create server profiles and templates, derive profiles from templates, qualify servers for pools, define Unified Edge profiles and assign or deploy profiles to servers.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**Server profiles** `intersight_server_profile`, `intersight_server_profile_info` **Server profile templates** `intersight_server_profile_template`, `intersight_server_profile_template_info` **Derived server profiles** `intersight_server_profile_derive` **Server pool qualification policies** `intersight_server_pool_qualification_policy`, `intersight_server_pool_qualification_policy_info` **Unified Edge profile templates** `intersight_unified_edge_profile`, `intersight_unified_edge_profile_info` **Server profile playbook** playbook `intersight_server_profile` **Server profile template playbook** playbook `intersight_server_profile_template` **Policy bucket profile playbook** playbook `profile_with_buckets` **Unassigned server profiles playbook** playbook `only_new_server_profiles` **Server profile assignment playbook** playbook `assign_server_to_profile` **Server profile deployment playbook** playbook `deploy_server_profiles`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Administer organizations, claims and API access

Description	Manage organizations and resource groups, claim devices as targets and call the Intersight REST API directly.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**Organizations** `intersight_organization`, `intersight_organization_info` **Resource groups** `intersight_resource_group`, `intersight_resource_group_info` **Target claims** `intersight_target_claim` **REST API calls** `intersight_rest_api` **Device claim playbook** playbook `claim_device`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Operate servers

Description	Update server firmware, run power and other server actions, and disable alarm suppression.
Collection	`cisco.intersight` (Certified, Cisco)

Key content	**Server firmware update playbook** playbook `server_firmware` **Firmware direct download playbook** playbook `firmware_direct_download` **Server actions playbook** playbook `server_actions` **Alarm suppression playbook** playbook `alarm_suppression`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Report on inventory and build Ansible inventories

Description	Gather Intersight information, count servers and VMs, report HCL status and GPU servers, and generate Ansible inventory files from Intersight.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**Intersight information** `intersight_info` **Object count playbook** playbook `intersight_info` **Server count playbook** playbook `count_servers` **VM count playbook** playbook `count_vms` **VM hosts CSV playbook** playbook `intersight_vm_hosts` **GPU servers CSV playbook** playbook `gpu_servers_to_csv` **HCL status playbook** playbook `hcl_status` **All-servers inventory playbook** playbook `update_all_inventory` **Standalone C-Series inventory playbook** playbook `update_standalone_inventory` **HyperFlex inventory playbook** playbook `update_hx_inventory` **HyperFlex Edge inventory playbook** playbook `update_hx_edge_inventory`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Use Case: Deploy solution blueprints

Description	Configure policies and profiles for AI Pod, cloud object storage and HyperFlex clusters, and run orchestration and workload definition workflows.
Collection	`cisco.intersight` (Certified, Cisco)
Key content	**AI Pod playbook** playbook `ai_pod` **Cloud object storage playbook** playbook `cos_server_policies_and_profiles` **HyperFlex cluster profiles playbook** playbook `hyperflex_cluster_profiles` **HyperFlex Edge cluster profiles playbook** playbook `hyperflex_edge_cluster_profiles` **OVA orchestration workflow playbook** playbook `ova_workflow` **Workload definition playbook** playbook `workload_definition`
Notes	• Policy, pool and profile modules cover both configuration and read-only info queries.

Dell OpenManage (iDRAC, OpenManage Enterprise, Redfish) `dellemc.openmanage`

Certified Dell Technologies · version 11.0.0 · updated 2026-10-05 · 101 modules → 17 use cases

Use Case: Configure iDRAC attributes, BIOS and boot

Description	Configure iDRAC attributes, BIOS settings, boot order and secure boot, and query network adapters and BIOS attribute registries.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**IDRAC attributes** `idrac_attributes` **IDRAC BIOS** `idrac_bios` **IDRAC BIOS registry** `idrac_bios_registry_info` **IDRAC boot** `idrac_boot` **IDRAC network** `idrac_network_info` **IDRAC network attributes** `idrac_network_attributes`, `idrac_network_attributes_info` **IDRAC secure boot** `idrac_secure_boot` **IDRAC attributes (playbook, idrac)** playbook `idrac.idrac_attributes` **IDRAC BIOS (playbook, idrac)** playbook `idrac.idrac_bios` **IDRAC BIOS registry info (playbook)** playbook `idrac.idrac_bios_registry_info` **IDRAC boot (playbook)** playbook `idrac.idrac_boot` **IDRAC network attributes (playbook)** playbook `idrac.idrac_network_attributes` **IDRAC network attributes info (playbook)** playbook `idrac.idrac_network_attributes_info` **IDRAC network attributes info validate (playbook)** playbook `idrac.idrac_network_attributes_info_validate` **IDRAC network info (playbook)** playbook `idrac.idrac_network_info` **IDRAC secure boot (playbook)** playbook `idrac.idrac_secure_boot` **IDRAC attributes (playbook, roles.idrac_attributes)** playbook `roles.idrac_attributes.idrac_attributes` **IDRAC BIOS (playbook, roles.idrac_bios)** playbook `roles.idrac_bios.idrac_bios` **IDRAC attributes (role)** role `idrac_attributes` **IDRAC BIOS (role)** role `idrac_bios` **IDRAC boot (role)** role `idrac_boot`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Update server firmware

Description	Update firmware on PowerEdge servers from a repository or DUP file through iDRAC or Redfish, and roll components back.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)

Key content	**IDRAC firmware** `idrac_firmware`, `idrac_firmware_info` **Redfish firmware** `redfish_firmware` **Redfish firmware rollback** `redfish_firmware_rollback` **IDRAC firmware (playbook, idrac)** playbook `idrac.idrac_firmware` **IDRAC firmware info (playbook)** playbook `idrac.idrac_firmware_info` **Redfish firmware (playbook, redfish.firmware)** playbook `redfish.firmware.redfish_firmware` **Redfish firmware from HTTP jobtracking (playbook)** playbook `redfish.firmware.redfish_firmware_from_http_jobtracking` **Redfish firmware from local jobtracking (playbook)** playbook `redfish.firmware.redfish_firmware_from_local_jobtracking` **Redfish firmware rollback (playbook)** playbook `redfish.firmware.redfish_firmware_rollback` **IDRAC firmware (playbook, roles.idrac_firmware)** playbook `roles.idrac_firmware.idrac_firmware` **Redfish firmware (playbook, roles.redfish_firmware)** playbook `roles.redfish_firmware.redfish_firmware` **IDRAC firmware (role)** role `idrac_firmware` **Redfish firmware (role)** role `redfish_firmware`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Track Lifecycle Controller status and jobs

Description	Check Lifecycle Controller readiness, follow and delete jobs, export its logs and manage the job queue.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**IDRAC lifecycle controller job status** `idrac_lifecycle_controller_job_status_info` **IDRAC lifecycle controller jobs** `idrac_lifecycle_controller_jobs` **IDRAC lifecycle controller logs** `idrac_lifecycle_controller_logs` **IDRAC lifecycle controller status** `idrac_lifecycle_controller_status_info` **IDRAC lifecycle controller job status info (playbook)** playbook `idrac.idrac_lifecycle_controller_job_status_info` **IDRAC lifecycle controller jobs (playbook)** playbook `idrac.idrac_lifecycle_controller_jobs` **IDRAC lifecycle controller logs (playbook)** playbook `idrac.idrac_lifecycle_controller_logs` **IDRAC lifecycle controller status info (playbook)** playbook `idrac.idrac_lifecycle_controller_status_info` **IDRAC job queue (playbook)** playbook `roles.idrac_job_queue.idrac_job_queue` **IDRAC job queue (role)** role `idrac_job_queue`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Export and import server configuration profiles

Description	Export and import iDRAC server configuration profiles (SCP) to capture and replicate server settings.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**IDRAC server config profile** `idrac_server_config_profile` **IDRAC server config profile (playbook)** playbook `idrac.idrac_server_config_profile` **IDRAC export server config profile (playbook)** playbook `roles.idrac_export_server_config_profile.idrac_export_server_config_profile` **IDRAC import server config profile (playbook)** playbook `roles.idrac_import_server_config_profile.idrac_import_server_config_profile` **IDRAC export server config profile (role)** role `idrac_export_server_config_profile` **IDRAC import server config profile (role)** role `idrac_import_server_config_profile`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Configure server storage and RAID

Description	Configure physical disks, virtual disks, RAID volumes and storage controllers through iDRAC and Redfish.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**IDRAC redfish storage controller** `idrac_redfish_storage_controller` **IDRAC storage volume** `idrac_storage_volume` **Redfish storage volume** `redfish_storage_volume` **IDRAC redfish storage controller (playbook)** playbook `idrac.idrac_redfish_storage_controller` **IDRAC redfish storage controller job tracking (playbook)** playbook `idrac.idrac_redfish_storage_controller_job_tracking` **IDRAC storage volume (playbook)** playbook `idrac.idrac_storage_volume` **Redfish storage volume (playbook, redfish.storage)** playbook `redfish.storage.redfish_storage_volume` **Redfish storage volume create job tracking (playbook)** playbook `redfish.storage.redfish_storage_volume_create_job_tracking` **Redfish storage volume delete job tracking (playbook)** playbook `redfish.storage.redfish_storage_volume_delete_job_tracking` **Redfish storage volume initialize job tracking (playbook)** playbook `redfish.storage.redfish_storage_volume_initialize_job_tracking` **Redfish storage volume modify job tracking (playbook)** playbook `redfish.storage.redfish_storage_volume_modify_job_tracking` **IDRAC storage controller (playbook)** playbook `roles.idrac_storage_controller.idrac_storage_controller` **Redfish storage volume (playbook, roles.redfish_storage_volume)** playbook `roles.redfish_storage_volume.redfish_storage_volume` **IDRAC storage controller (role)** role `idrac_storage_controller` **Redfish storage volume (role)** role `redfish_storage_volume`

Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Manage iDRAC users, certificates, licenses and sessions

Description	Configure local iDRAC user accounts, certificates and CSRs, licenses and web sessions.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**IDRAC certificates** `idrac_certificates` **IDRAC license** `idrac_license` **IDRAC session** `idrac_session`, `idrac_session_info` **IDRAC user** `idrac_user`, `idrac_user_info` **IDRAC certificates (playbook)** playbook `idrac.idrac_certificates` **IDRAC license (playbook)** playbook `idrac.idrac_license` **IDRAC session (playbook)** playbook `idrac.idrac_session` **IDRAC session info (playbook)** playbook `idrac.idrac_session_info` **IDRAC user (playbook, idrac)** playbook `idrac.idrac_user` **IDRAC user info (playbook)** playbook `idrac.idrac_user_info` **IDRAC certificate (playbook)** playbook `roles.idrac_certificate.idrac_certificate` **IDRAC user (playbook, roles.idrac_user)** playbook `roles.idrac_user.idrac_user` **IDRAC certificate (role)** role `idrac_certificate` **IDRAC user (role)** role `idrac_user`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Control server power, reset and OS deployment

Description	Power servers on and off, reset or factory-reset iDRAC, mount virtual media, boot network ISO images to deploy an OS and erase systems.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**IDRAC OS deployment** `idrac_os_deployment` **IDRAC reset** `idrac_reset` **IDRAC system erase** `idrac_system_erase` **IDRAC virtual media** `idrac_virtual_media` **Redfish powerstate** `redfish_powerstate` **IDRAC boot virtual media workflow (playbook)** playbook `idrac.idrac_boot_virtual_media_workflow` **IDRAC OS deployment (playbook, idrac)** playbook `idrac.idrac_os_deployment` **IDRAC reset (playbook, idrac)** playbook `idrac.idrac_reset` **IDRAC reset result tracking (playbook)** playbook `idrac.idrac_reset_result_tracking` **IDRAC virtual media (playbook)** playbook `idrac.idrac_virtual_media` **Redfish powerstate (playbook)** playbook `redfish.redfish_powerstate` **IDRAC OS deployment (playbook, roles.idrac_os_deployment)** playbook `roles.idrac_os_deployment.idrac_os_deployment` **IDRAC reset (playbook, roles.idrac_reset)** playbook `roles.idrac_reset.idrac_reset` **IDRAC server powerstate (playbook)** playbook `roles.idrac_server_powerstate.idrac_server_powerstate` **IDRAC OS deployment (role)** role `idrac_os_deployment` **IDRAC reset (role)** role `idrac_reset` **IDRAC server powerstate (role)** role `idrac_server_powerstate`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Gather inventory and diagnostics

Description	Collect system inventory, run and export diagnostics, SupportAssist and technical support reports, and build inventories from OME.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**IDRAC diagnostics** `idrac_diagnostics` **IDRAC support assist** `idrac_support_assist` **IDRAC system** `idrac_system_info` **OME diagnostics** `ome_diagnostics` **OME inventory (inventory plugin)** inventory `ome_inventory` **IDRAC diagnostics (playbook)** playbook `idrac.idrac_diagnostics` **IDRAC support assist (playbook)** playbook `idrac.idrac_support_assist` **IDRAC system info (playbook)** playbook `idrac.idrac_system_info` **OME diagnostics (playbook)** playbook `ome.ome_diagnostics` **IDRAC gather facts (playbook)** playbook `roles.idrac_gather_facts.idrac_gather_facts` **IDRAC gather facts (role)** role `idrac_gather_facts`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Discover and organise devices in OpenManage Enterprise

Description	Run discovery jobs, query and group managed devices, run device actions and power operations and follow OME jobs.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)

Key content	**Device inventory info** `ome_device_info` **OME device group** `ome_device_group` **OME devices** `ome_devices` **OME discovery** `ome_discovery` **OME groups** `ome_groups` **Job info** `ome_job_info` **OME powerstate** `ome_powerstate` **OME device group (playbook)** playbook `ome.ome_device_group` **OME device info (playbook)** playbook `ome.ome_device_info` **OME devices (playbook)** playbook `ome.ome_devices` **OME discovery (playbook)** playbook `ome.ome_discovery` **OME group device action (playbook)** playbook `ome.ome_group_device_action` **OME groups (playbook)** playbook `ome.ome_groups` **OME job info (playbook)** playbook `ome.ome_job_info` **OME powerstate (playbook)** playbook `ome.powerstate.ome_powerstate` **OME powerstate with job tracking (playbook)** playbook `ome.powerstate.ome_powerstate_with_job_tracking`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Manage firmware baselines and catalogs in OME

Description	Create firmware catalogs and baselines, check baseline compliance and update firmware on managed devices.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OME firmware** `ome_firmware` **OME firmware baseline** `ome_firmware_baseline`, `ome_firmware_baseline_info` **OME firmware baseline compliance** `ome_firmware_baseline_compliance_info` **OME firmware catalog** `ome_firmware_catalog` **Component complaince report with baseline (playbook)** playbook `ome.firmware.baseline.component_reports_filtering.component_complaince_report_with_baseline` **Component complaince report with devices (playbook)** playbook `ome.firmware.baseline.component_reports_filtering.component_complaince_report_with_devices` **OME firmware baseline (playbook)** playbook `ome.firmware.baseline.ome_firmware_baseline` **OME firmware baseline compliance info (playbook)** playbook `ome.firmware.baseline.ome_firmware_baseline_compliance_info` **OME firmware baseline compliance info filters (playbook)** playbook `ome.firmware.baseline.ome_firmware_baseline_compliance_info_filters` **OME firmware baseline info (playbook)** playbook `ome.firmware.baseline.ome_firmware_baseline_info` **OME firmware catalog (playbook)** playbook `ome.firmware.catalog.ome_firmware_catalog` **OME firmware (playbook)** playbook `ome.firmware.ome_firmware` **OME firmware with job tracking (playbook)** playbook `ome.firmware.ome_firmware_with_job_tracking`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Deploy templates and profiles and check compliance

Description	Create, deploy and clone configuration templates, profiles, identity pools and server interface profiles, and report on configuration compliance.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OME configuration compliance** `ome_configuration_compliance_info` **OME configuration compliance baseline** `ome_configuration_compliance_baseline` **OME identity pool** `ome_identity_pool` **OME profile** `ome_profile`, `ome_profile_info` **OME server interface profile** `ome_server_interface_profile_info` **OME server interface profiles** `ome_server_interface_profiles` **OME template** `ome_template`, `ome_template_info` **OME template identity pool** `ome_template_identity_pool` **OME template network VLAN** `ome_template_network_vlan`, `ome_template_network_vlan_info` **OME configuration compliance baseline (playbook)** playbook `ome.compliance.ome_configuration_compliance_baseline` **OME configuration compliance baseline workflow (playbook)** playbook `ome.compliance.ome_configuration_compliance_baseline_workflow` **OME configuration compliance info (playbook)** playbook `ome.compliance.ome_configuration_compliance_info` **OME identity pool (playbook)** playbook `ome.ome_identity_pool` **OME server interface profile info (playbook)** playbook `ome.ome_server_interface_profile_info` **OME server interface profile workflow (playbook)** playbook `ome.ome_server_interface_profile_workflow` **OME server interface profiles (playbook)** playbook `ome.ome_server_interface_profiles` **OME template identity pool (playbook)** playbook `ome.ome_template_identity_pool` **OME profile (playbook)** playbook `ome.profile.ome_profile` **OME profile assign job tracking (playbook)** playbook `ome.profile.ome_profile_assign_job_tracking` **OME profile info (playbook)** playbook `ome.profile.ome_profile_info` **OME profile migrate job tracking (playbook)** playbook `ome.profile.ome_profile_migrate_job_tracking` **OME profile unassign job tracking (playbook)** playbook `ome.profile.ome_profile_unassign_job_tracking` **OME template (playbook)** playbook `ome.template.ome_template` **OME template create modify lcd display (playbook)** playbook `ome.template.ome_template_create_modify_lcd_display` **OME template info (playbook)** playbook `ome.template.ome_template_info` **OME template info with filter (playbook)** playbook `ome.template.ome_template_info_with_filter` **OME template lcd display string deploy (playbook)** playbook `ome.template.ome_template_lcd_display_string_deploy` **OME template network VLAN (playbook)** playbook `ome.template.ome_template_network_vlan` **OME template network VLAN info (playbook)** playbook `ome.template.ome_template_network_vlan_info` **OME template with job tracking (playbook)** playbook `ome.template.ome_template_with_job_tracking`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Manage fabrics, VLANs and switch ports

Description	Create VLANs, smart fabrics and uplinks and configure port breakout.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OME network port breakout** `ome_network_port_breakout` **OME network VLAN** `ome_network_vlan`, `ome_network_vlan_info` **OME smart fabric** `ome_smart_fabric`, `ome_smart_fabric_info` **OME smart fabric uplink** `ome_smart_fabric_uplink`, `ome_smart_fabric_uplink_info` **OME network port breakout (playbook)** playbook `ome.ome_network_port_breakout` **OME network port breakout job traking (playbook)** playbook `ome.ome_network_port_breakout_job_traking` **OME network VLAN (playbook)** playbook `ome.ome_network_vlan` **OME network VLAN info (playbook)** playbook `ome.ome_network_vlan_info` **OME smart fabric (playbook)** playbook `ome.ome_smart_fabric` **OME smart fabric info (playbook)** playbook `ome.ome_smart_fabric_info` **OME smart fabric uplink (playbook)** playbook `ome.ome_smart_fabric_uplink` **OME smart fabric uplink info (playbook)** playbook `ome.ome_smart_fabric_uplink_info`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Configure OpenManage Enterprise Modular chassis

Description	Set chassis slot names, local access, location, management network, network services, power settings and quick deploy.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OME chassis slots** `ome_chassis_slots` **OME device local access configuration** `ome_device_local_access_configuration` **OME device location** `ome_device_location` **OME device mgmt network** `ome_device_mgmt_network` **OME device network services** `ome_device_network_services` **OME device power settings** `ome_device_power_settings` **OME device quick deploy** `ome_device_quick_deploy` **OME chassis slots (playbook)** playbook `ome.ome_chassis_slots` **OME device local access configuration (playbook)** playbook `ome.ome_device_local_access_configuration` **OME device location (playbook)** playbook `ome.ome_device_location` **OME device mgmt network (playbook)** playbook `ome.ome_device_mgmt_network` **OME device network services (playbook)** playbook `ome.ome_device_network_services` **OME device power settings (playbook)** playbook `ome.ome_device_power_settings` **OME device quick deploy (playbook)** playbook `ome.ome_device_quick_deploy`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Configure the OpenManage Enterprise console

Description	Configure console preferences, network address, proxy, time and web server, certificates, login security and email and syslog alert forwarding.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OME application alerts SMTP** `ome_application_alerts_smtp` **OME application alerts syslog** `ome_application_alerts_syslog` **OME application certificate** `ome_application_certificate` **OME application console preferences** `ome_application_console_preferences` **OME application network address** `ome_application_network_address` **OME application network proxy** `ome_application_network_proxy` **OME application network settings** `ome_application_network_settings` **OME application network time** `ome_application_network_time` **OME application network webserver** `ome_application_network_webserver` **OME application security settings** `ome_application_security_settings` **OME application alerts SMTP (playbook)** playbook `ome.application.ome_application_alerts_smtp` **OME application alerts syslog (playbook)** playbook `ome.application.ome_application_alerts_syslog` **OME application certificate (playbook)** playbook `ome.application.ome_application_certificate` **OME application console preferences (playbook)** playbook `ome.application.ome_application_console_preferences` **OME application network address (playbook)** playbook `ome.application.ome_application_network_address` **OME application network address with job tracking (playbook)** playbook `ome.application.ome_application_network_address_with_job_tracking` **OME application network proxy (playbook)** playbook `ome.application.ome_application_network_proxy` **OME application network settings (playbook)** playbook `ome.application.ome_application_network_settings` **OME application network time (playbook)** playbook `ome.application.ome_application_network_time` **OME application network time zone info (playbook)** playbook `ome.application.ome_application_network_time_zone_info` **OME application network webserver (playbook)** playbook `ome.application.ome_application_network_webserver` **OME application network webserver port changed tracking (playbook)** playbook `ome.application.ome_application_network_webserver_port_changed_trackin` **OME application security settings (playbook)** playbook `ome.application.ome_application_security_settings`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Manage OME users, directory services and sessions

Description	Create OME users, connect Active Directory and LDAP groups and manage console sessions.

Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OME active directory** `ome_active_directory` **OME domain user groups** `ome_domain_user_groups` **OME sessions** `ome_session` **OME user** `ome_user`, `ome_user_info` **OME active directory (playbook)** playbook `ome.ome_active_directory` **OME domain user groups (playbook)** playbook `ome.ome_domain_user_groups` **OME session (playbook)** playbook `ome.ome_session` **OME user (playbook)** playbook `ome.user.ome_user` **OME user info (playbook)** playbook `ome.user.ome_user_info`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Manage alert policies and event subscriptions

Description	Define OME alert policies and look up their actions, categories and message IDs, and manage Redfish event subscriptions.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OME alert policies** `ome_alert_policies`, `ome_alert_policies_info` **OME alert policies actions** `ome_alert_policies_actions_info` **OME alert policies category** `ome_alert_policies_category_info` **OME alert policies message ID** `ome_alert_policies_message_id_info` **Redfish event subscription** `redfish_event_subscription` **OME alert policies (playbook)** playbook `ome.alert_policy.ome_alert_policies` **OME alert policies actions info (playbook)** playbook `ome.alert_policy.ome_alert_policies_actions_info` **OME alert policies category info (playbook)** playbook `ome.alert_policy.ome_alert_policies_category_info` **OME alert policies info (playbook)** playbook `ome.alert_policy.ome_alert_policies_info` **OME alert policies message ID info (playbook)** playbook `ome.alert_policy.ome_alert_policies_message_id_info` **Redfish event subscription (playbook)** playbook `redfish.redfish_event_subscription`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

Use Case: Manage hosts in vCenter with OMEVV

Description	Maintain OMEVV baseline and firmware repository profiles, check cluster firmware compliance, update host firmware and query vCenter details.
Collection	`dellemc.openmanage` (Certified, Dell Technologies)
Key content	**OMEVV baseline profile** `omevv_baseline_profile`, `omevv_baseline_profile_info` **OMEVV firmware** `omevv_firmware` **OMEVV firmware compliance** `omevv_firmware_compliance_info` **OMEVV firmware repository profile** `omevv_firmware_repository_profile`, `omevv_firmware_repository_profile_info` **OMEVV vcenter** `omevv_vcenter_info` **OMEVV baseline profile (playbook)** playbook `omevv.omevv_baseline_profile` **OMEVV baseline profile info (playbook)** playbook `omevv.omevv_baseline_profile_info` **OMEVV firmware (playbook)** playbook `omevv.omevv_firmware` **OMEVV firmware compliance info (playbook)** playbook `omevv.omevv_firmware_compliance_info` **OMEVV firmware repository profile info (playbook)** playbook `omevv.omevv_firmware_repository_profile_info` **OMEVV firmware repository proile (playbook)** playbook `omevv.omevv_firmware_repository_proile` **OMEVV vcenter info (playbook)** playbook `omevv.omevv_vcenter_info`
Notes	• Capabilities are available as modules, roles and ready-to-run example playbooks for iDRAC, OpenManage Enterprise (OME), OpenManage Enterprise Modular, OMEVV and generic Redfish servers.

IBM PowerHA SystemMirror for AIX `enfence.powerha_aix`

Certified eNFence · version 1.3.3 · updated 2024-06-24 · 11 modules → 3 use cases

Use Case: Build and update PowerHA clusters

Description	Prepare AIX, create cluster configuration, update PowerHA and manage the cluster.
Collection	`enfence.powerha_aix` (Certified, eNFence)
Key content	**AIX preparation** role `cluster_prepare` **Cluster creation** role `cluster_create` **PowerHA update** role `cluster_update` **Clusters** `cluster` **PowerHA facts** `ha_facts`

Use Case: Manage resource groups and services

Description	Manage resource groups, application controllers, service IPs and file collections.
Collection	`enfence.powerha_aix` (Certified, eNFence)
Key content	**Resource groups** `rg` **Application controllers** `appcontroller` **Service IPs** `service_ip` **File collections** `fc`

Use Case: Manage cluster storage

Description	Manage volume groups, logical volumes, file systems and mirror pools, and find suitable physical volumes.
Collection	`enfence.powerha_aix` (Certified, eNFence)
Key content	**Volume groups** `vg` **Logical volumes** `lv` **File systems** `fs` **Mirror pools** `mp` **Physical volumes** `pv_info`

HPE iLO (Integrated Lights-Out) `hpe.ilo`

Certified HPE · version 1.0.41 · updated 2024-05-24 · 13 modules → 14 use cases

Use Case: Configure BIOS and boot settings

Description	Read and change BIOS attributes, boot mode, boot order and one-time boot, restore BIOS defaults, enable or disable PXE and verify applied settings.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Boot operations** `ilo_boot` **Disable pxe (playbook)** playbook `Bios.disable_pxe` **Enable pxe (playbook)** playbook `Bios.enable_pxe` **Get BIOS attributes (playbook)** playbook `Bios.get_bios_attributes` **Get BIOS boot order (playbook)** playbook `Bios.get_bios_boot_order` **Get BIOS registries (playbook)** playbook `Bios.get_bios_registries` **Get boot override (playbook)** playbook `Bios.get_boot_override` **Reboot system (playbook)** playbook `Bios.reboot_system` **Set BIOS attribute (playbook)** playbook `Bios.set_bios_attribute` **Set bootmode legacybios (playbook)** playbook `Bios.set_bootmode_legacybios` **Set bootmode uefi (playbook)** playbook `Bios.set_bootmode_uefi` **Set default BIOS settings (playbook)** playbook `Bios.set_default_bios_settings` **Set onetime boot (playbook)** playbook `Bios.set_onetime_boot` **Verify BIOS attributes (playbook)** playbook `Bios.verify_bios_attributes` **Get boot settings (playbook)** playbook `Network.get_boot_settings` **Verify uefi boot order (playbook)** playbook `Network.verify_uefi_boot_order` **Change BIOS attribute (role)** role `changbiosattr` **Get BIOS registries (role)** role `get_bios_registries` **Get boot settings (role)** role `get_boot_settings` **Get BIOS attributes (role)** role `getbiosattr` **Get boot order (role)** role `getbootorder` **Get boot override (role)** role `getbootoverride` **Set default BIOS settings (role)** role `setbiosdefault` **Set one-time boot (role)** role `setonetimeboot` **Verify BIOS attributes (role)** role `verify_bios_attributes` **Verify uefi boot order (role)** role `verify_uefi_boot_order`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Control server power

Description	Power servers on, off or restart them gracefully or by force, perform cold boots and wait for reboots to complete.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Power operations** `ilo_power` **Get server poststate (playbook)** playbook `Power.get_server_poststate` **Power force off (playbook)** playbook `Power.power_force_off` **Power graceful restart (playbook)** playbook `Power.power_graceful_restart` **Power graceful shutdown (playbook)** playbook `Power.power_graceful_shutdown` **Power on (playbook)** playbook `Power.power_on` **Set cold boot (playbook)** playbook `Power.set_cold_boot` **Wait for iLO reboot completion (playbook)** playbook `Power.wait_for_ilo_reboot_completion` **Get server poststate (role)** role `get_server_poststate` **Force power off (role)** role `powerforceoff` **Graceful shutdown (role)** role `powergracefullshutdown` **Power on (role)** role `poweron` **Restart (role)** role `powerreboot` **Set cold boot (role)** role `set_cold_boot` **Reboot system (role)** role `systemreboot` **Wait for iLO reboot completion (role)** role `wait_for_ilo_reboot_completion`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Update firmware and install packages

Description	Upload and flash firmware and BIOS images, update through install sets, check update status and install smart components and packages.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Firmware operations** `ilo_firmware` **Package install (playbook)** playbook `RLCP.package_install` **Smart comp install (playbook)** playbook `RLCP.smart_comp_install` **BIOS flash (playbook, UpdateService.DL)** playbook `UpdateService.DL.Bios_flash` **Flashfwpkg (playbook, UpdateService.DL)** playbook `UpdateService.DL.Flashfwpkg` **Flashfwpkgilo (playbook, UpdateService.DL)** playbook `UpdateService.DL.Flashfwpkgilo` **Upload comp (playbook, UpdateService.DL)** playbook `UpdateService.DL.Upload_comp` **BIOS flash (playbook, UpdateService.RL)** playbook `UpdateService.RL.Bios_flash` **Flashfwpkg (playbook, UpdateService.RL)** playbook `UpdateService.RL.Flashfwpkg` **FlashfwpkgUBM (playbook)** playbook `UpdateService.RL.FlashfwpkgUBM` **Flashfwpkgilo (playbook, UpdateService.RL)** playbook `UpdateService.RL.Flashfwpkgilo` **Upload comp (playbook, UpdateService.RL)** playbook `UpdateService.RL.Upload_comp` **Firmware upload (playbook)** playbook `UpdateService.firmware_upload` **Get firmware status (playbook)** playbook `UpdateService.get_firmware_status` **Update firmware through install set (playbook)** playbook `UpdateService.update_firmware_through_install_set` **Update firmware with upload (playbook)** playbook `UpdateService.update_firmware_with_upload` **Firmware upload (role)** role `firmware_upload` **Flash firmware package (role)** role `flashfwpkg` **Get firmware status (role)** role `get_firmware_status` **Install package (RLCP) (role)** role `rlcpinstall` **Install smart component (role)** role `smartcompinstall` **Update firmware through install set (role)** role `update_firmware_through_install_set` **Update firmware with upload (role)** role `update_firmware_with_upload` **Upload component and flash (role)** role `uploadcomp`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Inventory server hardware and software

Description	Collect system, CPU, memory, disk, NIC, PCI, fan, PSU, firmware and software inventory and store it as JSON.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Device operations** `ilo_device` **Redfish server information** `ilo_redfish_info` **Get device inventory info (playbook)** playbook `Chassis.get_device_inventory_info` **Get CPU inventory (playbook)** playbook `Inventory.get_cpu_inventory` **Get disk inventory (playbook)** playbook `Inventory.get_disk_inventory` **Get fan inventory (playbook)** playbook `Inventory.get_fan_inventory` **Get firmware inventory (playbook)** playbook `Inventory.get_firmware_inventory` **Get firmware update methods (playbook)** playbook `Inventory.get_firmware_update_methods` **Get memory inventory (playbook)** playbook `Inventory.get_memory_inventory` **Get NIC inventory (playbook)** playbook `Inventory.get_nic_inventory` **Get psu inventory (playbook)** playbook `Inventory.get_psu_inventory` **Get sessions inventory (playbook)** playbook `Inventory.get_sessions_inventory` **Get software inventory (playbook)** playbook `Inventory.get_software_inventory` **Get storage cont inventory (playbook)** playbook `Inventory.get_storage_cont_inventory` **Get system inventory (playbook)** playbook `Inventory.get_system_inventory` **Get system inventory all (playbook)** playbook `Inventory.get_system_inventory_all` **Get system inventory default (playbook)** playbook `Inventory.get_system_inventory_default` **Get volume inventory (playbook)** playbook `Inventory.get_volume_inventory` **Get network adapter details (playbook)** playbook `Network.get_network_adapter_details` **Get pci device details (playbook)** playbook `Network.get_pci_device_details` **Get pci slot details (playbook)** playbook `Network.get_pci_slot_details` **Get device inventory info (role)** role `get_device_inventory_info` **Get network adapter details (role)** role `get_network_adapter_details` **Get pci device details (role)** role `get_pci_device_details` **Get pci slot details (role)** role `get_pci_slot_details` **Get software inventory (role)** role `get_software_inventory` **Get all system inventory (role)** role `getallsysinven` **Get CPU inventory (role)** role `getcpuinven` **Get default system inventory (role)** role `getdefsysinv` **Get disk inventory (role)** role `getdiskinven` **Get fan inventory (role)** role `getfaninven` **Get firmware inventory (role)** role `getfirminven` **Get firmware update methods (role)** role `getfirmupdate` **Get memory inventory (role)** role `getmeminven` **Get NIC inventory (role)** role `getnicinven` **Get PSU inventory (role)** role `getpsuinven` **Get sessions (role)** role `getsessions` **Get storage controller inventory (role)** role `getstgctrlinv` **Get volume inventory (role)** role `getvolumeinven` **Get system inventory (role)** role `systeminven`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Monitor chassis power, thermals and indicator LEDs

Description	Report chassis inventory, power and thermal readings and switch the chassis indicator LED on or off.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Get chassis inventory (playbook)** playbook `Chassis.get_chassis_inventory` **Get chassis power (playbook)** playbook `Chassis.get_chassis_power` **Get chassis thermals (playbook)** playbook `Chassis.get_chassis_thermals` **Indicator LED off (playbook)** playbook `Chassis.indicator_led_off` **Indicator LED on (playbook)** playbook `Chassis.indicator_led_on` **Get chassis inventory (role)** role `getchassinven` **Get chassis thermals (role)** role `getchassistherm` **Get chassis power (role)** role `getchasspower` **Indicator LED off (role)** role `ledoff` **Indicator LED on (role)** role `ledon`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Configure server storage and logical drives

Description	Create, verify and delete logical drives and volumes, query physical drives and drive operating mode, and securely erase drives.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Storage operations** `ilo_storage` **Create logical drives (playbook)** playbook `Storage.create_logical_drives` **Create logical drives with particular physical drives (playbook)** playbook `Storage.create_logical_drives_with_particular_physical_drives` **Delete all logical drives (playbook)** playbook `Storage.delete_all_logical_drives` **Delete specified logical drives (playbook)** playbook `Storage.delete_specified_logical_drives` **Delete volumes (playbook)** playbook `Storage.delete_volumes` **Erase physical drives (playbook)** playbook `Storage.erase_physical_drives` **Get drive operating mode (playbook)** playbook `Storage.get_drive_operating_mode` **Get logical drives (playbook)** playbook `Storage.get_logical_drives` **Get physical drives (playbook)** playbook `Storage.get_physical_drives` **Get specified logical drives (playbook)** playbook `Storage.get_specified_logical_drives` **Get USB info (playbook)** playbook `Storage.get_usb_info` **Verify logical drives (playbook)** playbook `Storage.verify_logical_drives` **Verify specified logical drives (playbook)** playbook `Storage.verify_specified_logical_drives` **Create logical drives (role)** role `create_logical_drives` **Create logical drives with particular physical drives (role)** role `create_logical_drives_with_particular_physical_drives` **Create volume (role)** role `create_volume` **Delete all logical drives (role)** role `delete_all_logical_drives` **Delete specified logical drives (role)** role `delete_specified_logical_drives` **Delete volumes (role)** role `delete_volumes` **Erase physical drives (role)** role `erase_physical_drives` **Get drive operating mode (role)** role `get_drive_operating_mode` **Get logical drives (role)** role `get_logical_drives` **Get physical drives (role)** role `get_physical_drives` **Get specified logical drives (role)** role `get_specified_logical_drives` **Get USB info (role)** role `get_usb_info` **Verify logical drives (role)** role `verify_logical_drives` **Verify specified logical drives (role)** role `verify_specified_logical_drives`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Manage iLO user accounts and sessions

Description	Add, delete and list iLO users, change passwords, user names and roles, check user privileges and open and close sessions.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Adduser (playbook)** playbook `User.adduser` **Check user privileges (playbook)** playbook `User.check_user_privileges` **Deluser (playbook)** playbook `User.deluser` **Listusers (playbook)** playbook `User.listusers` **Updatepass (playbook)** playbook `User.updatepass` **Updateusername (playbook)** playbook `User.updateusername` **Updateuserrole (playbook)** playbook `User.updateuserrole` **Add user (role)** role `adduser` **Check user privileges (role)** role `check_user_privileges` **Delete user (role)** role `deluser` **List all users (role)** role `listallusers` **Log in (create session) (role)** role `login` **Log out (delete session) (role)** role `logout` **Update password (role)** role `updatepass` **Update user role (role)** role `updaterole` **Update user name (role)** role `updateusername`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Manage certificates and security settings

Description	Enable certificate login, import trusted CA certificates, map certificates to users and configure Secure Boot and SPDM.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Security operations** `ilo_security` **Enable certificate login (playbook)** playbook `Security.enable_certificate_login` **Get trusted ca certificates (playbook)** playbook `Security.get_trusted_ca_certificates` **Import trusted ca (playbook)** playbook `Security.import_trusted_ca` **Map user certificate (playbook)** playbook `Security.map_user_certificate` **Set secure boot (playbook)** playbook `Security.set_secure_boot` **Set spdm settings (playbook)** playbook `Security.set_spdm_settings` **Enable certificate login (role)** role `enable_certificate_login` **Get trusted ca certificates (role)** role `get_trusted_ca_certificates` **Import trusted ca (role)** role `import_trusted_ca` **Map user certificate (role)** role `map_user_certificate` **Set secure boot (role)** role `set_secure_boot` **Set spdm settings (role)** role `set_spdm_settings`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Configure iLO network, DNS and time

Description	Set the iLO hostname, domain, DNS servers, NIC settings, WINS registration, NTP servers and time zone, and read network protocols.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Network operations** `ilo_network` **Config hostname (playbook)** playbook `Manager.config_hostname` **Disable winsreg (playbook)** playbook `Manager.disable_winsreg` **Get host interfaces (playbook)** playbook `Manager.get_host_interfaces` **Get hostname (playbook)** playbook `Manager.get_hostname` **Get manager NIC inventory (playbook)** playbook `Manager.get_manager_nic_inventory` **Get network protocols (playbook)** playbook `Manager.get_network_protocols` **ILO nicsettings (playbook)** playbook `Manager.ilo_nicsettings` **Set DNS (playbook)** playbook `Manager.set_dns` **Set ntpservers (playbook)** playbook `Manager.set_ntpservers` **Set timezone (playbook)** playbook `Manager.set_timezone` **Configure iLO hostname (role)** role `confighostname` **Disable WINS registration (role)** role `disablewinsreg` **Get host interfaces (role)** role `get_host_interfaces` **Get hostname (role)** role `get_hostname` **Get network protocols (role)** role `get_network_protocols` **Get manager NIC inventory (role)** role `getmnicinven` **Set DNS (role)** role `setdns` **Set domain name (role)** role `setdomainname` **Set NTP servers (role)** role `setntpservers` **Set time zone (role)** role `settimezone`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Back up, restore and reset iLO

Description	Back up and restore iLO configuration, manage backup files, restart the manager and perform a factory reset.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Delete iLO backup files (playbook)** playbook `Manager.delete_ilo_backup_files` **Get iLO backup files (playbook)** playbook `Manager.get_ilo_backup_files` **ILO backup (playbook)** playbook `Manager.ilo_backup` **ILO factory reset (playbook)** playbook `Manager.ilo_factory_reset` **ILO restore (playbook)** playbook `Manager.ilo_restore` **Restart manager (playbook)** playbook `Manager.restart_manager` **Delete iLO backup files (role)** role `delete_ilo_backup_files` **Get iLO backup files (role)** role `get_ilo_backup_files` **ILO backup (role)** role `ilo_backup` **ILO factory reset (role)** role `ilo_factory_reset` **ILO restore (role)** role `ilo_restore` **Restart iLO manager (role)** role `iloreset`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Monitor iLO health and logs

Description	Report manager health and inventory, read and clear manager logs and list mounted virtual media.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Management operations** `ilo_manage` **Clear logs (playbook)** playbook `Manager.clear_logs` **Get health report (playbook)** playbook `Manager.get_health_report` **Get manager inventory (playbook)** playbook `Manager.get_manager_inventory` **Get manager logs (playbook)** playbook `Manager.get_manager_logs` **Get virtual media (playbook)** playbook `Manager.get_virtual_media` **Clear manager logs (role)** role `cleariellogs` **Get health report (role)** role `get_health_report` **Get manager inventory (role)** role `get_manager_inventory` **Get manager logs (role)** role `getiellogs` **Get virtual media info (role)** role `getvirtmediainfo`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Configure SNMP alerts and users

Description	Create, update and delete SNMP alert destinations and SNMPv3 users.
Collection	`hpe.ilo` (Certified, HPE)

Key content	**SNMP operations** `ilo_snmp` **Create SNMP alert destinations (playbook)** playbook `SNMP.create_snmp_alert_destinations` **Create snmpv3 users (playbook)** playbook `SNMP.create_snmpv3_users` **Delete all SNMP alert destinations (playbook)** playbook `SNMP.delete_all_snmp_alert_destinations` **Delete all snmpv3 users (playbook)** playbook `SNMP.delete_all_snmpv3_users` **Delete specified snmpv3 users (playbook)** playbook `SNMP.delete_specified_snmpv3_users` **Get SNMP alert destinations (playbook)** playbook `SNMP.get_snmp_alert_destinations` **Get snmpv3 users (playbook)** playbook `SNMP.get_snmpv3_users` **Update snmpv3 users (playbook)** playbook `SNMP.update_snmpv3_users` **Create SNMP alert destinations (role)** role `create_snmp_alert_destinations` **Create snmpv3 users (role)** role `create_snmpv3_users` **Delete all SNMP alert destinations (role)** role `delete_all_snmp_alert_destinations` **Delete all snmpv3 users (role)** role `delete_all_snmpv3_users` **Delete specified snmpv3 users (role)** role `delete_specified_snmpv3_users` **Get SNMP alert destinations (role)** role `get_snmp_alert_destinations` **Get snmpv3 users (role)** role `get_snmpv3_users` **Update snmpv3 users (role)** role `update_snmpv3_users`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Run Redfish commands and OEM configuration

Description	Send Redfish commands and set HPE OEM configuration attributes and firmware update commands on iLO.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Firmware update commands** `ilo_fwupdate_command` **Redfish commands** `ilo_redfish_command` **Redfish configuration attributes** `ilo_redfish_config`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

Use Case: Collect results and run example automation

Description	Helper roles that store task results as JSON and an example playbook set for automation testing.
Collection	`hpe.ilo` (Certified, HPE)
Key content	**Automation test playbook** playbook `automation` **Copy results to JSON file (role)** role `copyresulttoop` **Create JSON output file (role)** role `creatoutput` **Example playbooks role** role `playbooks`
Notes	• Modules use the iLO Redfish API; the bundled roles and example playbooks cover the same operations one task at a time.

HPE OneView `hpe.oneview`

Certified HPE · version 11.4.0 · updated 2026-08-13 · 102 modules → 9 use cases

Use Case: Configure the OneView appliance and its sessions

Description	Set appliance time and locale, network interfaces, proxy, SSH access, SNMP destinations and users, manage server certificates, and open or close API sessions.
Collection	`hpe.oneview` (Certified, HPE)
Key content	**Time configuration** `oneview_appliance_configuration_timeconfig_facts` **Time and locale** `oneview_appliance_time_and_locale_configuration`, `oneview_appliance_time_and_locale_configuration_facts` **Network interface information** `oneview_appliance_network_interface_facts` **Network interfaces** `oneview_appliance_network_interfaces` **Proxy configuration** `oneview_appliance_proxy_configuration`, `oneview_appliance_proxy_configuration_facts` **SSH access** `oneview_appliance_ssh_access`, `oneview_appliance_ssh_access_facts` **SNMPv1 trap destinations** `oneview_appliance_device_snmp_v1_trap_destinations`, `oneview_appliance_device_snmp_v1_trap_destinations_facts` **SNMPv3 trap destinations** `oneview_appliance_device_snmp_v3_trap_destinations`, `oneview_appliance_device_snmp_v3_trap_destinations_facts` **SNMPv3 users** `oneview_appliance_device_snmp_v3_users`, `oneview_appliance_device_snmp_v3_users_facts` **Server certificates** `oneview_certificates_server`, `oneview_certificates_server_facts` **API versions** `oneview_version_facts` **Login sessions** `oneview_get_session_id` **Session logout** `oneview_logout_session` **Time configuration facts role** role `oneview_appliance_configuration_timeconfig_facts` **Time and locale role** role `oneview_appliance_time_and_locale_configuration` **Time and locale facts role** role `oneview_appliance_time_and_locale_configuration_facts` **Network interface information facts role** role `oneview_appliance_network_interface_facts` **Network interfaces role** role `oneview_appliance_network_interfaces` **Proxy configuration role** role `oneview_appliance_proxy_configuration` **Proxy configuration facts role** role `oneview_appliance_proxy_configuration_facts` **SSH access role** role `oneview_appliance_ssh_access` **SSH access facts role** role `oneview_appliance_ssh_access_facts` **SNMPv1 trap destinations role** role `oneview_appliance_device_snmp_v1_trap_destination` **SNMPv1 trap destinations facts role** role `oneview_appliance_device_snmp_v1_trap_destination_facts` **SNMPv3 trap destinations role** role `oneview_appliance_device_snmp_v3_trap_destination` **SNMPv3 trap destinations facts role** role `oneview_appliance_device_snmp_v3_trap_destination_facts` **SNMPv3 users role** role `oneview_appliance_device_snmp_v3_users` **SNMPv3 users facts role** role `oneview_appliance_device_snmp_v3_users_facts` **Server certificates role** role `oneview_certificates_server` **Server certificates facts role** role `oneview_certificates_server_facts` **API versions facts role** role `oneview_version_facts`

Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Manage users, scopes, labels and tasks

Description	Create OneView users, group resources with scopes and labels, and query appliance tasks.
Collection	`hpe.oneview` (Certified, HPE)
Key content	**Users** `oneview_user`, `oneview_user_facts` **Scopes** `oneview_scope`, `oneview_scope_facts` **Labels** `oneview_label`, `oneview_label_facts` **Tasks** `oneview_task`, `oneview_task_facts` **Users role** role `oneview_user` **Users facts role** role `oneview_user_facts` **Scopes role** role `oneview_scope` **Scopes facts role** role `oneview_scope_facts` **Labels role** role `oneview_label` **Labels facts role** role `oneview_label_facts` **Tasks role** role `oneview_task` **Tasks facts role** role `oneview_task_facts`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Onboard and manage enclosures and server hardware

Description	Add and manage enclosures, enclosure groups, logical enclosures, drive enclosures, rack managers and server hardware.
Collection	`hpe.oneview` (Certified, HPE)
Key content	**Enclosures** `oneview_enclosure`, `oneview_enclosure_facts` **Enclosure groups** `oneview_enclosure_group`, `oneview_enclosure_group_facts` **Logical enclosures** `oneview_logical_enclosure`, `oneview_logical_enclosure_facts` **Drive enclosures** `oneview_drive_enclosure`, `oneview_drive_enclosure_facts` **Rack managers** `oneview_rack_manager`, `oneview_rack_manager_facts` **Server hardware** `oneview_server_hardware`, `oneview_server_hardware_facts` **Server hardware types** `oneview_server_hardware_type`, `oneview_server_hardware_type_facts` **Enclosures role** role `oneview_enclosure` **Enclosures facts role** role `oneview_enclosure_facts` **Enclosure groups role** role `oneview_enclosure_group` **Enclosure groups facts role** role `oneview_enclosure_group_facts` **Logical enclosures role** role `oneview_logical_enclosure` **Logical enclosures facts role** role `oneview_logical_enclosure_facts` **Drive enclosures role** role `oneview_drive_enclosure` **Drive enclosures facts role** role `oneview_drive_enclosure_facts` **Rack managers role** role `oneview_rack_manager` **Rack managers facts role** role `oneview_rack_manager_facts` **Server hardware role** role `oneview_server_hardware` **Server hardware facts role** role `oneview_server_hardware_facts` **Server hardware types role** role `oneview_server_hardware_type` **Server hardware types facts role** role `oneview_server_hardware_type_facts`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Define and apply server profiles

Description	Create server profiles and templates, and manage hypervisor managers and hypervisor cluster profiles.
Collection	`hpe.oneview` (Certified, HPE)
Key content	**Server profiles** `oneview_server_profile`, `oneview_server_profile_facts` **Server profile templates** `oneview_server_profile_template`, `oneview_server_profile_template_facts` **Hypervisor managers** `oneview_hypervisor_manager`, `oneview_hypervisor_manager_facts` **Hypervisor cluster profiles** `oneview_hypervisor_cluster_profile`, `oneview_hypervisor_cluster_profile_facts` **Server profiles role** role `oneview_server_profile` **Server profiles facts role** role `oneview_server_profile_facts` **Server profile templates role** role `oneview_server_profile_template` **Server profile templates facts role** role `oneview_server_profile_template_facts` **Hypervisor managers role** role `oneview_hypervisor_manager` **Hypervisor managers facts role** role `oneview_hypervisor_manager_facts` **Hypervisor cluster profiles role** role `oneview_hypervisor_cluster_profile` **Hypervisor cluster profiles facts role** role `oneview_hypervisor_cluster_profile_facts`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Configure networks, interconnects and ID pools

Description	Manage Ethernet, Fibre Channel and FCoE networks, network sets, uplink sets, interconnects, logical interconnects and groups, connection templates, and ID pools with IPv4 subnets and ranges.
Collection	`hpe.oneview` (Certified, HPE)

Key content	**Ethernet networks** `oneview_ethernet_network`, `oneview_ethernet_network_facts` **Fibre Channel networks** `oneview_fc_network`, `oneview_fc_network_facts` **FCoE networks** `oneview_fcoe_network`, `oneview_fcoe_network_facts` **Network sets** `oneview_network_set`, `oneview_network_set_facts` **Connection templates** `oneview_connection_template`, `oneview_connection_template_facts` **Uplink sets** `oneview_uplink_set`, `oneview_uplink_set_facts` **Interconnects** `oneview_interconnect`, `oneview_interconnect_facts` **Interconnect types** `oneview_interconnect_type_facts` **Logical interconnects** `oneview_logical_interconnect`, `oneview_logical_interconnect_facts` **Logical interconnect groups** `oneview_logical_interconnect_group`, `oneview_logical_interconnect_group_facts` **ID pools** `oneview_id_pools`, `oneview_id_pools_facts` **ID pool IPv4 ranges** `oneview_id_pools_ipv4_range`, `oneview_id_pools_ipv4_range_facts` **ID pool IPv4 subnets** `oneview_id_pools_ipv4_subnet`, `oneview_id_pools_ipv4_subnet_facts` **Ethernet networks role** role `oneview_ethernet_network` **Ethernet networks facts role** role `oneview_ethernet_network_facts` **Fibre Channel networks role** role `oneview_fc_network` **Fibre Channel networks facts role** role `oneview_fc_network_facts` **FCoE networks role** role `oneview_fcoe_network` **FCoE networks facts role** role `oneview_fcoe_network_facts` **Network sets role** role `oneview_network_set` **Network sets facts role** role `oneview_network_set_facts` **Connection templates role** role `oneview_connection_template` **Connection templates facts role** role `oneview_connection_template_facts` **Uplink sets role** role `oneview_uplink_set` **Uplink sets facts role** role `oneview_uplink_set_facts` **Interconnects role** role `oneview_interconnect` **Interconnects facts role** role `oneview_interconnect_facts` **Interconnect types facts role** role `oneview_interconnect_type_facts` **Logical interconnects role** role `oneview_logical_interconnect` **Logical interconnects facts role** role `oneview_logical_interconnect_facts` **Logical interconnect groups role** role `oneview_logical_interconnect_group` **Logical interconnect groups facts role** role `oneview_logical_interconnect_group_facts` **ID pools role** role `oneview_id_pools` **ID pools facts role** role `oneview_id_pools_facts` **ID pool IPv4 ranges role** role `oneview_id_pools_ipv4_range` **ID pool IPv4 ranges facts role** role `oneview_id_pools_ipv4_range_facts` **ID pool IPv4 subnets role** role `oneview_id_pools_ipv4_subnet` **ID pool IPv4 subnets facts role** role `oneview_id_pools_ipv4_subnet_facts`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Provision storage systems and volumes

Description	Register storage systems and SAN managers, manage storage pools, volumes and volume templates, and remove extra volume presentations from server profiles.
Collection	`hpe.oneview` (Certified, HPE)
Key content	**Storage systems** `oneview_storage_system`, `oneview_storage_system_facts` **SAN managers** `oneview_san_manager`, `oneview_san_manager_facts` **Storage pools** `oneview_storage_pool`, `oneview_storage_pool_facts` **Storage volume templates** `oneview_storage_volume_template`, `oneview_storage_volume_template_facts` **Volumes** `oneview_volume`, `oneview_volume_facts` **Volume attachments** `oneview_storage_volume_attachment`, `oneview_storage_volume_attachment_facts` **Storage systems role** role `oneview_storage_system` **Storage systems facts role** role `oneview_storage_system_facts` **SAN managers role** role `oneview_san_manager` **SAN managers facts role** role `oneview_san_manager_facts` **Storage pools role** role `oneview_storage_pool` **Storage pools facts role** role `oneview_storage_pool_facts` **Storage volume templates role** role `oneview_storage_volume_template` **Storage volume templates facts role** role `oneview_storage_volume_template_facts` **Volumes role** role `oneview_volume` **Volumes facts role** role `oneview_volume_facts` **Volume attachments role** role `oneview_storage_volume_attachment` **Volume attachments facts role** role `oneview_storage_volume_attachment_facts`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Manage SAS interconnects and logical JBODs

Description	Manage SAS interconnects, logical interconnects and groups, and SAS logical JBODs and their attachments.
Collection	`hpe.oneview` (Certified, HPE)
Key content	**SAS interconnects** `oneview_sas_interconnect`, `oneview_sas_interconnect_facts` **SAS interconnect types** `oneview_sas_interconnect_type_facts` **SAS logical interconnects** `oneview_sas_logical_interconnect`, `oneview_sas_logical_interconnect_facts` **SAS logical interconnect groups** `oneview_sas_logical_interconnect_group`, `oneview_sas_logical_interconnect_group_facts` **SAS logical JBODs** `oneview_sas_logical_jbod`, `oneview_sas_logical_jbod_facts` **SAS logical JBOD attachments** `oneview_sas_logical_jbod_attachment_facts` **SAS interconnects role** role `oneview_sas_interconnect` **SAS interconnects facts role** role `oneview_sas_interconnect_facts` **SAS interconnect types facts role** role `oneview_sas_interconnect_type_facts` **SAS logical interconnects role** role `oneview_sas_logical_interconnect` **SAS logical interconnects facts role** role `oneview_sas_logical_interconnect_facts` **SAS logical interconnect groups role** role `oneview_sas_logical_interconnect_group` **SAS logical interconnect groups facts role** role `oneview_sas_logical_interconnect_group_facts` **SAS logical JBODs role** role `oneview_sas_logical_jbod` **SAS logical JBODs facts role** role `oneview_sas_logical_jbod_facts` **SAS logical JBOD attachments facts role** role `oneview_sas_logical_jbod_attachment_facts`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Manage firmware and repositories

Description	Upload firmware bundles, remove firmware drivers and manage the repositories that hold them.

Collection	`hpe.oneview` (Certified, HPE)
Key content	**Firmware bundles** `oneview_firmware_bundle` **Firmware drivers** `oneview_firmware_driver`, `oneview_firmware_driver_facts` **Repositories** `oneview_repositories`, `oneview_repositories_facts` **Firmware bundles role** role `oneview_firmware_bundle` **Firmware drivers role** role `oneview_firmware_driver` **Firmware drivers facts role** role `oneview_firmware_driver_facts` **Repositories role** role `oneview_repositories` **Repositories facts role** role `oneview_repositories_facts`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

Use Case: Run OneView automation with helper roles and playbooks

Description	Install role dependencies, drive several OneView resources from one dynamic role, and run the collection's example automation playbook.
Collection	`hpe.oneview` (Certified, HPE)
Key content	**Role dependency installer** role `dependencies_list` **Dynamic multi-resource role** role `oneview_dynamic_role` **OneView automation playbook** playbook `automation`
Notes	• Each role wraps the matching module; roles ending in _facts only read information.

IBM z/OS Event-Driven Ansible `ibm.ibm_eda_zos`

Validated IBM · version 1.1.0 · updated 2026-10-02 · 0 modules → 3 use cases

Use Case: Parse and diagnose zSecure alerts

Description	Extract zSecure alert attributes from events and capture SMF flood diagnostics.
Collection	`ibm.ibm_eda_zos` (Validated, IBM)
Key content	**zSecure alert attributes** eda event filter `security_alerts` **SMF flood diagnostics** playbook `security.1607_diagnostic`

Use Case: Investigate and contain RACF security events

Description	Gather RACF user and password policy details, quarantine or unquarantine TSO users, remove UID access and issue SETROPTS commands.
Collection	`ibm.ibm_eda_zos` (Validated, IBM)
Key content	**RACF user details** playbook `security.gather_listuser_information` **Password threshold breach response** playbook `security.gather_password_policy_information` **Quarantine a TSO user** playbook `security.quarantine_user` **Unquarantine a TSO user** playbook `security.unquarantine_user` **Remove UID access** playbook `security.remove_uid_access` **SETROPTS JES command** playbook `security.setr_jes_batchallracf`

Use Case: Notify teams about alerts

Description	Send alert emails, SMF flood emails and Slack messages.
Collection	`ibm.ibm_eda_zos` (Validated, IBM)
Key content	**Alert email** playbook `security.send_alert_email` **SMF flood alert email** playbook `security.send_1607_alert_email` **Slack notification** playbook `security.send_slack_message`

IBM Z Hardware Management Console `ibm.ibm_zhmc`

Certified IBM · version 1.11.1 · updated 2026-08-18 · 38 modules → 5 use cases

Use Case: Manage partitions in DPM mode

Description	Create and configure DPM partitions with their NICs, HBAs, virtual functions and crypto attachments, and run console commands in them.
Collection	`ibm.ibm_zhmc` (Certified, IBM)

Key content	**Partitions** `zhmc_partition`, `zhmc_partition_list` **Partition NICs** `zhmc_nic`, `zhmc_nic_list` **Partition HBAs** `zhmc_hba` **Virtual functions** `zhmc_virtual_function` **Crypto attachments** `zhmc_crypto_attachment` **Partition console commands** `zhmc_partition_command` **Partition console messages** `zhmc_partition_messages`

Use Case: Manage storage and adapters

Description	Manage adapters, storage groups, storage volumes and their attachment to partitions.
Collection	`ibm.ibm_zhmc` (Certified, IBM)
Key content	**Adapters** `zhmc_adapter`, `zhmc_adapter_list` **Storage groups** `zhmc_storage_group`, `zhmc_storage_group_list` **Storage group attachments** `zhmc_storage_group_attachment`, `zhmc_storage_group_attachment_list` **Storage volumes** `zhmc_storage_volume`, `zhmc_storage_volume_list`

Use Case: Manage LPARs and CPCs

Description	Manage CPCs, temporary processor capacity and classic-mode LPARs including console commands and messages.
Collection	`ibm.ibm_zhmc` (Certified, IBM)
Key content	**CPCs** `zhmc_cpc`, `zhmc_cpc_list` **Temporary processor capacity** `zhmc_cpc_capacity` **LPARs** `zhmc_lpar`, `zhmc_lpar_list` **LPAR console commands** `zhmc_lpar_command` **LPAR console messages** `zhmc_lpar_messages`

Use Case: Administer the HMC and its users

Description	Manage HMC users, roles, patterns, password rules, LDAP server definitions and the HMC console.
Collection	`ibm.ibm_zhmc` (Certified, IBM)
Key content	**HMC console** `zhmc_console` **Users** `zhmc_user`, `zhmc_user_list` **User roles** `zhmc_user_role`, `zhmc_user_role_list` **User patterns** `zhmc_user_pattern`, `zhmc_user_pattern_list` **Password rules** `zhmc_password_rule`, `zhmc_password_rule_list` **LDAP server definitions** `zhmc_ldap_server_definition`, `zhmc_ldap_server_definition_list`

Use Case: Connect to the HMC and gather versions

Description	Manage HMC sessions, send direct HTTP requests and retrieve HMC and CPC version facts.
Collection	`ibm.ibm_zhmc` (Certified, IBM)
Key content	**Sessions** `zhmc_session` **HTTP requests** `zhmc_http` **HMC and CPC versions** `zhmc_versions`

IBM CICS Transaction Server for z/OS `ibm.ibm_zos_cics`

Certified IBM · version 2.2.1 · updated 2025-09-05 · 15 modules → 3 use cases

Use Case: Create and maintain CICS region data sets

Description	Allocate and remove the CSD, global and local catalogs, auxiliary temporary storage, trace and dump data sets, local request queue and transient data data sets.
Collection	`ibm.ibm_zos_cics` (Certified, IBM)
Key content	**CICS system definition data set** `csd` **Global catalog** `global_catalog` **Local catalog** `local_catalog` **Auxiliary temporary storage** `aux_temp_storage` **Auxiliary trace** `aux_trace` **Transaction dump** `transaction_dump` **Local request queue** `local_request_queue` **Transient data intrapartition** `td_intrapartition`

Use Case: Start and stop CICS regions

Description	Create startup JCL and stop a CICS region.
Collection	`ibm.ibm_zos_cics` (Certified, IBM)
Key content	**Startup JCL** `region_jcl` **Stop region** `stop_region`

Use Case: Query and manage CICS resources through CMCI

Description	Query, create, update, delete and act on CICS and CICSPlex SM resources and definitions.
Collection	`ibm.ibm_zos_cics` (Certified, IBM)
Key content	**CICS resource queries** `cmci_get` **Create definitions** `cmci_create` **Update resources** `cmci_update` **Delete resources** `cmci_delete` **Resource actions** `cmci_action`

IBM z/OS `ibm.ibm_zos_core`

Certified IBM · version 2.1.0 · updated 2026-09-30 · 29 modules → 5 use cases

Use Case: Manage data sets and files

Description	Create and manage data sets, copy, fetch, find, archive and back up data, and edit text in data sets and USS files.
Collection	`ibm.ibm_zos_core` (Certified, IBM)
Key content	**Data sets** `zos_data_set` **Copy** `zos_copy` **Fetch** `zos_fetch` **Find** `zos_find` **Data set and file facts** `zos_stat` **Archive** `zos_archive` **Unarchive** `zos_unarchive` **Backup and restore** `zos_backup_restore` **Encoding** `zos_encode` **Line edits** `zos_lineinfile` **Block edits** `zos_blockinfile` **Pattern replacement** `zos_replace` **File system mounts** `zos_mount` **zFS resize** `zos_zfs_resize` **Volume initialization** `zos_volume_init` **Random data set names** filter `generate_data_set_name` **zos_stat field filter** filter `zos_stat_by_type`

Use Case: Submit and monitor jobs

Description	Submit JCL, query job status, display job output, run programs and manage started tasks.
Collection	`ibm.ibm_zos_core` (Certified, IBM)
Key content	**JCL submission** `zos_job_submit` **Job status** `zos_job_query` **Job output** `zos_job_output` **MVS programs** `zos_mvs_raw` **Scripts** `zos_script` **Started tasks** `zos_started_task` **Job status report** role `job_status`

Use Case: Run commands and operator actions

Description	Run TSO and operator commands and display messages that need operator action.
Collection	`ibm.ibm_zos_core` (Certified, IBM)
Key content	**TSO commands** `zos_tso_command` **Operator commands** `zos_operator` **Operator action messages** `zos_operator_action_query` **WTOR message filter** filter `wtor`

Use Case: Administer security and system configuration

Description	Manage RACF user and group profiles and APF-authorized libraries.
Collection	`ibm.ibm_zos_core` (Certified, IBM)
Key content	**RACF users and groups** `zos_user`, `zos_user_info` **APF libraries** `zos_apf`

Use Case: Gather facts and diagnostics

Description	Check connectivity and dependencies, gather z/OS system facts and diagnostic data, and build a report for migrating playbooks to v2.0.0.
Collection	`ibm.ibm_zos_core` (Certified, IBM)
Key content	**Connectivity check** `zos_ping` **System facts** `zos_gather_facts` **Diagnostics collection** role `gather_diagnostics` **Playbook upgrade report** role `playbook_upgrade_validator`

IBM IMS `ibm.ibm_zos_ims`

Certified IBM · version 1.4.0 · updated 2026-05-15 · 8 modules → 2 use cases

Use Case: Generate IMS definitions and manage the catalog

Description	Generate ACB, DBD and PSB definitions, populate and purge the IMS Catalog and submit DDL statements.
Collection	`ibm.ibm_zos_ims` (Certified, IBM)
Key content	**ACB generation** `ims_acb_gen` **DBD generation** `ims_dbd_gen` **PSB generation** `ims_psb_gen` **Catalog population** `ims_catalog_populate` **Catalog purge** `ims_catalog_purge` **DDL statements** `ims_ddl`

Use Case: Run IMS and DBRC commands

Description	Submit IMS and DBRC commands.
Collection	`ibm.ibm_zos_ims` (Certified, IBM)
Key content	**IMS commands** `ims_command` **DBRC commands** `ims_dbrc`

IBM Z System Automation `ibm.ibm_zos_sysauto`

Certified IBM · version 1.1.0 · updated 2023-10-02 · 0 modules → 1 use cases

Use Case: Manage dynamic resources in IBM Z System Automation

Description	Create and resume or delete dynamic resource instances.
Collection	`ibm.ibm_zos_sysauto` (Certified, IBM)
Key content	**Create dynamic resources** role `sa_create_dynamic_resource` **Delete dynamic resources** role `sa_delete_dynamic_resource`

IBM z/OSMF `ibm.ibm_zosmf`

Certified IBM · version 1.6.0 · updated 2026-02-18 · 3 modules → 4 use cases

Use Case: Authenticate and run workflows

Description	Authenticate with z/OSMF, operate workflows, complete them and run management services.
Collection	`ibm.ibm_zosmf` (Certified, IBM)
Key content	**Authentication** `zmf_authenticate` **Workflows** `zmf_workflow` **Workflow completion** role `zmf_workflow_complete` **Management services** role `zmf_zmsc_run_management_service` **Security requirement validation** `zmf_sca`

Use Case: Provision software with Cloud Provisioning

Description	Create, query, manage, provision and remove software instances from the CP&M catalog.
Collection	`ibm.ibm_zosmf` (Certified, IBM)

Key content	**Software templates** role `zmf_cpm_list_software_templates` **Provisioning** role `zmf_cpm_provision_software_service` **Create instances** role `zmf_cpm_create_software_instance` **Get instances** role `zmf_cpm_get_software_instance` **Manage instances** role `zmf_cpm_manage_software_instance` **Remove instances** role `zmf_cpm_remove_software_instance`

Use Case: Report on installed software and missing updates

Description	Query the software inventory and report on holds, missing critical updates, missing fix category updates, update search results and system UUIDs.
Collection	`ibm.ibm_zosmf` (Certified, IBM)
Key content	**CSI query** role `zmf_swmgmt_csi_query` **Holds by reason** role `zmf_swmgmt_holds_for_reason` **Missing critical updates** role `zmf_swmgmt_identify_missing_critical_updates` **Missing fix category updates** role `zmf_swmgmt_identify_missing_fixcat_updates` **Software update search** role `zmf_swmgmt_search_software_updates` **System UUID** role `zmf_swmgmt_zos_system_uuid`

Use Case: Apply software updates

Description	Start, resume, cancel and monitor software update processes and copy their output.
Collection	`ibm.ibm_zosmf` (Certified, IBM)
Key content	**Start update** role `zmf_swupdate_start` **Resume update** role `zmf_swupdate_resume` **Cancel update** role `zmf_swupdate_cancel` **Update status** role `zmf_swupdate_retrieve` **All update statuses** role `zmf_swupdate_retrieve_all` **Copy update output** role `zmf_swupdate_copy`

IBM AIX on Power `ibm.power_aix`

Certified IBM · version 2.3.1 · updated 2026-06-17 · 70 modules → 11 use cases

Use Case: Patch and update AIX software

Description	Install and update filesets, apply interim fixes, generate FLRTVC reports, download fixes from IBM Fix Central, and bootstrap DNF on AIX.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**Filesets (installp)** `installp` **Generic installer** `geninstall` **Install all updates** `install_all_updates` **Interim fixes (emgr)** `emgr` **FLRTVC security fix reports** `flrtvc` **SUMA fix downloads** `suma` **Installed software facts** `lpp_facts` **DNF bootstrap role** role `power_aix_bootstrap` **Fileset installation demo** playbook `demo_installp` **Update-all demo** playbook `demo_install_all_updates` **Interim fix demo** playbook `demo_emgr` **FLRTVC demo** playbook `demo_flrtvc` **FLRTVC with local patch server demo** playbook `demo_flrtvc_local_patch_server` **Sync ifixes to a web server demo** playbook `demo_shell_flrtvc_wget_ifix` **SUMA demo** playbook `demo_suma` **Installed software facts demo** playbook `demo_lpp_facts` **DNF package install demo** playbook `demo_dnf` **DNF bootstrap demo** playbook `demo_dnf_bootstrap` **DNF bootstrap from local repository demo** playbook `demo_dnf_bootstrap_local` **Update all hosts demo** playbook `demo_update-all-hosts`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Apply kernel and library updates without downtime

Description	Run live kernel updates and live library updates, and clean up failed live update operations.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**Live kernel update** `lku` **Live library update** `llvupdate` **Failed live update cleanup** `clvupdate` **Live kernel update role** role `live_kernel_update` **Live kernel update demo** playbook `demo_lku` **Live kernel update role demo** playbook `demo_aix_lku_role` **Live library update demo** playbook `demo_llvupdate` **Live update cleanup demo** playbook `demo_clvupdate`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Install, upgrade and migrate with NIM

Description	Set up NIM servers and resources, install and back up clients, upgrade AIX and VIOS, and migrate NIM masters or client OS levels.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**NIM operations** `nim` **NIM client operations** `nimclient` **NIM resources** `nim_resource` **NIM client backups** `nim_backup` **NIM FLRTVC fixes** `nim_flrtvc` **NIM SUMA downloads** `nim_suma` **Target disk selection** `nim_select_target_disk` **VIOS updates** `nim_updateios` **VIOS upgrades** `nim_upgradeios` **VIOS upgrades (viosupgrade)** `nim_viosupgrade` **VIOS alternate disk** `nim_vios_alt_disk` **VIOS health check** `nim_vios_hc` **Alternate disk migration role** role `nim_alt_disk_migration` **NIM master migration role** role `nim_master_migration` **VIOS health checker role** role `power_aix_vioshc` **NIM operations demo** playbook `demo_nim` **Alternate disk migration demo** playbook `demo_nim_alt_disk_migration` **NIM backup demo** playbook `demo_nim_backup` **NIM check demo** playbook `demo_nim_check` **NIM FLRTVC demo** playbook `demo_nim_flrtvc` **BOS install from mksysb demo** playbook `demo_nim_install` **NIM fileset install demo** playbook `demo_nim_install_filesets` **NIM master migration demo** playbook `demo_nim_master_migration` **NIM resource demo** playbook `demo_nim_resource` **NIM SUMA demo** playbook `demo_nim_suma` **VIOS update demo** playbook `demo_nim_updateios` **VIOS health check demo** playbook `demo_nim_vios_hc` **VIOS upgrade demo** playbook `demo_nim_viosupgrade` **NIM client demo** playbook `demo_nimclient` **VIOS health checker demo** playbook `demo_vioshc`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Back up and clone system images

Description	Back up volume groups, clone the root volume group to an alternate disk, and manage boot images and boot lists.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**Volume group backups** `backup` **Alternate rootvg disk** `alt_disk` **Boot images** `bosboot` **Boot list** `bootlist` **Data volume group backup demo** playbook `demo_backup_datavg` **Root volume group backup demo** playbook `demo_backup_rootvg` **Alternate disk demo** playbook `demo_alt_disk` **Boot image demo** playbook `demo_bosboot`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Manage storage, filesystems and devices

Description	Configure LVM volume groups and logical volumes, filesystems, mounts, paging space, dump devices and multipath devices, and encrypt logical volumes.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**Volume groups** `lvg` **Logical volumes** `lvol` **LVM facts** `lvm_facts` **Filesystems** `filesystem` **Mounts** `mount` **Paging space** `pagingspace` **System dump devices** `sysdumpdev` **Devices** `devices` **MPIO devices** `mpio` **Encryption information** `hdcrypt_facts` **Encryption authentication methods** `hdcrypt_auth` **Encrypt and decrypt volumes** `hdcrypt_conv` **PKS authentication and keys** `hdcrypt_pks` **Volume group demo** playbook `demo_lvg` **Logical volume demo** playbook `demo_lvol` **LVM facts demo** playbook `demo_lvm_facts` **Filesystem demo** playbook `demo_filesystem` **Mount demo** playbook `demo_mount` **Paging space demo** playbook `demo_pagingspace` **Dump device demo** playbook `demo_sysdumpdev` **Device defaults demo** playbook `demo_devices` **MPIO demo** playbook `demo_mpio` **MPIO demo (dynamic inventory)** playbook `dynamic_mpio` **Encryption authentication demo** playbook `demo_hdcrypt_auth` **Encryption conversion demo** playbook `demo_hdcrypt_conv` **Encryption facts demo** playbook `demo_hdcrypt_facts` **Encryption PKS demo** playbook `demo_hdcrypt_pks`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Configure networking and IPsec

Description	Set up TCP/IP, routes, filter rules, tunnels and IPsec, and control inetd services and the bootptab file.
Collection	`ibm.power_aix` (Certified, IBM)

Key content	**TCP/IP setup** `mktcpip` **Routes** `route` **Filter rules** `mkfilt` **Tunnels** `mktun` **IPsec tunnels role** role `ipsec` **inetd services role** role `inetd` **bootptab role** role `bootptab` **TCP/IP setup demo** playbook `demo_mktcpip` **Route demo** playbook `demo_route` **Filter rule demo** playbook `demo_mkfilt` **Tunnel demo** playbook `demo_mktun` **Tunnel demo (dynamic inventory)** playbook `dynamic_mktun` **IPsec tunnel demo** playbook `demo_setup_ipsec_tunnel`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Manage users, groups and password policy

Description	Create and modify users and groups, set password rules and hashes, and edit security stanza files.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**Users** `user` **Groups** `group` **Password hashing** `password_hash` **Password rules and policies** `password_rules_policies` **Stanza file attributes** `chsec` **User demo** playbook `demo_user` **Group demo** playbook `demo_group` **Password policy demo** playbook `demo_password_rules_policies` **Stanza file demo** playbook `demo_chsec`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Harden and audit systems

Description	Apply AIX security hardening settings and control the auditing subsystem.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**Security hardening** `aixpert` **Auditing** `audit` **Audit demo** playbook `demo_audit`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Tune and configure system settings

Description	Set kernel and component tunables, SMT mode, inittab entries, timezone, system configuration variables, and reboot machines.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**Tunables** `tunables` **Tunable files** `tunfile_mgmt` **SMT mode** `smtctl` **inittab entries** `inittab` **Timezone** `timezone_mgmt` **System configuration variables** `getconf` **Reboot** `reboot` **Tunables demo** playbook `demo_tunables` **Tunables demo (dynamic inventory)** playbook `dynamic_tunables` **Tunable file demo** playbook `demo_tunfile_mgmt` **Tunable file demo (dynamic inventory)** playbook `dynamic_tunfile_mgmt` **inittab demo** playbook `demo_inittab` **Timezone demo** playbook `demo_timezone_mgmt` **System configuration demo** playbook `demo_getconf` **Reboot demo** playbook `demo_reboot`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Monitor performance and diagnose problems

Description	Collect CPU, memory, I/O, network, Fibre Channel and process statistics, report and clear error log entries, gather LPAR facts and run snap.
Collection	`ibm.power_aix` (Certified, IBM)

Key content	**I/O statistics** `iostat` **Virtual memory statistics** `vmstat` **LPAR statistics** `lparstat` **LPAR facts** `lpar_facts` **Health monitoring (nmon)** `nmon` **Processes** `ps` **Ethernet statistics** `entstat` **Fibre Channel statistics** `fcstat` **Network statistics** `netstat` **Traceroute** `traceroute` **Error log reports** `errpt` **Error log cleanup** `errclear` **System snap data** `snap` **I/O statistics demo** playbook `demo_iostat` **Virtual memory statistics demo** playbook `demo_vmstat` **LPAR statistics demo** playbook `demo_lparstat` **LPAR facts demo** playbook `demo_lpar_facts` **nmon demo** playbook `demo_nmon` **Process demo** playbook `demo_ps` **Ethernet statistics demo** playbook `demo_entstat` **Fibre Channel statistics demo** playbook `demo_fcstat` **Network statistics demo** playbook `demo_netstat` **Traceroute demo** playbook `demo_traceroute` **Error log report demo** playbook `demo_errpt` **Error log cleanup demo** playbook `demo_errclear` **Snap demo** playbook `demo_snap`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

Use Case: Respond to AIX events with Event-Driven Ansible

Description	Watch CPU, filesystem and file changes over SSH and new IBM FLRT security fixes, and react through rulebooks.
Collection	`ibm.power_aix` (Certified, IBM)
Key content	**CPU utilization event source** eda event source `aix_cpu_watch` **Filesystem utilization event source** eda event source `aix_filesystem_watch` **File change event source** eda event source `aix_file_watch` **FLRT security fix event source** eda event source `flrt_monitor` **CPU watch rulebook demo** playbook `eda.demo_aix_cpu_watch` **Filesystem watch rulebook demo** playbook `eda.demo_aix_filesystem_watch` **File watch rulebook demo** playbook `eda.demo_aix_file_watch` **Basic FLRT monitoring** playbook `eda.rulebook_flrt_monitor_basic` **FLRT notification only** playbook `eda.rulebook_flrt_monitor_notification_only` **Severity-based FLRT monitoring** playbook `eda.rulebook_flrt_monitor_severity_based`
Notes	• Many demo playbooks show a single module with various options; they are grouped here with the module they exercise.

IBM Power HMC `ibm.power_hmc`

Certified IBM · version 1.17.0 · updated 2026-10-01 · 22 modules → 5 use cases

Use Case: Manage Power systems and firmware

Description	Power on and off managed systems, change hardware resources, update firmware and platform levels, and create serviceable events.
Collection	`ibm.power_hmc` (Certified, IBM)
Key content	**Managed systems** `power_system` **Firmware levels** `firmware_update` **Platform updates** `platform_update` **Serviceable events** `create_service_event` **Power server inventory** inventory `powervm_inventory` **Firmware update demo** playbook `demo_firmware_update`

Use Case: Manage logical partitions

Description	Create, activate, shut down, resize, migrate and profile PowerVM LPARs and install Linux on them.
Collection	`ibm.power_hmc` (Certified, IBM)
Key content	**LPAR instances** `powervm_lpar_instance` **Partition profiles** `powervm_partition_profile` **Dynamic resource changes** `powervm_dlpar` **LPAR migration** `powervm_lpar_migration` **Red Hat Linux install (PXE)** role `redhat_linux_install` **Install Linux** playbook `redhat_linux_install`

Use Case: Manage virtual I/O and networking

Description	Create Virtual I/O Servers, virtual switches, virtual networks, bridges and client network adapters, and report VIOS device mappings.
Collection	`ibm.power_hmc` (Certified, IBM)

Key content	**Virtual I/O Servers** `vios` **VIOS device mappings** `vios_mapping_facts` **Virtual switches** `powervm_virtual_switches` **Virtual networks** `powervm_virtual_network` **Virtual network bridges** `power_network_bridge` **Client network adapters** `powervm_client_network_adapter`

Use Case: Maintain and secure VIOS

Description	Update and upgrade VIOS, back it up, create alternate rootvg disks and apply firewall and hardening rules.
Collection	`ibm.power_hmc` (Certified, IBM)
Key content	**VIOS update and upgrade** `vios_update_upgrade` **VIOS backup** `vios_maintenance` **Alternate rootvg** `vios_alt_root_vg` **VIOS security hardening** `vios_secure`

Use Case: Administer the HMC

Description	Update the HMC, run HMC commands and manage users and password policies.
Collection	`ibm.power_hmc` (Certified, IBM)
Key content	**HMC update and upgrade** `hmc_update_upgrade` **HMC commands** `hmc_command` **HMC users** `hmc_user` **Password policies** `hmc_pwdpolicy` **Password policy** role `password_policy` **HMC user demo** playbook `demo_hmc_user` **Passwordless setup demo** playbook `demo_hmc_passwordless_setup` **Password policy playbook** playbook `roles_passpolicy_playbook`

IBM i (IBM Power) `ibm.power_ibmi`

Certified IBM · version 3.5.1 · updated 2026-09-14 · 62 modules → 12 use cases

Use Case: Run CL commands, SQL and scripts on IBM i

Description	Execute CL commands, SQL statements, sqlite3 queries and CL or SQL script files on IBM i, with ready-made sample playbooks.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**CL commands** `ibmi_cl_command` **CL-program-only commands** `ibmi_rtv_command` **Local CL/SQL scripts** `ibmi_script` **Remote CL/SQL scripts** `ibmi_script_execute` **SQL statements** `ibmi_sql_execute` **SQL queries** `ibmi_sql_query` **SQLite3 statements** `ibmi_sqlite3` **CL command sample** playbook `ibmi-cl-command-sample` **SQL sample** playbook `ibmi-sql-sample` **SQLite3 sample** playbook `ibmi-sqlite3-sample`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Gather facts, jobs and system information

Description	Query system values, ethernet ports, unconfigured disks, jobs, job logs, messages and spooled file output.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Facts** `ibmi_facts` **System values** `ibmi_sysval` **Ethernet ports** `ibmi_ethernet_port` **Unconfigured disks** `ibmi_get_nonconfigure_disks` **Job information** `ibmi_job` **Job logs** `ibmi_query_job_log` **Message search** `ibmi_message` **Spooled file content** `ibmi_spooled_file_data` **System value sample** playbook `ibmi-sysval-sample` **iASP query sample** playbook `query-iasp-sample`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Run and schedule jobs and subsystems

Description	Submit or schedule batch jobs, manage subsystems and reply to inquiry messages.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Scheduled batch jobs** `ibmi_at` **Submitted jobs** `ibmi_submit_job` **Subsystems** `ibmi_subsystem` **Message replies** `ibmi_reply_message`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Control the system: services, devices, network and power

Description	Reboot the machine, vary devices, manage IASPs, host and TCP servers, TCP/IP interfaces and network redundancy groups.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Reboot** `ibmi_reboot` **Device vary on/off** `ibmi_device_vary` **Independent ASPs** `ibmi_iasp` **Host servers** `ibmi_host_server_service` **TCP servers** `ibmi_tcp_server_service` **TCP/IP interfaces** `ibmi_tcp_interface` **Network redundancy group links** `ibmi_nrg_link` **Active IP interfaces** role `present_ip_interface`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Manage users, authority and security

Description	Create user and group profiles, grant or check object authority, check user compliance and default passwords.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**User and group profiles** `ibmi_user_and_group` **User compliance checks** `ibmi_user_compliance_check` **Object authority** `ibmi_object_authority` **Module authority checks** `ibmi_module_authority_check` **Default password check** playbook `ibmi-check-default-passwords` **SSH key installation** playbook `ssh-addkey` **Passwordless SSH login** role `configure_passwordless_ssh_login`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Save, restore and transfer libraries and objects

Description	Save and restore libraries and objects, find objects, copy and fetch save files, and synchronise files between IBM i nodes.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Library save** `ibmi_lib_save` **Library restore** `ibmi_lib_restore` **Object save** `ibmi_object_save` **Object restore** `ibmi_object_restore` **Object search** `ibmi_object_find` **Save file copy to remote** `ibmi_copy` **Fetch from remote** `ibmi_fetch` **Save file sync** `ibmi_sync` **Save file synchronisation** `ibmi_synchronize` **File sync** `ibmi_sync_files` **File synchronisation** `ibmi_synchronize_files` **Image file checksum checks** role `check_file`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Install and remove licensed programs and open source

Description	Install, save and uninstall licensed products and set up Bash, Node.js and open source utilities.
Collection	`ibm.power_ibmi` (Certified, IBM)

Key content	**Product install from save file** `ibmi_install_product_from_savf` **Product save to save file** `ibmi_save_product_to_savf` **Product removal** `ibmi_uninstall_product` **Bash setup** playbook `ibmi-bash-setup` **Node.js installation** playbook `ibmi-install-nodejs.ibmi-install-nodejs` **Open source utilities** playbook `ibmi-install-oss-utils`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Prepare IBM i for Ansible

Description	Configure managed-node settings and set up IBM i for the collection, including offline targets.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Managed node configuration** `ibmi_module_config` **Ansible setup** playbook `enable-ansible-for-i.setup` **Offline target setup** playbook `enable_offline_ibmi.main`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Query, download and install PTFs

Description	Display, check, compare, download and install individual fixes and PTF groups, including via image catalog.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Fix display** `ibmi_display_fix` **Fix download** `ibmi_download_fix`, `ibmi_download_fix_status` **Fix download from cloud** `ibmi_download_fix_from_cloud` **Fix install and removal** `ibmi_fix` **PTF group check** `ibmi_fix_check` **Fix comparison** `ibmi_fix_compare` **PTF group information check** `ibmi_fix_group_check` **Fix install via image catalog** `ibmi_fix_imgclg` **Product fix check** `ibmi_fix_product_check` **Fix check sample** playbook `ibmi-fix-check` **Fix group check sample** playbook `ibmi-fix-group-check` **Apply all loaded PTFs** role `apply_all_loaded_ptfs` **Apply PTFs** role `apply_ptf` **PTF status check** role `check_ptf` **Individual PTF download** role `download_individual_ptfs` **PTF load** role `load_ptf` **PTF load and apply** role `load_apply_ptfs` **Individual PTF transfer and apply** role `sync_apply_individual_ptfs` **Local PTF transfer and apply** role `sync_apply_individual_ptfs_local` **Level 1 PTF transfer and apply** role `sync_apply_individual_ptfs_lv1` **PTF group transfer and apply** role `sync_apply_ptf_group` **PTF group network install** role `sync_apply_ptf_group_networkinstall`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Maintain a PTF repository and network install server

Description	Build a PTF fix repository database and set up network install servers and clients.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Fix repository** `ibmi_fix_repo` **Level 1 fix repository** `ibmi_fix_repo_lv1` **Network install client** `ibmi_fix_network_install_client` **Network install server** `ibmi_fix_network_install_server` **Fix repository dependencies** playbook `install_fix_repo_dependencies` **Cumulative package repository** playbook `ibmi-fix-repo-cum-package` **Repository download status** playbook `ibmi-fix-repo-download-status` **Level 1 repository** playbook `ibmi-fix-repo-lv1` **PTF group repository** playbook `ibmi-fix-repo-ptf-group` **Single PTF repository** playbook `ibmi-fix-repo-single-ptf` **PTF groups against repository** role `check_ptf_groups_against_fix_repo` **Product PTFs against repository** role `check_ptfs_by_product_against_fix_repo` **Check and download individual PTFs** role `fix_repo_check_download_individual_ptfs` **PTF group check in repository** role `fix_repo_check_ptf_group` **PTF group download to repository** role `fix_repo_download_add_ptf_group` **Individual PTF download and apply** role `fix_repo_download_apply_individual_ptfs` **PTF group information extraction** role `fix_repo_extract_ptf_group_info` **Level 1 PTF lookup** role `fix_repo_lv1_find_individual_ptf`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Run Db2 Mirror setup and warm clones

Description	Configure Db2 Mirror on source and target nodes and suspend or resume warm clone activity.
Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**Db2 Mirror source setup** `ibmi_mirror_setup_source` **Db2 Mirror target setup** `ibmi_mirror_setup_copy` **Warm clone activity** `ibmi_mirror_warm_clone_activity`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

Use Case: Manage IBM i VMs through PowerVC

Description	Deploy, capture, start and stop IBM i virtual machines and display their details and networks via PowerVC.

Collection	`ibm.power_ibmi` (Certified, IBM)
Key content	**VM deployment** role `deploy_vm_via_powervc` **VM capture** role `capture_server_via_powervc` **VM power state** role `change_server_state_via_powervc` **VM information** role `display_vm_info_via_powervc` **Network information** role `display_network_info_via_powervc`
Notes	• Plain keys are modules (ibmi_ prefix omitted); roles and playbooks are listed with their type.

IBM Power Virtual I/O Server (VIOS) `ibm.power_vios`

Certified IBM · version 1.3.0 · updated 2023-11-24 · 8 modules → 3 use cases

Use Case: Update and upgrade VIOS

Description	Download fixes, update to the latest maintenance level, upgrade VIOS and run end-to-end update demos.
Collection	`ibm.power_vios` (Certified, IBM)
Key content	**Fix downloads** `fix_download` **VIOS updates** `updateios` **VIOS upgrades** `viosupgrade` **Fix download demo** playbook `demo_fix_download` **Update demo** playbook `demo_updateios` **Download and update demo** playbook `demo_full_update` **Upgrade demo** playbook `demo_viosupgrade`

Use Case: Back up and secure VIOS

Description	Back up the root volume group and VIOS configuration, create alternate rootvg disks and apply security hardening.
Collection	`ibm.power_vios` (Certified, IBM)
Key content	**Root volume group backup** `backupios` **Configuration backup and restore** `viosbr` **Alternate rootvg** `alt_root_vg` **Security hardening and firewall** `viosecure` **Backup demo** playbook `demo_backupios` **viosbr demo** playbook `demo_viosbr`

Use Case: Inspect devices and bootstrap package management

Description	Report physical, logical and virtual device mappings, bootstrap DNF on AIX and check for updates with yum.
Collection	`ibm.power_vios` (Certified, IBM)
Key content	**Device mappings** `mapping_facts` **DNF bootstrap** role `power_vios_bootstrap` **Bootstrap DNF** playbook `demo_dnf_bootstrap` **yum update check** playbook `demo_yum`

Inspur server BMC (ISPIM) `inspur.ispim`

Certified Inspur · version 2.2.3 · updated 2024-06-14 · 128 modules → 9 use cases

Use Case: Collect server hardware inventory and health

Description	Read BMC, firmware, CPU, memory, GPU, PCIe, adapter, fan, temperature, voltage, power supply and sensor data, set fan, FRU, UID and sensor thresholds, and run a self test.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**Server status** `server_info` **BMC information** `bmc_info` **Support information** `support_info` **Firmware versions** `fw_version_info` **Self test** `self_test_info` **CPUs** `cpu_info` **Memory** `mem_info` **GPUs** `gpu_info` **PCIe devices** `pcie_info` **Adapters** `adapter_info` **FRU information** `fru_info` **FRU settings** `edit_fru` **Fans** `fan_info` **Fan settings** `edit_fan` **Temperatures** `temp_info` **Voltages** `volt_info` **Power supplies** `psu_info` **Sensors** `sensor_info` **Thresholds** `threshold_info` **Threshold settings** `edit_threshold` **UID LED** `uid_info` **UID LED settings** `edit_uid`

Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Configure storage, RAID and disks

Description	Read RAID and HBA controllers, backplanes and disks, and create or modify logical disks and physical disk settings.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**RAID controllers** `raid_info` **HBA cards** `hba_info` **Disk backplanes** `backplane_info` **Hard disks** `hard_disk_info` **Onboard disks** `onboard_disk_info` **Physical disks** `pdisk_info` **Physical disk settings** `edit_pdisk` **Logical disks** `ldisk_info` **Logical disk creation** `add_ldisk` **Logical disk settings** `edit_ldisk`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Control power and power budget

Description	Read and set power status, restore policy, power budget and power supply configuration, and read power consumption.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**Power status** `power_status_info` **Power control** `edit_power_status` **Power consumption** `power_consumption_info` **Power budget** `power_budget_info` **Power budget settings** `edit_power_budget` **Power restore policy** `power_restore_info` **Power restore settings** `edit_power_restore` **Power supply configuration** `psu_config_info` **Power supply configuration settings** `edit_psu_config` **Power supply peak settings** `psu_peak_info` **Power supply peak changes** `edit_psu_peak`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Configure BIOS and boot

Description	Read and change BIOS setup attributes, export and import BIOS configuration, and set boot options and boot images.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**BIOS setup** `bios_info` **BIOS attributes** `edit_bios` **BIOS export** `bios_export` **BIOS import** `bios_import` **Boot options** `boot_option_info` **Boot option settings** `edit_boot_option` **BMC boot images** `boot_image_info` **BMC boot image settings** `edit_boot_image`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Configure BMC network and services

Description	Set BMC network, IPv4, IPv6, VLAN, bonding, link and NCSI settings, DNS, NTP and enable or disable BMC services.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**Network** `network_info` **Network settings** `edit_network` **IPv4 settings** `edit_ipv4` **IPv6 settings** `edit_ipv6` **VLAN settings** `edit_vlan` **Network bonds** `network_bond_info` **Network bond settings** `edit_network_bond` **Network links** `network_link_info` **Network link settings** `edit_network_link` **NCSI** `ncsi_info` **NCSI settings** `edit_ncsi` **DNS** `dns_info` **DNS settings** `edit_dns` **NTP** `ntp_info` **NTP settings** `edit_ntp` **BMC services** `service_info` **BMC service settings** `edit_service`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Provide remote console and virtual media

Description	Manage KVM, virtual media and remote image redirection, and capture or download screenshots.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**KVM** `kvm_info` **KVM settings** `edit_kvm` **KVM reset** `reset_kvm` **Virtual media** `virtual_media_info` **Virtual media settings** `edit_virtual_media` **Virtual media instances** `media_instance_info` **Virtual media instance settings** `edit_media_instance` **Remote image redirection** `connect_media_info` **Virtual media image start and stop** `edit_connect_media` **Automatic screen capture** `auto_capture_info` **Automatic screen capture settings** `edit_auto_capture` **Manual screen capture** `edit_manual_capture` **Automatic screenshot downloads** `download_auto_screenshot` **Manual screenshot downloads** `download_manual_screenshot`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Manage BMC users and directory authentication

Description	Manage local users and groups, configure Active Directory and LDAP authentication with their groups, and list or delete sessions.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**Users** `user`, `user_info` **User groups** `user_group`, `user_group_info` **Active Directory information** `ad_info` **Active Directory settings** `edit_ad` **Active Directory groups** `ad_group`, `ad_group_info` **LDAP information** `ldap_info` **LDAP settings** `edit_ldap` **LDAP groups** `ldap_group`, `ldap_group_info` **Online sessions** `session_info` **Session deletion** `del_session`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Collect logs and send alerts

Description	Read and clear audit, event and system logs, collect log bundles, set log policies, and configure alert policies, SMTP and SNMP notifications.
Collection	`inspur.ispim` (Certified, Inspur)
Key content	**Audit log** `audit_log_info` **Audit log cleanup** `clear_audit_log` **Event log** `event_log_info` **Event log cleanup** `clear_event_log` **System log** `system_log_info` **System log cleanup** `clear_system_log` **Log collection** `collect_log` **Blackbox log collection** `collect_blackbox` **Log settings** `log_setting_info` **Log setting changes** `edit_log_setting` **Log setting changes (M6 servers)** `edit_m6_log_setting` **Event log policy** `event_log_policy_info` **Event log policy settings** `edit_event_log_policy` **Alert policy** `alert_policy_info` **Alert policy settings** `edit_alert_policy` **SMTP** `smtp_info` **SMTP settings** `edit_smtp` **SMTP communication settings** `edit_smtp_com` **SMTP destination settings** `edit_smtp_dest` **SNMP** `snmp_info` **SNMP settings** `edit_snmp` **SNMP traps** `snmp_trap_info` **SNMP trap settings** `edit_snmp_trap`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

Use Case: Update firmware and back up or reset the BMC

Description	Update firmware, CPLD and power supplies, back up and restore server settings, preserve configuration, restore factory defaults and reset the BMC.
Collection	`inspur.ispim` (Certified, Inspur)

Key content	**Firmware update** `update_fw` **CPLD update** `update_cpld` **Power supply update** `update_psu` **Settings backup** `backup` **Settings restore** `restore` **Preserved configuration** `preserve_config_info` **Preserved configuration settings** `edit_preserve_config` **Factory default restore** `edit_restore_factory_default` **BMC reset** `reset_bmc`
Notes	• Modules talk to the server BMC; read-only queries are named after the item (for example cpu) and changes are named edit_<item>.

WTI OOB console servers and PDUs `wti.remote`

Certified WTI · version 1.0.10 · updated 2024-09-12 · 38 modules → 6 use cases

Use Case: Control power outlets and monitor the device

Description	Switch and configure power plugs, and read power, current, temperature, alarm and general status.
Collection	`wti.remote` (Certified, WTI)
Key content	**Plug control** `cpm_plugcontrol` **Plug configuration** `cpm_plugconfig` **Power information** `cpm_power_info` **Current information** `cpm_current_info` **Temperature** `cpm_temp_info` **Alarms** `cpm_alarm_info` **Device status** `cpm_status_info` **Plug state control sample** playbook `cpm_plugcontrol.plug_control` **Plug parameters sample** playbook `cpm_plugcontrol.plug_control_info` **Plug configuration sample** playbook `cpm_plugconfig.plug_config` **Plug information sample** playbook `cpm_plugconfig.plug_info` **Status sample** playbook `cpm_status.status_info` **Power information sample** playbook `cpm_status.power_info` **Current information sample** playbook `cpm_status.current_info` **Temperature information sample** playbook `cpm_status.temp_info` **Alarm information sample** playbook `cpm_status.alarm_info`
Notes	• Module names have the cpm_ prefix omitted. Each setting usually has a read-only info module and a _config module that changes it, with matching sample playbooks.

Use Case: Manage serial console ports

Description	Read and set serial port parameters and connect or disconnect serial sessions.
Collection	`wti.remote` (Certified, WTI)
Key content	**Serial port parameters** `cpm_serial_port_info` **Serial port configuration** `cpm_serial_port_config` **Serial connection status** `cpm_serial_port_action_info` **Serial connect and disconnect** `cpm_serial_port_action_set` **Serial port parameters sample** playbook `cpm_serial_ports.serial_ports_info` **Serial port configuration sample** playbook `cpm_serial_ports.serial_ports_config` **Serial connection status sample** playbook `cpm_serial_ports.serial_ports_action_info` **Serial connection control sample** playbook `cpm_serial_ports.serial_ports_action_set`
Notes	• Module names have the cpm_ prefix omitted. Each setting usually has a read-only info module and a _config module that changes it, with matching sample playbooks.

Use Case: Configure network interfaces, DNS and cellular

Description	Read and set network interface, DNS services and cellular parameters.
Collection	`wti.remote` (Certified, WTI)

Key content	**Network interfaces** `cpm_interface_info` **Network interface configuration** `cpm_interface_config` **DNS services** `cpm_dnsservices_info` **DNS services configuration** `cpm_dnsservices_config` **Cellular information** `cpm_cellular_info` **Cellular configuration** `cpm_cellular_config` **Network interface information sample** playbook `cpm_interface.interface_info` **Network interface configuration sample** playbook `cpm_interface.interface_config` **DNS services information sample** playbook `cpm_dnsservices.dnsservices_info` **DNS services configuration sample** playbook `cpm_dnsservices.dnsservices_config` **DNS servers information sample** playbook `cpm_dnsservices.dnsservers_info` **DNS servers configuration sample** playbook `cpm_dnsservices.dnsservers_config` **Cellular information sample** playbook `cpm_cellular.cellular_info` **Cellular configuration sample** playbook `cpm_cellular.cellular_config`
Notes	• Module names have the cpm_ prefix omitted. Each setting usually has a read-only info module and a _config module that changes it, with matching sample playbooks.

Use Case: Secure management access

Description	Read and set SSH, web, IP tables and SNMP parameters, and manage local users.
Collection	`wti.remote` (Certified, WTI)
Key content	**SSH parameters** `cpm_ssh_info` **SSH configuration** `cpm_ssh_config` **Web parameters** `cpm_web_info` **Web configuration** `cpm_web_config` **IP tables** `cpm_iptables_info` **IP tables configuration** `cpm_iptables_config` **SNMP parameters** `cpm_snmp_info` **SNMP configuration** `cpm_snmp_config` **Users** `cpm_user` **SSH information sample** playbook `cpm_ssh.ssh_info` **SSH configuration sample** playbook `cpm_ssh.ssh_config` **Web information sample** playbook `cpm_web.web_info` **Web configuration sample** playbook `cpm_web.web_config` **IP tables information sample** playbook `cpm_iptables.iptables_info` **IP tables configuration sample** playbook `cpm_iptables.iptables_config` **SNMP information sample** playbook `cpm_snmp.snmp_info` **SNMP configuration sample** playbook `cpm_snmp.snmp_config` **User creation sample** playbook `cpm_user.user_add` **User edit sample** playbook `cpm_user.user_edit` **User deletion sample** playbook `cpm_user.user_delete` **User information sample** playbook `cpm_user.user_get`
Notes	• Module names have the cpm_ prefix omitted. Each setting usually has a read-only info module and a _config module that changes it, with matching sample playbooks.

Use Case: Configure logging, time and device identity

Description	Read and set syslog client and server, time and NTP, and hostname, site ID, location and asset tag.
Collection	`wti.remote` (Certified, WTI)
Key content	**Syslog client** `cpm_syslog_client_info` **Syslog client configuration** `cpm_syslog_client_config` **Syslog server** `cpm_syslog_server_info` **Syslog server configuration** `cpm_syslog_server_config` **Time and date** `cpm_time_info` **Time and date configuration** `cpm_time_config` **Hostname and asset tag** `cpm_hostname_info` **Hostname and asset tag configuration** `cpm_hostname_config` **Syslog client information sample** playbook `cpm_syslog_client.syslog_client_info` **Syslog client configuration sample** playbook `cpm_syslog_client.syslog_client_config` **Syslog server information sample** playbook `cpm_syslog_server.syslog_server_info` **Syslog server configuration sample** playbook `cpm_syslog_server.syslog_server_config` **Time information sample** playbook `cpm_time_date.time_info` **Time configuration sample** playbook `cpm_time_date.time_config` **Hostname information sample** playbook `cpm_hostname.hostname_info` **Hostname configuration sample** playbook `cpm_hostname.hostname_config`
Notes	• Module names have the cpm_ prefix omitted. Each setting usually has a read-only info module and a _config module that changes it, with matching sample playbooks.

Use Case: Back up configuration and upgrade firmware

Description	Save and restore device parameters and check or update firmware.
Collection	`wti.remote` (Certified, WTI)

Key content	**Configuration backup** `cpm_config_backup` **Configuration restore** `cpm_config_restore` **Firmware information** `cpm_firmware_info` **Firmware update** `cpm_firmware_update` **Configuration backup sample** playbook `cpm_config.cpm_config_backup` **Configuration restore sample** playbook `cpm_config.cpm_config_restore` **Firmware upgrade sample** playbook `cpm_firmwareupdate.firmware_upgrade` **Firmware information sample** playbook `cpm_status.firmware_info`
Notes	• Module names have the cpm_ prefix omitted. Each setting usually has a read-only info module and a _config module that changes it, with matching sample playbooks.