Ansible Automation - Use Cases

A reference of the use cases by which Ansible Automation Platform is commonly implemented, by domain. Each use case is described in the same format (Description, Collection, Key content, Notes) and mapped to Red Hat Certified and Validated content.

7 solution use cases · 126 product use cases · generated 2026-10-21 · community reference, not an official Red Hat publication

Contents

1. Storage
    - Solution use cases (7)
        - Provision block storage
        - Provision file storage
        - Manage snapshots, clones and replication
        - Provision object storage
        - Standardise storage system configuration
        - Gather storage facts and capacity reports
        - Decommission storage safely
    - Product use cases
        - Cohesity DataProtect (7)
        - Dell PowerFlex (8)
        - Dell PowerMax / VMAX (4)
        - Dell PowerScale (OneFS) (9)
        - Dell PowerStore (7)
        - Dell Unity (5)
        - Dell VPLEX (4)
        - Everpure (Pure Storage) FlashArray (9)
        - Everpure FlashBlade (8)
        - Pure Storage Pure1 (1)
        - Hitachi Vantara VSP One Block and SDS Block storage (18)
        - Hitachi Vantara VSP One Object (5)
        - IBM Storage Virtualize (FlashSystem and SAN Volume Controller) (9)
        - Infinidat InfiniBox (6)
        - NetApp Cloud Volumes Service for AWS (1)
        - NetApp Azure NetApp Files (1)
        - NetApp Cloud Manager (3)
        - NetApp ONTAP (13)
        - NetApp StorageGRID (6)
        - NetApp Unified Manager (2)

Storage

Provision, operate, protect and decommission storage.

Solution use cases

Use Case: Provision block storage

Description	Turn a request for a disk (size, performance tier, host or cluster) into a finished block volume that the host can see. One workflow creates the volume, registers the host's initiators, maps or masks the volume, and where required zones the Fibre Channel fabric. The steps are the same across vendors; only the modules differ.
Collection	`netapp.ontap` (Certified), `dellemc.powerstore` (Certified), `dellemc.powermax` (Certified), `dellemc.unity` (Certified), `everpure.flasharray` (Certified), `ibm.storage_virtualize` (Certified), `hitachivantara.vspone_block` (Certified), `infinidat.infinibox` (Certified), `cisco.nxos` (Certified)
Key content	• `netapp.ontap.na_ontap_lun` — NetApp ONTAP manage LUNs • `netapp.ontap.na_ontap_lun_map` — NetApp ONTAP LUN maps • `dellemc.powermax.maskingview` — Test masking view operations • `dellemc.powerstore.volume` — Manage volumes on a PowerStore storage system • `everpure.flasharray.purefa_volume` — Manage volumes on Everpure FlashArrays • `ibm.storage_virtualize.ibm_svc_manage_volume` — This module manages standard volumes on IBM Storage Virtualize family systems • `hitachivantara.vspone_block.hv_ldev` — Manages logical devices (LDEVs) on VSP block storage systems. • `cisco.nxos.nxos_zone_zoneset` — Configuration of zone/zoneset for Cisco NXOS MDS Switches.
Notes	• Keep the vendor differences in variable files and role defaults, and offer the requester one catalog item. A single job template can include the correct vendor tasks based on an array group variable. • Pair with Manage snapshots, clones and replication and with Decommission storage safely. • Other certified block collections in this domain include `dellemc.powerflex` (software-defined block storage) and `dellemc.vplex`. • On HPE ProLiant servers, local RAID volumes are handled by the server tools in Provision bare-metal servers. • Event-Driven Ansible can trigger expansion of a volume when a capacity alert is received.

Use Case: Provision file storage

Description	Deliver NFS exports and SMB shares from enterprise NAS systems through a repeatable request: create the filesystem or volume, publish it through the right protocol, restrict access, and apply a quota. Application and virtualization teams get file storage in minutes, while storage teams keep the naming, security and capacity standards.
Collection	`netapp.ontap` (Certified), `dellemc.powerscale` (Certified), `dellemc.powerstore` (Certified), `dellemc.unity` (Certified), `everpure.flashblade` (Certified), `infinidat.infinibox` (Certified)
Key content	• `netapp.ontap.na_ontap_volume` — NetApp ONTAP manage volumes. • `netapp.ontap.na_ontap_export_policy_rule` — NetApp ONTAP manage export policy rules • `netapp.ontap.na_ontap_cifs` — NetApp ONTAP Manage cifs-share • `netapp.ontap.na_ontap_quotas` — NetApp ONTAP Quotas • `dellemc.powerscale.nfs` — Manage NFS exports on a PowerScale Storage System • `dellemc.powerscale.smb` — Manage SMB shares on PowerScale Storage System • `dellemc.powerscale.smartquota` — Manage Smart Quotas on PowerScale • `dellemc.powerstore.filesystem` — Filesystem operations for PowerStore Storage system • `everpure.flashblade.purefb_fs` — Manage filesystemon Everpure FlashBlade`
Notes	• For Kubernetes persistent storage, create the backend storage with these modules, then claim it from the cluster with the Kubernetes tooling in Deploy applications to Kubernetes and OpenShift. • Dell PowerScale supports access zones (`dellemc.powerscale.accesszone`) and SmartConnect network pools, which are useful for multi-tenant designs. • Use the vendor info modules to check for name clashes before creating a share. • Pair with Decommission storage safely.

Use Case: Manage snapshots, clones and replication

Description	Protect and reuse data with the array's own features: scheduled snapshots, writable clones for development and testing, and replication to a second array for disaster recovery. Automation Platform sets up the policies once, applies them to every new volume, and runs on-demand snapshots and clones as part of change and test workflows.

Collection	`netapp.ontap` (Certified), `dellemc.powerstore` (Certified), `dellemc.powermax` (Certified), `dellemc.powerflex` (Certified), `everpure.flasharray` (Certified), `ibm.storage_virtualize` (Certified), `hitachivantara.vspone_block` (Certified), `cohesity.dataprotect` (Certified), `infra.lvm_snapshots` (Validated)
Key content	• `netapp.ontap.na_ontap_snapshot_policy` — NetApp ONTAP manage Snapshot Policy • `netapp.ontap.na_ontap_volume_clone` — NetApp ONTAP manage volume clones. • `netapp.ontap.na_ontap_snapmirror` — NetApp ONTAP or ElementSW Manage SnapMirror • `dellemc.powerstore.replicationsession` — Replication session operations on a PowerStore storage system • `dellemc.powermax.srdf` — Testing Storage Group SRDF operations • `everpure.flasharray.purefa_pg` — Manage protection groups on Everpure FlashArrays • `ibm.storage_virtualize.ibm_svc_manage_flashcopy` — This module manages FlashCopy mappings on IBM Storage Virtualize family systems • `hitachivantara.vspone_block.hv_snapshot` — Manages snapshots on VSP block storage systems. • `cohesity.dataprotect.cohesity_job` — Management of Cohesity Protection Jobs
Notes	• Snapshots on the same array are not a backup; keep a separate copy, either through replication or a backup product. • On Linux hosts without array integration, use the `infra.lvm_snapshots` roles (`snapshot_create`, `snapshot_revert`, `snapshot_remove`) for pre-change rollback points. • Application consistency (quiescing databases, hypervisor snapshots) is added in the workflow before the array snapshot node. • Pair with Provision block storage and Provision file storage. For Kubernetes data, see Back up Kubernetes applications. • Event-Driven Ansible can start a failover or an extra snapshot when replication alarms are raised.

Use Case: Provision object storage

Description	Give application teams an S3-compatible bucket with access keys and lifecycle rules without a storage ticket. Automation creates the tenant or account, the user, the keys and the bucket, and applies data placement and retention rules, then hands the endpoint and credentials to the requester through a secure channel.
Collection	`netapp.storagegrid` (Certified), `netapp.ontap` (Certified), `everpure.flashblade` (Certified), `dellemc.powerscale` (Certified)
Key content	• `netapp.storagegrid.na_sg_grid_tenant` — NetApp StorageGRID manage tenant accounts. • `netapp.storagegrid.na_sg_org_user` — NetApp StorageGRID manage users within a tenancy. • `netapp.storagegrid.na_sg_org_user_s3_key` — Creates NetApp StorageGRID User S3 keys. • `netapp.storagegrid.na_sg_org_bucket` — Manage buckets on StorageGRID. • `netapp.storagegrid.na_sg_grid_ilm_policy` — Manage ILM policies on StorageGRID. • `netapp.ontap.na_ontap_s3_buckets` — NetApp ONTAP S3 Buckets • `everpure.flashblade.purefb_s3acc` — Create or delete FlashBlade Object Store accounts • `everpure.flashblade.purefb_bucket` — Manage Object Store Buckets on a Everpure FlashBlade.
Notes	• Set `no_log` on tasks that return access keys. • Object storage is a common target for backups; see Manage snapshots, clones and replication and Back up Kubernetes applications. • Pair with Standardise storage system configuration for certificates, NTP and identity federation on the platform.

Use Case: Standardise storage system configuration

Description	Storage arrays are configured one at a time by different people, and settings drift. Define the baseline once (NTP, DNS, directory service, SNMP and syslog, alert destinations, certificates, users and firmware level) and apply it to every array on a schedule. A drift report then shows which systems differ from the baseline.
Collection	`netapp.ontap` (Certified), `dellemc.powerstore` (Certified), `dellemc.powerscale` (Certified), `everpure.flasharray` (Certified), `everpure.flashblade` (Certified), `ibm.storage_virtualize` (Certified), `infinidat.infinibox` (Certified), `netapp.storagegrid` (Certified)
Key content	• `netapp.ontap.na_ontap_ntp` — NetApp ONTAP NTP server • `netapp.ontap.na_ontap_dns` — NetApp ONTAP Create, delete, modify DNS servers. • `netapp.ontap.na_ontap_ldap` — NetApp ONTAP LDAP • `netapp.ontap.na_ontap_software_update` — NetApp ONTAP Update Software • `dellemc.powerstore.ntp` — NTP operations on a PowerStore storage system • `dellemc.powerscale.alert_channel` — Manage alert channel on a PowerScale Storage System • `everpure.flasharray.purefa_ntp` — Configure Everpure FlashArray NTP settings • `everpure.flasharray.purefa_syslog` — Configure Everpure FlashArray syslog settings • `ibm.storage_virtualize.ibm_sv_manage_syslog_server` — This module manages syslog server on IBM Storage Virtualize family systems • `infinidat.infinibox.infini_notification_target` — Config notification target
Notes	• Some arrays treat these settings as cluster-wide, others per node or per SVM; model that in the variable structure. • Storage alerts can start Event-Driven Ansible rulebooks, for example to expand a volume or open an incident. See Gather storage facts and capacity reports for the reporting side. • For switch and server firmware used with the arrays, see Update server firmware and BIOS. • Pair with Provision block storage once the baseline is in place.

Use Case: Gather storage facts and capacity reports

Description	Answer "what do we have, how full is it and is it healthy?" without logging in to each array. Facts are collected from all storage platforms, normalised into a common record (system, pool, volume, host, usage), and published as reports, a dashboard feed or a CMDB update. The same facts can validate that the state matches what was provisioned.
Collection	`netapp.ontap` (Certified), `netapp.um_info` (Certified), `dellemc.powerstore` (Certified), `dellemc.powermax` (Certified), `dellemc.unity` (Certified), `dellemc.powerscale` (Certified), `dellemc.powerflex` (Certified), `everpure.flasharray` (Certified), `everpure.flashblade` (Certified), `everpure.pure1` (Certified), `ibm.storage_virtualize` (Certified), `hitachivantara.vspone_block` (Certified), `cohesity.dataprotect` (Certified)
Key content	• `netapp.ontap.na_ontap_info` — NetApp information gatherer • `netapp.ontap.na_ontap_rest_info` — NetApp ONTAP information gatherer using REST APIs • `netapp.um_info.na_um_volumes_info` — NetApp Unified Manager list volumes. • `dellemc.powerstore.info` — Gathers information about PowerStore Storage entities • `dellemc.powermax.info` — Collect set of facts • `everpure.flasharray.purefa_info` — Collect information from Everpure FlashArray • `everpure.pure1.pure1_info` — Collect information from Pure1 • `ibm.storage_virtualize.ibm_svc_info` — This module gathers various information from the IBM Storage Virtualize family systems • `hitachivantara.vspone_block.hv_storagesystem_facts` — retrieves storage system information from VSP block storage systems.
Notes	• Use read-only accounts for reporting jobs. • Large arrays return a lot of data; request only the subsets needed (many info modules can limit what they gather). • Pair with Standardise storage system configuration and Decommission storage safely, which uses the same facts to find unused volumes. • Event-Driven Ansible can start expansion or clean-up jobs when capacity or health alerts arrive, using this report as the first diagnostic step.

Use Case: Decommission storage safely

Description	Remove storage that is no longer needed without breaking a workload or leaving data behind. The workflow proves that the volume is unused, takes a final copy where required, removes access in the right order, waits through a recovery period, and only then deletes data and, for retired arrays, erases the system.
Collection	`netapp.ontap` (Certified), `dellemc.powerstore` (Certified), `dellemc.powermax` (Certified), `everpure.flasharray` (Certified), `ibm.storage_virtualize` (Certified), `hitachivantara.vspone_block` (Certified), `infinidat.infinibox` (Certified), `cisco.nxos` (Certified)
Key content	• `netapp.ontap.na_ontap_lun_map` — NetApp ONTAP LUN maps • `netapp.ontap.na_ontap_volume` — NetApp ONTAP manage volumes. • `netapp.ontap.na_ontap_vserver_delete` — delete ONTAP vserver and all associated user data (volumes, snapshots, clones) • `dellemc.powermax.maskingview` — Test masking view operations • `dellemc.powerstore.volume` — Manage volumes on a PowerStore storage system • `everpure.flasharray.purefa_volume` — Manage volumes on Everpure FlashArrays • `everpure.flasharray.purefa_zte` — Perform Zero Touch Erasure (ZTE) on a FlashArray • `ibm.storage_virtualize.ibm_svc_vol_map` — This module manages volume mapping on IBM Storage Virtualize family systems
Notes	• Decommissioning is destructive; run the whole workflow in a check or report-only mode first and show the list to the owner. • Deleting an SVM with `na_ontap_vserver_delete` removes its volumes, snapshots and clones, so use it only after all earlier steps are complete. • Pair with Provision block storage and Manage snapshots, clones and replication for the matching create and protect steps. • Hypervisor datastores and Kubernetes persistent volumes on the storage should be migrated first; see Operate vSphere clusters and ESXi hosts.

Product use cases

Grouped from the modules of each certified or validated collection. Key content lists the components each use case supports, with the modules that manage them (create, update, delete) and query them (_info).

Cohesity DataProtect `cohesity.dataprotect`

Certified Cohesity · version 1.4.5 · updated 2026-07-23 · 23 modules → 7 use cases

Use Case: Install and remove agents and connectors

Description	Manage physical and Windows agents and datastore plugins, and install the agent on Linux, AIX or Windows hosts.
Collection	`cohesity.dataprotect` (Certified, Cohesity)
Key content	**Physical agents** `cohesity_agent` **Windows agents** `cohesity_win_agent` **Datastore plugins** `cohesity_plugin` **Linux agent install** playbook `physical-workflow.agent-install.install_linux_agent` **CentOS agent install** playbook `physical-workflow.agent-install.install_agent_centos` **Oracle Linux agent install** playbook `physical-workflow.agent-install.install_agent_oracle_linux` **SLES agent install** playbook `physical-workflow.agent-install.install_agent_sles` **Ubuntu agent install** playbook `physical-workflow.agent-install.install_agent_ubuntu` **AIX agent install** playbook `physical-workflow.agent-install.install_agent_aix` **Windows agent install** playbook `physical-workflow.agent-install.install_win_agent` **Linux agent removal** playbook `physical-workflow.uninstall-agent.uninstall_linux_agent` **Windows agent removal** playbook `physical-workflow.uninstall-agent.uninstall_win_agent` **PostgreSQL plugin install** playbook `uda-workflow.connector-install.install_postgres_plugin` **SAP HANA plugin install** playbook `uda-workflow.connector-install.install_sap_hana_plugin` **SAP HANA plugin removal** playbook `uda-workflow.connector-install.uninstall_sap_hana_plugin`
Notes	• Module names have the cohesity_ prefix omitted; playbooks are grouped by the workload they protect.

Use Case: Protect physical servers

Description	Register physical sources, create and update protection groups, and restore files on Linux hosts.
Collection	`cohesity.dataprotect` (Certified, Cohesity)
Key content	**Single source registration** playbook `physical-workflow.register_single_physical_source` **Multiple source registration** playbook `physical-workflow.register_multiple_physical_source` **Source refresh** playbook `physical-workflow.refresh_physical_sources` **Source unregistration** playbook `physical-workflow.unregister_source` **Protection group creation** playbook `physical-workflow.create_physical_protection_group` **Protection group update** playbook `physical-workflow.update_physical_protection_group` **Source removal from group** playbook `physical-workflow.remove_sources_from_protection_group` **Protection group deletion** playbook `physical-workflow.delete_protection_group` **Linux file restore** playbook `physical-workflow.restore_files_linux`
Notes	• Module names have the cohesity_ prefix omitted; playbooks are grouped by the workload they protect.

Use Case: Protect and recover VMware virtual machines

Description	Register vCenter sources, build protection jobs, restore VMs and files, and clone VMs.
Collection	`cohesity.dataprotect` (Certified, Cohesity)
Key content	**Protection sources** `cohesity_source` **Protection jobs** `cohesity_job` **VM restores** `cohesity_restore_vm` **File and folder restores** `cohesity_restore_file` **VMware file restores** `cohesity_restore_vmware_file` **VM clones** `cohesity_clone_vm` **vCenter source registration** playbook `vmware-workflow.register_vmware_source` **vCenter source update** playbook `vmware-workflow.update_vmware_source` **vCenter source refresh** playbook `vmware-workflow.refresh_source` **Protection group creation** playbook `vmware-workflow.create_vmware_protection_group` **Tag-based protection group creation** playbook `vmware-workflow.create_tag_based_protection_group` **Protection group update** playbook `vmware-workflow.update_vmware_protection_group` **VM removal from job** playbook `vmware-workflow.remove_vms_from_job` **Protection group deletion** playbook `vmware-workflow.delete_protection_group` **VM restore** playbook `vmware-workflow.restore_vm` **File restore** playbook `vmware-workflow.restore_files_vmware` **VM clone** playbook `vmware-workflow.cohesity_clone_vm`
Notes	• Module names have the cohesity_ prefix omitted; playbooks are grouped by the workload they protect.

Use Case: Migrate virtual machines

Description	Create, monitor, sync, finalise or cancel VM migrations from Cohesity backups.
Collection	`cohesity.dataprotect` (Certified, Cohesity)
Key content	**VM migrations** `cohesity_migrate_vm` **Migration sync status** `cohesity_migration_status` **Migration object sync** `cohesity_sync_objects` **Migration finalisation** `cohesity_finalize_migration` **Migration cancellation** `cohesity_cancel_migration` **VM migration creation** playbook `vmware-workflow.migration.create_vm_migration` **Migration task** playbook `vmware-workflow.migration.migrate_task` **Migration status** playbook `vmware-workflow.migration.get_migration_status` **Migration object sync** playbook `vmware-workflow.migration.sync_objects` **Migration finalisation** playbook `vmware-workflow.migration.finalize_migration` **Migration cancellation** playbook `vmware-workflow.migration.cancel_migration`
Notes	• Module names have the cohesity_ prefix omitted; playbooks are grouped by the workload they protect.

Use Case: Protect NAS and manage views

Description	Register NFS and SMB sources, create NAS protection jobs, and create or delete Cohesity views.
Collection	`cohesity.dataprotect` (Certified, Cohesity)
Key content	**Views** `cohesity_view` **NFS source registration** playbook `nas-workflow.register_NAS_NFS_source` **SMB source registration** playbook `nas-workflow.register_NAS_SMB_source` **NAS protection job** playbook `nas-workflow.create_nas_workflow` **Source removal from job** playbook `nas-workflow.remove_source_from_job` **View creation** playbook `view-workflow.create_view` **View deletion** playbook `view-workflow.delete_view`
Notes	• Module names have the cohesity_ prefix omitted; playbooks are grouped by the workload they protect.

Use Case: Protect and recover databases

Description	Protect Oracle, SQL Server and user-defined-archive (UDA) databases and recover Oracle databases.
Collection	`cohesity.dataprotect` (Certified, Cohesity)
Key content	**Oracle sources** `cohesity_oracle_source` **Oracle protection jobs** `cohesity_oracle_job` **Oracle restores** `cohesity_oracle_restore` **UDA sources** `cohesity_uda_source` **UDA protection groups** `cohesity_uda_protection_group` **Oracle source registration** playbook `oracle-workflow.register_oracle_source` **Oracle source refresh** playbook `oracle-workflow.refresh_oracle_source` **Oracle protection job** playbook `oracle-workflow.create_oracle_job` **Oracle recovery** playbook `oracle-workflow.recover_db` **SQL Server source registration** playbook `sql-workflow.register_sql_source` **UDA source registration** playbook `uda-workflow.register_uda_source` **UDA protection group** playbook `uda-workflow.create_uda_protection_group`
Notes	• Module names have the cohesity_ prefix omitted; playbooks are grouped by the workload they protect.

Use Case: Manage policies, storage domains and cluster runs

Description	Create protection policies and storage domains, start, stop or delete protection groups, and gather cluster facts.
Collection	`cohesity.dataprotect` (Certified, Cohesity)

Key content	**Protection policies** `cohesity_policy` **Storage domains** `cohesity_storage_domain` **Cluster facts** `cohesity_facts` **Policy creation** playbook `policy.create_policy` **Policy deletion** playbook `policy.delete_policy` **Storage domain creation** playbook `storage_domain_workflow.create_storage_domain` **Storage domain deletion** playbook `storage_domain_workflow.delete_storage_domain` **Protection group start** playbook `common.start_protection_group` **Protection group stop** playbook `common.stop_protection_group` **Protection group deletion** playbook `common.delete_protection_group` **Facts export** playbook `facts`
Notes	• Module names have the cohesity_ prefix omitted; playbooks are grouped by the workload they protect.

Dell PowerFlex `dellemc.powerflex`

Certified Dell Technologies · version 3.2.0 · updated 2026-10-07 · 25 modules → 8 use cases

Use Case: Provision volumes, snapshots and clones

Description	Create and map volumes, take snapshots, schedule snapshot policies and create thin clones.
Collection	`dellemc.powerflex` (Certified, Dell Technologies)
Key content	**Volumes** `volume` **Volumes (5.x)** `volume_v2` **Snapshots** `snapshot` **Snapshots (5.x)** `snapshot_v2` **Snapshot policies** `snapshot_policy` **Thin clones (5.x)** `thin_clone` **Thin clone sample playbook** playbook `modules.thin_clone_example` **Volumes sample playbook** playbook `modules.volume` **Volumes (5.x) sample playbook** playbook `modules.volume_v2` **Snapshots sample playbook** playbook `modules.snapshot` **Snapshots (5.x) sample playbook** playbook `modules.snapshot_v2` **Snapshot policies sample playbook** playbook `modules.snapshot_policy`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Use Case: Manage protection domains, pools and devices

Description	Create protection domains, storage pools, fault sets, devices, device groups and storage nodes.
Collection	`dellemc.powerflex` (Certified, Dell Technologies)
Key content	**Protection domains** `protection_domain` **Protection domains (5.x)** `protection_domain_v2` **Storage pools** `storagepool` **Storage pools (5.x)** `storagepool_v2` **Fault sets** `fault_set` **Devices** `device` **Devices (5.x)** `device_v2` **Device groups (5.x)** `device_group` **Storage nodes (5.x)** `storage_node` **Protection domains sample playbook** playbook `modules.protection_domain` **Protection domains (5.x) sample playbook** playbook `modules.protection_domain_v2` **Storage pools sample playbook** playbook `modules.storagepool` **Storage pools (5.x) sample playbook** playbook `modules.storagepool_v2` **Fault sets sample playbook** playbook `modules.fault_set` **Devices sample playbook** playbook `modules.device` **Devices (5.x) sample playbook** playbook `modules.device_v2` **Device groups (5.x) sample playbook** playbook `modules.device_group` **Storage nodes (5.x) sample playbook** playbook `modules.storage_node`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Use Case: Manage cluster components and hosts

Description	Manage the MDM cluster, SDCs, SDSs, SDTs and NVMe hosts.
Collection	`dellemc.powerflex` (Certified, Dell Technologies)

Key content	**MDM cluster** `mdm_cluster` **SDCs** `sdc` **SDSs** `sds` **SDTs (NVMe targets)** `sdt` **NVMe hosts** `nvme_host` **MDM cluster sample playbook** playbook `modules.mdm_cluster` **SDCs sample playbook** playbook `modules.sdc` **SDSs sample playbook** playbook `modules.sds` **SDTs (NVMe targets) sample playbook** playbook `modules.sdt` **NVMe hosts sample playbook** playbook `modules.nvme_host`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Use Case: Replicate volumes between systems

Description	Manage replication pairs and replication consistency groups.
Collection	`dellemc.powerflex` (Certified, Dell Technologies)
Key content	**Replication pairs** `replication_pair` **Replication consistency groups** `replication_consistency_group` **Replication pairs sample playbook** playbook `modules.replication_pair` **Replication consistency groups sample playbook** playbook `modules.replication_consistency_group`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Use Case: Deploy resource groups

Description	Manage resource group deployments.
Collection	`dellemc.powerflex` (Certified, Dell Technologies)
Key content	**Resource groups** `resource_group` **Resource groups sample playbook** playbook `modules.resource_group`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Use Case: Install and uninstall PowerFlex components

Description	Install or remove the MDM, SDS, SDC, SDT, SDR, gateway, ActiveMQ, LIA, tie-breaker and web UI, then configure protection domains, fault sets and pools.
Collection	`dellemc.powerflex` (Certified, Dell Technologies)
Key content	**Common functions** role `powerflex_common` **MDM** role `powerflex_mdm` **Tie-breaker** role `powerflex_tb` **SDS** role `powerflex_sds` **SDC** role `powerflex_sdc` **SDT** role `powerflex_sdt` **SDR** role `powerflex_sdr` **LIA** role `powerflex_lia` **Gateway** role `powerflex_gateway` **ActiveMQ** role `powerflex_activemq` **Web UI** role `powerflex_webui` **Protection domain, fault set and pool configuration** role `powerflex_config` **Installation** playbook `roles.site` **Installation (4.5)** playbook `roles.site_powerflex45` **SDC uninstall** playbook `roles.uninstall_powerflex` **SDC uninstall (4.5)** playbook `roles.uninstall_powerflex45`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Use Case: Provision Gen2 (5.x) storage with roles

Description	Provision devices, storage nodes, infrastructure, volumes and snapshots on PowerFlex Gen2 systems.

Collection	`dellemc.powerflex` (Certified, Dell Technologies)
Key content	**Gen2 provisioning** role `powerflex_provisioning_v2` **Device and storage node provisioning** playbook `roles.powerflex_provisioning_v2_devices` **Infrastructure provisioning** playbook `roles.powerflex_provisioning_v2_infrastructure` **Volume lifecycle** playbook `roles.powerflex_provisioning_v2_volumes` **Snapshot and thin clone management** playbook `roles.powerflex_provisioning_v2_snapshots`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Use Case: Query, validate and diagnose the system

Description	Gather system information, detect Gen2 systems, and validate configuration and diagnostics.
Collection	`dellemc.powerflex` (Certified, Dell Technologies)
Key content	**System information** `info` **System information (5.x)** `info_v2` **Gen2 detection and validation** role `powerflex_common_v2` **Gen2 queries, validation and diagnostics** role `powerflex_system_v2` **Gen2 detection and validation** playbook `roles.powerflex_common_v2` **Gen2 system queries** playbook `roles.powerflex_system_v2_queries` **Gen2 configuration validation** playbook `roles.powerflex_system_v2_validation` **Gen2 diagnostics** playbook `roles.powerflex_system_v2_diagnostics` **System information sample playbook** playbook `modules.info` **System information (5.x) sample playbook** playbook `modules.info_v2`
Notes	• Each module has a matching sample playbook (modules.*); _v2 modules target PowerFlex 5.x (Gen2) systems.

Dell PowerMax / VMAX `dellemc.powermax`

Certified Dell Technologies · version 4.1.0 · updated 2026-07-28 · 17 modules → 4 use cases

Use Case: Provision storage groups, volumes and pools

Description	Create storage groups, volumes and storage pools and place volumes where capacity allows.
Collection	`dellemc.powermax` (Certified, Dell Technologies)
Key content	**Storage groups** `storagegroup` **Volumes** `volume` **Storage pools** `storagepool` **Storage pool processing** `process_storage_pool_dict` **Capacity-optimized placement** role `capacity_role` **Intelligent volume placement** playbook `capacity_role` **Storage group playbook** playbook `storagegroup` **Volume playbook** playbook `volume` **Storage pool playbook** playbook `storagepool`

Use Case: Connect hosts through masking views

Description	Manage hosts, host groups, initiators, ports, port groups and masking views.
Collection	`dellemc.powermax` (Certified, Dell Technologies)
Key content	**Hosts** `host` **Host groups** `hostgroup` **Initiators** `initiator` **Ports** `port` **Port groups** `portgroup` **Masking views** `maskingview` **Host playbook** playbook `host` **Host group playbook** playbook `hostgroup` **Initiator playbook** playbook `initiator` **Port playbook** playbook `port` **Port group playbook** playbook `portgroup` **Masking view playbook** playbook `maskingview`

Use Case: Protect and replicate data

Description	Manage snapshots, snapshot policies, SRDF pairs, RDF groups and Metro DR environments.
Collection	`dellemc.powermax` (Certified, Dell Technologies)
Key content	**Snapshots** `snapshot` **Snapshot policies** `snapshotpolicy` **SRDF pairs** `srdf` **RDF groups** `rdfgroup` **Metro DR** `metrodr` **Snapshot playbook** playbook `snapshot` **Snapshot policy playbook** playbook `snapshotpolicy` **SRDF playbook** playbook `srdf` **RDF group playbook** playbook `rdfgroup` **Metro DR playbook** playbook `metrodr`

Use Case: Gather array information and job status

Description	Collect information about array entities and check job details.
Collection	`dellemc.powermax` (Certified, Dell Technologies)
Key content	**Array information** `info` **Jobs** `job` **Info playbook** playbook `info` **Job playbook** playbook `job`

Dell PowerScale (OneFS) `dellemc.powerscale`

Certified Dell Technologies · version 3.11.0 · updated 2026-10-07 · 57 modules → 9 use cases

Use Case: Manage filesystems, quotas and storage tiering

Description	Manage filesystems and their ACLs, enforce Smart Quotas, and define file pool policies, storage pool tiers and SmartPools settings.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)
Key content	**Filesystems** `filesystem` **Smart Quotas** `smartquota` **File pool policies** `filepoolpolicy` **Storage pool tiers** `storagepooltier` **SmartPools settings** `smartpoolsettings` **Filesystems playbook** playbook `modules.filesystem` **Filesystem ACL example: multi-trustee, container inherit** playbook `modules.filesystem_mult_ace_container_inherit` **Filesystem ACL example: allow and deny for one trustee** playbook `modules.filesystem_mult_ace_container_inherit_only` **Filesystem ACL example: multi-trustee, full inheritance** playbook `modules.filesystem_mult_ace_object_container_inherit` **Filesystem ACL example: multi-trustee, object inherit** playbook `modules.filesystem_mult_ace_object_inherit` **Filesystem ACL example: multi-trustee, object inherit without propagation** playbook `modules.filesystem_mult_ace_object_no_prop` **Smart Quotas playbook** playbook `modules.smartquota` **File pool policies playbook** playbook `modules.filepoolpolicy` **Storage pool tiers playbook** playbook `modules.storagepooltier` **SmartPools settings playbook** playbook `modules.smartpoolsettings`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Protect data with snapshots and SyncIQ replication

Description	Take, schedule and expose writable snapshots, and configure SyncIQ policies, jobs, performance rules, certificates, global settings and reports.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)

Key content	**Snapshots** `snapshot` **Snapshot schedules** `snapshotschedule` **Writable snapshots** `writable_snapshots` **SyncIQ policies** `synciqpolicy` **SyncIQ jobs** `synciqjob` **SyncIQ performance rules** `synciqrules` **SyncIQ target certificates** `synciqcertificate` **SyncIQ global settings** `synciq_global_settings` **SyncIQ reports** `synciqreports` **SyncIQ target reports** `synciqtargetreports` **Snapshots playbook** playbook `modules.snapshot` **Snapshot schedules playbook** playbook `modules.snapshotschedule` **Writable snapshots playbook** playbook `modules.writable_snapshots` **SyncIQ policies playbook** playbook `modules.synciqpolicy` **SyncIQ jobs playbook** playbook `modules.synciqjobs` **SyncIQ performance rules playbook** playbook `modules.synciqrules` **SyncIQ target certificates playbook** playbook `modules.synciqcertificate` **SyncIQ global settings playbook** playbook `modules.synciq_global_settings` **SyncIQ reports playbook** playbook `modules.synciqreports` **SyncIQ target reports playbook** playbook `modules.synciqtargetreports`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Share files over NFS and SMB

Description	Create NFS exports and aliases and SMB shares and files, and set the NFS and SMB defaults, global and zone settings.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)
Key content	**NFS exports** `nfs` **NFS aliases** `nfs_alias` **NFS default settings** `nfs_default_settings` **NFS global settings** `nfs_global_settings` **NFS zone settings** `nfs_zone_settings` **SMB shares** `smb` **SMB files** `smb_file` **SMB global settings** `smb_global_settings` **NFS exports playbook** playbook `modules.nfs` **NFS aliases playbook** playbook `modules.nfs_alias` **NFS default settings playbook** playbook `modules.nfs_default_settings` **NFS global settings playbook** playbook `modules.nfs_global_settings` **NFS zone settings playbook** playbook `modules.nfs_zone_settings` **SMB shares playbook** playbook `modules.smb` **SMB files playbook** playbook `modules.smb_file` **SMB global settings playbook** playbook `modules.smb_global_settings`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Provide S3 object storage

Description	Create S3 buckets and access keys and set the S3 global and zone settings.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)
Key content	**S3 buckets** `s3_bucket` **S3 keys** `s3_key` **S3 global settings** `s3_global_settings` **S3 zone settings** `s3_zone_settings` **S3 buckets playbook** playbook `modules.s3_bucket` **S3 keys playbook** playbook `modules.s3_key` **S3 global settings playbook** playbook `modules.s3_global_settings` **S3 zone settings playbook** playbook `modules.s3_zone_settings`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Manage access zones, identity and authentication

Description	Create access zones, connect Active Directory and LDAP providers, manage local users, groups and roles, user mapping rules and server certificates.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)

Key content	**Access zones** `accesszone` **Active Directory providers** `ads` **LDAP providers** `ldap` **Users** `user` **Groups** `group` **Roles** `role` **User mapping rules** `user_mapping_rule` **Server certificates** `server_certificate` **Access zones playbook** playbook `modules.accesszone` **Active Directory providers playbook** playbook `modules.ads` **LDAP providers playbook** playbook `modules.ldap` **Users playbook** playbook `modules.user` **Groups playbook** playbook `modules.group` **Roles playbook** playbook `modules.role` **User mapping rules playbook** playbook `modules.user_mapping_rules` **Server certificates playbook** playbook `modules.server_certificate`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Configure cluster networking

Description	Define groupnets, subnets, network pools, provisioning rules and network settings.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)
Key content	**Groupnets** `groupnet` **Subnets** `subnet` **Network pools** `networkpool` **Network provisioning rules** `networkrule` **Network settings** `networksettings` **Groupnets playbook** playbook `modules.groupnet` **Subnets playbook** playbook `modules.subnet` **Network pools playbook** playbook `modules.networkpool` **Network provisioning rules playbook** playbook `modules.networkrule` **Network settings playbook** playbook `modules.networksettings`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Configure alerts and support

Description	Set up alert channels, rules, settings and suppression, SNMP, Support Assist and IPMI.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)
Key content	**Alert channels** `alert_channel` **Alert rules** `alert_rule` **Alert settings** `alert_settings` **Event alert suppression** `event_alert_suppression` **SNMP settings** `snmp_settings` **Support Assist** `support_assist` **IPMI configuration** `ipmi` **Alert channels playbook** playbook `modules.alert_channel` **Alert rules playbook** playbook `modules.alert_rule` **Alert settings playbook** playbook `modules.alert_settings` **Event alert suppression playbook** playbook `modules.event_alert_suppression` **SNMP settings playbook** playbook `modules.snmp_settings` **Support Assist playbook** playbook `modules.support_assist` **IPMI configuration playbook** playbook `modules.ipmi`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Run and monitor cluster jobs

Description	Start and manage jobs, set job policies and read job types, events and reports.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)

Key content	**Jobs** `job`, `job_info` **Job policies** `job_policy` **Job types** `job_type_info` **Job events** `job_event_info` **Job reports** `job_report_info` **Jobs playbook** playbook `modules.job` **Jobs playbook** playbook `modules.job_info` **Job policies playbook** playbook `modules.job_policy` **Job types playbook** playbook `modules.job_type_info` **Job events playbook** playbook `modules.job_event_info` **Job reports playbook** playbook `modules.job_report_info`
Notes	• Each module has a matching example playbook under modules/.

Use Case: Administer the cluster and gather facts

Description	Collect cluster and node information, manage cluster services and general settings.
Collection	`dellemc.powerscale` (Certified, Dell Technologies)
Key content	**Cluster information** `info` **Nodes** `node` **Cluster services** `cluster_services` **General settings** `settings` **Cluster information playbook** playbook `modules.info` **Module defaults example playbook** playbook `modules.module_defaults_example` **Nodes playbook** playbook `modules.node` **Cluster services playbook** playbook `modules.cluster_services` **General settings playbook** playbook `modules.settings`
Notes	• Each module has a matching example playbook under modules/.

Dell PowerStore `dellemc.powerstore`

Certified Dell Technologies · version 3.8.1 · updated 2026-03-17 · 45 modules → 7 use cases

Use Case: Provision block storage: volumes and volume groups

Description	Create, modify, map and delete volumes and volume groups, and bulk-create or search volumes.
Collection	`dellemc.powerstore` (Certified, Dell Technologies)
Key content	**Volumes** `volume` **Volume groups** `volumegroup` **Storage containers** `storage_container` **Volumes above a capacity threshold** playbook `samples.capacity_volumes` **Multiple volume creation** playbook `samples.create_multiple_volumes` **Asynchronous multiple volume creation** playbook `samples.create_multiple_volumes_async` **Multiple volume deletion** playbook `samples.delete_multiple_volumes` **Empty volume group search** playbook `samples.find_empty_volume_groups` **Volume search by name pattern** playbook `samples.search_volumes` **Volumes sample playbook** playbook `modules.volume` **Volume groups sample playbook** playbook `modules.volumegroup` **Storage containers sample playbook** playbook `modules.storage_container`
Notes	• Each module has a matching sample playbook (modules.*), listed with it; further playbooks under samples.* show multi-step workflows.

Use Case: Manage hosts and performance limits

Description	Register hosts and host groups, attach vCenter, and apply IO limit and QoS policies.
Collection	`dellemc.powerstore` (Certified, Dell Technologies)

Key content	**Hosts** `host` **Host groups** `hostgroup` **vCenter** `vcenter` **IO limit rules** `io_limit_rule` **QoS policies** `qos_policy` **Hosts sample playbook** playbook `modules.host` **Host groups sample playbook** playbook `modules.hostgroup` **vCenter sample playbook** playbook `modules.vcenter` **IO limit rules sample playbook** playbook `modules.io_limit_rule` **QoS policies sample playbook** playbook `modules.qos_policy`
Notes	• Each module has a matching sample playbook (modules.*), listed with it; further playbooks under samples.* show multi-step workflows.

Use Case: Provision file storage: NAS servers, file systems and shares

Description	Create NAS servers with file interfaces, DNS and NIS, file systems, NFS exports and SMB shares, and apply quotas.
Collection	`dellemc.powerstore` (Certified, Dell Technologies)
Key content	**NAS servers** `nasserver` **File interfaces** `file_interface` **File DNS** `file_dns` **File NIS** `file_nis` **NFS servers** `nfs_server` **SMB servers** `smb_server` **File systems** `filesystem` **NFS exports** `nfs` **SMB shares** `smbshare` **Quotas** `quota` **File IO limit rules** `file_io_limit_rule` **NAS server end-to-end setup** playbook `samples.nas_server_end_to_end` **File systems above a used-size threshold** playbook `samples.get_fs_used_size_greaterthan_threshold` **SMB shares of a file system** playbook `samples.get_smbshares_associated_with_given_fs_name` **Unused file systems** playbook `samples.get_unused_fs` **NAS servers sample playbook** playbook `modules.nasserver` **File interfaces sample playbook** playbook `modules.file_interface` **File DNS sample playbook** playbook `modules.file_dns` **File NIS sample playbook** playbook `modules.file_nis` **NFS servers sample playbook** playbook `modules.nfs_server` **SMB servers sample playbook** playbook `modules.smb_server` **File systems sample playbook** playbook `modules.filesystem` **NFS exports sample playbook** playbook `modules.nfs` **SMB shares sample playbook** playbook `modules.smbshare` **Quotas sample playbook** playbook `modules.quota` **File IO limit rules sample playbook** playbook `modules.file_io_limit_rule`
Notes	• Each module has a matching sample playbook (modules.*), listed with it; further playbooks under samples.* show multi-step workflows.

Use Case: Protect data with snapshots and replication

Description	Define protection and snapshot rules, take snapshots, replicate to remote systems and recover from the recycle bin.
Collection	`dellemc.powerstore` (Certified, Dell Technologies)
Key content	**Protection policies** `protectionpolicy` **Snapshot rules** `snapshotrule` **Snapshots** `snapshot` **File system snapshots** `filesystem_snapshot` **Replication rules** `replicationrule` **Replication sessions** `replicationsession` **Remote systems** `remotesystem` **Recycle bin** `recycle_bin` **Protection policies sample playbook** playbook `modules.protectionpolicy` **Snapshot rules sample playbook** playbook `modules.snapshotrule` **Snapshots sample playbook** playbook `modules.snapshot` **File system snapshots sample playbook** playbook `modules.filesystem_snapshot` **Replication rules sample playbook** playbook `modules.replicationrule` **Replication sessions sample playbook** playbook `modules.replicationsession` **Remote systems sample playbook** playbook `modules.remotesystem` **Recycle bin sample playbook** playbook `modules.recycle_bin`
Notes	• Each module has a matching sample playbook (modules.*), listed with it; further playbooks under samples.* show multi-step workflows.

Use Case: Administer users, directory services and security

Description	Manage local users, roles, LDAP domains and accounts, certificates and security configuration.

Collection	`dellemc.powerstore` (Certified, Dell Technologies)
Key content	**Local users** `local_user` **Roles** `role` **LDAP domains** `ldap_domain` **LDAP accounts** `ldap_account` **Certificates** `certificate` **Security configuration** `security_config` **Local users sample playbook** playbook `modules.local_user` **Roles sample playbook** playbook `modules.role` **LDAP domains sample playbook** playbook `modules.ldap_domain` **LDAP accounts sample playbook** playbook `modules.ldap_account` **Certificates sample playbook** playbook `modules.certificate` **Security configuration sample playbook** playbook `modules.security_config`
Notes	• Each module has a matching sample playbook (modules.*), listed with it; further playbooks under samples.* show multi-step workflows.

Use Case: Configure the cluster, networks and notifications

Description	Set up cluster, networks, DNS, NTP, SMTP, email destinations, SNMP, remote support and service configuration.
Collection	`dellemc.powerstore` (Certified, Dell Technologies)
Key content	**Cluster** `cluster` **Networks** `network` **DNS** `dns` **NTP** `ntp` **SMTP** `smtp_config` **Email destinations** `email` **SNMP managers** `snmp_manager` **Remote support** `remote_support` **Remote support contacts** `remote_support_contact` **Service configuration** `service_config` **Cluster sample playbook** playbook `modules.cluster` **Networks sample playbook** playbook `modules.network` **DNS sample playbook** playbook `modules.dns` **NTP sample playbook** playbook `modules.ntp` **SMTP sample playbook** playbook `modules.smtp_config` **Email destinations sample playbook** playbook `modules.email` **SNMP managers sample playbook** playbook `modules.snmp_manager` **Remote support sample playbook** playbook `modules.remote_support` **Remote support contacts sample playbook** playbook `modules.remote_support_contact` **Service configuration sample playbook** playbook `modules.service_config`
Notes	• Each module has a matching sample playbook (modules.*), listed with it; further playbooks under samples.* show multi-step workflows.

Use Case: Gather system information and track jobs

Description	Collect facts about PowerStore entities and monitor asynchronous jobs.
Collection	`dellemc.powerstore` (Certified, Dell Technologies)
Key content	**Facts** `info` **Jobs** `job` **Facts sample playbook** playbook `modules.info` **Jobs sample playbook** playbook `modules.job`
Notes	• Each module has a matching sample playbook (modules.*), listed with it; further playbooks under samples.* show multi-step workflows.

Dell Unity `dellemc.unity`

Certified Dell Technologies · version 2.1.0 · updated 2025-08-08 · 18 modules → 5 use cases

Use Case: Manage block storage and volumes

Description	Create and modify storage pools, volumes and consistency groups, and manage hosts that access them.
Collection	`dellemc.unity` (Certified, Dell Technologies)

Key content	**Storage pools** `storagepool` **Volumes** `volume` **Consistency groups** `consistencygroup` **Hosts** `host` **Network interfaces** `interface` **Storage pool playbook** playbook `modules.storagepool` **Volume playbook** playbook `modules.volume` **Consistency group playbook** playbook `modules.consistencygroup` **Host playbook** playbook `modules.host` **Interface playbook** playbook `modules.interface`

Use Case: Manage NAS servers, file systems and shares

Description	Create NAS servers, CIFS and NFS servers, file systems, SMB shares and NFS exports.
Collection	`dellemc.unity` (Certified, Dell Technologies)
Key content	**NAS servers** `nasserver` **CIFS servers** `cifsserver` **NFS servers** `nfsserver` **File systems** `filesystem` **SMB shares** `smbshare` **NFS exports** `nfs` **NAS server playbook** playbook `modules.nasserver` **CIFS server playbook** playbook `modules.cifsserver` **NFS server playbook** playbook `modules.nfsserver` **File system playbook** playbook `modules.filesystem` **SMB share playbook** playbook `modules.smbshare` **NFS share playbook** playbook `modules.nfs`

Use Case: Protect data with snapshots and replication

Description	Manage snapshots, snapshot schedules and replication sessions.
Collection	`dellemc.unity` (Certified, Dell Technologies)
Key content	**Snapshots** `snapshot` **File system snapshots** `filesystem_snapshot` **Snapshot schedules** `snapshotschedule` **Replication sessions** `replication_session` **Snapshot playbook** playbook `modules.snapshot` **File system snapshot playbook** playbook `modules.filesystem_snapshot` **Snapshot schedule playbook** playbook `modules.snapshotschedule` **Replication session playbook** playbook `modules.replication_session`

Use Case: Control capacity with quotas

Description	Manage quota trees and user quotas on file systems.
Collection	`dellemc.unity` (Certified, Dell Technologies)
Key content	**Tree quotas** `tree_quota` **User quotas** `user_quota` **Tree quota playbook** playbook `modules.tree_quota` **User quota playbook** playbook `modules.user_quota`

Use Case: Gather Unity information

Description	Collect information about the Unity storage system.
Collection	`dellemc.unity` (Certified, Dell Technologies)
Key content	**Unity information** `info` **Info playbook** playbook `modules.info`

Dell VPLEX `dellemc.vplex`

Certified Dell Technologies · version 1.3.0 · updated 2025-07-11 · 15 modules → 4 use cases

Use Case: Provision storage and virtual volumes

Description	Manage storage volumes, extents, devices, distributed devices, and virtual and distributed virtual volumes, and rediscover arrays.
Collection	`dellemc.vplex` (Certified, Dell Technologies)
Key content	**Arrays** `dellemc_vplex_array` **Storage volumes** `dellemc_vplex_storage_volume` **Extents** `dellemc_vplex_extent` **Devices** `dellemc_vplex_device` **Distributed devices** `dellemc_vplex_distributed_device` **Virtual volumes** `dellemc_vplex_virtual_volume` **Distributed virtual volumes** `dellemc_vplex_distributed_virtual_volume` **Local device creation** role `createdevice` **Local device teardown** role `removedevice`

Use Case: Present storage to hosts

Description	Manage initiators, ports and storage views.
Collection	`dellemc.vplex` (Certified, Dell Technologies)
Key content	**Initiators** `dellemc_vplex_initiator` **Ports** `dellemc_vplex_port` **Storage views** `dellemc_vplex_storage_view` **Storage view creation** role `createstorageview`

Use Case: Protect and migrate data

Description	Manage consistency groups, distributed consistency groups and data migrations.
Collection	`dellemc.vplex` (Certified, Dell Technologies)
Key content	**Consistency groups** `dellemc_vplex_consistency_group` **Distributed consistency groups** `dellemc_vplex_distributed_consistency_group` **Data migrations** `dellemc_vplex_data_migration`

Use Case: Gather VPLEX information

Description	Gather storage details and map storage entity usage hierarchy.
Collection	`dellemc.vplex` (Certified, Dell Technologies)
Key content	**Storage details** `dellemc_vplex_gatherfacts` **Usage hierarchy maps** `dellemc_vplex_maps`

Everpure (Pure Storage) FlashArray `everpure.flasharray`

Certified Everpure · version 1.45.1 · updated 2026-09-17 · 78 modules → 9 use cases

Use Case: Provision volumes and connect hosts

Description	Create volumes and volume groups, define hosts, host groups and VMware protocol endpoints, and apply QoS and tags.
Collection	`everpure.flasharray` (Certified, Everpure)

Key content	**Volumes** `purefa_volume` **Volume tags** `purefa_volume_tags` **Volume groups** `purefa_vg` **Hosts** `purefa_host` **Host groups** `purefa_hg` **Protocol endpoints** `purefa_endpoint` **QoS policies** `purefa_qos_policy` **Resource tags** `purefa_tags`
Notes	• Module names have the purefa_ prefix omitted.

Use Case: Protect data with snapshots and protection groups

Description	Take volume snapshots, schedule protection group snapshots and replication, set SafeMode defaults and eradication timers, and manage offload targets.
Collection	`everpure.flasharray` (Certified, Everpure)
Key content	**Volume snapshots** `purefa_snap` **Protection groups** `purefa_pg` **Protection group snapshots** `purefa_pgsnap` **Protection group schedules** `purefa_pgsched` **SafeMode default protection** `purefa_default_protection` **Eradication timer** `purefa_eradication` **Offload targets** `purefa_offload`
Notes	• Module names have the purefa_ prefix omitted.

Use Case: Replicate and stretch across arrays

Description	Connect arrays, and manage ActiveCluster pods and ActiveDR replica links.
Collection	`everpure.flasharray` (Certified, Everpure)
Key content	**Array connections** `purefa_connect` **Pods** `purefa_pod` **Pod replica links** `purefa_pod_replica`
Notes	• Module names have the purefa_ prefix omitted.

Use Case: Provide file services

Description	Manage file systems, directories, exports, file servers, policies, directory snapshots and file copies.
Collection	`everpure.flasharray` (Certified, Everpure)
Key content	**File systems** `purefa_fs` **Directories** `purefa_directory` **Directory snapshots** `purefa_dirsnap` **File exports** `purefa_export` **File copies** `purefa_file` **File system policies** `purefa_policy` **File servers** `purefa_server`
Notes	• Module names have the purefa_ prefix omitted.

Use Case: Configure array networking

Description	Manage network interfaces, subnets, VLANs, network access policies, DNS and TLS policies.
Collection	`everpure.flasharray` (Certified, Everpure)
Key content	**Network interfaces** `purefa_network` **Subnets** `purefa_subnet` **VLANs** `purefa_vlan` **Network access policies** `purefa_network_access_policy` **DNS** `purefa_dns` **TLS policies** `purefa_tls_policy`

Notes	• Module names have the purefa_ prefix omitted.

Use Case: Manage users, directory services and authentication

Description	Manage local users, groups and API tokens, Active Directory, directory services and roles, SAML, RBAC policies, certificates and KMIP.
Collection	`everpure.flasharray` (Certified, Everpure)
Key content	**Local users** `purefa_user` **Local users (directory service)** `purefa_localuser` **Local groups** `purefa_localgroup` **Local directory services** `purefa_lds` **API tokens** `purefa_token` **API clients** `purefa_apiclient` **Active Directory accounts** `purefa_ad` **Directory service** `purefa_ds` **Directory service roles** `purefa_dsrole` **Directory service roles (pre-6.6.3)** `purefa_dsrole_old` **SAML identity providers** `purefa_saml` **Management access policies** `purefa_policy_management_access` **SSL certificates** `purefa_certs` **KMIP servers** `purefa_kmip`
Notes	• Module names have the purefa_ prefix omitted.

Use Case: Monitor the array and forward logs

Description	Configure alerts, email, SNMP and syslog, review audits, messages and sessions, collect metrics and manage phone home and remote assist.
Collection	`everpure.flasharray` (Certified, Everpure)
Key content	**Alert email** `purefa_alert` **SMTP** `purefa_smtp` **SNMP managers** `purefa_snmp` **SNMP agent** `purefa_snmp_agent` **Syslog** `purefa_syslog` **Syslog servers** `purefa_syslog_settings` **Audit and session logs** `purefa_logging` **Audit events** `purefa_audits` **Alert messages** `purefa_messages` **Sessions** `purefa_sessions` **OpenMetrics data** `purefa_metrics` **Phone home** `purefa_phonehome` **Phone home proxy** `purefa_proxy` **Remote assist** `purefa_ra`
Notes	• Module names have the purefa_ prefix omitted.

Use Case: Administer array settings and lifecycle

Description	Set array name, banners, timeouts, time, maintenance windows, EULA, hardware identification, capacity expansion and erasure, and collect array information.
Collection	`everpure.flasharray` (Certified, Everpure)

Key content	**Global admin settings** `purefa_admin` **Array name** `purefa_arrayname` **Login banners** `purefa_banner` **Console lock** `purefa_console` **GUI idle timeout** `purefa_timeout` **NTP** `purefa_ntp` **Maintenance windows** `purefa_maintenance` **EULA** `purefa_eula` **Hardware identification** `purefa_hardware` **Cloud Block Store capacity** `purefa_cbsexpand` **SMI-S** `purefa_smis` **VNC port** `purefa_vnc` **Zero Touch Erasure** `purefa_zte` **Array information** `purefa_info` **Inventory** `purefa_inventory`
Notes	• Module names have the purefa_ prefix omitted.

Use Case: Organise Fusion fleets and workloads

Description	Manage Fusion fleets, workloads, realms and topology groups.
Collection	`everpure.flasharray` (Certified, Everpure)
Key content	**Fleets** `purefa_fleet` **Workloads** `purefa_workload` **Realms** `purefa_realm` **Topology groups** `purefa_tgroup`
Notes	• Module names have the purefa_ prefix omitted.

Everpure FlashBlade `everpure.flashblade`

Certified Everpure · version 1.28.0 · updated 2026-09-17 · 66 modules → 8 use cases

Use Case: Provision file systems, exports and snapshots

Description	Create file systems and exports, take snapshots, set quotas, and apply policies.
Collection	`everpure.flashblade` (Certified, Everpure)
Key content	**File systems** `purefb_fs` **File system exports** `purefb_export` **File system snapshots** `purefb_snap` **Group quotas** `purefb_groupquota` **User quotas** `purefb_userquota` **Policies** `purefb_policy`

Use Case: Provision object storage

Description	Manage S3 object store accounts, users, buckets, access and lifecycle rules, virtual hosts, remote credentials and export policies.
Collection	`everpure.flashblade` (Certified, Everpure)
Key content	**Object store accounts** `purefb_s3acc` **Account exports** `purefb_s3acc_export` **Object store users** `purefb_s3user` **Buckets** `purefb_bucket` **Bucket access policies** `purefb_bucket_access` **Lifecycle rules** `purefb_lifecycle` **User access policies** `purefb_userpolicy` **S3 export policies** `purefb_s3_export_policy` **Virtual hosts** `purefb_virtualhost` **Remote credentials** `purefb_remote_cred`

Use Case: Replicate and back up data

Description	Set up replication connections and file system or bucket replica links, remote targets, realms and fleets.
Collection	`everpure.flashblade` (Certified, Everpure)
Key content	**Replication connections** `purefb_connect` **File system replica links** `purefb_fs_replica` **Bucket replica links** `purefb_bucket_replica` **Remote S3 targets** `purefb_target` **Realms** `purefb_realm` **Fusion fleets** `purefb_fleet`

Use Case: Configure networking

Description	Configure network interfaces, subnets, link aggregation groups and DNS, and test connectivity.
Collection	`everpure.flashblade` (Certified, Everpure)
Key content	**Network interfaces** `purefb_network` **Subnets** `purefb_subnet` **Link aggregation groups** `purefb_lag` **DNS** `purefb_dns` **Ping and trace** `purefb_pingtrace`

Use Case: Integrate directory services and authentication

Description	Configure Active Directory, directory services and roles, local directory users and groups, Kerberos keytabs, SAML and management accounts.
Collection	`everpure.flashblade` (Certified, Everpure)
Key content	**Active Directory accounts** `purefb_ad` **Directory services** `purefb_ds` **Directory service roles** `purefb_dsrole` **Local directory services** `purefb_local_ds` **Local groups** `purefb_local_group` **Local users** `purefb_local_user` **Kerberos keytabs** `purefb_keytabs` **SAML identity providers** `purefb_saml` **User accounts** `purefb_user`

Use Case: Manage administrative access and security

Description	Control management roles and access policies, authentication policies, password policy, API clients, certificates, TLS and encryption key servers.
Collection	`everpure.flashblade` (Certified, Everpure)
Key content	**Global admin settings** `purefb_admin` **Management roles** `purefb_mgmt_role` **Management access policies** `purefb_mgmt_policy` **Management authentication policies** `purefb_mgmt_auth_policy` **Password policy** `purefb_password_policy` **API clients** `purefb_apiclient` **Resource access** `purefb_resource_access` **SSL certificates** `purefb_certs` **Certificate groups** `purefb_certgrp` **TLS policies** `purefb_tls_policy` **KMIP servers** `purefb_kmip` **GUI idle timeout** `purefb_timeout`

Use Case: Configure array identity and services

Description	Set the array name, banner, time zone, NTP, SMTP, EULA and servers.
Collection	`everpure.flashblade` (Certified, Everpure)

Key content	**Array name** `purefb_bladename` **Banner** `purefb_banner` **Time zone** `purefb_tz` **NTP** `purefb_ntp` **SMTP** `purefb_smtp` **EULA** `purefb_eula` **Servers** `purefb_server`

Use Case: Monitor, alert and get support

Description	Configure alert email, SNMP, syslog, phone home and remote assist, and collect array information, hardware state and alert messages.
Collection	`everpure.flashblade` (Certified, Everpure)
Key content	**Alert email** `purefb_alert` **Alert messages** `purefb_messages` **SNMP agent** `purefb_snmp_agent` **SNMP managers** `purefb_snmp_mgr` **Syslog** `purefb_syslog` **Phone home** `purefb_phonehome` **Phone home proxy** `purefb_proxy` **Remote assist** `purefb_ra` **Array information** `purefb_info` **Inventory** `purefb_inventory` **Hardware** `purefb_hardware`

Pure Storage Pure1 `everpure.pure1`

Certified Everpure · version 1.5.0 · updated 2026-06-29 · 8 modules → 1 use cases

Use Case: Monitor Pure Storage arrays through Pure1

Description	Collect alerts, drives, NICs, ports, pods and volumes information for arrays from Pure1, and manage array tags.
Collection	`everpure.pure1` (Certified, Everpure)
Key content	**Pure1 information** `pure1_info` **Array alerts** `pure1_alerts` **Array tags** `pure1_array_tags` **Array drives** `pure1_drives` **Network interfaces** `pure1_nics` **FlashArray pods** `pure1_pods` **FlashArray ports** `pure1_ports` **Volumes** `pure1_volumes`

Hitachi Vantara VSP One Block and SDS Block storage `hitachivantara.vspone_block`

Certified Hitachi Vantara · version 4.8.3 · updated 2026-10-14 · 181 modules → 18 use cases

Use Case: Provision volumes and connect hosts

Description	Create logical devices (LDEVs), host groups, iSCSI targets, NVM subsystems and PAV aliases, set host modes and server priorities, and attach volumes to hosts.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)

Key content	**Host groups** `hv_hg`, `hv_hg_facts` **Host groups bulk** `hv_hg_bulk` **iSCSI target** `hv_iscsi_target`, `hv_iscsi_target_facts` **iSCSI target bulk** `hv_iscsi_target_bulk` **LDEV** `hv_ldev`, `hv_ldev_facts` **LDEV bulk** `hv_ldev_bulk` **NVM subsystems** `hv_nvm_subsystems`, `hv_nvm_subsystems_facts` **PAV alias** `hv_pav_alias`, `hv_pav_alias_facts` **Server priority manager** `hv_server_priority_manager`, `hv_server_priority_manager_facts` **Supported host mode** `hv_supported_host_mode_facts` **VSP One server** `hv_vsp_one_server`, `hv_vsp_one_server_facts` **VSP One server HBA** `hv_vsp_one_server_hba_facts` **VSP One volume** `hv_vsp_one_volume`, `hv_vsp_one_volume_facts` **Delete LDEV from host playbook** playbook `vsp_direct.delete_ldev_from_host` **Host group playbook** playbook `vsp_direct.hostgroup` **Host group bulk playbook** playbook `vsp_direct.hostgroup_bulk` **Host group information playbook** playbook `vsp_direct.hostgroup_facts` **iSCSI target playbook** playbook `vsp_direct.iscsi_target` **iSCSI target bulk playbook** playbook `vsp_direct.iscsi_target_bulk` **iSCSI target information playbook** playbook `vsp_direct.iscsi_target_facts` **LDEV playbook** playbook `vsp_direct.ldev` **LDEV bulk playbook** playbook `vsp_direct.ldev_bulk` **LDEV information playbook** playbook `vsp_direct.ldev_facts` **NVM subsystem information playbook** playbook `vsp_direct.nvm_subsystem_facts` **NVM subsystems playbook** playbook `vsp_direct.nvm_subsystems` **PAV alias playbook** playbook `vsp_direct.pav_alias` **PAV alias information playbook** playbook `vsp_direct.pav_alias_facts` **Provision LDEV to host playbook** playbook `vsp_direct.provision_ldev_to_host` **Server priority manager playbook** playbook `vsp_direct.server_priority_manager` **Server priority manager information playbook** playbook `vsp_direct.server_priority_manager_facts` **Supported host mode information playbook** playbook `vsp_direct.supported_host_mode_facts` **VSP One server playbook** playbook `vsp_direct.vsp_one_server` **VSP One server information playbook** playbook `vsp_direct.vsp_one_server_facts` **VSP One server HBA information playbook** playbook `vsp_direct.vsp_one_server_hba_facts` **VSP One volume playbook** playbook `vsp_direct.vsp_one_volume` **VSP One volume information playbook** playbook `vsp_direct.vsp_one_volume_facts`

Use Case: Manage pools, parity groups and drives

Description	Manage storage pools, DDP pools, parity groups, cache logical partitions, disk drives and MP blades.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**CLPR** `hv_clpr`, `hv_clpr_facts` **Command device** `hv_cmd_dev` **DDP pool** `hv_ddp_pool`, `hv_ddp_pool_facts` **Disk drive** `hv_disk_drive`, `hv_disk_drive_facts` **MP** `hv_mp_facts` **Parity group** `hv_paritygroup`, `hv_paritygroup_facts` **Storage pool** `hv_storagepool`, `hv_storagepool_facts` **CLPR playbook** playbook `vsp_direct.clpr` **CLPR information playbook** playbook `vsp_direct.clpr_facts` **Command device playbook** playbook `vsp_direct.cmd_dev` **DDP pool playbook** playbook `vsp_direct.ddp_pool` **DDP pool information playbook** playbook `vsp_direct.ddp_pool_facts` **Disk drive playbook** playbook `vsp_direct.disk_drive` **Disk drive information playbook** playbook `vsp_direct.disk_drive_facts` **MP information playbook** playbook `vsp_direct.mp_facts` **Parity group playbook** playbook `vsp_direct.paritygroup` **Parity group information playbook** playbook `vsp_direct.paritygroup_facts` **Storage pool playbook** playbook `vsp_direct.storage_pool` **Storage pool information playbook** playbook `vsp_direct.storagepool_facts` **VSP One ddp pool playbook** playbook `vsp_direct.vsp_one_ddp_pool` **VSP One ddp pool information playbook** playbook `vsp_direct.vsp_one_ddp_pool_facts`

Use Case: Virtualize external storage

Description	Manage external parity groups, external volumes and external path groups to bring external storage under VSP control.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**External parity group** `hv_external_paritygroup`, `hv_external_paritygroup_facts` **External path group** `hv_external_path_group`, `hv_external_path_group_facts` **External volume** `hv_external_volume`, `hv_external_volume_facts` **External parity group playbook** playbook `vsp_direct.external_paritygroup` **External parity group information playbook** playbook `vsp_direct.external_paritygroup_facts` **External path group playbook** playbook `vsp_direct.external_path_group` **External path group information playbook** playbook `vsp_direct.external_path_group_facts` **External volume playbook** playbook `vsp_direct.external_volume` **External volume information playbook** playbook `vsp_direct.external_volume_facts`

Use Case: Manage storage ports

Description	Change storage port settings on VSP and VSP One block storage systems.

Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Storage port** `hv_storage_port`, `hv_storage_port_facts` **VSP One port** `hv_vsp_one_port`, `hv_vsp_one_port_facts` **Storage port playbook** playbook `vsp_direct.storage_port` **Storage port information playbook** playbook `vsp_direct.storage_port_facts` **VSP One port playbook** playbook `vsp_direct.vsp_one_port` **VSP One port information playbook** playbook `vsp_direct.vsp_one_port_facts`

Use Case: Protect data with snapshots and local copies

Description	Create and manage Shadow Image pairs and groups, Thin Image snapshots and snapshot groups, and view snapshot families and virtual clone parents.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Shadow image group** `hv_shadow_image_group`, `hv_shadow_image_group_facts` **Shadow image pair** `hv_shadow_image_pair`, `hv_shadow_image_pair_facts` **Snapshot** `hv_snapshot`, `hv_snapshot_facts` **Snapshot family** `hv_snapshot_family_facts` **Snapshot group** `hv_snapshot_group`, `hv_snapshot_group_facts` **Virtual clone parent volume** `hv_vclone_parent_volume_facts` **VSP One snapshot** `hv_vsp_one_snapshot`, `hv_vsp_one_snapshot_facts` **VSP One snapshot group** `hv_vsp_one_snapshot_group`, `hv_vsp_one_snapshot_group_facts` **Shadow image group playbook** playbook `vsp_direct.shadow_image_group` **Shadow image group information playbook** playbook `vsp_direct.shadow_image_group_facts` **Shadow image pair playbook** playbook `vsp_direct.shadow_image_pair` **Shadow image pair information playbook** playbook `vsp_direct.shadow_image_pair_facts` **Snapshot playbook** playbook `vsp_direct.snapshot` **Snapshot information playbook** playbook `vsp_direct.snapshot_facts` **Snapshot family information playbook** playbook `vsp_direct.snapshot_family_facts` **Snapshot group playbook** playbook `vsp_direct.snapshot_group` **Snapshot group information playbook** playbook `vsp_direct.snapshot_group_facts` **Virtual clone parent volume information playbook** playbook `vsp_direct.vclone_parent_volume_facts` **VSP One snapshot playbook** playbook `vsp_direct.vsp_one_snapshot` **VSP One snapshot information playbook** playbook `vsp_direct.vsp_one_snapshot_facts` **VSP One snapshot group playbook** playbook `vsp_direct.vsp_one_snapshot_group` **VSP One snapshot group information playbook** playbook `vsp_direct.vsp_one_snapshot_group_facts`

Use Case: Replicate remotely with TrueCopy and Universal Replicator

Description	Create and manage TrueCopy and Hitachi Universal Replicator pairs, journals, journal volumes and remote copy groups.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**HUR** `hv_hur`, `hv_hur_facts` **HUR bulk** `hv_hur_bulk` **Journal** `hv_journal`, `hv_journal_facts` **Remote copy group** `hv_remote_copy_group`, `hv_remote_copy_group_facts` **Truecopy** `hv_truecopy`, `hv_truecopy_facts` **Truecopy bulk** `hv_truecopy_bulk` **HUR playbook** playbook `vsp_direct.hur` **HUR bulk playbook** playbook `vsp_direct.hur_bulk` **HUR information playbook** playbook `vsp_direct.hur_facts` **HUR with first available journal pool playbook** playbook `vsp_direct.hur_with_first_available_journal_pool` **Journal playbook** playbook `vsp_direct.journal` **Journal information playbook** playbook `vsp_direct.journal_facts` **Journal volume playbook** playbook `vsp_direct.journal_volume` **Journal volume information playbook** playbook `vsp_direct.journal_volume_facts` **Remote copy group playbook** playbook `vsp_direct.remote_copy_group` **Remote copy group information playbook** playbook `vsp_direct.remote_copy_group_facts` **Truecopy playbook** playbook `vsp_direct.truecopy` **Truecopy bulk playbook** playbook `vsp_direct.truecopy_bulk` **Truecopy information playbook** playbook `vsp_direct.truecopy_facts`

Use Case: Build global-active device (GAD) pairs and migrate with NDM

Description	Create and manage GAD pairs and consistency groups and run non-disruptive migration workflows that create, migrate and clean up GAD pairs.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)

Key content	**GAD** `hv_gad`, `hv_gad_facts` **GAD bulk** `hv_gad_bulk` **VSP One gad** `hv_vsp_one_gad`, `hv_vsp_one_gad_facts` **VSP One gad consistency group** `hv_vsp_one_gad_consistency_group`, `hv_vsp_one_gad_consistency_group_facts` **Cleanup Workflow - Remove Primary Volumes, Remote Connections, Quorum Disks** playbook `ndm_gad_playbooks.cleanup_gad_pairs_pvol` **Complete GAD Migration Workflow - Query, Create, Migrate, Cleanup** playbook `ndm_gad_playbooks.create_gad_pairs_using_wwns` **Migrate Existing GAD Pairs - Discovery, Migration, Cleanup** playbook `ndm_gad_playbooks.migrate_gad_pairs` **GAD pair playbook** playbook `vsp_direct.gad_pair` **GAD pair bulk playbook** playbook `vsp_direct.gad_pair_bulk` **GAD pair information playbook** playbook `vsp_direct.gad_pair_facts` **VSP One gad consistency group playbook** playbook `vsp_direct.vsp_one_gad_consistency_group` **VSP One gad consistency group information playbook** playbook `vsp_direct.vsp_one_gad_consistency_group_facts` **VSP One gad information playbook** playbook `vsp_direct.vsp_one_gad_facts` **VSP One gad pair playbook** playbook `vsp_direct.vsp_one_gad_pair`

Use Case: Connect storage systems and configure quorum disks

Description	Register remote storage systems, set up remote and iSCSI remote connections, and create quorum disks for replication and GAD.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**iSCSI remote connection** `hv_iscsi_remote_connection`, `hv_iscsi_remote_connection_facts` **Quorum disk** `hv_quorum_disk`, `hv_quorum_disk_facts` **Remote connection** `hv_remote_connection`, `hv_remote_connection_facts` **Remote storage registration** `hv_remote_storage_registration`, `hv_remote_storage_registration_facts` **iSCSI remote connection playbook** playbook `vsp_direct.iscsi_remote_connection` **iSCSI remote connection information playbook** playbook `vsp_direct.iscsi_remote_connection_facts` **Quorum disk playbook** playbook `vsp_direct.quorum_disk` **Quorum disk information playbook** playbook `vsp_direct.quorum_disk_facts` **Remote connection playbook** playbook `vsp_direct.remote_connection` **Remote connection information playbook** playbook `vsp_direct.remote_connection_facts` **Remote storage registration playbook** playbook `vsp_direct.remote_storage_registration` **Remote storage registration information playbook** playbook `vsp_direct.remote_storage_registration_facts`

Use Case: Control access with resource groups and locks

Description	Manage resource groups, lock and unlock them, and run lock-aware workflows against a single or replicated storage system.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Resource group** `hv_resource_group`, `hv_resource_group_facts` **Resource group lock** `hv_resource_group_lock` **Resource Group Lock Playbook** playbook `resource_management_with_lock.vsp_direct.remote_replication_example` **GAD and GAD Bulk Resource Group Lock Playbook** playbook `resource_management_with_lock.vsp_direct.remote_replication_gad` **Resource Group Lock Management** playbook `resource_management_with_lock.vsp_direct.single_storage_example` **Resource group playbook** playbook `vsp_direct.resource_group` **Resource group information playbook** playbook `vsp_direct.resource_group_facts`

Use Case: Manage users, user groups and sessions

Description	Manage users, user groups and API sessions on VSP block storage systems.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Session** `hv_session`, `hv_session_facts` **User** `hv_user`, `hv_user_facts` **User group** `hv_user_group`, `hv_user_group_facts` **Session playbook** playbook `vsp_direct.session` **Session information playbook** playbook `vsp_direct.session_facts` **User playbook** playbook `vsp_direct.user` **User information playbook** playbook `vsp_direct.user_facts` **User group playbook** playbook `vsp_direct.user_group` **User group information playbook** playbook `vsp_direct.user_group_facts`

Use Case: Configure, monitor and audit the storage system

Description	Update storage system settings, retrieve alerts and hardware information, configure SNMP, set up audit log transfer destinations and collect troubleshooting bundles.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Audit log transfer dest** `hv_audit_log_transfer_dest`, `hv_audit_log_transfer_dest_facts` **SNMP settings** `hv_snmp_settings`, `hv_snmp_settings_facts` **Storage system** `hv_storage_system` **Storage system monitor** `hv_storage_system_monitor_facts` **Storage system** `hv_storagesystem_facts` **Troubleshooting** `hv_troubleshooting_facts` **Upload file** `hv_upload_file` **Gather User Consent for Data Collection** playbook `accept_user_consent` **Audit log transfer dest playbook** playbook `vsp_direct.audit_log_transfer_dest` **Audit log transfer dest information playbook** playbook `vsp_direct.audit_log_transfer_dest_facts` **SNMP setting playbook** playbook `vsp_direct.snmp_setting` **SNMP settings information playbook** playbook `vsp_direct.snmp_settings_facts` **Storage system monitor information playbook** playbook `vsp_direct.storage_system_monitor_facts` **Storage system information playbook** playbook `vsp_direct.storagesystem_facts` **VSP storage connection session example playbook** playbook `vsp_direct.vsp_storage_connection_session_example` **VSP storage system playbook** playbook `vsp_direct.vsp_storage_system` **VSP upload files for audit log playbook** playbook `vsp_direct.vsp_upload_files_for_audit_log`

Use Case: Provision SDS Block volumes, pools and snapshots

Description	Create and manage volumes, storage pools, snapshots and Virtual Private Storage settings on VSP One SDS Block and Cloud systems, and estimate pool capacity.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Capacity management settings** `hv_sds_block_capacity_management_settings_facts` **Snapshot** `hv_sds_block_snapshot`, `hv_sds_block_snapshot_facts` **Storage pool** `hv_sds_block_storage_pool`, `hv_sds_block_storage_pool_facts` **Storage pool estimated capacity** `hv_sds_block_storage_pool_estimated_capacity_facts` **Volume** `hv_sds_block_volume`, `hv_sds_block_volume_facts` **VPS** `hv_sds_block_vps`, `hv_sds_block_vps_facts` **Capacity management settings information playbook** playbook `sds_block_direct.capacity_management_settings_facts` **Estimated capacity information playbook** playbook `sds_block_direct.estimated_capacity_facts` **Snapshot playbook** playbook `sds_block_direct.sdsb_snapshot` **Snapshot information playbook** playbook `sds_block_direct.sdsb_snapshot_facts` **Storage pool playbook** playbook `sds_block_direct.storage_pool` **Storage pool information playbook** playbook `sds_block_direct.storage_pool_facts` **Update VPS volume ADR setting playbook** playbook `sds_block_direct.update_vps_volume_adr_setting` **Volume playbook** playbook `sds_block_direct.volume` **Volume information playbook** playbook `sds_block_direct.volume_facts` **VPS playbook** playbook `sds_block_direct.vps` **VPS information playbook** playbook `sds_block_direct.vps_facts`

Use Case: Connect hosts to SDS Block

Description	Manage compute nodes, compute ports, port authentication and CHAP users, and review control and compute ports.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**CHAP user** `hv_sds_block_chap_user`, `hv_sds_block_chap_user_facts` **Compute node** `hv_sds_block_compute_node`, `hv_sds_block_compute_node_facts` **Compute port** `hv_sds_block_compute_port` **Compute port authentication** `hv_sds_block_compute_port_authentication` **Control port** `hv_sds_block_control_port_facts` **Port** `hv_sds_block_port_facts` **CHAP user playbook** playbook `sds_block_direct.chap_user` **CHAP user information playbook** playbook `sds_block_direct.chap_user_facts` **Compute node playbook** playbook `sds_block_direct.compute_node` **Compute node information playbook** playbook `sds_block_direct.compute_node_facts` **Compute port playbook** playbook `sds_block_direct.compute_port` **Compute port information playbook** playbook `sds_block_direct.compute_port_facts` **Port auth playbook** playbook `sds_block_direct.port_auth` **Control port information playbook** playbook `sds_block_direct.sdsb_control_port_facts`

Use Case: Manage SDS Block clusters, nodes and drives

Description	Manage clusters, storage nodes and BMC connections, spare nodes, drives, fault domains, protection domains, storage controllers and network settings.

Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Cluster** `hv_sds_block_cluster` **Cluster config** `hv_sds_block_cluster_config_facts` **Drive** `hv_sds_block_drive` **Drives** `hv_sds_block_drives_facts` **Fault domain** `hv_sds_block_fault_domain_facts` **Internode port** `hv_sds_block_internode_port_facts` **Protection domain** `hv_sds_block_protection_domain`, `hv_sds_block_protection_domain_facts` **Spare node** `hv_sds_block_spare_node`, `hv_sds_block_spare_node_facts` **Storage controller** `hv_sds_block_storage_controller`, `hv_sds_block_storage_controller_facts` **Storage network setting** `hv_sds_block_storage_network_setting_facts` **Storage node** `hv_sds_block_storage_node`, `hv_sds_block_storage_node_facts` **Storage node BMC connection** `hv_sds_block_storage_node_bmc_connection`, `hv_sds_block_storage_node_bmc_connection_facts` **Storage node network settings** `hv_sds_block_storage_node_network_settings_facts` **Storage time** `hv_sds_block_storage_time_facts` **Protection domain playbook** playbook `sds_block_direct.protection_domain` **Cluster playbook** playbook `sds_block_direct.sdsb_cluster` **Cluster config information playbook** playbook `sds_block_direct.sdsb_cluster_config_facts` **Cluster network information playbook** playbook `sds_block_direct.sdsb_cluster_network_facts` **Drive playbook** playbook `sds_block_direct.sdsb_drive` **Drive information playbook** playbook `sds_block_direct.sdsb_drive_facts` **Fault domain information playbook** playbook `sds_block_direct.sdsb_fault_domain_facts` **Internode port information playbook** playbook `sds_block_direct.sdsb_internode_port_facts` **Protection domains information playbook** playbook `sds_block_direct.sdsb_protection_domains_facts` **Storage controller playbook** playbook `sds_block_direct.sdsb_storage_controller` **Storage controller information playbook** playbook `sds_block_direct.sdsb_storage_controller_facts` **Storage node network setting information playbook** playbook `sds_block_direct.sdsb_storage_node_network_setting_facts` **Storage time information playbook** playbook `sds_block_direct.sdsb_storage_time_facts` **Spare node playbook** playbook `sds_block_direct.spare_node` **Spare node information playbook** playbook `sds_block_direct.spare_node_facts` **Storage node playbook** playbook `sds_block_direct.storage_node` **Storage node BMC connection playbook** playbook `sds_block_direct.storage_node_bmc_connection` **Storage node BMC connection information playbook** playbook `sds_block_direct.storage_node_bmc_connection_facts` **Storage node information playbook** playbook `sds_block_direct.storage_node_facts` **Storage system information playbook** playbook `sds_block_direct.storagesystem_facts`

Use Case: Replicate SDS Block data to remote systems

Description	Manage journals, remote iSCSI ports and remote path groups used for replication.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Journal** `hv_sds_block_journal`, `hv_sds_block_journal_facts` **Remote iSCSI port** `hv_sds_block_remote_iscsi_port`, `hv_sds_block_remote_iscsi_port_facts` **Remote path group** `hv_sds_block_remote_path_group`, `hv_sds_block_remote_path_group_facts` **Remote iSCSI port playbook** playbook `sds_block_direct.remote_iscsi_port` **Remote iSCSI port information playbook** playbook `sds_block_direct.remote_iscsi_port_facts` **Remote path group playbook** playbook `sds_block_direct.remote_path_group` **Remote path group information playbook** playbook `sds_block_direct.remote_path_group_facts` **Journal playbook** playbook `sds_block_direct.sdsb_journal` **Journal information playbook** playbook `sds_block_direct.sdsb_journal_facts`

Use Case: Secure and administer SDS Block access

Description	Manage users, user groups, external authentication servers, encryption, login messages, web server access, sessions and authentication tickets.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)

Key content	**Authentication ticket** `hv_sds_block_authentication_ticket` **Encryption environment setting** `hv_sds_block_encryption_environment_setting_facts` **Encryption environment settings** `hv_sds_block_encryption_environment_settings` **Encryption key** `hv_sds_block_encryption_key`, `hv_sds_block_encryption_key_facts` **Encryption key count** `hv_sds_block_encryption_key_count_facts` **Login message** `hv_sds_block_login_message`, `hv_sds_block_login_message_facts` **Session** `hv_sds_block_session`, `hv_sds_block_session_facts` **Storage external auth server setting** `hv_sds_block_storage_external_auth_server_setting`, `hv_sds_block_storage_external_auth_server_setting_facts` **Storage user auth setting** `hv_sds_block_storage_user_auth_setting`, `hv_sds_block_storage_user_auth_setting_facts` **User** `hv_sds_block_user`, `hv_sds_block_user_facts` **User group** `hv_sds_block_user_group`, `hv_sds_block_user_group_facts` **Web server** `hv_sds_block_web_server`, `hv_sds_block_web_server_facts` **Authentication ticket playbook** playbook `sds_block_direct.authentication_ticket` **Encryption environment setting information playbook** playbook `sds_block_direct.encryption_environment_setting_facts` **Encryption environment settings playbook** playbook `sds_block_direct.encryption_environment_settings` **Encryption key playbook** playbook `sds_block_direct.encryption_key` **Encryption key count information playbook** playbook `sds_block_direct.encryption_key_count_facts` **Encryption key information playbook** playbook `sds_block_direct.encryption_key_facts` **External auth server setting playbook** playbook `sds_block_direct.external_auth_server_setting` **External auth server setting information playbook** playbook `sds_block_direct.external_auth_server_setting_facts` **Login message playbook** playbook `sds_block_direct.sdsb_login_message` **Login message information playbook** playbook `sds_block_direct.sdsb_login_message_facts` **Session playbook** playbook `sds_block_direct.sdsb_session` **Session information playbook** playbook `sds_block_direct.sdsb_session_facts` **User information playbook** playbook `sds_block_direct.sdsb_user_facts` **User group information playbook** playbook `sds_block_direct.sdsb_user_group_facts` **User groups playbook** playbook `sds_block_direct.sdsb_user_groups` **Users playbook** playbook `sds_block_direct.sdsb_users` **Web server playbook** playbook `sds_block_direct.sdsb_web_server` **Web server information playbook** playbook `sds_block_direct.sdsb_web_server_facts` **User auth setting playbook** playbook `sds_block_direct.user_auth_setting` **User auth setting information playbook** playbook `sds_block_direct.user_auth_setting_facts`

Use Case: Monitor and maintain SDS Block systems

Description	Manage storage system settings and licenses, retrieve and configure event and audit logs, dump logs, run software updates, view jobs and configure SNMP.
Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Audit log setting** `hv_sds_block_audit_log_setting`, `hv_sds_block_audit_log_setting_facts` **Dump log file** `hv_sds_block_dump_log_file` **Dump log status** `hv_sds_block_dump_log_status_facts` **Event log setting** `hv_sds_block_event_log_setting`, `hv_sds_block_event_log_setting_facts` **Event logs** `hv_sds_block_event_logs_facts` **Job** `hv_sds_block_job_facts` **License** `hv_sds_block_license`, `hv_sds_block_license_facts` **License setting** `hv_sds_block_license_setting`, `hv_sds_block_license_setting_facts` **SNMP settings** `hv_sds_block_snmp_settings`, `hv_sds_block_snmp_settings_facts` **Software update file** `hv_sds_block_software_update_file_facts` **Storage software update** `hv_sds_block_storage_software_update` **Storage system** `hv_sds_block_storage_system`, `hv_sds_block_storage_system_facts` **Audit log setting playbook** playbook `sds_block_direct.audit_log_setting` **Event log information playbook** playbook `sds_block_direct.event_log_facts` **Event log setting playbook** playbook `sds_block_direct.event_log_setting` **Event log setting information playbook** playbook `sds_block_direct.event_log_setting_facts` **Events log information playbook** playbook `sds_block_direct.events_log_facts` **Job information playbook** playbook `sds_block_direct.job_facts` **Audit log setting information playbook** playbook `sds_block_direct.sdsb_audit_log_setting_facts` **Dump log file playbook** playbook `sds_block_direct.sdsb_dump_log_file` **Dump log file status information playbook** playbook `sds_block_direct.sdsb_dump_log_file_status_facts` **License playbook** playbook `sds_block_direct.sdsb_license` **License information playbook** playbook `sds_block_direct.sdsb_license_facts` **License setting playbook** playbook `sds_block_direct.sdsb_license_setting` **License setting information playbook** playbook `sds_block_direct.sdsb_license_setting_facts` **SNMP settings playbook** playbook `sds_block_direct.snmp_settings` **SNMP settings information playbook** playbook `sds_block_direct.snmp_settings_facts` **Software update file information playbook** playbook `sds_block_direct.software_update_file_facts` **Storage software update playbook** playbook `sds_block_direct.storage_software_update` **Storage system playbook** playbook `sds_block_direct.storage_system`

Use Case: Run guided storage workflows

Description	Run role-based workflows that create quorum disks, journals and GAD or HUR pairs, and delete or query host volumes by WWN.

Collection	`hitachivantara.vspone_block` (Certified, Hitachi Vantara)
Key content	**Create Primary and Secondary Quorum Disk** playbook `role_playbooks.create_primary_and_secondary_diskless_quorum_disk` **Create journal on primary and secondary storages using role** playbook `role_playbooks.create_primary_and_secondary_journals` **Create Primary and Secondary Quorum Disk** playbook `role_playbooks.create_primary_and_secondary_quorum_disk` **Create GAD Pairs using hv_vsp_gad_pairs_creation role** playbook `role_playbooks.hv_vsp_gad_pairs_creation` **Create HUR Pairs using hv_vsp_hur_pairs_creation role** playbook `role_playbooks.hv_vsp_hur_pairs_creation` **Create primary and secondary diskless quorum disk role** role `hv_vsp_create_primary_and_secondary_diskless_quorum_disk` **Create primary and secondary quorum disk role** role `hv_vsp_create_primary_and_secondary_quorum_disk` **GAD pairs creation role** role `hv_vsp_gad_pairs_creation` **Host volume deletion role** role `hv_vsp_host_volume_deletion` **HUR pairs creation role** role `hv_vsp_hur_pairs_creation` **NDM GAD migration pairs role** role `hv_vsp_ndm_gad_migration_pairs` **NDM GAD migration volumes role** role `hv_vsp_ndm_gad_migration_volumes` **Primary secondary journal creation role** role `hv_vsp_primary_secondary_journal_creation` **Query host volumes by WWNs role** role `hv_vsp_query_host_volumes_by_wwns`

Hitachi Vantara VSP One Object `hitachivantara.vspone_object`

Certified Hitachi Vantara · version 1.2.0 · updated 2026-05-28 · 28 modules → 5 use cases

Use Case: Manage certificates and encryption

Description	Manage certificates, KMIP key servers and S3 encryption settings, fetch CSRF tokens, and upload certificates or update KMIP ciphers with ready-made workflows.
Collection	`hitachivantara.vspone_object` (Certified, Hitachi Vantara)
Key content	**Certificates** `hv_certificates`, `hv_certificates_facts` **CSRF tokens** `hv_csrf` **KMIP servers** `hv_kmip` **KMIP server list** `hv_kmip_server_facts` **S3 encryption** `hv_s3_encryption`, `hv_s3_encryption_facts` **Certificate upload role** role `hv_vspone_object_certificate_upload_role` **KMIP cipher update role** role `hv_vspone_object_kmip_server_role` **Certificate upload workflow** playbook `role_playbooks.hv_vspone_object_certificate_upload_role` **KMIP cipher update workflow** playbook `role_playbooks.hv_vspone_object_kmip_server_role` **Certificate playbook** playbook `oneobject_node.certificate` **Certificate facts playbook** playbook `oneobject_node.certificate_facts` **CSRF token playbook** playbook `oneobject_node.csrf` **KMIP server playbook** playbook `oneobject_node.kmip_server` **KMIP server facts playbook** playbook `oneobject_node.kmip_server_facts` **S3 encryption playbook** playbook `oneobject_node.s3_encryption` **S3 encryption facts playbook** playbook `oneobject_node.s3_encryption_facts`

Use Case: Manage licenses and system identity

Description	Set the serial number, upload and query licenses, read region and galaxy information, and run the licensing workflow.
Collection	`hitachivantara.vspone_object` (Certified, Hitachi Vantara)
Key content	**License** `hv_license` **Licenses list** `hv_licenses_facts` **Serial number** `hv_serial_number`, `hv_serial_number_facts` **Region information** `hv_region_facts` **Galaxy information** `hv_galaxy_facts` **License role** role `hv_vspone_object_license_role` **License workflow** playbook `role_playbooks.hv_vspone_object_license_role` **License playbook** playbook `oneobject_node.license` **License facts playbook** playbook `oneobject_node.license_facts` **Serial number playbook** playbook `oneobject_node.serial_number` **Serial number facts playbook** playbook `oneobject_node.serial_number_facts` **Region facts playbook** playbook `oneobject_node.region_facts` **Galaxy facts playbook** playbook `oneobject_node.galaxy_facts`

Use Case: Manage storage components, classes and fault domains

Description	Create storage components, classes and fault domains, update component state, and activate components while checking capacity thresholds.
Collection	`hitachivantara.vspone_object` (Certified, Hitachi Vantara)
Key content	**Storage components** `hv_storage_component` **Component state** `hv_storage_component_state_update` **Storage component list** `hv_storage_components_facts` **Storage classes** `hv_storage_class`, `hv_storage_class_facts` **Fault domains** `hv_storage_fault_domain`, `hv_storage_fault_domain_facts` **Component activation role** role `hv_vspone_object_storage_component_role` **Component activation workflow** playbook `role_playbooks.hv_vspone_object_storage_component_role` **Storage component playbook** playbook `oneobject_node.storage_component` **Storage component facts playbook** playbook `oneobject_node.storage_component_facts` **Storage class playbook** playbook `oneobject_node.storage_class` **Storage class facts playbook** playbook `oneobject_node.storage_class_facts` **Fault domain playbook** playbook `oneobject_node.storage_fault_domain` **Fault domain facts playbook** playbook `oneobject_node.storage_fault_domain_facts`

Use Case: Manage S3 users and buckets

Description	Generate S3 user credentials and list users, user IDs and user buckets.
Collection	`hitachivantara.vspone_object` (Certified, Hitachi Vantara)
Key content	**S3 user credentials** `hv_s3_user_credentials` **Users** `hv_users_facts` **User IDs** `hv_user_id_facts` **User buckets** `hv_user_buckets_facts` **S3 credentials playbook** playbook `oneobject_node.s3_user_credentials` **User facts playbook** playbook `oneobject_node.user_facts` **User bucket facts playbook** playbook `oneobject_node.user_buckets_facts`

Use Case: Monitor jobs and events and collect diagnostics

Description	Track and manage jobs, read system events, create log bundles for troubleshooting, and record user consent for data collection.
Collection	`hitachivantara.vspone_object` (Certified, Hitachi Vantara)
Key content	**Jobs** `hv_job` **Job list** `hv_jobs_facts` **Events** `hv_events_facts` **Troubleshooting log bundle** `hv_troubleshooting_facts` **User consent playbook** playbook `accept_user_consent` **Job playbook** playbook `oneobject_node.job` **Job facts playbook** playbook `oneobject_node.jobs_facts` **Event facts playbook** playbook `oneobject_node.events_facts`

IBM Storage Virtualize (FlashSystem and SAN Volume Controller) `ibm.storage_virtualize`

Certified IBM · version 3.4.0 · updated 2026-07-18 · 50 modules → 9 use cases

Use Case: Set up and maintain the storage system

Description	Run initial setup, authenticate, gather information, send CLI commands, manage Call Home, remote support, syslog, FlashSystem grid, firmware upgrades and log collection.
Collection	`ibm.storage_virtualize` (Certified, IBM)

Key content	**Initial setup** `ibm_svc_initial_setup` **Initial setup completion** `ibm_svc_complete_initial_setup` **Full initial setup** playbook `initial_setup_system_complete` **Authentication tokens** `ibm_svc_auth` **System information** `ibm_svc_info` **svcinfo CLI commands** `ibm_svcinfo_command` **svctask CLI commands** `ibm_svctask_command` **Call Home** `ibm_svc_manage_callhome` **Remote support assistance** `ibm_svc_manage_sra` **Syslog servers** `ibm_sv_manage_syslog_server` **FlashSystem grid** `ibm_sv_manage_flashsystem_grid` **Firmware upgrade** playbook `firmware_upgrade.main` **Log and dump collection** playbook `flashsystem_log_collection.main` **Generic sample** playbook `generic_ansible_sample` **Generic information sample** playbook `generic_info` **Source cluster configuration export** playbook `cluster_config_replication.extract_src_cluster_config` **Configuration replication to target** playbook `cluster_config_replication.replicate_config_on_target_cluster`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Manage users, security and certificates

Description	Manage users, user groups, ownership groups, security options, system certificates and truststores.
Collection	`ibm.storage_virtualize` (Certified, IBM)
Key content	**Users** `ibm_svc_manage_user` **User groups** `ibm_svc_manage_usergroup` **Ownership groups** `ibm_svc_manage_ownershipgroup` **Security options** `ibm_sv_manage_security` **SSL certificates** `ibm_sv_manage_ssl_certificate` **System certificates** `ibm_sv_manage_system_certificate` **Replication truststores** `ibm_sv_manage_truststore_for_replication` **Security settings** playbook `security_mgmt`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Provision pools, drives and volumes

Description	Manage MDisks, pools, drives, provisioning policies, volumes, volume groups, mirrored volumes, change volumes and clones.
Collection	`ibm.storage_virtualize` (Certified, IBM)
Key content	**MDisks** `ibm_svc_mdisk` **Storage pools** `ibm_svc_mdiskgrp` **Drives** `ibm_sv_manage_drive` **Provisioning policies** `ibm_sv_manage_provisioning_policy` **Volumes** `ibm_svc_manage_volume` **Volume groups** `ibm_svc_manage_volumegroup` **Mirrored volumes** `ibm_svc_manage_mirrored_volume` **Change volumes** `ibm_svc_manage_cv` **Clones and thin clones** `ibm_sv_manage_clone` **Volume group creation** playbook `volumegrp_create`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Connect hosts and map volumes

Description	Define hosts and host clusters, port sets and FC port set members, IP provisioning, volume mappings and SAN zoning.
Collection	`ibm.storage_virtualize` (Certified, IBM)
Key content	**Hosts** `ibm_svc_host` **Host clusters** `ibm_svc_hostcluster` **Port sets** `ibm_svc_manage_portset` **FC port set members** `ibm_sv_manage_fcportsetmember` **IP provisioning** `ibm_svc_manage_ip` **Volume mappings** `ibm_svc_vol_map` **Volume-to-host mapping** playbook `map_volume_to_host` **Cisco SAN zoning pre-flight** playbook `cisco_fc_zoning.main` **Cisco SAN zone sync** playbook `cisco_fc_zoning.cisco_zone_sync`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Protect data with snapshots and FlashCopy

Description	Manage snapshots and snapshot policies, FlashCopy mappings and consistency groups, and safeguarded policies.
Collection	`ibm.storage_virtualize` (Certified, IBM)
Key content	**Snapshots** `ibm_sv_manage_snapshot` **Snapshot policies** `ibm_sv_manage_snapshotpolicy` **FlashCopy mappings** `ibm_svc_manage_flashcopy` **FlashCopy consistency groups** `ibm_svc_manage_consistgrp_flashcopy` **FlashCopy start and stop** `ibm_svc_start_stop_flashcopy` **Safeguarded policies** `ibm_svc_manage_safeguarded_policy`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Replicate data between systems

Description	Set up partnerships, remote copy relationships and groups, replication policies, and switch replication direction.
Collection	`ibm.storage_virtualize` (Certified, IBM)
Key content	**FC partnerships** `ibm_sv_manage_fc_partnership` **IP partnerships** `ibm_sv_manage_ip_partnership` **Remote copy relationships** `ibm_svc_manage_replication` **Remote copy consistency groups** `ibm_svc_manage_replicationgroup` **Remote copy start and stop** `ibm_svc_start_stop_replication` **Replication policies** `ibm_sv_manage_replication_policy` **Replication direction** `ibm_sv_switch_replication_direction` **Global Mirror with change volumes in a consistency group** playbook `create_GMCV_in_CG` **Policy-based replication** playbook `policy_based_replication.main`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Run policy-based high availability and disaster recovery

Description	Manage storage partitions, configure PBHA and PBR, and migrate objects or Hyperswap and Global Mirror to the new models.
Collection	`ibm.storage_virtualize` (Certified, IBM)
Key content	**Storage partitions** `ibm_sv_manage_storage_partition` **PBHA configuration** playbook `PBHA.main` **PBR configuration** playbook `PBRHA.main` **DR link removal** playbook `PBRHA.remove_dr_link` **Move objects into PBHA** playbook `move_existing_objects_into_PBHA_env.main` **Partition decommission** playbook `move_existing_objects_into_PBHA_env.decommission_partition` **Hyperswap to PBHA migration** playbook `hyperswap_to_pbha_migration.migrate_hyperswap_to_pbha` **Dependent volume migration** playbook `hyperswap_to_pbha_migration.migrate_dependent_volumes` **Consistency group migration to PBR** playbook `migrate_gm_gmcv_to_pbr.migrate_consistency_groups.main` **Consistency group migration cleanup** playbook `migrate_gm_gmcv_to_pbr.migrate_consistency_groups.cleanup` **Independent relationship migration to PBR** playbook `migrate_gm_gmcv_to_pbr.migrate_independent_relationships.main` **Independent relationship migration cleanup** playbook `migrate_gm_gmcv_to_pbr.migrate_independent_relationships.cleanup` **Prefix relationship migration to PBR** playbook `migrate_gm_gmcv_to_pbr.migrate_prefix_relationships.main` **Prefix relationship migration cleanup** playbook `migrate_gm_gmcv_to_pbr.migrate_prefix_relationships.cleanup`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Migrate volumes and hosts between systems

Description	Migrate volumes between clusters and iSCSI hosts, and handle multipath and host actions during partition migration.
Collection	`ibm.storage_virtualize` (Certified, IBM)

Key content	**Volume migration** `ibm_svc_manage_migration` **Volume migration** playbook `volume_migrate` **iSCSI host mapping switch** playbook `volume_migration_on_svc_iscsi.create_iscsi_host_map_vol_switch` **iSCSI volume migration** playbook `volume_migration_on_svc_iscsi.initiate_migration_for_given_volume` **Partition migration monitoring** playbook `partition_migration_host_actions.main` **Host identification** playbook `partition_migration_host_actions.host_identification` **Multipath discovery** playbook `partition_migration_host_actions.discover_multipath_devices` **Multipath rescan** playbook `partition_migration_host_actions.rescan_multipath_devices` **Multipath verification** playbook `partition_migration_host_actions.verify_multipath_devices` **iSCSI logout** playbook `partition_migration_host_actions.iscsi_logout`
Notes	• Module names have the ibm_ prefix omitted.

Use Case: Back up to and restore from cloud

Description	Configure Amazon S3 cloud accounts, cloud backups and restore backups.
Collection	`ibm.storage_virtualize` (Certified, IBM)
Key content	**Amazon S3 cloud accounts** `ibm_sv_manage_awss3_cloudaccount` **Cloud backups** `ibm_sv_manage_cloud_backups` **Cloud backup restores** `ibm_sv_restore_cloud_backup`
Notes	• Module names have the ibm_ prefix omitted.

Infinidat InfiniBox `infinidat.infinibox`

Certified Infinidat · version 1.8.4 · updated 2026-08-05 · 21 modules → 6 use cases

Use Case: Provision volumes, file systems and pools

Description	Create pools, volumes, snapshots and file systems, publish NFS exports and clients, and tag resources with metadata.
Collection	`infinidat.infinibox` (Certified, Infinidat)
Key content	**Pools** `infini_pool` **Volumes** `infini_vol` **File systems** `infini_fs` **NFS exports** `infini_export` **NFS export clients** `infini_export_client` **Metadata** `infini_metadata` **Create volumes example** playbook `test_create_volumes` **Create snapshots example** playbook `test_create_snapshots` **Remove snapshots example** playbook `test_remove_snapshots` **Remove volumes example** playbook `test_remove_volumes` **Create metadata example** playbook `test_create_metadata` **Search metadata example** playbook `test_search_metadata` **Remove metadata example** playbook `test_remove_metadata`

Use Case: Connect hosts and map storage

Description	Define hosts, host clusters and their FC and iSCSI ports, map volumes to hosts or clusters, name FC switches and configure network spaces.
Collection	`infinidat.infinibox` (Certified, Infinidat)
Key content	**Hosts** `infini_host` **Host clusters** `infini_cluster` **Host ports** `infini_port` **Volume mappings** `infini_map` **FC switch names** `infini_fibre_channel_switch` **Network spaces** `infini_network_space` **Create cluster mapping example** playbook `test_create_map_cluster` **Remove cluster mapping example** playbook `test_remove_map_cluster` **Create network spaces example** playbook `test_create_network_spaces` **Remove network spaces example** playbook `test_remove_network_spaces`

Use Case: Manage users, certificates and single sign-on

Description	Manage array users and user repositories, SSO configuration and SSL certificates.
Collection	`infinidat.infinibox` (Certified, Infinidat)
Key content	**Users** `infini_user` **User repositories** `infini_users_repository` **Single sign-on** `infini_sso` **SSL certificates** `infini_certificate` **Remove user repository example** playbook `test_remove_users_repository`

Use Case: Configure the array, notifications and monitoring

Description	Configure array settings, custom events, notification rules and targets, register with Infinimetrics, and configure a full array from one playbook.
Collection	`infinidat.infinibox` (Certified, Infinidat)
Key content	**Array configuration** `infini_config` **Custom events** `infini_event` **Notification rules** `infini_notification_rule` **Notification targets** `infini_notification_target` **Infinimetrics registration** `infini_infinimetrics` **Array configuration** playbook `configure_array` **Configuration example** playbook `test_config_sample` **Notification rules example** playbook `test_notification_rules_sample` **Persistent API session example** playbook `test_persist_api_session` **Time delta filter** filter `delta_time`

Use Case: Create and remove sample resource sets

Description	Create and remove a complete set of sample resources for testing and demonstrations.
Collection	`infinidat.infinibox` (Certified, Infinidat)
Key content	**Create resources** playbook `test_create_resources` **Create resources demo** playbook `test_create_resources_demo` **Remove resources** playbook `test_remove_resources` **Remove resources demo** playbook `test_remove_resources_demo`

Use Case: Demonstrate Infinisafe cyber resilience

Description	Set up, run and tear down the Infinisafe demonstration.
Collection	`infinidat.infinibox` (Certified, Infinidat)
Key content	**Demo setup** playbook `infinisafe_demo_setup` **Demo test run** playbook `infinisafe_demo_runtest` **Demo teardown** playbook `infinisafe_demo_teardown`

NetApp Cloud Volumes Service for AWS `netapp.aws`

Certified NetApp · version 21.8.0 · updated 2024-01-29 · 4 modules → 1 use cases

Use Case: Manage NetApp Cloud Volumes Service on AWS

Description	Manage pools, file systems, snapshots and Active Directory settings.
Collection	`netapp.aws` (Certified, NetApp)
Key content	**Pools** `aws_netapp_cvs_pool` **File systems** `aws_netapp_cvs_filesystems` **Snapshots** `aws_netapp_cvs_snapshots` **Active Directory** `aws_netapp_cvs_active_directory`

NetApp Azure NetApp Files `netapp.azure`

Certified NetApp · version 21.11.0 · updated 2024-01-29 · 4 modules → 1 use cases

Use Case: Manage Azure NetApp Files

Description	Create accounts, capacity pools, volumes and snapshots in Azure NetApp Files.
Collection	`netapp.azure` (Certified, NetApp)
Key content	**Accounts** `azure_rm_netapp_account` **Capacity pools** `azure_rm_netapp_capacity_pool` **Volumes** `azure_rm_netapp_volume` **Snapshots** `azure_rm_netapp_snapshot`

NetApp Cloud Manager `netapp.cloudmanager`

Certified NetApp · version 21.24.0 · updated 2024-01-29 · 13 modules → 3 use cases

Use Case: Deploy Cloud Manager connectors and accounts

Description	Deploy connectors in AWS, Azure and GCP, manage NSS accounts and gather information.
Collection	`netapp.cloudmanager` (Certified, NetApp)
Key content	**AWS connectors** `na_cloudmanager_connector_aws` **Azure connectors** `na_cloudmanager_connector_azure` **GCP connectors** `na_cloudmanager_connector_gcp` **NSS accounts** `na_cloudmanager_nss_account` **Cloud Manager information** `na_cloudmanager_info`

Use Case: Create Cloud Volumes ONTAP and FSx systems

Description	Create Cloud Volumes ONTAP working environments in AWS, Azure and GCP and ONTAP file systems on FSx.
Collection	`netapp.cloudmanager` (Certified, NetApp)
Key content	**CVO in AWS** `na_cloudmanager_cvo_aws` **CVO in Azure** `na_cloudmanager_cvo_azure` **CVO in GCP** `na_cloudmanager_cvo_gcp` **FSx for ONTAP** `na_cloudmanager_aws_fsx`

Use Case: Provision storage and replication

Description	Manage aggregates, volumes, CIFS servers and SnapMirror relationships.
Collection	`netapp.cloudmanager` (Certified, NetApp)
Key content	**Aggregates** `na_cloudmanager_aggregate` **Volumes** `na_cloudmanager_volume` **CIFS servers** `na_cloudmanager_cifs_server` **SnapMirror** `na_cloudmanager_snapmirror`

NetApp ONTAP `netapp.ontap`

Certified NetApp · version 23.3.0 · updated 2025-12-15 · 165 modules → 13 use cases

Use Case: Provision volumes, qtrees and quotas

Description	Create, resize, clone and delete FlexVol volumes, with qtrees, quotas, storage efficiency, SnapLock retention and QoS limits.
Collection	`netapp.ontap` (Certified, NetApp)

Key content	**Volumes** `na_ontap_volume` **Volume autosize** `na_ontap_volume_autosize` **Volume clones** `na_ontap_volume_clone` **Volume efficiency** `na_ontap_volume_efficiency` **Volume SnapLock retention** `na_ontap_volume_snaplock` **Efficiency policies** `na_ontap_efficiency_policy` **SnapLock compliance clock** `na_ontap_snaplock_clock` **Qtrees** `na_ontap_qtree` **Quota policies** `na_ontap_quota_policy` **Quotas** `na_ontap_quotas` **FlexCache relationships** `na_ontap_flexcache` **QoS policy groups** `na_ontap_qos_policy_group` **Adaptive QoS policy groups** `na_ontap_qos_adaptive_policy_group`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Protect data with snapshots and replication

Description	Take and schedule snapshots, replicate with SnapMirror, manage consistency groups and set up MetroCluster, cluster and SVM peering.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**Snapshots** `na_ontap_snapshot` **Snapshot policies** `na_ontap_snapshot_policy` **SnapMirror relationships** `na_ontap_snapmirror` **SnapMirror policies** `na_ontap_snapmirror_policy` **Consistency groups** `na_ontap_cg` **Consistency group snapshots** `na_ontap_cg_snapshot` **Cluster peers** `na_ontap_cluster_peer` **SVM peers** `na_ontap_vserver_peer` **SVM peer permissions** `na_ontap_vserver_peer_permissions` **MetroCluster** `na_ontap_metrocluster` **MetroCluster DR groups** `na_ontap_metrocluster_dr_group` **MetroCluster Mediator** `na_ontap_mcc_mediator` **Configuration backup** `na_ontap_support_config_backup` **NDMP services** `na_ontap_ndmp`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Share files over NFS and SMB

Description	Configure NFS and CIFS servers and shares, export policies and rules, and the file-level access settings behind them.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**NFS service** `na_ontap_nfs` **Export policies** `na_ontap_export_policy` **Export policy rules** `na_ontap_export_policy_rule` **CIFS shares** `na_ontap_cifs` **CIFS share ACLs** `na_ontap_cifs_acl` **CIFS servers** `na_ontap_cifs_server` **UNIX symlink mappings** `na_ontap_cifs_unix_symlink_mapping` **CIFS security settings** `na_ontap_vserver_cifs_security` **Domain tunnel** `na_ontap_domain_tunnel` **Active Directory accounts** `na_ontap_active_directory` **Preferred domain controllers** `na_ontap_active_directory_domain_controllers`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Control file access, auditing and virus scanning

Description	Set NTFS permissions and file-directory security policies, configure FPolicy and audit logging, and enable Vscan.
Collection	`netapp.ontap` (Certified, NetApp)

Key content	**File directory security descriptors** `na_ontap_fdsd` **File directory security policies** `na_ontap_fdsp` **Security policy tasks** `na_ontap_fdspt` **File directory security apply** `na_ontap_fdss` **File-directory policies** `na_ontap_file_directory_policy` **NTFS file permissions** `na_ontap_file_security_permissions` **NTFS permission ACLs** `na_ontap_file_security_permissions_acl` **NTFS DACLs** `na_ontap_ntfs_dacl` **NTFS security descriptors** `na_ontap_ntfs_sd` **FPolicy enable and disable** `na_ontap_fpolicy_status` **FPolicy events** `na_ontap_fpolicy_event` **FPolicy external engines** `na_ontap_fpolicy_ext_engine` **FPolicy policies** `na_ontap_fpolicy_policy` **FPolicy scopes** `na_ontap_fpolicy_scope` **SVM audit configuration** `na_ontap_vserver_audit` **Vscan service** `na_ontap_vscan` **Vscan on-access policies** `na_ontap_vscan_on_access_policy` **Vscan on-demand tasks** `na_ontap_vscan_on_demand_task` **Vscan scanner pools** `na_ontap_vscan_scanner_pool`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Provision block storage (iSCSI, FC and NVMe)

Description	Create LUNs and ASA r2 storage units, map them to initiators with igroups and portsets, and configure iSCSI, FC and NVMe services.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**LUNs** `na_ontap_lun` **LUN copies** `na_ontap_lun_copy` **LUN maps** `na_ontap_lun_map` **LUN map reporting nodes** `na_ontap_lun_map_reporting_nodes` **Initiator groups** `na_ontap_igroup` **Initiators** `na_ontap_igroup_initiator` **Portsets** `na_ontap_portset` **iSCSI service** `na_ontap_iscsi` **iSCSI security** `na_ontap_iscsi_security` **FCP service** `na_ontap_fcp` **WWPN aliases** `na_ontap_wwpn_alias` **Unified connect adapters** `na_ontap_ucadapter` **NVMe service** `na_ontap_nvme` **NVMe namespaces** `na_ontap_nvme_namespace` **NVMe subsystems** `na_ontap_nvme_subsystem` **ASA r2 storage units** `na_ontap_storage_unit` **ASA r2 storage unit snapshots** `na_ontap_storage_unit_snapshot`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Provide S3 object storage

Description	Enable the S3 service, create buckets, users, groups and policies, and configure object store targets.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**S3 services** `na_ontap_s3_services` **S3 buckets** `na_ontap_s3_buckets` **S3 users** `na_ontap_s3_users` **S3 groups** `na_ontap_s3_groups` **S3 policies** `na_ontap_s3_policies` **Object stores** `na_ontap_object_store`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Manage SVMs and identity services

Description	Create storage virtual machines and set their options, and configure LDAP, Kerberos, name services, UNIX and local CIFS users and name mappings.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**SVMs** `na_ontap_svm` **SVM options** `na_ontap_svm_options` **LDAP configuration** `na_ontap_ldap` **LDAP clients** `na_ontap_ldap_client` **Kerberos realms** `na_ontap_kerberos_realm` **Kerberos interfaces** `na_ontap_kerberos_interface` **Name mappings** `na_ontap_name_mappings` **Name service switch** `na_ontap_name_service_switch` **Local hosts** `na_ontap_local_hosts` **UNIX groups** `na_ontap_unix_group` **UNIX users** `na_ontap_unix_user` **CIFS local groups** `na_ontap_cifs_local_group` **CIFS local group members** `na_ontap_cifs_local_group_member` **CIFS local users** `na_ontap_cifs_local_user` **CIFS local user changes** `na_ontap_cifs_local_user_modify` **CIFS local user passwords** `na_ontap_cifs_local_user_set_password` **CIFS privileges** `na_ontap_cifs_privileges`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Configure cluster networking

Description	Manage IPspaces, broadcast domains, ports, VLANs, interface groups, subnets, LIFs, routes, BGP and service policies.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**IPspaces** `na_ontap_ipspace` **Broadcast domains** `na_ontap_broadcast_domain` **Broadcast domain ports** `na_ontap_broadcast_domain_ports` **Network ports** `na_ontap_net_port` **Interface groups** `na_ontap_net_ifgrp` **VLANs** `na_ontap_net_vlan` **Subnets** `na_ontap_net_subnet` **Routes** `na_ontap_net_routes` **Ports** `na_ontap_ports` **Logical interfaces (LIFs)** `na_ontap_interface` **Service policies** `na_ontap_service_policy` **Service processor network** `na_ontap_service_processor_network` **BGP configuration** `na_ontap_bgp_config` **BGP peer groups** `na_ontap_bgp_peer_group` **Firewall policies** `na_ontap_firewall_policy`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Build and maintain the cluster

Description	Create clusters and add nodes, assign disks and partitions, manage aggregates, HA and failover, licenses, and upgrade software and firmware.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**Clusters and nodes** `na_ontap_cluster` **Nodes** `na_ontap_node` **Cluster HA** `na_ontap_cluster_ha` **Aggregates** `na_ontap_aggregate` **Disk assignment** `na_ontap_disks` **Partition assignment** `na_ontap_partitions` **Disk options** `na_ontap_disk_options` **Storage failover** `na_ontap_storage_failover` **Storage auto giveback** `na_ontap_storage_auto_giveback` **Licenses** `na_ontap_license` **Software updates** `na_ontap_software_update` **Firmware upgrades** `na_ontap_firmware_upgrade` **Automatic update configuration** `na_ontap_autoupdate_config` **Automatic update status** `na_ontap_autoupdate_support` **Firmware upgrade playbook** playbook `examples.na_ontap_pb_upgrade_firmware` **Firmware upgrade playbook (extra vars)** playbook `examples.na_ontap_pb_upgrade_firmware_with_extra_vars` **Firmware upgrade playbook (vars file)** playbook `examples.na_ontap_pb_upgrade_firmware_with_vars_file`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Secure the cluster and control administrator access

Description	Manage administrator accounts and roles, certificates, SSL, IPsec, SSH, key managers and multi-admin verification.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**Administrator accounts** `na_ontap_user` **Roles** `na_ontap_user_role` **Account restrictions** `na_ontap_user_role_config` **SSH public keys** `na_ontap_publickey` **Certificates** `na_ontap_security_certificates` **SSL security configuration** `na_ontap_security_config` **SSH security** `na_ontap_security_ssh` **Key managers** `na_ontap_security_key_manager` **IPsec configuration** `na_ontap_security_ipsec_config` **IPsec CA certificates** `na_ontap_security_ipsec_ca_certificate` **IPsec policies** `na_ontap_security_ipsec_policy` **Multi-admin verification settings** `na_ontap_mav_config` **Multi-admin verification rules** `na_ontap_mav_rule` **Multi-admin approval groups** `na_ontap_mav_approval_group` **SSL certificate installation playbook** playbook `examples.na_ontap_pb_install_SSL_certificate` **SSL certificate installation playbook (REST)** playbook `examples.na_ontap_pb_install_SSL_certificate_REST`

Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Configure cluster services, monitoring and support

Description	Set DNS, NTP, schedules and login banners, and configure AutoSupport, EMS, SNMP and log forwarding.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**DNS** `na_ontap_dns` **NTP servers** `na_ontap_ntp` **NTP keys** `na_ontap_ntp_key` **Job schedules** `na_ontap_job_schedule` **CLI timeout** `na_ontap_cli_timeout` **Login banner** `na_ontap_login_messages` **Message of the day** `na_ontap_motd` **AutoSupport** `na_ontap_autosupport` **AutoSupport messages** `na_ontap_autosupport_invoke` **EMS configuration** `na_ontap_ems_config` **EMS destinations** `na_ontap_ems_destination` **EMS filters** `na_ontap_ems_filter` **Log forwarding** `na_ontap_log_forward` **SNMP users** `na_ontap_snmp` **SNMP configuration** `na_ontap_snmp_config` **SNMP trap hosts** `na_ontap_snmp_traphosts`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Gather facts, run commands and call APIs

Description	Collect cluster information, wait for conditions, and run CLI, REST or ZAPI calls when no dedicated module exists.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**Cluster information (ZAPI)** `na_ontap_info` **Cluster information (REST)** `na_ontap_rest_info` **CLI commands** `na_ontap_command` **CLI over REST** `na_ontap_rest_cli` **CLI over SSH** `na_ontap_ssh_command` **Generic REST API calls** `na_ontap_restit` **Generic ZAPI calls** `na_ontap_zapit` **Connection debugging** `na_ontap_debug` **Wait for condition** `na_ontap_wait_for_condition` **Seconds to ISO 8601 duration filter** filter `iso8601_duration_from_seconds` **ISO 8601 duration to seconds filter** filter `iso8601_duration_to_seconds` **ISO 8601 filter test playbook** playbook `examples.filter.test_na_filter_iso8601` **Online volumes query playbook** playbook `examples.json_query.na_ontap_pb_get_online_volumes` **Online volumes query playbook (loop)** playbook `examples.json_query.na_ontap_pb_get_online_volumes_loop` **List aggregates playbook** playbook `examples.rest_apis.list_aggregates` **Volumes REST API playbook** playbook `examples.rest_apis.volumes` **Connectivity debug playbook** playbook `examples.support.debug_connectivity`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

Use Case: Deploy standard ONTAP configurations with roles

Description	Use ready-made roles to configure a cluster, create SVMs, NAS shares, LUNs and SnapMirror relationships, or delete an SVM with its data.
Collection	`netapp.ontap` (Certified, NetApp)
Key content	**Cluster configuration** role `na_ontap_cluster_config` **SVM creation** role `na_ontap_vserver_create` **NFS and CIFS shares** role `na_ontap_nas_create` **LUN creation** role `na_ontap_san_create` **SnapMirror relationship** role `na_ontap_snapmirror_create` **SVM deletion** role `na_ontap_vserver_delete`
Notes	• Most modules are idempotent create/modify/delete operations; a few (info, rest, command) are read-only or run arbitrary commands.

NetApp StorageGRID `netapp.storagegrid`

Certified NetApp · version 21.16.0 · updated 2025-12-15 · 50 modules → 6 use cases

Use Case: Manage tenants, buckets and S3 access

Description	Create tenant accounts, buckets, users, groups and S3 keys, platform service endpoints and cloud mirror replication.
Collection	`netapp.storagegrid` (Certified, NetApp)
Key content	**Tenant accounts** `na_sg_grid_tenant` **Accounts** `na_sg_grid_account` **Tenant information** `na_sg_org_info` **Buckets** `na_sg_org_bucket` **Containers** `na_sg_org_container` **Tenant users** `na_sg_org_user` **Tenant groups** `na_sg_org_group` **User S3 keys** `na_sg_org_user_s3_key` **Tenant identity federation** `na_sg_org_identity_federation` **Platform service endpoints** `na_sg_org_endpoints` **Cloud mirror replication** `na_sg_org_cloud_mirror_replication`

Use Case: Manage data placement and protection

Description	Define ILM pools, rules, policies and policy tags, erasure-coding profiles, regions and traffic classification policies.
Collection	`netapp.storagegrid` (Certified, NetApp)
Key content	**ILM pools** `na_sg_grid_ilm_pool` **ILM rules** `na_sg_grid_ilm_rule` **ILM policies** `na_sg_grid_ilm_policy` **ILM policy tags** `na_sg_grid_ilm_policy_tag` **Erasure-coding profiles** `na_sg_grid_ec_profile` **Regions** `na_sg_grid_regions` **Traffic classification policies** `na_sg_grid_traffic_classes`

Use Case: Manage grid administrators, identity and certificates

Description	Manage grid users, groups, identity federation and single sign-on, and certificates, client certificates and SSH security.
Collection	`netapp.storagegrid` (Certified, NetApp)
Key content	**Grid users** `na_sg_grid_user` **Grid groups** `na_sg_grid_group` **Grid identity federation** `na_sg_grid_identity_federation` **Single sign-on** `na_sg_grid_sso` **Grid and API certificates** `na_sg_grid_certificate` **Self-signed certificates** `na_sg_grid_self_signed_certificate` **Client certificates** `na_sg_grid_client_certificate` **SSH security** `na_sg_grid_ssh_security`

Use Case: Configure grid networking and load balancing

Description	Configure DNS, NTP, proxy, domain names, firewall, VLAN interfaces, untrusted client networks, load balancer endpoints and HA groups.
Collection	`netapp.storagegrid` (Certified, NetApp)
Key content	**DNS servers** `na_sg_grid_dns` **NTP servers** `na_sg_grid_ntp` **Proxy settings** `na_sg_grid_proxy_settings` **Endpoint domain names** `na_sg_grid_domain_name` **Node firewall** `na_sg_grid_firewall` **VLAN interfaces** `na_sg_grid_vlan_interface` **Untrusted client network** `na_sg_grid_untrusted_client_network` **Load balancer endpoints** `na_sg_grid_gateway` **HA groups** `na_sg_grid_ha_group`

Use Case: Monitor the grid and support operations

Description	Log in, gather grid information and metrics, send alerts, configure audit destinations, autosupport and SNMP, and retrieve the recovery package.
Collection	`netapp.storagegrid` (Certified, NetApp)
Key content	**Grid information** `na_sg_grid_info` **Login** `na_sg_grid_login` **Metrics** `na_sg_grid_metrics` **Alert receivers** `na_sg_grid_alert_receiver` **Audit log destinations** `na_sg_grid_audit_destination` **AutoSupport** `na_sg_grid_autosupport` **SNMP agent** `na_sg_grid_snmp` **Recovery package** `na_sg_grid_recovery_package`

Use Case: Install and upgrade grid nodes

Description	Configure the cluster through the install API, apply hotfixes, and set up, install and reset appliance nodes.
Collection	`netapp.storagegrid` (Certified, NetApp)
Key content	**Cluster configuration** `na_sg_grid_cluster_config` **Hotfixes** `na_sg_grid_hotfix` **Appliance node information** `na_sg_pge_info` **Appliance node configuration** `na_sg_pge_config` **Appliance node install** `na_sg_pge_install` **Appliance initial setup** `na_sg_pge_setup` **Primary admin node reset** `na_sg_reset_node_to_pge`

NetApp Unified Manager `netapp.um_info`

Certified NetApp · version 21.9.0 · updated 2024-01-29 · 10 modules → 2 use cases

Use Case: List clusters, nodes and SVMs

Description	Retrieve information about clusters, nodes and storage virtual machines.
Collection	`netapp.um_info` (Certified, NetApp)
Key content	**Clusters** `na_um_clusters_info` **Cluster list** `na_um_list_clusters` **Nodes** `na_um_nodes_info` **Node list** `na_um_list_nodes` **SVMs** `na_um_svms_info` **SVM list** `na_um_list_svms`

Use Case: List aggregates and volumes

Description	Retrieve information about aggregates and volumes.
Collection	`netapp.um_info` (Certified, NetApp)
Key content	**Aggregates** `na_um_aggregates_info` **Aggregate list** `na_um_list_aggregates` **Volumes** `na_um_volumes_info` **Volume list** `na_um_list_volumes`

Other certified and validated collections

Module-level content for these collections could not be read from a public source repository. Browse them on Automation Hub.

`ibm.spectrum_virtualize`	Ansible Collections for IBM Spectrum Virtualize (Certified, IBM; Renamed to ibm.storage_virtualize.)

purestorage.flasharray	Deprecated namespace shim. This collection has been renamed to everpure.flasharray. It contains redirects only and pulls in the new collection as a dependency. Please update playbooks to the everpure.flasharray namespace. (Certified, Pure Storage; Deprecated namespace shim that redirects to everpure.flasharray.)
purestorage.flashblade	Collection of modules to manage Everpure FlashBlade (Certified, Pure Storage; Deprecated namespace; content now published as everpure.flashblade.)
purestorage.pure1	Collection of modules to manage Everpure Pure1 (Certified, Pure Storage; Deprecated namespace; content now published as everpure.pure1.)