Ansible Automation - Use Cases

A reference of the use cases by which Ansible Automation Platform is commonly implemented, by domain. Each use case is described in the same format (Description, Collection, Key content, Notes) and mapped to Red Hat Certified and Validated content.

13 solution use cases · 29 product use cases · generated 2026-10-21 · community reference, not an official Red Hat publication

Contents

1. Event-Driven & Observability
    - Solution use cases (13)
        - Build self-healing infrastructure from monitoring alerts
        - Remediate Dynatrace problems
        - Remediate Splunk ITSI episodes
        - Remediate Microsoft SCOM alerts
        - Remediate IBM Instana events
        - Act on LogicMonitor Edwin AI alerts
        - Remediate Zabbix problems
        - Right-size cloud instances from Turbonomic actions
        - Update BigPanda incidents from automation
        - React to Kafka and webhook event streams
        - React to Red Hat Insights events
        - Manage Event-Driven Ansible as code
        - Roll out monitoring agents at scale
    - Product use cases
        - Event-Driven Ansible (6)
        - BigPanda (1)
        - Splunk OpenTelemetry Collector (1)
        - Datadog (1)
        - Dynatrace (1)
        - Dynatrace (1)
        - IBM Instana (1)
        - IBM Turbonomic (1)
        - LogicMonitor Edwin AI (1)
        - LogicMonitor (3)
        - Red Hat Insights (1)
        - Sensu Go (6)
        - Splunk Enterprise (1)
        - Splunk IT Service Intelligence (2)
        - Zabbix (2)

Event-Driven & Observability

React automatically to events from monitoring, observability and messaging systems.

Solution use cases

Use Case: Build self-healing infrastructure from monitoring alerts

Description	When monitoring raises a known alert, such as a stopped service, a full file system or an unresponsive node, Event-Driven Ansible receives the event, checks it against rules and starts the matching job template or workflow in Automation Platform. The common failures are fixed in seconds, without a person being paged first, and everything is logged.
Collection	`ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `ansible.eda.alertmanager` — Receive events via a webhook from alertmanager or a compatible alerting system. • `ansible.eda.webhook` — Receive events via a webhook. • `ansible.eda.insert_hosts_to_meta` — Extract hosts from the event data and insert them to the meta dict. • `ansible.eda.decision_environment` — Create, update or delete decision environment in EDA Controller • `ansible.eda.project` — Create, update or delete project in EDA Controller • `ansible.eda.rulebook_activation` — Manage rulebook activations in the EDA Controller • `ansible.controller.job_template` — create, update, or destroy job templates.
Notes	• Use a separate rulebook activation per source, and keep rules narrow. Start in "notify only" mode, then switch the action to remediation. • Vendor-specific versions of this pattern: Remediate Dynatrace problems, Remediate Splunk ITSI episodes, Remediate Microsoft SCOM alerts, Remediate IBM Instana events, Act on LogicMonitor Edwin AI alerts, Remediate Zabbix problems and Update BigPanda incidents from automation. • Tie each automatic fix to a ticket using Create and update ServiceNow incidents from automation. • Network alerts: Kentik and Juniper provide event sources in the network domain.

Use Case: Remediate Dynatrace problems

Description	Dynatrace detects problems and identifies the affected entities. With the Dynatrace event sources for Event-Driven Ansible, those problems start the right remediation job in Automation Platform, so known issues are fixed automatically and the result is reported back to the operations team.
Collection	`dynatrace.event_driven_ansible` (Certified), `dynatrace.oneagent` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)

Key content	• `dynatrace.event_driven_ansible.dt_esa_api` — This Event source plugin from Dynatrace captures all problems from your Dynatrace tenant and in conjunction with Ansible EDA rulebooks helps to enable auto-remediation in your environment. • `dynatrace.event_driven_ansible.dt_webhook` — This is an event source plugin for receiving events via a webhook from the "send-event-to-eda" action of the Red Hat Ansible Connector. The payload must be a valid JSON object. • `dynatrace.oneagent.oneagent` — Installs and configures Dynatrace OneAgent on Linux, Windows, and AIX • `ansible.eda.rulebook_activation` — Manage rulebook activations in the EDA Controller • `ansible.controller.job_template` — create, update, or destroy job templates.
Notes	• Start with the webhook path if Dynatrace workflows are already in use, because it removes polling. • Follow the general pattern in Build self-healing infrastructure from monitoring alerts. • Roll out agents together with the other tools in Roll out monitoring agents at scale.

Use Case: Remediate Splunk ITSI episodes

Description	Splunk ITSI groups related alerts into episodes. Event-Driven Ansible reads those episodes, starts a fix when the episode matches a known pattern and records what it did on the episode itself. Operators then see the automation result next to the alert history.
Collection	`splunk.itsi` (Certified), `splunk.enterprise` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `splunk.itsi.aap_eda_rulebook` — Event Driven Ansible (EDA) source for Splunk ITSI Episodes. • `splunk.itsi.itsi_episode_details_info` — Read Splunk ITSI notable_event_group (episodes) • `splunk.itsi.itsi_add_episode_comments` — Add comments to Splunk ITSI episodes • `splunk.itsi.itsi_update_episode_details` — Update specific fields of Splunk ITSI episodes • `splunk.itsi.itsi_aggregation_policy` — Manage Splunk ITSI aggregation policies • `ansible.controller.job_template` — create, update, or destroy job templates.
Notes	• Use `splunk.itsi.itsi_service` and `splunk.itsi.itsi_glass_table` to manage services and dashboards as code in the same repository. • The `splunk.enterprise` collection installs and checks Splunk Universal Forwarders, which feeds the data behind ITSI. • See Build self-healing infrastructure from monitoring alerts for the common design.

Use Case: Remediate Microsoft SCOM alerts

Description	Organizations that monitor Windows servers and applications with System Center Operations Manager (SCOM) can react to alerts automatically. Event-Driven Ansible receives new SCOM alerts, runs the fix, and the playbook closes the alert and puts servers in maintenance while work is done.
Collection	`microsoft.scom` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)

Key content	• `microsoft.scom.scom_plugin` — Event Driven Ansible source for System Center Operations Manager (SCOM) Alerts. • `microsoft.scom.alert` — Manage the state of a SCOM alert. • `microsoft.scom.alert_info` — Retrieve information about SCOM alerts. • `microsoft.scom.maintenance_schedule` — Manage SCOM maintenance schedules. • `ansible.eda.rulebook_activation` — Manage rulebook activations in the EDA Controller
Notes	• Pair with the Windows use cases for patching and service configuration, which provide the fixes. • See Build self-healing infrastructure from monitoring alerts for the general design and guard rails.

Use Case: Remediate IBM Instana events

Description	IBM Instana detects application and infrastructure issues in real time. The Instana webhook source passes those events to Event-Driven Ansible, where rules decide which job template to start, such as restarting a service, scaling a tier or clearing a queue.
Collection	`ibm.instana` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `ibm.instana.instana_webhook` — • `ansible.eda.rulebook_activation` — Manage rulebook activations in the EDA Controller • `ansible.eda.normalize_keys` — Change keys that contain non-alpha numeric or underscore to underscores. • `ansible.controller.job_template` — create, update, or destroy job templates.
Notes	• Publish the Event-Driven Ansible endpoint through a load balancer or an event stream if Instana cannot reach the controller directly. • Follow Build self-healing infrastructure from monitoring alerts for design guidance.

Use Case: Act on LogicMonitor Edwin AI alerts

Description	LogicMonitor Edwin AI correlates and reduces alert noise into fewer, more meaningful alerts. Event-Driven Ansible consumes those alerts and starts remediation for the ones with a known fix, so automation works on an incident and not on dozens of duplicate symptoms.
Collection	`logicmonitor.edwin_ai` (Certified), `logicmonitor.integration` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `logicmonitor.edwin_ai.alerts` — • `logicmonitor.edwin_ai.kafka` — • `logicmonitor.edwin_ai.webhook` — Receive Edwin AI alert events via an HTTP webhook. • `logicmonitor.edwin_ai.query_api` — Edwin Query API • `logicmonitor.integration.lm_device` — LogicMonitor Device Ansible module for managing devices. • `ansible.controller.job_template` — create, update, or destroy job templates.

Notes	• Choose Kafka when alert volumes are high or when delivery must survive controller downtime. • See Build self-healing infrastructure from monitoring alerts for the shared pattern, and React to Kafka and webhook event streams for source details.

Use Case: Remediate Zabbix problems

Description	Zabbix triggers raise problems for hosts and services. A webhook from Zabbix delivers them to Event-Driven Ansible, which starts the remediation job for known problems. The same collection deploys agents and registers hosts so that monitoring follows the automation inventory.
Collection	`zabbix.zabbix` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `zabbix.zabbix.zabbix_event` — Module for event actions • `zabbix.zabbix.zabbix_host` — Module for creating and deleting hosts, and updating existing ones. • `zabbix.zabbix.zabbix_inventory` — Zabbix inventory plugin • `zabbix.zabbix.agent` — Zabbix agent maintenance • `ansible.eda.webhook` — Receive events via a webhook. • `ansible.controller.job_template` — create, update, or destroy job templates.
Notes	• The collection ships remediation examples (`zabbix.zabbix.example_oci_volume_extend`) that show the intended wiring. • See Build self-healing infrastructure from monitoring alerts and Roll out monitoring agents at scale.

Use Case: Right-size cloud instances from Turbonomic actions

Description	Turbonomic recommends resizing cloud instances to match actual demand. Instead of copying each recommendation into a ticket, Turbonomic sends the approved action to Event-Driven Ansible, and a playbook resizes the EC2 instance or Azure virtual machine.
Collection	`ibm.turbonomic_eda` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `ibm.turbonomic_eda.eda_webhook` — Module to allow users to create Turbonomic Webhooks to send actions to Event Drive Ansible • `ibm.turbonomic_eda.resize_ec2_instance` — Role used with Turbonomic and Event Driven Ansible to resize AWS EC2 instance • `ibm.turbonomic_eda.resize_azure_instance` — Role used with Turbonomic and Event Driven Ansible to resize Azure Virtual Machines • `ibm.turbonomic_eda.resize_ec2` — Resize EC2 Instance from Turbonomic Recommendation via Event Driven Ansible • `ibm.turbonomic_eda.resize_azure` — Resize Azure Virtual Machine from Turbonomic Recommendation via Event Driven Ansible • `ansible.eda.webhook` — Receive events via a webhook.
Notes	• Begin with non-production accounts and recommendations that scale down idle instances. • Pair with the cloud use cases for tagging and cost hygiene.

Use Case: Update BigPanda incidents from automation

Description	BigPanda groups alerts from many tools into incidents. Automation can act on those incidents and keep BigPanda current: a job comments on the incident, tags it, assigns it, and resolves it when the fix is confirmed, so the operations center sees what automation did.
Collection	`bigpanda.incident` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `bigpanda.incident.comment` — Add a comment to a BigPanda incident. • `bigpanda.incident.assign` — Assign a user to a BigPanda incident. • `bigpanda.incident.add_tag` — Update a BigPanda incident tag. • `bigpanda.incident.resolve` — Resolve a BigPanda incident. • `bigpanda.incident.resolve_alert` — Resolve one or more BigPanda alerts. • `bigpanda.incident.merge` — Merge multiple BigPanda incidents into one. • `ansible.eda.webhook` — Receive events via a webhook.
Notes	• Use Create and update ServiceNow incidents from automation when tickets live in ServiceNow and BigPanda is only the correlation layer. • See Build self-healing infrastructure from monitoring alerts.

Use Case: React to Kafka and webhook event streams

Description	Business and platform events often travel on Kafka topics, cloud queues or webhooks: a new order, a deployment record, a pushed commit or a cloud audit event. Event-Driven Ansible subscribes to them and launches the matching automation, so integrations no longer depend on polling or on scheduled jobs.
Collection	`ansible.eda` (Certified), `ansible.controller` (Certified), `ansible.scm` (Certified)
Key content	• `ansible.eda.kafka` — Receive events via a kafka topic. • `ansible.eda.webhook` — Receive events via a webhook. • `ansible.eda.aws_sqs_queue` — Receive events via an AWS SQS queue. • `ansible.eda.azure_service_bus` — Receive events from an Azure service bus. • `ansible.eda.event_stream` — Manage event streams in EDA Controller • `ansible.eda.json_filter` — Filter keys out of events. • `ansible.controller.project_update` — Update a Project in Automation Platform Controller
Notes	• Use Kafka rather than direct webhooks when the sender cannot retry, or when events must be buffered. • Avoid putting secrets in events. Use credentials in Automation Platform for the job itself. • Observability tools that offer their own source plugins are covered by the vendor pages, starting with Build self-healing infrastructure from monitoring alerts.

Use Case: React to Red Hat Insights events

Description	Red Hat Insights analyses registered RHEL systems and reports findings. The Insights event source brings those events to Event-Driven Ansible, so a new finding can open a ticket, run a remediation playbook or start a patch workflow, instead of waiting for someone to review a console.
Collection	`redhat.insights_eda` (Certified), `redhat.insights` (Certified), `ansible.eda` (Certified), `ansible.controller` (Certified)
Key content	• `redhat.insights_eda.insights` — Receive Red Hat Insights events. • `redhat.insights.insights_client` — Install and configure Red Hat Insights Client • `redhat.insights.insights` — insights inventory source • `ansible.eda.rulebook_activation` — Manage rulebook activations in the EDA Controller • `ansible.controller.job_template` — create, update, or destroy job templates.
Notes	• Combine with the Linux use cases for patching and remediation with Red Hat Insights. • Review the event types delivered by the source in its documentation, and match on those fields only.

Use Case: Manage Event-Driven Ansible as code

Description	Rulebook activations, credentials and decision environments are configured in the Event-Driven Ansible controller. Defining them in Git as variable files, and applying them with a pipeline, gives review, history and a repeatable setup across development, test and production.
Collection	`ansible.eda` (Certified), `infra.eda_configuration` (Validated), `infra.aap_configuration` (Validated)
Key content	• `ansible.eda.project` — Create, update or delete project in EDA Controller • `ansible.eda.decision_environment` — Create, update or delete decision environment in EDA Controller • `ansible.eda.credential` — Manage credentials in EDA Controller • `ansible.eda.event_stream` — Manage event streams in EDA Controller • `ansible.eda.rulebook_activation` — Manage rulebook activations in the EDA Controller • `infra.eda_configuration.dispatch` — An Ansible Role to call other roles to create objects on Ansible eda. • `infra.aap_configuration.eda_rulebook_activations` — An Ansible Role to create rulebook activations in EDA controller.
Notes	• Related: Manage Automation Platform as code for the same approach on controller, gateway and hub. • Restart an activation when its rulebook changes, so the new rules are loaded.

Use Case: Roll out monitoring agents at scale

Description	Event-Driven remediation only works for hosts that are monitored. This use case installs, configures and upgrades the monitoring agent of the chosen platform on all servers, and applies it automatically to new builds.

Collection	`datadog.dd` (Certified), `dynatrace.oneagent` (Certified), `cisco.splunk_otel_collector` (Validated), `splunk.enterprise` (Certified), `zabbix.zabbix` (Certified)
Key content	• `datadog.dd.agent` — Install Datadog agent and configure checks • `dynatrace.oneagent.oneagent` — Installs and configures Dynatrace OneAgent on Linux, Windows, and AIX • `cisco.splunk_otel_collector.collector` — Ansible role to install and configure the Splunk OpenTelemetry Collector • `splunk.enterprise.splunk_universal_forwarder_linux` — Manage Splunk Universal Forwarder installations on RHEL systems • `splunk.enterprise.win_splunk_universal_forwarder` — Install and bootstrap Splunk Universal Forwarder on Windows • `zabbix.zabbix.agent` — Zabbix agent maintenance
Notes	• Install only one agent per purpose to avoid duplicate data and cost. • Once hosts are monitored, use Build self-healing infrastructure from monitoring alerts to act on their alerts.

Product use cases

Grouped from the modules of each certified or validated collection. Key content lists the components each use case supports, with the modules that manage them (create, update, delete) and query them (_info).

Event-Driven Ansible `ansible.eda`

Certified Red Hat · version 2.13.0 · updated 2026-07-07 · 19 modules → 6 use cases

Use Case: Run rulebook activations

Description	Manage rulebooks, projects, decision environments, rulebook activations and event streams in EDA Controller.
Collection	`ansible.eda` (Certified, Red Hat)
Key content	**Projects** `project`, `project_info` **Decision environments** `decision_environment`, `decision_environment_info` **Rulebooks** `rulebook_info` **Rulebook activations** `rulebook_activation`, `rulebook_activation_info` **Activation copies** `rulebook_activation_copy` **Event streams** `event_stream`, `event_stream_info` **Hello playbook** playbook `hello`

Use Case: Manage EDA Controller credentials and access

Description	Manage credentials, credential types and input sources, users, tokens and team role assignments.
Collection	`ansible.eda` (Certified, Red Hat)

Key content	**Credentials** `credential`, `credential_info` **Credential types** `credential_type`, `credential_type_info` **Credential input sources** `credential_input_source`, `credential_input_source_info` **Controller tokens** `controller_token` **Users** `user` **Team role assignments** `role_team_assignment`

Use Case: Receive events from webhooks, alerts and message queues

Description	Receive events through webhooks, Alertmanager, Kafka, AWS SQS and CloudTrail, Azure Service Bus and PostgreSQL notifications.
Collection	`ansible.eda` (Certified, Red Hat)
Key content	**Webhooks** eda event source `webhook` **Alertmanager** eda event source `alertmanager` **Kafka topics** eda event source `kafka` **AWS SQS queues** eda event source `aws_sqs_queue` **AWS CloudTrail** eda event source `aws_cloudtrail` **Azure Service Bus** eda event source `azure_service_bus` **PostgreSQL pub/sub** eda event source `pg_listener`

Use Case: Watch systems, files and URLs

Description	Generate events from file changes, journald logs and URL status checks.
Collection	`ansible.eda` (Certified, Red Hat)
Key content	**YAML fact files** eda event source `file` **File system changes** eda event source `file_watch` **journald logs** eda event source `journald` **URL status checks** eda event source `url_check`

Use Case: Test rulebooks with generated events

Description	Generate synthetic events for developing and testing rules.
Collection	`ansible.eda` (Certified, Red Hat)
Key content	**Custom data** eda event source `generic` **Finite event ranges** eda event source `range` **Continuous ticks** eda event source `tick`

Use Case: Shape and normalize event data

Description	Filter keys, normalize key names and extract hosts from events before rules evaluate them.
Collection	`ansible.eda` (Certified, Red Hat)

Key content	**Dashes to underscores** eda event filter `dashes_to_underscores` **Hosts to event metadata** eda event filter `insert_hosts_to_meta` **Key filter** eda event filter `json_filter` **No-op filter** eda event filter `noop` **Key normalization** eda event filter `normalize_keys`

BigPanda `bigpanda.incident`

Certified BigPanda · version 1.3.1 · updated 2026-06-15 · 7 modules → 1 use cases

Use Case: Triage and resolve BigPanda incidents

Description	Tag, assign, comment on, merge, split and resolve BigPanda incidents and resolve alerts.
Collection	`bigpanda.incident` (Certified, BigPanda)
Key content	**Incident tags** `add_tag` **Incident assignment** `assign` **Incident comments** `comment` **Merge incidents** `merge` **Split incidents** `split` **Resolve incidents** `resolve` **Resolve alerts** `resolve_alert`

Splunk OpenTelemetry Collector `cisco.splunk_otel_collector`

Validated Cisco · version 1.0.0 · updated 2026-03-03 · 0 modules → 1 use cases

Use Case: Install the Splunk OpenTelemetry Collector

Description	Install and configure the collector.
Collection	`cisco.splunk_otel_collector` (Validated, Cisco)
Key content	**OpenTelemetry Collector** role `collector`

Datadog `datadog.dd`

Certified Datadog · version 6.5.0 · updated 2026-02-11 · 0 modules → 1 use cases

Use Case: Install the Datadog agent

Description	Install the Datadog agent and configure checks.
Collection	`datadog.dd` (Certified, Datadog)
Key content	**Datadog agent** role `agent`

Dynatrace `dynatrace.event_driven_ansible`

Certified Dynatrace · version 1.2.3 · updated 2025-08-25 · 0 modules → 1 use cases

Use Case: Remediate Dynatrace problems with Event-Driven Ansible

Description	Receive Dynatrace problems or webhook events in rulebooks to trigger auto-remediation.
Collection	`dynatrace.event_driven_ansible` (Certified, Dynatrace)
Key content	**Problems API event source** eda event source `dt_esa_api` **Webhook event source** eda event source `dt_webhook` **Test playbook** playbook `run-task`

Dynatrace `dynatrace.oneagent`

Certified Dynatrace · version 1.3.1 · updated 2026-08-28 · 0 modules → 1 use cases

Use Case: Install Dynatrace OneAgent

Description	Install and configure OneAgent on Linux, Windows and AIX.
Collection	`dynatrace.oneagent` (Certified, Dynatrace)
Key content	**OneAgent** role `oneagent`

IBM Instana `ibm.instana`

Certified IBM · version 1.0.32 · updated 2024-04-15 · 0 modules → 1 use cases

Use Case: Respond to Instana events

Description	Receive Instana webhook events in Event-Driven Ansible.
Collection	`ibm.instana` (Certified, IBM)
Key content	**Webhook event source** eda event source `instana_webhook`

IBM Turbonomic `ibm.turbonomic_eda`

Certified IBM · version 1.0.2 · updated 2024-05-29 · 1 modules → 1 use cases

Use Case: Resize cloud instances from Turbonomic recommendations

Description	Create Turbonomic webhooks that send actions to Event-Driven Ansible and resize Azure virtual machines or AWS EC2 instances accordingly.

Collection	`ibm.turbonomic_eda` (Certified, IBM)
Key content	**Turbonomic webhooks** `eda_webhook` **Resize Azure VMs** role `resize_azure_instance` **Resize Azure VM playbook** playbook `resize_azure` **Resize EC2 instances** role `resize_ec2_instance` **Resize EC2 playbook** playbook `resize_ec2`

LogicMonitor Edwin AI `logicmonitor.edwin_ai`

Certified LogicMonitor · version 1.0.1 · updated 2026-04-02 · 1 modules → 1 use cases

Use Case: Respond to Edwin AI alerts

Description	Receive Edwin AI alerts through webhook, Kafka or alert sources in Event-Driven Ansible, query the Edwin API and debug events.
Collection	`logicmonitor.edwin_ai` (Certified, LogicMonitor)
Key content	**Alerts event source** eda event source `alerts` **Kafka event source** eda event source `kafka` **Webhook event source** eda event source `webhook` **Edwin Query API** `query_api` **Debug event playbook** playbook `debug_event`

LogicMonitor `logicmonitor.integration`

Certified LogicMonitor · version 2.0.3 · updated 2023-10-27 · 10 modules → 3 use cases

Use Case: Onboard and organize monitored devices

Description	Manage devices, device groups and datasources, and gather information about LogicMonitor objects.
Collection	`logicmonitor.integration` (Certified, LogicMonitor)
Key content	**Devices** `lm_device` **Device groups** `lm_device_group` **Datasources** `lm_datasource` **Website checks** `lm_website_check` **LogicMonitor information** `lm_info`

Use Case: Manage collectors

Description	Manage collectors, collector groups and OpenTelemetry collectors.
Collection	`logicmonitor.integration` (Certified, LogicMonitor)

Key content	**Collectors** `lm_collector` **Collector groups** `lm_collector_group` **OpenTelemetry collectors** `lm_otel_collector`

Use Case: Route alerts

Description	Manage alert rules and escalation chains and receive events in Event-Driven Ansible.
Collection	`logicmonitor.integration` (Certified, LogicMonitor)
Key content	**Alert rules** `lm_alert_rule` **Escalation chains** `lm_escalation_chain` **Webhook event source** eda event source `webhook`

Red Hat Insights `redhat.insights_eda`

Certified Red Hat · version 1.2.6 · updated 2026-08-14 · 0 modules → 1 use cases

Use Case: Respond to Red Hat Insights events

Description	Receive Red Hat Insights events in Event-Driven Ansible.
Collection	`redhat.insights_eda` (Certified, Red Hat)
Key content	**Insights event source** eda event source `insights`

Sensu Go `sensu.sensu_go`

Certified Sensu · version 1.14.0 · updated 2023-09-01 · 51 modules → 6 use cases

Use Case: Define monitoring checks and assets

Description	Create checks, hooks, assets and Bonsai assets, and register monitored entities.
Collection	`sensu.sensu_go` (Certified, Sensu)
Key content	**Checks** `check`, `check_info` **Hooks** `hook`, `hook_info` **Assets** `asset`, `asset_info` **Bonsai assets** `bonsai_asset` **Entities** `entity`, `entity_info`

Use Case: Process events and route notifications

Description	Manage events, filters, mutators, handlers, handler sets, pipelines and silences to route and suppress alerts.

Collection	`sensu.sensu_go` (Certified, Sensu)
Key content	**Events** `event`, `event_info` **Filters** `filter`, `filter_info` **Mutators** `mutator`, `mutator_info` **Handlers** `handler_info` **Handler sets** `handler_set` **Pipe handlers** `pipe_handler` **Socket handlers** `socket_handler` **Pipelines** `pipeline`, `pipeline_info` **Silences** `silence`, `silence_info`

Use Case: Control access and authentication

Description	Manage users, roles, role bindings, cluster roles and bindings, and AD, LDAP and OIDC authentication providers.
Collection	`sensu.sensu_go` (Certified, Sensu)
Key content	**Users** `user`, `user_info` **Roles** `role`, `role_info` **Role bindings** `role_binding`, `role_binding_info` **Cluster roles** `cluster_role`, `cluster_role_info` **Cluster role bindings** `cluster_role_binding`, `cluster_role_binding_info` **Authentication providers** `auth_provider_info` **Active Directory provider** `ad_auth_provider` **LDAP provider** `ldap_auth_provider` **OIDC provider** `oidc_auth_provider`

Use Case: Manage namespaces, secrets and datastores

Description	Manage namespaces, secrets and secrets providers (environment and Vault), external datastores, and Tessen data sharing.
Collection	`sensu.sensu_go` (Certified, Sensu)
Key content	**Namespaces** `namespace`, `namespace_info` **Secrets** `secret`, `secret_info` **Secrets providers** `secrets_provider_info` **Environment secrets provider** `secrets_provider_env` **Vault secrets provider** `secrets_provider_vault` **External datastores** `datastore`, `datastore_info` **Tessen** `tessen`

Use Case: Operate Sensu clusters

Description	Manage Sensu Go clusters and etcd replicators.
Collection	`sensu.sensu_go` (Certified, Sensu)

Key content	**Clusters** `cluster`, `cluster_info` **Etcd replicators** `etcd_replicator`, `etcd_replicator_info`

Use Case: Install the backend and agents

Description	Enable Sensu repositories and install, configure and start the backend and agents, with helper filters for inventory.
Collection	`sensu.sensu_go` (Certified, Sensu)
Key content	**Installation role** role `install` **Backend role** role `backend` **Agent role** role `agent` **Backend connection filter** filter `backends` **Package name filter** filter `package_name`

Splunk Enterprise `splunk.enterprise`

Certified Red Hat · version 1.0.0 · updated 2026-01-27 · 4 modules → 1 use cases

Use Case: Deploy Splunk Universal Forwarders

Description	Install and bootstrap the Splunk Universal Forwarder on Linux and Windows hosts.
Collection	`splunk.enterprise` (Certified, Red Hat)
Key content	**Universal Forwarder on Linux** `splunk_universal_forwarder_linux`, `splunk_universal_forwarder_linux_info` **Universal Forwarder on Windows** `win_splunk_universal_forwarder`, `win_splunk_universal_forwarder_info`

Splunk IT Service Intelligence `splunk.itsi`

Certified Red Hat · version 2.0.0 · updated 2026-04-16 · 11 modules → 2 use cases

Use Case: Manage services, glass tables and correlation searches

Description	Create and update ITSI services, the glass tables that visualise them, and correlation searches that generate notable events.
Collection	`splunk.itsi` (Certified, Red Hat)
Key content	**Services** `itsi_service`, `itsi_service_info` **Glass tables** `itsi_glass_table`, `itsi_glass_table_info` **Correlation searches** `itsi_correlation_search`, `itsi_correlation_search_info`

Use Case: Group and respond to episodes

Description	Define aggregation policies that group notable events into episodes, read episode details, add comments and update episode fields, and trigger Event-Driven Ansible from ITSI episodes.
Collection	`splunk.itsi` (Certified, Red Hat)
Key content	**Aggregation policies** `itsi_aggregation_policy`, `itsi_aggregation_policy_info` **Episode details** `itsi_episode_details_info` **Episode comments** `itsi_add_episode_comments` **Episode updates** `itsi_update_episode_details` **ITSI episode event source** eda event source `aap_eda_rulebook`

Zabbix `zabbix.zabbix`

Certified Zabbix · version 1.4.2 · updated 2025-07-10 · 5 modules → 2 use cases

Use Case: Manage monitored hosts and proxies

Description	Create, update and delete hosts, host groups, proxies and proxy groups, and maintain hosts and agents.
Collection	`zabbix.zabbix` (Certified, Zabbix)
Key content	**Hosts** `zabbix_host` **Host groups** `zabbix_hostgroup` **Proxies** `zabbix_proxy` **Proxy groups** `zabbix_proxy_group` **Host maintenance** role `host` **Agent maintenance** role `agent` **Repository list** role `repository` **Zabbix inventory** inventory `zabbix_inventory`

Use Case: Respond to Zabbix events

Description	Act on events and run example remediation playbooks.
Collection	`zabbix.zabbix` (Certified, Zabbix)
Key content	**Events** `zabbix_event` **Example remediation** playbook `example_dummy` **OCI volume extension remediation** playbook `example_oci_volume_extend`