Ansible Automation - Use Cases

A reference of the use cases by which Ansible Automation Platform is commonly implemented, by domain. Each use case is described in the same format (Description, Collection, Key content, Notes) and mapped to Red Hat Certified and Validated content.

14 solution use cases · 56 product use cases · generated 2026-10-21 · community reference, not an official Red Hat publication

Contents

1. Applications, Middleware & Databases
    - Solution use cases (14)
        - Deploy and patch JBoss EAP
        - Deploy JBoss Web Server and JBoss Core Services
        - Patch application nodes one at a time behind a load balancer
        - Deploy applications from a Maven repository
        - Build and deploy a Quarkus application from Git
        - Configure MySQL and MariaDB databases and replication
        - Install PostgreSQL and SQL Server
        - Deploy AMQ Broker messaging
        - Deploy Apache Kafka with AMQ Streams or Confluent Platform
        - Deploy Red Hat Data Grid and caches
        - Deploy Red Hat build of Keycloak
        - Install SAP HANA and S/4HANA
        - Run SAP Day 2 operations
        - Shut down and start up a multi-tier application
    - Product use cases
        - MariaDB (3)
        - MySQL and MariaDB (3)
        - Avantra (1)
        - Confluent Platform (5)
        - Red Hat OpenShift Virtualization (2)
        - Microsoft SQL Server (1)
        - Red Hat AMQ Broker (ActiveMQ Artemis) (2)
        - Red Hat AMQ Streams (Apache Kafka) (2)
        - Red Hat Data Grid (1)
        - Red Hat JBoss EAP / WildFly (3)
        - Red Hat JBoss Core Services (1)
        - Red Hat JBoss Web Server (1)
        - Quarkus (1)
        - Red Hat Customer Portal (1)
        - Red Hat build of Keycloak (7)
        - Red Hat JBoss middleware runtimes (1)
        - SAP infrastructure on Red Hat (1)
        - SAP on Red Hat Enterprise Linux (5)
        - Red Hat Single Sign-On (Keycloak) (7)
        - SAP (HANA, ABAP, NetWeaver and BTP) (8)

Applications, Middleware & Databases

Day 2 operations for applications, middleware, databases and SAP.

Solution use cases

Use Case: Deploy and patch JBoss EAP

Description	JBoss EAP servers are installed, configured, patched and removed the same way on every host. The automation covers the full life cycle that administrators do by hand today: install and service setup, subsystem and data source configuration, a version update with a rollback point, and uninstall.
Collection	`redhat.eap` (Certified), `redhat.runtimes_common` (Certified), `redhat.redhat_csp_download` (Certified)
Key content	• `redhat.eap.wildfly_install` — Install wildfly application server or JBoss Enterprise Application (EAP) • `redhat.eap.wildfly_systemd` — Configure systemd service unit for wildfly or EAP • `redhat.eap.wildfly_subs` — Install wildfly application server or JBoss Enterprise Application (EAP) • `redhat.eap.wildfly_driver` — Install a JDBC driver module in wildfly application server or JBoss Enterprise Application (EAP) • `redhat.eap.wildfly_snapshot` — WildFly configuration snapshot and rollback management • `redhat.eap.wildfly_validation` — Provides handy, reusable playbooks to validate that server was properly installed • `redhat.eap.wildfly_uninstall` — Uninstalls wildfly • `redhat.runtimes_common.product_download` — Downloads products from the Red Hat Unified Downloads API.
Notes	• Deploy the applications themselves with Deploy applications from a Maven repository. • For clusters patch node by node with Patch application nodes one at a time behind a load balancer. • Use `redhat.eap.wildfly_migration` to move configuration between versions where supported. • The same roles manage upstream WildFly, which is useful for development environments.

Use Case: Deploy JBoss Web Server and JBoss Core Services

Description	Web and servlet tiers are built the same way every time. JBoss Web Server (Apache Tomcat) hosts Java web applications, and JBoss Core Services (Apache HTTP Server) acts as the front end. The automation installs, configures, restarts, upgrades and removes both, with validation after each change.
Collection	`redhat.jws` (Certified), `redhat.jbcs` (Certified), `redhat.runtimes_common` (Certified)
Key content	• `redhat.jws.jws` — Install and configure a tomcat or jws server • `redhat.jws.jws_validation` — This role validates JWS deployment and setup. • `redhat.jbcs.jbcs` — Install and configure JBoss Core Service. • `redhat.runtimes_common.product_download` — Downloads products from the Red Hat Unified Downloads API. • `redhat.runtimes_common.xml` — Manage bits and pieces of XML files or strings

Notes	• Combine with Patch application nodes one at a time behind a load balancer for rolling upgrades. • Application files are deployed separately, see Deploy applications from a Maven repository.

Use Case: Patch application nodes one at a time behind a load balancer

Description	Clustered application servers are updated without an outage. A playbook takes one node at a time out of the load balancer pool, stops traffic, patches or reconfigures it, checks health and puts it back, and only then moves to the next node.
Collection	`f5networks.f5_modules` (Certified), `redhat.eap` (Certified), `redhat.jws` (Certified), `redhat.runtimes_common` (Certified)
Key content	• `f5networks.f5_modules.bigip_pool_member` — Manages F5 BIG-IP LTM pool members • `redhat.eap.wildfly_snapshot` — WildFly configuration snapshot and rollback management • `redhat.eap.wildfly_install` — Install wildfly application server or JBoss Enterprise Application (EAP) • `redhat.eap.wildfly_validation` — Provides handy, reusable playbooks to validate that server was properly installed • `redhat.jws.jws_validation` — This role validates JWS deployment and setup. • `redhat.runtimes_common.tail_grep` — Tail a logfile until a regex matcher is found or a timeout triggers
Notes	• Other load balancers have their own collections in the network domain, so replace the pool member step to suit. • Use this pattern for Deploy and patch JBoss EAP, Deploy JBoss Web Server and JBoss Core Services, and database node maintenance. • Run it from a workflow that adds approval and a ServiceNow change, see Automate change requests with approval gates.

Use Case: Deploy applications from a Maven repository

Description	Build pipelines publish WAR and JAR files to a Maven repository such as Nexus or Artifactory. A job pulls an exact version from the repository and deploys it to the target servers, so any environment can be given any released version in the same way.
Collection	`redhat.runtimes_common` (Certified), `redhat.eap` (Certified)
Key content	• `redhat.runtimes_common.maven_artifact` — Downloads an Artifact from a Maven Repository • `redhat.eap.wildfly_app_deploy` — Deploy applications to WildFly application server • `redhat.eap.wildfly_validation` — Provides handy, reusable playbooks to validate that server was properly installed • `redhat.runtimes_common.tail_grep` — Tail a logfile until a regex matcher is found or a timeout triggers
Notes	• Use Build and deploy a Quarkus application from Git when the application is built on the target from source. • Do not store repository passwords in playbooks. Use a credential.

Use Case: Build and deploy a Quarkus application from Git

Description	Teams that run Quarkus applications on virtual machines or bare metal can have the build, install and service setup done by Ansible. The role clones the repository, builds the application and starts it as a systemd service, so a new environment needs one job run.
Collection	`redhat.quarkus` (Certified), `redhat.runtimes_common` (Certified)
Key content	• `redhat.quarkus.quarkus` — Automate the installation and deployement of a Quarkus application • `redhat.quarkus.playbook` — Build and deploy a Quarkus app using Ansible • `redhat.runtimes_common.tail_grep` — Tail a logfile until a regex matcher is found or a timeout triggers
Notes	• For container deployments use the Kubernetes and OpenShift use cases instead. • For pre-built artifacts see Deploy applications from a Maven repository.

Use Case: Configure MySQL and MariaDB databases and replication

Description	Database servers are configured with the same standard every time. The automation creates the schema, users and roles that an application needs, sets server variables and password policy, and builds replication between primary and replica servers.
Collection	`ansible.mysql` (Certified), `ansible.mariadb` (Certified)
Key content	• `ansible.mysql.mysql_db` — Add or remove MySQL or MariaDB databases from a remote host • `ansible.mysql.mysql_user` — Adds or removes a user from a MySQL or MariaDB database • `ansible.mysql.mysql_role` — Adds, removes, or updates a MySQL or MariaDB role • `ansible.mysql.mysql_variables` — Manage MySQL or MariaDB global variables • `ansible.mysql.mysql_replication` — Manage MySQL or MariaDB replication • `ansible.mysql.mysql_info` — Gather information about MySQL or MariaDB servers • `ansible.mariadb.mariadb_db` — Add or remove MariaDB databases from a remote host • `ansible.mariadb.mariadb_replication` — Manage MariaDB replication
Notes	• For a rolling restart or upgrade of replicas see Patch application nodes one at a time behind a load balancer. • PostgreSQL and SQL Server are covered in Install PostgreSQL and SQL Server.

Use Case: Install PostgreSQL and SQL Server

Description	Database servers are delivered ready to use: the packages are installed, the service is configured and secured, and the basic settings follow the standard. The same job templates serve development, test and production.
Collection	`redhat.rhel_system_roles` (Certified), `microsoft.sql` (Certified), `edb.epas_postgresql` (Certified)
Key content	• `redhat.rhel_system_roles.postgresql` — The PostgreSQL system role installs, configures, and starts the PostgreSQL • `microsoft.sql.server` — This role installs and configures Microsoft SQL Server

Notes	• MySQL and MariaDB are covered in Configure MySQL and MariaDB databases and replication. • Use the SAP use cases for SAP HANA, see Install SAP HANA and S/4HANA. • Take a backup before any change to a production database, and keep it outside the job host.

Use Case: Deploy AMQ Broker messaging

Description	Messaging brokers are installed with the same security and queue configuration in every environment. The automation builds standalone brokers or primary and backup pairs, configures addresses, queues and users, and removes brokers cleanly when they are retired.
Collection	`redhat.amq_broker` (Certified), `redhat.runtimes_common` (Certified)
Key content	• `redhat.amq_broker.activemq` — Installs and configures ActiveMQ services. • `redhat.amq_broker.activemq_cluster` — Playbook to deploy activemq in master/standby with shared datadir • `redhat.amq_broker.activemq_facts` — Return activemq configuration as fact data • `redhat.amq_broker.activemq_uninstall` — Uninstalls an ActiveMQ service installed by the activemq role. • `redhat.runtimes_common.product_download` — Downloads products from the Red Hat Unified Downloads API.
Notes	• For event streaming see Deploy Apache Kafka with AMQ Streams or Confluent Platform. • Event-Driven Ansible can consume the same Kafka topics, see React to Kafka and webhook event streams.

Use Case: Deploy Apache Kafka with AMQ Streams or Confluent Platform

Description	Event streaming clusters are built from the same inventory and variables every time. Ansible installs the brokers, controllers and supporting services, applies security settings and validates the cluster. Two certified options are covered: Red Hat AMQ Streams, and Confluent Platform.
Collection	`redhat.amq_streams` (Certified), `confluent.platform` (Certified)
Key content	• `redhat.amq_streams.amq_streams_kraft` — Install AMQ Streams Kafka server in KRaft mode • `redhat.amq_streams.amq_streams_broker` — Install AMQ Streams Zookeeper server • `redhat.amq_streams.amq_streams_connect` — Install AMQ Streams Zookeeper server • `redhat.amq_streams.amq_streams_exporter` — Install AMQ Streams Exporter server • `confluent.platform.kafka_broker` — This is role for setting up Kafka Brokers • `confluent.platform.kafka_controller` — This is role for setting up Kafka Controller • `confluent.platform.schema_registry` — This is role for setting up Schema Registry • `confluent.platform.kafka_connectors` — This module allows setting up Kafka connectors from Ansible.
Notes	• Confluent playbooks also support support-bundle collection when a run fails, which helps with vendor cases. • Use React to Kafka and webhook event streams to start automation from the topics. • For traditional queues and topics see Deploy AMQ Broker messaging.

Use Case: Deploy Red Hat Data Grid and caches

Description	In-memory data grids hold session data and fast-changing application data. The automation installs a Data Grid cluster with the same security and clustering settings on every node, and creates or changes caches without restarting the servers.
Collection	`redhat.data_grid` (Certified), `redhat.runtimes_common` (Certified)
Key content	• `redhat.data_grid.infinispan` — Install and configure an Infinispan or DataGrid service. • `redhat.data_grid.infinispan_cache` — Configure Infinispan or DataGrid cache at runtime. • `redhat.runtimes_common.product_download` — Downloads products from the Red Hat Unified Downloads API.
Notes	• Use Data Grid together with Deploy and patch JBoss EAP for session clustering.

Use Case: Deploy Red Hat build of Keycloak

Description	Single sign-on is delivered as a service for applications. Ansible installs Red Hat build of Keycloak with a database, TLS and clustering, so the identity service is the same in every environment and can be rebuilt on demand.
Collection	`redhat.rhbk` (Certified), `redhat.sso` (Certified), `redhat.runtimes_common` (Certified)
Key content	• `redhat.rhbk.keycloak` — Install keycloak or Red Hat Single Sign-On server configurations • `redhat.rhbk.rhsso` — Playbook for Red Hat SSO Hosts • `redhat.sso.keycloak` — Install keycloak or Red Hat Single Sign-On server configurations • `redhat.runtimes_common.product_download` — Downloads products from the Red Hat Unified Downloads API.
Notes	• Use `redhat.rhbk.rhsso` or the `redhat.sso` collection for environments that still run Red Hat Single Sign-On, and plan the move to the newer product. • Configuring realms, clients and users after installation is a separate task for Keycloak administration.

Use Case: Install SAP HANA and S/4HANA

Description	SAP landscapes are installed from code, so that every system is built to the same Red Hat and SAP recommendations. Ansible provisions the virtual machine, prepares RHEL, sets up storage, installs SAP HANA and the application layer with SAP Software Provisioning Manager, and optionally builds the high-availability cluster.
Collection	`redhat.sap_install` (Certified), `redhat.sap_infrastructure` (Certified), `sap.sap_operations` (Certified)

Key content	• `redhat.sap_infrastructure.sap_vm_provision` — The Ansible Role `sap_vm_provision` is used to provision Virtual Machines to host SAP Software. • `redhat.sap_install.sap_general_preconfigure` — Variables for SAP general preconfiguration • `redhat.sap_install.sap_hana_preconfigure` — Variables for SAP HANA preconfiguration • `redhat.sap_install.sap_storage_setup` — SAP system storage setup • `redhat.sap_install.sap_hana_install` — SAP HANA Installation • `redhat.sap_install.sap_swpm` — The Ansible role `sap_swpm` installs various SAP Systems installable by SAP Software Provisioning Manager (SWPM). • `redhat.sap_install.sap_ha_pacemaker_cluster` — SAP HA automated cluster setup requirements • `redhat.sap_install.sap_install_media_detect` — The Ansible Role `sap_install_media_detect` is used to detect and extract SAP installation media.
Notes	• Continue with Run SAP Day 2 operations. • The collection contains sample playbooks for single-node, distributed and two-node cluster installs. Start from the one that matches the design. • Database tier alternatives are in Install PostgreSQL and SQL Server.

Use Case: Run SAP Day 2 operations

Description	Routine SAP administration, such as backups, start and stop, kernel and HANA updates, license handling and cluster checks, is run as controlled automation. Basis teams get the same procedure on every system, with approvals and logs, and fewer hand-typed commands.
Collection	`sap.sap_operations` (Certified), `avantra.core` (Certified), `redhat.sap_install` (Certified)
Key content	• `sap.sap_operations.hana_backup` — Create SAP HANA database file backup • `sap.sap_operations.hana_restore` — Restore SAP HANA database backup • `sap.sap_operations.hana_update` — Role updates a SAP HANA system or instance on a given host. • `sap.sap_operations.sap_kernel_update` — Role replaces existing SAP kernel with kernel provided in SAP CAR files. • `sap.sap_operations.system` — Manage SAP system • `sap.sap_operations.pcs_status_info` — Get pacemaker status information • `sap.sap_operations.hana_system_replication_info` — Get info about SAP HANA system replication configuration • `avantra.core.workflow_execution` — execute Avantra workflows
Notes	• The system build is in Install SAP HANA and S/4HANA. • Use Shut down and start up a multi-tier application when SAP is one part of a larger stack. • Take care with restores: always require an explicit approval.

Use Case: Shut down and start up a multi-tier application

Description	Maintenance windows, data centre moves and disaster recovery tests need an application to be stopped and started in the right order: web tier first, then application servers, then databases, and the reverse at start-up. A workflow encodes that order and checks health between the steps.
Collection	`ansible.controller` (Certified), `redhat.runtimes_common` (Certified)

Key content	• `ansible.controller.workflow_job_template` — create, update, or destroy Automation Platform Controller workflow job templates. • `ansible.controller.workflow_job_template_node` — create, update, or destroy Automation Platform Controller workflow job template nodes. • `ansible.controller.workflow_launch` — Run a workflow in Automation Platform Controller • `ansible.controller.workflow_approval` — Approve an approval node in a workflow job. • `ansible.controller.schedule` — create, update, or destroy Automation Platform Controller schedules. • `redhat.runtimes_common.tail_grep` — Tail a logfile until a regex matcher is found or a timeout triggers
Notes	• Patching and upgrade steps belong in the maintenance node: see Patch application nodes one at a time behind a load balancer. • Workflow mechanics are explained in Orchestrate approvals, surveys and notifications in workflows. • For SAP stacks combine this with Run SAP Day 2 operations.

Product use cases

Grouped from the modules of each certified or validated collection. Key content lists the components each use case supports, with the modules that manage them (create, update, delete) and query them (_info).

MariaDB `ansible.mariadb`

Certified Red Hat · version 6.0.2 · updated 2026-07-13 · 12 modules → 3 use cases

Use Case: Manage databases, users and access

Description	Add and remove databases, users and roles and manage password policies.
Collection	`ansible.mariadb` (Certified, Red Hat)
Key content	**Databases** `mariadb_db` **Users** `mariadb_user` **Roles** `mariadb_role` **Password policies** `mariadb_password_policy`

Use Case: Run queries and manage replication

Description	Run queries and manage replication and replication filters.
Collection	`ansible.mariadb` (Certified, Red Hat)
Key content	**Queries** `mariadb_query` **Replication** `mariadb_replication` **Replication filters** `mariadb_replication_filter`

Use Case: Tune and monitor servers

Description	Manage global variables, Performance Schema setup and slow query log settings, and gather server and binary log information.
Collection	`ansible.mariadb` (Certified, Red Hat)
Key content	**Global variables** `mariadb_variables` **Performance Schema** `mariadb_perf_schema` **Slow query log** `mariadb_slow_log` **Server information** `mariadb_info` **Binary logs** `mariadb_binlog_info`

MySQL and MariaDB `ansible.mysql`

Certified Red Hat · version 5.0.0 · updated 2026-05-11 · 19 modules → 3 use cases

Use Case: Manage databases, users and access

Description	Add and remove databases, users and roles, set password policies, resource groups and TLS settings.
Collection	`ansible.mysql` (Certified, Red Hat)
Key content	**Databases** `mysql_db` **Users** `mysql_user` **Roles** `mysql_role` **Password policies** `mysql_password_policy` **Resource groups** `mysql_resource_group`, `mysql_resource_group_info` **TLS settings** `mysql_tls`

Use Case: Run queries and manage replication and cloning

Description	Run queries, clone instances from a donor, configure replication and replication filters, and manage table partitions and tablespaces.
Collection	`ansible.mysql` (Certified, Red Hat)
Key content	**Queries** `mysql_query` **Instance cloning** `mysql_clone` **Replication** `mysql_replication` **Replication filters** `mysql_replication_filter` **Table partitions** `mysql_partition` **InnoDB tablespaces** `mysql_tablespace`, `mysql_tablespace_info`

Use Case: Tune and monitor servers

Description	Manage global variables, Performance Schema setup, slow query log settings, and gather server and binary log information.
Collection	`ansible.mysql` (Certified, Red Hat)

Key content	**Global variables** `mysql_variables` **Performance Schema** `mysql_perf_schema` **Slow query log** `mysql_slow_log` **Server information** `mysql_info` **Binary logs** `mysql_binlog_info`

Avantra `avantra.core`

Certified Avantra · version 25.3.3 · updated 2026-03-11 · 6 modules → 1 use cases

Use Case: Manage Avantra servers, SAP systems and workflows

Description	Authenticate to Avantra, manage servers and SAP systems, and run workflows.
Collection	`avantra.core` (Certified, Avantra)
Key content	**Authentication** `login` **Servers** `server`, `server_info` **SAP systems** `sapsystem`, `sapsystem_info` **Workflow execution** `workflow_execution`

Confluent Platform `confluent.platform`

Certified Confluent · version 8.3.2 · updated 2026-09-21 · 2 modules → 5 use cases

Use Case: Deploy Kafka brokers and controllers

Description	Install and configure Kafka brokers and KRaft controllers, including common prerequisites, variables, and the static-to-dynamic quorum migration.
Collection	`confluent.platform` (Certified, Confluent)
Key content	**Common prerequisites** role `common` **Shared variables** role `variables` **Kafka brokers** role `kafka_broker` **Kafka controllers** role `kafka_controller` **Host prerequisites** playbook `all` **Kafka broker status** playbook `kafka_broker` **Kafka controller playbook** playbook `kafka_controller` **KRaft quorum migration precheck** playbook `StaticToDynamicQuorumMigration` **KRaft dynamic quorum validation** playbook `validations.validate_dynamic_quorum_configs`

Use Case: Deploy Connect, Schema Registry, ksqlDB and REST services

Description	Set up Kafka Connect, Replicator, Schema Registry with exporter and importer, ksqlDB, REST Proxy and Control Center.
Collection	`confluent.platform` (Certified, Confluent)

Key content	**Kafka Connect clusters** role `kafka_connect` **Connect Replicator** role `kafka_connect_replicator` **Schema Registry** role `schema_registry` **Schema Exporter** role `schema_exporter` **Schema Importer** role `schema_importer` **ksqlDB clusters** role `ksql` **Kafka REST Proxy** role `kafka_rest` **Control Center** role `control_center_next_gen` **Kafka Connect status** playbook `kafka_connect` **Replicator status** playbook `kafka_connect_replicator` **Schema Registry provisioning** playbook `schema_registry` **ksqlDB status** playbook `ksql` **REST Proxy status** playbook `kafka_rest` **Control Center status** playbook `control_center_next_gen` **Schema Registry switchover to Confluent Cloud** playbook `primary_sr_switchover_cp_to_cc` **Schema Registry switchover validations** playbook `validations.primary_sr_switchover_validations` **Kafka connectors** `kafka_connectors`

Use Case: Secure Confluent Platform

Description	Configure TLS certificates and keys, Kerberos, and rootless installation.
Collection	`confluent.platform` (Certified, Confluent)
Key content	**TLS certificates and keys** role `ssl` **Kerberos configuration** role `kerberos` **Rootless bootstrap** playbook `rootless_bootstrap`

Use Case: Monitor, validate and collect diagnostics

Description	Validate hosts, run health checks, restart components, collect logs and support bundles, manage the USM agent and log4j2 policies, and retire bundled monitoring.
Collection	`confluent.platform` (Certified, Confluent)
Key content	**Host validation** playbook `validate_hosts` **Health checks** playbook `health_check` **Component restarts** playbook `restart` **Log collection** playbook `fetch_logs` **Support bundle setup** playbook `support_bundle` **Support bundle on failure** callback `support_bundle_on_failure` **USM agent** role `usm_agent` **USM agent playbook** playbook `usm_agent` **USM agent validation** playbook `validations.validate_usm_agent_configs` **Bundled Prometheus teardown** playbook `external_prometheus_teardown_bundled_monitoring` **log4j2 and log redaction** `update_log4j2`

Use Case: Generate configuration from Ansible input

Description	Use custom filters to turn Ansible variables into Confluent Platform configuration.
Collection	`confluent.platform` (Certified, Confluent)
Key content	**Configuration filters** filter `filters`

Red Hat OpenShift Virtualization `infra.middleware_ocpv`

Validated Red Hat · version 1.0.0 · updated 2024-02-26 · 0 modules → 2 use cases

Use Case: Deploy a lab on OpenShift Virtualization

Description	Install OpenShift Virtualization, provision the environment, deploy the collection content and configure Ansible Automation Platform.
Collection	`infra.middleware_ocpv` (Validated, Red Hat)
Key content	**OpenShift Virtualization installation** role `ocpv_install` **Collection deployment** role `deploy_collection` **AAP configuration** role `configure_aap` **Install OpenShift Virtualization** playbook `install_ocpv` **Provisioning** playbook `provision` **Deploy lab** playbook `deploy_lab`

Use Case: Discover virtual machines dynamically

Description	Discover VirtualMachine instances from Kubernetes.
Collection	`infra.middleware_ocpv` (Validated, Red Hat)
Key content	**VM discovery** role `k8s_discovery` **Dynamic VM discovery** playbook `k8s_discovery`

Microsoft SQL Server `microsoft.sql`

Certified Red Hat · version 2.5.2 · updated 2024-12-18 · 0 modules → 1 use cases

Use Case: Install and configure SQL Server

Description	Install and configure Microsoft SQL Server.
Collection	`microsoft.sql` (Certified, Red Hat)
Key content	**SQL Server** role `server`

Red Hat AMQ Broker (ActiveMQ Artemis) `redhat.amq_broker`

Certified Red Hat · version 2.3.6 · updated 2026-06-11 · 1 modules → 2 use cases

Use Case: Install and run ActiveMQ brokers

Description	Install, configure, cluster and uninstall ActiveMQ Artemis brokers and read their configuration as facts.
Collection	`redhat.amq_broker` (Certified, Red Hat)

Key content	**Broker installation** role `activemq` **Broker uninstallation** role `activemq_uninstall` **Broker configuration facts** `activemq_facts` **ActiveMQ Artemis** playbook `activemq` **Master/standby cluster** playbook `activemq_cluster`

Use Case: Prepare broker configuration data

Description	Merge lists by attribute, generate PBKDF2 password hashes and create security matches.
Collection	`redhat.amq_broker` (Certified, Red Hat)
Key content	**Security matches** filter `create_security_matches` **List merging** filter `lists_mergeby` **Password hashes** filter `pbkdf2_hmac`

Red Hat AMQ Streams (Apache Kafka) `redhat.amq_streams`

Certified Red Hat · version 1.0.3 · updated 2026-10-09 · 0 modules → 2 use cases

Use Case: Install AMQ Streams

Description	Install ZooKeeper-based or KRaft-mode Kafka brokers, Connect, Cruise Control and the exporter.
Collection	`redhat.amq_streams` (Certified, Red Hat)
Key content	**Common plays** role `amq_streams_common` **ZooKeeper** role `amq_streams_zookeeper` **KRaft-mode Kafka** role `amq_streams_kraft` **Brokers** role `amq_streams_broker` **Kafka Connect** role `amq_streams_connect` **Cruise Control** role `amq_streams_cruise_control` **Exporter** role `amq_streams_exporter` **AMQ Streams installation** playbook `playbook`

Use Case: Validate the installation

Description	Check that AMQ Streams was installed correctly.
Collection	`redhat.amq_streams` (Certified, Red Hat)
Key content	**Installation validation** playbook `validate`

Red Hat Data Grid `redhat.data_grid`

Certified Red Hat · version 1.3.4 · updated 2026-06-04 · 0 modules → 1 use cases

Use Case: Deploy Data Grid and manage caches

Description	Install and configure Infinispan or Data Grid servers and configure caches at runtime.
Collection	`redhat.data_grid` (Certified, Red Hat)
Key content	**Data Grid server** role `infinispan` **Data Grid playbook** playbook `infinispan` **Caches** role `infinispan_cache`

Red Hat JBoss EAP / WildFly `redhat.eap`

Certified Red Hat · version 1.6.0 · updated 2026-09-30 · 0 modules → 3 use cases

Use Case: Install and run the application server

Description	Install WildFly or JBoss EAP, register subscriptions, open firewall ports, run it as a systemd service, add JDBC drivers and uninstall it.
Collection	`redhat.eap` (Certified, Red Hat)
Key content	**Installation** role `wildfly_install` **Subscriptions** role `wildfly_subs` **Firewall** role `wildfly_firewalld` **systemd service** role `wildfly_systemd` **JDBC drivers** role `wildfly_driver` **Uninstallation** role `wildfly_uninstall` **EAP utilities** role `wildfly_utils` **Install and run as a service** playbook `playbook`

Use Case: Deploy applications and manage the server over time

Description	Deploy applications, snapshot and roll back configuration, and migrate servers.
Collection	`redhat.eap` (Certified, Red Hat)
Key content	**Application deployment** role `wildfly_app_deploy` **Configuration snapshot and rollback** role `wildfly_snapshot` **Migration** role `wildfly_migration`

Use Case: Validate the server

Description	Verify the server is properly installed.
Collection	`redhat.eap` (Certified, Red Hat)

Key content	**Validation** role `wildfly_validation` **Verification** playbook `validate`

Red Hat JBoss Core Services `redhat.jbcs`

Certified Red Hat · version 1.1.6 · updated 2026-06-16 · 0 modules → 1 use cases

Use Case: Install JBoss Core Services

Description	Install and configure JBoss Core Services.
Collection	`redhat.jbcs` (Certified, Red Hat)
Key content	**JBoss Core Services** role `jbcs`

Red Hat JBoss Web Server `redhat.jws`

Certified Red Hat · version 2.1.4 · updated 2026-06-04 · 0 modules → 1 use cases

Use Case: Install, configure and validate JBoss Web Server

Description	Install and configure Tomcat or JBoss Web Server and validate the deployment.
Collection	`redhat.jws` (Certified, Red Hat)
Key content	**Install and configure** role `jws` **Install and configure playbook** playbook `playbook` **Validation** role `jws_validation` **Validation playbook** playbook `validate`

Quarkus `redhat.quarkus`

Certified Red Hat · version 1.0.4 · updated 2026-06-04 · 0 modules → 1 use cases

Use Case: Build and deploy Quarkus applications

Description	Install and deploy a Quarkus application.
Collection	`redhat.quarkus` (Certified, Red Hat)
Key content	**Quarkus application** role `quarkus` **Build and deploy playbook** playbook `playbook`

Red Hat Customer Portal `redhat.redhat_csp_download`

Certified Red Hat · version 1.2.2 · updated 2022-05-17 · 1 modules → 1 use cases

Use Case: Download content from the Red Hat customer portal

Description	Download resources from the customer portal and install the dependencies the module needs.
Collection	`redhat.redhat_csp_download` (Certified, Red Hat)
Key content	**Portal downloads** `redhat_csp_download` **Module dependencies** role `redhat_csp_download`

Red Hat build of Keycloak `redhat.rhbk`

Certified Red Hat · version 3.0.2 · updated 2026-06-25 · 36 modules → 7 use cases

Use Case: Manage realms, keys and organizations

Description	Create and configure realms, organizations, realm keys, localization overrides and components, and create realms and clients with the realm role and playbooks.
Collection	`redhat.rhbk` (Certified, Red Hat)
Key content	**Realms** `keycloak_realm`, `keycloak_realm_info` **Realm keys** `keycloak_realm_key` **Realm key metadata** `keycloak_realm_keys_metadata_info` **Localization overrides** `keycloak_realm_localization` **Organizations** `keycloak_organization`, `keycloak_organization_info` **Components** `keycloak_component`, `keycloak_component_info` **Realm and client role** role `keycloak_realm` **Realm playbook** playbook `keycloak_realm` **Realm and client playbook** playbook `keycloak_realm_client`

Use Case: Manage clients and client scopes

Description	Create and configure clients, client templates and scopes, scope role mappings, and client secrets.
Collection	`redhat.rhbk` (Certified, Red Hat)
Key content	**Clients** `keycloak_client` **Client templates** `keycloak_clienttemplate` **Client scopes** `keycloak_client_scope` **Client scope types** `keycloak_client_scope_type` **Client scope role mappings** `keycloak_client_scope_rolemappings` **Client role scope** `keycloak_client_rolescope` **Client secrets** `keycloak_clientsecret_info` **Client secret regeneration** `keycloak_clientsecret_regenerate` **Client scope playbook** playbook `keycloak_client_scope`

Use Case: Configure fine-grained authorization

Description	Define client authorization scopes, custom policies and permissions.
Collection	`redhat.rhbk` (Certified, Red Hat)
Key content	**Authorization scopes** `keycloak_authz_authorization_scope` **Custom policies** `keycloak_authz_custom_policy` **Permissions** `keycloak_authz_permission`, `keycloak_authz_permission_info`

Use Case: Manage users, groups and roles

Description	Manage users, user profiles, groups and roles, assign realm, client and user role mappings, send required-action emails and list realm users.
Collection	`redhat.rhbk` (Certified, Red Hat)
Key content	**Users** `keycloak_user` **User profiles** `keycloak_userprofile` **Required-action emails** `keycloak_user_execute_actions_email` **Realm users** `keycloak_realm_users_info` **Groups** `keycloak_group` **Roles** `keycloak_role` **Realm role mappings** `keycloak_realm_rolemapping` **Client role mappings** `keycloak_client_rolemapping` **User role mappings** `keycloak_user_rolemapping`

Use Case: Configure authentication flows

Description	Configure authentication flows and required actions.
Collection	`redhat.rhbk` (Certified, Red Hat)
Key content	**Authentication** `keycloak_authentication` **Authentication (v2)** `keycloak_authentication_v2` **Authentication flows** `keycloak_authentication_flow` **Required actions** `keycloak_authentication_required_actions` **Authentication flow playbook** playbook `keycloak_authentication_flow`

Use Case: Federate identities

Description	Integrate external identity providers and user federation sources such as LDAP.
Collection	`redhat.rhbk` (Certified, Red Hat)
Key content	**Identity providers** `keycloak_identity_provider` **User federation** `keycloak_user_federation` **Federation playbook** playbook `keycloak_federation`

Use Case: Install and run the Keycloak server

Description	Install Keycloak or Red Hat Single Sign-On on hosts, including the Quarkus distribution with HTTPS or in development mode.
Collection	`redhat.rhbk` (Certified, Red Hat)
Key content	**Keycloak server role** role `keycloak` **Keycloak Quarkus role** role `keycloak_quarkus` **Keycloak hosts playbook** playbook `keycloak` **Red Hat SSO hosts playbook** playbook `rhsso` **Quarkus with HTTPS playbook** playbook `keycloak_quarkus` **Quarkus development playbook** playbook `keycloak_quarkus_dev`

Red Hat JBoss middleware runtimes `redhat.runtimes_common`

Certified Red Hat · version 1.2.5 · updated 2026-06-04 · 5 modules → 1 use cases

Use Case: Download artifacts and manage files for middleware runtimes

Description	Download Maven artifacts and Red Hat products, search products, edit XML, wait on log output and sort versions.
Collection	`redhat.runtimes_common` (Certified, Red Hat)
Key content	**Maven artifacts** `maven_artifact` **Product downloads** `product_download` **Product search** `product_search` **XML files** `xml` **Log file wait** `tail_grep` **Version sort filter** filter `version_sort`

SAP infrastructure on Red Hat `redhat.sap_infrastructure`

Certified Red Hat · version 1.3.1 · updated 2026-03-02 · 0 modules → 1 use cases

Use Case: Provision and prepare infrastructure for SAP

Description	Preconfigure hypervisor nodes, provision VMs on OpenShift Virtualization or AWS EC2, prepare and verify them and enable temporary virtual IPs for installation.
Collection	`redhat.sap_infrastructure` (Certified, Red Hat)

Key content	**Hypervisor node preconfiguration** role `sap_hypervisor_node_preconfigure` **VM provisioning** role `sap_vm_provision` **VM preconfiguration** role `sap_vm_preconfigure` **VM verification** role `sap_vm_verify` **Temporary virtual IP** role `sap_vm_temp_vip` **OpenShift Virtualization hypervisor preconfiguration** playbook `sample-sap-hypervisor-redhat-ocp-virt-preconfigure` **VM provisioning on OpenShift Virtualization** playbook `sample-sap-vm-provision-redhat-ocpv` **VM provisioning on AWS EC2** playbook `sample-sap-vm-provision-aws-ec2-vs`

SAP on Red Hat Enterprise Linux `redhat.sap_install`

Certified Red Hat · version 1.9.2 · updated 2026-05-28 · 0 modules → 5 use cases

Use Case: Prepare hosts for SAP

Description	Preconfigure RHEL for SAP general, HANA and NetWeaver workloads, set up storage and hosts entries, and detect installation media.
Collection	`redhat.sap_install` (Certified, Red Hat)
Key content	**General SAP preconfiguration** role `sap_general_preconfigure` **SAP HANA preconfiguration** role `sap_hana_preconfigure` **SAP NetWeaver preconfiguration** role `sap_netweaver_preconfigure` **SAP storage setup** role `sap_storage_setup` **/etc/hosts entries** role `sap_maintain_etc_hosts` **Installation media detection** role `sap_install_media_detect` **SAP Host Agent** role `sap_hostagent` **HANA preconfiguration sample** playbook `sample-sap-hana-preconfigure` **HANA preparation** playbook `sap_hana_preconfigure_exec` **Distributed S/4HANA infrastructure setup** playbook `sample-sap-storage-setup_sap_s4hana_distributed`

Use Case: Install SAP HANA and databases

Description	Install SAP HANA and Oracle Database for SAP systems.
Collection	`redhat.sap_install` (Certified, Red Hat)
Key content	**SAP HANA** role `sap_hana_install` **Oracle Database** role `sap_anydb_install_oracle` **HANA installation sample** playbook `sample-sap-hana-install`

Use Case: Install SAP applications with SWPM

Description	Install SAP systems with Software Provisioning Manager in default, advanced, template, inifile and interactive modes.
Collection	`redhat.sap_install` (Certified, Red Hat)

Key content	**SAP SWPM** role `sap_swpm` **SWPM default mode** playbook `sample-sap-swpm-default-mode` **SWPM default templates mode** playbook `sample-sap-swpm-default-templates-mode` **SWPM advanced mode** playbook `sample-sap-swpm-advanced-mode` **SWPM advanced templates mode** playbook `sample-sap-swpm-advanced-templates-mode` **SWPM inifile reuse mode** playbook `sample-sap-swpm-inifile-reuse-mode` **SWPM interactive modes** playbook `sample-sap-swpm-all-modes-interactive`

Use Case: Configure SAP high availability

Description	Set up Pacemaker clusters, HANA System Replication and Db2 HADR, and ASCS/ERS clusters.
Collection	`redhat.sap_install` (Certified, Red Hat)
Key content	**Pacemaker cluster** role `sap_ha_pacemaker_cluster` **HANA System Replication** role `sap_ha_install_hana_hsr` **IBM Db2 HADR** role `sap_ha_install_anydb_ibmdb2` **HANA 2-node cluster** playbook `sample-sap-ha-deployment-hana-2-node-cluster` **NetWeaver ASCS/ERS cluster** playbook `sample-sap-nwas-ascs-ers-2-node-cluster`

Use Case: Validate SAP identifiers

Description	Check that SAP system IDs, instance numbers and hostnames are valid.
Collection	`redhat.sap_install` (Certified, Red Hat)
Key content	**SAP SID validation** filter `validate_sap_sid` **Instance number validation** filter `validate_sap_instance_nr` **ABAP hostname validation** filter `validate_sap_abap_platform_hostname` **Valid SAP SID** test `valid_sap_sid` **Valid instance number** test `valid_sap_instance_nr` **Valid ABAP hostname** test `valid_sap_abap_platform_hostname`

Red Hat Single Sign-On (Keycloak) `redhat.sso`

Certified Red Hat · version 2.0.2 · updated 2026-06-25 · 36 modules → 7 use cases

Use Case: Manage realms, keys and organizations

Description	Create and configure realms, organizations, realm keys, localization overrides and components, and create realms and clients with the realm role and playbooks.
Collection	`redhat.sso` (Certified, Red Hat)

Key content	**Realms** `keycloak_realm`, `keycloak_realm_info` **Realm keys** `keycloak_realm_key` **Realm key metadata** `keycloak_realm_keys_metadata_info` **Localization overrides** `keycloak_realm_localization` **Organizations** `keycloak_organization`, `keycloak_organization_info` **Components** `keycloak_component`, `keycloak_component_info` **Realm and client role** role `keycloak_realm` **Realm playbook** playbook `keycloak_realm` **Realm and client playbook** playbook `keycloak_realm_client`

Use Case: Manage clients and client scopes

Description	Create and configure clients, client templates and scopes, scope role mappings, and client secrets.
Collection	`redhat.sso` (Certified, Red Hat)
Key content	**Clients** `keycloak_client` **Client templates** `keycloak_clienttemplate` **Client scopes** `keycloak_client_scope` **Client scope types** `keycloak_client_scope_type` **Client scope role mappings** `keycloak_client_scope_rolemappings` **Client role scope** `keycloak_client_rolescope` **Client secrets** `keycloak_clientsecret_info` **Client secret regeneration** `keycloak_clientsecret_regenerate` **Client scope playbook** playbook `keycloak_client_scope`

Use Case: Configure fine-grained authorization

Description	Define client authorization scopes, custom policies and permissions.
Collection	`redhat.sso` (Certified, Red Hat)
Key content	**Authorization scopes** `keycloak_authz_authorization_scope` **Custom policies** `keycloak_authz_custom_policy` **Permissions** `keycloak_authz_permission`, `keycloak_authz_permission_info`

Use Case: Manage users, groups and roles

Description	Manage users, user profiles, groups and roles, assign realm, client and user role mappings, send required-action emails and list realm users.
Collection	`redhat.sso` (Certified, Red Hat)

Key content	**Users** `keycloak_user` **User profiles** `keycloak_userprofile` **Required-action emails** `keycloak_user_execute_actions_email` **Realm users** `keycloak_realm_users_info` **Groups** `keycloak_group` **Roles** `keycloak_role` **Realm role mappings** `keycloak_realm_rolemapping` **Client role mappings** `keycloak_client_rolemapping` **User role mappings** `keycloak_user_rolemapping`

Use Case: Configure authentication flows

Description	Configure authentication flows and required actions.
Collection	`redhat.sso` (Certified, Red Hat)
Key content	**Authentication** `keycloak_authentication` **Authentication (v2)** `keycloak_authentication_v2` **Authentication flows** `keycloak_authentication_flow` **Required actions** `keycloak_authentication_required_actions` **Authentication flow playbook** playbook `keycloak_authentication_flow`

Use Case: Federate identities

Description	Integrate external identity providers and user federation sources such as LDAP.
Collection	`redhat.sso` (Certified, Red Hat)
Key content	**Identity providers** `keycloak_identity_provider` **User federation** `keycloak_user_federation` **Federation playbook** playbook `keycloak_federation`

Use Case: Install and run the Keycloak server

Description	Install Keycloak or Red Hat Single Sign-On on hosts, including the Quarkus distribution with HTTPS or in development mode.
Collection	`redhat.sso` (Certified, Red Hat)
Key content	**Keycloak server role** role `keycloak` **Keycloak Quarkus role** role `keycloak_quarkus` **Keycloak hosts playbook** playbook `keycloak` **Red Hat SSO hosts playbook** playbook `rhsso` **Quarkus with HTTPS playbook** playbook `keycloak_quarkus` **Quarkus development playbook** playbook `keycloak_quarkus_dev`

SAP (HANA, ABAP, NetWeaver and BTP) `sap.sap_operations`

Certified Red Hat · version 2.2.0 · updated 2025-05-08 · 51 modules → 8 use cases

Use Case: Prepare hosts for SAP

Description	Prepare RHEL hosts and containers for SAP, register subscriptions, open firewall ports, distribute SSH keys and load the collection's variables.
Collection	`sap.sap_operations` (Certified, Red Hat)
Key content	**Collection variables** role `sap_operations` **RHEL host preparation** role `prepare` **Container preparation** role `prepare_container` **General SAP preconfiguration** role `general_preconfigure` **SAP HANA preconfiguration** role `hana_preconfigure` **Subscription registration** role `subscription_manager` **Firewall for SAP instances** role `firewall` **SSH key distribution** role `ssh_keys_distribute` **PowerShell** role `powershell` **Container detection** `is_container` **Azure instance metadata** `azure_imds`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Use Case: Download and install SAP software

Description	Download SAP software from the download center and baskets, unpack SAR archives, run SWPM and sapinst, install the SAP host agent and JVM, and replace the SAP kernel.
Collection	`sap.sap_operations` (Certified, Red Hat)
Key content	**Software download** role `download` **Download basket content** role `downloadbasket` **SWPM download service** role `swpm_download_service` **SWPM** role `swpm` **sapinst** role `sapinst` **sapinst certificate revocation list** role `sapinst_crl` **SAPCAR** role `sapcar` **SAR and ZIP unpacking** role `unpack` **SAP host agent from SAR** role `saphostagent_sar` **SAP JVM** role `sapjvm` **SAP kernel update** role `sap_kernel_update` **Download center authentication** `swdc_auth_info` **Download basket information** `me_downloadbasket_info` **Download item set information** `me_downloaditemset_info` **File information** `me_file_info` **Software aliases filter** filter `me_aliases` **ENR from alias filter** filter `me_enr_from_alias` **Valid software alias test** test `me_valid_alias` **SAP host agent install sample** playbook `sample_saphostagent_sar_e2e`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Use Case: Install and operate SAP HANA

Description	Install and update HANA instances, manage services, the user store and SSFS keys, back up and restore databases and read system replication status.
Collection	`sap.sap_operations` (Certified, Red Hat)
Key content	**HANA instance** role `hana` **HANA update** role `hana_update` **HANA sudoers** role `hana_sudoers` **SSFS key synchronization** role `ssfs_sync` **HANA services** `service` **HANA user store** `hdbuserstore`, `hdbuserstore_info` **HANA backups** `hana_backup` **HANA restores** `hana_restore` **HANA system replication information** `hana_system_replication_info` **HANA instance test** test `hana_instance` **HANA download and install sample** playbook `sample_hana_present_e2e`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Use Case: Build and check high-availability clusters

Description	Pre-configure and check Pacemaker clusters, authorize nodes, read cluster status and CIB, check SAP HA and failover configuration, manage enqueue locks and switch kernels in a rolling fashion.
Collection	`sap.sap_operations` (Certified, Red Hat)
Key content	**Cluster package preconfiguration** role `cluster_preconfigure` **Cluster configuration checks** role `pcs_config_checks` **Cluster node authorization** `pcs_auth` **Cluster status** `pcs_status_info` **Cluster information base** `pcs_cib_info` **Pacemaker capabilities** `pcs_capabilities_info` **Azure fence host list** `pcs_fence_azure_arm_list_info` **HA configuration check** `ha_check_config_info` **HA failover configuration check** `ha_check_failoverconfig_info` **HA failover configuration** `ha_get_failoverconfig_info` **Enqueue server information** `enq_admin_info` **Enqueue server lock management** `enq_admin_lock` **Enqueue server locks** `enq_admin_locks_info` **Rolling kernel switch** `rolling_kernel_switch` **Cluster property filter** filter `pcs_cluster_property_mapping` **Cluster nodes filter** filter `pcs_nodes_from_status` **Cluster resources filter** filter `pcs_resources` **Cluster resources from CIB filter** filter `pcs_resources_from_cib` **Cluster resources from status filter** filter `pcs_resources_from_status` **ASCS instance test** test `ascs_instance`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Use Case: Administer SAP systems, instances and licenses

Description	Manage SAP systems, list installed instances, read parameters and /proc data, install and inspect license keys, and run SAP quality checks.

Collection	`sap.sap_operations` (Certified, Red Hat)
Key content	**SAP systems** `system`, `system_info` **Installed SAP instances** `host_info` **Parameters** `parameter_info` **/proc file contents** `proc_info` **SAP quality checks** role `quality` **License keys** `saplikey` **Hardware key information** `saplikey_get_info` **License key information** `saplikey_show_info` **License content filter** filter `license_content` **Application instance test** test `app_instance` **Copyright notice** `show_c` **Warranty notice** `show_w`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Use Case: Manage ABAP systems and transports

Description	Read ABAP system details, search transport requests, and create and import transports.
Collection	`sap.sap_operations` (Certified, Red Hat)
Key content	**ABAP system information** `abap_system_info` **Transport request information** `abap_transport_info` **Transport request search** `abap_transports_info` **Transport request creation** `abap_transport_create` **Transport request import** `abap_transport_import`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Use Case: Manage SAP BTP and Cloud Foundry

Description	Read BTP global accounts and subaccounts, manage subaccounts, browse the Cloud Foundry marketplace, spaces and service plans, manage service instances and keys, and install the Cloud Foundry CLI and SAP Cloud Connector.
Collection	`sap.sap_operations` (Certified, Red Hat)

Key content	**BTP global account** `btp_global_account_info` **Global account assignments** `btp_global_account_assignments_info` **BTP subaccount** `btp_subaccount` **BTP subaccounts** `btp_subaccounts_info` **Cloud Foundry marketplace** `cf_marketplace_info` **Cloud Foundry spaces** `cf_spaces_info` **Service plans** `cf_service_plans_info` **Service instance** `cf_service_instance`, `cf_service_instance_info` **Service instances** `cf_service_instances_info` **Service instance key** `cf_service_instance_key` **Service instance keys** `cf_service_instance_keys_info` **Cloud Foundry CLI** role `cf` **SAP Cloud Connector** role `cloudconnector` **BTP test sample** playbook `sample_test_sap_btp`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Use Case: Validate and transform data in playbooks

Description	Check SAP system IDs, host names and FQDNs, evaluate truthiness, merge defaults, find mount paths and render inifile parameters.
Collection	`sap.sap_operations` (Certified, Red Hat)
Key content	**SAP system ID filter** filter `valid_sid` **Host name filter** filter `valid_hostname` **FQDN filter** filter `valid_fqdn` **All-true filter** filter `all` **Any-true filter** filter `any` **Default dictionary merge filter** filter `combine_default` **Inifile parameters filter** filter `inifile_params` **Mount path filter** filter `mount_path` **SAP system ID test** test `valid_sid` **Host name test** test `valid_hostname` **FQDN test** test `valid_fqdn` **All-true test** test `all` **Any-true test** test `any`
Notes	• Includes many filters and tests that help parse SAP, pcs cluster and license data inside playbooks.

Other certified and validated collections

Module-level content for these collections could not be read from a public source repository. Browse them on Automation Hub.

`edb.epas_postgresql`	A collection of modules for managing EDB Postgres Advanced Server (EPAS) (Certified, EnterpriseDB)