

some reference:

```
import pandas as pd
import numpy as np
from tqdm import tqdm

tqdm.pandas()

from sklearn.model_selection import train_test_split, StratifiedKFold
from sklearn import metrics

from keras.preprocessing.text import Tokenizer
from keras.preprocessing.sequence import pad_sequences
from keras.layers import *
from keras.models import *
from keras import initializers, regularizers, constraints, optimizers, layers
from keras.initializers import *
from keras.optimizers import *
import keras.backend as K
from keras.callbacks import *
import tensorflow as tf

import os
import time
import gc
import re

from unicode import unicodecode
```

```
del train, test
```

```

word_index = tokenizer.word_index
max_features = len(word_index)+1
def load_glove(word_index):
    EMBEDDING_FILE = '../input/embeddings/glove.840B.300d/glove.840B.300d.txt'
    def get_coefs(word,*arr): return word, np.asarray(arr, dtype='float32')
    embeddings_index = dict(get_coefs(*o.split(" ")) for o in open(EMBEDDING_FILE) if o.split(" ")[0] in word_index)

    all_embs = np.stack(embeddings_index.values())
    emb_mean,emb_std = all_embs.mean(), all_embs.std()
    embed_size = all_embs.shape[1]

    embedding_matrix = np.random.normal(emb_mean, emb_std, (max_features, embed_size))
    for word, i in word_index.items():
        if i >= max_features: continue
        embedding_vector = embeddings_index.get(word)
        if embedding_vector is not None: embedding_matrix[i] = embedding_vector

    return embedding_matrix

def load_fasttext(word_index):
    EMBEDDING_FILE = '../input/embeddings/wiki-news-300d-1M/wiki-news-300d-1M.vec'
    def get_coefs(word,*arr): return word, np.asarray(arr, dtype='float32')
    embeddings_index = dict(get_coefs(*o.split(" ")) for o in open(EMBEDDING_FILE) if len(o)>100 and o.
split(" ")[0] in word_index )

    all_embs = np.stack(embeddings_index.values())
    emb_mean,emb_std = all_embs.mean(), all_embs.std()
    embed_size = all_embs.shape[1]

    embedding_matrix = np.random.normal(emb_mean, emb_std, (max_features, embed_size))
    for word, i in word_index.items():
        if i >= max_features: continue
        embedding_vector = embeddings_index.get(word)
        if embedding_vector is not None: embedding_matrix[i] = embedding_vector

    return embedding_matrix

def load_para(word_index):
    EMBEDDING_FILE = '../input/embeddings/paragram_300_sl999/paragram_300_sl999.txt'
    def get_coefs(word,*arr): return word, np.asarray(arr, dtype='float32')
    embeddings_index = dict(get_coefs(*o.split(" ")) for o in open(EMBEDDING_FILE, encoding="utf8", err
ors='ignore') if len(o)>100 and o.split(" ")[0] in word_index)

    all_embs = np.stack(embeddings_index.values())
    emb_mean,emb_std = all_embs.mean(), all_embs.std()
    embed_size = all_embs.shape[1]

    embedding_matrix = np.random.normal(emb_mean, emb_std, (max_features, embed_size))
    for word, i in word_index.items():
        if i >= max_features: continue
        embedding_vector = embeddings_index.get(word)

```

```
def fl_smart(y_true, y_pred):
    args = np.argsort(y_pred)
    tp = y_true.sum()
    fs = (tp - np.cumsum(y_true[args[: -1]])) / np.arange(y_true.shape[0] + tp - 1, tp, -1)
    res_idx = np.argmax(fs)
    return 2 * fs[res_idx], (y_pred[args[res_idx]] + y_pred[args[res_idx + 1]]) / 2
```

```
f1, threshold = f1_smart(np.squeeze(Y_val), np.s
print('Optimal F1: {:.4f} at threshold: {:.4f}'.f
bestscore.append(threshold)
```