
Sage FAQ

Release 6.3

The Sage Development Team

August 11, 2014

CONTENTS

1	FAQ: General	3
1.1	Why does this project exist?	3
1.2	What does “Sage” mean and how do you pronounce it?	3
1.3	Who is behind this project?	3
1.4	Why is Sage free/open source?	4
1.5	Why did you write Sage from scratch, instead of using other existing software and/or libraries?	5
1.6	Who uses Sage?	5
1.7	How do I get help?	6
1.8	Wouldn’t it be way better if Sage did not ship as a gigantic bundle?	6
1.9	With so many bugs in Sage and hundreds of open tickets, why don’t you produce a stabilization release?	7
1.10	How can I download the Sage documentation to read it offline?	7
2	FAQ: Using Sage	9
2.1	How do I get started?	9
2.2	What are Sage’s prerequisites?	9
2.3	How to get Sage’s Python to recognize my system’s Tcl/Tk install?	10
2.4	How do I import Sage into a Python script?	10
2.5	How can I reload a Python script in a Sage session?	10
2.6	Can I use Sage with Python 3.x?	11
2.7	I’m seeing an error about “Permission denied” on a file called “sage-flags.txt”.	11
2.8	I downloaded a Sage binary and it crashes on startup with “Illegal instruction”. What can I do?	11
2.9	I used Debian/Ubuntu to install Sage 3.0.5 and that version is giving lots of errors. What can I do?	12
2.10	Should I use the official version or development version?	12
2.11	Is Sage difficult to learn?	12
2.12	Can I do X in Sage?	12
2.13	What exactly does Sage do when I type “0.6**2”?	13
2.14	Why is Sage’s command history different from Magma’s?	13
2.15	I have type issues using SciPy, cvxopt or NumPy from Sage.	13
2.16	How do I save an object so I don’t have to compute it each time I open a worksheet?	14
2.17	I get an error from jsMath or the math symbols don’t look right when displaying in the notebook.	14
2.18	I created the file SAGE_ROOT/devel/sage/sage/calculus/stokes.py, and have changed my mind and want to completely delete it from Sage, but it keeps coming back (i.e. it is still importable) when I type “sage -br”. What do I do?	14
2.19	Does Sage contain a function similar to Mathematica’s ToCharacterCode[]?	15
2.20	Can I make Sage automatically execute commands on startup?	15
2.21	My Sage upgrade failed with missing gmp symbols on OSX 10.4. What can I do?	15
2.22	When I compile Sage my computer beeps and shuts down or hangs.	15
2.23	When I run doctests on Mac OS X I see the messages with “malloc”, but in the end Sage reports that everything went fine.	16

2.24	Sage 2.9 and higher fails compiling ATLAS on Linux. How can I fix this?	17
2.25	Sage fails with the error message “restore segment prot after reloc: Permission denied”. What is wrong?	17
2.26	When I start Sage, SELinux complains that “/path/to/libpari-gmp.so.2” requires text-relocation. How can I fix it?	17
2.27	Upgrading Sage went fine, but now the banner still shows the old version. How can I fix this?	17
2.28	How do I run sage in daemon mode, i.e. as a service?	17
2.29	I am using Mac OS X. Where do I put the jsMath “font” directory to eliminate the red box?	18
2.30	The show command for plotting 3-D objects does not work.	18
2.31	May I use Sage tools in a commercial environment?	18
2.32	I want to write some Cython code that uses finite field arithmetic but “cimport sage.rings.finite_field_givaro” fails. What can I do?	18
2.33	I’m getting weird build failures on Mac OS X. How do I fix this?	19
2.34	How do I use the bitwise XOR operator in Sage?	19
2.35	When I try to use LaTeX in the notebook, it says it cannot find fullpage.sty.	20
2.36	With objects a and b and a function f, I accidentally typed $f(a) = b$ instead of $f(a) == b$. This returned a TypeError (as expected), but also deleted the object a. Why?	20
3	FAQ: Contributing to Sage	21
3.1	How can I get started contributing to Sage?	21
3.2	I’m not a programmer. Is there another way I can help out?	21
3.3	Where can I find resources on Python or Cython?	22
3.4	Are there any coding conventions I need to follow?	23
3.5	I submitted a bug fix to the trac server several weeks ago. Why are you ignoring my patch?	23
3.6	When and how might I remind the Sage community of a patch I care about?	23
3.7	I wrote some Sage code and I want it to be integrated into Sage. However, after renaming my file <code>a.sage</code> to <code>a.py</code> , I got syntax errors. Do I have to rewrite all my code in Python instead of Sage?	24
4	Indices and tables	25

This FAQ was compiled and is maintained by Minh Van Nguyen <nguyenminh2@gmail.com>.

This work is licensed under a [Creative Commons Attribution-Share Alike 3.0 License](https://creativecommons.org/licenses/by-sa/3.0/).

FAQ: GENERAL

1.1 Why does this project exist?

The stated mission of Sage is to be a viable free open source alternative to Magma, Maple, Mathematica, and Matlab. Sage's predecessors, known as HECKE and Manin, came about because William Stein needed to write them as part of his research in number theory. Started by William in 2005 during his time at Harvard University, Sage combines best-of-breed free open source mathematics software, packaging and unifying them through a common interface. Many researchers in number theory, including William himself, use this common interface to build upon and extend the functionalities of underlying packages for number theory research. Such software packages include [Givaro](#), [MPIR](#), [NTL](#), [Pari/GP](#), and many others too numerous to list here. Students, teachers, professors, researchers throughout the world use Sage because they require a comprehensive free open source mathematics package that offers symbolic and numerical computation. Most of the time, people are happy with what Sage has to offer. As is common throughout the free open source software (FOSS) world, many people often identify cases where Sage lacks certain mathematics functionalities that they require. And so they delve into the underlying source code that comprises Sage in order to extend it for their purposes, or expose functionalities of underlying packages shipped with Sage in order to use their favourite mathematics software packages from within Sage. The [Sage-Combinat](#) team is comprised of researchers in algebraic combinatorics. The team's stated mission is to improve Sage as an extensible toolbox for computer exploration in algebraic combinatorics, and foster code sharing between researchers in this area. For detailed information about why Sage exists, see William's personal [mathematics software biography](#).

1.2 What does “Sage” mean and how do you pronounce it?

In the first few years of Sage's existence, the project was called “SAGE”. This acronym stood for “Software for Algebra and Geometry Experimentation”. Starting around 2007 and early 2008, the name “Sage” was widely adopted. Think of “Sage” as a name for a free open source mathematics software project, just as “Python” is a name for a free open source general purpose programming language. Whenever possible, please use the name “Sage” instead of “SAGE” to avoid confusing the Sage project with a computer project called [SAGE](#). You pronounce “Sage” similar to how you would pronounce “sage” which refers to a wise person, or “sage” which refers to a plant. Some people pronounce “Sage” as “sarge”, similar to how you would pronounce [Debian Sarge](#). However you pronounce “Sage”, please do not confuse the Sage project with an accounting software by the same name.

1.3 Who is behind this project?

Sage is a volunteer based project. Its success is due to the voluntary effort of a large international team of students, teachers, professors, researchers, software engineers, and people working in diverse areas of mathematics, science, engineering, software development, and all levels of education. The development of Sage has benefited from the financial support of numerous institutions, and the previous and ongoing work of many authors of included components.

A list of direct contributors can be found on the [Sage Development Map](#) and the history of changes can be found in the high-level [changelog](#). Refer to the [acknowledgment page](#) of the Sage website for an up-to-date list of financial and infrastructure supporters, mirror network hosting providers, and indirect contributors.

1.4 Why is Sage free/open source?

A standard rule in the mathematics community is that everything is laid open for inspection. The Sage project believes that not doing the same for mathematics software is at best a gesture of impoliteness and rudeness, and at worst a violation against standard scientific practices. An underlying philosophical principle of Sage is to apply the system of open exchange and peer review that characterizes scientific communication to the development of mathematics software. Neither the Sage project nor the Sage Development Team make any claims to being the original proponents of this principle. The development model of Sage is largely inspired by the free software movement as spearheaded by the [Free Software Foundation](#), and by the open source movement. One source of inspiration from within the mathematics community is Joachim Neubüser as expressed in the paper

- J. Neubüser. An invitation to computational group theory. In C. M. Campbell, T. C. Hurley, E. F. Robertson, S. J. Tobin, and J. J. Ward, editors, *Groups '93 Galway/St. Andrews, Volume 2*, volume 212 of London Mathematical Society Lecture Note Series, pages 457–475. Cambridge University Press, 1995.

and in particular the following quotation from his paper:

You can read Sylow's Theorem and its proof in Huppert's book in the library without even buying the book and then you can use Sylow's Theorem for the rest of your life free of charge, but...for many computer algebra systems license fees have to be paid regularly for the total time of their use. In order to protect what you pay for, you do not get the source, but only an executable, i.e. a black box. You can press buttons and you get answers in the same way as you get the bright pictures from your television set but you cannot control how they were made in either case.

With this situation two of the most basic rules of conduct in mathematics are violated: In mathematics information is passed on free of charge and everything is laid open for checking. Not applying these rules to computer algebra systems that are made for mathematical research...means moving in a most undesirable direction. Most important: Can we expect somebody to believe a result of a program that he is not allowed to see? Moreover: Do we really want to charge colleagues in Moldava several years of their salary for a computer algebra system?

Similar sentiments were also expressed by Andrei Okounkov as can be found in

- V. Muñoz and U. Persson. Interviews with three Fields medalists. *Notices of the American Mathematical Society*, 54(3):405–410, 2007.

in particular the following quotation:

Computers are no more a threat to mathematicians than food processors are a threat to cooks. As mathematics gets more and more complex while the pace of our lives accelerates, we must delegate as much as we can to machines. And I mean both numeric and symbolic work. Some people can manage without dishwashers, but I think proofs come out a lot cleaner when routine work is automated.

This brings up many issues. I am not an expert, but I think we need a symbolic standard to make computer manipulations easier to document and verify. And with all due respect to the free market, perhaps we should not be dependent on commercial software here. An open-source project could, perhaps, find better answers to the obvious problems such as availability, bugs, backward compatibility, platform independence, standard libraries, etc. One can learn from the success of TeX and more specialized software like Macaulay2. I do hope that funding agencies are looking into this.

1.5 Why did you write Sage from scratch, instead of using other existing software and/or libraries?

Sage was not written from scratch. Most of its underlying mathematics functionalities are made possible through FOSS projects such as

- [ATLAS](#) — Automatically Tuned Linear Algebra Software.
- [BLAS](#) — Basic Linear Algebra Subprograms.
- [FLINT](#) — C library for doing number theory.
- [GAP](#) — a system for computational discrete algebra, with particular emphasis on computational group theory.
- [Maxima](#) — system for symbolic and numerical computation.
- [mpmath](#) — a pure-Python library for multiprecision floating-point arithmetic.
- [NumPy](#) — numerical linear algebra and other numerical computing capabilities for Python.
- [Pari/GP](#) — a computer algebra system for fast computations in number theory.
- [Pynac](#) — a modified version of GiNaC that replaces the dependency on CLN by Python.
- [R](#) — a language and environment for statistical computing and graphics.
- And many more too numerous to list here.

An up-to-date list can be found on the page for the [standard packages repository](#). The principle programming languages of Sage are [Python](#) and [Cython](#). Python is the primary programming and interfacing language, while Cython is the primary language for optimizing critical functionalities and interfacing with C libraries and C extensions for Python. Sage integrates over 90 FOSS packages into a common interface. On top of these packages is the Sage library, which consists of over 700,000 lines of new Python and Cython code. See [ohloh.net](#) for source code analysis of the latest stable Sage release.

1.6 Who uses Sage?

The following is an incomplete list of institutions and projects that use Sage. If any institution or project is missing, please let us know by reporting to the [sage-devel](#) mailing list.

1. [California Institute of Technology](#), Pasadena, California, USA
2. [California Polytechnic State University](#), San Luis Obispo, CA, USA
3. [Chang Gung University](#), Taiwan
4. [Chapman University](#), Orange, CA, USA

5. [Clemson University](#), Clemson, South Carolina, USA
6. [Drake University](#), Des Moines, IA, USA
7. [FEMhub](#), an open source distribution of scientific computing code enhanced with a unified Python interface. The FEMhub Notebook is based on the Sage Notebook.
8. [Gordon College](#), Wenham, MA, USA
9. [Korea Advanced Institute of Science and Technology](#), Daejeon, Korea
10. [Mendel University in Brno](#), Czech Republic
11. [Reykjavik University](#), Iceland
12. [Universidad Autónoma de Madrid](#), Spain
13. [Universidad de la República](#), Montevideo, Uruguay
14. [Universitat Politècnica de Catalunya](#), Barcelona, Catalonia, Spain
15. [Université Claude Bernard Lyon 1](#), France
16. [Université de Provence](#), Marseille, France
17. [Universiteit Leiden](#), The Netherlands
18. [University of Canterbury](#), Christchurch, New Zealand
19. [University of Minnesota Duluth](#), Duluth, MN, USA
20. [University of Nevada, Reno](#), Reno, NV, USA
21. [University of Puget Sound](#), Tacoma, WA, USA
22. [University of Washington](#), Seattle, Washington, USA
23. [University of Wisconsin, Oshkosh](#), Oshkosh, WI, USA
24. [US Naval Academy](#), Annapolis, Maryland, USA

1.7 How do I get help?

Sage has two very active email lists:

- `sage-devel`: <http://groups.google.com/group/sage-devel>
- `sage-support`: <http://groups.google.com/group/sage-support>

There is also a very active IRC channels: `#sage-devel` on freenode. Many developers also actively blog and also post other Sage-related tutorials and talks. See <http://www.sagemath.org/help.html> for a listing of these resources.

1.8 Wouldn't it be way better if Sage did not ship as a gigantic bundle?

This topic has been discussed over and over again. So before you resume the discussion, ensure you have read and understood the arguments below. Sage is a distribution of over 90 FOSS packages for symbolic, numerical, and scientific computation. In general, the combinatorial explosion of configurations to debug is way too large. It is next to impossible to find any Linux distribution (e.g. Arch, CentOS, Debian, Fedora, Gentoo, Mandriva, Ubuntu) where the version numbers of packages that Sage depends on even remotely match.

The majority of people who contribute to Sage do so in their free time. These are people who hold day jobs that are not directly related to computer programming or software development. It is next to impossible for anyone to track down the correct versions of packages, configure and compile them on Linux, Mac OS X, Solaris, or Windows, just so that they could start using Sage or start working on their first contribution to Sage. While the Sage project aims to be useful to as wide an audience as possible, we believe that Sage first needs to be as easy as possible to install by anyone with any level of computer experience. If you want to help Sage realize this goal, please email the [sage-devel](#) mailing list.

1.9 With so many bugs in Sage and hundreds of open tickets, why don't you produce a stabilization release?

Any software package contains bug. With something as complex as Sage, neither the Sage community nor the Sage Development Team make any claims that Sage is free of bugs. To do so would be an act of dishonesty.

A Sage release cycle usually lasts for about 3 to 4 weeks. Each release cycle is usually chaired by a single release manager who looks after the Sage merge tree for the duration of the release cycle. During that time, the release manager often needs to devote the equivalent of full-time work to quality management and actively interacts with an international community of Sage users, developers, and potential contributors. There have been a number of cases where two Sage contributors paired up to be the release managers for a Sage release cycle. However, it is often the case that few people have the equivalent of 3 weeks' worth of free time to devote to release management. If you want to help out with release management, please subscribe to the [sage-release](#) mailing list.

Since the beginning of the Sage project, Sage contributors have tried to listen and think about what would increase the chances that serious potential contributors would actually contribute. What encourages one contributor can discourage another, so tradeoffs need to be made. To decide that a stabilization release would merge patches with bug fixes, and only fix bugs, would likely discourage someone from contributing when they have been told in advance that their positively reviewed patches will not be merged. The Sage community believes in the principle of "release early, release often". How the Sage project is organized and run differ greatly from that of a commercial software company. Contributors are all volunteers and this changes the dynamic of the project dramatically from what it would be if Sage were a commercial development effort with all developers being full-time employees.

1.10 How can I download the Sage documentation to read it offline?

To download the Sage standard documentation in HTML or PDF formats, visit the [Help and Support](#) page on the Sage website. Each release of Sage comes with the full documentation that makes up the Sage standard documentation. If you have downloaded a binary Sage release, the HTML version of the corresponding documentation comes pre-built and can be found under the directory `SAGE_ROOT/devel/sage-main/doc/output/html/`. During the compilation of Sage from source, the HTML version of the documentation is also built in the process. To build the HTML version of the documentation, issue the following command from `SAGE_ROOT`:

```
$ ./sage -docbuild --no-pdf-links all html
```

Building the PDF version requires that your system has a working LaTeX installation. To build the PDF version of the documentation, issue the following command from `SAGE_ROOT`:

```
$ ./sage -docbuild all pdf
```

For more command line options, refer to the output of any of the following commands:

```
$ ./sage -help
$ ./sage -advanced
```


FAQ: USING SAGE

2.1 How do I get started?

You can try out Sage without downloading anything. Go to <http://www.sagenb.org> and set up a free account. If you log in, you will be working on a free Sage notebook server that will work identically to the one you get with Sage. To download a pre-built binary Sage distribution, visit the page <http://www.sagemath.org/download.html> and click on the link for the binary for your operating system. The source code of Sage is also available for you to download and use. Go to <http://www.sagemath.org/download-source.html> to download the tar archive for any release of Sage. Previous releases of Sage are available at <http://www.sagemath.org/src-old>.

The Sage notebook runs within a web browser. You can run Sage in a browser that is not the system default. To do so, issue the following command

```
env SAGE_BROWSER=opera /usr/bin/sage -notebook
```

either from the command prompt or as a menu command for Sage.

2.2 What are Sage's prerequisites?

Most of the dependencies of Sage are shipped with Sage itself. In most cases, you can download a pre-built binary and use that without installing any dependencies. If you use Windows, you will need to install [VirtualBox](http://www.virtualbox.org/wiki/Downloads), which can be downloaded from the page <http://www.virtualbox.org/wiki/Downloads>. After installing VirtualBox, you need to download a VirtualBox distribution of Sage available at <http://www.sagemath.org/download-windows.html>. Ensure you follow the instructions at that page. Now you can start the Sage virtual machine using the VirtualBox software, wait for the virtual machine to boot up, then type `notebook` at the prompt.

You can get the complete source for Sage to compile it on your own Linux or Mac OS X system. Sage lives in an isolated directory and does not interfere with your surrounding system. It ships together with everything necessary to develop Sage, the source code, all its dependencies and the complete changelog. On Linux systems like Debian/Ubuntu, you may have to install the `build-essential` package and the `m4` macro processor. Your system needs to have a working C compiler if you want to compile Sage from source. On Debian/Ubuntu, you can install these prerequisites as follows:

```
sudo apt-get install build-essential m4
```

If you have a multi-core system, you can opt for a parallel build of Sage. The command

```
export MAKE='make -j8'
```

will enable 8 threads for parts of the build that support parallelism. Change the number 8 as appropriate to suit the number of cores on your system.

2.3 How to get Sage's Python to recognize my system's Tcl/Tk install?

It may be that you have Tcl/Tk installed and that your system's Python recognizes it but Sage's Python does not. To fix that, install the tcl/tk development library. On Ubuntu, this is the command

```
sudo apt-get install tk8.5-dev
```

or something along that line. Next, reinstall Sage's Python:

```
sage -f python
```

This will pick up the tcl/tk library automatically. After successfully reinstalling Sage's Python, from within the Sage command line interface, issue these commands:

```
import _tkinter
import Tkinter
```

If they do not raise an `ImportError` then it worked.

2.4 How do I import Sage into a Python script?

You can import Sage as a library in a Python script. One caveat is that you need to run that Python script using the version of Python that is bundled with Sage; currently Python 2.6.x. To import Sage, put the following in your Python script:

```
from sage.all import *
```

When you want to run your script, you need to invoke Sage with the option `-python` which would run your script using the version of Python that comes with Sage. For example, if Sage is in your `PATH` variable then you can do this:

```
sage -python /path/to/my/script.py
```

Another way is to write a Sage script and run that script using Sage itself. A Sage script has the file extension `.sage` and is more or less a Python script but uses Sage-specific functions and commands. You can then run that Sage script like so:

```
sage /path/to/my/script.sage
```

This will take care of loading the necessary environment variables and default imports for you.

2.5 How can I reload a Python script in a Sage session?

You can load a Python script in a Sage session with the command **load**. For example, we could use Sage to import a file called `simple.py` with:

```
load("simple.py")
```

and repeat this command every time that we change the file `simple.py`. However, if we type:

```
attach("simple.py")
```

every change applied to the file `simple.py` will be automatically updated in Sage.

2.6 Can I use Sage with Python 3.x?

Currently, no. Sage depends on the [SciPy](#) stack of Python numerical and scientific packages. As of 2010, SciPy still uses Python 2.x. So until SciPy is ported to run with Python 3.x and [Cython](#) supports Python 3.x, Sage will continue to use Python 2.x.

2.7 I'm seeing an error about "Permission denied" on a file called "sage-flags.txt".

When sage is built from source, it keeps track of what special instructions your CPU supports (such as SSE2) and records these. This is so that if you try running the code on a different machine, which does not support these extra instructions, you get a sensible error message instead of a segfault or illegal instruction. Since this should be stored with Sage itself (as opposed to a user's `.sage` directory), it has to be created by someone with the appropriate permissions. So if you are seeing something like this

```
Traceback (most recent call last):
  File "/usr/local/sage-4.0.2/local/bin/sage-location", line 174, in <module>
    t, R = install_moved()
  File "/usr/local/sage-4.0.2/local/bin/sage-location", line 18, in install_moved
    write_flags_file()
  File "/usr/local/sage-4.0.2/local/bin/sage-location", line 82, in write_flags_file
    open(flags_file, 'w').write(get_flags_info())
IOError: [Errno 13] Permission denied:
  '/usr/local/sage-4.0.2/local/lib/sage-flags.txt'
```

it probably means that you compiled/installed Sage as one user, but have not run it to let it generate the `sage-flags.txt` file. Just run Sage one time as whatever user installed it and this problem should go away. This would also be easy to fix by having Sage run once as part of the install process; see [trac ticket #6375](#) for this fix.

2.8 I downloaded a Sage binary and it crashes on startup with "Illegal instruction". What can I do?

One way to fix this is to build Sage entirely from source. Another option is to fix your Sage installation by rebuilding MPIR and ATLAS by typing the following from the `SAGE_ROOT` of your Sage installation directory and wait about 15 to 20 minutes:

```
rm spkg/installed/mpir* spkg/installed/atlas*
make
```

It is possible that the binaries have been built for a newer architecture than what you have. Nobody has yet figured out how to build Sage in such a way that MPIR and ATLAS work on all hardware. This will eventually get fixed. Any help is appreciated.

2.9 I used Debian/Ubuntu to install Sage 3.0.5 and that version is giving lots of errors. What can I do?

The version of Sage, i.e. Sage version 3.0.5, that is available through `apt-get` in Debian and Ubuntu is very old. No one has yet found time to update the Debian/Ubuntu version of Sage. Any help is greatly appreciated. You should download the latest version of Sage from the [download page](#). If you would like to help with updating the Debian/Ubuntu version of Sage, please email the [sage-devel](#) mailing list.

2.10 Should I use the official version or development version?

You are encouraged to use the latest official version of Sage. Development versions are frequently announced on the [sage-devel](#) and [sage-release](#) mailing lists. An easy way of helping out with Sage development is to download the latest development release, compile it on your system, run all doctests, and report any compilation errors or doctest failures.

2.11 Is Sage difficult to learn?

Basic features of Sage should be as easy to learn as learning the basics of Python. Numerous tutorials are available online to help you learn Sage. To get the most out of Sage, you are encouraged to learn some features of the Python programming language. Here is an incomplete list of resources on Python. Further resources can be found by a web search.

- [Building Skills in Python](#) by Steven F. Lott
- [Dive into Python](#) by Mark Pilgrim
- [How to Think Like a Computer Scientist](#) by Jeffrey Elkner, Allen B. Downey, and Chris Meyers
- [Official Python Tutorial](#)
- [Python](#) home page and the [Python standard documentation](#)

2.12 Can I do X in Sage?

You are encouraged to use Sage's tab autocompletion. Just type a few characters, hit the tab key, and see if the command you want appears in the list of tab autocompletion. If you have a command called `mycmd`, then type `mycmd.` and hit the tab key to get a list of functionalities that are supported by that command. To read the documentation of `mycmd`, type `mycmd?` and press the enter key to read the documentation for that command. Similarly, type `mycmd??` and hit the enter key to get the source code of that command. You are also encouraged to search through the source code and documentation of the Sage library. To search through the source code of the Sage library, use the command `search_src("<search-keyword>")` where you should replace `<search-keyword>` with the keywords you are looking for. Also, you can search through the documentation of the Sage library using the command `search_doc("<search-keyword>")`.

2.13 What exactly does Sage do when I type “0.6**2”?

When you type “0.6**2” in Python, it returns something like 0.3599999999999999. But when you do the same in Sage it returns 0.3600000000000000. To understand why Python behaves as it does, see the [Python Tutorial](#), especially the chapter “Floating Point Arithmetic: Issues and Limitations”. What Sage does is “preparse” the input and transforms it like this:

```
sage: preparse("0.6**2")
"RealNumber('0.6')**Integer(2)"
```

So what is *actually* run is:

```
RealNumber('0.6')**Integer(2)
```

The Sage developers (in fact, Carl Witty) decided that Sage floating point numbers should by default print only the known correct decimal digits, when possible, thus skirting the problem that Python has. This decision has its pros and cons. Note that `RealNumber` and `Integer` are Sage specific, so you would not be able to just type the above into Python and expect it to work without first an import statement such as:

```
from sage.all import RealNumber, Integer, preparse
```

2.14 Why is Sage’s command history different from Magma’s?

Using Sage, you are missing a feature of the Magma command line interface. In Magma, if you enter a line found in history using up arrow key and then press down arrow key, then the next line in history is fetched. This feature allows you to fetch as many successive lines in history as you like. However, Sage does not have a similar feature. The IPython command prompt uses the readline library (via pyreadline), which evidently does not support this feature. Magma has its own custom “readline-like” library, which does support this feature. (Since so many people have requested this feature, if anybody can figure out how to implement it, then such an implementation would certainly be welcome!)

2.15 I have type issues using SciPy, cvxopt or NumPy from Sage.

You are using SciPy or cvxopt or NumPy from Sage and you get type errors, e.g.

```
TypeError: function not supported for these types, and can't coerce safely to supported types.
```

When you type in numbers into Sage, the pre-processor converts them to a base ring, which you can see by doing:

```
sage: preparse("stats.uniform(0,15).ppf([0.5,0.7])")
"stats.uniform(Integer(0), Integer(15)).ppf([RealNumber('0.5'), RealNumber('0.7')])"
```

Unfortunately, NumPy support of these advanced Sage types like `Integer` or `RealNumber` is not yet at 100%. As a solution, redefine `RealNumber` and/or `Integer` to change the behavior of the Sage preparser, so decimal literals are floats instead of Sage arbitrary precision real numbers, and integer literals are Python ints. For example:

```
sage: RealNumber = float; Integer = int
sage: from scipy import stats
sage: stats.ttest_ind(list([1,2,3,4,5]), list([2,3,4,5,.6]))
(array(0.07675295564533369), 0.94070490247380478)
sage: stats.uniform(0,15).ppf([0.5,0.7])
array([ 7.5, 10.5])
```

Alternatively, be explicit about data types, e.g.

```
sage: from scipy import stats
sage: stats.uniform(int(0),int(15)).ppf([float(0.5),float(0.7)])
array([ 7.5, 10.5])
```

As a third alternative, use the raw suffix:

```
sage: from scipy import stats
sage: stats.uniform(0r,15r).ppf([0.5r,0.7r])
array([ 7.5, 10.5])
```

You can also disable the preprocessor in your code via `preparse(False)`. You can may start IPython alone from the command line `sage -ipython` which does not pre-load anything Sage-specific. Or switching the Notebook language to “Python”.

2.16 How do I save an object so I don’t have to compute it each time I open a worksheet?

The `save` and `load` commands will save and load an object, respectively. In the notebook, the `DATA` variable is the location of the data storage area of the worksheet. To save the object `my_stuff` in a worksheet, you could do

```
save(my_stuff, DATA + "my_stuff")
```

and to reload it, you would just do

```
my_stuff = load(DATA + "my_stuff")
```

2.17 I get an error from jsMath or the math symbols don’t look right when displaying in the notebook.

If you see the error

It looks like jsMath failed to set up properly (error code -7). I will try to keep going, but it could

you have not installed the TeX fonts which help jsMath render beautiful typeset mathematics. To get the nice TeX display with jsMath, please download a set of fonts from here from <http://www.math.union.edu/~dpvc/jsMath/download/jsMath-fonts.html>. If you are on Linux/Unix, ignore the instructions on the page and just unzip the fonts into your `~/.fonts` directory. You can also install the `jsmath-fonts` package.

2.18 I created the file `SAGE_ROOT/devel/sage/sage/calculus/stokes.py`, and have changed my mind and want to completely delete it from Sage, but it keeps coming back (i.e. it is still importable) when I type “`sage -br`”. What do I do?

Delete both of the file

`SAGE_ROOT/devel/sage/build/sage/calculus/stokes.py`

and the file

`SAGE_ROOT/devel/sage/build/lib.*/sage/calculus/stokes.py`

2.19 Does Sage contain a function similar to Mathematica's `ToCharacterCode[]`?

You might want to convert ASCII characters such as “Big Mac” to ASCII numerals for further processing. In Sage and Python, you can use `ord`, e.g.

```
sage: map(ord, "abcde")
[97, 98, 99, 100, 101]
sage: map(ord, "Big Mac")
[66, 105, 103, 32, 77, 97, 99]
```

2.20 Can I make Sage automatically execute commands on startup?

Yes, just make a file `$HOME/.sage/init.sage` and it will be executed any time you start Sage. This assumes that the Sage environment variable `DOT_SAGE` points to the hidden directory `$HOME/.sage`, which by default is the case.

2.21 My Sage upgrade failed with missing gmp symbols on OSX 10.4. What can I do?

Moving a Sage install on Mac OS X 10.4 and then upgrading anything that is linked against NTL leads to link errors due to missing gmp symbols. The problem is the link mode with which the dynamic NTL is created. There is have a fix, but it still being verified that it really fixes the issue. Everything that is linked against NTL needs to be recompiled, i.e. singular and cremona at the moment. To add to the confusion: This is not an issue on Mac OS X 10.5. A fix for this issue went into Sage 2.8.15, so please report if you see this with a more current Sage release.

2.22 When I compile Sage my computer beeps and shuts down or hangs.

Compiling Sage is quite taxing on the CPU. The above behavior usually indicates that your computer has overheated. In many cases this can be fixed by cleaning the CPU fan and assuring proper ventilation of the system. Please ask your system administrator or a professional to do this in case you have never done this. Such hardware maintenance, if not performed by a skilled professional, you can potentially damage your system.

For Linux users, if you suspect that the compilation fails because of a resource issue, a fix might be to edit your `/etc/inittab` so that Linux boots into run level 3. The file `/etc/inittab` usually contains something similar to the following snippet:

```
# 0 - halt (Do NOT set initdefault to this)
# 1 - Single user mode
# 2 - Multiuser, without NFS (The same as 3, if you do not have
# networking)
# 3 - Full multiuser mode
# 4 - unused
# 5 - X11
# 6 - reboot (Do NOT set initdefault to this)
#
id:5:initdefault:
```

which directs your Linux distribution to boot into a graphical login screen. Comment out the line `id:5:initdefault:` and add the line `id:3:initdefault:`, so that you now have something like:

```
# 0 - halt (Do NOT set initdefault to this)
# 1 - Single user mode
# 2 - Multiuser, without NFS (The same as 3, if you do not have
# networking)
# 3 - Full multiuser mode
# 4 - unused
# 5 - X11
# 6 - reboot (Do NOT set initdefault to this)
#
# id:5:initdefault:
id:3:initdefault:
```

Now if you reboot your system, you will be greeted with a text based login screen. This allows you to log into your system with a text based session from within a virtual terminal. A text based session usually does not consume as much system resources as would be the case with a graphical session. Then build your Sage source distribution from within your text based session. You need to make sure that you can first restore your graphical session, before you attempt to log into a text based session.

2.23 When I run doctests on Mac OS X I see the messages with “malloc”, but in the end Sage reports that everything went fine.

The “malloc” messages you refer to might be something such as the following:

```
sage -t devel/sage-main/sage/libs/pari/gen.pyx
python(4563) malloc: *** vm_allocate(size=4096000000) failed (error code=3)
python(4563) malloc: *** error: can't allocate region
python(4563) malloc: *** set a breakpoint in szone_error to debug
```

The issue above is not a doctest failure. It is an error message printed by the system and it is exactly what one expects to see. In that particular doctest, we try to allocate a very large list in Pari that does not fit into physical memory (it is at least 100GB in size). So Mac OS X tells you that it could not allocate a chunk of memory roughly 4 GB in size, which is expected, if you are using Sage on a 32-bit version of OS X and you have compiled Sage in 32-bit mode or your binary Sage distribution is 32-bit.

2.24 Sage 2.9 and higher fails compiling ATLAS on Linux. How can I fix this?

The most likely cause is enabled power management. Disabling it should fix the problem. Depending on your flavor of distribution, this might either be possible with some nice GUI tool or not. On the command line do the following as root for each CPU you have:

```
/usr/bin/cpufreq-selector -g performance -c #number CPU
```

On Ubuntu, try disabling “Power Manager” via

```
System --> Preferences --> Sessions
```

under the “Startup Programs” or using `cpufreq-set` via the command line.

2.25 Sage fails with the error message “restore segment prot after reloc: Permission denied”. What is wrong?

The problem is related to SELinux. See this page for some tips to fix this: <http://www.itvis.com/services/techtip.asp?ttid=3092>. We are currently tracking this issue at [ticket #480](#).

2.26 When I start Sage, SELinux complains that “/path/to/libpari-gmp.so.2” requires text-relocation. How can I fix it?

The problem can be fixed by running the following command:

```
chcon -t textrel_shlib_t /path/to/libpari-gmp.so.2
```

2.27 Upgrading Sage went fine, but now the banner still shows the old version. How can I fix this?

The banner is stored and not computed at every new start of Sage. If it has not been updated, this should not prevent Sage to run correctly. Type `banner()` in a Sage session to check the real version. If you want the correct banner, you need to build Sage again by typing `make build` in a terminal.

2.28 How do I run sage in daemon mode, i.e. as a service?

We currently do not have a ready-to-go solution. There are several possibilities. Use `screen`, `nohup` or `disown`. We are tracking the issue at [ticket #381](#) so stay tuned.

2.29 I am using Mac OS X. Where do I put the jsMath “font” directory to eliminate the red box?

See <http://www.math.union.edu/~dpvc/jsMath/download/jsMath-fonts.html> where it says:

For Mac OS X users: download and unpack the archive, then drag the fonts to your Library/Fonts folder (or to the FontBook, or just double-click them and press the "install" button).

2.30 The show command for plotting 3-D objects does not work.

Since Sage 2.9.2, we have switched to using [Jmol](#), a Java applet, for 3-D plotting. There are several possibilities for the cause of the malfunction. You do not have Java installed at all or the Java installed is an older GNU based alternative Java implementation, which causes some yet to determine problem. A solution to both issues is to either install Sun's Java SDK or to update the GNU based Java implementation. As of January 2008 Debian's Java in testing works, but stable does have problems.

If you are running a brand new (as of April 2008) Ubuntu 8.04, they ship the Java Plugin by IcedTea. This is basically a good idea, but a bit too early since it is broken. Either wait for an update or uninstall the IcedTea Plugin and install the “SUN Java 6 Plugin”. Later, switch back to IcedTea, since it is based on OpenJDK 7 (or SUNs Java 7) which is the next Java version. You can check for the used plugin in Firefox 3 by typing “about:plugins” into the URL bar. Read more about this issue at [launchpad](#).

2.31 May I use Sage tools in a commercial environment?

Yes! Absolutely! Basically the *only* constraint is that if you make changes to Sage itself and redistribute this changed version of Sage publicly, then you must make these changes available to us so that we can put them into the standard version of Sage (if we want). Otherwise, you are free to use as many copies of Sage as you want completely for free to make money, etc. without paying any license fees at all.

2.32 I want to write some Cython code that uses finite field arithmetic but “`cimport sage.rings.finite_field_givaro`” fails. What can I do?

You need to give hints to Sage so that it uses C++ (both Givaro and NTL are C++ libraries), and it also needs the GMP and STDC C++ libraries. Here is a small example:

```
# These comments are hints to Sage/Pyrex about the compiler and
# libraries needed for the Givaro library:
#
#clang c++
#clib givaro gmpxx gmp m stdc++
cimport sage.rings.finite_field_givaro
# Construct a finite field of order 11.
cdef sage.rings.finite_field_givaro.FiniteField_givaro K
K = sage.rings.finite_field_givaro.FiniteField_givaro(11)
print "K is a", type(K)
print "K cardinality =", K.cardinality()
```

```
# Construct two values in the field:
cdef sage.rings.finite_field_givaro.FiniteField_givaroElement x
cdef sage.rings.finite_field_givaro.FiniteField_givaroElement y
x = K(3)
y = K(6)
print "x is a", type(x)
print "x =", x
print "y =", y
print "x has multiplicative order =", x.multiplicative_order()
print "y has multiplicative order =", y.multiplicative_order()
print "x*y =", x*y
# Show that x behaves like a finite field element:
for i in range(1, x.multiplicative_order() + 1):
    print i, x**i
assert x*(1/x) == K.one_element()
```

To find out more, type

```
sage.rings.finite_field_givaro.FiniteField_givaro.
```

at the Sage prompt and hit tab, then use ?? to get more information on each function. For example:

```
sage.rings.finite_field_givaro.FiniteField_givaro.one_element??
```

tells you more about the multiplicative unit element in the finite field.

2.33 I'm getting weird build failures on Mac OS X. How do I fix this?

Search the build log (install.log) to see if you are getting the following log message:

```
fork: Resource temporarily unavailable.
```

If so, try the following. Create (or edit) `/etc/launchd.conf` and include the following:

```
limit maxproc 512 2048
```

then reboot. See [this page](#) for more details.

2.34 How do I use the bitwise XOR operator in Sage?

The exclusive or operator in Sage is `^^`. This also works for the inplace operator `^^=`:

```
sage: 3^^2
1
sage: a = 2
sage: a ^^= 8
sage: a
10
```

If you define two variables and then evaluate as follows:

```
sage: a = 5; b = 8
sage: a.__xor__(b), 13
(13, 13)
```

You can also do

```
sage: (5).__xor__(8)
13
```

The parentheses are necessary so that Sage does not think you have a real number. There are several ways to define a function:

```
sage: xor = lambda x, y: x.__xor__(y)
sage: xor(3, 8)
11
```

Another option, which sneaks around the Sage preparser, is

```
sage: def xor(a, b):
...     return eval("%s^%s" % (a, b))
...
sage: xor(3, 8)
11
```

You can also turn off the Sage preparser with `preparser(False)`, then `^` will work just like in Python. You can later turn on the preparser with `preparser(True)`. That only works in command line Sage. In a notebook, switch to Python mode.

2.35 When I try to use LaTeX in the notebook, it says it cannot find `fullpage.sty`.

The general—but perhaps not very helpful—answer is that you need to install `fullpage.sty` into a directory searched by TeX. On Ubuntu (and probably many other Linux distributions), you should install the `texlive-latex-extra` package. If that is not available, try installing the `tetex-extra` package. If you are using Mac OS X, you will have to use whatever TeX distribution you use to get `fullpage.sty` (if you use MacTeX, it is likely already installed). If you are using the VirtualBox image on Windows, you will need to log into the VirtualBox image and install `texlive-latex-extra` there.

2.36 With objects `a` and `b` and a function `f`, I accidentally typed `f(a) = b` instead of `f(a) == b`. This returned a `TypeError` (as expected), but also deleted the object `a`. Why?

It is because of how functions are defined in Sage with the `f(x) = expr` notation using the preparser. Also notice that if you make this mistake inside of an `if` statement, you will get a `SyntaxError` before anything else goes wrong. So in this case, there is no problem.

FAQ: CONTRIBUTING TO SAGE

3.1 How can I get started contributing to Sage?

This is a quick guide for anyone who wants to contribute to Sage. It is intended especially for anyone who is new to computer programming. First, Sage’s main programming language is [Python](#). Some parts of Sage can be written in other languages, especially the components that do the heavy number crunching, but most native functionality is done using Python, including “glue code”. One of the good aspects of Python that Sage inherits is that working code is considered more valuable than just fast code. Fast code is valuable, but clean, readable code is important. In the mathematics community, inaccurate results are unacceptable. Correctness comes before optimization. In the following paper

- D. Knuth. Structured Programming with go to Statements. *ACM Journal Computing Surveys*, 6(4), 1974.

Don Knuth observes that: “We should forget about small efficiencies, say about 97% of the time: premature optimization is the root of all evil.”

If you do not know Python, you should start learning that language. A good place to start is the [Python Official Tutorial](#) and other documents in the [Python standard documentation](#). Another good place to take a look at is [Dive Into Python](#) by Mark Pilgrim, which may be pretty helpful on some specific topics like test-driven development. The book [Building Skills in Python](#) by Steven F. Lott is suitable for anyone who is already comfortable with programming.

In the meantime, you can grab your copy of the Sage source and familiarize yourself with the [git](#) version control system. Once you are comfortable with Python itself, which is pretty fast for basics, you can start using Sage. If you want, you can try to learn Python by using Sage, but that is not recommended because it is helpful to know what is pure Python and when Sage is doing its “magic”. There are many things that work in Python but not in Sage, and vice versa.

Then take a look at the [official development guide](#) for Sage. At a minimum, the first chapter in that guide is required reading for any Sage developer. Also pay special attention to the [trac guidelines](#). You can also join the [sage-devel](#) mailing list and hang around on the `#sage-devel` IRC channel on [freenode](#).

The best way to become familiar with the Sage development process is to choose a ticket from the [trac server](#) and review the proposed changes contained in that ticket. If you want to implement something, it is a good practice to discuss your ideas on the `sage-devel` mailing list first, so that other developers have a chance to comment on your ideas/proposals. They are pretty open to new ideas, too, like all mathematicians should be.

3.2 I’m not a programmer. Is there another way I can help out?

Yes. Like any free open source software project, there are numerous ways in which you could help out within the Sage community. And programming is one of many ways to contribute. If you can speak, read, and write in another (natural) language, there are many ways in which your contribution would be very valuable to the whole Sage community. Say

you know Italian. Then you can write a Sage tutorial in Italian, or help out with translating the official Sage tutorial to Italian. For the graphics designers or artistically creative, you can help out with improving the design of the Sage website. Or you can cast your critical artistic eyes over the Sage notebook interface and find out where it needs improvement.

Many people like writing technical tutorials. One of the joys of doing so is that you also learn something new in the process. At the same time, you communicate your knowledge to beginners, a skill which is useful in fields other than technical writing itself. A main point about technical writing is that you communicate a technical subject to beginners, so keep technical jargons to a minimum. Darrell Anderson has written some [tips on technical writing](#), which you are highly recommended to read. The above is a very short list. There are many, many more ways in which you can help out. Feel free to send an email to the [sage-devel](#) mailing list to ask about possible ways in which you could help out, or to suggest a project idea.

3.3 Where can I find resources on Python or Cython?

Here is an incomplete list of resources on Python and Cython. Further resources can be found by a web search.

General resources

- [Cython](#)
- [pep8](#)
- [py2depgraph](#)
- [pycallgraph](#)
- [PyChecker](#)
- [PyFlakes](#)
- [Pylint](#)
- [Python home page](#) and the [Python standard documentation](#)
- [Snakefood](#)
- [Sphinx](#)
- [XDot](#)

Tutorials and books

- [Building Skills in Python](#) by Steven F. Lott
- [Cython Tutorial](#) by Stefan Behnel, Robert W. Bradshaw, and Dag Sverre Seljebotn
- [Dive into Python](#) by Mark Pilgrim
- [Dive Into Python 3](#) by Mark Pilgrim
- [Fast Numerical Computations with Cython](#) by Dag Sverre Seljebotn
- [How to Think Like a Computer Scientist](#) by Jeffrey Elkner, Allen B. Downey, and Chris Meyers
- [Official Python Tutorial](#)

Articles and HOWTOs

- [decorator](#)
- [Functional Programming HOWTO](#) by A. M. Kuchling
- [Python Functional Programming for Mathematicians](#) by Minh Van Nguyen

- [Regular Expression HOWTO](#) by A. M. Kuchling
- [reStructuredText](#)
- [Static Code Analyzers for Python](#) by Doug Hellmann

3.4 Are there any coding conventions I need to follow?

You should follow the standard Python conventions as documented at [PEP 0008](#) and [PEP 0257](#). Also consult the Sage Developer's Guide, especially the chapter [Conventions for Coding in Sage](#).

3.5 I submitted a bug fix to the trac server several weeks ago. Why are you ignoring my patch?

We are not trying to ignore your patch. People who work on Sage do so in their free time. With hundreds of open tickets of varying degrees of impacts on the whole Sage community, people who work on tickets need to prioritize their time and work on those tickets that interest them. Sometimes you may be the only person who understands your patch. In that case, you are encouraged to take extra care to make it as easy as possible for anyone to review your patch. Here are some tips on making your patch easy to review:

- Have you clearly described the problem your patch is trying to solve?
- Have you provided any background information relevant to the problem your patch is trying to solve? Such information include links to online resources and any relevant papers, books and reference materials.
- Have you clearly described how your patch solves the problem under consideration?
- Have you clearly described how to test the changes in your patch?
- Have you listed any tickets that your patch depends on?
- If there are more than one patch, have you clearly stated the order in which those patches are to be applied?
- Does your patch [follow relevant conventions](#) as documented in the Developer's Guide?

If your patch stands no chance of being merged in the Sage source tree, we will not ignore your patch but simply close the relevant ticket with an explanation why we cannot include your changes.

3.6 When and how might I remind the Sage community of a patch I care about?

You are encouraged to take extra care in how you remind the Sage community of a patch you want to get merged into the Sage source tree. There might be an upcoming bug squash sprint or an upcoming Sage Days workshop that relates to your patch. Monitor the relevant Sage mailing lists and respond politely to any relevant email threads, with clear explanation on why your patch is relevant. Monitor the `#sage-devel` IRC channel, taking care to strategically time your reminders.

3.7 I wrote some Sage code and I want it to be integrated into Sage. However, after renaming my file a .sage to a .py, I got syntax errors. Do I have to rewrite all my code in Python instead of Sage?

The basic answer is yes, but rewriting is a big word for what is really needed. There is little work to do since Sage mostly follows Python syntax. The two main differences are handling of integer (see also the [afterword](#) for more on the sage preparer), and the necessity to import what you need.

- **Handling of integer:** You need to take care of the following changes:
 - Notation for exponentiation: In Python `**` means exponentiation and `^` means “xor”.
 - If you need to return an integer to the user, write `return Integer(1)` instead of `return 1`. In Python, `1` is a python `int`, and `Integer(1)` is a Sage/Gmp integer. In addition, `Integer` are much more powerful than `int`; for example, they know about being prime and factorization.
 - You should also notice that `2 / 3` no longer means `Integer(2) / Integer(3)` and returns `2/3`, but rather `int(2) / int(3)`, and therefore returns `0` due to integer division where it deregards any remainder. If you are dealing with `Integer` but you really need an integer division you can use `Integer(2) // Integer(3)`.
- **Importing stuff:** The second big change is the necessity to import everything what you need. More precisely, each time you use some Sage function, you need to import it at the beginning of the file. For example, if you want `PolynomialRing`, you need to write:

```
from sage.rings.polynomial.polynomial_ring_constructor import PolynomialRing
```

You can ask Sage where to find `PolynomialRing` using:

```
sage: PolynomialRing.__module__  
'sage.rings.polynomial.polynomial_ring_constructor'
```

This also corresponds to the path starting after `site-packages` given when you ask Sage for `PolynomialRing help`. For example, if you call `PolynomialRing?`, you get:

```
Type:      function  
[...]  
File:      /home/florent/src/Sage/sage/local/lib/python2.6/site-packages/sage/rings/polynomial/pol  
[...]
```

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*