

# Simple Types

**Concepts of Programming Languages**  
**Lecture 18**

# Outline

Have a high-level discussion of **type theory** in general

Introduce and analyze the **simply-typed lambda calculus** (STLC)

Demo an **implementation** of the STLC

# Recap

# Recall: The Environment Model

$$\langle \mathcal{E}, e \rangle \Downarrow v$$

# Recall: The Environment Model

$$\langle \mathcal{E}, e \rangle \Downarrow v$$

Idea. We keep track of their values in an *environment*

# Recall: The Environment Model

$$\langle \mathcal{E}, e \rangle \Downarrow v$$

Idea. We keep track of their values in an *environment*

And evaluate *relative* to the environment, *lazily* filling in variable values along the way

# Recall: The Environment Model

$$\langle \mathcal{E}, e \rangle \Downarrow v$$

Idea. We keep track of their values in an *environment*

And evaluate *relative* to the environment, *lazily* filling in variable values along the way

Now the **configurations** in our semantics have nonempty state

# Recall: Closures

$$(\mathcal{E}, e)$$



# Recall: Closures

$$(\mathcal{E}, e)$$

Definition. A **closure** is an expression together with an environment

# Recall: Closures

$$(\mathcal{E}, e)$$

Definition. A **closure** is an expression together with an environment

The environment *captures* bindings which a function needs

# Recall: Closures

$$(\mathcal{E}, e)$$

Definition. A **closure** is an expression together with an environment

The environment *captures* bindings which a function needs

Functions need to *remember* what the environment looks like in order to behave correctly according to lexical scoping

# Recall: Named Closures

$(\text{name}, \mathcal{E}, \lambda x. e)$

# Recall: Named Closures

$$(\text{name}, \mathcal{E}, \lambda x. e)$$

To implement recursion, we need to be able to *name* closures

# Recall: Named Closures

$$(\text{name}, \mathcal{E}, \lambda x. e)$$

To implement recursion, we need to be able to *name* closures

The idea. Named closures will put themselves into their environment *when they're called*

# Recall: Lambda Calculus<sup>++</sup> (Syntax)

```
<expr> ::=  $\lambda$ <var>.<expr>
          | <var>
          | <expr><expr>
          | let <var> = <expr>
            in <expr>
          | let rec <var> <var> = <expr>
            in <expr>
          | <num>
```

# Recall: Lambda Calculus<sup>++</sup> (Semantics)



# Recall: Lambda Calculus<sup>++</sup> (Semantics)

values and variables

$$\frac{}{\langle \mathcal{E}, \lambda x. e \rangle \Downarrow (\mathcal{E}, \lambda x. e)}$$

$$\frac{}{\langle \mathcal{E}, n \rangle \Downarrow n}$$

$$\frac{\mathcal{E}(x) \neq \perp}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)}$$

# Recall: Lambda Calculus<sup>++</sup> (Semantics)

values and variables

$$\frac{}{\langle \mathcal{E}, \lambda x. e \rangle \Downarrow (\mathcal{E}, \lambda x. e)} \quad \frac{}{\langle \mathcal{E}, n \rangle \Downarrow n} \quad \frac{\mathcal{E}(x) \neq \perp}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)}$$

application (unnamed closure)

$$\frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (\mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v}$$

# Recall: Lambda Calculus<sup>++</sup> (Semantics)

## values and variables

$$\frac{}{\langle \mathcal{E}, \lambda x. e \rangle \Downarrow (\mathcal{E}, \lambda x. e)} \quad \frac{}{\langle \mathcal{E}, n \rangle \Downarrow n} \quad \frac{\mathcal{E}(x) \neq \perp}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)}$$

## application (unnamed closure)

$$\frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (\mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v}$$

## application (named closure)

$$\frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (f, \mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[f \mapsto (f, \mathcal{E}', \lambda x. e)][x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v}$$

# Recall: Lambda Calculus<sup>++</sup> (Semantics)

## values and variables

$$\frac{}{\langle \mathcal{E}, \lambda x. e \rangle \Downarrow (\mathcal{E}, \lambda x. e)} \quad \frac{}{\langle \mathcal{E}, n \rangle \Downarrow n} \quad \frac{\mathcal{E}(x) \neq \perp}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)}$$

## application (unnamed closure)

$$\frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (\mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v}$$

## application (named closure)

$$\frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (f, \mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[f \mapsto (f, \mathcal{E}', \lambda x. e)][x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v}$$

## let expressions

$$\frac{\langle \mathcal{E}, e_1 \rangle \Downarrow v_1 \quad \langle \mathcal{E}[x \mapsto v_1], e_2 \rangle \Downarrow v_2}{\langle \mathcal{E}, \text{let } x = e_1 \text{ in } e_2 \rangle \Downarrow v_2}$$

$$\frac{\langle \mathcal{E}[f \mapsto (f, \mathcal{E}, \lambda x. e_1)], e_2 \rangle \Downarrow v_2}{\langle \mathcal{E}, \text{let rec } f x = e_1 \text{ in } e_2 \rangle \Downarrow v_2}$$

# Practice Problem

```
let x = 0 in
let g = fun y -> x + 1 in
let x = 1 in
let f = fun y -> g x in
let x = 2 in
f
```

*What (closure) does the following expression evaluate to? You don't need to give the derivation*

# Answer

```
let x = 0 in
let g = fun y -> x + 1 in
let x = 1 in
let f = fun y -> g x in
let x = 2 in
f
```

demo

# Type Theory



# What is a Type?

```
let f : int -> int = ...
```

# What is a Type?

```
let f : int -> int = ...
```

*Who knows...*

# What is a Type?

```
let f : int -> int = ...
```

*Who knows...*

A **type** is an *syntactic object* that we give to an expression which describes something about its behavior

# What is a Type?

```
let f : int -> int = ...
```

*Who knows...*

A **type** is an *syntactic object* that we give to an expression which describes something about its behavior

This description can be used to *restrict* the use of the expression *within* a program

# What is a Type?

```
let f : int -> int = ...
```

*Who knows...*

A **type** is an *syntactic object* that we give to an expression which describes something about its behavior

This description can be used to *restrict* the use of the expression *within* a program

**Types help us delineate "well-behaved" programs**

# Trade-offs

$$(\lambda x . xx)(\lambda x . xx)$$

lambda term called  $\Omega$

# Trade-offs

$$(\lambda x . xx)(\lambda x . xx)$$

lambda term called  $\Omega$

Types are *restrictive*. They tells us what we *can't* do in our programs

# Trade-offs

$$(\lambda x . xx)(\lambda x . xx)$$

lambda term called  $\Omega$

Types are *restrictive*. They tell us what we *can't* do in our programs

But types are *safe*. They make sure we don't do dumb things in our program



# Trade-offs

$$(\lambda x . xx)(\lambda x . xx)$$

lambda term called  $\Omega$

Types are *restrictive*. They tell us what we *can't* do in our programs

But types are *safe*. They make sure we don't do dumb things in our program

The goal is to balance:

# Trade-offs

$$(\lambda x . xx)(\lambda x . xx)$$

lambda term called  $\Omega$

Types are *restrictive*. They tell us what we *can't* do in our programs

But types are *safe*. They make sure we don't do dumb things in our program

The goal is to balance:

» Simplicity/Usability

# Trade-offs

$$(\lambda x . xx)(\lambda x . xx)$$

lambda term called  $\Omega$

Types are *restrictive*. They tell us what we *can't* do in our programs

But types are *safe*. They make sure we don't do dumb things in our program

The goal is to balance:

- » Simplicity/Usability
- » Expressivity

# Trade-offs

$$(\lambda x . xx)(\lambda x . xx)$$

lambda term called  $\Omega$

Types are *restrictive*. They tell us what we *can't* do in our programs

But types are *safe*. They make sure we don't do dumb things in our program

The goal is to balance:

- » Simplicity/Usability
- » Expressivity
- » Safety/Theoretical Guarantees

# OCaml

```
# let big_omega =  
    let little_omega x = x x in  
    little_omega little_omega;;
```

**Error:** This expression has type 'a -> 'b  
but an expression was expected of type 'a  
The type variable 'a occurs inside 'a -> 'b

# OCaml

```
# let big_omega =  
    let little_omega x = x x in  
    little_omega little_omega;;
```

**Error:** This expression has type 'a -> 'b  
but an expression was expected of type 'a  
The type variable 'a occurs inside 'a -> 'b

The type system of OCaml tells us when we're trying to define an ill-behaved program

# OCaml

```
# let big_omega =  
    let little_omega x = x x in  
    little_omega little_omega;;
```

**Error:** This expression has type 'a -> 'b  
but an expression was expected of type 'a  
The type variable 'a occurs inside 'a -> 'b

The type system of OCaml tells us when we're trying to define an ill-behaved program

But OCaml also has strong *type inference* and *polymorphism* to balance these benefits with better ergonomics (these are topics for mini-project 3)

# OCaml

```
# let big_omega =  
    let little_omega x = x x in  
    little_omega little_omega;;
```

**Error:** This expression has type 'a -> 'b  
but an expression was expected of type 'a  
The type variable 'a occurs inside 'a -> 'b

The type system of OCaml tells us when we're trying to define an ill-behaved program

But OCaml also has strong *type inference* and *polymorphism* to balance these benefits with better ergonomics (these are topics for mini-project 3)

**The more expressive, the more complex the the type system, designing programming languages is finding the balance that works for you**



# Recall: Typing Judgments

$$\Gamma \vdash e : \tau$$

This judgment reads:

*$e$  has type  $\tau$  in the context  $\Gamma$*

We say that  $e$  is **well-typed** if  $\cdot \vdash e : \tau$  for some type  $\tau$

# Recall: Typing Judgments

$$\Gamma \vdash e : \tau$$

This judgment reads:

*$e$  has type  $\tau$  in the context  $\Gamma$*

We say that  $e$  is **well-typed** if  $\cdot \vdash e : \tau$  for some type  $\tau$

**Most of what type theorists do is come up with rules for deriving typing judgments**

# Recall: Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : \tau$$
$$x ::= \text{vars}$$
$$\tau ::= \text{types}$$

# Recall: Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : \tau$$
$$x ::= \text{vars}$$
$$\tau ::= \text{types}$$

In Theory: A context is an inductively-defined syntactic object,  
just like a type or a expression

# Recall: Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : \tau$$
$$x ::= \text{vars}$$
$$\tau ::= \text{types}$$

In Theory: A context is an inductively-defined syntactic object, just like a type or a expression

In Practice: A context is a set (or ordered list, in some cases) of **variable declarations**

# Recall: Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : \tau$$
$$x ::= \text{vars}$$
$$\tau ::= \text{types}$$

In Theory: A context is an inductively-defined syntactic object, just like a type or a expression

In Practice: A context is a set (or ordered list, in some cases) of **variable declarations**

*(a variable declaration is a variable together with a type)*

# Recall: Inference Rules

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \dots \quad \Gamma \vdash e_k : \tau_k}{\Gamma \vdash e : \tau}$$

# Recall: Inference Rules

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \dots \quad \Gamma \vdash e_k : \tau_k}{\Gamma \vdash e : \tau}$$

**Inference rules** then tell us when we derive a new typing judgment from old typing judgments



# Recall: Inference Rules

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \dots \quad \Gamma \vdash e_k : \tau_k}{\Gamma \vdash e : \tau}$$

**Inference rules** then tell us when we derive a new typing judgment from old typing judgments

The questions we need to answer:

# Recall: Inference Rules

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \dots \quad \Gamma \vdash e_k : \tau_k}{\Gamma \vdash e : \tau}$$

**Inference rules** then tell us when we derive a new typing judgment from old typing judgments

The questions we need to answer:

» How do we know what rules to include?

# Recall: Inference Rules

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \dots \quad \Gamma \vdash e_k : \tau_k}{\Gamma \vdash e : \tau}$$

**Inference rules** then tell us when we derive a new typing judgment from old typing judgments

The questions we need to answer:

- » How do we know what rules to include?
- » How do we know if we've chosen *good* rules?

# Simply-Typed Lambda Calculus

# STLC Syntax

$\langle e \rangle ::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle$   
 $\quad \mid \text{fun } ( \langle v \rangle : \langle \text{ty} \rangle ) \rightarrow \langle e \rangle$   
 $\langle \text{ty} \rangle ::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle$   
 $\langle v \rangle ::= a \mid \dots \mid z$

# STLC Syntax

$\langle e \rangle ::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle$   
 $\quad \mid \text{fun } ( \langle v \rangle : \langle ty \rangle ) \rightarrow \langle e \rangle$   
 $\langle ty \rangle ::= \text{unit} \mid \langle ty \rangle \rightarrow \langle ty \rangle$   
 $\langle v \rangle ::= a \mid \dots \mid z$

The syntax is the same as that of the lambda calculus except:

# STLC Syntax

$$\begin{aligned} \langle e \rangle &::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle \\ &\quad \mid \text{fun } ( \langle v \rangle : \langle \text{ty} \rangle ) \rightarrow \langle e \rangle \\ \langle \text{ty} \rangle &::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle \\ \langle v \rangle &::= a \mid \dots \mid z \end{aligned}$$

The syntax is the same as that of the lambda calculus except:

» we include a unit expression

# STLC Syntax

$$\begin{aligned} \langle e \rangle &::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle \\ &\quad \mid \text{fun } ( \langle v \rangle : \langle \text{ty} \rangle ) \rightarrow \langle e \rangle \\ \langle \text{ty} \rangle &::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle \\ \langle v \rangle &::= a \mid \dots \mid z \end{aligned}$$

The syntax is the same as that of the lambda calculus except:

- » we include a unit expression
- » we have types, which annotate arguments



# STLC Syntax

$$\begin{aligned} \langle e \rangle &::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle \\ &\quad \mid \text{fun } ( \langle v \rangle : \langle \text{ty} \rangle ) \rightarrow \langle e \rangle \\ \langle \text{ty} \rangle &::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle \\ \langle v \rangle &::= a \mid \dots \mid z \end{aligned}$$

The syntax is the same as that of the lambda calculus except:

- » we include a unit expression
- » we have types, which annotate arguments

This is the first time that **types are a part of our syntax**

# Syntax

$$e ::= \bullet \mid x \mid \lambda x^\tau . e \mid ee$$

$$\tau ::= \top \mid \tau \rightarrow \tau$$

$$x ::= \textit{variables}$$

The syntax is the same as that of the lambda calculus except:

- » we include a unit expression
- » we have types, which annotate arguments

This is the first time that **types are a part of our syntax**

# STLC Typing

# STLC Typing

$$\frac{}{\Gamma \vdash \bullet : T} \text{unit}$$

# STLC Typing

$$\frac{}{\Gamma \vdash \bullet : \top} \text{unit}$$

$$\frac{(x : \tau) \in \Gamma}{\Gamma \vdash x : \tau} \text{variable}$$

# STLC Typing

$$\frac{}{\Gamma \vdash \bullet : \top} \text{unit}$$

$$\frac{(x : \tau) \in \Gamma}{\Gamma \vdash x : \tau} \text{variable}$$

$$\frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x^\tau . e : \tau \rightarrow \tau'} \text{abstraction}$$

# STLC Typing

$$\frac{}{\Gamma \vdash \bullet : \top} \text{unit}$$

$$\frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x^\tau . e : \tau \rightarrow \tau'} \text{abstraction}$$

$$\frac{(x : \tau) \in \Gamma}{\Gamma \vdash x : \tau} \text{variable}$$

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'} \text{application}$$

# STLC Typing

$$\frac{}{\Gamma \vdash \bullet : \top} \text{unit}$$

$$\frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x^\tau . e : \tau \rightarrow \tau'} \text{abstraction}$$

$$\frac{(x : \tau) \in \Gamma}{\Gamma \vdash x : \tau} \text{variable}$$

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'} \text{application}$$

These rules enforce that a function can only be applied if we *know* that it's a function



# Type Annotations?

$\langle e \rangle ::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle$   
                   $\mid \text{fun } \langle v \rangle \rightarrow \langle e \rangle$   
 $\langle \text{ty} \rangle ::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle$   
 $\langle v \rangle ::= a \mid \dots \mid z$

$$\frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x. e : \tau \rightarrow \tau'}$$

# Type Annotations?

$\langle e \rangle ::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle$   
                   $\mid \text{fun } \langle v \rangle \rightarrow \langle e \rangle$   
 $\langle \text{ty} \rangle ::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle$   
 $\langle v \rangle ::= a \mid \dots \mid z$

$$\frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x. e : \tau \rightarrow \tau'}$$

*Do we have to include the type annotation on function arguments?*

# Type Annotations?

$\langle e \rangle ::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle$   
                   $\mid \text{fun } \langle v \rangle \rightarrow \langle e \rangle$   
 $\langle \text{ty} \rangle ::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle$   
 $\langle v \rangle ::= a \mid \dots \mid z$

$$\frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x. e : \tau \rightarrow \tau'}$$

*Do we have to include the type annotation on function arguments?*

**No**, but it does change the way typing works

# Type Annotations?

$\langle e \rangle ::= () \mid \langle v \rangle \mid \langle e \rangle \langle e \rangle$   
                   $\mid \text{fun } \langle v \rangle \rightarrow \langle e \rangle$   
 $\langle \text{ty} \rangle ::= \text{unit} \mid \langle \text{ty} \rangle \rightarrow \langle \text{ty} \rangle$   
 $\langle v \rangle ::= a \mid \dots \mid z$

$$\frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x. e : \tau \rightarrow \tau'}$$

*Do we have to include the type annotation on function arguments?*

**No**, but it does change the way typing works

If we include annotations we're using **Church-style typing**. If we drop annotations, we're using **Curry-style typing**

# Aside: Church vs. Curry Typing

```
fun x -> x
```

```
fun (x : unit) -> x
```

# Aside: Church vs. Curry Typing

```
fun x -> x
```

```
fun (x : unit) -> x
```

*What is the type of the first expression? How about the second?*

# Aside: Church vs. Curry Typing

```
fun x -> x
```

```
fun (x : unit) -> x
```

*What is the type of the first expression? How about the second?*

In **Curry-style typing**, the type of an expression is *extrinsic*, the expression is just an expression in the lambda calculus

# Aside: Church vs. Curry Typing

```
fun x -> x
```

```
fun (x : unit) -> x
```

*What is the type of the first expression? How about the second?*

In **Curry-style typing**, the type of an expression is *extrinsic*, the expression is just an expression in the lambda calculus

In **Church-style typing**, it's *intrinsic*, built into the expression and the semantics



# Aside: Church vs. Curry Typing

```
fun x -> x
```

```
fun (x : unit) -> x
```

*What is the type of the first expression? How about the second?*

In **Curry-style typing**, the type of an expression is *extrinsic*, the expression is just an expression in the lambda calculus

In **Church-style typing**, it's *intrinsic*, built into the expression and the semantics

**Using Curry-style typing is not the same as having polymorphism**

# Uniqueness of Types

# Uniqueness of Types

**Lemma.** If  $\Gamma \vdash e : \tau_1$  and  $\Gamma \vdash e : \tau_2$  then  $\tau_1 = \tau_2$

# Uniqueness of Types

**Lemma.** If  $\Gamma \vdash e : \tau_1$  and  $\Gamma \vdash e : \tau_2$  then  $\tau_1 = \tau_2$

*Proof.* The rough idea is to do induction *on the derivations themselves* (whoa)

# Uniqueness of Types

**Lemma.** If  $\Gamma \vdash e : \tau_1$  and  $\Gamma \vdash e : \tau_2$  then  $\tau_1 = \tau_2$

*Proof.* The rough idea is to do induction *on the derivations themselves* (whoa)

In the simply typed lambda calculus with Church-style typing, every expression has a *unique type*

# Uniqueness of Types

**Lemma.** If  $\Gamma \vdash e : \tau_1$  and  $\Gamma \vdash e : \tau_2$  then  $\tau_1 = \tau_2$

*Proof.* The rough idea is to do induction *on the derivations themselves* (whoa)

In the simply typed lambda calculus with Church-style typing, every expression has a *unique type*

In particular, the function `type_of` is well-defined

# STLC Semantics (Review)

$$\begin{array}{c} \frac{}{\langle \mathcal{E}, \lambda x^\tau. e \rangle \Downarrow (\mathcal{E}, \lambda x. e)} \text{fun} \qquad \frac{}{\langle \mathcal{E}, \bullet \rangle \Downarrow \bullet} \text{unit} \qquad \frac{}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)} \text{variable} \\[1em] \frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (\mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v} \text{application} \end{array}$$

# STLC Semantics (Review)

$$\begin{array}{c} \frac{}{\langle \mathcal{E}, \lambda x^\tau . e \rangle \Downarrow (\mathcal{E}, \lambda x . e)} \text{ fun} \qquad \frac{}{\langle \mathcal{E}, \bullet \rangle \Downarrow \bullet} \text{ unit} \qquad \frac{}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)} \text{ variable} \\[2ex] \frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (\mathcal{E}', \lambda x . e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v} \text{ application} \end{array}$$

The semantics are identical



# STLC Semantics (Review)

$$\begin{array}{c} \frac{}{\langle \mathcal{E}, \lambda x^\tau. e \rangle \Downarrow (\mathcal{E}, \lambda x. e)} \text{ fun} \qquad \frac{}{\langle \mathcal{E}, \bullet \rangle \Downarrow \bullet} \text{ unit} \qquad \frac{}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)} \text{ variable} \\[2ex] \frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (\mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v} \text{ application} \end{array}$$

The semantics are identical

**This is part of the point.** Type-checking only determines *whether* we go on to evaluate the program (whether it makes sense to)

# STLC Semantics (Review)

$$\begin{array}{c} \frac{}{\langle \mathcal{E}, \lambda x^\tau. e \rangle \Downarrow (\mathcal{E}, \lambda x. e)} \text{ fun} \qquad \frac{}{\langle \mathcal{E}, \bullet \rangle \Downarrow \bullet} \text{ unit} \qquad \frac{}{\langle \mathcal{E}, x \rangle \Downarrow \mathcal{E}(x)} \text{ variable} \\[2ex] \frac{\langle \mathcal{E}, e_1 \rangle \Downarrow (\mathcal{E}', \lambda x. e) \quad \langle \mathcal{E}, e_2 \rangle \Downarrow v_2 \quad \langle \mathcal{E}'[x \mapsto v_2], e \rangle \Downarrow v}{\langle \mathcal{E}, e_1 e_2 \rangle \Downarrow v} \text{ application} \end{array}$$

The semantics are identical

**This is part of the point.** Type-checking only determines *whether* we go on to evaluate the program (whether it makes sense to)

It doesn't determine **how** we evaluate the program

# Example (Church)

$$\lambda x^\tau . xx$$

*What happens if we try to give a type to the above expression? What should  $\tau$  be?*

# Practice Problem

•  $\vdash \lambda f^{\top \rightarrow \top}. \lambda x^{\top}. fx : ( \top \rightarrow \top ) \rightarrow \top \rightarrow \top$

*Give a derivation for the above judgment*

$$\frac{(x : \tau) \in \Gamma}{\Gamma \vdash x : \tau} \quad \frac{\Gamma, x : \tau \vdash e : \tau'}{\Gamma \vdash \lambda x^{\tau}. e : \tau \rightarrow \tau'}$$

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'}$$

# Answer

$$\cdot \vdash \lambda f^{\top \rightarrow \top} . \lambda x^{\top} . f x : ( \top \rightarrow \top ) \rightarrow \top \rightarrow \top$$

How do we know if we've defined  
a "good" programming language?

# Type Safety

# Type Safety

**Theorem.** If  $\cdot \vdash e : \tau$  then there is a value  $v$  such that  $\langle \emptyset, e \rangle \Downarrow v$  and  $\cdot \vdash v : \tau$



# Type Safety

**Theorem.** If  $\cdot \vdash e : \tau$  then there is a value  $v$  such that  $\langle \emptyset, e \rangle \Downarrow v$  and  $\cdot \vdash v : \tau$

With small-step semantics, we can give a finer-grained analysis:

# Type Safety

**Theorem.** If  $\cdot \vdash e : \tau$  then there is a value  $v$  such that  $\langle \emptyset, e \rangle \Downarrow v$  and  $\cdot \vdash v : \tau$

With small-step semantics, we can give a finer-grained analysis:

**Theorem.** If  $\cdot \vdash e : \tau$ , then

- » (*progress*) either  $e$  is a value or there is an  $e'$  such that  $e \longrightarrow e'$
- » (*preservation*) If  $\cdot \vdash e : \tau$  and  $e \longrightarrow e'$  then  $\cdot \vdash e' : \tau$

# Type Safety

**Theorem.** If  $\cdot \vdash e : \tau$  then there is a value  $v$  such that  $\langle \emptyset, e \rangle \Downarrow v$  and  $\cdot \vdash v : \tau$

With small-step semantics, we can give a finer-grained analysis:

**Theorem.** If  $\cdot \vdash e : \tau$ , then


» (*progress*) either  $e$  is a value or there is an  $e'$  such that  $e \longrightarrow e'$

» (*preservation*) If  $\cdot \vdash e : \tau$  and  $e \longrightarrow e'$  then  $\cdot \vdash e' : \tau$

These results are *fundamental*. They tell us that our PL is well-behaved (it's a "good" PL)

# Type Checking

# The Picture



# Type Checking vs. Type Inference

```
type_check : expr -> ty -> bool  
type_of   : expr -> ty option
```

# Type Checking vs. Type Inference

```
type_check : expr -> ty -> bool  
type_of   : expr -> ty option
```

**Type checking** the problem of determining whether a given expression is a given type

# Type Checking vs. Type Inference

```
type_check : expr -> ty -> bool  
type_of   : expr -> ty option
```

**Type checking** the problem of determining whether a given expression is a given type

**Type inference** is the problem of *synthesizing* a type for a given expression, if possible



# Type Checking vs. Type Inference

```
type_check : expr -> ty -> bool  
type_of    : expr -> ty option
```

**Type checking** the problem of determining whether a given expression is a given type

**Type inference** is the problem of *synthesizing* a type for a given expression, if possible

Theoretically, these two problems can be very different

# Type Checking vs. Type Inference

```
type_check : expr -> ty -> bool  
type_of    : expr -> ty option
```

**Type checking** the problem of determining whether a given expression is a given type

**Type inference** is the problem of *synthesizing* a type for a given expression, if possible

Theoretically, these two problems can be very different

*For STLC, they are both easy*

# The One Issue

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'}$$

# The One Issue

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'}$$

*How do we turn this into a type-checking procedure?*

# The One Issue

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'}$$

*How do we turn this into a type-checking procedure?*

It seems like we need to do *some* amount of inference because it's not immediately clear what type we should check  $e_1$  to be

# The One Issue

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'}$$

*How do we turn this into a type-checking procedure?*

It seems like we need to do *some* amount of inference because it's not immediately clear what type we should check  $e_1$  to be

**Aside:** If you're interested there is a way of *combining* checking and inference in what's called bidirectional type checking

# The One Issue

$$\frac{\Gamma \vdash e_1 : \tau \rightarrow \tau' \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 e_2 : \tau'}$$

*How do we turn this into a type-checking procedure?*

It seems like we need to do *some* amount of inference because it's not immediately clear what type we should check  $e_1$  to be

**Aside:** If you're interested there is a way of *combining* checking and inference in what's called bidirectional type checking

**Our solution:** We'll just use type inference

demo



# Summary

**Type systems** delineate well-behaved expressions

**Type inference** can sometimes be easier to  
implement