

Xpath Locators:

Writing Smart XPaths for Dynamic Elements

1. Tag – Attribute – Value Trio
2. Contains
3. Starts-with
4. Chained XPaths Declarations
5. XPath with “or” Statement
6. XPath with “and” Statement
7. XPath Text
8. Ancestor
9. Following
10. Child
11. Preceding
12. Following-sibling
13. Descendant
14. Parent
15. Locate an Element inside Array of Elements

Basic:

Syntax = `//tagname[@attribute='Value']`

Example = `//input[@id='user-message']`




You can also use **class**, **name**, **link text**, and the other attributes to locate an element with XPath as shown above.

Writing Smart XPaths for Complex and Dynamic Elements

Tag - Attribute - Value Trio

Syntax: `//tag[@attribute='value']`

Example: `//input[@id, 'user-message']`



Examples:

```
1 //input[@type='send text']
2
3 //label[@id='clkBtn']
4
5 //input[@value='SEND']
6
7 /**[@class='swtestacademy']
8 --> "*" means, search "swtestacademy" class for all tags.
9
10 //a[@href='http://www.swtestacademy.com/']
11
12 //img[@src='cdn.medianova.com/images/img_59c4334feaa6d.png']
```

Contains

It is very handy XPath Selenium locator and sometimes it saves the life of a test automation engineer. When an attribute of an element is dynamic, then you can use contains() for the constant part of the web element but also you can use contains() in any condition when you need.

Syntax: `//tag[contains(@attribute, 'value')]`

Example: `//input[contains(@id, 'er-messa')]`



Examples:




Starts-with

This method checks the starting text of an attribute. It is very handy to use when the attribute value changes dynamically but also you can use this method for non-changing attribute values.

Syntax: `//tag[starts-with(@attribute, 'value')]`


Example: `//input[starts-with(@id, 'user')]`



Chained Declarations

We can chain multiple relative XPath declarations with **“//” double slash** to find an element location as shown below.

Example: `./div[@class='form-group']/input[@id='user-message']`



Operator “or”


In this method, we use two interrogation conditions such as A and B and return a result-set as shown below:

A	B	Result
False	False	No Element
True	False	Returns A
False	True	Returns B
True	True	Returns Both

“or” is **case-sensitive**, you should not use capital “OR”.

Syntax: `//tag[XPath Statement-1 or XPath Statement-2]`

Example: `//*[@id='user-message' or @class='form-control']`



Operator "and"


In this method, we use two interrogation conditions such as A and B and return a result-set as shown below:

A	B	Result
False	False	No Element
True	False	No Element
False	True	No Element
True	True	Returns Both

"and" is case-sensitive, you should not use capital "AND".

Syntax: `//tag[XPath Statement-1 and XPath Statement-2]`

Example: `//*[@id='user-message' and @class='form-control']`




Text

We can find an element with its exact text.

Syntax: `//tag[text()='text value']`

Example: `//label[text()='Enter message']`




Ancestor

It finds the element before the ancestor statement and set it as a top node and then starts to **find the elements in that node**. In below example,

1- First, it finds the class which id is "container-fluid"

2- Then, starts to find div elements in that node.

Example: `//*[@class='container-fluid']/ancestor::div`



You can select specific div groups by changing div depths as shown below.

`//*[@class='container-fluid']/ancestor::div[1]` – Returns 13 nodes

`//*[@class='container-fluid']/ancestor::div[2]` – Returns 7 nodes

`//*[@class='container-fluid']/ancestor::div[3]` – Returns 5 nodes

`//*[@class='container-fluid']/ancestor::div[4]` – Returns 3 nodes


`//*[@class='container-fluid']/ancestor::div[5]` – Returns 1 node

Following

Starts to locate elements **after the given parent node**. It finds the element before the following statement and set as the top node and then starts to find **all elements after that node**. In below example,

- 1- First, it finds the form which id is "gettotal"
- 2- Then, starts to find all input elements after that node.


Example: `./form[@id='gettotal']/following::input`




Child

Selects all children elements of the current node.

Example: `//nav[@class='fusion-main-menu']/ul[@id='menu-main']/child::li`




You can also select the required "li" element by using `li[1]`, `li[2]`, `li[3]`, etc. syntax as shown below.



Preceding

Select all nodes that come before the current node. I give an example on swtestacademy. We will find all "li" elements in the homepage. First, we will locate the bottom element, then use preceding with "li" to find all "li" elements as shown below.

Example: `//img[contains(@src,'cs.mailmunch.co')]/preceding::li`



Also, you can use `[1]`, `[2]`, etc. to select a specific element in the preceding element list.

Following-sibling

Select the following siblings of the context node.

Example: `//*[@class='col-md-6 text-left']/child::div[2]//*[@class='panel-body']/following-sibling::li`

The screenshot shows a web application titled "Two Input Fields". The page content includes a heading "First Let us try with Two input fields and a Button", two input fields labeled "Enter Value for a" and "Enter Value for b", and a button labeled "Click on 'Get Total' button to display the sum of two numbers 'a and b'". Below the inputs is a form with a "Get Total" button. The FirePath console shows the XPath expression `//*[@class='col-md-6 text-left']/child::div[2]//*[@class='panel-body']/following-sibling::li`, which selects the list items under the second panel-body. The selected list items are: ` Enter Value for a `, ` Enter Value for b `, and `Click on 'Get Total' button to display the sum of two numbers 'a and b'`.

Descendant

Identifies and returns all the element descendants to current element which means traverse down under the current element's node. Below, the XPath returns all "li" elements under the "menu-main".


Example: `//nav[@class='fusion-main-menu']//*[@id='menu-main']/descendant::li`

The screenshot shows the FirePath console with the XPath expression `//nav[@class='fusion-main-menu']//*[@id='menu-main']/descendant::li`. The selected list items are: `<li id="menu-item-884" class="menu-item menu-item-type-custom menu-item-type-post_type taxonomies" > `, `<li id="menu-item-21" class="menu-item menu-item-type-post_type taxonomies" > `, `<li id="menu-item-844" class="menu-item menu-item-type-taxonomy menu-item-type-post_type taxonomies" > `, `<li id="menu-item-845" class="menu-item menu-item-type-taxonomy menu-item-type-post_type taxonomies" > `, `<li id="menu-item-846" class="menu-item menu-item-type-taxonomy menu-item-type-post_type taxonomies" > `, `<li id="menu-item-963" class="menu-item menu-item-type-taxonomy menu-item-type-post_type taxonomies" > `, `<li id="menu-item-4087" class="menu-item menu-item-type-taxonomy menu-item-type-post_type taxonomies" > `, `<li id="menu-item-1187" class="menu-item menu-item-type-taxonomy menu-item-type-post_type taxonomies" > `, `<li id="menu-item-20" class="menu-item menu-item-type-post_type taxonomies" > `, and `<li class="fusion-custom-menu-item fusion-main-menu-search fusion-main-menu" > `.

Parent

Returns the parent of the current node as shown in the below example.

Example: `//*[@id='get-input']/button//parent::form`




Locate an Element inside Array of Elements

In Trivago website, let's search "Antalya" keyword. Then, find the first Odamax hotel with XPath.


First, we can find all Odamax hotels by using its text with below XPath:

`//span[contains(text(),'odamax')]`



Above XPath returns many Odamax hotel's, we can select the first one with below XPath expression:

`(//span[contains(text(),'odamax')])[1]`



You can also continue to search and find the related hotel's price element with below XPath:

`(//span[contains(text(),'odamax')])[1]/following-sibling::strong[@class='deals__price']`

