

Spring Learn Assignment

application.properties

```
logging.level.org.springframework=info
logging.level.com.cognizant.springlearn=debug
logging.pattern.console=%d{yyMMdd} | %d{HH:mm:ss.SSS} | %-20.20thread | %5p | %-
25.25logger{25} | %25M | %m%n
server.port=8080
```

SpringLearnApplication.java

```
@SpringBootApplication
public class SpringLearnApplication {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args){
        SpringApplication.run(SpringLearnApplication.class,args);
        SpringLearnApplication app=new SpringLearnApplication();
        app.displayDate();
        app.displayCountry();
        app.displayCountries();
    }

    public void displayDate(){
        LOGGER.info("START");
        ApplicationContext context=
            new ClassPathXmlApplicationContext("date-format.xml");
        SimpleDateFormat
format=context.getBean("dateFormat",SimpleDateFormat.class);
        try{
            Date date=format.parse("31/12/2018");
            LOGGER.debug("{} ",date);
        }catch(Exception e){LOGGER.error(e.getMessage());}
        LOGGER.info("END");
    }

    public void displayCountry(){
        LOGGER.info("START");
        ApplicationContext context=
            new ClassPathXmlApplicationContext("country.xml");
        Country country=context.getBean("country",Country.class);
        Country another=context.getBean("country",Country.class);
        LOGGER.debug("Country : {} ",country);
    }
}
```

```

        LOGGER.info("END");
    }

    public void displayCountries(){
        LOGGER.info("START");
        ApplicationContext context=new
        ClassPathXmlApplicationContext("country.xml");
        ArrayList<Country>
        list=context.getBean("countryList",ArrayList.class);
        LOGGER.debug("{} ",list);
        LOGGER.info("END");
    }
}

```

date-format.xml

```

<beans xmlns="http://www.springframework.org/schema/beans"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.springframework.org/schema/beans
https://www.springframework.org/schema/beans/spring-beans.xsd">
<bean id="dateFormat" class="java.text.SimpleDateFormat">
<constructor-arg value="dd/MM/yyyy"/>
</bean>
</beans>

```

Country.java

```

public class Country{
private static final Logger LOGGER=LoggerFactory.getLogger(Country.class);
private String code;
private String name;
public Country(){LOGGER.debug("Inside Country Constructor.");}
public String getCode(){return code;}
public void setCode(String code){this.code=code;}
public String getName(){return name;}
public void setName(String name){this.name=name;}
public String toString(){return "Country [code="+code+", name="+name+"]";}
}

```

country.xml

```

<beans xmlns="http://www.springframework.org/schema/beans"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.springframework.org/schema/beans
https://www.springframework.org/schema/beans/spring-beans.xsd">
<bean id="in" class="com.cognizant.springlearn.Country"
scope="prototype"><property name="code" value="IN"/><property name="name"
value="India"/></bean>
<bean id="us" class="com.cognizant.springlearn.Country"><property name="code"
value="US"/><property name="name" value="United States"/></bean>

```

```
<bean id="de" class="com.cognizant.springlearn.Country"><property name="code"
value="DE"/><property name="name" value="Germany"/></bean>
<bean id="jp" class="com.cognizant.springlearn.Country"><property name="code"
value="JP"/><property name="name" value="Japan"/></bean>
<bean id="country" class="com.cognizant.springlearn.Country"><property
name="code" value="IN"/><property name="name" value="India"/></bean>
<bean id="countryList" class="java.util.ArrayList"><constructor-arg><list><ref
bean="in"/><ref bean="us"/><ref bean="de"/><ref
bean="jp"/></list></constructor-arg></bean>
</beans>
```