

Data Analysis with SQL

MSSQL Cheat Sheet

Created By [Ram Kedom](#), [Shuki Molk](#), [Dotan Entin](#), and [Elad Peleg](#)

Basic SQL Statements

Select all	SELECT * FROM table
Select specific columns	SELECT column1, column2 FROM table
Arithmetic operations	SELECT column + value FROM table
String concatenation	SELECT string_column + ' ' + string_column FROM table
Column alias	SELECT column AS 'alias'
Distinct values of a single column	SELECT DISTINCT column FROM table
Distinct values of multiple Columns	SELECT DISTINCT column, column FROM table
Quote column name in case it contains spaces, punctuation or conflicts with a reserved keyword	SELECT [column_name]

Filter the Dataset

Specify a numeric value	5
Specify a string value	'string'
Specify a date value	'2019-05-28'
Basic operators	WHERE column = value (or >, <, >=, <=, !=)
IN	WHERE column IN (value1, value2, value3)
BETWEEN	WHERE column BETWEEN value1 AND value2
LIKE	WHERE column LIKE 'pattern'
IS NULL	WHERE column IS NULL
IS NOT NULL	WHERE column IS NOT NULL
AND	WHERE condition1 AND condition2
OR	WHERE condition1 OR condition2

Sort the Result Set

ORDER BY a single column ascending	ORDER BY column
ORDER BY a single column descending	ORDER BY column DESC
ORDER BY multiple columns	ORDER BY column1, column2 DESC ..

Limit the Result Set

Retrieves first N rows	SELECT TOP N ...
Retrieves first N percent	SELECT TOP N PERCENT ..
TOP N Analysis	SELECT TOP N .. ORDER BY ..

Common String Related Functions

Returns the right part of a string	RIGHT('hello' , 2) → 'lo'
Returns the left side of a string	LEFT('hello', 2) → 'he'
Returns the number of characters in a string	LEN('hello') → 5
Replaces all occurrences of a given substring	REPLACE('hello world' , 'l', '*') → 'he**o wor*d'
Reverses a string	REVERSE('hello') → 'olleh'
Returns a substring of a string	SUBSTRING('hello world' , 2, 3) → 'ell'
Returns a string in lower-case	LOWER('HELLO') → 'hello'
Returns a string in upper-case	UPPER('hello') → 'HELLO'
Returns the position of a substring in a string	CHARINDEX('e', 'hello') → 2

Common Numeric Functions & Operations	
Rounds the number	ROUND (92.56, 1) → 92.6
Rounds a number downwards the nearest integer	FLOOR (92.56) → 92
Rounds a number upwards the nearest integer	CEILING (92.56) → 93
Returns the absolute value of a number	ABS (-28) → 28
Returns the square root of a number	SQRT (100) → 10
Returns a number raised to the power of another	POWER (10, 2) → 100
If an integer <i>dividend</i> is divided by an integer <i>divisor</i> , the result is an integer	5/2 → 2
Return a Decimal output from dividing two integers	5 / (CAST 2 AS DECIMAL) → 2.5

Converting Values using CAST	
Convert a value to an int datatype	CAST (5.25 as INT) → 5
Convert a value to a varchar datatype	CAST (5.25 as VARCHAR) → '5.25'
Convert a value to a date datatype	CAST ('2020-01-25' AS DATE)
Convert a value to a decimal datatype	CAST (5 AS DECIMAL)

Common Date Related Functions	
Returns the current database date	GETDATE ()
Adds a time/date interval to a date	DATEADD (YEAR, 1, '2020-01-24') → 2021-01-24
Return the difference between two date values	DATEDIFF (MONTH, '2020-01-24', '2020-04-24') → 3
Returns the year of a specified date	YEAR ('2020-01-24') → 1
Returns the month of a specified date	MONTH ('2020-01-24') → 2020
Returns the day of a specified date	DAY ('2020-01-24') → 24

Common Null Handling Functions	
Returns the specified value IF the expression is NULL, otherwise return the expression	ISNULL (column, value_to_return_if_null)

Conditional Expressions	
Goes through a series of conditions and returns a value when the first condition is met	CASE WHEN condition1 THEN result1 WHEN condition2 THEN result2 WHEN conditionN THEN resultN ELSE result END;

Common Group Operations	
Returns the average	AVG ()
Returns the minimum	MIN ()
Returns the maximum	MAX ()
Returns the sum	SUM ()
Counts the number of rows in a table	COUNT (*)
Counts the number of values in a column	COUNT (column)
Counts the number of distinct values in a column	COUNT (DISTINCT column)
Divides the query result into groups of rows	GROUP BY column, column...
Filter condition based on a group or aggregate	HAVING <condition>
Returns the aggregation result for each row in the table	agg_function () OVER ()
Returns the aggregated results for each partition, in each row (of the same partition)	agg_function () OVER (PARTITION BY ..)
Returns the cumulative aggregated results	agg_function () OVER (ORDER BY..)
Returns the cumulative aggregated results in each partition	agg_function () OVER (PARTITION BY.. ORDER BY..)

Syntax vs Execution Order

Writing	Execution
SELECT	FROM (Joins included)
FROM (JOINS included)	WHERE
WHERE	GROUP BY
GROUP BY	HAVING
HAVING	SELECT
ORDER BY	ORDER BY

JOIN Operations

Inner	FROM table1 t1 INNER JOIN table2 t2 ON <condition>
Full outer	FROM table1 t1 FULL OUTER JOIN table2 t2 ON <condition>
Outer Left	FROM table1 t1 LEFT OUTER JOIN table2 t2 ON <condition>
Outer Right	FROM table1 t1 RIGHT OUTER JOIN table2 t2 ON <condition>

Subqueries in the WHERE Clause

Single row Subqueries	WHERE column = (INNER QUERY)
Comparing against multiple values	WHERE column IN (INNER QUERY)

CTE

A common table expression (CTE) is a named temporary result set that exists within the scope of a single statement and that can be referred to later within that statement, possibly multiple times

```
WITH expression_name [ ( column_name [,...n] ) ]
AS
( CTE_query_definition )
```

SET Operators

Combines the result set of two or more SELECT statements (allows duplicate values)	SELECT ... FROM table_1 UNION ALL SELECT ... FROM table_2
Combines the result set of two or more SELECT statements (only distinct values)	SELECT ... FROM table_1 UNION SELECT ... FROM table_2
Returns the intersection of two SELECT statements	SELECT ... FROM table_1 INTERSECT SELECT ... FROM table_2
Returns any distinct values from the query left of the EXCEPT operator	SELECT ... FROM table_1 EXCEPT SELECT ... FROM table_2

Ranking Functions

Returns the rank of each row within the partition of a result set. The rank of a row is one plus the number of ranks that come before the row in question.	RANK () OVER (PARTITION BY... ORDER BY...)
Returns the rank of each row within a result set partition. The rank of a specific row is one plus the number of distinct rank values that come before that specific row.	DENSE_RANK () OVER (PARTITION BY... ORDER BY...)
Returns the sequential number of a row within a partition of a result set, starting at 1	ROW_NUMBER () OVER (PARTITION BY... ORDER BY...)
Divides the result set produced by the FROM clause into partitions	NTILE (n) OVER (PARTITION BY... ORDER BY...)

Analytic Functions	
Accesses data from a previous row in the same result	LAG(column) OVER (PARTITION BY.. ORDER BY..)
Accesses data from a subsequent row in the same result set	LEAD(column) OVER (PARTITION BY.. ORDER BY..)

PIVOT
PIVOT rotates a table-valued expression by turning the unique values from one column in the expression into multiple columns in the output
<pre>SELECT .. FROM (SELECT query that produces the data for axis) AS alias PIVOT (aggregate_function (column) FOR x_axis_column IN (list of values)) AS alias</pre>

UNPIVOT
UNPIVOT carries out the opposite operation to PIVOT by rotating columns of a table-valued expression into column values
<pre>SELECT .. FROM (SELECT columns participating in the process) AS alias UNPIVOT (column_representing_z_values FOR column_representing_x_values IN (list of values..)) AS alias</pre>

Essential Data Types	
String Data Types	Description
CHAR(number)	A fixed number of characters
VARCHAR(number / MAX)	A variable number of characters
Numeric Data Types	Description
TINYINT	Integers between 0 and 255
SMALLINT	Integers between (-32,768) and 32,767
INT	Integers between (-2,147,483,648) and 2,147,483,647
BIGINT	Integers between (-9,223,372,036,854,775,808) and 9,223,372,036,854,775,807
DECIMAL(p,s)	Numbers from $(-10^{38} + 1)$ to $(10^{38} - 1)$ p = total number of digits, s = number of decimal digits. I.e 123.4567 → p=7, s=4
NUMERIC(p,s)	numeric is functionally identical to decimal
BIT	Holds either 0 ('false') of 1 ('true'). Can hold also NULL.
Date Data Types	Description
DATETIME	From 1753-Jan-01 to 9999-Dec-31 with an accuracy of 1/3 millisecond (.000, .003, or .007 seconds)
DATE	From 1753-Jan-01 to 9999-Dec-31 with an accuracy of 1 day