

Obstacle Avoidance Robot

Sittalatchoumy R

Department of Electronics and Communication Engineering
College of Engineering Guindy, Anna University
Chennai, India
sittalatchoumy@gmail.com

Shanmugavalli P

Department of Electronics and Communication Engineering
College of Engineering Guindy, Anna University
Chennai, India
shanmugavalli871@gmail.com

Mirunalini S

Department of Electronics and Communication Engineering
College of Engineering Guindy, Anna University
Chennai, India
mirunalinisaravanankumar@gmail.com

Dharshini R

Department of Electronics and Communication Engineering
College of Engineering Guindy, Anna University
Chennai, India
dharshiniramesh006@gmail.com

Abstract - Autonomous navigation is a critical technology enabling robots to independently traverse unfamiliar areas, circumventing human limitations and potential dangers. This paper presents the design, implementation, and performance evaluation of an autonomous mobile robot (AMR) capable of real-time obstacle detection and avoidance. The primary objective is to develop a reliable and efficient platform for navigation in unknown, unstructured environments. Utilizing ultrasonic range-finders (e.g., HC-SR04), the robot adeptly detects the distance and location of both static and dynamic obstacles. The core of the system is a microcontroller-based reactive algorithm that facilitates immediate course correction and avoidance maneuvers to maintain continuous motion toward a goal while preventing collisions. This work contributes a practical, easily reproducible solution that enhances the reliability of autonomous navigation algorithms, offering insights into robot behavior and intelligent navigation in dynamic, real-world settings.

Keywords - Autonomous Mobile Robot (AMR), Obstacle Avoidance, Real-time Navigation, Ultrasonic Sensor, Arduino Microcontroller, Reactive Algorithm, Low-Cost Robotics

I. INTRODUCTION

In the modern era of technology and innovation, robotics has emerged as one of the most dynamic and transformative fields. Robots are increasingly being designed to perform tasks that are repetitive, dangerous, or require precision beyond human capability. Among the various types of autonomous robots, the obstacle avoiding robot is one of the most fundamental and widely studied systems. It represents the foundation of autonomous navigation and intelligent motion control. The ability of a robot to detect obstacles in its path and take corrective actions without human intervention is a crucial aspect of autonomous systems used in industrial automation, military operations, space exploration, and service robotics.

An obstacle avoiding robot uses sensors and actuators to perceive its environment and respond accordingly. The most common sensing device used for obstacle detection is the ultrasonic sensor. It works on the principle of sound wave reflection, where high-frequency sound waves are emitted and the time taken for the echo to return is measured.

Using this time interval, the distance between the robot and the obstacle is calculated. This method is highly efficient

because ultrasonic sensors are inexpensive, reliable, and unaffected by lighting conditions, making them suitable for both indoor and outdoor environments.

The control unit of the robot is typically a microcontroller that processes the sensor data and decides the movement of the robot. In this project, the Arduino Uno microcontroller is used due to its simplicity, flexibility, and open-source nature. It reads the distance data from the ultrasonic sensor and determines whether the robot should move forward, stop, or change direction. A servo motor is employed to rotate the ultrasonic sensor, enabling the robot to scan its surroundings to the left and right when an obstacle is detected. Based on the comparison of distances on both sides, the robot turns toward the direction with more space available.

The robot's movement is achieved using DC motors controlled through a motor driver module (such as L293D or L298N). The driver acts as an interface between the low-power Arduino and the high-power motors, allowing the robot to move forward, backward, or turn smoothly. The system's operation is governed by a decision-making algorithm embedded in the Arduino, which ensures real-time obstacle detection and avoidance.

The proposed design offers a cost-effective and practical approach to autonomous navigation. It demonstrates how basic sensors, microcontrollers, and actuators can be integrated to achieve intelligent behavior. This type of robot can be applied in numerous domains, such as automated vacuum cleaners, delivery robots, surveillance systems, and autonomous vehicles. The same principle can also be extended to more complex robots that use machine learning, computer vision, and mapping algorithms for enhanced decision-making and environmental understanding.

The obstacle avoiding robot serves as an excellent platform for understanding the interaction between hardware and software in robotic systems. It embodies the essential concepts of embedded systems, sensor interfacing, and real-time control. Through this project, the implementation of an autonomous robotic system capable of intelligent obstacle avoidance is achieved, laying the groundwork for future advancements in robotics and automation

II. LITERATURE ANALYSIS

The study of obstacle avoiding robots has gained significant attention in the field of robotics and automation, as autonomous systems are increasingly applied in industrial, domestic, and military environments. Various research works have been carried out to develop intelligent robots capable of sensing and avoiding obstacles while navigating independently. Early designs were mostly based on simple reactive systems that used infrared or ultrasonic sensors connected to basic microcontrollers such as Arduino or PIC. These robots employed straightforward algorithms that allowed them to detect nearby objects and change direction accordingly, ensuring safe movement without human control.

As technology evolved, researchers began integrating multiple sensors to improve environmental awareness and precision. The combination of ultrasonic, infrared, and LIDAR sensors has enhanced accuracy in detecting both stationary and moving obstacles. Some studies introduced computer vision techniques using cameras for real-time object recognition and mapping. In addition, control strategies like fuzzy logic, neural networks, and machine learning have been adopted to allow robots to make smarter and adaptive navigation decisions in complex and dynamic environments.

Recent developments also focus on techniques such as Simultaneous Localization and Mapping (SLAM), which enable a robot to map unknown surroundings while keeping track of its own position. Microcontrollers with higher computational capabilities, such as STM32 and Raspberry Pi, have made these implementations more efficient.

The reviewed literature reveals a consistent trend toward improving autonomy, intelligence, and environmental interaction. Building upon these previous studies, the proposed project implements a cost-effective obstacle avoidance system using an Arduino microcontroller, ultrasonic sensor, servo motor, and motor driver. This approach provides an efficient solution for small-scale autonomous navigation and serves as a foundation for future research in intelligent robotics and embedded control systems.

III. OBJECTIVES

- To design and develop an autonomous mobile robot capable of detecting and avoiding obstacles in its path without human intervention.
- To integrate Arduino Uno as the main control unit, enabling decision-making and system coordination through embedded programming.
- To ensure smooth navigation in dynamic environments by maintaining continuous sensing and responsive movement adjustments.
- To create a cost-effective, power-efficient, and scalable robotic platform suitable for educational, research, and automation applications.

IV. SYSTEM ARCHITECTURE

The system architecture of the obstacle avoiding robot is designed as an integrated control system consisting of sensing, processing, driving, and actuation components. The primary sensing element used in this project is the HC-SR04 ultrasonic sensor, which continuously detects the presence and distance of obstacles by transmitting ultrasonic pulses and measuring the time taken for the echo to return. This sensor provides real-time distance data that serves as the primary input for navigation decisions.

The Arduino Uno is employed as the central control unit of the system. It receives the distance information from the ultrasonic sensor and processes it according to the programmed decision-making algorithm. The microcontroller determines whether the robot should move forward, stop, or change direction based on a predefined threshold distance. The decision output from the Arduino is then transmitted to the motor driving module.

The L298N motor driver module serves as the interface between the control unit and the actuation unit. Since the Arduino cannot directly supply the required current to drive the motors, the motor driver amplifies and conditions the control signals to operate the DC motors efficiently. It also facilitates directional control by enabling forward and reverse rotation of the motors as required.

The actuation unit comprises two DC motors connected to the wheels of the robot chassis. The speed and direction of the motors determine the motion of the robot. By adjusting the rotation of the motors, the robot can move straight, turn left, turn right, or halt entirely. Together, these components form a closed-loop autonomous navigation system where continuous sensing and feedback ensure obstacle-free movement in dynamic environments.




Fig.1 Circuit Diagram

V. HARDWARE COMPONENTS

A. Arduino microcontroller

The Arduino Uno is used as the main control unit of the robot. It is based on the ATmega328P microcontroller and provides sufficient digital I/O pins to interface sensors and motor drivers. It processes the input received from the ultrasonic sensor and executes the decision-making algorithm to control the robot's movement. Its simplicity, low cost, and ease of programming make it suitable for small embedded robotic applications.




Fig.2 Arduino microcontroller

B. HC – SR04 Ultrasonic sensor

The HC-SR04 ultrasonic sensor is used for obstacle detection. It operates by transmitting ultrasonic waves and measuring the time taken for the reflected waves to return. Using this time delay, the distance to an obstacle is calculated. The sensor provides accurate and reliable distance measurement within a range of approximately 2 cm to 400 cm, enabling the robot to detect obstacles in real time.



Fig.3 HC-SR04 Ultrasonic sensor

C. L298N Motor Driver Module

The L298N motor driver is used to control the DC motors that drive the robot. The Arduino cannot supply the high current required by the motors, so the motor driver acts as an interface, providing appropriate voltage and current. It allows both direction control and speed control of the motors using input signals from the Arduino. It supports dual H-bridge configuration, making it suitable for driving two DC motors simultaneously.



Fig.4 L298N Motor Driver Module

D. DC Gear Motors

The robot uses two DC gear motors for locomotion. These motors convert electrical energy into rotational mechanical energy, enabling the wheels to move. The built-in gear reduction increases torque while reducing speed, making the movement of the robot stable and controlled. The motors' direction and speed are regulated through the motor driver based on control commands.



Fig.5 DC Motors

VI. SOFTWARE IMPLEMENTATION

The software implementation of the obstacle avoiding robot involves the development of an embedded control program using the Arduino Integrated Development Environment (Arduino IDE). The Arduino Uno microcontroller is programmed using the C/C++ based Arduino programming language. The code begins with the initialization of the ultrasonic sensor pins, motor control pins, and required variables. The trigger and echo pins of the ultrasonic sensor are configured for sending and receiving ultrasonic pulses, while the motor driver input pins are set as outputs to control the direction and motion of the DC motors.

The logic for obstacle detection is implemented within the main program loop. The microcontroller continuously sends trigger pulses to the ultrasonic sensor and calculates the distance to the nearest object by measuring the duration of the returned echo signal. This measured distance is compared with a predefined threshold value. If the distance is greater than the threshold, the robot moves forward. If an obstacle is detected below the threshold distance, the robot stops and performs an avoidance maneuver, such as turning left or right, based on the programmed decision logic.

Motor control functions are used to drive the robot in different directions by setting the motor driver input pins to appropriate logic levels. Timing delays are incorporated to stabilize motion transitions and avoid jitter. The program is tested, debugged, and uploaded to the Arduino Uno through a USB interface. The final software implementation ensures continuous sensing and smooth autonomous navigation, enabling the robot to react to obstacles in real time.




Fig.6 Flowchart

VII. WORKING METHODOLOGY

A. System Operation Overview

The obstacle-avoiding robot functions through a coordinated interaction of sensing, control, and actuation elements. The ultrasonic sensor acts as the primary sensing component to detect obstacles, while the Arduino Uno serves as the control unit responsible for executing decision logic. The L298N motor driver powers and regulates the movement of the two DC motors that provide locomotion to the robot. During operation, the system continuously monitors the environment and adjusts its movement to avoid collisions. The methodology ensures smooth, autonomous navigation by continuously sensing distance, comparing it with predefined thresholds, and altering motor actions accordingly.

B. Continuous Distance Monitoring

The HC-SR04 ultrasonic sensor is used to measure the distance between the robot and obstacles in its path. The Arduino triggers the sensor to emit an ultrasonic wave, which reflects off nearby objects and returns to the receiver. The time delay between transmission and reception is used to calculate the distance to the obstacle. This process repeats continuously in real time, allowing the robot to constantly assess its surroundings and respond dynamically to changes in proximity.

C. Forward Motion and Obstacle Detection

Under normal conditions, the robot advances forward when the measured distance to any obstacle exceeds a threshold value of 30 cm. The motors are driven in a forward rotation mode to sustain smooth motion. When an obstacle is detected at a distance less than or equal to 30 cm, the control unit immediately stops the motors to prevent collision. This stoppage marks the transition from normal movement mode to obstacle-avoidance mode, enabling the robot to analyze alternative pathways for safe navigation.

D. Environmental Scanning and Decision Logic

After halting, the robot evaluates the surrounding space to determine the most appropriate avoidance maneuver. Distance readings from the left and right directions are obtained and compared. If both directions are restricted (i.e., distances less than 25 cm), the robot briefly reverses in order to reposition itself. If one direction provides greater open space, the robot turns toward that direction. This turning movement is executed in a controlled manner to ensure stability and prevent abrupt directional changes.

E. Directional Movement and Realignment

The robot executes its chosen avoidance maneuver by controlling the rotation of the DC motors through the L298N motor driver. To turn left or right, one motor may be slowed or stopped while the other continues rotating. Once the robot has successfully oriented itself away from the obstacle, forward motion resumes. The system then returns to continuous distance monitoring mode, forming a closed-loop feedback cycle that maintains ongoing autonomous navigation.

F. Adaptive Navigation Outcome

This sequential working approach enables the robot to navigate dynamically in environments containing obstacles of varying shapes and distances. The continuous sensing and repositioning logic ensures that the robot does not collide with objects and can adapt to changing paths. The smooth pivoting turns and distance-based movement transitions contribute to stable motion control and improved maneuverability. Overall, the method provides reliable real-time obstacle avoidance and supports autonomous operation in indoor and small-scale exploratory settings.

The obstacle-avoiding robot was tested under various indoor conditions involving different types of obstacles, surface materials, and navigation layouts. The performance of the robot demonstrated effective real-time detection and avoidance of objects positioned within its sensing range. During straight-path navigation, the robot moved forward smoothly without significant oscillations in speed or direction, indicating that the motor control signals and PWM-based regulation provided stable locomotion. When the ultrasonic sensor detected an obstacle closer than the threshold distance of 30 cm, the robot consistently responded by stopping its forward motion and entering the avoidance phase with minimal delay. This ensured that collision events were successfully prevented during all test scenarios.

The environmental scanning mechanism showed reliable operation in identifying alternative free paths. When the ultrasonic sensor performed left and right directional checks, the measured distances exhibited good repeatability with negligible variation when obstacles remained stationary. In scenarios where both directions were blocked, the robot successfully executed a backward retreat to re-establish maneuvering space. This behavior prevented the system from being trapped in cornered or congested environments, demonstrating the practicality of the decision logic. Additionally, the comparison-based directional selection allowed the robot to choose the side with greater clearance, leading to a smooth turning motion without abrupt or jerky rotation.

The sway-turn movement pattern, particularly where one motor slowed or stopped while the other continued to rotate, resulted in smooth and controlled directional changes. This method reduced mechanical stress on the wheels and chassis during pivoting, contributing to better stability and improved turning accuracy. The robot also returned to its forward motion seamlessly after completing the avoidance maneuver, indicating effective closed-loop operation. Although performance was generally stable, occasional variations in distance readings were observed when the robot encountered reflective or curved surfaces. These variations are attributed to the acoustic reflection characteristics of the ultrasonic sensor and represent a known limitation of the sensing principle rather than a fault in the implementation.

Overall, the system demonstrated robust obstacle avoidance behavior across multiple test runs. The combination of continuous distance monitoring, environmental scanning, and adaptive directional movement enabled the robot to autonomously navigate through dynamic pathways. The results affirm that the designed system is suitable for small-scale autonomous navigation, educational robotics, and further extension into semi-autonomous smart mobility applications.

XI. CONCLUSION

This project successfully demonstrates the design and implementation of an obstacle-avoidance robot using an Arduino-based control system. The integration of ultrasonic sensing, servo-based scanning, and L298N motor driver control proved effective for achieving autonomous navigation. The experimental results confirm that the robot can detect and avoid obstacles smoothly, maintaining continuous motion

without human intervention. The early-stop and sway-turn logic enhanced both responsiveness and movement stability compared to traditional differential-turn methods.




Fig.7 Hardware setup

The work also reinforces the importance of sensor fusion and real-time processing in autonomous systems. Future improvements could include Bluetooth or Wi-Fi connectivity for remote control and monitoring, as well as additional sensors such as infrared or LIDAR to improve environmental awareness and precision. Overall, the developed system provides a solid foundation for further research and experimentation in mobile robotics and autonomous navigation.

REFERENCES

- [1] A. Kumar and S. Singh, "Design and Implementation of an Obstacle Avoidance Robot using Ultrasonic Sensor," *International Journal of Scientific Research in Engineering and Management*, vol. 4, no. 3, pp. 1–6, 2021.
- [2] M. S. Mazhar, R. Ahmed, and K. M. Hasan, "Autonomous Robot for Obstacle Avoidance Using Arduino and Ultrasonic Sensor," *International Journal of Advanced Computer Science and Applications*, vol. 12, no. 7, pp. 45–51, 2021.
- [3] A. Sharma and P. Verma, "Microcontroller Based Intelligent Obstacle Avoidance Vehicle," *International Journal of Engineering Research & Technology*, vol. 9, no. 5, pp. 250–253, 2020.
- [4] N. Gupta and R. Chauhan, "Application of HC-SR04 Ultrasonic Sensor for Distance Measurement and Obstacle Detection," *Proceedings of the International Conference On Computing, Communication, and Automation*, IEEE, pp. 112–116, 2019.
- [5] H.A. Hassan, "Embedded Control of Mobile Robot Navigation using Arduino," *IEEE International Conference on Electrical, Computer and Communication Technologies*.