

Cloud MCP Suite — Nexus Deployment Guide

Five FastMCP Python servers + rclone iDrive E2.

All servers use `streamable_http` transport on `127.0.0.1` , reverse-proxied by NPM.

Port Map

Service	Container Name	Port	Subdomain
pCloud	pcloud-mcp	8201	pcloud-mcp.shannonjlove.cloud
Backblaze B2	backblaze-mcp	8202	b2-mcp.shannonjlove.cloud
MediaFire	mediafire-mcp	8203	mediafire-mcp.shannonjlove.cloud
MEGA	mega-mcp	8204	mega-mcp.shannonjlove.cloud
Google Drive	gdrive-mcp	8205	gdrive-mcp.shannonjlove.cloud
rclone/iDrive	host-level	—	iDrive E2 (S3 endpoint)

Quick Deploy

```
# 1. Clone / SCP this suite to Nexus
scp -r mcp-cloud-suite/ shannon@nexus.shannonjlove.cloud:/opt/mcp-suite/

# 2. Run the master deploy script
cd /opt/mcp-suite/mcp-cloud-suite
chmod +x deploy-cloud-mcp-suite.sh
./deploy-cloud-mcp-suite.sh

# 3. Fill in credentials for each service
vim /opt/mcp-servers/pcloud/pcloud.env
vim /opt/mcp-servers/backblaze/backblaze.env
vim /opt/mcp-servers/mediafire/mediafire.env
vim /opt/mcp-servers/mega/mega.env
vim /opt/mcp-servers/gdrive/gdrive.env
```

```
# 4. Restart each container after filling in creds
for svc in pcloud-mcp backblaze-mcp mediafire-mcp mega-mcp gdrive-mcp; do
    systemctl --user restart "$svc"
done

# 5. Deploy rclone for iDrive E2
export IDRIVEE2_ACCESS_KEY=YOUR_KEY
export IDRIVEE2_SECRET_KEY=YOUR_SECRET
export IDRIVEE2_ENDPOINT=https://YOUR_ACCOUNT.idrivee2-N.com
bash rclone-idrivee2/deploy-rclone-idrivee2.sh
```

Credentials Reference

pCloud

- Get OAuth2 token: <https://docs.pcloud.com/methods/auth/>
- `PCLOUD_ACCESS_TOKEN` — Long-lived OAuth2 bearer token
- `PCLOUD_REGION` — `us` (default) or `eu`

Backblaze B2

- Console: https://secure.backblaze.com/app_keys.htm
- `B2_APPLICATION_KEY_ID` — Application Key ID
- `B2_APPLICATION_KEY` — Application Key (secret)

MediaFire

- Developer portal: <https://www.mediafire.com/developer/>
- `MEDIAFIRE_APP_ID` — Your Application ID
- `MEDIAFIRE_API_KEY` — Your API Key
- `MEDIAFIRE_EMAIL` + `MEDIAFIRE_PASSWORD` — Account credentials

MEGA

- No API key needed — uses email/password
- `MEGA_EMAIL` + `MEGA_PASSWORD` — Account credentials

Google Drive (local server)

Option A — Service Account (recommended for server):

1. GCP Console → IAM → Service Accounts → Create
2. Enable Google Drive API
3. Download JSON key → place in `/opt/mcp-servers/gdrive/credentials/service-account.json`
4. Share folders/drives with the service account email

Option B — OAuth2:

1. GCP Console → APIs → Credentials → Create OAuth 2.0 Client ID (Desktop)
2. Download → `/opt/mcp-servers/gdrive/credentials/credentials.json`
3. First run will open browser for auth → generates `token.json`

iDrive E2 (rclone)

1. iDrive E2 Console → Access Keys → Create Key
 2. Note your Endpoint URL under Buckets
-

NPM Proxy Host Setup (for each server)

In the NPM Admin UI (<https://admin.shannonjlove.cloud>):

1. **Proxy Hosts → Add Proxy Host**
 2. Domain Names: (see Port Map above)
 3. Scheme: `http`
 4. Forward Hostname: `127.0.0.1`
 5. Forward Port: (see Port Map above)
 6. Websockets Support: ☒ ON
 7. Block Exploits: ☒ ON
 8. **SSL tab** → Request new certificate → Force SSL → HSTS ☒
-

Claude Desktop MCP Config

Add to ~/.config/claude-desktop/mcp_servers.json :

```
{
  "mcpServers": {
    "pcloud": {
      "url": "https://pcloud-mcp.shannonjlove.cloud/mcp",
      "transport": "streamable_http"
    },
    "backblaze": {
      "url": "https://b2-mcp.shannonjlove.cloud/mcp",
      "transport": "streamable_http"
    },
    "mediafire": {
      "url": "https://mediafire-mcp.shannonjlove.cloud/mcp",
      "transport": "streamable_http"
    },
    "mega": {
      "url": "https://mega-mcp.shannonjlove.cloud/mcp",
      "transport": "streamable_http"
    },
    "gdrive-local": {
      "url": "https://gdrive-mcp.shannonjlove.cloud/mcp",
      "transport": "streamable_http"
    }
  }
}
```

Useful Commands

```
# Status
systemctl --user status pcloud-mcp backblaze-mcp mediafire-mcp mega-mcp gdrive-mc

# Logs (live)
journalctl --user -u pcloud-mcp -f
journalctl --user -u backblaze-mcp -f

# Restart all
for svc in pcloud-mcp backblaze-mcp mediafire-mcp mega-mcp gdrive-mcp; do
  systemctl --user restart "$svc"
done
```

```
# Test MCP endpoint
curl -s https://pcloud-mcp.shannonjlove.cloud/mcp | jq .

# rclone - iDrive E2
rclone ls idrivee2:                                # list buckets
rclone ls idrivee2:BUCKET --max-depth 2           # list files
rclone copy /local/path idrivee2:BUCKET/ -P       # upload
rclone sync idrivee2:BUCKET/ /local/path -P       # sync down
rclone size idrivee2:BUCKET                       # storage used
rclone check /local/path idrivee2:BUCKET          # integrity check
```

Tools by Server

pcloud_mcp

```
pcloud_get_user_info • pcloud_list_folder • pcloud_get_file_info
pcloud_create_folder • pcloud_delete_file • pcloud_delete_folder
pcloud_rename_file • pcloud_move_file • pcloud_copy_file
pcloud_search_files • pcloud_get_public_link • pcloud_upload_file •
pcloud_download_file
```

backblaze_mcp

```
b2_get_account_info • b2_list_buckets • b2_list_files • b2_get_file_info
b2_create_bucket • b2_delete_bucket • b2_delete_file • b2_hide_file
b2_copy_file • b2_upload_file • b2_download_file
```

mediafire_mcp

```
mf_get_user_info • mf_list_folder • mf_get_file_info • mf_get_download_link
mf_create_folder • mf_delete_file • mf_delete_folder
mf_move_files • mf_copy_files • mf_rename_file
mf_search • mf_update_privacy • mf_upload_file
```

mega_mcp

```
mega_get_storage_info • mega_list_files • mega_find_file
mega_upload_file • mega_download_file • mega_create_folder
mega_delete_node • mega_export_link • mega_move_node • mega_rename_node
```

gdrive_mcp

```
gdrive_get_about • gdrive_list_folder • gdrive_search • gdrive_get_file_info  
gdrive_create_folder • gdrive_upload_file • gdrive_download_file  
gdrive_delete_file • gdrive_move_file • gdrive_copy_file  
gdrive_rename_file • gdrive_share_file
```

File Naming Convention

All new files created by upload tools follow your canonical convention: YYYY-MM-DD_HH-MM_category-subcategory_description_UUID24.ext

Apply via the `rename_to` / `dest_key` parameters on upload tools.