

List and Column Input ○○○○○○○○○○	Formatted Input ○○○○○○○○○○○○	More on moving the pointer ○○○○○○○○○○○○	INFILE ○○○○○○
-------------------------------------	---------------------------------	--	------------------

# Inputting Raw Data

Shannon Pileggi

STAT 330

STAT 330: Lecture 18 1 / 39

List and Column Input ○○○○○○○○○○	Formatted Input ○○○○○○○○○○○○	More on moving the pointer ○○○○○○○○○○○○	INFILE ○○○○○○
-------------------------------------	---------------------------------	--	------------------

# OUTLINE

List and Column Input

Formatted Input

More on moving the pointer

INFILE

STAT 330: Lecture 18 2 / 39

List and Column Input ●○○○○○○○○	Formatted Input ○○○○○○○○○○○○	More on moving the pointer ○○○○○○○○○○○○	INFILE ○○○○○○
------------------------------------	---------------------------------	--	------------------

# Overview

So far we have learned three methods for working with data in SAS:

1. use a LIBNAME statement to access a SAS library that contains SAS data
2. use DATALINES in a DATA step to enter data (this is an example of *list input* with instream data)
3. use PROC IMPORT for structured data files like CSV or EXCEL

Today - importing “raw”/less structured data (think .txt or .dat extension) with INFILE.

STAT 330: Lecture 18 3 / 39

List and Column Input ●○○○○○○○○	Formatted Input ○○○○○○○○○○○○	More on moving the pointer ○○○○○○○○○○○○	INFILE ○○○○○○
------------------------------------	---------------------------------	--	------------------

# The Pointer

- ▶ SAS has a virtual *pointer* which keeps track of the ‘reading’ location in the data file
- ▶ Pointer location depends upon method of data input
  1. List - pointer moves to next non-empty column to begin reading
  2. Column - pointer moves to the explicitly designated column location
  3. Formatted - pointer moves to column depending upon specified informat length

STAT 330: Lecture 18 4 / 39

List and Column Input  
○○●○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
○○○○○○

## INFILE statement

SAS Code

```

DATA mydata ;
  INFILE "C:/ComputerLocation/datasetname.ext" ;
  INPUT var1 var2 var3;
RUN;

```

SAS Code

- the INFILE statement specifies the computer location of the data file
  - be sure to include the data set name at the end of the path
  - be sure to include the data set extension at the end of the path
  - the path goes in quotes
- the INPUT statement names the variables

STAT 330: Lecture 18
5 / 39

List and Column Input  
○○●○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
○○○○○○

## About the cheese data

In a study of cheddar cheese from the LaTrobe Valley of Victoria, Australia, samples of cheese were analyzed for their chemical composition and were subjected to taste tests.

case	sample number	Data_cheese.dat				
taste	subjective averaged taste					
	test score	1	12.3	4.543	3.135	0.86
acetic	natural log of concentration	2	20.9	5.159	5.043	1.53
	of acetic acid	3	39	5.366	5.438	1.57
h2S	natural log of concentration	4	47.9	5.759	7.496	1.81
	of hydrogen sulfide	5	5.6	4.663	3.807	0.99
lactic	concentration of lactic acid	Data_cheese.dat				

STAT 330: Lecture 18
6 / 39

List and Column Input  
○○○○●○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
○○○○○○

## Importing the cheese data

SAS Code

```

DATA cheese;
  INFILE "&path.Data_cheese.dat";
  INPUT case taste acetic h2s lactic;
RUN;

```

SAS Code

Which method determined the pointer location?

- list
- column
- formatted
- none of these

STAT 330: Lecture 18
7 / 39

List and Column Input  
○○○○●○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
○○○○○○

## List input limitations

We can't use list input when we

- do not have a delimiter (ie, no space or comma or something) between values
- do not have periods for missing values
- have non-standard data (ie, dates)
- have data with embedded spaces
- have character variables with width > 8 characters

STAT 330: Lecture 18
8 / 39

## Column input

- ▶ limitations: data must be lined up in the same columns
- ▶ advantages: can work with embedded spaces, character variables > 8, missing data indicated by spaces

Data_cheese.dat					
1	12.3	4.543	3.135	0.86	
2	20.9	5.159	5.043	1.53	
3	39	5.366	5.438	1.57	
4	47.9	5.759	7.496	1.81	
5	5.6	4.663	3.807	0.99	

Can we use column input for the cheese data?

1. Yes
2. No

## Column input

Data_cheese.dat					
0	1	2	3		
123456789012345678901234567890123456					
-----					
1	12.3	4.543	3.135	0.86	
2	20.9	5.159	5.043	1.53	
3	39	5.366	5.438	1.57	
4	47.9	5.759	7.496	1.81	
5	5.6	4.663	3.807	0.99	

In which columns is the second variable (taste) located?

1. 2 through 9
2. 8 through 13
3. 9 through 12
4. 9 through 16
5. 6 though 16

## Column input example

```
SAS Code
DATA cheese2;
  INFILE "&path.Data_cheese.dat";
  INPUT case 1-2 taste 9-12 acetic 17-21 h2s 25-29 lactic 33-36;
RUN;
```

- ▶ after each variable name, specify the numeric range of column position

## Discussion

```
SAS Code
*Example 3 - change input order;
DATA cheese3;
  INFILE "&path.Data_cheese.dat";
  INPUT lactic 33-36 case 1-2 taste 9-12 acetic 17-21 h2s 25-29;
RUN;

*Example 4 - mix input methods;
DATA cheese4;
  INFILE "&path.Data_cheese.dat";
  INPUT case taste acetic 17-21 h2s 25-29 lactic 33-36;
RUN;
```

On your own: Will these examples work or will there be an error?



List and Column Input  
oooooooooooo

Formatted Input  
oooo●ooooo

More on moving the pointer  
oooooooooooo

INFILE  
oooooo

## Discussion

SAS Code

```

DATA test2;
INPUT name $11. money DOLLAR10.2 ;
DATALINES;
Constantine $15,000.35
Billy $8,000.05
Sue $3,000.63
Megan $400.45
;
RUN;

```

SAS Code

If my data look like this, will it still import correctly?

- Yes
- No

STAT 330: Lecture 18
17 / 39

List and Column Input  
oooooooooooo

Formatted Input  
oooo●ooooo

More on moving the pointer  
oooooooooooo

INFILE  
oooooo

## The colon modifier

- A colon modifies an informat
- examples: `:COMMA6.` `:MMDDYY10.` `:$10.`
- A colon allows you to use an informat for reading data in an otherwise list input process. Why?
  - If you assign an informat like `$10.`, SAS will read 10 columns every time, and may include unwanted characters
- Applying the colon modifier tells SAS to read a value *until* it encounters a space (so it doesn't use a set column position)

STAT 330: Lecture 18
18 / 39

List and Column Input  
oooooooooooo

Formatted Input  
oooo●ooooo

More on moving the pointer  
oooooooooooo

INFILE  
oooooo

## The ampersand modifier

- An ampersand modifies an informat
- examples: `&COMMA6.` `&MMDDYY10.` `&$10.`
- Continues to read a character value, even if it contains blanks
- Two or more blanks indicates the data value is complete

**On your own:** How can we correctly read in the test data from the previous slide?

STAT 330: Lecture 18
19 / 39

List and Column Input  
oooooooooooo

Formatted Input  
oooo●ooooo

More on moving the pointer  
oooooooooooo

INFILE  
oooooo

## Moving the pointer

Formatted data can cause issues with the pointer because it forces the pointer to look in specific columns. You can manually move the pointer by specifying pointer location before the variable name.

- `+n` – Move pointer ahead *n* columns
- `@n` – Move pointer directly to column *n*

STAT 330: Lecture 18
20 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○●○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
○○○○○○

## House data

price	selling price
size	square feet of home
age	age of home
numfeat	number of features
NEloc	NorthEast Location
CustLab	Customer Label
CorLoc	Corner Location
tax	Annual taxes

On your own: What features do you notice in the data?

Data.homeprice.dat

205,000	2650	sqft	13	7	1	1	0	1639
208,000	2600	sqft	.	4	1	1	0	1088
215,000	2664	sqft	6	5	1	1	0	1193
215,000	2921	sqft	3	6	1	1	0	1635
199,900	2580	sqft	4	4	1	1	0	1732
190,000	2580	sqft	4	4	1	0	0	1534
180,000	2774	sqft	2	4	1	0	0	1765
156,000	1920	sqft	1	5	1	1	0	1161
145,000	2150	sqft	.	4	1	0	0	.
144,900	1710	sqft	1	3	1	1	0	1010
137,500	1837	sqft	4	5	1	0	0	1191
127,000	1880	sqft	8	6	1	0	0	930

STAT 330: Lecture 18
21 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○●

More on moving the pointer  
○○○○○○○○○○

INFILE  
○○○○○○

## Discussion

SAS Code

```

DATA homes;
INFILE "&path.Data_homeprice.dat";
INPUT price COMMA7. size 12-15 @23 age
      numfeat NEloc CustLab CorLoc tax;
RUN;

```

SAS Code

Which method(s) did I use to import the data?

- list input
- column input
- formatted input
- list + column
- list + formatted
- column + formatted
- list + column + formatted

STAT 330: Lecture 18
22 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○●

More on moving the pointer  
○○○○○○○○○○

INFILE  
○○○○○○

## Wrap up

- Importing data correctly may take some trial and error and there can be multiple correct methods.
- TIP:** the pointer moves from left to right. Variable 10 will likely not appear correctly if Variable 1 does not appear correctly. Get variables to appear correctly, one at a time, according to their input order.
- TIP:** Always check PROC CONTENTS to make sure that variables have the correct type (numeric vs character).
- TIP:** If data file is open in a separate application, you may need to close it before you import it.
- Input features must go before/after variable names

Feature	Before	After
Column position (e.g., 3-4)	✗	✓
Informat (e.g., COMMA7.2)	✗	✓
+n/@n	✓	✗

STAT 330: Lecture 18
23 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○●

More on moving the pointer  
●○○○○○○○○○○

INFILE  
○○○○○○

List and Column Input

Formatted Input

More on moving the pointer

INFILE

STAT 330: Lecture 18
24 / 39

List and Column Input  
Formatted Input  
More on moving the pointer  
INFILE

## @"XXXX" column pointer

Data.Dogs.dat

```

Name- Kia Breed: Shepherd Vet Bills: 325.25
Name- Sam Breed: Beagle Vet Bills: 478.78
Name- Sydney Breed: Boxer Vet Bills: 733.54
Name- Bugsy Breed: Pug Vet Bills: 518.09

```

Data.Dogs.dat

- When data have a consistent prefix use the @"XXXX" column pointer
- XXXX represents the prefix

What are the exact prefixes for...

- Name of the dog
- Breed of the dog
- Amount spent at the vet

STAT 330: Lecture 18
25 / 39

List and Column Input  
Formatted Input  
More on moving the pointer  
INFILE

## Importing the dog data

SAS Code

```

DATA dogs;
INFILE "&path.Data_dogs.dat";
INPUT @"Name- " name $
      @"Breed: " breed $
      @"Bills: " spending COMMA6.2;
RUN;

```

SAS Code

STAT 330: Lecture 18
26 / 39

List and Column Input  
Formatted Input  
More on moving the pointer  
INFILE

## Address data

mailing.dat

```

Brenda Smith email: Bsmith@charter.net
123 Grand Ave.
Arroyo Grande CA 93420
David White email: david6060@gmail.com
456 Traffic Wy.
Arroyo Grande CA 93420
Alexandra Jones email: AJJ43@yahoo.com
789 Foothill Blvd.
San Luis Obispo CA 93405

```

mailing.dat

On your own: What features does this data have that we will need to address when importing?

STAT 330: Lecture 18
27 / 39

List and Column Input  
Formatted Input  
More on moving the pointer  
INFILE

## Line pointers

- Raw data sets typically consist of one observation per line
- Line pointers tells SAS to skip to a new line
  - / skip to next line
  - #n skip to line n
- This is used to read multiple lines of data into a single observation

STAT 330: Lecture 18
28 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○●○○○○

INFILE  
○○○○○○

## Reading the mail data

SAS Code

```

DATA mailing;
INFILE "&path.mailing.dat";
INPUT fname :$10. lname $ @"email: " email :$20.
      / street &$30.
      / city &$30. state $2. zip ;

/*this also works:
INPUT fname :$10. lname $ @"email: " email :$20.
      #2 street &$30.
      #3 city &$30. state $2. zip ;
*/
RUN;

```

SAS Code

STAT 330: Lecture 18
29 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○●○○○○

INFILE  
○○○○○○

## @ vs @@

Double trailing at @@

- ▶ SAS assumes that a single line of data corresponds to a single observation
- ▶ If a single line of a data corresponds to multiple observations, need to use @@
- ▶ Tells SAS to keep reading data into new observations until it runs out

Trailing at @

- ▶ Use when interested in specific records from raw data
- ▶ Tells SAS to wait for more information
- ▶ Syntax is typically
  - ▶ input statement with @
  - ▶ if-then statement to select obs
  - ▶ new input statement

STAT 330: Lecture 18
30 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○●○○○○

INFILE  
○○○○○○

## @@ example

baggagefees.dat

```

1 Delta 863,608 2 American 593,465
3 US Airways 506,339 4 Continental 353,416
5 United 276,817 6 AirTran 164,670
7 Alaska 157,013 8 Spirit 133,970
9 JetBlue 64,078 10 Hawaiian 56,590
11 Frontier 54,862 12 Allegiant 53,562
13 Virgin America 33,482 14 Southwest 32,035
15 Sun Country 13,398 16 Mesa 1,683
17 USA 3000 1,650

```

baggagefees.dat

SAS Code

```

DATA baggage ;
INFILE "&path.baggagefees.dat";
INPUT rank airline &$20. revenue :COMMA. @@;
RUN;

```

SAS Code

STAT 330: Lecture 18
31 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○●○○○○

INFILE  
○○○○○○

## @ example

potassium.dat

Mollusk, clams	534	85	3 oz.
Cod	439	85	3 oz.
Halibut	490	85	3 oz.
Salmon	319	85	3 oz.
Trout	375	85	3 oz.
Tuna	484	85	3 oz.
Apricots, dried	814	70	10 med.

potassium.dat

SAS Code

```

DATA potassium ;
INFILE "&path.potassium.dat" ;
INPUT @21 K COMMA5. @ ;
IF K < 500 THEN DELETE ;
INPUT food $ 1-20 @28 weight measure &$10.;
RUN;

```

SAS Code

Objective: retain observations with potassium (K) greater than 500

STAT 330: Lecture 18
32 / 39



List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○●

INFILE  
○○○○○○

## Discussion

Which symbol best represents the *opposite* operation performed by @@?

1. @
2. @"XXX"
3. @n, +n
4. /, #n
5. &
6. :

STAT 330: Lecture 18
33 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
●○○○○○

List and Column Input

Formatted Input

More on moving the pointer

INFILE

STAT 330: Lecture 18
34 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
●●○○○○

## INFILE options

- ▶ `FIRSTOBS=` tells SAS at which line to *start* reading  
useful to skip variable names
- ▶ `OBS=` tells SAS at which line to *stop* reading  
useful to read in part of data file
- ▶ `FLOWOVER` default value; SAS jumps to next line if current line does not have enough values to read. After a jump, SAS reads the next line regardless of whether it has enough values.
- ▶ `MISSOEVER` Set a variable to missing value if missing or if length is too short
- ▶ `TRUNCOVER` Allows SAS to handle data values of varying lengths appropriately with column or formatted input

STAT 330: Lecture 18
35 / 39

List and Column Input  
○○○○○○○○○○

Formatted Input  
○○○○○○○○○○

More on moving the pointer  
○○○○○○○○○○

INFILE  
●●●○○○

## Try it

names.txt

```

FirstName LastName
Allison Allen
Billy Bryson
Carmen Cottle
David Decker
Enrique Edwards
Faith Firth

```

What values should I use below to read in the A through D names?

1. 1, 5
2. 2, 5
3. 1, 4
4. 2, 4
5. 4, 2

SAS Code

```

DATA names ;
  INFILE "&path.names.txt" FIRSTOBS=  OBS= ;
  INPUT fname $ lname $;
RUN;

```

SAS Code

STAT 330: Lecture 18
36 / 39

List and Column Input  
Formatted Input  
More on moving the pointer  
INFILE

## Try it

SAS Code

```

%MACRO checkoptions(option);
DATA test;
  INFILE "&path.numbers.txt" &option;
  INPUT numbers 6.;
RUN;
TITLE "&option";
PROC PRINT; RUN;
%MEND;

%checkoptions(flowover);
%checkoptions(missover);
%checkoptions(truncover);

```

SAS Code

numbers.txt

```

666666
1
22
333
4444
55555

```

numbers.txt

On your own: Try changing the **6.** numeric format to

- (nothing)
- :6.

What differences do you observe?

STAT 330: Lecture 18
37 / 39

List and Column Input  
Formatted Input  
More on moving the pointer  
INFILE

## Delimited files

- ▶ A delimited file contains a specific character that separates data values
- ▶ with list input, SAS assumes the delimiter is a space
- ▶ **DLM=** option in the infile statement specifies the delimiter
  - ▶ **DLM=' , '** for commas
  - ▶ **DLM='09'x** for tabs
- ▶ by default, SAS assumes that  $\geq 2$  delimiters in a row is a single delimiter; to override this, the **DSD** option:
  - ▶ treats two delimiters in a row as a missing value
  - ▶ ignores delimiters enclosed in quotes
  - ▶ does not read quotes as part of the data value

STAT 330: Lecture 18
38 / 39

List and Column Input  
Formatted Input  
More on moving the pointer  
INFILE

## Example

beer.csv

```

Consumption per capita [1],,,
Country,Consumption (liters),20092010 (change 633-ml bottles),Total
Vietnam,19,,
Venezuela,83,-4.7,2259
Uzbekistan,11,,
United States,78,-2.5,24138
United Kingdom,74,-3.4,4587

```

beer.csv

SAS Code

```

DATA beer;
  INFILE "&path.beer.csv" DSD FIRSTOBS=3 DLM=",";
  INPUT country :$30. consumption change total;
RUN;

```

SAS Code

STAT 330: Lecture 18
39 / 39