ParkPing Zone Predictor

Drivers in George Town waste time circling for parking. I want to give someone planning a trip a rough idea of how busy a zone will be, for a day and hour they choose. This notebook builds and tests the model behind that. The data is the Kaggle Smart Parking Management dataset, not live George Town data.

https://www.kaggle.com/datasets/datasetengineer/smart-parking-management-dataset

1. Import libraries & read the CSV

The file has 1,000 rows and 28 columns. Each row is one reading of one parking spot at one moment: when it was, which zone, and whether it was occupied.

In [1]:
```
import pandas as pd
import matplotlib.pyplot as plt

df = pd.read_csv("./data/IIoT_Smart_Parking_Management.csv")
print(df.shape)
df.head()
```

```
(1000, 28)
```

Out[1]:

	Timestamp	Parking_Spot_ID	Sensor_Reading_Proximity	Sensor_Reading_Pressure
0	2021-01-01 00:00:00.000000000	20	1.023651	1.541461
1	2021-01-02 06:39:16.756756756	49	3.903349	1.621719
2	2021-01-03 13:18:33.513513513	38	10.315709	6.292374
3	2021-01-04 19:57:50.270270270	31	6.588039	1.659870
4	2021-01-06 02:37:07.027027027	8	8.213969	3.278467

5 rows × 28 columns

2. Keep only what we need

I kept four columns. Timestamp gives me the hour and day. Parking_Lot_Section is the zone. Occupancy_Status is what I want to predict. Parking_Spot_ID identifies the bay. I dropped the other 24 because a driver planning a trip wouldn't know them. The sensor readings are the

clearest case: a sensor only shows a car when one is already there, so using it would give the model the answer.

In [2]:
```
df = df[["Timestamp", "Parking_Spot_ID", "Parking_Lot_Section", "Occupancy_Status"]
df.head()
```

Out[2]:

	Timestamp	Parking_Spot_ID	Parking_Lot_Section	Occupancy_Status
0	2021-01-01 00:00:00.000000000	20	Zone A	Occupied
1	2021-01-02 06:39:16.756756756	49	Zone A	Occupied
2	2021-01-03 13:18:33.513513513	38	Zone B	Vacant
3	2021-01-04 19:57:50.270270270	31	Zone B	Vacant
4	2021-01-06 02:37:07.027027027	8	Zone C	Occupied

3. Check if the data is healthy, along with the min & max

No empty cells and no duplicate rows, so there was nothing to remove. Spot IDs run from 1 to 50. Zone A has the most records (382) and Zone D the fewest (114). 550 rows are Occupied and 450 are Vacant, so always guessing “occupied” would be right a bit more than half the time.

In [3]:
```
print("empty cells:", df.isnull().sum().sum())
print("copied rows:", df.duplicated().sum())
print("smallest spot ID:", df["Parking_Spot_ID"].min())
print("biggest spot ID:", df["Parking_Spot_ID"].max())
```

```
empty cells: 0
copied rows: 0
smallest spot ID: 1
biggest spot ID: 50
```

In [4]:
```
print(df["Parking_Lot_Section"].value_counts())
print(df.groupby("Parking_Lot_Section")["Parking_Spot_ID"].nunique()) #Count differ
print(df["Occupancy_Status"].value_counts())
```

```
Parking_Lot_Section
Zone A    382
Zone B    307
Zone C    197
Zone D    114
Name: count, dtype: int64
Parking_Lot_Section
Zone A    50
Zone B    50
Zone C    49
Zone D    44
Name: Parking_Spot_ID, dtype: int64
Occupancy_Status
Occupied    550
Vacant      450
Name: count, dtype: int64
```

4. Make the three clues and the answer

I turned the timestamp into Hour and Day, because those are what a driver can choose. I changed Occupied and Vacant into 1 and 0, because a model works with numbers.

In [5]:
```
df["Timestamp"] = pd.to_datetime(df["Timestamp"])
df["Hour"] = df["Timestamp"].dt.hour
df["Day"] = df["Timestamp"].dt.day_name()
df["Occupied"] = df["Occupancy_Status"].map({"Occupied": 1, "Vacant": 0}) #represen
df.head()
```

Out[5]:


	Timestamp	Parking_Spot_ID	Parking_Lot_Section	Occupancy_Status	Hour	
0	2021-01-01 00:00:00.000000000	20	Zone A	Occupied	0	
1	2021-01-02 06:39:16.756756756	49	Zone A	Occupied	6	Sa
2	2021-01-03 13:18:33.513513513	38	Zone B	Vacant	13	S
3	2021-01-04 19:57:50.270270270	31	Zone B	Vacant	19	M
4	2021-01-06 02:37:07.027027027	8	Zone C	Occupied	2	Wedr


5. Look at the patterns

I expected busy and quiet hours, but the bars are all close to the middle, and the zones look alike too. The app's "Usually 38% full at 14:00" comes from this same sum: 16 of the 42 records at hour 14 were occupied. Because the pattern is weak, I don't expect the model to score highly.

In [6]:
```
(df.groupby("Hour")["Occupied"].mean() * 100).plot(kind="bar", title="Percent occup
plt.ylim(0, 100)
plt.show()

(df.groupby("Parking_Lot_Section")["Occupied"].mean() * 100).plot(kind="bar", title
plt.ylim(0, 100)
plt.show()
```





6. Split: old records to learn from, new records to test on

I sorted by date, then used the oldest 800 rows to train and the newest 200 to test. The app is for planning future visits, so I tested the same way: learn from the past, check on what came later.

In [7]:
```
df = df.sort_values("Timestamp") #data sorted from oldest to newest, making predict

features = ["Hour", "Day", "Parking_Lot_Section"] #questions
target = "Occupied" #answers

X = df[features]
y = df[target]

cut = int(len(df) * 0.8) #of 1000 rows takes 80% converts to integer saved to cut (
X_train, y_train = X.iloc[:cut], y.iloc[:cut] #train 80
X_test, y_test = X.iloc[cut:], y.iloc[cut:] #test 20

print("learn rows:", len(X_train), " test rows:", len(X_test))
```

```
learn rows: 800  test rows: 200
```

7. The lazy guess (baseline

This is my bar to beat. Always guessing “occupied” gets 52.5% right on the test rows. If my model can’t beat that, it hasn’t learned anything.

In [8]:
```
from sklearn.dummy import DummyClassifier

lazy = DummyClassifier(strategy="most_frequent")
lazy.fit(X_train, y_train)
print("lazy guess score:", round(lazy.score(X_test, y_test), 3))
```

```
lazy guess score: 0.525
```

8. The real model: a decision tree

I chose a decision tree because I can print its questions and read them. I limited it to 3 questions deep so it learns general patterns and doesn’t memorise the training rows. It scored 56.5%, four points above the baseline.

In [9]:
```
from sklearn.pipeline import Pipeline
from sklearn.compose import ColumnTransformer
from sklearn.preprocessing import OneHotEncoder
from sklearn.tree import DecisionTreeClassifier, export_text

translator = ColumnTransformer(
    [("words", OneHotEncoder(handle_unknown="ignore"), ["Day", "Parking_Lot_Section
    remainder="passthrough",
)
tree = DecisionTreeClassifier(max_depth=3, random_state=42) # Max depth of 3 decisi
model = Pipeline([("translate", translator), ("tree", tree)]) #Translate data then

model.fit(X_train, y_train) #training the model, learn patterns and fitting to corr
print("tree score:", round(model.score(X_test, y_test), 3)) #print the score after
```

```
tree score: 0.565
```

In [10]:
```
names = model.named_steps["translate"].get_feature_names_out()
print(export_text(model.named_steps["tree"], feature_names=list(names)))
```

```
|--- remainder__Hour <= 5.50
|   |--- words__Parking_Lot_Section_Zone C <= 0.50
|   |   |--- words__Day_Saturday <= 0.50
|   |   |   |--- class: 1
|   |   |--- words__Day_Saturday >  0.50
|   |   |   |--- class: 1
|   |--- words__Parking_Lot_Section_Zone C >  0.50
|   |   |--- words__Day_Monday <= 0.50
|   |   |   |--- class: 1
|   |   |--- words__Day_Monday >  0.50
|   |   |   |--- class: 0
|--- remainder__Hour >  5.50
|   |--- words__Day_Friday <= 0.50
|   |   |--- remainder__Hour <= 16.50
|   |   |   |--- class: 1
|   |   |--- remainder__Hour >  16.50
|   |   |   |--- class: 0
|   |--- words__Day_Friday >  0.50
|   |   |--- words__Parking_Lot_Section_Zone C <= 0.50
|   |   |   |--- class: 1
|   |   |--- words__Parking_Lot_Section_Zone C >  0.50
|   |   |   |--- class: 0
```

9. Mark the test properly (Detailed Breakdown of the results)

The model says “occupied” too often. Of the 95 truly vacant records it got 34 right and called 61 occupied. Of the 105 truly occupied records it got 79 right. So it’s weak, mainly at spotting vacant spots. The limits: only 1,000 rows, very little pattern in the data, and it isn’t real George Town data.

In [11]:
```
from sklearn.metrics import classification_report, ConfusionMatrixDisplay


pred = model.predict(X_test) #predict for each row of 200
print(classification_report(y_test, pred, target_names=["Vacant", "Occupied"])) #ca

ConfusionMatrixDisplay.from_predictions(y_test, pred, display_labels=["Vacant", "Oc
plt.show()
```

```
              precision    recall  f1-score   support

      Vacant       0.57      0.36      0.44        95
    Occupied       0.56      0.75      0.64       105

    accuracy                           0.56       200
   macro avg       0.57      0.56      0.54       200
weighted avg       0.57      0.56      0.55       200
```



10. Save the calculator, open it again, ask one question

I saved the trained model to a file and loaded it back to check it works. Monday at 14:00 in Zone A gives 57%. The app gives the same answer for the same choices.

In [12]:
```
import joblib

joblib.dump(model, "model/parkping_model.joblib")
loaded = joblib.load("model/parkping_model.joblib")

question = pd.DataFrame([{"Hour": 14, "Day": "Monday", "Parking_Lot_Section": "Zone
chance = loaded.predict_proba(question)[0][1]
print("Monday 14:00, Zone A:", round(chance * 100), "% chance occupied")
```

```
Monday 14:00, Zone A: 57 % chance occupied
```

11. Save the tidy table

In [13]:
```
df[["Timestamp", "Parking_Spot_ID", "Parking_Lot_Section", "Hour", "Day", "Occupied
    "data/final_parking_cleaned.csv", index=False
)
print("saved")
```

```
saved
```