

Deploying a New Tenant

Seminar Desk · one D1 database and one Worker per tenant, same codebase

Pick a short slug per tenant (example below: **acme**). Run all commands from the repo root.

1. Create the tenant's database

Note the **database_id** it prints. Never reuse another tenant's D1_DATABASE_ID.

```
npx wrangler d1 create seminar-desk-acme
```

2. Apply all four migrations, in order

A new database needs 0000 to 0003, not only the latest.

```
for f in drizzle/0000_parched_purple_man.sql \
  drizzle/0001_wandering_whiplash.sql \
  drizzle/0002_flimsy_flyer_fields.sql \
  drizzle/0003_rename_study_add_email.sql; do
  npx wrangler d1 execute seminar-desk-acme --remote --file=$f
done
```

3. Build and deploy under a different Worker name

```
D1_DATABASE_ID=<acme-db-id> npm run deploy -- --name seminar-desk-acme
```

The generated config (dist/server/wrangler.json) names the Worker **seminar-desk**. Deploying with that name again would overwrite your first tenant's Worker, so always pass --name. Confirm the output says it deployed seminar-desk-acme.

4. Set the tenant's secrets

Run after the first deploy (the Worker must exist). Use unique values per tenant.

```
npx wrangler secret put ADMIN_PASSWORD --name seminar-desk-acme
npx wrangler secret put SESSION_SECRET --name seminar-desk-acme # openssl rand -hex 32
npx wrangler secret put FEATURE_REGISTRATIONS_TABLE_VIEW --name seminar-desk-acme # true / false
```

Add the WhatsApp secrets as well if this tenant uses WhatsApp.

5. Add a domain (optional)

Use the default *.workers.dev URL, or attach a custom domain/route in the Cloudflare dashboard. The README notes the hosting access policy defaults to owner-private; change the audience if outside visitors must reach the registration forms.

6. Verify

Sign in at /signin, create a webinar, submit a test registration, and confirm the Registrations tab shows the table view.

7. Record the tenant and back it up

Keep a list of slug, Worker name, DB name and DB id. Back up each tenant separately:

```
npx wrangler d1 export seminar-desk-acme --remote --output acme.sql
```

Shipping new code or migrations later

Redeploy every tenant with its own D1_DATABASE_ID and --name, and run any new migration file against each tenant's database. Feature flags are per deployment: FEATURE_<KEY> env vars, read via process.env.