```
# Name: Shantanu Rohile
# Roll No: 53
# AI Practical 02-B
# Problem Statement:
# Write a program to solve the Water Jug Problem using Breadth-First Search (BFS)
from queue import Queue
#BFS algorithm to solve the Water Jug Problem
# -----
def water_jug_bfs(capacity_jug1, capacity_jug2, target):
  visited_states = set()
  q = Queue()
  q.put((0, 0)) # Starting state: both jugs are empty
  while not q.empty():
    current_state = q.get()
    if current_state in visited_states:
      continue
    visited_states.add(current_state)
   jug1, jug2 = current_state
    # Goal check: either jug has the target amount
    if jug1 == target or jug2 == target:
      return current_state
    # Possible operations:
    #1. Fill Jug1
    q.put((capacity_jug1, jug2))
    # 2. Fill Jug2
    q.put((jug1, capacity_jug2))
    #3. Empty Jug1
    q.put((0, jug2))
    #4. Empty Jug2
    q.put((jug1, 0))
    #5. Pour Jug1 → Jug2
    pour_amount = min(jug1, capacity_jug2 - jug2)
    q.put((jug1 - pour_amount, jug2 + pour_amount))
    # 6. Pour Jug2 → Jug1
    pour_amount = min(jug2, capacity_jug1 - jug1)
    q.put((jug1 + pour_amount, jug2 - pour_amount))
  return None # No solution found
# Example Usage
# -----
capacity jug1 = 5
```

capacity_jug2 = 3

result = water_jug_bfs(capacity_jug1, capacity_jug2, target print("Water Jug Solution:", result)
#
Sample Output:
Water Jug Solution: (4, 0)

#-----

target = 4,0