

Assessment API Documentation

Base URL

<https://assess.hipster-dev.com/api/>

Authentication

All requests must include an API key in headers:

x-api-key: YOUR_API_KEY

Endpoint

POST /meetings

Purpose

We are using a single API endpoint to handle both meeting creation and attendee (agent/client) token generation.

First, the agent creates a meeting using the API, which returns the Meeting ID along with the agent's join token.

After that, the same API is used to generate join tokens for other participant (such as clients) by passing the Meeting ID.

Additionally, agent token can also be generated again for the same meeting when needed by calling the same API with the Meeting ID.

The API differentiates requests based on the "type" field (agent or client).

This API is used for:

1. **Agent (Create Meeting) → Create a meeting**
2. **Client / Agent (Get Attendee) → Create an attendee for an existing meeting**

Flow

STEP 1: Agent creates a meeting

The agent initiates the process by creating a meeting.

Upon creation, the agent also receives their attendee (join) token.

Endpoint:

POST /meetings

Headers:

Content-Type: application/json

x-api-key: YOUR_API_KEY

Accept: application/json

Request:

```
{  
  "type": "agent"  
}
```

Success Response:

```
{
  "status": "success",
  "message": "Meeting created successfully",
  "data": {
    "meeting": {
      "MeetingId": "283ef2b1-0214-4506-a547-656fefaf2954",
      "ExternalMeetingId": "3131",
      "MediaRegion": "ap-southeast-1",
      "MediaPlacement": {
        "AudioHostUrl":
"c98cdd79639fadfb70890016890e1a22.k.m1.as1.app.chime.aws:3478",
        "AudioFallbackUrl":
"wss://wss.k.m1.as1.app.chime.aws:443/calls/283ef2b1-0214-4506-a547-656fefaf2954",
        "SignalingUrl":
"wss://signal.m1.as1.app.chime.aws/control/283ef2b1-0214-4506-a547-656fefaf2954",
        "TurnControlUrl":
"https://2954.cell.ap-southeast-1.meetings.chime.aws/v2/turn_sessions",
        "ScreenDataUrl":
"wss://bitpw.m1.as1.app.chime.aws:443/v2/screen/283ef2b1-0214-4506-a547-656fefaf2954",
        "ScreenViewingUrl":
"wss://bitpw.m1.as1.app.chime.aws:443/ws/connect?passcode=null&viewer_uuid=null&X-BitHub-Call-Id=283ef2b1-0214-4506-a547-656fefaf2954",
```

```
    "ScreenSharingUrl":  
    "wss://bitpw.m1.as1.app.chime.aws:443/v2/screen/283ef2b1-0214-4506-a5  
47-656fefaf2954",  
    "EventIngestionUrl":  
    "https://data.svc.as1.ingest.chime.aws/v1/client-events"  
  },  
  "MeetingFeatures": {  
    "Audio": {  
      "EchoReduction": "UNAVAILABLE"  
    }  
  },  
  "TenantIds": [],  
  "MeetingArn":  
  "arn:aws:chime:ap-southeast-1:490864477453:meeting/283ef2b1-0214-450  
6-a547-656fefaf2954"  
},  
"attendee": {  
  "ExternalUserId": "agent",  
  "AttendeeId": "89513158-5b23-596e-6b3e-ec916725c7",  
  "JoinToken":  
  "ODk1MTMxNTgtNWlyMy01OTZlTzIm2UtzWNlZjknNjcyNWM3OmM1NmViNm  
lxLTl4YTItNDYyOS05NDYxLTQzNzhiOTIxNTA3YW",  
  "Capabilities": {  
    "Audio": "SendReceive",  
    "Video": "SendReceive",  
    "Content": "SendReceive"  
  }  
}  
}  
}
```

Error Response

Meeting Creation Failed

```
{  
  "status": "error",  
  "message": "Meeting creation failed"  
}
```

IMPORTANT

From this response, you will get:

MeetingId = 283ef2b1-0214-4506-a547-656fefaf2954

Important: The MeetingId must be exactly the same as returned in the agent response.

This MeetingId is required to add other users (clients) to the same meeting

STEP 2: Get Client token

Now a client can be added to this meeting using the MeetingId

The client must use the MeetingId received from Step 1 to create a client (user) attendee.

Note: Each API call creates a new JoinToken for that user.

Endpoint:

POST /meetings

Headers:

Content-Type: application/json

x-api-key: YOUR_API_KEY

Accept: application/json

Request:

```
{
  "type": "client",
  "meeting_id": "283ef2b1-0214-4506-a547-656fefaf2954"
}
```

Success Response:

```
{
  "status": "success",
  "message": "Client token retrieved successfully",
  "data": {
    "meeting": {
      "MeetingId": "283ef2b1-0214-4506-a547-656fefaf2954"
    },
    "attendee": {
      "ExternalUserId": "client",
      "AttendeeId": "40840e80-9bf0-07c0-b4f7-cbb38ec36cc5",
      "JoinToken":
"NDA4NDBIODA†OWJmMC0wN2MwLWI0ZjctY2JiMzhIYzM2Y2M1OjEwYzliNz
A5LTA0NGY†NGVjMC1hM2JILTU5OTI1ZmE4NDBjNA",

```

```
"Capabilities": {  
  "Audio": "SendReceive",  
  "Video": "SendReceive",  
  "Content": "SendReceive"  
}  
}  
}
```

Error Response

Missing Meeting ID (Client)

```
{  
  "status": "error",  
  "message": "meeting_id is required for client"  
}
```

Attendee Creation Failed

```
{  
  "status": "error",  
  "message": "Attendee creation failed"  
}
```

Server Error

```
{  
  "status": "error",  
  "message": "Something went wrong"  
}
```

STEP 3: Get Agent token

This API is used to create an attendee token for an agent in an existing meeting.

The Meeting ID from Step 1 must be provided to associate the agent with the correct meeting.

Each API call generates a unique join token for the agent.

Endpoint:

POST /meetings

Headers:

Content-Type: application/json

x-api-key: YOUR_API_KEY

Accept: application/json

Request:

```
{  
  "type": "agent",  
  "meeting_id": "283ef2b1-0214-4506-a547-656fefaf2954"  
}
```

Success Response:

```
{  
  "status": "success",  
  "message": "Agent token retrieved successfully",  
  "data": {  
    "meeting": {
```



```
"MeetingId": "283ef2b1-0214-4506-a547-656fefaf2954"
},
"attendee": {
  "ExternalUserId": "agent",
  "AttendeeId": "db60bfb1-fd30-d074-46f0-502d03cc593b",
  "JoinToken":
"ZGI2MGJmYjEtZmQzMCIkMDc0LTQ2ZjAtNTAyZDAzY2M1OTNiOjFhZjcyMzZk
LWI0MWU0NGRkMy1hMzc3LWM4ZjUyYTM3NDk4Yg",
  "Capabilities": {
    "Audio": "SendReceive",
    "Video": "SendReceive",
    "Content": "SendReceive"
  }
}
}
```

Error Response

Attendee Creation Failed

```
{
  "status": "error",
  "message": "Attendee creation failed"
}
```

Server Error

```
{
  "status": "error",
  "message": "Something went wrong"
}
```

