



THE PRODUCT

A convex design to match the curves of the body is the characteristic feature of the ERGO-CASE range of cases.

As "bodycases" they for the first time make it possible for the user to wear the unit comfortably – whether on their arm, chest or waist.

The innovative design not only makes it easier to operate but also easier to read off.

YOUR ADVANTAGE

Ergonomically shaped case designed for carrying on the body.

Flat surface for individual interfaces on the front side.

Belt strap and eyelet for belt strap available as accessories, easy to fit. Max. size of the belt strap: height 1.378", thickness 0.118".

Available for operation either with or without batteries. Add-on battery compartments (M, L) or integrated supports (S).



Can also be used as hand-held, desktop or wall-mounted case.


Available either with flat or with high top part for individual installation configuration.

Rational case mounting.

Recessed operating area in order to protect the membrane keyboard.



Off-white, RAL 9002 
Black, RAL 9005 



APPLICATIONS

Mobile data recording and transmission in the fields of medical, laboratory and measuring technology, storage and sales logistics, digital open and closed-loop control technology.

PROTECTION CLASS IP 54

With sealing/sealing kit (accessory).

MAX. SIZE OF PCB

ERGO-CASE	L x W in inches	
	flat top part	high top part
S	2.559 x 2.205	2.402 x 2.205
M	5.039 x 2.835	5.039 x 2.677
L	4.921 x 6.378	4.685 x 6.299

(cutouts for pillars not taken into consideration)

ENCLOSURES

ERGO-CASE	Outside dim. in inches			Combination	Equipment (dim. in inches)			Material	Part-No.		
	L	W	H		batt. comp.	lid of batt. comp.	max. dim. keypad		off-white	black	
S*1	3.150	3.780	1.260	flat	2 x AAA	—	1.724 x 2.291	ABS (UL 94 HB)	B 70 00 107	B 70 00 109	
	3.150	3.780	1.732	high	2 x AAA	—	1.724 x 2.293	ABS (UL 94 HB)	B 70 05 107	B 70 05 109	
M	5.906	3.937	1.575	flat	• (see acc. ①)	clip-lock	4.012 x 2.295	ABS (UL 94 HB)	B 70 10 107	B 70 10 109	
	5.906	3.937	2.165	high	• (see acc. ①)	clip-lock	4.008 x 2.291	ABS (UL 94 HB)	B 70 15 107	B 70 15 109	
	5.906	3.937	1.575	flat	—	—	4.012 x 2.295	ABS (UL 94 HB)	B 70 10 207	B 70 10 209	
	5.906	3.937	2.165	high	—	—	4.008 x 2.291	ABS (UL 94 HB)	B 70 15 207	B 70 15 209	
L	5.906	7.874	2.126	flat	• (see acc. ①)	clip-lock	3.705 x 5.882	ABS (UL 94 HB)	B 70 20 107	B 70 20 109	
	5.906	7.874	2.717	high	• (see acc. ①)	clip-lock	3.701 x 5.870	ABS (UL 94 HB)	B 70 25 107	B 70 25 109	
	5.906	7.874	2.126	flat	—	—	3.705 x 5.882	ABS (UL 94 HB)	B 70 20 207	B 70 20 209	
	5.906	7.874	2.717	high	—	—	3.701 x 5.870	ABS (UL 94 HB)	B 70 25 207	B 70 25 209	
Color combination enclosure/display panel							off-white	off-white/translucent	black	black/translucent	
L*2 with display panel	5.906	7.874	2.126	flat	• (see acc. ①)	clip-lock	3.299 x 5.555	B 70 20 137	B 70 20 147	B 70 20 139	B 70 20 149
	5.906	7.874	2.717	high	• (see acc. ①)	clip-lock	3.299 x 5.555	B 70 25 137	B 70 25 147	B 70 25 139	B 70 25 149
	5.906	7.874	2.126	flat	—	—	3.299 x 5.555	B 70 20 237	B 70 20 247	B 70 20 239	B 70 20 249
	5.906	7.874	2.717	high	—	—	3.299 x 5.555	B 70 25 237	B 70 25 247	B 70 25 239	B 70 25 249

ACCESSORIES

Article	For enclosure ERGO-CASE	Version / Application	Part-No.	
① Battery compartment	M, L	ABS, off-white, for 4 x 1.5 V mignon cells (AA)	A 91 74 004	
	M, L	ABS, off-white, for 1 x 9 V flat battery	A 91 74 003	
	M, L	ABS, off-white, for 2 x 9 V flat batteries	A 91 74 002	
② Set of battery clips	S	for 2 x 1.5 V micro cells (AAA), incl. battery contact for serial connection	B 71 00 002	
	M, L	tin-plated, for 4 x 1.5 V mignon cells (AA)	A 91 61 001	
	M, L	tin-plated, for 1 x 9 V flat battery	A 91 74 006	
	M, L	tin-plated, for 2 x 9 V flat batteries	A 91 61 002	
③ Plug-in contact	M, L	for 1 x 9 V flat battery	A 91 60 003	
④ Sealing	S	for sealing up to IP 54	B 71 00 005	
	M	for case version without battery compartment and lid, sealing up to IP 54	B 71 10 005	
	L	for case version without battery compartment and lid, sealing up to IP 54	B 71 20 005	
④ Sealing kit	M	for case version with battery compartment and lid, sealing up to IP 54	B 71 10 001	
	L	for case version with battery compartment and lid, sealing up to IP 54	B 71 20 001	
⑤ Strap eyelet	S, M, L	for strap attachment and secure storage of the cases with wall-susp. element, kit with 2 pcs (4 mounting holes ø 0.177 inch necessary)	B 71 10 028	
⑥ Belt strap	S, M, L	elastic belt with clamp lock, approx. 17.717 x 1.378 inch, black	B 71 10 129	
	S, M, L	elastic belt with push-in buckle, approx. 47.244 x 1.181 inch, black	B 71 10 139	
⑦ Wall suspension element*3	S, M	PA 6x, volcano, for storing the cases, with removal securing clip	B 71 10 048	
	L	PA 6x, volcano, for storing the cases, with removal securing clip	B 71 20 048	
⑧ Contacts*4	S, M, L	contact male for the wall suspension element, 6-pole	A 91 78 007	
	S, M, L	contact female for the case, 6-pole (additional holes necessary)	A 91 78 008	
			off-white	black
⑨ Belt / pocket clip	S, M	PA 6x, 2 mounting holes ø 0.165 inch necessary, 1 pc	B 71 10 107	B 71 10 109



*1 with ERGO-CASE S, case assembly with threaded screws; advantageous when changing batteries

*2 Material: ABS (UL 94 HB), translucent display panel PC (UL 94 V-0); protection class IP 54 not possible

*3 the strap eyelet attachment (⑤, separate article) is required for storing the case

*4 see assembly instruction on our website www.okw.com