

[Home](#)[Customer Service](#)[Tutorials](#)[Forum](#)[Distributors](#)[About Us](#)[Contact](#)**Search**[Go](#)

- ☐ Products
- ☐ News
- ☒ Tutorials

Products[New Products](#)[Top Sellers](#)[Featured Products](#)[Breakout Boards](#)[Cables](#)[Cellular](#)[Classes](#)[Components](#)[Development Tools](#)[Dings and Dents](#)[Gift Certificates](#)[GPS](#)[Kits](#)[LCDs](#)[Port-O-Rotary](#)[Programmable](#)[Prototyping](#)[Robotics](#)[Sensors](#)[SFE Widgets](#)[Swag](#)[Tools](#)[Tracking](#)[Wireless](#)[Full catalog](#)

(PDF 5.1 MB)

[Home](#) | [Tutorials](#) | [Beginning Embedded Electronics](#) | **Beginning Embedded Electronics - 11****Beginning Embedded Electronics - 11**by [Nate](#) | June 19, 2008 | [2 comments](#)

Skill level: ★ Beginner

Common Mistakes, Tips and Tricks

1. All grounds need to be connected together.
2. TX/RX loop back trick: When in doubt of a serial conversion circuit, short the TX and RX pins together to get an echo.
3. Normal length wires for breadboard connections: Don't use a 9" wire where a 2" wire will do.
4. Minimize short potential in your breadboard wiring: Don't expose an inch of wire from the insulation if all you need is 1/4".
5. You will learn best when you have a *simple* project to work on. Don't create the 'house-pet robot' just yet.
6. Google is, of course, your friend. When you don't know, go do some research.
7. for(x = 0 ; x < 400 ; x++) : If x is defined as an 8-bit integer, the for loop will loop forever!
8. Soldering basics: Wet your @\$%% sponge.
9. Take your time with ground plane solder joints. Do not be fooled by a cold joint.
10. Never trick yourself into thinking you're that good. Print out a 1:1 and compare the footprints!
11. Check that TX and RX are wired correctly to all peripherals. TX/RX swap is the one of the greatest causes of PCB failures.
12. When laying out a PCB with SMD micros, don't forget to include the programming port!
13. Don't run silkscreen across pads.
14. Connector PCB footprint mis-numbering: always check the pin number on your connector - they can have very obfuscated schemes.
15. In Eagle, use vector fonts only!
16. Review your gerber files before submitting them.

[Lecture 1 - Background and Power Supply](#)[Lecture 2 - How to Get Code Onto a Microcontroller](#)[Lecture 3 - What is an oscillator?](#)[Lecture 4 - UART and Serial Communication](#)[Lecture 5 - AVR GCC Compiling](#)[Lecture 6 - Soldering Basics](#)[Lecture 7 - SMD Soldering](#)[Lecture 8 - Eagle: Schematics](#)[Lecture 9 - Eagle: PCB Layout](#)[Lecture 10 - Eagle: Creating a new part](#)[Common Mistakes, Tips and Tricks](#)[Back to Tutorials](#)**Comments**[2 comments](#)[Log in to post comments.](#)[by Tracekill](#) ★ +1 | June 25, 2009 at 0:47 AM ★ 0

Your cart is empty

[log in](#)**Feeds**

- [News](#)
- [Products](#)
- [Product Changes](#)
- [Comments](#)

Resources[Official SparkFun IRC Channel](#)[Custom PCBs](#)[Open Circuits](#)**Currency**

Display prices in

- [US Dollar](#)
- [Canada Dollar](#)
- [Australian Dollar](#)
- [British Pound](#)
- [Euro](#)

Feedback




What's on your mind?

Please include your email address if you'd like us to respond to a specific question.

[submit](#)If you would like to tell us more, you can fill out our form if you need some psycho-suggestive questions. [Go to the form.](#)

Hey guys. These are a great selection of tips, I found a few of them useful even at my early stage. As a computer science student however, I have to know: Why does the for-loop in 7 increment indefinitely? I'm not very intimate with the characteristics of an 8-bit integer. With the data sets we work with, I find myself more commonly using 16- and 32-bit integers. Is it simply because of the limited range of the 8-bit integer? If so would not `for(x = 0; x < 256; x++)` also loop indefinitely? Great advice and great tutorials. I've spent nearly \$100 at this site already, and it was worth every penny.

© SparkFun Electronics | Boulder, Colorado | Customer Service

 by **Keegan**  +1.1 | July 4, 2009 at 3:44 AM  0

If an 8-bit integer is 255, and you increment it, it will rollover and become 0. 8-bit integers can only hold a value from 0 to 255. The condition part of the loop would have to be "`x < 255`" or lower.