Mobile Light Tower without Genset

MOBILE TOWER WITHOUT GENSET

High-Performance 80,000 Lumens Grid-Powered 12.0M Mobile Tower

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
39 ft (12.0 MTR)	4 x 200W LED = 800W Bajaj ...	Continuous Grid / External...	Up to 3800 sq. m

LIGHTING SYSTEM & OPTICS	TECHNICAL SPECIFICATION DETAILS
Lights Configuration	4 x 200W LED Flood Lights (Total 800W) Make- Bajaj
Beam Angle	30 Degree & 60 Degree Mix
Brightness	80,000 Lumens (100 lm/w)
Ingress Protection	IP-66
Correlated Color Temp (CCT)	5000 - 6500K
Upper Connection Box	Provided
Electrical Standards	Certified CE Electrical Fittings
Illumination Coverage	Up to 3,800 sq. meters

TOWER & MAST ASSEMBLY	TECHNICAL SPECIFICATION DETAILS
Tower Height	12.0 m (Ground Level to Light)
Material & Thickness	Mild Steel, 4 mm Thick
Extension / Closing / Tilt	Manual Winch
Extension / Closing Time	Max. 2 Minutes Each
Wire Rope Metal	Stainless Steel
Wire Rope Size	10 mm
Safety Switches	02 Nos.

CONTROLS & SAFETY SYSTEMS	TECHNICAL SPECIFICATION DETAILS
Control System	Integrated Control System
Earth Leakage	Earth Leakage Protection
Circuit Protection	Each Light Has a Separate Miniature Circuit Breaker (MCB)

CHASSIS, WHEELS & MOBILITY	TECHNICAL SPECIFICATION DETAILS
Balancing Riggers	4 Nos. (Collapsible)
Tyres	2 x 8/9"
Suspension	Leaf Spring (2 Nos.)
Loading Hooks	4 Nos.
Approx Dimensions	Length: 1635 mm | Width: 1354 mm
Total Weight	Approx. 400 / 450 kg

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- Technical Specification – Mobile Light Tower without genset 12 mtr with 4 LED
- 4 x 200W LED Flood Lights (Total 800W) Make- Bajaj (80,000 Lumens / 100 lm/w)
- Beam Angle: 30 Degree & 60 Degree Mix for surrounding and perimeter coverage
- Area illumination coverage up to 3,800 square meters

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- 12.0-meter heavy-duty Mild Steel mast (4 mm wall thickness) with manual winch
- Extension / Closing / Tilt time: Max. 2 minutes each with 10mm stainless steel wire rope
- Controls & Safety: Control system, Earth Leakage protection, 2 Safety switches, MCB per light
- Chassis: 4 collapsible balancing jacks, 2 tyres (8/9"), 2 leaf springs, 4 loading hooks

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.