ACE 5 SLT 6000

SOLAR OPERATED

5.0 KVA Inverter Solar Mobile Light Tower - 7.0M Mast

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
23 ft (7.0 MTR Tiltable)	4 x 150W LED (87,000 Lumens)	10.2+ Hours Battery Backup...	5000 sq. m

ELECTRICAL & SOLAR SYSTEM	TECHNICAL SPECIFICATION DETAILS
Inverter & Power Conditioning	5.0 kVA Pure Sine Wave, 230V AC Output (Overload & Short Circuit Protection)
Solar Power Generation	Solar Panels: 595W x 4 Modules (Total Array: 2380W), Sliding Rail System
Solar Panel Efficiency	>= 18%
Charge Controller	MPPT 48V, Charge Efficiency >= 95% (Reverse Polarity, Overcharge, Over-Temp Protection)
Battery Bank	LiFePO4 (LFP) 48V, 150Ah x 1 (Total Storage: 7200Wh / 7.2 kWh)
Solar Charging & Metrics	Solar Input: 2380W x 5h = 11900Wh/day | Backup Time: 10.2 Hours Actual Backup

LIGHTING SYSTEM & PHOTOMETRICS	TECHNICAL SPECIFICATION DETAILS
LED Flood Lights	04 Units x 150W Each (Total 600W), Linear Sport Flood Light
Luminous Efficacy	145 lm/W
Total Brightness	87,000 Lumens (150W x 145 lm/w x 4)
Ingress Protection	IP66
Light Performance	Illumination Coverage: Up to 5000 sq.m | Spread: Around + Long Range
Tilt Adjustment	90° Manual Tilt

TOWER & WINCH SYSTEM	TECHNICAL SPECIFICATION DETAILS
Mast Height	7.0 m (Ground Level to Light)
Construction	Plated or Hot Dip Galvanized
Rotation	359° Manual
Wire Rope	Stainless Steel, 06 mm (Spiral Cable)
Winch Operation	Manual Mechanism Winch (Raising & Lowering Time: <= 5 min max)

CONTROL & SAFETY SYSTEMS	TECHNICAL SPECIFICATION DETAILS
Control Panel	Weatherproof Compartment
Individual Light Control	Individual Light ON/OFF: 04 Nos.
AC Ports	AC Inlet Available | AC Charging Input Available
Safety Protections	Overload, Short Circuit, Deep Discharge, Surge Protection

MECHANICAL STRUCTURE & MOBILITY	TECHNICAL SPECIFICATION DETAILS
Trailer & Chassis	Heavy-Duty Steel Construction, Anti-Rust Coating, Canopy Provided
Mobility Components	Tyre: 13" (2 Nos.) | Suspension: Leaf Spring x 2 | Towing Hitch: Adjustable
Hooks & Jacks	Crane Hooks: 4 Nos. | Leveling Jacks: 4 Nos.
Dimensions	Length: 2.8m - 3.2m | Width: 2.0m - 2.2m | Height: 2.3m - 2.6m
Gross Weight	950 - 980 kg
Optional Upgrades	Camera Compatible, USB/C-Port, Camouflage Paint

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.