ACE B -02

BATTERY OPERATED

Dual-Light Portable Lithium Battery Tower - 102CM Mast

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
3.3 ft (102 cm Telescopic)	2 x 50W LED (10,000 Lumens)	6 - 7 Hours (75AH Lithium)	1200 sq. m

BATTERY & POWER SYSTEM	TECHNICAL SPECIFICATION DETAILS
Battery Capacity	75AH X 1 (Lithium)
Battery Voltage	12 V
Battery Charger	Yes (Included)
Battery Charging Time	5 Hours
Back Up Time	Approx. 6-7 Hrs (According to Brightness on Medium Mode)

LIGHTING SYSTEM & OPTICS	TECHNICAL SPECIFICATION DETAILS
Light Source	LED Type Cool White
Light Power	50 W X 2 nos. (High Power LED - 100W Total)
Brightness	10,000 Lumens
Dimmer Settings	Low - Medium - High - SOS

TOWER & ELEVATION ASSEMBLY	TECHNICAL SPECIFICATION DETAILS
Tower Type	Telescopic MS Rod
Tower Height	Expendable 102 cm +/- 10 cm
Time for Tower Extension	60 Seconds
Time for Tower Closing	2 Minutes
Method of Step Up & Down	Manual

PHYSICAL CONSTRUCTION & BUILD	TECHNICAL SPECIFICATION DETAILS
Material Type	ABS Black
Body Material	Heavy-Duty Industrial Plastic
Weight	20 Kg Approx.
Warranty	12 Month

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.