ACE 1.2 IT 4500

INFLATABLE TOWER

360° Glare-Free 42,000 Lumens Inflatable Balloon Light Tower

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
15 ft (4.5 MTR)	42,000 Lumens (360° Glare-...	10-12 Hours (8 Ltr Tank)	10,000 sq. m

POWER & BLOWER SYSTEM	TECHNICAL SPECIFICATION DETAILS
Electrical Base	230V 1200VA Single Phase (+/- 5V)
Inflation Mechanism	High-Pressure Electric Inflation Blower Fan
Inflation Time	Under 60 Seconds to Full 4.5m Deployment
Fuel Tank Capacity	8 Liters (10 - 12 Continuous Runtime Hours)
Lube Oil Capacity	400 ml

LIGHTING SYSTEM & OPTICS	TECHNICAL SPECIFICATION DETAILS
Brightness	42,000 Lumens
Optical Envelope	Translucent Ripstop Balloon Fabric
Light Dispersion	360° Circular Glare-Free & Shadow-Free Diffusion
Illumination Area	Up to 10,000 sq. meters

PHYSICAL DIMENSIONS & WEIGHT	TECHNICAL SPECIFICATION DETAILS
Deployed Height	4.5 Meters (15 ft)
Gross Weight	50 kg
Packaged Dimensions	0.6 x 0.5 x 0.8 m
Wind Stability	Up to 60 km/h with Heavy Anchor Pegs & Guy Lines

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- Massive 10,000 square meter area illumination with 360-degree diffusion
- 42,000 lumens total brightness eliminating dark shadows and driver blinding
- 230 Volt 1200VA single-phase electrical power base
- 8-liter fuel tank capacity delivering all-night runtime with 400ml lube oil capacity
- Rapid inflation to 4.5 meters in less than 60 seconds via internal blower fan
- Compact 50 kg total weight, easily loaded into the boot of an SUV or utility truck

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.