ACE B -04

BATTERY OPERATED

Tactical 4-Light Lithium Portable Light Tower - 2.0M Mast

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
6.5 ft (2.0 MTR Telescopic)	4 x 50W LED (28,000 Lumens)	6 - 8 Hours (100AH Lithium)	2500 sq. m

BATTERY & POWER SYSTEM	TECHNICAL SPECIFICATION DETAILS
Battery Capacity	100AH X 1 (Lithium)
Battery Voltage	12 V
Battery Charger	Yes (Included)
Battery Charging Time	4-5 Hours
Back Up Time	Approx. 6-8 Hrs (According to Brightness on Medium Mode)

LIGHTING SYSTEM & OPTICS	TECHNICAL SPECIFICATION DETAILS
Light Source	LED Type Cool White
Light Power	50 W X 4 nos. (High Power LED - 200W Total)
Brightness	20,000 - 28,000 Lumens
Dimmer Settings	HIGH - LOW - MEDIUM

TOWER & ELEVATION ASSEMBLY	TECHNICAL SPECIFICATION DETAILS
Tower Type	Telescopic MS Rod
Tower Height	2 Meter +/- 10 cm
Time for Tower Extension	2 Min
Time for Tower Closing	2 Min
Method of Step Up & Down	Manual

PHYSICAL CONSTRUCTION & BUILD	TECHNICAL SPECIFICATION DETAILS
Material Type	ABS Black
Body Material	Heavy-Duty Industrial Plastic
Waterproof Rating	Yes (Weatherproof Sealed Case)
Weight	25 Kg Approx.
Warranty	12 Month

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- Battery Capacity: 100AH X 1 (Lithium), 12V with included 4-5 hours battery charger
- Brightness: 20,000 - 28,000 lumens from 4 x 50W High Power Cool White LEDs
- Extended 6-8 hours continuous backup time on medium mode with 3-mode dimmer (HIGH-LOW-MEDIUM)
- Telescopic MS Rod tower extending to 2 Meter (+/- 10 cm) in 2 minutes
- Manual step up and step down method with 2-minute closing time
- Ultra-portable 25 kg approx weight with waterproof tactical ABS black plastic casing
- 12-month manufacturer warranty

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.