# ACE LT 12000

DIESEL POWERED

*High-Voltage 240,000 Lumens Heavy Diesel Mobile Lighting Tower*

| MAST HEIGHT | LIGHT / LUMENS | POWER / RUNTIME | COVERAGE AREA |
|---|---|---|---|
| 39 ft (12.0 MTR) | 4 x 300W-500W LED (2,40,00... | 80+ Hours (100L Kubota Die... | 8000 sq. m |

| POWER & ENGINE SYSTEM | TECHNICAL SPECIFICATION DETAILS |
|---|---|
| **Engine Make & Model** | Escort Kubota 14.5 HP Water-Cooled Diesel |
| **Rated Speed** | 1500 RPM |
| **Alternator / Output** | 220V Connection Board Output with Auxiliary Power Sockets |
| **Fuel Tank Capacity** | 100 Liters (Diesel) |
| **Operating Runtime** | 80+ Continuous Operating Hours |
| **Starting System** | 12V Heavy-Duty Electric Starter |

| LIGHTING SYSTEM & OPTICS | TECHNICAL SPECIFICATION DETAILS |
|---|---|
| **Floodlight Configuration** | 4 x 300W - 500W High-Voltage LED Luminaires |
| **Total Luminous Flux** | 2,40,000 Lumens (40,000 to 60,000 lm per light) |
| **Illumination Area** | Up to 8,000 sq. meters |
| **Luminaire Protection** | IP67 / IP68 Cast Aluminum Heavy Housing |
| **Beam Orientation** | Independent 3-Axis Multi-Directional Manual Aiming |

| MAST & TOWER ASSEMBLY | TECHNICAL SPECIFICATION DETAILS |
|---|---|
| **Maximum Height** | 12.0 Meters (39 ft) Ground Level to Light |
| **Mast Material** | Heavy-Duty Galvanized Steel |
| **Elevation Mechanism** | Self-Locking Worm Winch with Stainless Steel Cable |
| **Rotation** | 355° Rotation with Positive Locking Pin |
| **Wind Stability** | Certified Stable up to 100 km/h with Outriggers |

| CHASSIS, TRAILER & MOBILITY | TECHNICAL SPECIFICATION DETAILS |
|---|---|
| **Trailer Chassis** | Heavy-Duty Single Axle with Leaf Spring Suspension |
| **Tyres** | 14" All-Terrain Pneumatic Wheels (Highway Towable up to 80 km/h) |
| **Stabilizers** | 4 Independent Wind-Down Outrigger Jacks with Footpads |
| **Lifting Points** | Integrated Central Crane Lifting Eye & Forklift Pockets |
| **Gross Weight** | 600 - 700 kg |
| **Dimensions** | Travel: 2.3 x 1.4 x 2.4 m \| Operation: 2.6 x 2.4 x 12.0 m |

| CONTROLS & SAFETY SYSTEMS | TECHNICAL SPECIFICATION DETAILS |
|---|---|
| **Control Panel** | Weatherproof Canopy Compartment with MCBs |
| **Engine Protection** | Low Oil Pressure & High Coolant Temperature Automatic Shutdown |
| **Electrical Safety** | Earth Leakage Protection & Individual MCB per Luminaire |


© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.

## KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- Combined luminous output of 240,000 lumens (40,000 - 60,000 lumens per light)
- High-voltage LED flood lights with power range 300W to 500W
- Illumination coverage up to 8,000 square meters
- Japanese Escort Kubota 14.5 H.P 1500 R.P.M water-cooled diesel engine
- 12.0-meter heavy-duty vertical telescopic mast (ground level to lights)
- Single-axle trailer chassis with 4 heavy-duty outrigger leveling jacks


© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.